Singularity

Singularity AIDR

PRODUCT CATALOG

The entire AI agent security lifecycle, in one platform.


Detection, response and data privacy for AI agents and AI chat tools

1 DISCOVER	2 ASSESS	3 PROTECT	4 CONTROL	5 INSPECT	6 APPROVE	7 PROVE
inventory	risk and CVEs	masking, DLP	allow · ask · deny	tool output	approval, response	evidence, improvement

singularityrd.com anil@singularityrd.com

The entire AI agent security lifecycle, in one platform

Singularity AIDR follows AI agents and AI chat tools from discovery to proof: it finds what exists, measures the risk, protects data, controls actions, inspects output, manages human approval and response, and proves the outcome. Simulation and coverage results feed back into policy, and a governance layer spans every stage.



1 Discover
Fleet inventory · MCP discovery · Continuous inventory · Shadow AI

2 Assess
CVE scan · Scan-to-policy · Skill scan · Posture dashboard

3 Protect data
Browser Guard masking · Prompt protection · DLP · Exact data match

4 Control actions
allow/ask/deny · MCP Gateway · Lethal trifecta · Permission profiles

5 Inspect output
Output scanning · Quarantine · Poisoning protection

6 Approve and respond
Operator approval · Dashboard approvals · Alerts · Response

7 Prove and improve
Audit log · SIEM · Simulation feeds back into policy

G Govern and comply
Asset register · Intake · Four-eyes change · Framework mapping

Product lines

AIDR for coding agents
6 connectors, 386 rules, MCP Gateway, SDK

AIDR Browser Guard
8 AI chat sites, 23 data types, reversible masking

AIDR Privacy engine
Turkish/English detection; the same rules in the browser, in agents and on the CLI

AI Security Posture
146 components, 2,000+ CVE rules, 14 MCP risk categories

Coverage: every stage, every surface

The table shows which feature covers each stage on each surface. Empty cells are out of scope.

STAGE	CODING AGENTS	MCP TOOLS	AI CHAT SITES	AI INFRASTRUCTURE	GOVERNANCE
1 **Discover**	✓ fleet inventory	✓ MCP discovery	✓ shadow AI	✓ continuous inventory	✓ asset register
2 **Assess**	✓ skill scanning	✓ 14 risk categories	✓ Monitor-mode baseline	✓ CVE scan	✓ posture dashboard
3 **Protect data**	✓ prompt protection, DLP	✓ DLP on arguments	✓ reversible masking	—	✓ managed policy
4 **Control actions**	✓ allow · ask · deny	✓ MCP policy, Gateway	✓ site blocking	✓ scan-to-policy	✓ four-eyes policy
5 **Inspect output**	✓ output scan, poisoning	✓ result inspection	—	—	—
6 **Approve and respond**	✓ operator approval	✓ toolset approval	✓ Confirm mode	—	✓ dashboard approval, alerts
7 **Prove and improve**	✓ audit log, simulation	✓ findings record	✓ counts dashboard	✓ CVE findings	✓ KVKK/GDPR report

Why Singularity AIDR?

Local-first processing

Detection and decisions happen on the device; agents and Browser Guard are protected with no account or network.

Reversible masking

The AI keeps its context; the original value comes back only on the user's screen.

Turkish-specific detection

T.C. Kimlik and IBAN by checksum; Turkish phones, addresses, labels and classification marks.

One engine for agents and chat

The same TR/EN rules run in the browser, in agent DLP and on the command line.

Auditable decisions

Rules are readable data, and a person, not the agent, gives approval.

Your choice of deployment

Cloud, on-premises or air-gapped; local protection continues even if a licence lapses.

1 Discover

The loop starts with knowing what exists: agents, MCP servers, AI services and the AI tools your people use.

01 **Fleet inventory** — which agent runs, on which version, and when it was last seen, in one list.

02 **MCP server discovery** — finds the MCP servers in agent configurations and maps them to 14 risk categories.

03 **Continuous infrastructure inventory** — internal AI services are polled on a schedule; silent targets are flagged.

04 **Shadow AI discovery and control** — see which AI tools employees use (counts only), then allow or block them.

MCP RISK CATEGORIES (14)

Token Mismanagement & Secret Exposure · Privilege Escalation via Scope Creep · Tool Poisoning · Software Supply Chain Attacks · Command Injection & Execution · Prompt Injection via Contextual Payloads · Insufficient Auth & Authorization · Lack of Audit and Telemetry · Shadow MCP Servers · Context Injection & Over-Sharing · Name Confusion Attack · Rug Pull Attack · Tool Shadowing Attack · CORS Misconfiguration

WHAT YOU GET You see what your agents connect to and which AI tools your people use.

2 Assess

The risk of what was found is measured: known vulnerabilities, risky MCP configurations and dangerous plugins.

05 **AI infrastructure CVE scan** — recognises 146 components and matches versions to 2,000+ CVE rules.

06 **Scan-to-policy** — agent calls to a service with a version-confirmed critical flaw are stopped.

07 **Skill and plugin scanning** — hidden instructions, remote code and persistence found with T01–T09.

08 **Posture dashboard** — CVE, MCP and plugin findings by severity, with a 30-day trend.

SKILL AND PLUGIN RISK TYPES

T01 Instruction hijacking · **T02** Memory poisoning · **T03** Remote payload execution · **T04** Embedded malicious code · **T05** Privilege escalation · **T06** Persistence · **T07** Tool hijacking · **T08** Insecure dependencies · **T09** Insecure coding

EXAMPLES OF RECOGNISED COMPONENTS

Ollama · vLLM · ComfyUI · Dify · Langflow · Gradio · Jupyter · Open WebUI · LiteLLM · Flowise · MLflow · Ray

WHAT REACHES THE CONSOLE?

Only CVE IDs, severities, component and version, rule IDs and digests. Target addresses, file paths, matched text and credentials stay on the device. An unreachable target is never reported as clean.

WHAT YOU GET You know about vulnerable services and risky plugins before your agents use them.

3 Protect data

While AI is in use, sensitive data is masked or stopped before it reaches a model.

WHAT THE USER TYPES	Draft a refund letter to Mrs. Ayşe Yılmaz. TCKN 10000000146, IBAN TR33 0006 1005 1978 6457 8413 26, email ayse.yilmaz@example.com, key AKIAIOSFODNN7EXAMPLE
WHAT THE SITE RECEIVES	Draft a refund letter to Mrs. `[PERSON_1]`. TCKN `[TCKN_1]`, IBAN `[IBAN_1]`, email `[EMAIL_1]`, key `[SECRET_1]`
ON THE USER'S SCREEN	Dear Ayşe Yılmaz, your refund goes to TR33 0006 1005 1978 6457 8413 26; we will write to ayse.yilmaz@example.com. Rotate `[SECRET_1]`.

Masking and restore were produced with Browser Guard's default settings on this example; the answer is illustrative. The key is never shown again.

AIDR BROWSER GUARD · CHATGPT · GEMINI · CLAUDE · COPILOT · PERPLEXITY · DEEPSEEK · MISTRAL · GROK · CHROME, EDGE, FIREFOX

09	**Reversible masking** — a sensitive value becomes a placeholder such as `[EMAIL_1]` before sending.
10	**Restore on the user's screen only** — the answer shows the original value; the site never sees it.
11	**TR/EN personal-data detection** — T.C. Kimlik, IBAN and cards by checksum; phones, addresses, names by context.
12	**Secret detection** — cloud, Git and AI provider keys, JWTs and private keys; never shown again.
13	**Four protection modes** — Auto-mask, Confirm, Block, Monitor; from measuring to full protection.
14	**Paste protection** — clipboard text is masked before it enters the prompt box.
15	**File protection** — clean copies of CSV, JSON, .env and code are uploaded; formula injection is defused.
16	**Office and PDF masking** — DOCX, XLSX, PPTX and PDF uploads are scanned and masked first.
17	**Company terms** — project code names, internal hostnames and similar words are masked.
18	**Exact data match** — your own customer records are recognised by fingerprint only.
19	**Prompt-injection coaching** — risky text is explained to the user, in Turkish or English, before sending.
20	**Optional local NER** — names and addresses in running text are found without leaving the device.
21	**Managed policy** — deploy with GPO, Intune, Jamf or Firefox; weakening settings are locked.
22	**Site blocking and pause** — unapproved sites do not load; pauses are timed and still counted.
23	**Internal AI sites** — your own internal AI portals get the same masking.
24	**Counts-only telemetry** — the console receives counts per type and site, never content.

CODING AGENTS AND THE COMMAND LINE

25	**Prompt protection** — on every connector, prompts are checked for secrets and personal data first.
26	**DLP policies** — 18 TR/EN detectors, keywords, regular expressions; signed policy.
27	**DLP input redaction** — on Claude Code and OpenCode the value is masked and the tool still runs.
28	`aidr privacy scan` — check a file locally before sharing it; values are never printed.
29	**Screenshot redaction** — local OCR paints over personal data in images (optional).
30	**Enterprise privacy gateway** — a server component that inspects AI traffic at your network exit.

WHAT YOU GET Personal data and keys stay inside, and people keep getting value from AI.

4 Control actions


When an agent acts, every tool call is evaluated before it runs.

31	**Six connectors** — Claude Code, Cursor, VS Code, OpenClaw, OpenCode, Codex CLI; one engine.
32	**Tool-call inspection** — shell, file, web and MCP calls are evaluated before they run.
33	**allow / ask / deny** — every decision shows its rule and reason; the strictest wins.
34	**386 detection rules** — readable YAML for Linux, macOS and Windows; add your own.
35	**Sensitivity presets** — paranoid, balanced, relaxed; the right threshold per team.
36	**Encoded and chained commands** — commands hidden in base64 or built from variables are resolved.
37	**Package supply chain** — non-existent or brand-new npm/PyPI packages (slopsquatting) are stopped.
38	**Reputation and AMSI** — URL, file and package reputation; Windows antimalware scanning.
39	**MCP policy** — allow, approve or deny per server and tool; a rule for unknown servers.
40	**MCP Gateway** — tool calls and arguments are checked before they run; signed tool manifests.
41	**Central policy** — written in YAML, dry-run, published, with version history.
42	**Local policy and allowlists** — write roots, domains, private IPs; exact-match exceptions.
43	**SDK** — protect your own agent applications with the same decision contract.
44	**Fail-closed connectors** — an internal error denies the call instead of passing it.
45	**Self-defence** — attempts by an agent to disable or bypass AIDR are caught.
46	**Offline operation** — protection continues from signed cached state without a network.
47	**Lethal trifecta and attack chains** — the step that would complete the chain is stopped.
48	**Canary credentials** — catch a compromised agent the moment it touches a decoy key.
49	**Agent permission profiles** — allowed tools, MCP, paths, domains, commands per agent or repo; templates.

HIGHLIGHT

Lethal trifecta and attack-chain detection

If one session lets an agent touch private data, read untrusted content and reach an external channel, everything needed to exfiltrate data is in place. AIDR tracks these three conditions across the session and stops the step that would complete the chain; exfiltration and injection-to-action chains are caught as well.



WHAT YOU GET Destructive commands, credential reads and exfiltration attempts stop before they run.

5 Inspect output

What the agent reads back is inspected before it can steer the next step.

50	**Tool-output scanning** — finds leaked keys, prompt-injection payloads and system-prompt leaks.
51	**Quarantine notice** — a risky result is replaced before the model sees it; outbound messages too.
52	**MCP output inspection** — the MCP Gateway scans each result in full before the model gets it.
53	**Data and context poisoning protection** — instruction files, content read, tool definitions and memory are guarded.

HIGHLIGHT · OWASP LLM04 AND AGENTIC ASI06

Data and context poisoning protection

- **Instruction and memory files** (CLAUDE.md, AGENTS.md, .cursorrules, MCP and agent settings) are guarded at runtime: writes need approval; invisible Unicode and hidden instructions are blocked.
- **Content the agent reads** (files, fetched pages, tool output) is checked for poisoning and quarantined.
- **MCP tool poisoning and rug pulls:** tool descriptions are scanned for hidden instructions; the approved tool list is pinned and any later change is blocked until an operator re-approves.
- **Memory and vector-store writes** are scanned before they are stored; **supply-chain poisoning** (typosquatting, slopsquatting) is stopped.

WHAT YOU GET Instructions and leaked keys in tool results cannot steer the model.

6 Approve and respond

When something is suspicious a person decides, and incidents get a recorded, controlled response.

54	**Out-of-band operator approval** — a one-time approval from the terminal; the agent cannot approve itself.
55	**Dashboard approvals** — a second person approves in the console: signed, single-use, short-lived.
56	**Slack, Teams, webhook and email alerts** — blocks, approval requests and incidents reach your team's channel.
57	**Incidents and evidence chain** — blocked decisions in one view, in order, per device.
58	**Response playbook** — the agent is paused, then network-isolated; every step is recorded.
59	**Staged policy rollout** — canary agents first, then the fleet; roll back to a previous version.
60	**File quarantine and snapshots** — risky files set aside; protected paths restorable (optional).
61	**Operator tools** — `aidr pending`, `allowlist`, `audit`, `doctor`.

WHAT YOU GET A hijacked agent cannot lift its own block, and the team sees the incident in its own channel.

7 Prove and improve

Every decision becomes evidence, and simulation results strengthen the policy to close the loop.

62	**Audit log and export** — rule and summary of every decision; no values (JSONL, CSV).
63	**Signed record chain** — Ed25519-signed records for tamper-evident proof.
64	**SIEM delivery** — events to Splunk, Microsoft Sentinel, Elastic and webhooks.
65	**Browser Privacy dashboard** — counts of masked, warned and blocked sends; no content.
66	**Attack simulation and scorecard** — `aidr simulate` tests built-in attacks against your policy, executing nothing.

WHAT YOU GET You can show auditors what happened and improve policy by measuring it.

G Govern and comply

The governance layer spans every stage: which AI is used, who owns it and under which rules.

67	**AI asset register** — agents, MCP, sites and models with owner, purpose, data and risk tier.
68	**AI-BOM** — agents, MCP, models, plugins and known flaws as CycloneDX 1.6.
69	**AI intake and approval workflow** — approved or banned status flows straight into enforcement.
70	**Four-eyes policy change** — second approval, version history and rollback.
71	**Time-boxed exceptions** — an exception expires on its own.
72	**Security framework mapping** — rules mapped to OWASP LLM, OWASP Agentic and MITRE ATLAS.
73	**Governance frameworks** — mapping to NIST AI RMF, ISO/IEC 42001 and the EU AI Act.
74	**KVKK and GDPR evidence report** — protection coverage and counts-only evidence in a signable report.
75	**Governance scorecard** — a scheduled report for executives.
76	**Acceptable-use acknowledgement** — in Browser Guard; supports EU AI Act Article 4 literacy.
77	**Teams and roles** — owner, admin, member, viewer; email invitations.
78	**Team audit log** — every administrative action, with who did it.
79	**Retention, legal hold, deletion** — per data class; receipted deletion.

FRAMEWORKS MAPPED

OWASP LLM Top 10 (2025) · OWASP Agentic Top 10 (2026) · MITRE ATLAS · NIST AI RMF · ISO/IEC 42001 · EU AI Act · KVKK · GDPR

Designed to support KVKK and GDPR obligations. Reports and mappings support accountability work; they are not a compliance attestation on their own.

WHAT YOU GET AI use is owned, approved and mapped to the frameworks you report against.

Platform and deployment

Every stage runs on one platform: in the cloud, on-premises or air-gapped.

80 **Tenant isolation** — row-level security in the database.

81 **Identity** — Entra ID, SAML, SCIM, MFA, session revocation.

82 **Device enrollment** — short-code approval; one-time tokens for CI.

83 **Download center** — every package verified by SHA-256.

84 `aidr` **command line** — setup, status, configuration, key rotation.

85 **Endpoint rollout** — local installer; Windows, macOS, Linux scripts.

86 **Local mode** — protection from install, no account or network.

87 **Signed integrity** — signed packages, rules and intel.

88 **Docker Compose** — one on-prem host; three resource profiles.

89 **Kubernetes Helm** — refuses to install with a weak configuration.

90 **Air-gapped install** — signed offline licence and packs.

91 **TLS** — ACME renewal or your own certificate.

92 **Upgrades and backups** — interruption-safe upgrades, encrypted backups.

93 **Monitoring and alerting** — readiness checks, Prometheus rules.

94 **Operator administration** — licences and usage, behind MFA.

95 **Update notices** — tells you when a new version is out.

Editions

	FREE	TEAM	BUSINESS	ENTERPRISE
Who it is for	One developer, evaluation	Small teams, at least 3 developers	Organisations, at least 25 developers	On-premises and isolated networks
Deployment	Cloud	Cloud	Cloud, on-premises	On-premises, air-gapped
Event retention	7 days	90 days	365 days	Contractual
Local detection engine, agent connectors	✓	✓	✓	✓
Management console, policy, incidents	✓	✓	✓	✓
AIDR Browser Guard	—	✓	✓	✓
Microsoft Entra ID single sign-on	—	✓	✓	✓
SIEM export	—	—	✓	✓
SCIM provisioning	—	—	✓	✓
AI Security Posture	—	—	✓	✓
Air-gapped deployment	—	—	—	✓
Dedicated support	—	—	—	✓

Local detection runs on every endpoint with or without a plan. You can try the cloud service with one agent for 14 days.
Contact us for pricing and a quote: anil@singularityrd.com

From discovery to proof — every step your agents take is visible, controlled and proven.

NEXT STEPS

Demo

We walk through agent control, Browser Guard masking and the console on your own scenarios.

Pilot

A controlled trial that starts with a few teams in Monitor mode, with scope and success criteria agreed together.

Technical evaluation

Security questionnaire answers, data-flow and architecture documents and the detailed feature guide are shared on request.

Singularity

Singularity AIDR

CONTACT

singularityrd.com

anil@singularityrd.com

Contact us for pricing and a quote.