

intuitmailchimp

Get personalized content recommendations to help make your emails more engaging.

ads via Carbon

# Xpath cheatsheet

Xpath test bed

Test queries in the Xpath test bed:

Xpath test bed

(whitebeam.org)

Browser console

\$x("//div")

Works in Firefox and Chrome.

## # Selectors

Descendant selectors

h1	//h1	?
div p	//div//p	?
ul > li	//ul/li	?
ul > li > a	//ul/li/a	
div > *	//div/*	
:root	/	?
:root > body	/body	

Attribute selectors

#id	//*[@id="id"]	?
.class	//*[@class="class"] ...kinda	
input[type="submit"]	//input[@type="submit"]	
a#abc[for="xyz"]	//a[@id="abc"][@for="xyz"]	?
a[rel]	//a[@rel]	
a[href^='/']	//a[starts-with(@href, '/')]	?
a[href\$='.pdf']	//a[ends-with(@href, '.pdf')]	
a[href*=':']	//a[contains(@href, ':')]	
a[rel='help']	//a[contains(@rel, 'help')] ...kinda	

Order selectors

ul > li:first-of-type	//ul/li[1]	?
ul > li:nth-of-type(2)	//ul/li[2]	
ul > li:last-of-type	//ul/li[last()]	
li#id:first-of-type	//li[1][@id="id"]	?
a:first-child	//*[1][name()='a']	
a:last-child	//*[last()][name()='a']	

Other things

h1:not([id])	//h1[not(@id)]	?
Text match	//button[text()='Submit']	?
Text match (substring)	//button[contains(text(), "Go")]	
Arithmetic	//product[@price > 2.50]	
Has children	//ul[*]	
Has children (specific)	//ul[li]	
Or logic	//a[@name or @href]	?
Union (joins results)	//a   //div	?

Siblings

h1 ~ ul	//h1/following-sibling::ul	?
h1 + ul	//h1/following-sibling::ul[1]	
h1 ~ #id	//h1/following-sibling::[@id="id"]	

jQuery

\$('#ul > li').parent()	//ul/li/..	?
\$('#li').closest('section')Yli/ancestor-or-self::section		
\$('#a').attr('href')	//a[@href]	?
\$('#span').text()	//span/text()	

Class check

//div[contains(concat(' ',normalize-space(@class),' '), ' foobar ')]

Xpath doesn't have the "check if part of space-separated list" operator, so this is the workaround (source).

## # Expressions

Steps and axes

//	ul	/	a[@id='link']
Axis	Step	Axis	Step

Prefixes

Prefix	Example	What
//	//hr[@class='edge']	Anywhere
./	./a	Relative
/	/html/body/div	Root
Begin your expression with any of these.		

Axes

Axis	Example	What
/	//ul/li/a	Child
//	//[@id="list"]//a	Descendant
Separate your steps with /. Use two (//) if you don't want to select direct children.		

Steps

//div  
//div[@name='box']  
//[@id='link']

A step may have an element name (div) and predicates ([...]). Both are optional. They can also be these other things:

//a/text()   #=> "Go home"  
//a/@href   #=> "index.html"  
//a/\*       #=> All a's child elements

## # Predicates

Predicates

//div[true()]  
//div[@class="head"]  
//div[@class="head"][@id="top"]

Restricts a nodeset only if some condition is true. They can be chained.

Using nodes

# Use them inside functions  
//ul[count(li) > 2]  
//ul[count(li[@class="hide"]) > 0]

# This returns '<ul>' that has a '<li>' child  
//ul[li]

You can use nodes inside predicates.

Chaining order

a[1][@href='/']  
a[@href='/'][1]

Order is significant, these two are different.

Operators

# Comparison  
//a[@id = "xyz"]  
//a[@id != "xyz"]  
//a[@price > 25]

# Logic (and/or)  
//div[@id="head" and position()=2]  
//div[(x and y) or not(z)]

Use comparison and logic operators to make conditionals.

Indexing

//a[1]               # first <a>  
//a[last()]       # last <a>  
//ol/li[2]        # second <li>  
//ol/li[position()=2]   # same as above  
//ol/li[position()>1]   # :not(:first-of-type)

Use [] with a number, or last() or position().

Nesting predicates

//section[./h1[@id='hi']]

This returns <section> if it has an <h1> descendant with id='hi'.

## # Functions

Node functions

name()               # //[starts-with(name(), 'h')]  
text()               # //button[text()='Submit']  
                      # //button/text()  
  
lang(str)  
namespace-uri()

count()               # //table[count(tr)=1]  
position()            # //ol/li[position()=2]

Boolean functions

not(expr)            # button[not(starts-with(text()), "Submit")]

String functions

contains()            # font[contains(@class,"head")]  
starts-with()         # font[starts-with(@class,"head")]  
ends-with()            # font[ends-with(@class,"head")]  
  
concat(x,y)  
substring(str, start, len)  
substring-before("01/02", "/")   #=> 01  
substring-after("01/02", "/")   #=> 02  
translate()  
normalize-space()  
string-length()

## # Axes

Using axes

//ul/li               # ul > li  
//ul/child::li        # ul > li (same)  
//ul/following-sibling::li   # ul ~ li  
//ul/descendant-or-self::li   # ul li  
//ul/ancestor-or-self::li   # \$( 'ul' ).closest( 'li' )

Steps of an expression are separated by /, usually used to pick child nodes. That's not always true: you can specify a different "axis" with ::.

//	ul	/child::	li
Axis	Step	Axis	Step

Child axis

# both the same  
//ul/li/a  
//child::ul/child::li/child::a

child:: is the default axis. This makes //a/b/c work.

# both the same  
# this works because `child::li` is truthful, so the predicate succeeds  
//ul[li]  
//ul[child::li]

# both the same  
//ul[count(li) > 2]  
//ul[count(child::li) > 2]

Descendant-or-self axis

# both the same  
//div//h4  
//div/descendant-or-self::h4

// is short for the descendant-or-self:: axis.

# both the same  
//ul//[last()]  
//ul/descendant-or-self::[last()]

Unions

//a | //span

Use | to join two expressions.

Other axes

Axis	Abbr	Notes
ancestor		
ancestor-or-self		
attribute	@	@href is short for attribute::href
child		div is short for child::div
descendant		
descendant-or-self	//	// is short for /descendant-or-self::node()/
namespace		
self	.	. is short for self::node()
parent	..	.. is short for parent::node()
following		
following-sibling		
preceding		
preceding-sibling		
There are other axes you can use.		

## # More examples

Examples

/\*\*  
count(\*\*)  
((/h1[1]/text()  
//li[span])  
//ul/li/..

# all elements  
# count all elements  
# text of the first h1 heading  
# find a <li> with an <span> inside it  
# ...expands to //li[child::span]  
# use .. to select a parent

Closest

./ancestor-or-self::[@class="box"]

Works like jQuery's \$(...).closest('.box').

Find a parent

//section[h1[@id='section-name']]

Finds a <section> that directly contains h1#section-name

//section[./h1[@id='section-name']]

Finds a <section> that contains h1#section-name. (Same as above, but uses descendant-or-self instead of child)

Attributes

//item[@price > 2\*@discount]

Finds <item> and check its attributes

## # References

- Xpath test bed (whitebeam.org)

devhints.io / Search 358+ cheatsheets

Over 358 curated cheatsheets, by developers for developers.

Devhints home

Other HTML cheatsheets

Input tag cheatsheet

Layout thrashing cheatsheet

Applinks cheatsheet

HTML meta tags cheatsheet

Appcache cheatsheet

HTML emails cheatsheet

Top cheatsheets

Elixir cheatsheet

React.js cheatsheet

Vim cheatsheet

ES2015+ cheatsheet

Vimdiff cheatsheet

Vim scripting cheatsheet

21 Comments

for this cheatsheet. Write yours!