

```

// A* pseudocode from the wikipedia article
function A*(start, goal)
    // The set of nodes already evaluated
    closedSet := {}

    // The set of currently discovered nodes that are not evaluated
    yet.
    // Initially, only the start node is known.
    openSet := {start}

    // For each node, which node it can most efficiently be reached
    from.
    // If a node can be reached from many nodes, cameFrom will
    eventually
    // contain the most efficient previous step.
    cameFrom := an empty map

    // For each node, the cost of getting from the start node to that
    node.
    gScore := map with default value of Infinity

    // The cost of going from start to start is zero.
    gScore[start] := 0

    // For each node, the total cost of getting from the start node to
    the goal
    // by passing by that node. That value is partly known, partly
    heuristic.
    fScore := map with default value of Infinity

    // For the first node, that value is completely heuristic.
    fScore[start] := heuristic_cost_estimate(start, goal)

    while openSet is not empty
        current := the node in openSet having the lowest fScore[]
    value
        if current = goal
            return reconstruct_path(cameFrom, current)

        openSet.Remove(current)
        closedSet.Add(current)

        for each neighbor of current
            if neighbor in closedSet
                continue // Ignore the neighbor which is already
evaluated.

            if neighbor not in openSet // Discover a new node
                openSet.Add(neighbor)

```

```

        // The distance from start to a neighbor
        //the "dist_between" function may vary as per the solution
requirements.
        tentative_gScore := gScore[current] +
dist_between(current, neighbor)
        if tentative_gScore >= gScore[neighbor]
            continue // This is not a better path.

        // This path is the best until now. Record it!
        cameFrom[neighbor] := current
        gScore[neighbor] := tentative_gScore
        fScore[neighbor]
            := gScore[neighbor] +
heuristic_cost_estimate(neighbor, goal)

    return failure

function reconstruct_path(cameFrom, current)
    total_path := {current}
    while current in cameFrom.Keys:
        current := cameFrom[current]
        total_path.append(current)
    return total_path

```