# Shioaji

## Usage Manual

Yvictor,

Copyright © 2025 SinoPac

# Table of contents


1. Shioaji 4
   1.1 Installation 4
2. 5
   2.1 Streaming Market Data 5
   2.2 Place Order 5
   2.3 Conclusion 6
3. Environment Setup 7
   3.1 Install Python Environment 7
   3.2 Create Project Environment 7
4. - 10
   4.1 10
   4.2 22
   4.3 26
   4.4 30
   4.5 58
   4.6 CallBack 96
   4.7 104
   4.8 118
   4.9 119
5. 134
   5.1 Shioaji 134
   5.2 Login 136
   5.3 Stock Order 136
   5.4 Futures Order 140
   5.5 Market Data 143
   5.6 Future Account Info. 145
6. 146
7. 149
   7.1 version: 1.2.5 (2024-10-01) 149
   7.2 version: 1.2.4 (2024-08-28) 149
   7.3 version: 1.2.3 (2024-03-06) 149
   7.4 version: 1.2.2 (2024-01-09) 149
   7.5 version: 1.2.1 (2023-12-22) 149
   7.6 version: 1.2.0 (2023-12-20) 149
   7.7 version: 1.1.13 (2023-11-01) 150




Copyright © 2025 SinoPac

7.8 version: 1.1.12 (2023-08-22) 150
7.9 version: 1.1.11 (2023-08-04) 150
7.10 version: 1.1.10 (2023-07-23) 150
7.11 version: 1.1.9 (2023-07-20) 150
7.12 version: 1.1.8 (2023-07-18) 151
7.13 version: 1.1.7 (2023-07-18) 151
7.14 version: 1.1.6 (2023-06-19) 151
7.15 version: 1.1.5 (2023-06-07) 151
8. 152


Copyright © 2025 SinoPac

# 1. Shioaji

shioaji-logosinopac-logo

PyPI - Status PyPI - Python Version PyPI - Downloads Build - Status Coverage Binder doc Telegram

Shioaji is the most pythonic API for trading the Taiwan and global financial market. You can integrated your favorite Python packages such as NumPy, pandas, PyTorch or TensorFlow to build your trading model with the Shioaji API on cross-platform.

We are in early-release alpha. Expect some adventures and rough edges.

The key features are:

- Fast: High performance with c++ implement core and FPGA event broker.
- Easy: Designed to be easy to use and learn.
- Fast to code: With native python to integrate with large python ecosystem.
- Cross-Platform: The first one python trading API with Linux compatible in Taiwan.

## 1.1 Installation

### 1.1.1 Binaries

simple using pip to install

```
pip install shioaji
```

update shioaji with

```
pip install -U shioaji
```

### 1.1.2 uv

using uv to install

```
uv add shioaji
```

install speed version

```
uv add shioaji --extra speed
```

### 1.1.3 Docker Image

simple run with interactive mode in docker

```
docker run -it sinotrade/shioaji:latest
```

run with jupyter lab or notebook

```
docker run -p 8888:8888 sinotrade/shioaji:jupyter
```


Copyright © 2025 SinoPac

# 2.

Just import our API library like other popular python library and new the instance to start using our API. Login your account and activate the certification then you can start placing order.

> **Note**
>
> ** Please complete the Prepare before starting, including Open Account, Terms of Service and Token. **

**Login and Activate CA**

version>=1.0 version<1.0

```
import shioaji as sj

api = sj.Shioaji()
accounts =  api.login("YOUR_API_KEY", "YOUR_SECRET_KEY")
api.activate_ca(
    ca_path="/c/your/ca/path/Sinopac.pfx",
    ca_passwd="YOUR_CA_PASSWORD",
    person_id="Person of this Ca",
)
```

```
import shioaji as sj

api = sj.Shioaji()
accounts = api.login("YOUR_PERSON_ID", "YOUR_PASSWORD")
api.activate_ca(
    ca_path="/c/your/ca/path/Sinopac.pfx",
    ca_passwd="YOUR_CA_PASSWORD",
    person_id="Person of this Ca",
)
```

> **The Certification Path**
>
> In Windows you copy the file path with `\` to separate the file, you need to replace it with `/`.

## 2.1 Streaming Market Data

Subscribe the real time market data. Simplely pass contract into quote `subscribe` function and give the quote type will receive the streaming data.

```
api.quote.subscribe(api.Contracts.Stocks["2330"], quote_type="tick")
api.quote.subscribe(api.Contracts.Stocks["2330"], quote_type="bidask")
api.quote.subscribe(api.Contracts.Futures["TXFC0"], quote_type="tick")
```

> **Quote Type**
>
> Currently we support two quote type you can see in `shioaji.constent.QuoteType`. The best way to use that is directly pass this enum into `subscribe` function.

## 2.2 Place Order

Like the above subscribing market data using the contract, then need to define the order. Pass them into `place_order` function, then it will return the trade that describe the status of your order.

```
contract = api.Contracts.Stocks["2890"]
order = api.Order(
    price=12,
    quantity=5,
```



Copyright © 2025 SinoPac

```
    action=sj.constant.Action.Buy,
    price_type=sj.constant.StockPriceType.LMT,
    order_type=sj.constant.OrderType.ROD,
)
trade = api.place_order(contract, order)
```

## 2.3 Conclusion

This quickstart demonstrates how easy to use our package for native Python users. Unlike many other trading API is hard for Python developer. We focus on making more pythonic trading API for our users.


Copyright © 2025 SinoPac

# 3. Environment Setup

In this section, we will introduce how to setup the python environment with `uv` for using Shioaji API. `uv` is the best solution for managing python environment on cross-platform.

### 3.0.1 System Requirements

Before starting, please ensure your system meets the following requirements:

- Operating System: 64-bit version of Windows, MacOS, or Linux
- Python Version: 3.8 or later
- User needs to have a Sinopac account and obtain Shioaji API permissions.

## 3.1 Install Python Environment

First, you need to install Python on your system. We recommend using `uv` as the Python environment and project environment management tool. And we will use `uv` to install Shioaji API in the project.

**note**

`uv` is the best solution for managing python environment on cross-platform.

### 3.1.1 Install uv

**script**

**Linux and MacOS** **Windows**

```
curl -LsSf https://astral.sh/uv/install.sh | sh
```

```
powershell -c "irm https://astral.sh/uv/install.ps1 | iex"
```

More information about installation and usage can be found at uv official document

## 3.2 Create Project Environment

First, create a project named `sj-trading`

```
uv init sj-trading --package --app --vcs git
cd sj-trading
```

The project structure will be like this:

```
sj-trading
├── README.md
├── pyproject.toml
└── src
    └── sj_trading
        └── __init__.py
```

add Shioaji API to the project

```
uv add shioaji
```



Copyright © 2025 SinoPac

Open `pyproject.toml` file and you will see the following content

```
[project]
name = "sj-trading"
version = "0.1.0"
description = "Shioaji Trading"
readme = "README.md"
requires-python = ">=3.12"
dependencies = [
    "shioaji>=1.2.5",
]

[project.scripts]
hello = "sj_trading:hello"

[build-system]
requires = ["hatchling"]
build-backend = "hatchling.build"
```

the `hello` command is the entry point of the project.

**execute hello command**

```
uv run hello
```

**output**

```
Hello from sj-trading!
```

open `src/sj_trading/__init__.py` file and copy the following content

```
import shioaji as sj

def hello():
    get_shioaji_client()


def get_shioaji_client() -> sj.Shioaji:
    api =  sj.Shioaji()
    print("Shioaji API created")
    return api
```

**execute command**

```
uv run hello
```

**output**

```
Shioaji API created
```

This is the most basic environment setup and you can start using Shioaji API now.

## 3.2.1 Use Jupyter Environment

**Add ipykernel to the project development dependencies**

```
uv add --dev ipykernel
```



Copyright © 2025 SinoPac

**Add the project environment to the Jupyter kernel**

```
uv run ipython kernel install --user --name=sj-trading
```

**Start Jupyter**

```
uv run --with jupyter jupyter lab
```

Open `dev.ipynb` file in Jupyter and select `sj-trading` kernel to execute the command

The `hello` command we wrote earlier can be executed in this way
jupyterlab

If you have already opened an account, you can skip the next chapter and go to Token & Certificate to get the API Key and certificate.


Copyright © 2025 SinoPac

# 4. -

## 4.1

### 4.1.1

To use Shioaji, you must have a SinoPac Securities account. If you do not have a SinoPac Securities account yet, please follow the steps below to open an account:

1. To Open Account Page.
   open_acct
2. If you do not have a bank account with Bank SinoPac, please open a bank account as your delivery account.
   open_bank_1
3. Please select **DAWHO+** , to open a bank account and a securities account.
   open_bank_2
4. Complete bank and securities account opening.


Copyright © 2025 SinoPac

## 4.1.2

After version 1.0, we will use Token as our login method. Please follow the steps below to apply and use.

#### APPLY THE API KEY

1. Go to the API management page in the personal service.
   newweb_1
2. Click Add API KEY.
   newweb_2
3. Use your mobile phone or email to do two-factor authentication, and the API KEY can only be established if the verification is successful.
   newweb_3
4. You can set expiration time, permission, which account can be used, whether it can be used in the production environment and allowed IP list of the key.
   newweb_4

> **Permission Description**
>
> - Market / Data : Whether to use the market / data related API
> - Account : Whether to use the account related API
> - Trading : Whether to use the trading related API
> - Production Environment : Whether to use in the production environment

> **Attention**
>
> It is recommended to limit the use of IP, which can improve the security of the KEY.

5. If you add successfully, you will get the API Key and Secret Key.
   newweb_5

> **Attention**
>
> - Please keep your key properly and do not disclose it to anyone to avoid property loss.
> - The Secret Key is only obtained when the establishment is successful, and there is no way to obtain it after that, please make sure to save it.

#### DOWNLOAD CERTIFICATE

1. Click the Download Certificate button

   newweb_7
2. Download the certificate and place it into the folder that the API can read

   newweb_8

### Confirm The API Key And Certificate

Continue with the previous project `sj-trading`, add `.env` file in the project folder, and add the following content


Copyright © 2025 SinoPac

`.env`

```
API_KEY=<API Key>
SECRET_KEY=<Secret Key>
CA_CERT_PATH=<CA Certificate Path>
CA_PASSWORD=<CA Certificate Password>
```

the project folder structure should be like this

```
sj-trading
├── README.md
├── .env
├── pyproject.toml
├── src
│   └── sj_trading
│       └── __init__.py
└── uv.lock
```

Add the `python-dotenv` package to load the key and certificate into environment variables

```
uv add python-dotenv
```

Add the following content into `src/sj_trading/__init__.py`

```
import os
from dotenv import load_dotenv

load_dotenv()

def main():
    api = sj.Shioaji(simulation=True)
    api.login(
        api_key=os.environ["API_KEY"],
        secret_key=os.environ["SECRET_KEY"],
        fetch_contract=False
    )
    api.activate_ca(
        ca_path=os.environ["CA_CERT_PATH"],
        ca_passwd=os.environ["CA_PASSWORD"],
    )
    print("login and activate ca success")
```

Add the `main` command into `pyproject.toml`

```
[project.scripts]
main = "sj_trading"
```

Run the `main` command

```
uv run main
```

If you see `login and activate ca success`, it means you have successfully logged in to the simulation environment.

Next, if you have not yet completed the API usage signature, please proceed to the next chapter to complete the signature and pass the audit for the API.


Copyright © 2025 SinoPac

## 4.1.3

Restricted by Taiwan's financial regulations, new users need to sign relevant documents and complete a test report in the simulation mode before using it in a production environment.

### Sign Documents

Please refer to sign center and **read the documents carefully** before you sign.
signature

### Test Report

To ensure that you fully understand how to use Shioaji, you need to complete the test in the simulation mode, which includes the following functions:

- `login`
- `place_order`

> **Attention**
>
> Service Hour:
>
> - In response to the company's information security regulations, the test service is Monday to Friday 08:00 ~ 20:00
> - 18:00 ~ 20:00: Only allow Taiwan IP
> - 08:00 ~ 18:00: No limit
>
> Version Restriction:
>
> - version >= 1.2:
> install command: `uv add shioaji` or `pip install -U shioaji`
>
> Others:
>
> - You should sign the API related document before you test!
> - Stock and Futures account should be test separately.
> - The time interval between stock place order test and futures place order test should be more than 1 second.

VERSION CHECK

> **version**

```python
import shioaji as sj

print(sj.__version__)
# 1.0.0
```

- please note the **Version Restriction**.


Copyright © 2025 SinoPac

### LOGIN TEST

**Login**

**version>=1.0** **version<1.0**

```
api = sj.Shioaji(simulation=True)   # Simulation Mode
api.login(
    api_key="YOUR_API_KEY",         # edit it
    secret_key="YOUR_SECRET_KEY"    # edit it
)

api = sj.Shioaji(simulation=True)   # Simulation Mode
api.login(
    person_id="YOUR_PERSON_ID",     # edit it
    passwd="YOUR_PASSWORD",         # edit it
)
```

- version >= 1.0: use `api_key` to login, if you haven't applied for the API Key, please refer to Token section.
- version < 1.0: use `person_id` to login.

### PLACE ORDER TEST - STOCK

**Stock Order**

**version>=1.0** **version<1.0**

```
# contract - edit it
contract = api.Contracts.Stocks.TSE["2890"]

# order - edit it
order = api.Order(
    price=18,
    quantity=1,
    action=sj.constant.Action.Buy,
    price_type=sj.constant.StockPriceType.LMT,
    order_type=sj.constant.OrderType.ROD,
    account=api.stock_account
)

# place order
trade = api.place_order(contract, order)
trade
```

```
# contract - edit it
contract = api.Contracts.Stocks.TSE["2890"]

# order - edit it
order = api.Order(
    price=18,
    quantity=1,
    action=sj.constant.Action.Buy,
    price_type=sj.constant.TFTStockPriceType.LMT,
    order_type=sj.constant.TFTOrderType.ROD,
    account=api.stock_account
)

# place order
trade = api.place_order(contract, order)
trade
```


Copyright © 2025 SinoPac

**Out**

```
Response Code: 0 | Event Code: 0 | Info: host '218.32.76.102:80', IP 218.32.76.102:80 (host 1 of 1) (host connection attempt 1 of 1) (total connection attempt 1
of 1) | Event: Session up
```

```
Trade(
    contract=Stock(...),
    order=Order(...),
    status=OrderStatus(
        id='531e27af',
        status=<Status.Submitted: 'Submitted'>,
        status_code='00',
        order_datetime=datetime.datetime(2023, 1, 12, 11, 18, 3, 867490),
        order_quantity=1,
        deals=[]
    )
)
```

- You should receive the message, `Response Code: 0 | Event Code: 0 | Info: host '218.32.76.102:80' ...`, which means that you have successfully connected to our testing server. The message will only appear on your first order. If you don't receive the connected message, please confirm that all the following conditions are met.

a. Doing test in the service hour

b. Version restriction

c. `signed` is not present in your account

- order status should **NOT** be `Failed`. If you got `Failed` status, please modify your order correctly and then `place_order` again.
- Contract
- Stock Order



Copyright © 2025 SinoPac

PLACE ORDER TEST - FUTURES

### Future Order

verion>=1.0 verion<1.0

```
# near-month TXF - edit it
contract = min(
    [
        x for x in api.Contracts.Futures.TXF
        if x.code[-2:] not in ["R1", "R2"]
    ],
    key=lambda x: x.delivery_date
)

# order - edit it
order = api.Order(
    action=sj.constant.Action.Buy,
    price=15000,
    quantity=1,
    price_type=sj.constant.FuturesPriceType.LMT,
    order_type=sj.constant.OrderType.ROD,
    octype=sj.constant.FuturesOCType.Auto,
    account=api.futopt_account
)

# place order
trade = api.place_order(contract, order)
trade
```

```
# near-month TXF - edit it
contract = min(
    [
        x for x in api.Contracts.Futures.TXF
        if x.code[-2:] not in ["R1", "R2"]
    ],
    key=lambda x: x.delivery_date
)

# order - edit it
order = api.Order(
    action=sj.constant.Action.Buy,
    price=15000,
    quantity=1,
    price_type=sj.constant.FuturesPriceType.LMT,
    order_type=sj.constant.FuturesOrderType.ROD,
    octype=sj.constant.FuturesOCType.Auto,
    account=api.futopt_account
)

# place order
trade = api.place_order(contract, order)
trade
```



Copyright © 2025 SinoPac

**Out**

```
Response Code: 0 | Event Code: 0 | Info: host '218.32.76.102:80', IP 218.32.76.102:80 (host 1 of 1) (host connection attempt 1 of 1) (total connection attempt 1
of 1) | Event: Session up

Trade(
    contract=Future(...),
    order=Order(...),
    status=OrderStatus(
        id='531e27af',
        status=<Status.Submitted: 'Submitted'>,
        status_code='00',
        order_datetime=datetime.datetime(2023, 1, 12, 11, 18, 3, 867490),
        order_quantity=1,
        deals=[]
    )
)
```

- You should receive the message, `Response Code: 0 | Event Code: 0 | Info: host '218.32.76.102:80' ...`, which means that you have successfully connected to our testing server. The message will only appear on your first order. If you don't receive the connected message, please confirm that all the following conditions are met.

a. Doing test in the service hour

b. Version restriction

c. `signed` is not present in your account

- order status should **NOT** be `Failed`. If you got `Failed` status, please modify your order correctly and then `place_order` again.
- Contract
- Future Order

#### CHECK IF API TESTS HAS PASSED

**Attention**

Before you check, please confirm the following conditions are met.

- Sign the API related document before you test, or you will not pass the test.
- Doing test in service hour.
- Stock accounts and Futures accounts should be tested separately.
- Waiting for reviewing your tests at least 5 minutes.

**Sign Status**

**version>=1.0** **version<1.0**

```
import shioaji as sj

api = sj.Shioaji(simulation=False)  # Production Mode
accounts = api.login(
    api_key="YOUR_API_KEY",         # edit it
    secret_key="YOUR_SECRET_KEY"    # edit it
)
accounts
```

```
import shioaji as sj

api = sj.Shioaji(simulation=False)  # Production Mode
accounts = api.login(
    person_id="YOUR_PERSON_ID",     # edit it
    passwd="YOUR_PASSWORD",         # edit it
)
accounts
```



Copyright © 2025 SinoPac

**Out**

```
Response Code: 0 | Event Code: 0 | Info: host '203.66.91.161:80', hostname '203.66.91.161:80' IP 203.66.91.161:80 (host 1 of 1) (host connection attempt 1 of 1)
(total connection attempt 1 of 1) | Event: Session up

[FutureAccount(person_id='QBCCAIGJBJ', broker_id='F002000', account_id='9100020', signed=True, username='PAPIUSER01'),
StockAccount(person_id='QBCCAIGJBJ', broker_id='9A95', account_id='0504350', username='PAPIUSER01')]
```

- `signed=True`: Congrats, done! Ex: FutureAccount.
- `signed=False` or `signed` not present: the account haven't passed the api tests or haven't been signed the api documents. Ex: StockAccount.

### CA

You must **apply** and **activate** the CA before `place_order`.

#### APPLY CA

1. Go to SinoPac Securities to download eleader eleader_download
2. Login eleader
   login eleader
3. Select (3303) from the above eleader_account
4. Click " " CA_step
5. CA Operation steps CA_info

#### ACTIVATE CA

- If you use simulation account, you don't have to activate CA.
- If you are a macOS user, you may subject to version-issue. We suggest you to use docker and run shioaji service on docker.

**In**

```python
result = api.activate_ca(
    ca_path="/c/your/ca/path/Sinopac.pfx",
    ca_passwd="YOUR_CA_PASSWORD",
    person_id="Person ID of this Ca",
)

print(result)
# True
```

**The Certification Path**

In Windows you copy the file path with `\` to separate the file, you need to replace it with `/`.

#### Check CA expire time

**In**

```python
api.get_ca_expiretime("Person ID")
```



Copyright © 2025 SinoPac

## 4.1.4

First, we extend the project `sj-trading` created using `uv` in the environment creation chapter to add the testing flow part.

The complete project code can be referred to sj-trading https://github.com/Sinotrade/sj-trading-demo.

You can use `git` to clone the entire environment to your local machine and use it directly.

**Download Project**

```
git clone https://github.com/Sinotrade/sj-trading-demo.git
cd sj-trading-demo
```

Next, we will step by step introduce how to add the testing flow.

#### SHIOAJI VERSION

Get Shioaji version information

**Add Version Information**

Add the following content to `src/sj_trading/__init__.py`

```
def show_version() -> str:
    print(f"Shioaji Version: {sj.__version__}")
    return sj.__version__
```

**Add `version` Command to Project**

Add `version` command to `pyproject.toml`

```
[project.scripts]
version = "sj_trading:show_version"
```

Execute `uv run version` to see the Shioaji version information

```
Shioaji Version: 1.2.0
```



Copyright © 2025 SinoPac

STOCK TESTING

### Add Stock Testing File

Add file `testing_flow.py` to `src/sj_trading`

Add the following content

```
import shioaji as sj
from shioaji.constant import Action, StockPriceType, OrderType
import os

def testing_stock_ordering():
    # Login to the testing environment
    api = sj.Shioaji(simulation=True)
    accounts = api.login(
        api_key=os.environ["API_KEY"],
        secret_key=os.environ["SECRET_KEY"],
    )
    # Show all available accounts
    print(f"Available accounts: {accounts}")
    api.activate_ca(
        ca_path=os.environ["CA_CERT_PATH"],
        ca_passwd=os.environ["CA_PASSWORD"],
    )

    # Prepare the Contract for Ordering
    # Use 2890 Fubon Financial as an example
    contract = api.Contracts.Stocks["2890"]
    print(f"Contract: {contract}")

    # Create an Order for Ordering
    order = sj.order.StockOrder(
        action=Action.Buy, # Buy
        price=contract.reference, # Buy at the reference price
        quantity=1, # Order quantity
        price_type=StockPriceType.LMT, # Limit price order
        order_type=OrderType.ROD, # Effective for the day
        account=api.stock_account, # Use the default account
    )
    print(f"Order: {order}")

    # Send the order
    trade = api.place_order(contract=contract, order=order)
    print(f"Trade: {trade}")

    # Update the status
    api.update_status()
    print(f"Status: {trade.status}")
```

### Add `stock_testing` Command to Project

Add `stock_testing` command to `pyproject.toml`

```
[project.scripts]
stock_testing = "sj_trading.testing_flow:testing_stock_ordering"
```

Execute `uv run stock_testing` to start testing stock ordering



Copyright © 2025 SinoPac

FUTURES TESTING

### Add Futures Testing Content

Add the following content to `src/sj_trading/testing_flow.py`

```
from shioaji.constant import (
    FuturesPriceType,
    FuturesOCType,
)

def testing_futures_ordering():
    # Login to the testing environment
    api = sj.Shioaji(simulation=True)
    accounts = api.login(
        api_key=os.environ["API_KEY"],
        secret_key=os.environ["SECRET_KEY"],
    )
    # Show all available accounts
    print(f"Available accounts: {accounts}")
    api.activate_ca(
        ca_path=os.environ["CA_CERT_PATH"],
        ca_passwd=os.environ["CA_PASSWORD"],
    )

    # Get the contract for ordering
    # Use TXFR1 as an example
    contract = api.Contracts.Futures["TXFR1"]
    print(f"Contract: {contract}")

    # Create an Order for Ordering
    order = sj.order.FuturesOrder(
        action=Action.Buy,  # Buy
        price=contract.reference,  # Buy at the reference price
        quantity=1,  # Order quantity
        price_type=FuturesPriceType.LMT,  # Limit price order
        order_type=OrderType.ROD,  # Effective for the day
        octype=FuturesOCType.Auto,  # Auto select new close
        account=api.futopt_account,  # Use the default account
    )
    print(f"Order: {order}")

    # Send the order
    trade = api.place_order(contract=contract, order=order)
    print(f"Trade: {trade}")

    # Update the status
    api.update_status()
    print(f"Status: {trade.status}")
```

### Add `futures_testing` Command to Project

Add `futures_testing` command to `pyproject.toml`

```
[project.scripts]
futures_testing = "sj_trading.testing_flow:testing_futures_ordering"
```

Execute `uv run futures_testing` to start testing futures ordering



Copyright © 2025 SinoPac

# 4.2

Login must have a SinoPac Securities account. If you do not have a SinoPac Securities account yet. See the document for details.

## 4.2.1 Login

**Token login**

After version 1.0, we are using token as our `login` method. You can be found in Token. Before version 1.0, using person id and password.

**In**

version>=1.0 version<1.0

```
import shioaji as sj
api = sj.Shioaji()
api.login(
    api_key="YOUR_API_KEY",
    secret_key="YOUR_SECRET_KEY"
)
```

```
import shioaji as sj
api = sj.Shioaji()
api.login(
    person_id="YOUR_PERSON_ID",
    passwd="YOUR_PASSWORD",
)
```

**Out**

```
[FutureAccount(person_id='', broker_id='', account_id='', signed=True, username=''),
StockAccount(person_id='', broker_id='', account_id='', signed=True, username='')]
```

- If you cannot find `signed` in your accounts, please refer to terms of service first.

**Login Arguments**

version>=1.0 version<1.0

```
api_key (str): API Key
secret_key (str): Secret Key
fetch_contract (bool): whether to load contracts from cache or server (Default: True)
contracts_timeout (int): fetch contract timeout (Default: 0 ms)
contracts_cb (typing.Callable): fetch contract callback (Default: None)
subscribe_trade (bool): whether to subscribe Order/Deal event callback (Default: True)
receive_window (int): valid duration for login execution. (Default: 30,000 ms)

person_id (str): person_id
passwd (str): password
hashed (bool): whether password has been hashed (Default: False)
fetch_contract (bool): whether to load contracts from cache or server (Default: True)
contracts_timeout (int): fetch contract timeout (Default: 0 ms)
contracts_cb (typing.Callable): fetch contract callback (Default: None)
subscribe_trade (bool): whether to subscribe Order/Deal event callback (Default: True)
```

**Warning**

When the version is greater than 1.0, you may receive **Sign data is timeout** when login. That is, login has exceeded the effective execution time. It may be that the time difference between your computer and server is too large, you need to calibrate your computer time. Or login execution time exceeds valid time, you can increase `receive_window`.



Copyright © 2025 SinoPac

### Fetch Contracts Callback

You can use `contracts_cb` as print to check contract download status.

**In**

version>=1.0 version<1.0

```
import shioaji as sj
api = sj.Shioaji()
api.login(
    api_key="YOUR_API_KEY",
    secret_key="YOUR_SECRET_KEY",
    contracts_cb=lambda security_type: print(f"{repr(security_type)} fetch done.")
)

import shioaji as sj
api = sj.Shioaji()
api.login(
    person_id="YOUR_PERSON_ID",
    passwd="YOUR_PASSWORD",
    contracts_cb=lambda security_type: print(f"{repr(security_type)} fetch done.")
)
```

**Out**

```
[
    FutureAccount(person_id='', broker_id='', account_id='', signed=True, username=''),
    StockAccount(person_id='', broker_id='', account_id='', signed=True, username='')
]
<SecurityType.Index: 'IND'> fetch done.
<SecurityType.Future: 'FUT'> fetch done.
<SecurityType.Option: 'OPT'> fetch done.
<SecurityType.Stock: 'STK'> fetch done.
```

### Subscribe Trade

There are 2 options that you can adjust whether to subscribe trade (Order/Deal Event Callback).
The first is `subscribe_trade` in login aruguments. Default value of `subscribe_trade` is `True`, and it will automatically subscribe trade from all accounts. You don't need to make any adjustments, if you would like to receive Order/Deal Events.

**In**

version>=1.0 version<1.0

```
import shioaji as sj
api = sj.Shioaji()
api.login(
    api_key="YOUR_API_KEY",
    secret_key="YOUR_SECRET_KEY",
    subscribe_trade=True
)

import shioaji as sj
api = sj.Shioaji()
api.login(
    person_id="YOUR_PERSON_ID",
    passwd="YOUR_PASSWORD",
    subscribe_trade=True
)
```

The second one is to manually use the API `subscribe_trade` and `unsubscribe_trade` for specific account.

**Subscribe trade**

```
api.subscribe_trade(account)
```


Copyright © 2025 SinoPac

**unsubscribe trade**

```
api.unsubscribe_trade(account)
```

## 4.2.2 Account

### List Accounts

**In:**

```
accounts = api.list_accounts()
```

**Out**

```
# print(accounts)
[
    FutureAccount(person_id='PERSON_ID_1', broker_id='BROKER_ID_1', account_id='ACCOUNT_ID_1', signed=True, username='USERNAME_1'),
    FutureAccount(person_id='PERSON_ID_2', broker_id='BROKER_ID_2', account_id='ACCOUNT_ID_2', username='USERNAME_2'),
    StockAccount(person_id='PERSON_ID_3', broker_id='BROKER_ID_3', account_id='ACCOUNT_ID_3', username='USERNAME_3'),
    StockAccount(person_id='PERSON_ID_4', broker_id='BROKER_ID_4', account_id='ACCOUNT_ID_4', signed=True, username='USERNAME_4')
]
```

- If `signed` does not appear in the account list, like ACCOUNT_ID_2 and ACCOUNT_ID_3, it means that the account has not signed or completed the test report in the simulation mode. Please refer to Terms of service.

### Default Account

**In**

```
# Futures default account
print(api.futopt_account)
```

**Out**

```
FutureAccount(person_id='PERSON_ID_1', broker_id='BROKER_ID_1', account_id='ACCOUNT_ID_1', signed=True, username='USERNAME_1')
```

Set default account

**In**

```
# Default futures account switch to ACCOUNT_ID_2 from ACCOUNT_ID_1.
api.set_default_account(accounts[1])
print(api.futopt_account)
```

**Out**

```
FutureAccount(person_id='PERSON_ID_2', broker_id='BROKER_ID_2', account_id='ACCOUNT_ID_2', username='USERNAME_2')
```

In Order object, you need to specify which account you want to place order. For more information about Order, please refer to Stock Order and Futures Order.



Copyright © 2025 SinoPac

```
order = api.Order(
    price=12,
    quantity=1,
    action=sj.constant.Action.Buy,
    price_type=sj.constant.StockPriceType.LMT,
    order_type=sj.constant.OrderType.ROD,
    order_lot=sj.constant.StockOrderLot.Common,
    account=api.stock_account
)
```

## 4.2.3 Logout

Logout funciton will close the connection between the client and the server.
In order to provide high quality services, starting from 2021/08/06, we've limit the number of connections used. It's a good practice to logout or to terminate the program when it is not in use.

**logout**

```
api.logout()
# True
```



Copyright © 2025 SinoPac

# 4.3

Contract object will be used by a lot of place like place order, subscribe quote, etc.

### Get Contracts

The following provides two methods to get contracts:

- method 1: After Login success we will start to fetch all kind of contract but fetching will not block other action. So how to know the fetch action is done ? We have status of contracts download that you can use `Contracts.status`. If you set contracts_timeout inside `login` set to 10000, it will block the fetch and wait 10 second until the contract is back.

**version>=1.0** **version<1.0**

```python
import shioaji as sj
api = sj.Shioaji()
api.login(
    api_key="YOUR_API_KEY",
    secret_key="YOUR_SECRET_KEY",
    contracts_timeout=10000,
)

import shioaji as sj
api = sj.Shioaji()
api.login(
    person_id="YOUR_PERSON_ID",
    passwd="YOUR_PASSWORD",
    contracts_timeout=10000,
)
```

- method 2: If `fetch_contract` inside `login` is set to False, it will not download contract. You can use `fetch_contracts` to download.

**version>=1.0** **version<1.0**

```python
import shioaji as sj
api = sj.Shioaji()
api.login(
    api_key="YOUR_API_KEY",
    secret_key="YOUR_SECRET_KEY",
    fetch_contract=False,
)
api.fetch_contracts(contract_download=True)

import shioaji as sj
api = sj.Shioaji()
api.login(
    person_id="YOUR_PERSON_ID",
    passwd="YOUR_PASSWORD",
    fetch_contract=False,
)
api.fetch_contracts(contract_download=True)
```

### Contracts Information

The contracts we currently offer include: stocks, futures, options and indices. The products we provide can get more detailed information through the following ways.

```python
api.Contracts
```



Copyright © 2025 SinoPac

**Out**

```
Contracts(Indexs=(OTC, TSE), Stocks=(OES, OTC, TSE), Futures=(BRF, CAF, CBF, CCF, CDF, CEF, CFF, CGF, CHF, CJF, CK1, CKF, CLF, CM1, CMF, CNF, CQF, CRF, CSF, CU1,
CUF, CWF, CXF, CYF, CZ1, CZF, DCF, DD1, DDF, DEF, DFF, DGF, DHF, DIF, DJF, DKF, DLF, DNF, DOF, DPF, DQF, DSF, DUF, DVF, DWF, DXF, DYF, DZF, EEF, EGF, EHF, EMF,
EPF, ERF, EXF, EY1, EYF, FEF, FFF, FGF, FKF, FQF, FRF, FTF, FVF, FWF, FXF, FYF, FZF, G2F, GAF, GCF, GDF, GHF, GIF, GJF, GLF, GMF, GNF, GOF, GRF, GTF, GUF, GWF,
GXF, GZF, HAF, HBF, HCF, HHF, HIF, HLF, HOF, HS1, HSF, HY1, HYF, IA1, IAF, IHF, IIF, IJF, IMF, IOF, IPF, IQF, IRF, ITF, IXF, IYF, IZF, JBF, JFF, JNF, JPF, JSF,
JWF, JZF, KAF, KB1, KBF, KCF, KDF, KFF, KGF, KIF, KKF, KLF, KOF, KPF, KSF, KWF, LBF, LCF, LE1, LEF, LIF, LMF, LOF, LQF, LRF, LTF, LUF, LVF, LWF, LXF, LYF, MAF,
MBF, MCF, MJF, MKF, MPF, MQF, MVF, MX1, MXF, MYF, NAF, NBF, NCF, NDF, NEF, NGF, NHF, NIF, NJF, NLF, NMF, NNF, NOF, NQF, NSF, NUF, NVF, NWF, NXF, NYF, NZF, OAF,
OBF, OCF, ODF, OEF, OGF, OHF, OJF, OKF, OLF, OMF, OOF, OPF, OQF, ORF, OS1, OSF, OTF, OUF, OVF, OWF, OXF, OYF, OZF, PAF, PBF, PCF, PDF, PEF, PFF, PGF, PHF, PIF,
PJF, PKF, PLF, PMF, PNF, POF, PPF, PQF, RHF, RTF, SPF, T5F, TGF, TJF, TXF, UDF, UNF, XAF, XBF, XEF, XIF, XJF), Options=(CAO, CBO, CCO, CDO, CEO, CFO, CGO, CHO,
CJO, CKO, CLO, CMO, CNO, CQO, CRO, CSO, CXO, CZO, DCO, DEO, DFO, DGO, DHO, DJO, DKO, DLO, DNO, DOO, DPO, DQO, DSO, DUO, DVO, DWO, DXO, GIO, GXO, HCO, IJO, LOO,
NYA, NYO, NZO, OAO, OBO, OCO, OJO, OKO, OOO, OZO, RHO, RTO, TEO, TFO, TGO, TX1, TXO))
```

**STOCK**

**In**

```
api.Contracts.Stocks["2890"]
# or api.Contracts.Stocks.TSE.TSE2890
```

**Out**

```
Stock(
    exchange=<Exchange.TSE: 'TSE'>,
    code='2890',
    symbol='TSE2890',
    name='    ',
    category='17',
    unit=1000,
    limit_up=19.1,
    limit_down=15.7,
    reference=17.4,
    update_date='2023/01/17',
    day_trade=<DayTrade.Yes: 'Yes'>
)
```

**Stock**

```
exchange (Exchange): Attributes of industry
    {OES, OTC, TSE ...etc}
code (str): Id
symbol (str): Symbol
name (str): Name
category (str): Category
unit (int): Unit
limit_up (float): Limit up
limit_down (float): Limit down
reference (float): Reference price
update_date (str): Update date
margin_trading_balance (int): Margin trading balance
short_selling_balance (int): Short selling balance
day_trade (DayTrade): Day trade
    {Yes, No, OnlyBuy}
```

**Out**

```
Stock(
    exchange=<Exchange.TSE: 'TSE'>,
    code='2890',
    symbol='TSE2890',
    name='    ',
    category='17',
    unit=1000,
    limit_up=19.1,
    limit_down=15.7,
    reference=17.4,
    update_date='2023/01/17',
    day_trade=<DayTrade.Yes: 'Yes'>
)
```



Copyright © 2025 SinoPac

### FUTURES

**In**

```
api.Contracts.Futures["TXFA3"]
# or api.Contracts.Futures.TXF.TXF202301
```

**Out**

```
Future(
    code='TXFA3',
    symbol='TXF202301',
    name='    01',
    category='TXF',
    delivery_month='202301',
    delivery_date='2023/01/30',
    underlying_kind='I',
    unit=1,
    limit_up=16417.0,
    limit_down=13433.0,
    reference=14925.0,
    update_date='2023/01/18'
)
```

**Future**

```
code (str): Id
symbol (str): Symbol
name (str): Name
category (str): Category
delivery_month (str): Delivery Month
delivery_date (str): Delivery Date
underlying_kind (str): Underlying Kind
unit (int): Unit
limit_up (float): Limit up
limit_down (float): Limit down
reference (float): Reference price
update_date (str): Update date
```

### OPTIONS

**In**

```
api.Contracts.Options["TXO18000R3"]
# or api.Contracts.Options.TXO.TXO20230618000P
```

**Out**

```
Option(
    code='TXO18000R3',
    symbol='TXO20230618000P',
    name='     06  18000P',
    category='TXO',
    delivery_month='202306',
    delivery_date='2023/06/21',
    strike_price=18000,
    option_right=<OptionRight.Put: 'P'>,
    underlying_kind='I',
    unit=1,
    limit_up=4720.0,
    limit_down=1740.0,
    reference=3230.0,
    update_date='2023/01/18'
)
```



Copyright © 2025 SinoPac

**Option**

```
code (str): Id
symbol (str): Symbol
name (str): Name
category (str): Category
delivery_month (str): Delivery Month
delivery_date (str): Delivery Date
strike_price (int or float): Strike Price
option_right (OptionRight): Option Right
underlying_kind (str): Underlying Kind
unit (int): Unit
limit_up (float): Limit up
limit_down (float): Limit down
reference (float): Reference price
update_date (str): Update date
```

#### INDEX

The `Indexs` object shows all supported index contracts, among other categories. Index contracts do not support place_order, but allow subscribing to market quotes. This will be discussed in the next topic.

**In**

```
api.Contracts.Indexs.TSE
```

**Out**

```
TSE(TSE001, TSE015, TSE016, TSE017, TSE018, TSE019, TSE020, TSE022, TSE023, TSE024, TSE025, TSE026, TSE028, TSE029, TSE030, TSE031, TSE032, TSE033, TSE035,
TSE036, TSE037, TSE038, TSE039, TSE040, TSE041, TSE042, TSE043, TSE004, TSE005)
```

**In**

```
api.Contracts.Indexs.TSE["001"]
# or api.Contracts.Indexs.TSE.TSE001
```

**Out**

```
Index(
    exchange=<Exchange.TSE: 'TSE'>,
    code='001',
    symbol='TSE001',
    name='    '
)
```

**Index**

```
exchange (Exchange): exchange
    {OES, OTC, TSE ...etc}
code (str): Code
symbol (str): Symbol
name (str): Name
```



Copyright © 2025 SinoPac

# 4.4

## 4.4.1

To subscribe quotes is very easy, just call `subscribe` function with contract which we've discussed in previous topic.

**Subscribe**

```
>> api.quote.subscribe?

Signature:
    api.quote.subscribe(
        contract:shioaji.contracts.Contract,
        quote_type:shioaji.constant.QuoteType=<QuoteType.Tick: 'tick'>,
        intraday_odd:bool=False,
        version: shioaji.constant.QuoteVersion=<QuoteVersion.v0: 'v0'>,
    )
```

**Quote Parameters**

```
quote_type: tick price or bid/ask price to subscribe
    {'tick', 'bidask'}
intraday_odd:
    {True, False}
version: version of quote format
    {'v1', 'v0'}
```

**TICK**

**Common Stock**

**In**

```
api.quote.subscribe(
    api.Contracts.Stocks["2330"],
    quote_type = sj.constant.QuoteType.Tick,
    version = sj.constant.QuoteVersion.v1
)
```



Copyright © 2025 SinoPac

**Out**

**QuoteVersion.v1** **QuoteVersion.v0**

```
Response Code: 200 | Event Code: 16 | Info: TIC/v1/STK/*/TSE/2330 | Event: Subscribe or Unsubscribe ok

Exchange.TSE
Tick(
    code = '2330',
    datetime = datetime.datetime(2021, 7, 2, 13, 16, 35, 92970),
    open = Decimal('590'),
    avg_price = Decimal('589.05'),
    close = Decimal('590'),
    high = Decimal('593'),
    low = Decimal('587'),
    amount = Decimal('590000'),
    total_amount = Decimal('8540101000'),
    volume = 1,
    total_volume = 14498,
    tick_type = 1,
    chg_type = 4,
    price_chg = Decimal('-3'),
    pct_chg = Decimal('-0.505902'),
    bid_side_total_vol= 6638,
    ask_side_total_vol = 7860,
    bid_side_total_cnt = 2694,
    ask_side_total_cnt = 2705,
    closing_oddlot_shares = 0,
    fixed_trade_vol = 0,
    suspend = 0,
    simtrade = 0,
    intraday_odd = 0
)

Response Code: 200 | Event Code: 16 | Info: MKT/*/TSE/2330 | Event: Subscribe or Unsubscribe ok

MKT/idcdmzpcr01/TSE/2330
{
    'AmountSum': [1688787000.0],
    'Close': [593.0],
    'Date': '2021/07/01',
    'TickType': [2],
    'Time': '09:10:20.628620',
    'VolSum': [2837],
    'Volume': [1]
}
```

**Intraday odd**

**In**

```
api.quote.subscribe(
    api.Contracts.Stocks["2330"],
    quote_type = sj.constant.QuoteType.Tick,
    version = sj.constant.QuoteVersion.v1,
    intraday_odd = True
)
```



Copyright © 2025 SinoPac

### Out

**QuoteVersion.v1** **QuoteVersion.v0**

```
Response Code: 200 | Event Code: 16 | Info: TIC/v1/ODD/*/TSE/2330 | Event: Subscribe or Unsubscribe ok

Exchange.TSE
Tick(
    code = '2330',
    datetime = datetime.datetime(2021, 7, 2, 13, 16, 55, 544646),
    open = Decimal('591'),
    avg_price = Decimal('590.24415'),
    close = Decimal('590'),
    high = Decimal('591'),
    low = Decimal('589'),
    amount = Decimal('276120'),
    total_amount = Decimal('204995925'),
    volume = 468,
    total_volume = 347307,
    tick_type = 1,
    chg_type = 4,
    price_chg = Decimal('-3'),
    pct_chg = Decimal('-0.505902'),
    bid_side_total_vol= 68209,
    ask_side_total_vol = 279566,
    bid_side_total_cnt = 28,
    ask_side_total_cnt = 56,
    closing_oddlot_shares = 0,
    fixed_trade_vol = 0,
    suspend = 0,
    simtrade = 1,
    intraday_odd = 1
)

Response Code: 200 | Event Code: 16 | Info: TIC/v2/*/TSE/2330/ODDLOT | Event: Subscribe or Unsubscribe ok

TIC/v2/replay/TSE/2330/ODDLOT
{
    'Date': '2021/07/01',
    'Time': '09:23:36.880878',
    'Close': '593',
    'TickType': 1,
    'Shares': 1860,
    'SharesSum': 33152,
    'Simtrade': 1
}
```

**Attributes**

### Tick

**QuoteVersion.v1** **QuoteVersion.v0**

```
code (str):
datetime (datetime):
open (decimal):
avg_price (decimal):
close (decimal):
high (decimal):    (   )
low (decimal):    (   )
amount (decimal):     (NTD)
total_amount (decimal):      (NTD)
volume (int):     (  : ,     :  )
total_volume (int):      (  : ,     :  )
tick_type (int):     {1:   , 2:   , 0:     }
chg_type (int):     {1:   , 2:  , 3:   , 4:  , 5:   }
price_chg (decimal):
pct_chg (decimal):
bid_side_total_vol (int):        (  : ,     :  )
ask_side_total_vol (int):        (  : ,     :  )
bid_side_total_cnt (int):
ask_side_total_cnt (int):
closing_oddlot_shares (int):         ( )
fixed_trade_vol (int):       (  : ,     :  )
suspend (bool):
simtrade (bool):
intraday_odd (int):      {0:   , 1:    }

AmountSum (:List:float):
Close (:List:float):
Date (str):    (yyyy/MM/dd)
TickType (:List:int):     {1:   , 2:   , 0:     }
Time (str):    (HH:mm:ss.ffffff)
VolSum (:List:int):      ( )
Volume (:List:int):     ( )
```



Copyright © 2025 SinoPac

### BIDASK

#### Common Stock

In

```
api.quote.subscribe(
    api.Contracts.Stocks["2330"],
    quote_type = sj.constant.QuoteType.BidAsk,
    version = sj.constant.QuoteVersion.v1
)
```

Out

**QuoteVersion.v1** **QuoteVersion.v0**

```
Response Code: 200 | Event Code: 16 | Info: QUO/v1/STK/*/TSE/2330 | Event: Subscribe or Unsubscribe ok

Exchange.TSE
BidAsk(
    code = '2330',
    datetime = datetime.datetime(2021, 7, 1, 9, 9, 54, 36828),
    bid_price = [Decimal('593'), Decimal('592'), Decimal('591'), Decimal('590'), Decimal('589')],
    bid_volume = [248, 180, 258, 267, 163],
    diff_bid_vol = [3, 0, 0, 0, 0],
    ask_price = [Decimal('594'), Decimal('595'), Decimal('596'), Decimal('597'), Decimal('598')],
    ask_volume = [1457, 531, 506, 90, 259],
    diff_ask_vol = [0, 0, 0, 0, 0],
    suspend = 0,
    simtrade = 0,
    intraday_odd = 0
)

Response Code: 200 | Event Code: 16 | Info: QUT/*/TSE/2330 | Event: Subscribe or Unsubscribe ok

QUT/idcdmzpcr01/TSE/2330
{
    'AskPrice': [594.0, 595.0, 596.0, 597.0, 598.0],
    'AskVolume': [1465, 532, 507, 92, 258],
    'BidPrice': [593.0, 592.0, 591.0, 590.0, 589.0],
    'BidVolume': [254, 178, 255, 268, 163],
    'Date': '2021/07/01',
    'Time': '09:09:48.447219'
}
```

#### Intraday odd

In

```
api.quote.subscribe(
    api.Contracts.Stocks["2330"],
    quote_type = sj.constant.QuoteType.BidAsk,
    version = sj.constant.QuoteVersion.v1
    intraday_odd=True
)
```



Copyright © 2025 SinoPac

**Out**

QuoteVersion.v1 QuoteVersion.v0

```
Response Code: 200 | Event Code: 16 | Info: QUO/v1/ODD/*/TSE/2330 | Event: Subscribe or Unsubscribe ok

Exchange.TSE
BidAsk(
    code = '2330',
    datetime = datetime.datetime(2021, 7, 2, 13, 17, 45, 743299),
    bid_price = [Decimal('589'), Decimal('588'), Decimal('587'), Decimal('586'), Decimal('585')],
    bid_volume = [59391, 224490, 74082, 68570, 125246],
    diff_bid_vol = [49874, 101808, 23863, 38712, 77704],
    ask_price = [Decimal('590'), Decimal('591'), Decimal('592'), Decimal('593'), Decimal('594')],
    ask_volume = [26355, 9680, 18087, 11773, 3568],
    diff_ask_vol = [13251, -14347, 39249, -20397, -10591],
    suspend = 0,
    simtrade = 1,
    intraday_odd = 1
)

Response Code: 200 | Event Code: 16 | Info: QUO/v2/*/TSE/2330/ODDLOT | Event: Subscribe or Unsubscribe ok

QUO/v2/replay/TSE/2330/ODDLOT
{
    'Date': '2021/07/01',
    'Time': '09:43:47.143789',
    'BidPrice': ['592', '591', '590', '589', '588'],
    'AskPrice': ['593', '594', '595', '596', '597'],
    'BidShares': [16979, 12009, 45045, 5501, 12956],
    'AskShares': [17276, 14823, 26518, 23388, 10527],
    'Simtrade': 1
}
```

**Attributes**

**BidAsk**

QuoteVersion.v1 QuoteVersion.v0

```
code (str):
datetime (datetime):
bid_price (:List:decimal):
bid_volume (:List:int):     ( )
diff_bid_vol (:List:int):       ( )
ask_price (:List:decimal):
ask_volume (:List:int):
diff_ask_vol (:List:int):       ( )
suspend (bool):
simtrade (bool):

AskPrice (:List:float):
AskVolume (:List:int):
BidPrice (:List:float):
BidVolume (:List:int):
Date (datetime.date):    (yyyy/MM/dd)
Time (time):    (HH:mm:ss.ffffff)
```

**QUOTE**

**Common Stock**

**In**

```
api.quote.subscribe(
    api.Contracts.Stocks["2330"],
    quote_type = sj.constant.QuoteType.Quote,
    version = sj.constant.QuoteVersion.v1
)
```



Copyright © 2025 SinoPac

**Out**

```
Response Code: 200 | Event Code: 16 | Info: QUO/v2/STK/*/TSE/2330 | Event: Subscribe or Unsubscribe ok

Exchange.TSE,
Quote(
    code='2330',
    datetime=datetime.datetime(2022, 7, 1, 10, 43, 15, 430329),
    open=Decimal('471.5'),
    avg_price=Decimal('467.91'),
    close=Decimal('461'),
    high=Decimal('474'),
    low=Decimal('461'),
    amount=Decimal('461000'),
    total_amount=Decimal('11834476000'),
    volume=1,
    total_volume=25292,
    tick_type=2,
    chg_type=4,
    price_chg=Decimal('-15'),
    pct_chg=Decimal('-3.15'),
    bid_side_total_vol=9350,
    ask_side_total_vol=15942,
    bid_side_total_cnt=2730,
    ask_side_total_cnt=2847,
    closing_oddlot_shares=0,
    closing_oddlot_close=Decimal('0.0'),
    closing_oddlot_amount=Decimal('0'),
    closing_oddlot_bid_price=Decimal('0.0'),
    closing_oddlot_ask_price=Decimal('0.0'),
    fixed_trade_vol=0,
    fixed_trade_amount=Decimal('0'),
    bid_price=[Decimal('461'), Decimal('460.5'), Decimal('460'), Decimal('459.5'), Decimal('459')],
    bid_volume=[220, 140, 994, 63, 132],
    diff_bid_vol=[-1, 0, 0, 0, 0],
    ask_price=[Decimal('461.5'), Decimal('462'), Decimal('462.5'), Decimal('463'), Decimal('463.5')],
    ask_volume=[115, 101, 103, 147, 91],
    diff_ask_vol=[0, 0, 0, 0, 0],
    avail_borrowing=9579699,
    suspend=0,
    simtrade=0
)
```

**Attributes**

**Quote**

```
code (str):
datetime (datetime):
open (decimal):
avg_price (decimal):
close (decimal):
high (decimal):    (   )
low (decimal):    (   )
amount (decimal):     (NTD)
total_amount (decimal):      (NTD)
volume (int):
total_volume (int):
tick_type (int):
chg_type (int):
price_chg (decimal):
pct_chg (decimal):
bid_side_total_vol (int):        ( )
ask_side_total_vol (int):        ( )
bid_side_total_cnt (int):
ask_side_total_cnt (int):
closing_oddlot_shares (int):
closing_oddlot_close (decimal):
closing_oddlot_amount (decimal):
closing_oddlot_bid_price (decimal):
closing_oddlot_ask_price (decimal):
fixed_trade_vol (int):       ( )
fixed_trade_amount (decimal):
bid_price (:List:decimal):
bid_volume (:List:int)
diff_bid_vol (:List:int)
ask_price (:List:decimal):
ask_volume (:List:int)
diff_ask_vol (:List:int)
avail_borrowing (int):
suspend (bool):
simtrade (bool):
```

**CALLBACK**

In default, we set quote callback as print function. You can modify callback function as you wish. Just remember, always avoid making calulations inside the callback function.



Copyright © 2025 SinoPac

**Tick**

**In: pythonic way by using decorator**

QuoteVersion.v1 QuoteVersion.v0

```python
from shioaji import TickSTKv1, Exchange

@api.on_tick_stk_v1()
def quote_callback(exchange: Exchange, tick:TickSTKv1):
    print(f"Exchange: {exchange}, Tick: {tick}")

@api.quote.on_quote
def quote_callback(topic: str, quote: dict):
    print(f"Topic: {topic}, Quote: {quote}")
```

**In: traditional way**

QuoteVersion.v1 QuoteVersion.v0

```python
from shioaji import TickSTKv1, Exchange

def quote_callback(exchange: Exchange, tick:TickSTKv1):
    print(f"Exchange: {exchange}, Tick: {tick}")

api.quote.set_on_tick_stk_v1_callback(quote_callback)

def quote_callback(topic: str, quote: dict):
    print(f"Topic: {topic}, Quote: {quote}")

api.quote.set_quote_callback(quote_callback)
```

**Out**

QuoteVersion.v1 QuoteVersion.v0

```
Exchange: Exchange.TSE, Tick: Tick(code='2330', datetime=datetime.datetime(2021, 7, 2, 13, 16, 35, 92970), open=Decimal('590'), avg_price=Decimal('589.05'),
close=Decimal('590'), high=Decimal('593'), low=Decimal('587'), amount=Decimal('590000'), total_amount=Decimal('8540101000'), volume=1, total_volume=14498,
tick_type=1, chg_type=4, price_chg=Decimal('-3'), pct_chg=Decimal('-0.505902'), trade_bid_volume=6638, ask_side_total_vol=7860, bid_side_total_cnt=2694,
ask_side_total_cnt=2705, closing_oddlot_shares=0, fixed_trade_vol=0, suspend=0, simtrade=0, intraday_odd=0)

Topic: MKT/*/TSE/2330, Quote: {'AmountSum': [4739351000.0], 'Close': [596.0], 'Date': '2021/03/30', 'TickType': [2], 'Time': '10:01:33.349431', 'VolSum': [7932],
'Volume': [1]}
```

**BidAsk**

**In: pythonic way by using decorator**

QuoteVersion.v1 QuoteVersion.v0

```python
from shioaji import BidAskSTKv1, Exchange

@api.on_bidask_stk_v1()
def quote_callback(exchange: Exchange, bidask:BidAskSTKv1):
    print(f"Exchange: {exchange}, BidAsk: {bidask}")

@api.quote.on_quote
def quote_callback(topic: str, quote: dict):
    print(f"Topic: {topic}, Quote: {quote}")
```



Copyright © 2025 SinoPac

**In: traditional way**

QuoteVersion.v1 QuoteVersion.v0

```
from shioaji import BidAskSTKv1, Exchange

def quote_callback(exchange: Exchange, bidask:BidAskSTKv1):
    print(f"Exchange: {exchange}, BidAsk: {bidask}")

api.quote.set_on_bidask_stk_v1_callback(quote_callback)

def quote_callback(topic: str, quote: dict):
    print(f"Topic: {topic}, Quote: {quote}")

api.quote.set_quote_callback(quote_callback)
```

**Out**

QuoteVersion.v1 QuoteVersion.v0

```
Exchange: Exchange.TSE, BidAsk: BidAsk(code='2330', datetime=datetime.datetime(2021, 7, 2, 13, 17, 29, 726428), bid_price=[Decimal('589'), Decimal('588'),
Decimal('587'), Decimal('586'), Decimal('585')], bid_volume=[223, 761, 1003, 809, 1274], diff_bid_vol=[0, 0, 0, 0, 0], ask_price=[Decimal('590'), Decimal('591'),
Decimal('592'), Decimal('593'), Decimal('594')], ask_volume=[304, 232, 183, 242, 131], diff_ask_vol=[1, 0, 0, 0, 0], suspend=0, simtrade=0, intraday_odd=0)

Topic: QUT/idcdmzpcr01/TSE/2330, Quote: {'AskPrice': [590.0, 591.0, 592.0, 593.0, 594.0], 'AskVolume': [303, 232, 183, 242, 131], 'BidPrice': [589.0, 588.0,
587.0, 586.0, 585.0], 'BidVolume': [224, 762, 1003, 809, 1274], 'Date': '2021/07/02', 'Time': '13:17:26.391840'}
```

### Quote

**In: pythonic way by using decorator**

```
from shioaji import QuoteSTKv1, Exchange

@api.on_quote_stk_v1()
def quote_callback(exchange: Exchange, quote:QuoteSTKv1):
    print(f"Exchange: {exchange}, Quote: {quote}")
```

**In: traditional way**

```
from shioaji import QuoteSTKv1, Exchange

def quote_callback(exchange: Exchange, quote:QuoteSTKv1):
    print(f"Exchange: {exchange}, Quote: {quote}")

api.quote.set_on_quote_stk_v1_callback(quote_callback)
```

**Out**

```
Exchange: TSE, Quote: Quote(code='2330', datetime=datetime.datetime(2022, 7, 1, 10, 43, 15, 430329), open=Decimal('471.5'), avg_price=Decimal('467.91'),
close=Decimal('461'), high=Decimal('474'), low=Decimal('461'), amount=Decimal('461000'), total_amount=Decimal('11834476000'), volume=1, total_volume=25292,
tick_type=2, chg_type=4, price_chg=Decimal('-15'), pct_chg=Decimal('-3.15'), bid_side_total_vol=9350, ask_side_total_vol=15942, bid_side_total_cnt=2730,
ask_side_total_cnt=2847, closing_oddlot_shares=0, closing_oddlot_close=Decimal('0.0'), closing_oddlot_amount=Decimal('0'),
closing_oddlot_bid_price=Decimal('0.0'), closing_oddlot_ask_price=Decimal('0.0'), fixed_trade_vol=0, fixed_trade_amount=Decimal('0'), bid_price=[Decimal('461'),
Decimal('460.5'), Decimal('460'), Decimal('459.5'), Decimal('459')], bid_volume=[220, 140, 994, 63, 132], diff_bid_vol=[-1, 0, 0, 0, 0],
ask_price=[Decimal('461.5'), Decimal('462'), Decimal('462.5'), Decimal('463'), Decimal('463.5')], ask_volume=[115, 101, 103, 147, 91], diff_ask_vol=[0, 0, 0, 0,
0], avail_borrowing=9579699, suspend=0, simtrade=0)
```

- Intraday odd share the callback function with common stock.
- Advanced quote callback settings please refer to Quote-Binding Mode.



Copyright © 2025 SinoPac

To subscribe quotes is very easy, just call `subscribe` function with contract which we've discussed in previous topic.

**Subscribe**

```
api.quote.subscribe?

    Signature:
        api.quote.subscribe(
            contract:shioaji.contracts.Contract,
            quote_type:shioaji.constant.QuoteType=<QuoteType.Tick: 'tick'>,
            intraday_odd:bool=False,
            version: shioaji.constant.QuoteVersion=<QuoteVersion.v0: 'v0'>,
        )
    Docstring: <no docstring>
    Type:      method
```

**Quote Parameters:**

```
quote_type: tick price or bid/ask price to subscribe
    {'tick', 'bidask'}
intraday_odd:
    {True, False}
version: version of quote format
    {'v1', 'v0'}
```

**TICK**

**Example**

**In**

```
api.quote.subscribe(
    api.Contracts.Futures.TXF['TXF202107'],
    quote_type = sj.constant.QuoteType.Tick,
    version = sj.constant.QuoteVersion.v1,
)
```



Copyright © 2025 SinoPac

**Out**

**QuoteVersion.v1** **QuoteVersion.v0**

```
Response Code: 200 | Event Code: 16 | Info: TIC/v1/FOP/*/TFE/TXFG1 | Event: Subscribe or Unsubscribe ok

Exchange.TAIFEX
Tick(
    code = 'TXFG1',
    datetime = datetime.datetime(2021, 7, 1, 10, 42, 29, 757000),
    open = Decimal('17678'),
    underlying_price = Decimal('17849.57'),
    bid_side_total_vol= 32210,
    ask_side_total_vol= 33218,
    avg_price = Decimal('17704.663999'),
    close = Decimal('17753'),
    high = Decimal('17774'),
    low = Decimal('17655'),
    amount = Decimal('17753'),
    total_amount = Decimal('913790823'),
    volume = 1,
    total_volume = 51613,
    tick_type = 0,
    chg_type = 2,
    price_chg = Decimal('41'),
    pct_chg = Decimal('0.231481'),
    simtrade = 0
)

Response Code: 200 | Event Code: 16 | Info: L/*/TXFG1 | Event: Subscribe or Unsubscribe ok

L/TFE/TXFG1
{
    'Amount': [17754.0],
    'AmountSum': [913027415.0],
    'AvgPrice': [17704.623134],
    'Close': [17754.0],
    'Code': 'TXFG1',
    'Date': '2021/07/01',
    'DiffPrice': [42.0],
    'DiffRate': [0.237127],
    'DiffType': [2],
    'High': [17774.0],
    'Low': [17655.0],
    'Open': 17678.0,
    'TargetKindPrice': 17849.57,
    'TickType': [2],
    'Time': '10:42:25.552000',
    'TradeAskVolSum': 33198,
    'TradeBidVolSum': 32180,
    'VolSum': [51570],
    'Volume': [1]
}
```



Copyright © 2025 SinoPac

**Attributes**

**Tick**

**QuoteVersion.v1** **QuoteVersion.v0**

```
code (str):
datetime (datetime.datetime):
open (Decimal):
underlying_price (Decimal):
bid_side_total_vol(int):        (lot)
ask_side_total_vol(int):        (lot)
avg_price (Decimal):
close (Decimal):
high (Decimal):    (   )
low (Decimal):    (   )
amount (Decimal):     (NTD)
total_amount (Decimal):      (NTD)
volume (int):     (lot)
total_volume (int):      (lot)
tick_type (int):     {1:   , 2:   , 0:     }
chg_type (int):     {1:   , 2:  , 3:   , 4:  , 5:   }
price_chg (Decimal):
pct_chg (Decimal):     (%)
simtrade (int):

Amount (list of float):     (   )
AmountSum (list of float):      (    )
AvgPrice (list of float):
Close (list of float):
Code (str):
Date (str):    (yyyy/MM/dd)
DiffPrice (list of float):
DiffRate (list of float):     (%)
DiffType (list of int):     {1:   , 2:  , 3:   , 4:  , 5:   }
High (list of float):    (   )
Low (list of float):    (   )
Open (float):
TargetKindPrice float:
TickType (:list:int):     {1:   , 2:   , 0:     }
Time (str):    (HH:mm:ss.ffffff)
TradeAskVolSum (int):        (lot)
TradeBidVolSum (int):        (lot)
VolSum (list of int):      (lot)
Volume (list of int):     (lot)
```

**BIDASK**

**Example**

```
api.quote.subscribe(
    api.Contracts.Futures.TXF['TXF202107'],
    quote_type = sj.constant.QuoteType.BidAsk,
    version = sj.constant.QuoteVersion.v1
)
```



Copyright © 2025 SinoPac

**Out**

**QuoteVersion.v1** **QuoteVersion.v0**

```
Response Code: 200 | Event Code: 16 | Info: QUO/v1/FOP/*/TFE/TXFG1 | Event: Subscribe or Unsubscribe ok

Exchange.TAIFEX
BidAsk(
    code = 'TXFG1',
    datetime = datetime.datetime(2021, 7, 1, 10, 51, 31, 999000),
    bid_total_vol = 66,
    ask_total_vol = 101,
    bid_price = [Decimal('17746'), Decimal('17745'), Decimal('17744'), Decimal('17743'), Decimal('17742')],
    bid_volume = [1, 14, 19, 17, 15],
    diff_bid_vol = [0, 1, 0, 0, 0],
    ask_price = [Decimal('17747'), Decimal('17748'), Decimal('17749'), Decimal('17750'), Decimal('17751')],
    ask_volume = [6, 22, 25, 32, 16],
    diff_ask_vol = [0, 0, 0, 0, 0],
    first_derived_bid_price = Decimal('17743'),
    first_derived_ask_price = Decimal('17751'),
    first_derived_bid_vol = 1,
    first_derived_ask_vol = 1,
    underlying_price = Decimal('17827.94'),
    simtrade = 0
)

Response Code: 200 | Event Code: 16 | Info: Q/*/TXFG1 | Event: Subscribe or Unsubscribe ok

Q/TFE/TXFG1
{
    'AskPrice': [17747.0, 17748.0, 17749.0, 17750.0, 17751.0],
    'AskVolSum': 99,
    'AskVolume': [6, 22, 25, 31, 15],
    'BidPrice': [17746.0, 17745.0, 17744.0, 17743.0, 17742.0],
    'BidVolSum': 81,
    'BidVolume': [1, 12, 23, 25, 20],
    'Code': 'TXFG1',
    'Date': '2021/07/01',
    'DiffAskVol': [0, 0, 0, 0, 0],
    'DiffAskVolSum': 0,
    'DiffBidVol': [0, 0, 2, 0, 0],
    'DiffBidVolSum': 0,
    'FirstDerivedAskPrice': 17751.0,
    'FirstDerivedAskVolume': 1,
    'FirstDerivedBidPrice': 17743.0,
    'FirstDerivedBidVolume': 1,
    'TargetKindPrice': 17828.46,
    'Time': '10:51:29.999000'
}
```



Copyright © 2025 SinoPac

#### Attributes

**BidAsk**

QuoteVersion.v1 QuoteVersion.v0

```
code (str):
datetime (datetime.datetime):
bid_total_vol (int):       (lot)
ask_total_vol (int):       (lot)
bid_price (:List:decimal):
bid_volume (:List:int):     (lot)
diff_bid_vol (:List:int):        (lot)
ask_price (:List:decimal):
ask_volume (:List:int):     (lot)
diff_ask_vol (:List:int):        (lot)
first_derived_bid_price (decimal):
first_derived_ask_price (decimal):
first_derived_bid_vol (int):
first_derived_ask_vol (int):
underlying_price (decimal):
simtrade (int):

AskPrice (:List:float):
AskVolSum (int):      (lot)
AskVolume (:List:int):
BidPrice (:List:float):
BidVolSum (int):      (lot)
BidVolume (:List:int):
Code (str):
Date (str):    (yyyy/MM/dd)
DiffAskVol (:List:int):      (lot)
DiffAskVolSum (int):
DiffBidVol (:List:int):      (lot)
DiffBidVolSum (int):
FirstDerivedAskPrice (float):
FirstDerivedAskVolume (int):
FirstDerivedBidPrice (float):
FirstDerivedBidVolume (int):
TargetKindPrice (float):
Time (str):    (HH:mm:ss.ffffff)
```

#### CALLBACK

In default, we set quote callback as print function. You can modify callback function as you wish. Just remember, always avoid making calulations inside the callback function.

#### Tick

**i.: pythonic way by using decorator**

QuoteVersion.v1 QuoteVersion.v0

```
from shioaji import TickFOPv1, Exchange

@api.on_tick_fop_v1()
def quote_callback(exchange:Exchange, tick:TickFOPv1):
    print(f"Exchange: {exchange}, Tick: {tick}")

@api.quote.on_quote
def quote_callback(topic: str, quote: dict):
    print(f"Topic: {topic}, Quote: {quote}")
```

**i.: traditional way**

QuoteVersion.v1 QuoteVersion.v0

```
from shioaji import TickFOPv1, Exchange

def quote_callback(exchange:Exchange, tick:TickFOPv1):
    print(f"Exchange: {exchange}, Tick: {tick}")

api.quote.set_on_tick_fop_v1_callback(quote_callback)

def quote_callback(topic: str, tick: dict):
    print(f"Topic: {topic}, Tick: {tick}")

api.quote.set_quote_callback(quote_callback)
```


Copyright © 2025 SinoPac

**Out**

QuoteVersion.v1 QuoteVersion.v0

```
Exchange: Exchange.TAIFEX, Tick: Tick(code='TXFG1', datetime=datetime.datetime(2021, 7, 2, 13, 17, 22, 784000), open=Decimal('17651'),
underlying_price=Decimal('17727.12'), trade_bid_total_vol=61550, trade_ask_volume=60914, avg_price=Decimal('17657.959752'), close=Decimal('17653'),
high=Decimal('17724'), low=Decimal('17588'), amount=Decimal('35306'), total_amount=Decimal('1683421593'), volume=2, total_volume=95335, tick_type=1, chg_type=2,
price_chg=Decimal('7'), pct_chg=Decimal('0.039669'), simtrade=0)

Topic: L/TFE/TXFG1, Quote: {'Amount': [17654.0], 'AmountSum': [1682856730.0], 'AvgPrice': [17657.961764], 'Close': [17654.0], 'Code': 'TXFG1', 'Date':
'2021/07/02', 'DiffPrice': [8.0], 'DiffRate': [0.045336], 'DiffType': [2], 'High': [17724.0], 'Low': [17588.0], 'Open': 17651.0, 'TargetKindPrice': 17725.14,
'TickType': [1], 'Time': '13:17:16.533000', 'TradeAskVolSum': 60890, 'TradeBidVolSum': 61520, 'VolSum': [95303], 'Volume': [1]}
```

**BidAsk**

**In: pythonic way by using decorator**

QuoteVersion.v1 QuoteVersion.v0

```
from shioaji import BidAskFOPv1, Exchange

@api.on_bidask_fop_v1()
def quote_callback(exchange:Exchange, bidask:BidAskFOPv1):
    print(f"Exchange: {exchange}, BidAsk: {bidask}")

@api.quote.on_quote
def quote_callback(topic: str, quote: dict):
    print(f"Topic: {topic}, Quote: {quote}")
```

**In: traditional way**

QuoteVersion.v1 QuoteVersion.v0

```
from shioaji import BidAskFOPv1, Exchange

def quote_callback(exchange:Exchange, bidask:BidAskFOPv1):
    print(f"Exchange: {exchange}, BidAsk: {bidask}")

api.quote.set_on_bidask_fop_v1_callback(quote_callback)

def quote_callback(topic: str, quote: dict):
    print(f"Topic: {topic}, Quote: {quote}")

api.quote.set_quote_callback(quote_callback)
```

**Out**

QuoteVersion.v1 QuoteVersion.v0

```
Exchange: Exchange.TAIFEX, BidAsk: BidAsk(code='TXFG1', datetime=datetime.datetime(2021, 7, 2, 13, 18, 0, 684000), bid_total_vol=69, ask_total_vol=94,
bid_price=[Decimal('17651'), Decimal('17650'), Decimal('17649'), Decimal('17648'), Decimal('17647')], bid_volume=[10, 12, 18, 18, 11], diff_bid_vol=[0, 0, 0, 0,
0], ask_price=[Decimal('17653'), Decimal('17654'), Decimal('17655'), Decimal('17656'), Decimal('17657')], ask_volume=[6, 17, 29, 22, 20], diff_ask_vol=[0, 0, 0,
0, 0], first_derived_bid_price=Decimal('17647'), first_derived_ask_price=Decimal('17657'), first_derived_bid_vol=2, first_derived_ask_vol=3,
underlying_price=Decimal('17725.5'), simtrade=0)

Topic: Q/TFE/TXFG1, Quote: {'AskPrice': [17653.0, 17654.0, 17655.0, 17656.0, 17657.0], 'AskVolSum': 85, 'AskVolume': [3, 16, 24, 22, 20], 'BidPrice': [17651.0,
17650.0, 17649.0, 17648.0, 17647.0], 'BidVolSum': 67, 'BidVolume': [10, 10, 18, 18, 11], 'Code': 'TXFG1', 'Date': '2021/07/02', 'DiffAskVol': [-4, -2, 0, 0, 0],
'DiffAskVolSum': 0, 'DiffBidVol': [1, 0, 2, 0, 0], 'DiffBidVolSum': 0, 'FirstDerivedAskPrice': 17657.0, 'FirstDerivedAskVolume': 3, 'FirstDerivedBidPrice':
17647.0, 'FirstDerivedBidVolume': 2, 'TargetKindPrice': 17716.19, 'Time': '13:17:57.809000'}
```

- Advanced quote callback settings please refer to Quote-Binding Mode.



Copyright © 2025 SinoPac

## 4.4.2

### Ticks

Ticks can get all day, period of time or last counts of the day. The default is get ticks of last trade day .

**Ticks**

```
api.ticks?

Signature:
    api.ticks(
        contract: shioaji.contracts.BaseContract,
        date: str = '2022-12-26',
        query_type: shioaji.constant.TicksQueryType = <TicksQueryType.AllDay: 'AllDay'>,
        time_start: Union[str, datetime.time] = None,
        time_end: Union[str, datetime.time] = None,
        last_cnt: int = 0,
        timeout: int = 30000,
        cb: Callable[[shioaji.data.Ticks], NoneType] = None,
    ) -> shioaji.data.Ticks
Docstring:
    get contract tick volumn
```

**BY DATE**

**In**

```
ticks = api.ticks(
    contract=api.Contracts.Stocks["2330"],
    date="2023-01-16"
)
ticks
```

**Out**

```
Ticks(
    ts=[1673859600113699000, 1673859600228800000, 1673859600244294000, 1673859600308595000],
    close=[506.0, 505.0, 506.0, 506.0],
    volume=[3340, 1, 17, 2],
    bid_price=[505.0, 505.0, 506.0, 506.0],
    bid_volume=[122, 320, 60, 58],
    ask_price=[506.0, 506.0, 507.0, 507.0],
    ask_volume=[13, 22, 702, 702]
    tick_type=[1, 2, 1, 2]
)
```

**Ticks**

```
ts (int): timestamp
close (float): close
volume (int): volume
bid_price (float): bid price
bid_volume (int): bid volume
ask_price (float): ask price
ask_volume (int): ask volume
tick_type (int):     {1:   , 2:   , 0:     }
```

To DataFrame

**In**

```
import pandas as pd
df = pd.DataFrame({**ticks})
df.ts = pd.to_datetime(df.ts)
df.head()
```



Copyright © 2025 SinoPac

Out

| ts | ask_price | close | bid_volume | volume | ask_volume | tick_type | bid_price |
|---|---|---|---|---|---|---|---|
| 2023-01-16 09:00:00.113699 | 506 | 506 | 122 | 3340 | 13 | 1 | 505 |
| 2023-01-16 09:00:00.228800 | 506 | 505 | 320 | 1 | 22 | 2 | 505 |
| 2023-01-16 09:00:00.244294 | 507 | 506 | 60 | 17 | 702 | 1 | 506 |
| 2023-01-16 09:00:00.308595 | 507 | 506 | 58 | 2 | 702 | 2 | 506 |

### RANGE TIME

In

```
ticks = api.ticks(
    contract=api.Contracts.Stocks["2330"],
    date="2023-01-16",
    query_type=sj.constant.TicksQueryType.RangeTime,
    time_start="09:00:00",
    time_end="09:20:01"
)
ticks
```

Out

```
Ticks(
    ts=[1673859600113699000, 1673859600228800000, 1673859600244294000, 1673859600308595000],
    close=[506.0, 505.0, 506.0, 506.0],
    volume=[3340, 1, 17, 2],
    bid_price=[505.0, 505.0, 506.0, 506.0],
    bid_volume=[122, 320, 60, 58],
    ask_price=[506.0, 506.0, 507.0, 507.0],
    ask_volume=[13, 22, 702, 702]
    tick_type=[1, 2, 1, 2]
)
```

### LAST COUNT

In

```
ticks = api.ticks(
    contract=api.Contracts.Stocks["2330"],
    date="2023-01-16",
    query_type=sj.constant.TicksQueryType.LastCount,
    last_cnt=4,
)
ticks
```

Out

```
Ticks(
    ts=[1673859600113699000, 1673859600228800000, 1673859600244294000, 1673859600308595000],
    close=[506.0, 505.0, 506.0, 506.0],
    volume=[3340, 1, 17, 2],
    bid_price=[505.0, 505.0, 506.0, 506.0],
    bid_volume=[122, 320, 60, 58],
    ask_price=[506.0, 506.0, 507.0, 507.0],
    ask_volume=[13, 22, 702, 702]
    tick_type=[1, 2, 1, 2]
)
```



Copyright © 2025 SinoPac

### KBar

**Kbars**

```
api.kbars?

Signature:
api.kbars(
    contract: shioaji.contracts.BaseContract,
    start: str = '2023-01-15',
    end: str = '2023-01-16',
    timeout: int = 30000,
    cb: Callable[[shioaji.data.Kbars], NoneType] = None,
) -> shioaji.data.Kbars
Docstring:
get Kbar
```

**In**

```
kbars = api.kbars(
    contract=api.Contracts.Stocks["2330"],
    start="2023-01-15",
    end="2023-01-16",
)
kbars
```

**Out**

```
Kbars(
    ts=[1673859660000000000, 1673859720000000000, 1673859780000000000, 1673859840000000000],
    Open=[506.0, 505.0, 505.0, 504.0],
    High=[508.0, 506.0, 506.0, 505.0],
    Low=[505.0, 505.0, 504.0, 504.0],
    Close=[505.0, 505.0, 504.0, 504.0],
    Volume=[5308, 1018, 543, 209]
)
```

**Kbars**

```
ts (int): timestamp
Open (float): open price
High (float): the highest price
Low: (float): the lowest price
Close (float): close price
Volume (int): volume
```

To DataFrame

**In**

```
import pandas as pd
df = pd.DataFrame({**kbars})
df.ts = pd.to_datetime(df.ts)
df.head()
```



Copyright © 2025 SinoPac

Out

| Close | Amount | Low | Volume | ts | Open | High |
|---|---|---|---|---|---|---|
| 505 | 2.68731e+09 | 505 | 5308 | 2023-01-16 09:01:00 | 506 | 508 |
| 505 | 5.14132e+08 | 505 | 1018 | 2023-01-16 09:02:00 | 505 | 506 |
| 504 | 2.74112e+08 | 504 | 543 | 2023-01-16 09:03:00 | 505 | 506 |
| 504 | 1.0542e+08 | 504 | 209 | 2023-01-16 09:04:00 | 504 | 505 |

### Historical Periods

Historical Periods

| | Start Date | End Date |
|---|---|---|
| Index | 2020-03-02 | Today |
| Stock | 2020-03-02 | Today |
| Futures | 2020-03-22 | Today |

### Continuous Futures

Once a futures contract passes its expiration date, the contract is invalid, and it will not exist in your `api.Contracts`. In order to get historical data for expired futures contract, we provide continuous futures contracts. `R1`, `R2` are continuous near-month and next-to-near-month futures contracts respectively. They will automatically roll contracts on delivery date. You can get historical data by using `R1`, `R2` contracts, ex `api.Contracts.Futures.TXF.TXFR1`. We show examples below.

Ticks

Ticks

```
ticks = api.ticks(
    contract=api.Contracts.Futures.TXF.TXFR1,
    date="2020-03-22"
)
ticks
```

Out

```
Ticks(
    ts=[1616166000030000000, 1616166000140000000, 1616166000140000000, 1616166000190000000],
    close=[16011.0, 16013.0, 16014.0, 16011.0],
    volume=[49, 2, 2, 1],
    bid_price=[0.0, 16011.0, 16011.0, 16011.0],
    bid_volume=[0, 1, 1, 1],
    ask_price=[0.0, 16013.0, 16013.0, 16013.0],
    ask_volume=[0, 1, 1, 1]
    tick_type=[1, 1, 1, 2]
)
```

Kbars



Copyright © 2025 SinoPac

### Kbars

```
kbars = api.kbars(
    contract=api.Contracts.Futures.TXF.TXFR1,
    start="2023-01-15",
    end="2023-01-16",
)
kbars
```

### Out

```
Kbars(
    ts=[1616402760000000000, 1616402820000000000, 1616402880000000000, 1616402940000000000],
    Open=[16018.0, 16018.0, 16000.0, 15992.0],
    High=[16022.0, 16020.0, 16005.0, 15999.0],
    Low=[16004.0, 16000.0, 15975.0, 15989.0],
    Close=[16019.0, 16002.0, 15992.0, 15994.0],
    Volume=[1791, 864, 1183, 342]
)
```



Copyright © 2025 SinoPac

## 4.4.3

Snapshot is a present stock, future, option info. It contain open, high, low, close, change price, average price, volume, total volume, buy price, buy volume, sell price, sell volume and yesterday volume.

**Reminder**

Each snapshot can contain up to 500 contracts.

**Snapshots**

```
>> api.snapshots?

Signature:
api.snapshots(
    contracts: List[Union[shioaji.contracts.Option, shioaji.contracts.Future, shioaji.contracts.Stock, shioaji.contracts.Index]],
    timeout: int = 30000,
    cb: Callable[[shioaji.data.Snapshot], NoneType] = None,
) -> List[shioaji.data.Snapshot]
Docstring:
get contract snapshot info
```

**Example**

**In**

```
contracts = [
    api.Contracts.Stocks['2330'],
    api.Contracts.Stocks['2317']
]
snapshots = api.snapshots(contracts)
snapshots
```



Copyright © 2025 SinoPac

**Out**

```
[
    Snapshot(
        ts=1673620200000000000,
        code='2330',
        exchange='TSE',
        open=507.0,
        high=509.0,
        low=499.0,
        close=500.0,
        tick_type=<TickType.Sell: 'Sell'>,
        change_price=13.5,
        change_rate=2.77,
        change_type=<ChangeType.Up: 'Up'>,
        average_price=502.42,
        volume=48,
        total_volume=77606,
        amount=24000000,
        total_amount=38990557755,
        yesterday_volume=20963.0,
        buy_price=500.0,
        buy_volume=122.0,
        sell_price=501.0,
        sell_volume=1067,
        volume_ratio=3.7
    ),
    Snapshot(
        ts=1673620200000000000,
        code='2317',
        exchange='TSE',
        open=99.0,
        high=99.5,
        low=98.6,
        close=98.6,
        tick_type=<TickType.Sell: 'Sell'>,
        change_price=0.0,
        change_rate=0.0,
        change_type=<ChangeType.Unchanged: 'Unchanged'>,
        average_price=98.96,
        volume=63,
        total_volume=17809,
        amount=6211800,
        total_amount=1762344817,
        yesterday_volume=18537.0,
        buy_price=98.6,
        buy_volume=607.0,
        sell_price=98.7,
        sell_volume=4,
        volume_ratio=0.96
    )
]
```

To DataFrame

**In**

```
df = pd.DataFrame(s.__dict__ for s in snapshots)
df.ts = pd.to_datetime(df.ts)
df
```

**Out**

| ts | code | exchange | open | high | low | close | tick_type | change_price | cl |
|---|---|---|---|---|---|---|---|---|---|
| 2023-01-13 14:30:00 | 2330 | TSE | 507 | 509 | 499 | 500 | Sell | 13.5 | |
| 2023-01-13 14:30:00 | 2317 | TSE | 99 | 99.5 | 98.6 | 98.6 | Sell | 0 | |



Copyright © 2025 SinoPac

### Attributes

#### Snapshot

```
ts (int): TimeStamp
code (str): Contract id
exchange (Exchange): exchange
open (float): open
high (float): high
low (float): low
close (float): close
tick_type (TickType): Close is buy or sell price
    {None, Buy, Sell}
change_price (float): change price
change_rate (float): change rate
change_type (ChangeType):
    {LimitUp, Up, Unchanged, Down, LimitDown}
avgerage_price (float): avgerage of price
volume (int): volume
total_volume (int): total volume
amount (int): Deal amount
total_amount (int): Total deal amount
yestoday_volume (float): Volume of yestoday
buy_price (float): Price of buy
buy_volume (float): Volume of sell
sell_price (float): Price of sell
sell_volume (int): Volume of sell
volume_ratio (float): total_volume/yestoday_volume
```



Copyright © 2025 SinoPac

## 4.4.4

### Short Stock Sources

```
>> api.short_stock_sources?

Signature:
api.short_stock_sources(
    contracts: List[shioaji.contracts.Stock],
    timeout: int = 5000,
    cb: Callable[[shioaji.data.ShortStockSource], NoneType] = None,
) -> List[shioaji.data.ShortStockSource]
```

**Example**

**In**

```
contracts = [
    api.Contracts.Stocks['2330'],
    api.Contracts.Stocks['2317']
]
short_stock_sources = api.short_stock_sources(contracts)
short_stock_sources
```

**Out**

```
[
    ShortStockSource(code='2330', short_stock_source=58260, ts=1673943433000000000),
    ShortStockSource(code='2317', short_stock_source=75049, ts=1673943433000000000)
]
```

To DataFrame

**In**

```
df = pd.DataFrame(s.__dict__ for s in short_stock_sources)
df.ts = pd.to_datetime(df.ts)
df
```

**Out**

| | code | short_stock_source | ts |
|---|---|---|---|
| 2330 | | 58260 | 2023-01-17 08:17:13 |
| 2317 | | 75049 | 2023-01-17 08:17:13 |

**Attributes**

### ShortStockSource

```
code (str): contract id
short_stock_source (float): short stock source
ts (int): timeStamp
```



Copyright © 2025 SinoPac

## 4.4.5

### Credit Enquires

```
>> api.credit_enquires?

Signature:
api.credit_enquires(
    contracts: List[shioaji.contracts.Stock],
    timeout: int = 30000,
    cb: Callable[[shioaji.data.CreditEnquire], NoneType] = None,
) -> List[shioaji.data.CreditEnquire]
```

**Example**

In

```
contracts = [
    api.Contracts.Stocks['2330'],
    api.Contracts.Stocks['2890']
]
credit_enquires = api.credit_enquires(contracts)
credit_enquires
```

Out

```
[
    CreditEnquire(update_time='2020-12-11 13:30:13', system='HE', stock_id='2330', margin_unit=1381),
    CreditEnquire(update_time='2020-12-11 13:30:02', system='HC', stock_id='2330', margin_unit=1371),
    CreditEnquire(update_time='2020-12-11 13:30:05', system='HN', stock_id='2330', margin_unit=1357),
    CreditEnquire(update_time='2020-12-11 13:30:03', system='HF', stock_id='2330', margin_unit=1314),
    CreditEnquire(update_time='2020-12-09 10:56:05', system='HE', stock_id='2890'),
    CreditEnquire(update_time='2020-12-11 09:33:04', system='HN', stock_id='2890'),
    CreditEnquire(update_time='2020-12-02 09:01:03', system='HF', stock_id='2890')
]
```

To DataFrame

In

```
df = pd.DataFrame(c.__dict__ for c in credit_enquires)
df.update_time = pd.to_datetime(df.update_time)
df
```



Copyright © 2025 SinoPac

**Out**

| | margin_unit | short_unit | stock_id | system | update_time |
|---|---|---|---|---|---|
| 0 | 1381 | 0 | 2330 | HE | 2020-12-11 13:30:13 |
| 1 | 1371 | 0 | 2330 | HC | 2020-12-11 13:30:02 |
| 2 | 1357 | 0 | 2330 | HN | 2020-12-11 14:31:19 |
| 3 | 1314 | 0 | 2330 | HF | 2020-12-11 14:31:19 |
| 4 | 0 | 0 | 2890 | HE | 2020-12-09 10:56:05 |
| 5 | 0 | 0 | 2890 | HN | 2020-12-11 09:33:04 |
| 6 | 0 | 0 | 2890 | HF | 2020-12-02 09:01:03 |

### Attributes

**CreditEnquire**

```
update_time (str): update time
system (str): system
stock_id (str): stock id
margin_unit (int): margin unit
short_unit (int): short unit
```



Copyright © 2025 SinoPac

## 4.4.6

Scanners can use parameter of scannertype to get the rank of ChangePercent, ChangePrice, DayRange, Volume and Amount.

**Scanners**

```
>> api.scanners?

Signature:
api.scanners(
    scanner_type: shioaji.constant.ScannerType,
    ascending: bool = True,
    date: str = None,
    count: shioaji.shioaji.ConstrainedIntValue = 100, # 0 <= count <= 200
    timeout: int = 30000,
    cb: Callable[[List[shioaji.data.ChangePercentRank]], NoneType] = None,
) -> List[shioaji.data.ChangePercentRank]
```

Ascending is sorted from largest to smallest by default, and the value of ascending is True. Set ascending to False to sort in descending order, and the other ranking methods are the same. `count` is how many ranks you get.

**Supported Scanner Type**

```
ChangePercentRank: rank by price percentage change
ChangePriceRank: rank by price change
DayRangeRank: rank by day range
VolumeRank: rank by volume
AmountRank: rank by amount
```

### Example

**ChangePercentRank**

```
scanners = api.scanners(
    scanner_type=sj.constant.ScannerType.ChangePercentRank,
    count=1
)
scanners
```



Copyright © 2025 SinoPac

**Out**

```
[
    ChangePercentRank(
        date='2021-04-09',
        code='5211',
        name='  ',
        ts=1617978600000000000,
        open=16.4,
        high=17.6,
        low=16.35,
        close=17.6,
        price_range=1.25,
        tick_type=1,
        change_price=1.6,
        change_type=1,
        average_price=17.45,
        volume=7,
        total_volume=1742,
        amount=123200,
        total_amount=30397496,
        yesterday_volume=514,
        volume_ratio=3.39,
        buy_price=17.6,
        buy_volume=723,
        sell_price=0.0,
        sell_volume=0,
        bid_orders=237,
        bid_volumes=82,
        ask_orders=33,
        ask_volumes=64
    )
]
```

To DataFrame

**In**

```
scanners = api.scanners(
    scanner_type=sj.constant.ScannerType.ChangePercentRank,
    count=5
)
df = pd.DataFrame(s.__dict__ for s in scanners)
df.ts = pd.to_datetime(df.ts)
df
```

**Out**

| date | code | name | ts | open | high | low | close | price_range |
|---|---|---|---|---|---|---|---|---|
| 2023-01-17 | 6259 | | 2023-01-17 11:11:41.030000 | 22.8 | 23.75 | 22.45 | 23.75 | 1.3 |
| 2023-01-17 | 6788 | | 2023-01-17 11:19:01.924000 | 107 | 116 | 107 | 116 | 9 |
| 2023-01-17 | 2540 | | 2023-01-17 11:17:39.435000 | 85.2 | 85.2 | 83 | 85.2 | 2.2 |
| 2023-01-17 | 8478 | | 2023-01-17 11:18:33.702000 | 350.5 | 378 | 347 | 378 | 31 |
| 2023-01-17 | 6612 | | 2023-01-17 11:15:32.752000 | 102 | 109 | 102 | 109 | 7 |



Copyright © 2025 SinoPac

### Attributes

#### ChangePercentRank

```
date (str): date
code (str): code
name (str): name
ts (int): timestamp
open (float): open price
high (float): high price
low (float): low price
close (float): close price
price_range (float): range of price
tick_type (int):     {1:   , 2:    , 0:     }
change_price (float): change in price
change_type (int):
    {LimitUp, Up, Unchanged, Down, LimitDown}
average_price (float): average price
volume (int): volume
total_volume (int): total volume since market open
amount (int): amount
total_amount (int): total amount since market open
yesterday_volume (int): yesterday volume
volume_ratio (float): total_volume/yestoday_volume
buy_price (float): bid
buy_volume (int): bid volume
sell_price (float): ask
sell_volume (int): ask volume
bid_orders (int): number of orders that deal at bid
bid_volumes (int): total volume that deal at bid
ask_orders (int): number of orders that deal at ask
ask_volumes (int): total volume that deal at ask
```



Copyright © 2025 SinoPac

# 4.5

## 4.5.1

**Reminder**

First, you need to login and activate CA.

STOCK ORDER

**Order Attributes**

version>=1.0 version<1.0

```
price (float or int): the price of order
quantity (int): the quantity of order
action (str): order action to buy or sell
    {Buy, Sell}
price_type (str): pricing type of order
    {LMT, MKT, MKP} (          )
order_type (str): the type of order
    {ROD, IOC, FOK}
order_cond (str): order condition stock only
    {Cash, MarginTrading, ShortSelling} (        )
order_lot (str): the type of order
    {Common, Fixing, Odd, IntradayOdd} (               )
daytrade_short {bool}: the type of first sell
    {True, False}
custom_field {str}: memo field, only letters and numbers are allowed, and the maximum length is 6.
account (:obj:Account): which account to place this order
ca (binary): the ca of this order

price (float or int): the price of order
quantity (int): the quantity of order
action (str): order action to buy or sell
    {Buy, Sell}
price_type (str): pricing type of order
    {LMT, MKT, MKP} (          )
order_type (str): the type of order
    {ROD, IOC, FOK}
order_cond (str): order condition stock only
    {Cash, MarginTrading, ShortSelling} (        )
order_lot (str): the type of order
    {Common, Fixing, Odd, IntradayOdd} (               )
first_sell {str}: the type of first sell
    {true, false}
custom_field {str}: memo field, only letters and numbers are allowed, and the maximum length is 6.
account (:obj:Account): which account to place this order
ca (binary): the ca of this order
```

PLACE ORDER

Product information ( `contract` ) and order information ( `order` ) must be provided when placing an order.

**Place Order**

```
api.place_order?

    Signature:
        api.place_order(
            contract: shioaji.contracts.Contract,
            order: shioaji.order.Order,
            timeout: int = 5000,
            cb: Callable[[shioaji.order.Trade], NoneType] = None,
        ) -> shioaji.order.Trade
    Docstring:
    placing order
```



Copyright © 2025 SinoPac

**Contract**

```
contract = api.Contracts.Stocks.TSE.TSE2890
```

**Order**

version>=1.0 version<1.0

```
order = api.Order(
    price=17,
    quantity=3,
    action=sj.constant.Action.Buy,
    price_type=sj.constant.StockPriceType.LMT,
    order_type=sj.constant.OrderType.ROD,
    order_lot=sj.constant.StockOrderLot.Common,
    # daytrade_short=False,
    custom_field="test",
    account=api.stock_account
)

order = api.Order(
    price=17,
    quantity=3,
    action=sj.constant.Action.Buy,
    price_type=sj.constant.TFTStockPriceType.LMT,
    order_type=sj.constant.TFTOrderType.ROD,
    order_lot=sj.constant.TFTStockOrderLot.Common,
    # first_sell=sj.constant.StockFirstSell.No,
    custom_field="test",
    account=api.stock_account
)
```

**Place Order**

```
trade = api.place_order(contract, order)
trade
```

**Out**

```
Trade(
    contract=Stock(
        exchange=<Exchange.TSE: 'TSE'>,
        code='2890',
        symbol='TSE2890',
        name='    ',
        category='17',
        unit=1000,
        limit_up=19.05,
        limit_down=15.65,
        reference=17.35,
        update_date='2023/01/12',
        day_trade=<DayTrade.Yes: 'Yes'>
    ),
    order=Order(
        action=<Action.Buy: 'Buy'>,
        price=17,
        quantity=3,
        id='531e27af',
        seqno='000002',
        ordno='000001',
        account=Account(
            account_type=<AccountType.Stock: 'S'>,
            person_id='A123456789',
            broker_id='9A95',
            account_id='1234567',
            signed=True
        ),
        custom_field='test',
        price_type=<StockPriceType.LMT: 'LMT'>,
        order_type=<OrderType.ROD: 'ROD'>,
        daytrade_short=False
    ),
    status=OrderStatus(
        id='531e27af',
        status=<Status.PendingSubmit: 'PendingSubmit'>,
        status_code='00',
        order_datetime=datetime.datetime(2023, 1, 12, 11, 18, 3, 867490),
        deals=[]
    )
)
```



Copyright © 2025 SinoPac

After `place_order`, you will also receive the information sent back from the exchange. For details, please refer to Order & Deal Event.

To update the `trade` status, you need to call `update_status`.

**Update Status**

```
api.update_status(api.stock_account)
trade
```

**Out**

```
Trade(
    contract=Stock(
        exchange=<Exchange.TSE: 'TSE'>,
        code='2890',
        symbol='TSE2890',
        name='    ',
        category='17',
        unit=1000,
        limit_up=19.05,
        limit_down=15.65,
        reference=17.35,
        update_date='2023/01/12',
        day_trade=<DayTrade.Yes: 'Yes'>
    ),
    order=Order(
        action=<Action.Buy: 'Buy'>,
        price=17,
        quantity=3,
        id='531e27af',
        seqno='000002',
        ordno='000001',
        account=Account(
            account_type=<AccountType.Stock: 'S'>,
            person_id='A123456789',
            broker_id='9A95',
            account_id='1234567',
            signed=True
        ),
        custom_field='test',
        price_type=<StockPriceType.LMT: 'LMT'>,
        order_type=<OrderType.ROD: 'ROD'>,
        daytrade_short=False
    ),
    status=OrderStatus(
        id='531e27af',
        status=<Status.Submitted: 'Submitted'>,
        status_code='00',
        order_datetime=datetime.datetime(2023, 1, 12, 11, 18, 3, 867490),
        order_quantity=3,
        deals=[]
    )
)
```

**Status of Trade**

- `PendingSubmit`: Sending
- `PreSubmitted`: Reservation
- `Submitted`: Send Successfully
- `Failed`: Failed
- `Cancelled`: Cancelled
- `Filled`: Complete Fill
- `Filling`: Part Fill



Copyright © 2025 SinoPac

### UPDATE ORDER

**Update Order**

```
api.update_order?

    Signature:
        api.update_order(
            trade: shioaji.order.Trade,
            price: Union[pydantic.types.StrictInt, float] = None,
            qty: int = None,
            timeout: int = 5000,
            cb: Ca  lable[[shioaji.order.Trade], NoneType] = None,
        ) -> shioaji.order.Trade
    Docstring: update the order price or qty
```

#### Update Price

**Update Price**

```
api.update_order(trade=trade, price=17.5)
api.update_status(api.stock_account)
trade
```

**Out**

```
Trade(
    contract=Stock(
        exchange=<Exchange.TSE: 'TSE'>,
        code='2890',
        symbol='TSE2890',
        name='    ',
        category='17',
        unit=1000,
        limit_up=19.05,
        limit_down=15.65,
        reference=17.35,
        update_date='2023/01/12',
        day_trade=<DayTrade.Yes: 'Yes'>
    ),
    order=Order(
        action=<Action.Buy: 'Buy'>,
        price=17,
        quantity=3,
        id='531e27af',
        seqno='000002',
        ordno='000001',
        account=Account(
            account_type=<AccountType.Stock: 'S'>,
            person_id='A123456789',
            broker_id='9A95',
            account_id='1234567',
            signed=True
        ),
        custom_field='test',
        price_type=<StockPriceType.LMT: 'LMT'>,
        order_type=<OrderType.ROD: 'ROD'>,
        daytrade_short=False
    ),
    status=OrderStatus(
        id='531e27af',
        status=<Status.Submitted: 'Submitted'>,
        status_code='00',
        order_datetime=datetime.datetime(2023, 1, 12, 11, 18, 3, 867490),
        modified_price=17.5,
        order_quantity=3,
        deals=[]
    )
)
```

#### Update Quantity (Reduce)

`update_order` can only reduce the quantity of the order.



Copyright © 2025 SinoPac

**Update Quantity**

```
api.update_order(trade=trade, qty=1)
api.update_status(api.stock_account)
trade
```

**Out**

```
Trade(
    contract=Stock(
        exchange=<Exchange.TSE: 'TSE'>,
        code='2890',
        symbol='TSE2890',
        name='    ',
        category='17',
        unit=1000,
        limit_up=19.05,
        limit_down=15.65,
        reference=17.35,
        update_date='2023/01/12',
        day_trade=<DayTrade.Yes: 'Yes'>
    ),
    order=Order(
        action=<Action.Buy: 'Buy'>,
        price=17,
        quantity=3,
        id='531e27af',
        seqno='000002',
        ordno='000001',
        account=Account(
            account_type=<AccountType.Stock: 'S'>,
            person_id='A123456789',
            broker_id='9A95',
            account_id='1234567',
            signed=True
        ),
        custom_field='test',
        price_type=<StockPriceType.LMT: 'LMT'>,
        order_type=<OrderType.ROD: 'ROD'>,
        daytrade_short=False
    ),
    status=OrderStatus(
        id='531e27af',
        status=<Status.Submitted: 'Submitted'>,
        status_code='00',
        order_datetime=datetime.datetime(2023, 1, 12, 11, 18, 3, 867490),
        order_quantity=3,
        cancel_quantity=1,
        deals=[]
    )
)
```

### CANCEL ORDER

**Cancel Order**

```
api.cancel_order(trade)
api.update_status(api.stock_account)
trade
```



Copyright © 2025 SinoPac

**Out**

```
Trade(
    contract=Stock(
        exchange=<Exchange.TSE: 'TSE'>,
        code='2890',
        symbol='TSE2890',
        name='   ',
        category='17',
        unit=1000,
        limit_up=19.05,
        limit_down=15.65,
        reference=17.35,
        update_date='2023/01/12',
        day_trade=<DayTrade.Yes: 'Yes'>
    ),
    order=Order(
        action=<Action.Buy: 'Buy'>,
        price=17,
        quantity=3,
        id='531e27af',
        seqno='000002',
        ordno='000001',
        account=Account(
            account_type=<AccountType.Stock: 'S'>,
            person_id='A123456789',
            broker_id='9A95',
            account_id='1234567',
            signed=True
        ),
        custom_field='test',
        price_type=<StockPriceType.LMT: 'LMT'>,
        order_type=<OrderType.ROD: 'ROD'>,
        daytrade_short=False
    ),
    status=OrderStatus(
        id='531e27af',
        status=<Status.Cancelled: 'Cancelled'>,
        status_code='00',
        order_datetime=datetime.datetime(2023, 1, 12, 11, 18, 3, 867490),
        order_quantity=3,
        cancel_quantity=3,
        deals=[]
    )
)
```

**DEAL**

**Update Status**

```
api.update_status(api.stock_account)
trade
```



Copyright © 2025 SinoPac

**Out**

```
Trade(
    contract=Stock(
        exchange=<Exchange.TSE: 'TSE'>,
        code='2890',
        symbol='TSE2890',
        name='   ',
        category='17',
        unit=1000,
        limit_up=19.05,
        limit_down=15.65,
        reference=17.35,
        update_date='2023/01/12',
        day_trade=<DayTrade.Yes: 'Yes'>
    ),
    order=Order(
        action=<Action.Buy: 'Buy'>,
        price=17,
        quantity=3,
        id='531e27af',
        seqno='000002',
        ordno='000001',
        account=Account(
            account_type=<AccountType.Stock: 'S'>,
            person_id='A123456789',
            broker_id='9A95',
            account_id='1234567',
            signed=True
        ),
        custom_field='test',
        price_type=<StockPriceType.LMT: 'LMT'>,
        order_type=<OrderType.ROD: 'ROD'>,
        daytrade_short=False
    ),
    status=OrderStatus(
        id='531e27af',
        status=<Status.Filled: 'Filled'>,
        status_code='00',
        order_datetime=datetime.datetime(2023, 1, 12, 11, 18, 3, 867490),
        order_quantity=3,
        deals=[
            Deal(seq='000001', price=17, quantity=3, ts=1673501631.62918)
        ]
    )
)
```

## Examples

Stock place order jupyter link

### ACTION

**Buy**

```
order = api.Order(
    price=12,
    quantity=1,
    action=sj.constant.Action.Buy,
    price_type=sj.constant.StockPriceType.LMT,
    order_type=sj.constant.OrderType.ROD,
    order_lot=sj.constant.StockOrderLot.Common,
    custom_field="test",
    account=api.stock_account
)
```

**Sell**

```
order = api.Order(
    price=12,
    quantity=1,
    action=sj.constant.Action.Sell,
    price_type=sj.constant.StockPriceType.LMT,
    order_type=sj.constant.OrderType.ROD,
    order_lot=sj.constant.StockOrderLot.Common,
    custom_field="test",
    account=api.stock_account
)
```



Copyright © 2025 SinoPac

**Daytrade Short**

version>=1.0 version<1.0

```
order = api.Order(
    price=12,
    quantity=1,
    action=sj.constant.Action.Sell,
    price_type=sj.constant.StockPriceType.LMT,
    order_type=sj.constant.OrderType.ROD,
    order_lot=sj.constant.StockOrderLot.Common,
    daytrade_short=True,
    custom_field="test",
    account=api.stock_account
)

order = api.Order(
    price=12,
    quantity=1,
    action=sj.constant.Action.Sell,
    price_type=sj.constant.TFTStockPriceType.LMT,
    order_type=sj.constant.TFTOrderType.ROD,
    order_lot=sj.constant.TFTStockOrderLot.Common,
    first_sell=sj.constant.StockFirstSell.Yes,
    custom_field="test",
    account=api.stock_account
)
```

**ROD + LMT**

**ROD + LMT**

version>=1.0 version<1.0

```
order = api.Order(
    price=12,
    quantity=1,
    action=sj.constant.Action.Sell,
    price_type=sj.constant.StockPriceType.LMT,
    order_type=sj.constant.OrderType.ROD,
    order_lot=sj.constant.StockOrderLot.Common,
    custom_field="test",
    account=api.stock_account
)

order = api.Order(
    price=12,
    quantity=1,
    action=sj.constant.Action.Sell,
    price_type=sj.constant.TFTStockPriceType.LMT,
    order_type=sj.constant.TFTOrderType.ROD,
    order_lot=sj.constant.TFTStockOrderLot.Common,
    custom_field="test",
    account=api.stock_account
)
```



Copyright © 2025 SinoPac

## 4.5.2

**Reminder**

First, you need to login and activate CA.

### FUTURES ORDER

**Order Attributes**

```
price (float or int): the price of order
quantity (int): the quantity of order
action (str): order action to buy or sell
    {Buy, Sell}
price_type (str): pricing type of order
    {LMT, MKT, MKP}
order_type (str): the type of order
    {ROD, IOC, FOK}
octype (str): the type or order to open new position or close position future only
    {Auto, New, Cover, DayTrade} (           )
account (:obj:Account): which account to place this order
ca (binary): the ca of this order
```

### PLACE ORDER

Product information ( `contract` ) and order information ( `order` ) must be provided when placing an order.

**Place Order**

```
api.place_order?

    Signature:
        api.place_order(
            contract: shioaji.contracts.Contract,
            order: shioaji.order.Order,
            timeout: int = 5000,
            cb: Callable[[shioaji.order.Trade], NoneType] = None,
        ) -> shioaji.order.Trade
    Docstring:
    placing order
```

**Contract**

```
contract = api.Contracts.Futures.TXF.TXF202301
```

**Order**

**version>=1.0** **version<1.0**

```
order = api.Order(
    action=sj.constant.Action.Buy,
    price=14400,
    quantity=3,
    price_type=sj.constant.FuturesPriceType.LMT,
    order_type=sj.constant.OrderType.ROD,
    octype=sj.constant.FuturesOCType.Auto,
    account=api.futopt_account
)

order = api.Order(
    action=sj.constant.Action.Buy,
    price=14400,
    quantity=3,
    price_type=sj.constant.FuturesPriceType.LMT,
    order_type=sj.constant.FuturesOrderType.ROD,
    octype=sj.constant.FuturesOCType.Auto,
    account=api.futopt_account
)
```



Copyright © 2025 SinoPac

**Place Order**

```
trade = api.place_order(contract, order)
trade
```

**Out**

```
Trade(
    contract=Future(
        code='TXFA3',
        symbol='TXF202301',
        name='    01',
        category='TXF',
        delivery_month='202301',
        delivery_date='2023/01/30',
        underlying_kind='I',
        unit=1,
        limit_up=16270.0,
        limit_down=13312.0,
        reference=14791.0,
        update_date='2023/01/12'
    ),
    order=Order(
        action=<Action.Buy: 'Buy'>,
        price=14400,
        quantity=3,
        id='5efffde1',
        seqno='000004',
        ordno='000003',
        account=Account(
            account_type=<AccountType.Future: 'F'>,
            person_id='A123456789',
            broker_id='F002000',
            account_id='1234567',
            signed=True
        ),
        price_type=<StockPriceType.LMT: 'LMT'>,
        order_type=<OrderType.ROD: 'ROD'>
    ),
    status=OrderStatus(
        id='5efffde1',
        status=<Status.PendingSubmit: 'PendingSubmit'>,
        status_code='00',
        order_datetime=datetime.datetime(2023, 1, 12, 14, 56, 13, 995651),
        deals=[]
    )
)
```

After `place_order`, you will also receive the information sent back from the exchange. For details, please refer to Order & Deal Event.

To update the `trade` status, you need to call `update_status`.

**Update Status**

```
api.update_status(api.futopt_account)
trade
```



Copyright © 2025 SinoPac

**Out**

```
Trade(
    contract=Future(
        code='TXFA3',
        symbol='TXF202301',
        name='    01',
        category='TXF',
        delivery_month='202301',
        delivery_date='2023/01/30',
        underlying_kind='I',
        unit=1,
        limit_up=16270.0,
        limit_down=13312.0,
        reference=14791.0,
        update_date='2023/01/12'
    ),
    order=Order(
        action=<Action.Buy: 'Buy'>,
        price=14400,
        quantity=3,
        id='5efffde1',
        seqno='000004',
        ordno='000003',
        account=Account(
            account_type=<AccountType.Future: 'F'>,
            person_id='A123456789',
            broker_id='F002000',
            account_id='1234567',
            signed=True
        ),
        price_type=<StockPriceType.LMT: 'LMT'>,
        order_type=<OrderType.ROD: 'ROD'>
    ),
    status=OrderStatus(
        id='5efffde1',
        status=<Status.Submitted: 'Submitted'>,
        status_code='00',
        order_datetime=datetime.datetime(2023, 1, 12, 14, 56, 13, 995651),
        deals=[]
    )
)
```

**Status of Trade**

- `PendingSubmit` : Sending
- `PreSubmitted` : Reservation
- `Submitted` : Send Successfully
- `Failed` : Failed
- `Cancelled` : Cancelled
- `Filled` : Complete Fill
- `Filling` : Part Fill

**UPDATE ORDER**

**Update Order**

```
api.update_order?

    Signature:
        api.update_order(
            trade: shioaji.order.Trade,
            price: Union[pydantic.types.StrictInt, float] = None,
            qty: int = None,
            timeout: int = 5000,
            cb: Ca  lable[[shioaji.order.Trade], NoneType] = None,
        ) -> shioaji.order.Trade
    Docstring: update the order price or qty
```



Copyright © 2025 SinoPac

#### Update Price

**Update Price**

```
api.update_order(trade=trade, price=14450)
api.update_status(api.futopt_account)
trade
```

**Out**

```
Trade(
    contract=Future(
        code='TXFA3',
        symbol='TXF202301',
        name='    01',
        category='TXF',
        delivery_month='202301',
        delivery_date='2023/01/30',
        underlying_kind='I',
        unit=1,
        limit_up=16270.0,
        limit_down=13312.0,
        reference=14791.0,
        update_date='2023/01/12'
    ),
    order=Order(
        action=<Action.Buy: 'Buy'>,
        price=14400,
        quantity=3,
        id='5efffde1',
        seqno='000004',
        ordno='000003',
        account=Account(
            account_type=<AccountType.Future: 'F'>,
            person_id='A123456789',
            broker_id='F002000',
            account_id='1234567',
            signed=True
        ),
        price_type=<StockPriceType.LMT: 'LMT'>,
        order_type=<OrderType.ROD: 'ROD'>
    ),
    status=OrderStatus(
        id='5efffde1',
        status=<Status.Submitted: 'Submitted'>,
        status_code='00',
        order_datetime=datetime.datetime(2023, 1, 12, 14, 56, 13, 995651),
        modified_price=14450,
        order_quantity=3,
        deals=[]
    )
)
```

#### Update Quantity (Reduce)

`update_order` can only reduce the quantity of the order.

**Update Quantity**

```
api.update_order(trade=trade, qty=1)
api.update_status(api.futopt_account)
trade
```



Copyright © 2025 SinoPac

**Out**

```
Trade(
    contract=Future(
        code='TXFA3',
        symbol='TXF202301',
        name='    01',
        category='TXF',
        delivery_month='202301',
        delivery_date='2023/01/30',
        underlying_kind='I',
        unit=1,
        limit_up=16270.0,
        limit_down=13312.0,
        reference=14791.0,
        update_date='2023/01/12'
    ),
    order=Order(
        action=<Action.Buy: 'Buy'>,
        price=14400,
        quantity=3,
        id='5efffde1',
        seqno='000004',
        ordno='000003',
        account=Account(
            account_type=<AccountType.Future: 'F'>,
            person_id='A123456789',
            broker_id='F002000',
            account_id='1234567',
            signed=True
        ),
        price_type=<StockPriceType.LMT: 'LMT'>,
        order_type=<OrderType.ROD: 'ROD'>
    ),
    status=OrderStatus(
        id='5efffde1',
        status=<Status.Submitted: 'Submitted'>,
        status_code='00',
        order_datetime=datetime.datetime(2023, 1, 12, 14, 56, 13, 995651),
        order_quantity=3,
        cancel_quantity=1,
        deals=[]
    )
)
```

### CANCEL ORDER

**Cancel Order**

```
api.cancel_order(trade)
api.update_status(api.futopt_account)
trade
```



Copyright © 2025 SinoPac

**Out**

```
Trade(
    contract=Future(
        code='TXFA3',
        symbol='TXF202301',
        name='    01',
        category='TXF',
        delivery_month='202301',
        delivery_date='2023/01/30',
        underlying_kind='I',
        unit=1,
        limit_up=16270.0,
        limit_down=13312.0,
        reference=14791.0,
        update_date='2023/01/12'
    ),
    order=Order(
        action=<Action.Buy: 'Buy'>,
        price=14400,
        quantity=3,
        id='5efffde1',
        seqno='000004',
        ordno='000003',
        account=Account(
            account_type=<AccountType.Future: 'F'>,
            person_id='A123456789',
            broker_id='F002000',
            account_id='1234567',
            signed=True
        ),
        price_type=<StockPriceType.LMT: 'LMT'>,
        order_type=<OrderType.ROD: 'ROD'>
    ),
    status=OrderStatus(
        id='5efffde1',
        status=<Status.Cancelled: 'Cancelled'>,
        status_code='00',
        order_datetime=datetime.datetime(2023, 1, 12, 14, 56, 13, 995651),
        order_quantity=3,
        cancel_quantity=3,
        deals=[]
    )
)
```

**DEAL**

**Update Status**

```
api.update_status(api.futopt_account)
trade
```



Copyright © 2025 SinoPac

**Out**

```
Trade(
    contract=Future(
        code='TXFA3',
        symbol='TXF202301',
        name='    01',
        category='TXF',
        delivery_month='202301',
        delivery_date='2023/01/30',
        underlying_kind='I',
        unit=1,
        limit_up=16270.0,
        limit_down=13312.0,
        reference=14791.0,
        update_date='2023/01/12'
    ),
    order=Order(
        action=<Action.Buy: 'Buy'>,
        price=14400,
        quantity=3,
        id='5efffde1',
        seqno='000004',
        ordno='000003',
        account=Account(
            account_type=<AccountType.Future: 'F'>,
            person_id='A123456789',
            broker_id='F002000',
            account_id='1234567',
            signed=True
        ),
        price_type=<StockPriceType.LMT: 'LMT'>,
        order_type=<OrderType.ROD: 'ROD'>
    ),
    status=OrderStatus(
        id='5efffde1',
        status=<Status.Filled: 'Filled'>,
        status_code='00',
        order_datetime=datetime.datetime(2023, 1, 12, 14, 56, 13, 995651),
        order_quantity=3,
        deals=[
            Deal(seq='000001', price=14400, quantity=3, ts=1673501631.62918)
        ]
    )
)
```

## Examples

Future and Option place order jupyter link

### ACTION

**Buy**

```
order = api.Order(
    action=sj.constant.Action.Buy,
    price=14400,
    quantity=2,
    price_type=sj.constant.FuturesPriceType.LMT,
    order_type=sj.constant.OrderType.ROD,
    octype=sj.constant.FuturesOCType.Auto,
    account=api.futopt_account
)
```

**Sell**

```
order = api.Order(
    action=sj.constant.Action.Sell,
    price=14400,
    quantity=2,
    price_type=sj.constant.FuturesPriceType.LMT,
    order_type=sj.constant.OrderType.ROD,
    octype=sj.constant.FuturesOCType.Auto,
    account=api.futopt_account
)
```



Copyright © 2025 SinoPac

**ROD + LMT**

### ROD + LMT

```
order = api.Order(
    action=sj.constant.Action.Sell,
    price=14400,
    quantity=2,
    price_type=sj.constant.FuturesPriceType.LMT,
    order_type=sj.constant.OrderType.ROD,
    octype=sj.constant.FuturesOCType.Auto,
    account=api.futopt_account
)
```



Copyright © 2025 SinoPac

## 4.5.3

**Reminder**

First, you need to login and activate CA.

place intraday odd order jupyter link

**PLACE ORDER**

**In**

```
contract = api.Contracts.Stocks.TSE.TSE0050
order = api.Order(
    price=90,
    quantity=10,
    action=sj.constant.Action.Buy,
    price_type=sj.constant.StockPriceType.LMT,
    order_type=sj.constant.OrderType.ROD,
    order_lot=sj.constant.StockOrderLot.IntradayOdd,
    account=api.stock_account,
)

trade = api.place_order(contract, order)
trade
```

**Out**

```
Trade(
    contract=Stock(
        exchange=<Exchange.TSE: 'TSE'>,
        code='0050',
        symbol='TSE0050',
        name='    50',
        category='00',
        limit_up=115.8,
        limit_down=94.8,
        eference=105.3,
        update_date='2020/09/21',
        margin_trading_balance=15390,
        short_selling_balance=2,
        day_trade=<DayTrade.Yes: 'Yes'>
    ),
    order=Order(
        action=<Action.Buy: 'Buy'>,
        price=90.0,
        quantity=10,
        id='38e68afe',
        seqno='482283',
        ordno='WA313',
        account=Account(
            account_type=<AccountType.Stock: 'S'>,
            person_id='YOUR_PERSON_ID',
            broker_id='9A95',
            account_id='0506112',
            signed=True
        ),
        price_type=<StockPriceType.LMT: 'LMT'>,
        order_type=<OrderType.ROD: 'ROD'>,
        order_lot=<StockOrderLot.IntradayOdd: 'IntradayOdd'>
    ),
    status=OrderStatus(
        id='38e68afe',
        status=<Status.Submitted: 'Submitted'>,
        status_code='00',
        order_datetime=datetime.datetime(2020, 9, 21, 14, 38, 51),
        deals=[]
    )
)
```



Copyright © 2025 SinoPac

### UPDATE ORDER

**Attention**

**Intraday Odd cannot update price.**

`update_order` can only reduce the quantity of the order.

**Update Quantity**

```
api.update_order(trade=trade, qty=2)
api.update_status(api.stock_account)
trade
```

**Out**

```
Trade(
    contract=Stock(
        exchange=<Exchange.TSE: 'TSE'>,
        code='0050',
        symbol='TSE0050',
        name='    50',
        category='00',
        limit_up=115.8,
        limit_down=94.8,
        reference=105.3,
        update_date='2020/09/21',
        margin_trading_balance=15390,
        short_selling_balance=2,
        day_trade=<DayTrade.Yes: 'Yes'>
    ),
    order=Order(
        action=<Action.Buy: 'Buy'>,
        price=90.0,
        quantity=10,
        id='9b44c3b2',
        seqno='482293',
        ordno='WA328',
        account=Account(
            account_type=<AccountType.Stock: 'S'>,
            person_id='YOUR_PERSON_ID',
            broker_id='9A95',
            account_id='0506112',
            signed=True
        ),
    price_type=<StockPriceType.LMT: 'LMT'>,
    order_type=<OrderType.ROD: 'ROD'>,
    order_lot=<StockOrderLot.IntradayOdd: 'IntradayOdd'>),
    status=OrderStatus(
        id='9b44c3b2',
        status=<Status.Submitted: 'Submitted'>,
        status_code='00',
        order_datetime=datetime.datetime(2020, 9, 21, 14, 54, 36),
        cancel_quantity=2,
        deals=[]
    )
)
```

### CANCEL ORDER

**Cancel Order**

```
api.cancel_order(trade)
api.update_status(api.stock_account)
trade
```



Copyright © 2025 SinoPac

**Out**

```
Trade(
    contract=Stock(
        exchange=<Exchange.TSE: 'TSE'>,
        code='0050',
        symbol='TSE0050',
        name='    50',
        category='00',
        limit_up=115.8,
        limit_down=94.8,
        reference=105.3,
        update_date='2020/09/21',
        margin_trading_balance=15390,
        short_selling_balance=2,
        day_trade=<DayTrade.Yes: 'Yes'>
    ),
    order=Order(
        action=<Action.Buy: 'Buy'>,
        price=90.0,
        quantity=10,
        id='9b44c3b2',
        seqno='482293',
        ordno='WA328',
        account=Account(
            account_type=<AccountType.Stock: 'S'>,
            person_id='YOUR_PERSON_ID',
            broker_id='9A95',
            account_id='0506112',
            signed=True
        ),
        price_type=<StockPriceType.LMT: 'LMT'>,
        order_type=<OrderType.ROD: 'ROD'>,
        order_lot=<StockOrderLot.IntradayOdd: 'IntradayOdd'>
    ),
    status=OrderStatus(
        id='9b44c3b2',
        status=<Status.Cancelled: 'Cancelled'>,
        status_code='00',
        order_datetime=datetime.datetime(2020, 9, 21, 14, 54, 36),
        cancel_quantity=10,
        deals=[]
    )
)
```



Copyright © 2025 SinoPac

## 4.5.4

**Reminder**

First, you need to login and activate CA.

#### PLACE COMBO ORDER.

Combo orders offer types include: **Price Call/Put Spreads**, **Time Call/Put Spreads**, **Straddles**, **Strangles**, **Conversions** and **Reversal**. Please refer to the futures exchange document for details on the combo rules.

**place_comboorder**

```
api.place_comboorder?

    Signature:
        api.place_comboorder(
            combo_contract: shioaji.contracts.ComboContract,
            order: shioaji.order.ComboOrder,
            timeout: int = 5000,
            cb: Callable[[shioaji.order.ComboTrade], NoneType] = None,
        )
    Docstring:
        placing combo order
```

Product information ( `contract` ) and order information ( `order` ) must be provided when placing an order. The order of the contracts is irrelevant, only the approved combination is required.

**Combo Contract**

```
contract_1 = api.Contracts.Options.TX4.TX4202111017850C
contract_2 = api.Contracts.Options.TX4.TX4202111017850P
combo_contract = sj.contracts.ComboContract(
    legs=[
        sj.contracts.ComboBase(action="Sell", **contract_1.dict()),
        sj.contracts.ComboBase(action="Sell", **contract_2.dict()),
    ]
)
```

**Order**

```
order = api.ComboOrder(
    price_type="LMT",
    price=1,
    quantity=1,
    order_type="IOC",
    octype=sj.constant.FuturesOCType.New,
)
```

**In**

```
trade = api.place_comboorder(combo_c, order)
```

#### CANCEL COMBO ORDER

`Trade` is the order to be deleted, which can be obtained from the `update_combostatus`.



Copyright © 2025 SinoPac

```
api.cancel_comboorder(trade)
```

#### UPDATE COMBO STATUS

Like `list_trades` and `update_status` concepts. Before getting the combo status, the status must be updated with `update_combostatus`.

```
api.update_combostatus()
api.list_combotrades()
```



Copyright © 2025 SinoPac

**Out**

```
[
    ComboTrade(
        contract=ComboContract(
            legs=[
                ComboBase(
                    security_type=<SecurityType.Option: 'OPT'>,
                    exchange=<Exchange.TAIFEX: 'TAIFEX'>,
                    code='TX516000L1',
                    symbol='TX5202112016000C',
                    name='     12W5  16000C',
                    category='TX5',
                    delivery_month='202112',
                    delivery_date='2021/12/29',
                    strike_price=16000.0,
                    option_right=<OptionRight.Call: 'C'>,
                    underlying_kind='I',
                    unit=1,
                    limit_up=3630.0,
                    limit_down=68.0,
                    reference=1850.0,
                    update_date='2021/12/23',
                    action=<Action.Sell: 'Sell'>),
                ComboBase(
                    security_type=<SecurityType.Option: 'OPT'>,
                    exchange=<Exchange.TAIFEX: 'TAIFEX'>,
                    code='TX516000X1',
                    symbol='TX5202112016000P',
                    name='     12W5  16000P',
                    category='TX5',
                    delivery_month='202112',
                    delivery_date='2021/12/29',
                    strike_price=16000.0,
                    option_right=<OptionRight.Put: 'P'>,
                    underlying_kind='I',
                    unit=1,
                    limit_up=1780.0,
                    limit_down=0.1,
                    reference=0.9,
                    update_date='2021/12/23',
                    action=<Action.Sell: 'Sell'>)
                ]
            ),
        order=Order(
            action=<Action.Sell: 'Sell'>,
            price=1.0,
            quantity=1,
            id='46989de8',
            seqno='743595',
            ordno='000000',
            account=Account(
                account_type=<AccountType.Future: 'F'>,
                person_id='YOUR_PERSON_ID',
                broker_id='F002000',
                account_id='1234567',
                signed=True
            ),
            price_type=<StockPriceType.LMT: 'LMT'>,
            order_type=<OrderType.IOC: 'IOC'>,
            octype=<FuturesOCType.New: 'New'>
        ),
        status=ComboStatus(
            id='46989de8',
            status=<Status.Failed: 'Failed'>,
            status_code='99Q9',
            order_datetime=datetime.datetime(2021, 12, 23, 8, 46, 47),
            msg='       ',
            modified_price=1.0,
            deals={}
        )
    )
]
```



Copyright © 2025 SinoPac

## 4.5.5

When Stock triggers some transaction abnormal conditions, it is necessary to `Reserve Order` in advance. Abnormal conditions include: watch out for stocks, warn about stocks, dispose of stocks, and manage stocks.

**Reminder**

- First, you need to login and activate CA.
- Service hours are from 8:00 to 14:30 on trading days.

#### GET STOCK RESERVE SUMMAY STATUS

**In**

```
reserve_summary_resp = api.stock_reserve_summary(account)
```

**Out**

```
ReserveStocksSummaryResponse(
    response=ReserveStocksSummary(
        stocks=[
            ReserveStockSummary(
                contract=Contract(
                    security_type=<SecurityType.Stock: 'STK'>,
                    exchange=<Exchange.TSE: 'TSE'>,
                    code='2890',
                    name='    '
                ),
                available_share=5000,
                reserved_share=0
            )
        ],
        account=StockAccount(
            person_id='X123456789',
            broker_id='9A95',
            account_id='12345678',
            signed=True
            )
        )
    )
```

#### RESERVE STOCK

**In**

```
contract = api.Contracts.Stocks["2890"]
resp = api.reserve_stock(account, contract, 1000)
```



Copyright © 2025 SinoPac

Out

```
ReserveStockResponse(
    response=ReserveOrderResp(
        contract=Stock(
            exchange=<Exchange.TSE: 'TSE'>,
            code='2890',
            symbol='TSE2890',
            name='    '
        ),
        account=StockAccount(
            person_id='X123456789',
            broker_id='9A95',
            account_id='12345678',
            signed=True),
        share=1000,
        status=True,
        info=''
    )
)
```

### GET STOCK RESERVE DETAIL SATUS

```
resp = api.stock_reserve_detail(account)
```

Out

```
ReserveStocksDetailResponse(
    response=ReserveStocksDetail(stocks=[
            ReserveStockDetail(
                contract=Contract(
                    security_type=<SecurityType.Stock: 'STK'>,
                    exchange=<Exchange.TSE: 'TSE'>,
                    code='6153',
                    name='    '
                ),
                share=1000,
                order_ts=1638253253,
                status=True,
                info='    '
            )
        ],
        account=StockAccount(
            person_id='X123456789',
            broker_id='9A95',
            account_id='12345678',
            signed=True)
        )
)
```

### RESERVE EARMARKING

```
contract = api.Contracts.Stocks["2890"]
resp = api.reserve_earmarking(account, contract, 1000, 15.15)
```



Copyright © 2025 SinoPac

**Out**

```
ReserveEarmarkingResponse(
    response=EarmarkingOrderResp(
        contract=Stock(
            exchange=<Exchange.TSE: 'TSE'>,
            code='2890',
            symbol='TSE2890',
            name='    ',
        ),
        account=StockAccount(
            person_id='X123456789',
            broker_id='9A95',
            account_id='12345678',
            signed=True)
        ),
        share=1000,
        price=15.15,
        status=True,
        info='OK')
)
```

#### GET EARMARKING DETAIL STATUS

**In**

```
api.earmarking_detail(account)
```

**Out**

```
EarmarkStocksDetailResponse(
    response=EarmarkStocksDetail(
        stocks=[
            EarmarkStockDetail(
                contract=Contract(
                    security_type=<SecurityType.Stock: 'STK'>,
                    exchange=<Exchange.TSE: 'TSE'>,
                    code='2890',
                    name='    '
                ),
                share=1000,
                price=15.15,
                amount=15171,
                order_ts=1638416488,
                status=False,
                info='    '),
            EarmarkStockDetail(
                contract=Contract(
                    security_type=<SecurityType.Stock: 'STK'>,
                    exchange=<Exchange.TSE: 'TSE'>,
                    code='2890',
                    name='    '
                ),
                share=1000,
                price=15.15,
                amount=15171,
                order_ts=1638415662, status=True,
                info='')
            ],
            account=StockAccount(
                person_id='X123456789',
                broker_id='9A95',
                account_id='12345678',
                signed=True)
            )
        )
    )
```

#### EXAMPLE

Query the reserve status of all accounts under your name.



Copyright © 2025 SinoPac

```python
import shioaji as sj

api = sj.Shioaji()
accounts = api.login("YOUR_PERSON_ID", "YOUR_PASSWORD", contracts_timeout=10000)
api.activate_ca(
    ca_path="/c/your/ca/path/Sinopac.pfx",
    ca_passwd="YOUR_CA_PASSWORD",
    person_id="Person of this Ca",
)
for account in accounts:
    if account.account_type == AccountType.Stock:
        reserve_summary_resp = api.stock_reserve_summary(account)
        for reserve_stock_summary in reserve_summary_resp.response.stocks:
                if reserve_stock_summary.available_share:
                    resp = api.reserve_stock(
                        account,
                        reserve_stock_summary.contract,
                        reserve_stock_summary.available_share
                    )
```



Copyright © 2025 SinoPac

## 4.5.6

**Reminder**

First, you need to login and activate CA.

Before obtaining the `Trade` status, it must be updated with `update_status`. If you cannot successfully `update_order` or `cancel_order`, you can use `update_status` to update the specific `trade` status, and check the `OrderStatus` in `trade`, whether it is available to modify the order.

The update_status defaults to querying all accounts under the user's name. If you wish to inquire about a specific account, provide the account as a parameter to account.

**Update Status**

```
api.update_status?
```

**Out**

```
Signature:
    api.update_status(
        account: shioaji.account.Account = None,
        trade: shioaji.order.Trade = None,
        timeout: int = 5000,
        cb: Callable[[List[shioaji.order.Trade]], NoneType] = None,
    )
Docstring: update status of all trades you have
```

#### GET STOCK TRADES

**Get Stock Trades**

```
api.update_status(api.stock_account)
api.list_trades()
```



Copyright © 2025 SinoPac

**Out**

```
[
    Trade(
        contract=Stock(
            exchange=<Exchange.TSE: 'TSE'>,
            code='2890',
            symbol='TSE2890',
            name='    ',
            category='17',
            unit=1000,
            limit_up=19.05,
            limit_down=15.65,
            reference=17.35,
            update_date='2023/01/12',
            day_trade=<DayTrade.Yes: 'Yes'>
        ),
        order=Order(
            action=<Action.Buy: 'Buy'>,
            price=17,
            quantity=3,
            id='531e27af',
            seqno='000002',
            ordno='000001',
            account=Account(
                account_type=<AccountType.Stock: 'S'>,
                person_id='A123456789',
                broker_id='9A95',
                account_id='1234567',
                signed=True
            ),
            custom_field='test',
            price_type=<StockPriceType.LMT: 'LMT'>,
            order_type=<OrderType.ROD: 'ROD'>,
            daytrade_short=True
        ),
        status=OrderStatus(
            id='531e27af',
            status=<Status.Filled: 'Filled'>,
            status_code='00',
            order_datetime=datetime.datetime(2023, 1, 12, 11, 18, 3, 867490),
            order_quantity=3,
            deals=[
                Deal(seq='000001', price=17, quantity=3, ts=1673501631.62918)
            ]
        )
    )
]
```

### GET FUTURES TRADES

**Get Futures Trades**

```
api.update_status(api.futopt_account)
api.list_trades()
```



Copyright © 2025 SinoPac

**Out**

```
[
    Trade(
        contract=Future(
            code='TXFA3',
            symbol='TXF202301',
            name='    01',
            category='TXF',
            delivery_month='202301',
            delivery_date='2023/01/30',
            underlying_kind='I',
            unit=1,
            limit_up=16270.0,
            limit_down=13312.0,
            reference=14791.0,
            update_date='2023/01/12'
        ),
        order=Order(
            action=<Action.Buy: 'Buy'>,
            price=14400,
            quantity=3,
            id='5efffde1',
            seqno='000004',
            ordno='000003',
            account=Account(
                account_type=<AccountType.Future: 'F'>,
                person_id='A123456789',
                broker_id='F002000',
                account_id='1234567',
                signed=True
            ),
            price_type=<StockPriceType.LMT: 'LMT'>,
            order_type=<OrderType.ROD: 'ROD'>
        ),
        status=OrderStatus(
            id='5efffde1',
            status=<Status.Filled: 'Filled'>,
            status_code='00',
            order_datetime=datetime.datetime(2023, 1, 12, 14, 56, 13, 995651),
            order_quantity=3,
            deals=[
                Deal(seq='000001', price=14400, quantity=3, ts=1673501631.62918)
            ]
        )
    )
]
```

### UPDATE SPECIFIC TRADE

**Update Trade**

```
# you can get trade from place_order
# trade = api.place_order(contract, order)

# or get from api.list_trades
# trade = api.list_trades()[0]

api.update_status(trade=trade)
```

### TRADE STATUS

**OrderStatus**

```
id (str): the id uses to correlate the order object
status (:obj:Status): the status of order {Cancelled, Filled, PartFilled, Failed, PendingSubmit, PreSubmitted, Submitted}
status_code (str): the code of status
order_datetime (datetime): order time
order_quantity (int): order quantity
modified_price (float): the price of modification
cancel_quantity (int): the quantity of cancel
deals (:List:Deal): information of filled order
```



Copyright © 2025 SinoPac

### Deal

```
seq (str): deal sequence number
price (int or float): deal price
quantity (int): deal quantity
ts (float): deal timestamp
```



Copyright © 2025 SinoPac

## 4.5.7

**Order CallBack**

When the exchange receives the order, it will return the callback. The callback is divided into four parts, including operation, order, status and contract. We will explain in detail below.


Copyright © 2025 SinoPac

**Order Event**

version>=1.0 version<1.0

```
OrderState.StockOrder {
    'operation': {
        'op_type': 'New',
        'op_code': '00',
        'op_msg': ''
    },
    'order': {
        'id': '97b63e2f',
        'seqno': '267677',
        'ordno': 'IM394',
        'account': {
            'account_type': 'S',
            'person_id': '',
            'broker_id': '9A95',
            'account_id': '1234567',
            'signed': True
        },
        'action': 'Buy',
        'price': 16.0,
        'quantity': 1,
        'order_type': 'ROD',
        'price_type': 'LMT',
        'order_cond': 'Cash',
        'order_lot': 'Common',
        'custom_field': 'test'
    },
    'status': {
        'id': '97b63e2f',
        'exchange_ts': 1673576134.038,
        'modified_price': 0.0,
        'cancel_quantity': 0,
        'order_quantity': 1,
        'web_id': '137'
    },
    'contract': {
        'security_type': 'STK',
        'exchange': 'TSE',
        'code': '2890',
        'symbol': '',
        'name': '',
        'currency': 'TWD'
    }
}
```

```
OrderState.TFTOrder {
    'operation': {
        'op_type': 'New',
        'op_code': '00',
        'op_msg': ''
    },
    'order': {
        'id': '97b63e2f',
        'seqno': '267677',
        'ordno': 'IM394',
        'account': {
            'account_type': 'S',
            'person_id': '',
            'broker_id': '9A95',
            'account_id': '1234567',
            'signed': True
        },
        'action': 'Buy',
        'price': 16.0,
        'quantity': 1,
        'order_type': 'ROD',
        'price_type': 'LMT',
        'order_cond': 'Cash',
        'order_lot': 'Common',
        'custom_field': 'test'
    },
    'status': {
        'id': '97b63e2f',
        'exchange_ts': 1673576134.038,
        'modified_price': 0.0,
        'cancel_quantity': 0,
        'order_quantity': 1,
        'web_id': '137'
    },
    'contract': {
        'security_type': 'STK',
        'exchange': 'TSE',
        'code': '2890',
        'symbol': '',
        'name': '',
        'currency': 'TWD'
    }
}
```



Copyright © 2025 SinoPac

**Order CallBack Info.**

**operation**

```
op_type (str): {
        "New": new order,
        "Cancel": cancel order,
        "UpdatePrice": update price,
        "UpdateQty": update quantity
    }
op_code (str): {"00": success, others: fail}
op_msg (str): error message
```

**order**

```
id (str): same as the trade_id in SDeal
seqno (str): sequence number
ordno (str): order number
account (dict): account info
action (str): {Buy, Sell}
price (float or int): order price
quantity (int): order quantity
order_type (str): the type of order {ROD, IOC, FOK}
price_type (str): pricing type of order {LMT, MKT, MKP}
order_cond (str): {
            Cash:   ,
            MarginTrading:   ,
            ShortSelling:
        }
order_lot (str): {
            Common:   ,
            Fixing:   ,
            Odd:     ,
            IntradayOdd:
        }
custom_field (str): memo field
```

**status**

```
id (str): same as the trade_id in SDeal
exchange_ts (int): exchange time
modified_price (float or int): modified price
cancel_quantity (int): cancel quantity
order_quantity (int): order quantity
web_id (str): web id
```

**contract**

```
security_type (str): security type
exchange (str): exchange
code (str): code id
symbol (str): symbol
name (str): name
currency (str): currency
```

#### Deal CallBack

When the matching is successful, the exchange will send a transaction report notification. Successful matching includes partial transactions and complete transactions. You can confirm whether it is the same order from the `id` in the order callback to the `trade_id` in the deal callback.



Copyright © 2025 SinoPac

**Deal Event**

version>=1.0 version<1.0

```
OrderState.StockDeal {
    'trade_id': '9c6ae2eb',
    'seqno': '269866',
    'ordno': 'IN497',
    'exchange_seq': '669915',
    'broker_id': '9A95',
    'account_id': '1234567',
    'action': 'Buy',
    'code': '2890',
    'order_cond': 'Cash',
    'order_lot': 'IntradayOdd',
    'price': 267.5,
    'quantity': 3,
    'web_id': '137',
    'custom_field': 'test',
    'ts': 1673577256.354
}
```

```
OrderState.TFTDeal {
    'trade_id': '9c6ae2eb',
    'seqno': '269866',
    'ordno': 'IN497',
    'exchange_seq': '669915',
    'broker_id': '9A95',
    'account_id': '1234567',
    'action': 'Buy',
    'code': '2890',
    'order_cond': 'Cash',
    'order_lot': 'IntradayOdd',
    'price': 267.5,
    'quantity': 3,
    'web_id': '137',
    'custom_field': 'test',
    'ts': 1673577256.354
}
```

**Deal Callback Info.**

```
trade_id (str): same as the id in StockOrder
seqno (str): sequence number
ordno (str): The first 5 characters is the same as ordno in StockOrder. The last 3 characters represent the deal sequence number.
exchange_seq (str): exchange sequence number
broker_id (str): broker id
account_id (str): account
action (str): {Buy, Sell}
code (str): code id
order_cond (str): {
            Cash:   ,
            MarginTrading:   ,
            ShortSelling:
        }
order_lot (str): {
            Common:   ,
            Fixing:   ,
            Odd:     ,
            IntradayOdd:
        }
price (float or int): deal price
quantity (int): deal quantity
web_id (str): web id
custom_field (str): memo field
ts (int): deal timestamp
```

**Note**

you "may" recieve the deal event sooner than the order event due to message priority in exchange.

#### Handle Callback

If you would like to handle callback info, please refer to Callback.



Copyright © 2025 SinoPac

#### Order CallBack

When the exchange receives the order, it will return the callback. The callback is divided into four parts, including operation, order, status and contract. We will explain in detail below.


Copyright © 2025 SinoPac

**Order Event**

**version>=1.0** **version<1.0**

```
OrderState.FuturesOrder {
    'operation': {
        'op_type': 'New',
        'op_code': '00',
        'op_msg': ''
    },
    'order': {
        'id': 'fcb42a6e',
        'seqno': '585886',
        'ordno': '00',
        'account': {
            'account_type': 'F',
            'person_id': '',
            'broker_id': 'F002000',
            'account_id': '1234567',
            'signed': True
        },
        'action': 'Buy',
        'price': 14000.0,
        'quantity': 1,
        'order_type': 'ROD',
        'price_type': 'LMT',
        'market_type': 'Night',
        'oc_type': 'New',
        'subaccount': '',
        'combo': False
    },
    'status': {
        'id': 'fcb42a6e',
        'exchange_ts': 1673512283.0,
        'modified_price': 0.0,
        'cancel_quantity': 0,
        'order_quantity': 1,
        'web_id': 'Z'
    },
    'contract': {
        'security_type': 'FUT',
        'code': 'TXF',
        'exchange': 'TIM',
        'delivery_month': '202301',
        'delivery_date': '',
        'strike_price': 0.0,
        'option_right': 'Future'
    }
}

OrderState.FOrder {
    'operation': {
        'op_type': 'New',
        'op_code': '00',
        'op_msg': ''
    },
    'order': {
        'id': 'fcb42a6e',
        'seqno': '585886',
        'ordno': '00',
        'account': {
            'account_type': 'F',
            'person_id': '',
            'broker_id': 'F002000',
            'account_id': '1234567',
            'signed': True
        },
        'action': 'Buy',
        'price': 14000.0,
        'quantity': 1,
        'order_type': 'ROD',
        'price_type': 'LMT',
        'market_type': 'Night',
        'oc_type': 'New',
        'subaccount': '',
        'combo': False
    },
    'status': {
        'id': 'fcb42a6e',
        'exchange_ts': 1673512283.0,
        'modified_price': 0.0,
        'cancel_quantity': 0,
        'order_quantity': 1,
        'web_id': 'Z'
    },
    'contract': {
        'security_type': 'FUT',
        'code': 'TXF',
        'exchange': 'TIM',
        'delivery_month': '202301',
        'delivery_date': '',
        'strike_price': 0.0,
        'option_right': 'Future'
    }
}
```



Copyright © 2025 SinoPac

**Order CallBack Info.**

**operation**

```
op_type (str): {
            "New": new order,
            "Cancel": cancel order,
            "UpdatePrice": update price,
            "UpdateQty": update quantity
        }
op_code (str): {"00": success, others: fail}
op_msg (str): error message
```

**order**

```
id (str): same as the trade_id in FuturesDeal
seqno (str): sequence number
ordno (str): order number
account (dict): account info
action (str): {Buy, Sell}
price (float or int): order price
quantity (int): order quantity
order_type (str): the type of order {ROD, IOC, FOK}
price_type (str): pricing type of order {LMT, MKT, MKP}
market_type (str): {Day, Night}
oc_type (str): {New:   , Cover:   , Auto:   }
subaccount (str): subaccount
combo (bool): whether order is combo order
```

**status**

```
id (str): same as the trade_id in FuturesDeal
exchange_ts (int): exchange time
modified_price (float or int): modified price
cancel_quantity (int): cancel quantity
order_quantity (int): irder quantity
web_id (str): web id
```

**contract**

```
security_type (str): security type
code (str): code id
exchange (str): exchange
delivery_month (str): delivery month
delivery_date (str): delivery date
strike_price (float): strike price
option_right (str): {Future, OptionCall, OptionPut}
```

#### Deal CallBack

When the matching is successful, the exchange will send a transaction report notification. Successful matching includes partial transactions and complete transactions. You can confirm whether it is the same order from the `id` in the order callback to the `trade_id` in the deal callback.



Copyright © 2025 SinoPac

**Deal Event**

version>=1.0 version<1.0

```
OrderState.FuturesDeal {
    'trade_id': '4e6df0f6',
    'seqno': '458545',
    'ordno': 'tA0deX1O',
    'exchange_seq': 'j5006396',
    'broker_id': 'F002000',
    'account_id': '1234567',
    'action': 'Sell',
    'code': 'TXO',
    'price': 58.0,
    'quantity': 1,
    'subaccount': '',
    'security_type': 'OPT',
    'delivery_month': '202301',
    'strike_price': 14300.0,
    'option_right': 'OptionPut',
    'market_type': 'Day',
    'combo': False,
    'ts': 1673270852.0
}

OrderState.FDeal {
    'trade_id': '4e6df0f6',
    'seqno': '458545',
    'ordno': 'tA0deX1O',
    'exchange_seq': 'j5006396',
    'broker_id': 'F002000',
    'account_id': '1234567',
    'action': 'Sell',
    'code': 'TXO',
    'price': 58.0,
    'quantity': 1,
    'subaccount': '',
    'security_type': 'OPT',
    'delivery_month': '202301',
    'strike_price': 14300.0,
    'option_right': 'OptionPut',
    'market_type': 'Day',
    'combo': False,
    'ts': 1673270852.0
}
```

**FuturesDeal**

```
trade_id (str): same as the id in FuturesOrder
seqno (str): sequence number
ordno (str): The first 5 characters is the same as ordno in FuturesOrder. The last 3 characters represent the deal sequence number.
exchange_seq (str): exchange sequence number
broker_id (str): broker id
account_id (str): account
action (str): buy/sell
code (str): code
price (float or int): deal price
quantity (int): deal quantity
subaccount (str): subaccount
security_type (str): security type
delivery_month (str): delivery month
strike_price (float): strike price
option_right (str): {Future, OptionCall, OptionPut}
market_type (str): {Day, Night}
ts (int): deal timestamp
```

**Note**

you "may" recieve the deal event sooner than the order event due to message priority in exchange.

#### Handle Callback

If you would like to handle callback info, please refer to Callback.



Copyright © 2025 SinoPac

# 4.6 CallBack

## 4.6.1

Each time you `place_order`, `update_order` or `cancel_order`, by default, you will recieve an order event (or deal event) from exchange. If you don't want recieve both events, please refer to Subscribe Trade. We also provide interface to handle order and deal events. It's extremely helpful if you are implementing your custom trading system.

### Handle Order Callback

You can use `set_order_callback` to handle order/deal events. The example below shows custom order callback function (`order_cb`), which will print `my_order_callback` first and then print the order/deal event.

**Set Order Callback**

```
def order_cb(stat, msg):
    print('my_order_callback')
    print(stat, msg)

api.set_order_callback(order_cb)
```

**Place Order**

version>=1.0 version<1.0

```
contract = api.Contracts.Stocks.TSE.TSE2890
order = api.Order(
    price=16,
    quantity=1,
    action=sj.constant.Action.Buy,
    price_type=sj.constant.StockPriceType.LMT,
    order_type=sj.constant.OrderType.ROD,
    order_lot=sj.constant.StockOrderLot.Common,
    custom_field="test",
    account=api.stock_account
)
trade = api.place_order(contract, order)

contract = api.Contracts.Stocks.TSE.TSE2890
order = api.Order(
    price=16,
    quantity=1,
    action=sj.constant.Action.Buy,
    price_type=sj.constant.TFTStockPriceType.LMT,
    order_type=sj.constant.TFTOrderType.ROD,
    order_lot=sj.constant.TFTStockOrderLot.Common,
    custom_field="test",
    account=api.stock_account
)
trade = api.place_order(contract, order)
```


Copyright © 2025 SinoPac

**ORDER EVENT**



Copyright © 2025 SinoPac

### Order Event

**version>=1.0** **version<1.0**

```
my_order_callback
OrderState.StockOrder {
    'operation': {
        'op_type': 'New',
        'op_code': '00',
        'op_msg': ''
    },
    'order': {
        'id': '97b63e2f',
        'seqno': '267677',
        'ordno': 'IM394',
        'account': {
            'account_type': 'S',
            'person_id': '',
            'broker_id': '9A95',
            'account_id': '1234567',
            'signed': True
        },
        'action': 'Buy',
        'price': 16.0,
        'quantity': 1,
        'order_type': 'ROD',
        'price_type': 'LMT',
        'order_cond': 'Cash',
        'order_lot': 'Common',
        'custom_field': 'test'
    },
    'status': {
        'id': '97b63e2f',
        'exchange_ts': 1673576134.038,
        'modified_price': 0.0,
        'cancel_quantity': 0,
        'order_quantity': 1,
        'web_id': '137'
    },
    'contract': {
        'security_type': 'STK',
        'exchange': 'TSE',
        'code': '2890',
        'symbol': '',
        'name': '',
        'currency': 'TWD'
    }
}
```

```
my_order_callback
OrderState.TFTOrder {
    'operation': {
        'op_type': 'New',
        'op_code': '00',
        'op_msg': ''
    },
    'order': {
        'id': '97b63e2f',
        'seqno': '267677',
        'ordno': 'IM394',
        'account': {
            'account_type': 'S',
            'person_id': '',
            'broker_id': '9A95',
            'account_id': '1234567',
            'signed': True
        },
        'action': 'Buy',
        'price': 16.0,
        'quantity': 1,
        'order_type': 'ROD',
        'price_type': 'LMT',
        'order_cond': 'Cash',
        'order_lot': 'Common',
        'custom_field': 'test'
    },
    'status': {
        'id': '97b63e2f',
        'exchange_ts': 1673576134.038,
        'modified_price': 0.0,
        'cancel_quantity': 0,
        'order_quantity': 1,
        'web_id': '137'
    },
    'contract': {
        'security_type': 'STK',
        'exchange': 'TSE',
        'code': '2890',
        'symbol': '',
        'name': '',
        'currency': 'TWD'
    }
}
```



Copyright © 2025 SinoPac

DEAL EVENT

### Deal Event

version>=1.0 version<1.0

```
my_order_callback
OrderState.StockDeal {
    'trade_id': '9c6ae2eb',
    'seqno': '269866',
    'ordno': 'IN497',
    'exchange_seq': '669915',
    'broker_id': '9A95',
    'account_id': '1234567',
    'action': 'Buy',
    'code': '2890',
    'order_cond': 'Cash',
    'order_lot': 'IntradayOdd',
    'price': 267.5,
    'quantity': 3,
    'web_id': '137',
    'custom_field': 'test',
    'ts': 1673577256.354
}
```

```
my_order_callback
OrderState.TFTDeal {
    'trade_id': '9c6ae2eb',
    'seqno': '269866',
    'ordno': 'IN497',
    'exchange_seq': '669915',
    'broker_id': '9A95',
    'account_id': '1234567',
    'action': 'Buy',
    'code': '2890',
    'order_cond': 'Cash',
    'order_lot': 'IntradayOdd',
    'price': 267.5,
    'quantity': 3,
    'web_id': '137',
    'custom_field': 'test',
    'ts': 1673577256.354
}
```



Copyright © 2025 SinoPac

## 4.6.2

In this api, we use solace as mesh broker. This event mean the status for your client with solace connection situation. If you have no experience with networking, please skip this part, In defalut, we help you reconnect solace broker 50 times without any setting. Best way is keep your network connection alive.

**In**

```
@api.quote.on_event
def event_callback(resp_code: int, event_code: int, info: str, event: str):
    print(f'Event code: {event_code} | Event: {event}')
```

**Out**

```
Event code: 16 | Event: Subscribe or Unsubscribe ok
```

Like the quote callback, your can also set event cllback with two way.

**In**

```
api.quote.set_event_callback?
```

**Out**

```
Signature: api.quote.set_event_callback(func:Callable[[int, int, str, str], NoneType]) -> None
Docstring: <no docstring>
Type:      method
```



Copyright © 2025 SinoPac

**EVENT CODE**



Copyright © 2025 SinoPac

| Event Code | Event Code Enumerator | Description |
|---|---|---|
| 0 | SOLCLIENT_SESSION_EVENT_UP_NOTICE | The Session is established. |
| 1 | SOLCLIENT_SESSION_EVENT_DOWN_ERROR | The Session was established and then went down. |
| 2 | SOLCLIENT_SESSION_EVENT_CONNECT_FAILED_ERROR | The Session attempted to connect but was unsucces |
| 3 | SOLCLIENT_SESSION_EVENT_REJECTED_MSG_ERROR | The appliance rejected a published message. |
| 4 | SOLCLIENT_SESSION_EVENT_SUBSCRIPTION_ERROR | The appliance rejected a subscription (add or remov |
| 5 | SOLCLIENT_SESSION_EVENT_RX_MSG_TOO_BIG_ERROR | The API discarded a received message that exceede Session buffer size. |
| 6 | SOLCLIENT_SESSION_EVENT_ACKNOWLEDGEMENT | The oldest transmitted Persistent/Non-Persistent me that has been acknowledged. |
| 7 | SOLCLIENT_SESSION_EVENT_ASSURED_PUBLISHING_UP | Deprecated -- see notes in solClient_session_startAssuredPublishing.The AD Ha (that is, Guaranteed Delivery handshake) has compl the publisher and Guaranteed messages can be sent |
| 8 | SOLCLIENT_SESSION_EVENT_ASSURED_CONNECT_FAILED | Deprecated -- see notes in solClient_session_startAssuredPublishing.The applia rejected the AD Handshake to start Guaranteed pub Use SOLCLIENT_SESSION_EVENT_ASSURED_DELIVER instead. |
| 8 | SOLCLIENT_SESSION_EVENT_ASSURED_DELIVERY_DOWN | Guaranteed Delivery publishing is not available.The guaranteed delivery capability on the session has be disabled by some action on the appliance. |
| 9 | SOLCLIENT_SESSION_EVENT_TE_UNSUBSCRIBE_ERROR | The Topic Endpoint unsubscribe command failed. |
| 9 | SOLCLIENT_SESSION_EVENT_DTE_UNSUBSCRIBE_ERROR | Deprecated name; SOLCLIENT_SESSION_EVENT_TE_UNSUBSCRIBE_ is preferred. |
| 10 | SOLCLIENT_SESSION_EVENT_TE_UNSUBSCRIBE_OK | The Topic Endpoint unsubscribe completed. |
| 10 | SOLCLIENT_SESSION_EVENT_DTE_UNSUBSCRIBE_OK | Deprecated name; SOLCLIENT_SESSION_EVENT_TE_UNSUBSCRIBE_ preferred. |
| 11 | SOLCLIENT_SESSION_EVENT_CAN_SEND | The send is no longer blocked. |
| 12 | SOLCLIENT_SESSION_EVENT_RECONNECTING_NOTICE | The Session has gone down, and an automatic recon attempt is in progress. |
| 13 | SOLCLIENT_SESSION_EVENT_RECONNECTED_NOTICE | The automatic reconnect of the Session was success the Session was established again. |
| 14 | SOLCLIENT_SESSION_EVENT_PROVISION_ERROR | The endpoint create/delete command failed. |
| 15 | SOLCLIENT_SESSION_EVENT_PROVISION_OK | The endpoint create/delete command completed. |
| 16 | SOLCLIENT_SESSION_EVENT_SUBSCRIPTION_OK | The subscribe or unsubscribe operation has succeed |
| 17 | SOLCLIENT_SESSION_EVENT_VIRTUAL_ROUTER_NAME_CHANGED | The appliance's Virtual Router Name changed durin reconnect operation.This could render existing queu temporary topics invalid. |
| 18 | SOLCLIENT_SESSION_EVENT_MODIFYPROP_OK | The session property modification completed. |
| 19 | SOLCLIENT_SESSION_EVENT_MODIFYPROP_FAIL | The session property modification failed. |


Copyright © 2025 SinoPac

| Event Code | Event Code Enumerator | Description |
| --- | --- | --- |
| 20 | SOLCLIENT_SESSION_EVENT_REPUBLISH_UNACKED_MESSAGES | After successfully reconnecting a disconnected sess SDK received an unknown publisher flow name resp when reconnecting the GD publisher flow. |



Copyright © 2025 SinoPac

# 4.7

## 4.7.1

The feature of account_balance is used to query account balance of stock account and you need to login first.

**In**

```
api.account_balance?
```

**Out**

```
Signature:
    api.account_balance(
        timeout: int = 5000,
        cb: Callable[[shioaji.position.AccountBalance], NoneType] = None,
    )
Docstring: query stock account balance
```

**In**

```
api.account_balance()
```

**Out**

```
AccountBalance(
    status=<FetchStatus.Fetched: 'Fetched'>,
    acc_balance=100000.0,
    date='2023-01-06 13:30:00.000000',
    errmsg=''
)
```

**AccountBalance**

```
status (FetchStatus): fetch status
acc_balance (float): account balance
date (str): query date
errmsg (str): error message
```



Copyright © 2025 SinoPac

## 4.7.2

The feature of margin is used to query margin of futures account and you need to login first.

In

```
api.margin?
```

Out

```
Signature:
api.margin(
    account: shioaji.account.Account = None,
    timeout: int = 5000,
    cb: Callable[[shioaji.position.Margin], NoneType] = None,
) -> shioaji.position.Margin
Docstring: query future account of margin
```

In

```
api.margin(api.futopt_account)
```

Out

```
Margin(
    status=<FetchStatus.Fetched: 'Fetched'>,
    yesterday_balance=6000.0,
    today_balance=6000.0,
    deposit_withdrawal=0.0,
    fee=0.0,
    tax=0.0,
    initial_margin=0.0,
    maintenance_margin=0.0,
    margin_call=0.0,
    risk_indicator=999.0,
    royalty_revenue_expenditure=0.0,
    equity=6000.0,
    equity_amount=6000.0,
    option_openbuy_market_value=0.0,
    option_opensell_market_value=0.0,
    option_open_position=0.0,
    option_settle_profitloss=0.0,
    future_open_position=0.0,
    today_future_open_position=0.0,
    future_settle_profitloss=0.0,
    available_margin=6000.0,
    plus_margin=0.0,
    plus_margin_indicator=0.0,
    security_collateral_amount=0.0,
    order_margin_premium=0.0,
    collateral_amount=0.0
)
```



Copyright © 2025 SinoPac

### Margin

```
status (FetchStatus): fetch status
yesterday_balance (float): balance of yesterday
today_balance (float): balance of today
deposit_withdrawal (float): deposit and withdrawal
fee (float): fee
tax (float): tax
initial_margin (float): margin of origin
maintenance_margin (float):  margin of maintenance
margin_call (float):  margin of call
risk_indicator (float): risk indicator
royalty_revenue_expenditure (float): revenue and expenditure of royalty
equity (float): equity
equity_amount (float): amount of equity
option_openbuy_market_value (float): value of option openbuy market
option_opensell_market_value (float): value of option opensell market
option_open_position (float): profit loss of open option
option_settle_profitloss (float): profit loss of settle option
future_open_position (float): profit loss of open future
today_future_open_position (float): profit loss of today open future
future_settle_profitloss (float): profit loss of settle future
available_margin (float): available margin
plus_margin (float): plus margin
plus_margin_indicator (float): indicator of plus margin
security_collateral_amount (float): amount of security collateral
order_margin_premium (float): order margin and order premium
collateral_amount (float): amount of collateral
```



Copyright © 2025 SinoPac

## 4.7.3

The feature of list_positions is used to query unrealized gain or loss of account and you need to login first.

### Position

In

```
api.list_positions?
```

Out

```
Signature:
api.list_positions(
    account: shioaji.account.Account = None,
    unit: shioaji.constant.Unit = <Unit.Common: 'Common'>,
    timeout: int = 5000,
    cb: Callable[[List[Union[shioaji.position.StockPosition, shioaji.position.FuturePosition]]], NoneType] = None,
) -> List[Union[shioaji.position.StockPosition, shioaji.position.FuturePosition]]
Docstring:
query account of unrealized gain or loss
Args:
    account (:obj:Account):
        choice the account from listing account (Default: stock account)
```

#### STOCKS

#### Common Stocks

In

```
api.list_positions(api.stock_account)
```

Out

```
[
    StockPosition(
        id=0,
        code='2890',
        direction=<Action.Buy: 'Buy'>,
        quantity=12,
        price=2.79,
        last_price=16.95,
        pnl=169171.0,
        yd_quantity=12,
        margin_purchase_amount=0,
        collateral=0,
        short_sale_margin=0,
        interest=0
    )
]
```

To DataFrame

In

```
positions = api.list_positions(api.stock_account)
df = pd.DataFrame(s.__dict__ for s in positions)
df
```



Copyright © 2025 SinoPac

**Out**

| id | code | direction | quantity | price | last_price | pnl | yd_quantity | cond | margi |
|---|---|---|---|---|---|---|---|---|---|
| 0 | 0 | 2890 | Buy | 12 | 2.79 | 16.95 | 169172 | 12 | |

**StockPosition**

```
id (int): position id
code (str): contract id
direction (Action): action
    {Buy, Sell}
quantity (int): quantity
price (float): the average price
last_price (float): last price
pnl (float): unrealized profit
yd_quantity (int): yesterday
cond (StockOrderCond): Default Cash
    {Cash(  ), Netting(    ), MarginTrading(  ),ShortSelling(  ), Emerging(  )}
margin_purchase_amount (int): margin_purchase_amount
collateral (int): collateral
short_sale_margin (int): short_sale_margin
interest (int): interest
```

#### Odd Stocks

The unit is the number of shares.

**In**

```
api.list_positions(
    api.stock_account,
    unit=sj.constant.Unit.Share
)
```

**Out**

```
[
    StockPosition(
        id=0,
        code='2890',
        direction=<Action.Buy: 'Buy'>,
        quantity=10000,
        price=10.1,
        last_price=12.0,
        pnl=1234.0,
        yd_quantity=10000,
        margin_purchase_amount=0,
        collateral=0,
        short_sale_margin=0,
        interest=0
    )
]
```

#### FUTURES AND OPTIONS

`account` is defaulted as a Stock account, and if you want to query the Futures or Options content, you need to bring in the `futopt_account`.

**In**

```
api.list_positions(api.futopt_account)
```



Copyright © 2025 SinoPac

Out

```
[
    FuturePosition(
        id=0,
        code='TX201370J2',
        direction=<Action.Buy: 'Buy'>,
        quantity=3,
        price=131.0000,
        last_price=126.0,
        pnl=-750.00
    )
]
```

To DataFrame

In

```
positions = api.list_positions(api.futopt_account)
df = pd.DataFrame(p.__dict__ for p in positions)
df
```

Out

| | id | code | direction | quantity | price | last_price | pnl |
|---|---|---|---|---|---|---|---|
| 0 | 0 | TXFA3 | Buy | 4 | 14181 | 14375 | 155200 |

FuturePosition

```
id (int): position id
code (str): contract id
direction (Action): action
    {Buy, Sell}
quantity (int): quantity
price (float): the average price
last_price (float): last price
pnl (float): unrealized profit
```

### Position Detail

Using the result obtained from `list_positions`, bring the `id` into `detail_id` to query the details of that position.

STOCKS

In

```
api.list_position_detail?
```

Out

```
Signature:
    api.list_position_detail(
    account: shioaji.account.Account = None,
    detail_id: int = 0,
    timeout: int = 5000,
    cb: Callable[[List[Union[shioaji.position.StockPositionDetail, shioaji.position.    FuturePositionDetail]]], NoneType] = None,
) -> List[Union[shioaji.position.StockPositionDetail, shioaji.position.FuturePositionDetail]]
Docstring:
query account of position detail

Args:
    account (:obj:Account):
        choice the account from listing account (Default: stock account)
    detail_id (int): the id is from Position object, Position is from list_positions
```



Copyright © 2025 SinoPac

In

```
position_detail = api.list_position_detail(api.stock_account, 1)
position_detail
```

Out

```
[
    StockPositionDetail(
        date='2023-02-22',
        code='3558',
        quantity=0,
        price=1461.0,
        last_price=1470.0,
        dseq='WA371',
        direction=<Action.Buy: 'Buy'>,
        pnl=9.0,
        currency=<Currency.TWD: 'TWD'>,
        fee=1.0
    )
]
```

To DataFrame

In

```
df = pd.DataFrame(pnl.__dict__ for pnl in position_detail)
df
```

Out

| date | code | quantity | price | last_price | direction | pnl | currency | fee |
|---|---|---|---|---|---|---|---|---|
| 2023-02-22 | 3558 | 0 | 1461.0 | WA371 | Action.Buy | 11.0 | Currency.TWD | 1.0 |

```
date (str): trade date
code (str): contract id
quantity (int): quantity
price (float): price
last_price (float): last price
dseq (str): detail seqno no
direction (Action): {Buy, Sell}
pnl (decimal): unrealized profit
currency (string): {NTD, USD, HKD, EUR, CAD, BAS}
fee (decimal): fee
cond (StockOrderCond): Default Cash
    {Cash, Netting, MarginTrading,ShortSelling, Emerging}
ex_dividends(int): ex-dividend amount
interest (int): interest
margintrading_amt(int): margin trading amount
collateral (int): collateral
```

**FUTURES AND OPTIONS**

In

```
position_detail = api.list_position_detail(api.futopt_account, 0)
position_detail
```



Copyright © 2025 SinoPac

**Out**

```
[
    FuturePositionDetail(
        date='2023-02-14',
        code='MXFC3',
        quantity=1,
        price=15611.0,
        last_price=15541.0,
        dseq='tA0n8',
        direction=<Action.Buy: 'Buy'>,
        pnl=-3500.0,
        currency=<Currency.TWD: 'TWD'>,
        entry_quantity=1
    )
]
```

To DataFrame

**In**

```
df = pd.DataFrame(pnl.__dict__ for pnl in position_detail)
df
```

**Out**

| date | code | quantity | price | last_price | dseq | direction | pnl | curr |
|---|---|---|---|---|---|---|---|---|
| 2023-02-14 | MXFC3 | 1 | 15611.0 | 15541.0 | tA0n8 | Action.Buy | -3500.0 | Currency. |

```
code (str): contract id
date (str): trade date
quantity (int): quantity
price (float): price
last_price (float): last price
dseq (str): detail seqno no
direction (Action): {Buy, Sell}
pnl (float): unrealized profit
currency (str): {NTD, USD, HKD, EUR, CAD, BAS}
fee (float or int): fee
entry_quantity(int): entry quantity
```



Copyright © 2025 SinoPac

## 4.7.4

You need to login first.

### Profit Loss

The feature of list_profit_loss is used to query realized profit loss of account.

In

```
api.list_profit_loss?
```

Out

```
Signature:
    api.list_profit_loss(
        account: shioaji.account.Account = None,
        begin_date: str = '',
        end_date: str = '',
        unit: shioaji.constant.Unit = <Unit.Common: 'Common'>,
        timeout: int = 5000,
        cb: Callable[[List[shioaji.position.ProfitLoss]], NoneType] = None,
    ) -> List[shioaji.position.ProfitLoss]
Docstring:
    query account of profit loss

    Args:
        account (:obj:Account):
            choice the account from listing account (Default: stock account)
        begin_date (str): the start date of query profit loss (Default: today)
        end_date (str): the end date of query profit loss (Default: today)
```

Enter the time interval you want to query. `begin_date` is the start time, and `end_date` is the end time. `unit` is the quantity unit, where `Common` represents whole shares and `Share` represents fractional shares.

In

```
profitloss = api.list_profit_loss(api.stock_account,'2020-05-05','2020-05-30')
profitloss
```

Out

```
[
    StockProfitLoss(
        id=0,
        code='2890',
        seqno='14816',
        dseq='ID111',
        quantity=1,
        price=10.1,
        pnl=1234.0,
        pr_ratio=0.1237,
        cond='Cash',
        date='2020-05-22'
    )
]
```

To DataFrame

In

```
df = pd.DataFrame(pnl.__dict__ for pnl in profitloss)
df
```



Copyright © 2025 SinoPac

Out

| id | code | cond | date | pnl | pr_ratio | price | quantity | seqno |
|---|---|---|---|---|---|---|---|---|
| 0 | 2890 | StockOrderCond.Cash | 2020-05-22 | 1000.0 | 0.1237 | 10.1 | 1 | 14816 |

StockProfitLoss

```
id (int): use to find detail
code (str): contract id
seqno (str): seqno no
dseq (str): seqno no
quantity (int): quantity
price (float): price
pnl (float): profit and loss
pr_ratio (float): profit rate
cond (StockOrderCond): {Cash, Netting, MarginTrading, ShortSelling}
date (str): trade date
```

FutureProfitLoss

```
id (int): use to find detail
code (str): contract id
quantity (int): quantity
pnl (float): profit and loss
date (str): trade date
entry_price (int): entry price
cover_price (int): cover price
tax (int): tax
fee (int): transaction fee
```

### Profit Loss Detail

The feature of list_profit_loss_detail is used to query profit loss detail of account. `unit` is the quantity unit, where `Common` represents whole shares and `Share` represents fractional shares.

In

```
api.list_profit_loss_detail?
```

Out

```
Signature:
api.list_profit_loss_detail(
    account: shioaji.account.Account = None,
    detail_id: int = 0,
    unit: shioaji.constant.Unit = <Unit.Common: 'Common'>,
    timeout: int = 5000,
    cb: Callable[[List[Union[shioaji.position.StockProfitDetail, shioaji.position.FutureProfitDetail]]], NoneType] = None,
) -> List[Union[shioaji.position.StockProfitDetail, shioaji.position.FutureProfitDetail]]
Docstring:
query account of profit loss detail

Args:
    account (:obj:Account):
        choice the account from listing account (Default: stock account)
    detail_id (int): the id is from ProfitLoss object, ProfitLoss is from list_profit_loss
```

In

```
profitloss_detail = api.list_profit_loss_detail(api.stock_account, 2)
profitloss_detail
```



Copyright © 2025 SinoPac

**Out**

```
[
    StockProfitDetail(
        date='2020-01-01',
        code='2890',
        quantity=1,
        dseq='IX000',
        fee=20,
        tax=0,
        currency='TWD',
        price=10.8,
        cost=10820,
        rep_margintrading_amt=0,
        rep_collateral=0,
        rep_margin=0,
        shortselling_fee=0,
        ex_dividend_amt=0,
        interest=0
    )
]
```

To DataFrame

**In**

```
df = pd.DataFrame(pnl.__dict__ for pnl in profitloss_detail)
df
```

**Out**

| date | code | quantity | dseq | fee | tax | currency | price | cost | rep_margint |
|---|---|---|---|---|---|---|---|---|---|
| 2020-01-01 | 2890 | 1 | IX000 | 20 | 0 | TWD | 10.8 | 10820 | |

**StockProfitDetail**

```
date (str): trade date
code (str): contract id
quantity (int): quantity
dseq (str): detail seqno no
fee (int): fee
tax (int): trading tax
currency (str): {NTD, USD, HKD, EUR, CAD, BAS}
price (float): price
cost (int): cost of price
rep_margintrading_amt (int): repay amount of margin trading
rep_collateral (int): repay collateral
rep_margin (int): repay margin
shortselling_fee (int): fee of short selling
ex_dividend_amt: ex-dividend amount
interest (int): interest
trade_type (TradeType): {Common, DayTrade}
cond (StockOrderCond): {Cash, Netting, MarginTrading, ShortSelling}
```

**FutureProfitDetail**

```
date (str): trade date
code (str): contract id
quantity (int): quantity
dseq (str): detail seqno no
fee (int): fee
tax (int): trading tax
currency (str): {NTD, USD, HKD, EUR, CAD, BAS}
direction (Action): {Buy, Sell}
entry_price (int): entry price
cover_price (int): cover price
pnl (int): profit and loss
```



Copyright © 2025 SinoPac

### Profit Loss Summary

The feature of list_profit_loss_summary is used to query summary of profit loss for a period of time.

In

```
api.list_profit_loss_summary?
```

Out

```
Signature:
api.list_profit_loss_summary(
    account: shioaji.account.Account = None,
    begin_date: str = '',
    end_date: str = '',
    timeout: int = 5000,
    cb: Callable[[ProfitLossSummaryTotal], NoneType] = None,
) -> ProfitLossSummaryTotal
Docstring:
query summary profit loss of a period time

Args:
    account (:obj:Account):
        choice the account from listing account (Default: stock account)
    begin_date (str): the start date of query profit loss (Default: today)
    end_date (str): the end date of query profit loss (Default: today)
```

Enter the time interval you want to query. `begin_date` is the start time, and `end_date` is the end time.

In

```
profitloss_summary = api.list_profit_loss_summary(api.stock_account,'2020-05-05','2020-05-30')
profitloss_summary
```

Out

```
ProfitLossSummaryTotal(
    status=<FetchStatus.Fetched: 'Fetched'>,
    profitloss_summary=[
        StockProfitLossSummary(
            code='2890',
            quantity=2000,
            entry_price=17,
            cover_price=10,
            pnl=-11585.0,
            currency='NTD',
            entry_cost=34550,
            cover_cost=21600,
            buy_cost=33112,
            sell_cost=21527,
            pr_ratio=-34.99
        )
    ],
    total=ProfitLossTotal(
        quantity=2000,
        buy_cost=33112,
        sell_cost=21527,
        pnl=-11585.0,
        pr_ratio=-34.99
    )
)
```

To DataFrame

In

```
df = pd.DataFrame(pnl.__dict__ for pnl in profitloss_summary.profitloss_summary)
df
```



Copyright © 2025 SinoPac

**Out**

| code | quantity | entry_price | cover_price | pnl | currency | entry_cost | cover_cost | bu |
|---|---|---|---|---|---|---|---|---|
| 2890 | 2000 | 17 | 10 | -11585 | NTD | 34550 | 21600 | |

**StockProfitLossSummary**

```
code (str): contract id
quantity (int): quantity
entry_price (int): price of entry
cover_price (int): price of cover
pnl (float): profit and loss
currency (str): currency
entry_cost (int): cost of entry
cover_cost (int): cost of cover
buy_cost (int): cost of buy
sell_cost (int): cost of sell
pr_ratio (float): profit rate
cond (StockOrderCond): {Cash, Netting, MarginTrading, ShortSelling}
```

**FutureProfitLossSummary**

```
code (str): contract id
quantity (int): quantity
entry_price (int): price of entry
cover_price (int): price of cover
pnl (float): profit and loss
currency (str): currency
direction (Action): {Buy, Sell}
tax (int): tax
fee (int): fee
```



Copyright © 2025 SinoPac

## 4.7.5

The feature of settlements is used to query settlements of stock account and you need to login first.

### Settlements

In

```
api.settlements?
```

Out

```
Signature:
api.settlements(
    account: shioaji.account.Account = None,
    timeout: int = 5000,
    cb: Callable[[List[shioaji.position.SettlementV1]], NoneType] = None,
) -> List[shioaji.position.SettlementV1]
Docstring: query stock account of settlements
```

In

```
settlements = api.settlements(api.stock_account)
settlements
```

Out

```
[
    SettlementV1(date=datetime.date(2022, 10, 13), amount=0.0, T=0),
    SettlementV1(date=datetime.date(2022, 10, 14), amount=0.0, T=1),
    SettlementV1(date=datetime.date(2022, 10, 17), amount=0.0, T=2)
]
```

To DataFrame

In

```
df = pd.DataFrame([s.__dict__ for s in settlements]).set_index("T")
df
```

Out

| T | date | amount |
|---|---|---|
| 0 | 2022-10-13 | 0 |
| 1 | 2022-10-14 | 0 |
| 2 | 2022-10-17 | 0 |

SettlementV1

```
date (datetime.date): date of Tday
amount (float): settlement amount
T (int): Tday
```



Copyright © 2025 SinoPac

# 4.8

Users can first familiarize themselves with the API services in the simulation mode, which can avoid the loss of property caused by operational errors in the production environment.

**Simulation**

```
import shioaji as sj
api = sj.Shioaji(simulation=True)
```

## 4.8.1 Available APIs

**Data**

1. quote.subscribe
2. quote.unsubscribe
3. ticks
4. kbars
5. snapshots
6. short_stock_sources
7. credit_enquires
8. scanners

**Order**

1. place_order
2. update_order
3. cancel_order
4. update_status
5. list_trades

**Account**

1. list_positions
2. list_profit_loss


Copyright © 2025 SinoPac

# 4.9

## 4.9.1

Shioaji provides quote-binding mode which you can store tick/bidask in queue, push them to redis, or submit a stop order inside quote callback function. We show examples to make you more understand how to use quote-binding mode.

### Examples

#### BIND QUOTE TO MESSAGE QUEUE

**In: pythonic way by using decorator**

```
from collections import defaultdict, deque
from shioaji import TickFOPv1, Exchange

# set context
msg_queue = defaultdict(deque)
api.set_context(msg_queue)

# In order to use context, set bind=True
@api.on_tick_fop_v1(bind=True)
def quote_callback(self, exchange:Exchange, tick:TickFOPv1):
    # append quote to message queue
    self[tick.code].append(tick)

# subscribe
api.quote.subscribe(
    api.Contracts.Futures.TXF['TXF202107'],
    quote_type = sj.constant.QuoteType.Tick,
    version = sj.constant.QuoteVersion.v1
)
```

**In: traditional way**

```
def quote_callback(self, exchange:Exchange, tick:TickFOPv1):
    # append tick to context
    self[tick.code].append(tick)

# In order to use context, set bind=True
api.quote.set_on_tick_fop_v1_callback(quote_callback, bind=True)
```

**Out**

```
# after subscribe and wait for a few seconds ...
# print(msg_queue)
defaultdict(collections.deque,
    {
        'TXFG1': [
            Tick(code='TXFG1', datetime=datetime.datetime(2021, 7, 5, 10, 0, 21, 220000), open=Decimal('17755'), underlying_price=Decimal('17851.88'),
bid_side_total_vol=34824, ask_side_total_vol=36212, avg_price=Decimal('17837.053112'), close=Decimal('17833'), high=Decimal('17900'), low=Decimal('17742'),
amount=Decimal('17833'), total_amount=Decimal('981323314'), volume=1, total_volume=55016, tick_type=1, chg_type=2, price_chg=Decimal('184'),
pct_chg=Decimal('1.042552'), simtrade=0),
            Tick(code='TXFG1', datetime=datetime.datetime(2021, 7, 5, 10, 0, 21, 781000), open=Decimal('17755'), underlying_price=Decimal('17851.88'),
bid_side_total_vol=34825, ask_side_total_vol=36213, avg_price=Decimal('17837.053056'), close=Decimal('17834'), high=Decimal('17900'), low=Decimal('17742'),
amount=Decimal('17834'), total_amount=Decimal('981341148'), volume=1, total_volume=55017, tick_type=1, chg_type=2, price_chg=Decimal('185'),
pct_chg=Decimal('1.048218'), simtrade=0)
        ]
    }
)
```

#### PUSH QUOTE TO REDIS STREAM

Before start, please install redis first. Below example shows how to push quote massages to redis stream.



Copyright © 2025 SinoPac

In

```
import redis
import json
from shioaji import TickFOPv1, Exchange

# redis setting
r = redis.Redis(host='localhost', port=6379, db=0, decode_responses=True)

# set up context
api.set_context(r)

# In order to use context, set bind=True
@api.on_tick_fop_v1(bind=True)
def quote_callback(self, exchange:Exchange, tick:TickFOPv1):
    # push them to redis stream
    channel = 'Q:' + tick.code # ='Q:TXFG1' in this example
    self.xadd(channel, {'tick':json.dumps(tick.to_dict(raw=True))})
```

Out

```
# after subscribe and wait for a few seconds ...
# r.xread({'Q:TXFG1':'0-0'})
[
    ['Q:TXFG1',
        [
            ('1625454940107-0',
                {'tick':
                    '{"code": "TXFG1", "datetime": "2021-07-05T11:15:49.066000", "open": "17755", "underlying_price": "17904.03", "bid_side_total_vol": 49698,
"ask_side_total_vol": 51490, "avg_price": "17851.312322", "close": "17889", "high": "17918", "low": "17742", "amount": "268335", "total_amount": "1399310819",
"volume": 15, "total_volume": 78387, "tick_type": 2, "chg_type": 2, "price_chg": "240", "pct_chg": "1.35985", "simtrade": 0}'
                }
            ),
            ('1625454941854-0',
                {'tick':
                    '{"code": "TXFG1", "datetime": "2021-07-05T11:15:50.815000", "open": "17755", "underlying_price": "17902.58", "bid_side_total_vol": 49702,
"ask_side_total_vol": 51478, "avg_price": "17851.313258", "close": "17888", "high": "17918", "low": "17742", "amount": "35776", "total_amount": "1399346595",
"volume": 2, "total_volume": 78389, "tick_type": 2, "chg_type": 2, "price_chg": "239", "pct_chg": "1.354184", "simtrade": 0}'
                }
            )
        ]
    ]
]


# parse redis stream
# [json.loads(x[-1]['tick']) for x in r.xread({'Q:TXFG1':'0-0'})[0][-1]]
[
    {
        'code': 'TXFG1',
        'datetime': '2021-07-05T11:15:49.066000',
        'open': '17755',
        'underlying_price': '17904.03',
        'bid_side_total_vol': 49698,
        'ask_side_total_vol': 51490,
        'avg_price': '17851.312322',
        'close': '17889',
        'high': '17918',
        'low': '17742',
        'amount': '268335',
        'total_amount': '1399310819',
        'volume': 15,
        'total_volume': 78387,
        'tick_type': 2,
        'chg_type': 2,
        'price_chg': '240',
        'pct_chg': '1.35985',
        'simtrade': 0
    },
    {
        'code': 'TXFG1',
        'datetime': '2021-07-05T11:15:50.815000',
        'open': '17755',
        'underlying_price': '17902.58',
        'bid_side_total_vol': 49702,
        'ask_side_total_vol': 51478,
        'avg_price': '17851.313258',
        'close': '17888',
        'high': '17918',
        'low': '17742',
        'amount': '35776',
        'total_amount': '1399346595',
        'volume': 2,
        'total_volume': 78389,
        'tick_type': 2,
        'chg_type': 2,
        'price_chg': '239',
        'pct_chg': '1.354184',
        'simtrade': 0
    },
]
```



Copyright © 2025 SinoPac

#### STOP ORDER IMPLEMENTATION

A stop order is an order to buy or sell a security when its price moves past a particular point, ensuring a higher probability of achieving a predetermined entry or exit price, limiting the investor's loss, or locking in a profit. Once the price crosses the predefined entry/exit point, the stop order becomes a market order.

We provide an example of stop order below. **Please use at your own risk.**


Copyright © 2025 SinoPac

**Example: stop order**

```
import time
from typing import Union

import shioaji as sj

class StopOrderExcecutor:
    def __init__(self, api: sj.Shioaji) -> None:
        self.api = api
        self._stop_orders = {}

    def on_quote(
        self, quote: Union[sj.BidAskFOPv1, sj.BidAskSTKv1, sj.TickFOPv1, sj.TickSTKv1]
    ) -> None:
        code = quote.code
        if code in self._stop_orders:
            for stop_order in self._stop_orders[code]:
                if stop_order['executed']:
                    continue
                if hasattr(quote, "ask_price"):
                    price = 0.5 * float(
                        quote.bid_price[0] + quote.ask_price[0]
                    )  # mid price
                else:
                    price = float(quote.close)  # Tick

                is_execute = False
                if stop_order["stop_price"] >= stop_order["ref_price"]:
                    if price >= stop_order["stop_price"]:
                        is_execute = True

                elif stop_order["stop_price"] < stop_order["ref_price"]:
                    if price <= stop_order["stop_price"]:
                        is_execute = True

                if is_execute:
                    self.api.place_order(stop_order["contract"], stop_order["pending_order"])
                    stop_order['executed'] = True
                    stop_order['ts_executed'] = time.time()
                    print(f"execute stop order: {stop_order}")
                else:
                    self._stop_orders[code]

    def add_stop_order(
        self,
        contract: sj.contracts.Contract,
        stop_price: float,
        order: sj.order.Order,
    ) -> None:
        code = contract.code
        snap = self.api.snapshots([contract])[0]
        # use mid price as current price to avoid illiquidity
        ref_price = 0.5 * (snap.buy_price + snap.sell_price)
        stop_order = {
            "code": contract.code,
            "stop_price": stop_price,
            "ref_price": ref_price,
            "contract": contract,
            "pending_order": order,
            "ts_create": time.time(),
            "executed": False,
            "ts_executed": 0.0
        }

        if code not in self._stop_orders:
            self._stop_orders[code] = []
        self._stop_orders[code].append(stop_order)
        print(f"add stop order: {stop_order}")

    def get_stop_orders(self) -> dict:
        return self._stop_orders

    def cancel_stop_order_by_code(self, code: str) -> None:
        if code in self._stop_orders:
            _ = self._stop_orders.pop(code)

    def cancel_stop_order(self, stop_order: dict) -> None:
        code = stop_order["code"]
        if code in self._stop_orders:
            self._stop_orders[code].remove(stop_order)
            if len(self._stop_orders[code]) == 0:
                self._stop_orders.pop(code)

    def cancel_all_stop_orders(self) -> None:
        self._stop_orders.clear()
```

- We use mid price of snapshots as our reference price to differentiate the direction of stop order.

Basically, order will be pending at your computer. The order won't be submitted to exchange until close/mid price hit the stop price. Below example shows how to submit a stop-limit order.



Copyright © 2025 SinoPac

**Set up a stop order**

```
# shioaji order
contract = api.Contracts.Futures.TXF['TXF202301']
order = api.Order(
    action='Buy',
    price=14800,
    quantity=1,
    price_type='LMT',
    order_type='ROD',
    octype=sj.constant.FuturesOCType.Auto,
    account=api.futopt_account
)

# Stop Order Excecutor
soe = StopOrderExcecutor(api)
soe.add_stop_order(contract=contract, stop_price=14805, order=order)
```

**Out**

```
add stop order: {
    'code': 'TXFA3',
    'stop_price': 14805,
    'ref_price': 14790,
    'contract': Future(
        code='TXFA3',
        symbol='TXF202301',
        name='    01',
        category='TXF',
        delivery_month='202301',
        delivery_date='2023/01/30',
        underlying_kind='I',
        unit=1,
        limit_up=16241.0,
        limit_down=13289.0,
        reference=14765.0,
        update_date='2023/01/10'
    ),
    'pending_order': Order(
        action=<Action.Buy: 'Buy'>,
        price=14800,
        quantity=1,
        account=FutureAccount(person_id='A123456789', broker_id='F002000', account_id='1234567', signed=True, username='PAIUSER'),
        price_type=<StockPriceType.LMT: 'LMT'>,
        order_type=<OrderType.ROD: 'ROD'>
    ),
    'ts_create': 1673329115.1056178,
    'executed': False,
    'ts_executed': 0.0
}
```

- Stop-Market Order: `price_type = 'MKT'`

Finally, we bind `StopOrderExcecutor` to quote callback function. Note that you have to subscribe quote, so that stop order will be executed.

**Set up context and callback function**

```
from shioaji import TickFOPv1, Exchange

# set up context
api.set_context(soe)

# In order to use context, set bind=True
@api.on_tick_fop_v1(bind=True)
def quote_callback(self, exchange:Exchange, tick:TickFOPv1):
    # pass tick object to Stop Order Excecutor
    self.on_quote(tick)

# subscribe
api.quote.subscribe(
    contract,
    quote_type = sj.constant.QuoteType.Tick,
    version = sj.constant.QuoteVersion.v1
)
```



Copyright © 2025 SinoPac

**Out: Once close/mid price hit stop price**

```
execute stop order: {
    'code': 'TXFA3',
    'stop_price': 14805,
    'ref_price': 14790,
    'contract': Future(
        code='TXFA3',
        symbol='TXF202301',
        name='    01',
        category='TXF',
        delivery_month='202301',
        delivery_date='2023/01/30',
        underlying_kind='I',
        unit=1,
        limit_up=16241.0,
        limit_down=13289.0,
        reference=14765.0,
        update_date='2023/01/10'
    ),
    'pending_order': Order(
        action=<Action.Buy: 'Buy'>,
        price=14800,
        quantity=1,
        account=FutureAccount(person_id='A123456789', broker_id='F002000', account_id='1234567', signed=True, username='PAIUSER'),
        price_type=<StockPriceType.LMT: 'LMT'>,
        order_type=<OrderType.ROD: 'ROD'>
    ),
    'ts_create': 1673329115.1056178,
    'executed': True,
    'ts_executed': 1673329161.3224185
}
```



Copyright © 2025 SinoPac

## 4.9.2

Blocking is a pattern where a function must wait for something to complete. Every function is waiting, whether it is doing I/O or doing CPU tasks. For example, if the function tries to get data from the database, it needs to stop and wait for the return result, and then continue processing the next task after receiving the return result. In contrast, non-blocking mode does not wait for operations to complete. Non-blocking mode is useful if you are trying to send batch operation in a short period of time. We provide the following examples to give you a better understanding of the difference.

To switch blocking/non-blocking mode use parameter `timeout`. Set the API parameter `timeout` to `0` for non-blocking mode. The default value of `timeout` is 5000 (milliseconds), which means the function waits for up to 5 seconds.

#### NON-BLOCKING PLACE ORDER

Set `timeout = 0` in `place_order` function.

In

```
contract = api.Contracts.Futures.TXF['TXF202301']
order = api.Order(
    action=sj.constant.Action.Sell,
    price=14000,
    quantity=1,
    price_type=sj.constant.FuturesPriceType.LMT,
    order_type=sj.constant.OrderType.ROD,
    octype=sj.constant.FuturesOCType.Auto,
    account=api.futopt_account
)
trade = api.place_order(contract, order, timeout=0)
trade
```

Out

```
Trade(
    contract=Future(
        code='TXFA3',
        symbol='TXF202301',
        name='    01',
        category='TXF',
        delivery_month='202301',
        delivery_date='2023/01/30',
        underlying_kind='I',
        unit=1,
        limit_up=16241.0,
        limit_down=13289.0,
        reference=14765.0,
        update_date='2023/01/10'
    ),
    order=Order(
        action=<Action.Sell: 'Sell'>,
        price=14000,
        quantity=1,
        account=FutureAccount(
            person_id='F123456789',
            broker_id='F002000',
            account_id='1234567',
            signed=True,
            username='PAPIUSER'
        ),
        price_type=<StockPriceType.LMT: 'LMT'>,
        order_type=<OrderType.ROD: 'ROD'>
    ),
    status=OrderStatus(status=<Status.Inactive: 'Inactive'>)
)
```

The `Trade` object obtained in non-blocking mode will lack some information because the order is still in transit and has not been sent to the exchange. There are no `id` and `seqno` in the `Order` object, `id`, `status_code`, `order_datetime` and `deals` are missing in the `OrderStatus` object, and `status` is displayed as `Inactive`. In the non-blocking mode, there are two ways to obtain the above-mentioned information: `` `order event callback` `` and `non-blocking place order callback`.



Copyright © 2025 SinoPac

**Order event callback**

**Out**

```
OrderState.FuturesOrder {
    'operation': {
        'op_type': 'New',
        'op_code': '00',
        'op_msg': ''
    },
    'order': {
        'id': 'de616839',
        'seqno': '500009',
        'ordno': '000009',
        'action': 'Sell',
        'price': 14000,
        'quantity': 1,
        'order_type': 'ROD',
        'price_type': 'LMT',
        'oc_type': 'Auto',
        'custom_field': ''
    },
    'status': {
        'id': 'de616839',
        'exchange_ts': 1673334371.492948,
        'order_quantity': 1,
        'modified_price': 0,
        'cancel_quantity': 0,
        'web_id': 'Z'
    },
    'contract': {
        'security_type': 'FUT',
        'exchange': 'TAIFEX',
        'code': 'TXFA3'
    }
}
```

**Non-blocking place order callback**

**In**

```
from shioaji.order import Trade

def non_blocking_cb(trade:Trade):
    print('__my_callback__')
    print(trade)

trade = api.place_order(
    contract,
    order,
    timeout=0,
    cb=non_blocking_cb # only work in non-blocking mode
)
```



Copyright © 2025 SinoPac

**Out: place order callback**

```
__my_callback__
contract=Future(
    code='TXFA3',
    symbol='TXF202301',
    name='    01',
    category='TXF',
    delivery_month='202301',
    delivery_date='2023/01/30',
    underlying_kind='I',
    unit=1,
    limit_up=16241.0,
    limit_down=13289.0,
    reference=14765.0,
    update_date='2023/01/10'
),
order=Order(
    action=<Action.Sell: 'Sell'>,
    price=14000,
    quantity=1,
    id='40fd85d6',
    seqno='958433',
    ordno='kY01g',
    account=FutureAccount(
        person_id='F123456789',
        broker_id='F002000',
        account_id='1234567',
        signed=True,
        username='PAPIUSER'
    ),
    price_type=<StockPriceType.LMT: 'LMT'>,
    order_type=<OrderType.ROD: 'ROD'>
),
status=OrderStatus(
    id='40fd85d6',
    status=<Status.Submitted: 'Submitted'>,
    status_code='    ',
    order_datetime=datetime.datetime(2023, 01, 10, 15, 14, 32),
    deals=[]
)
```

#### COMPARE BOTH MODES

In non-wait mode, executing `place_order` takes about 0.01 seconds, which is 12 times faster than the execution time in blocking mode. Although it is more efficient to place order in the non-blocking mode, the order will not take effect until the exchange receives the order.

**contract and order**

```
contract = api.Contracts.Futures.TXF['TXF202301']
order = api.Order(
    action='Sell',
    price=14000,
    quantity=1,
    price_type='LMT',
    order_type='ROD',
    octype=sj.constant.FuturesOCType.Auto,
    account=api.futopt_account
)
```

**Blocking**

```
start_time = time.time()
api.place_order(contract, order) # block and wait for the order response
print(time.time() - start_time)
# 0.136578369140625 <- may be different
```

**Non-Blocking**

```
start_time = time.time()
api.place_order(contract, order, timeout=0) # non-block, the order is in transmition (inactive).
print(time.time() - start_time)
# 0.011670351028442383 <- may be different
```



Copyright © 2025 SinoPac

**Non-Blocking mode Supported Function**

```
- place_order
- update_order
- cancel_order
- update_status
- list_positions
- list_position_detail
- list_profit_loss
- list_profit_loss_detail
- list_profit_loss_summary
- settlements
- margin
- ticks
- kbars
```


Copyright © 2025 SinoPac

## 4.9.3

### Touch Price Order

Here is a simple example that how to build your price monitor and when price touches the condition will place the order.

```
from pydantic import BaseModel

class TouchOrderCond(BaseModel):
    contract: Contract
    order: Order
    order: Order
    touch_price: float

class TouchOrder:
   def __init__(self, api: sj.Shioaji, condition: TouchOrderCond
    ):
       self.flag = False
       self.api = api
       self.order = condition.order
       self.contract = condition.contract
       self.touch_price = condition.touch_price
       self.api.quote.subscribe(self.contract)
       self.api.quote.set_quote_callback(self.touch)

   def touch(self, topic, quote):
       price = quote["Close"][0]
       if price == self.touch_price and not self.flag:
           self.flag = True
           self.api.place_order(self.contract, self.order)
           self.api.quote.unsubscribe(self.contract)
```

Complete TouchPrice Order Extention can be found here.



Copyright © 2025 SinoPac

## 4.9.4

the whole project code can be found in sj-trading, the whole example jupyter notebook can be found in quote_manager_usage.

this project is created by using `uv`, if you are not familiar with how to use `uv` to create a project and manage dependencies, it is recommended to learn from the environment setup chapter.

before start writing the quote manager, we will use the Polars package to process the quote data, so we need to add it to the project dependencies, at the same time, this tutorial will have an example of how to use Polars to quickly calculate technical indicators for multiple commodities, so we also need to add the polars_talib package to the project dependencies.

**add Polars dependencies**

```
uv add polars polars_talib
```

if you are not familiar with Polars, you can refer to the Polars official documentation to learn how to use it.

polars_talib is a Polars extension package that provides the complete functionality of the ta-lib library in the polars expression version, allowing us to easily calculate technical indicators using Polars. It is developed by the shioaji author, and detailed usage can be found in polars_ta_extension.

Polars is an efficient DataFrame package that is suitable for processing large amounts of data and can use multiple cores without any additional configuration. In this example, we can see how to use the Shioaji quote manager to obtain quote data, and use Polars for parallel computation, while converting the ticks of the commodity into K lines, and performing parallel multi-commodity technical indicator calculations.

**add quote.py**

add `quote.py` file in `src/sj_trading/`, and add the following code

```python
import shioaji as sj
from typing import List

class QuoteManager:
    def __init__(self, api: sj.Shioaji):
        self.api = api
        self.api.quote.set_on_tick_stk_v1_callback(self.on_stk_v1_tick_handler)
        self.api.quote.set_on_tick_fop_v1_callback(self.on_fop_v1_tick_handler)
        self.ticks_stk_v1: List[sj.TickSTKv1] = []
        self.ticks_fop_v1: List[sj.TickFOPv1] = []

    def on_stk_v1_tick_handler(self, _exchange: sj.Exchange, tick: sj.TickSTKv1):
        self.ticks_stk_v1.append(tick)

    def on_fop_v1_tick_handler(self, _exchange: sj.Exchange, tick: sj.TickFOPv1):
        self.ticks_fop_v1.append(tick)
```

this part is relatively simple, let the handle func of receiving the quote data do as little as possible, we define a `QuoteManager` class, and register two callback functions in the initialization, respectively `on_stk_v1_tick_handler` and `on_fop_v1_tick_handler`, these two functions will be called when receiving the quote data, and the quote data will be stored in `ticks_stk_v1` and `ticks_fop_v1`.


Copyright © 2025 SinoPac

**add `QuoteManager` subscribe and unsubscribe methods**

```
def __init__(self, api: sj.Shioaji):
    # skip
    self.subscribed_stk_tick: Set[str] = set()

def subscribe_stk_tick(self, codes: List[str], recover: bool = False):
    for code in codes:
        contract = self.api.Contracts.Stocks[code]
        if contract is not None and code not in self.subscribed_stk_tick:
            self.api.quote.subscribe(contract, "tick")
            self.subscribed_stk_tick.add(code)

def unsubscribe_stk_tick(self, codes: List[str]):
    for code in codes:
        contract = self.api.Contracts.Stocks[code]
        if contract is not None and code in self.subscribed_stk_tick:
            self.api.quote.unsubscribe(contract, "tick")
            self.subscribed_stk_tick.remove(code)

def unsubscribe_all_stk_tick(self):
    for code in self.subscribed_stk_tick:
        contract = self.api.Contracts.Stocks[code]
        if contract is not None:
            self.api.quote.unsubscribe(contract, "tick")
    self.subscribed_stk_tick.clear()
```

in the above code, we have added the `subscribe_stk_tick` method, this method will add the commodity codes in the incoming commodity code list to the `subscribed_stk_tick`, and call the `subscribe` method of Shioaji to subscribe to the market, `subscribed_stk_tick` is a `Set`, used to store the commodity codes that have been subscribed to avoid duplicate subscriptions and facilitate subsequent unsubscribing all subscribed commodities.

**add `QuoteManager` get ticks method**

```
def __init__(self, api: sj.Shioaji):
    # skip
    self.df_stk: pl.DataFrame = pl.DataFrame(
        [],
        schema=[
            ("datetime", pl.Datetime),
            ("code", pl.Utf8),
            ("price", pl.Float64),
            ("volume", pl.Int64),
            ("tick_type", pl.Int8),
        ],
    )

def get_df_stk(self) -> pl.DataFrame:
    poped_ticks, self.ticks_stk_v1 = self.ticks_stk_v1, []
    if poped_ticks:
        df = pl.DataFrame([tick.to_dict() for tick in poped_ticks]).select(
            pl.col("datetime", "code"),
            pl.col("close").cast(pl.Float64).alias("price"),
            pl.col("volume").cast(pl.Int64),
            pl.col("tick_type").cast(pl.Int8),
        )
        self.df_stk = self.df_stk.vstack(df)
    return self.df_stk
```

in `__init__` we define a `df_stk` Polars DataFrame, used to store all subscribed stock tick data, `get_df_stk` method will convert the `ticks_stk_v1` list to a Polars DataFrame, and return it, at this point, we have already got a DataFrame that can be used to calculate technical indicators.

df_stk



Copyright © 2025 SinoPac

**add `QuoteManager` get kbar method**

```
def get_df_stk_kbar(
    self, unit: str = "1m", exprs: List[pl.Expr] = []
) -> pl.DataFrame:
    df = self.get_df_stk()
    df = df.group_by(
        pl.col("datetime").dt.truncate(unit),
        pl.col("code"),
        maintain_order=True,
    ).agg(
        pl.col("price").first().alias("open"),
        pl.col("price").max().alias("high"),
        pl.col("price").min().alias("low"),
        pl.col("price").last().alias("close"),
        pl.col("volume").sum().alias("volume"),
    )
    if exprs:
        df = df.with_columns(exprs)
    return df
```

in `get_df_stk_kbar` method, we will use `get_df_stk` method to get the Ticks DataFrame and then group the data by truncated `datetime` and `code`, and then aggregate the data in each group to get the K line data, finally, we will return the K line DataFrame. Here we remain the `exprs` parameter, allowing users to pass in additional expressions for more calculations.

In this part, we use `1m` to represent 1 minute, if you want to get 5 minutes K line, you can change the unit to `5m`, 1 hour K line can be changed to `1h`, if you want more different units, you can refer to the truncate API documentation.

**add custom technical indicator calculation method**

```
import polars as pl
import polars_talib as plta

quote_manager.get_df_stk_kbar("5m", [
    pl.col("close").ta.ema(5).over("code").fill_nan(None).alias("ema5"),
    plta.macd(pl.col("close"), 12, 26, 9).over("code").struct.field("macd").fill_nan(None),
])
```

in this part, we use polars_ta to calculate technical indicators and add them to the K line data, here we calculate `ema` and `macd` two indicators, more indicators can refer to polars_ta_extension supported indicators list.

in this polars_ta expression, we use `over("code")` to group the data by commodity code for independent calculation of each commodity, so even if all commodities are in the same DataFrame, the calculation results are independent of each other, and this `over` partition is automatically parallel computing, so even if there are a large number of commodities, the calculation can be very fast and then using `alias` to set the field name of the calculation result as `ema5`, in the `macd` indicator, the return is a struct with multiple fields, and this part gets the `macd` field.

because this part only passes in expressions and is very lightweight, you can pass in any expressions you need according to your needs, and you can also make your own indicators using polars expression, this part just provides an interface for calculation and a simple usage example.


Copyright © 2025 SinoPac

**add `QuoteManager` backfill missed ticks method**

```python
def fetch_ticks(self, contract: BaseContract) -> pl.DataFrame:
    code = contract.code
    ticks = self.api.ticks(contract)
    df = pl.DataFrame(ticks.dict()).select(
        pl.from_epoch("ts", time_unit="ns").dt.cast_time_unit("us").alias("datetime"),
        pl.lit(code).alias("code"),
        pl.col("close").alias("price"),
        pl.col("volume").cast(pl.Int64),
        pl.col("tick_type").cast(pl.Int8),
    )
    return df

def subscribe_stk_tick(self, codes: List[str], recover: bool = False):
    for code in codes:
        # skop
        if recover:
            df = self.fetch_ticks(contract)
            if not df.is_empty():
                code_ticks = [t for t in self.ticks_stk_v1 if t.code == code]
                if code_ticks:
                    t_first = code_ticks[0].datetime
                    df = df.filter(pl.col("datetime") < t_first)
                    self.df_stk = self.df_stk.vstack(df)
                else:
                    self.df_stk = self.df_stk.vstack(df)
```

in `subscribe_stk_tick` method, we will check if the `recover` parameter is true, if it is, we will call `fetch_ticks` method to get the historical ticks data, and then use `filter` method to filter out the ticks data that have been received, and use `vstack` method to add the historical ticks data to the `df_stk` DataFrame.

In above we have completed a quote manager that can subscribe to market data, backfill missed ticks, and calculate technical indicators. Next, we will integrate all the code and use it in a jupyter lab environment.

The complete QuoteManager can be found in quote.py.

The complete example jupyter notebook can be found in quote_manager_usage.



Copyright © 2025 SinoPac

# 5.

Version 1.0 is a major release. This document assist users migrating to version 1.0.

## 5.1 Shioaji

Remove argument `backend`

```
import shioaji as sj
sj.Shioaji?
```



Copyright © 2025 SinoPac

**Out**

**version>=1.0** **version<1.0**

```
Init signature:
sj.Shioaji(
    simulation: bool = False,
    proxies: Dict[str, str] = {},
    currency: str = 'NTD',
)
Docstring:
shioaji api

Functions:
    login
    logout
    activate_ca
    list_accounts
    set_default_account
    get_account_margin
    get_account_openposition
    get_account_settle_profitloss
    get_stock_account_funds
    get_stock_account_unreal_profitloss
    get_stock_account_real_profitloss
    place_order
    update_order
    update_status
    list_trades

Objects:
    Quote
    Contracts
    Order
Init docstring:
initialize Shioaji to start trading

Args:
    simulation (bool):
        - False: to trading on real market (just use your Sinopac account to start trading)
        - True: become simulation account(need to contract as to open simulation account)
    proxies (dict): specific the proxies of your https
        ex: {'https': 'your-proxy-url'}
    currency (str): {NTX, USX, NTD, USD, HKD, EUR, JPY, GBP}
        set the default currency for display
```

```
Init signature:
sj.Shioaji(
    backend: str = 'http',
    simulation: bool = False,
    proxies: Dict[str, str] = {},
    currency: str = 'NTD',
)
Docstring:
shioaji api

Functions:
    login
    activate_ca
    list_accounts
    set_default_account
    get_account_margin
    get_account_openposition
    get_account_settle_profitloss
    get_stock_account_funds
    get_stock_account_unreal_profitloss
    get_stock_account_real_profitloss
    place_order
    update_order
    update_status
    list_trades

Objects:
    Quote
    Contracts
    Order
Init docstring:
initialize Shioaji to start trading

Args:
    backend (str): {http, socket}
        use http or socket as backend currently only support http, async socket backend coming soon.
    simulation (bool):
        - False: to trading on real market (just use your Sinopac account to start trading)
        - True: become simulation account(need to contract as to open simulation account)
    proxies (dict): specific the proxies of your https
        ex: {'https': 'your-proxy-url'}
    currency (str): {NTX, USX, NTD, USD, HKD, EUR, JPY, GBP}
        set the default currency for display
```



Copyright © 2025 SinoPac

## 5.2 Login

Please update your login parameters from `person_id` and `passwd` to `api_key` and `secret_key` in order to use version 1.0. You can apply for an api_key on the Token page.

**In**

**version>=1.0** **version<1.0**

```
import shioaji as sj
api = sj.Shioaji()
api.login(
    api_key="YOUR_API_KEY",
    secret_key="YOUR_SECRET_KEY"
)
```

```
import shioaji as sj
api = sj.Shioaji()
api.login(
    person_id="YOUR_PERSON_ID",
    passwd="YOUR_PASSWORD",
)
```

**Out**

```
[
    FutureAccount(person_id='', broker_id='', account_id='', signed=True, username=''),
    StockAccount(person_id='', broker_id='', account_id='', signed=True, username='')
]
```

## 5.3 Stock Order

Rename `TFTStockOrder` to `StockOrder`



Copyright © 2025 SinoPac

**StockOrder**

verion>=1.0 verion<1.0

```
>> sj.order.StockOrder?

Init signature:
sj.order.StockOrder(
    *,
    action: shioaji.constant.Action,
    price: Union[pydantic.types.StrictInt, float],
    quantity: shioaji.order.ConstrainedIntValue,
    id: str = '',
    seqno: str = '',
    ordno: str = '',
    account: shioaji.account.Account = None,
    custom_field: shioaji.order.ConstrainedStrValue = '',
    ca: str = '',
    price_type: shioaji.constant.StockPriceType,
    order_type: shioaji.constant.OrderType,
    order_lot: shioaji.constant.StockOrderLot = <StockOrderLot.Common: 'Common'>,
    order_cond: shioaji.constant.StockOrderCond = <StockOrderCond.Cash: 'Cash'>,
    daytrade_short: bool = False,
) -> None

>> sj.order.TFTStockOrder?

Init signature:
sj.order.TFTStockOrder(
    *,
    action: shioaji.constant.Action,
    price: Union[pydantic.types.StrictInt, float],
    quantity: shioaji.order.ConstrainedIntValue,
    id: str = '',
    seqno: str = '',
    ordno: str = '',
    account: shioaji.account.Account = None,
    custom_field: shioaji.order.ConstrainedStrValue = '',
    ca: str = '',
    price_type: shioaji.constant.TFTStockPriceType,
    order_type: shioaji.constant.TFTOrderType,
    order_lot: shioaji.constant.TFTStockOrderLot = <TFTStockOrderLot.Common: 'Common'>,
    order_cond: shioaji.constant.StockOrderCond = <StockOrderCond.Cash: 'Cash'>,
    first_sell: shioaji.constant.StockFirstSell = <StockFirstSell.No: 'false'>,
) -> None
```

## 5.3.1 Order

Rename

- `TFTStockPriceType` to `StockPriceType`
- `TFTOrderType` to `OrderType`
- `TFTStockOrderLot` to `StockOrderLot`
- `first_sell` to `daytrade_short`, and type changed to `Bool`.



Copyright © 2025 SinoPac

**Order**

**version>=1.0** **version<1.0**

```
order = api.Order(
    price=12,
    quantity=1,
    action=sj.constant.Action.Sell,
    price_type=sj.constant.StockPriceType.LMT,
    order_type=sj.constant.OrderType.ROD,
    order_lot=sj.constant.StockOrderLot.Common,
    daytrade_short=True,
    custom_field="test",
    account=api.stock_account
)

order = api.Order(
    price=12,
    quantity=1,
    action=sj.constant.Action.Sell,
    price_type=sj.constant.TFTStockPriceType.LMT,
    order_type=sj.constant.TFTOrderType.ROD,
    order_lot=sj.constant.TFTStockOrderLot.Common,
    first_sell=sj.constant.StockFirstSell.Yes,
    custom_field="test",
    account=api.stock_account
)
```

## 5.3.2 Order Callback

Rename `TFTOrder` to `StockOrder`



Copyright © 2025 SinoPac

**Order Callback**

**version>=1.0** **version<1.0**

```
OrderState.StockOrder {
    'operation': {
        'op_type': 'New',
        'op_code': '00',
        'op_msg': ''
    },
    'order': {
        'id': 'c21b876d',
        'seqno': '429832',
        'ordno': 'W2892',
        'action': 'Buy',
        'price': 12.0,
        'quantity': 10,
        'order_cond': 'Cash',
        'order_lot': 'Common',
        'custom_field': 'test',
        'order_type': 'ROD',
        'price_type': 'LMT'
    },
    'status': {
        'id': 'c21b876d',
        'exchange_ts': 1583828972,
        'modified_price': 0,
        'cancel_quantity': 0,
        'web_id': '137'
    },
    'contract': {
        'security_type': 'STK',
        'exchange': 'TSE',
        'code': '2890',
        'symbol': '',
        'name': '',
        'currency': 'TWD'
    }
}
```

```
OrderState.TFTOrder {
    'operation': {
        'op_type': 'New',
        'op_code': '00',
        'op_msg': ''
    },
    'order': {
        'id': 'c21b876d',
        'seqno': '429832',
        'ordno': 'W2892',
        'action': 'Buy',
        'price': 12.0,
        'quantity': 10,
        'order_cond': 'Cash',
        'order_lot': 'Common',
        'custom_field': 'test',
        'order_type': 'ROD',
        'price_type': 'LMT'
    },
    'status': {
        'id': 'c21b876d',
        'exchange_ts': 1583828972,
        'modified_price': 0,
        'cancel_quantity': 0,
        'web_id': '137'
    },
    'contract': {
        'security_type': 'STK',
        'exchange': 'TSE',
        'code': '2890',
        'symbol': '',
        'name': '',
        'currency': 'TWD'
    }
}
```

## 5.3.3 Deal Callback

Rename `TFTDeal` to `StockDeal`



Copyright © 2025 SinoPac

**Deal Callback**

version>=1.0 version<1.0

```
OrderState.StockDeal {
    'trade_id': '12ab3456',
    'exchange_seq': '123456',
    'broker_id': 'your_broker_id',
    'account_id': 'your_account_id',
    'action': <Action.Buy: 'Buy'>,
    'code': '2890',
    'order_cond': <StockOrderCond.Cash: 'Cash'>,
    'order_lot': <TFTStockOrderLot.Common: 'Common'>,
    'price': 12,
    'quantity': 10,
    'web_id': '137',
    'custom_field': 'test',
    'ts': 1583828972
}

OrderState.TFTDeal {
    'trade_id': '12ab3456',
    'exchange_seq': '123456',
    'broker_id': 'your_broker_id',
    'account_id': 'your_account_id',
    'action': <Action.Buy: 'Buy'>,
    'code': '2890',
    'order_cond': <StockOrderCond.Cash: 'Cash'>,
    'order_lot': <TFTStockOrderLot.Common: 'Common'>,
    'price': 12,
    'quantity': 10,
    'web_id': '137',
    'custom_field': 'test',
    'ts': 1583828972
}
```

## 5.4 Futures Order

**FuturesOrder**

verion>=1.0 verion<1.0

```
>> sj.order.FuturesOrder?

Init signature:
sj.order.FuturesOrder(
    *,
    action: shioaji.constant.Action,
    price: Union[pydantic.types.StrictInt, float],
    quantity: shioaji.order.ConstrainedIntValue,
    id: str = '',
    seqno: str = '',
    ordno: str = '',
    account: shioaji.account.Account = None,
    custom_field: shioaji.order.ConstrainedStrValue = '',
    ca: str = '',
    price_type: shioaji.constant.FuturesPriceType,
    order_type: shioaji.constant.OrderType,
    octype: shioaji.constant.FuturesOCType = <FuturesOCType.Auto: 'Auto'>,
) -> None

>> sj.order.FuturesOrder?

Init signature:
sj.order.FuturesOrder(
    *,
    action: shioaji.constant.Action,
    price: Union[pydantic.types.StrictInt, float],
    quantity: shioaji.order.ConstrainedIntValue,
    id: str = '',
    seqno: str = '',
    ordno: str = '',
    account: shioaji.account.Account = None,
    custom_field: shioaji.order.ConstrainedStrValue = '',
    ca: str = '',
    price_type: shioaji.constant.FuturesPriceType,
    order_type: shioaji.constant.FuturesOrderType,
    octype: shioaji.constant.FuturesOCType = <FuturesOCType.Auto: 'Auto'>,
) -> None
```

### 5.4.1 Order

Rename `FuturesOrderType` to `OrderType`



Copyright © 2025 SinoPac

**Order**

**verion>=1.0** **verion<1.0**

```
order = api.Order(
    action=sj.constant.Action.Buy,
    price=100,
    quantity=1,
    price_type=sj.constant.FuturesPriceType.LMT,
    order_type=sj.constant.OrderType.ROD,
    octype=sj.constant.FuturesOCType.Auto,
    account=api.futopt_account
)

order = api.Order(
    action=sj.constant.Action.Buy,
    price=100,
    quantity=1,
    price_type=sj.constant.FuturesPriceType.LMT,
    order_type=sj.constant.FuturesOrderType.ROD,
    octype=sj.constant.FuturesOCType.Auto,
    account=api.futopt_account
)
```

## 5.4.2 Order Callback

Rename `FOrder` to `FuturesOrder`



Copyright © 2025 SinoPac

**Order Event**

**version>=1.0** **version<1.0**

```
OrderState.FuturesOrder {
    'operation': {
        'op_type': 'New',
        'op_code': '00',
        'op_msg': ''
    },
    'order': {
        'id': '02c347f7',
        'seqno': '956201',
        'ordno': 'kY00H',
        'action': 'Sell',
        'price': 17760.0,
        'quantity': 1,
        'order_cond': None,
        'order_type': 'ROD',
        'price_type': 'LMT',
        'market_type': 'Night',
        'oc_type': 'New',
        'subaccount': ''
    },
    'status': {
        'id': '02c347f7',
        'exchange_ts': 1625729890,
        'modified_price': 0.0,
        'cancel_quantity': 0,
        "web_id": "P"
    },
    'contract': {
        'security_type': 'FUT',
        'code': 'TXF',
        'exchange': 'TIM',
        'delivery_month': '202107',
        'strike_price': 0.0,
        'option_right': 'Future'
    }
}
```

```
OrderState.FOrder {
    'operation': {
        'op_type': 'New',
        'op_code': '00',
        'op_msg': ''
    },
    'order': {
        'id': '02c347f7',
        'seqno': '956201',
        'ordno': 'kY00H',
        'action': 'Sell',
        'price': 17760.0,
        'quantity': 1,
        'order_cond': None,
        'order_type': 'ROD',
        'price_type': 'LMT',
        'market_type': 'Night',
        'oc_type': 'New',
        'subaccount': ''
    },
    'status': {
        'id': '02c347f7',
        'exchange_ts': 1625729890,
        'modified_price': 0.0,
        'cancel_quantity': 0,
        "web_id": "P"
    },
    'contract': {
        'security_type': 'FUT',
        'code': 'TXF',
        'exchange': 'TIM',
        'delivery_month': '202107',
        'strike_price': 0.0,
        'option_right': 'Future'
    }
}
```

## 5.4.3 Deal Callback

Rename `FDeal` to `FuturesDeal`



Copyright © 2025 SinoPac

**Deal Event**

version>=1.0 version<1.0

```
OrderState.FuturesDeal {
    "trade_id":"02c347f7",
    "seqno":"956344",
    "ordno":"ky00N11O",
    "exchange_seq":"a0000060",
    "broker_id":"F002000",
    "account_id":"9104000",
    "action":"Sell",
    "code":"TXF",
    "price":17650.0,
    "quantity":4,
    "subaccount":"",
    "security_type":"FUT",
    "delivery_month":"202107",
    "strike_price":0.0,
    "option_right":"Future",
    "market_type":"Day",
    "ts":1625800369
}

OrderState.FDeal {
    "trade_id":"02c347f7",
    "seqno":"956344",
    "ordno":"ky00N11O",
    "exchange_seq":"a0000060",
    "broker_id":"F002000",
    "account_id":"9104000",
    "action":"Sell",
    "code":"TXF",
    "price":17650.0,
    "quantity":4,
    "subaccount":"",
    "security_type":"FUT",
    "delivery_month":"202107",
    "strike_price":0.0,
    "option_right":"Future",
    "market_type":"Day",
    "ts":1625800369
}
```

## 5.5 Market Data

**Warn**

**version >= 1.1 will no longer provide QuoteVersion.v0, please change to QuoteVersion.v1.**

### 5.5.1 Callback

**Tick**

**hint: pythonic way by using decorator**

QuoteVersion.v1 QuoteVersion.v0

```
from shioaji import TickSTKv1, Exchange

@api.on_tick_stk_v1()
def quote_callback(exchange: Exchange, tick:TickSTKv1):
    print(f"Exchange: {exchange}, Tick: {tick}")

@api.quote.on_quote
def quote_callback(topic: str, quote: dict):
    print(f"Topic: {topic}, Quote: {quote}")
```



Copyright © 2025 SinoPac

**In: traditional way**

QuoteVersion.v1 QuoteVersion.v0

```
from shioaji import TickSTKv1, Exchange

def quote_callback(exchange: Exchange, tick:TickSTKv1):
    print(f"Exchange: {exchange}, Tick: {tick}")

api.quote.set_on_tick_stk_v1_callback(quote_callback)

def quote_callback(topic: str, quote: dict):
    print(f"Topic: {topic}, Quote: {quote}")

api.quote.set_quote_callback(quote_callback)
```

**Out**

QuoteVersion.v1 QuoteVersion.v0

```
Exchange: Exchange.TSE, Tick: Tick(code='2330', datetime=datetime.datetime(2021, 7, 2, 13, 16, 35, 92970), open=Decimal('590'), avg_price=Decimal('589.05'),
close=Decimal('590'), high=Decimal('593'), low=Decimal('587'), amount=Decimal('590000'), total_amount=Decimal('8540101000'), volume=1, total_volume=14498,
tick_type=1, chg_type=4, price_chg=Decimal('-3'), pct_chg=Decimal('-0.505902'), trade_bid_volume=6638, ask_side_total_vol=7860, bid_side_total_cnt=2694,
ask_side_total_cnt=2705, closing_oddlot_shares=0, fixed_trade_vol=0, suspend=0, simtrade=0, intraday_odd=0)

Topic: MKT/*/TSE/2330, Quote: {'AmountSum': [4739351000.0], 'Close': [596.0], 'Date': '2021/03/30', 'TickType': [2], 'Time': '10:01:33.349431', 'VolSum': [7932],
'Volume': [1]}
```

### BidAsk

**In: pythonic way by using decorator**

QuoteVersion.v1 QuoteVersion.v0

```
from shioaji import BidAskSTKv1, Exchange

@api.on_bidask_stk_v1()
def quote_callback(exchange: Exchange, bidask:BidAskSTKv1):
    print(f"Exchange: {exchange}, BidAsk: {bidask}")

@api.quote.on_quote
def quote_callback(topic: str, quote: dict):
    print(f"Topic: {topic}, Quote: {quote}")
```

**In: traditional way**

QuoteVersion.v1 QuoteVersion.v0

```
from shioaji import BidAskSTKv1, Exchange

def quote_callback(exchange: Exchange, bidask:BidAskSTKv1):
    print(f"Exchange: {exchange}, BidAsk: {bidask}")

api.quote.set_on_bidask_stk_v1_callback(quote_callback)

def quote_callback(topic: str, quote: dict):
    print(f"Topic: {topic}, Quote: {quote}")

api.quote.set_quote_callback(quote_callback)
```



Copyright © 2025 SinoPac

Out

QuoteVersion.v1 QuoteVersion.v0

```
Exchange: Exchange.TSE, BidAsk: BidAsk(code='2330', datetime=datetime.datetime(2021, 7, 2, 13, 17, 29, 726428), bid_price=[Decimal('589'), Decimal('588'),
Decimal('587'), Decimal('586'), Decimal('585')], bid_volume=[223, 761, 1003, 809, 1274], diff_bid_vol=[0, 0, 0, 0, 0], ask_price=[Decimal('590'), Decimal('591'),
Decimal('592'), Decimal('593'), Decimal('594')], ask_volume=[304, 232, 183, 242, 131], diff_ask_vol=[1, 0, 0, 0, 0], suspend=0, simtrade=0, intraday_odd=0)

Topic: QUT/idcdmzpcr01/TSE/2330, Quote: {'AskPrice': [590.0, 591.0, 592.0, 593.0, 594.0], 'AskVolume': [303, 232, 183, 242, 131], 'BidPrice': [589.0, 588.0,
587.0, 586.0, 585.0], 'BidVolume': [224, 762, 1003, 809, 1274], 'Date': '2021/07/02', 'Time': '13:17:26.391840'}
```

## 5.6 Future Account Info.

Remove functions

```
1. get_account_margin
2. get_account_openposition
3. get_account_settle_profitloss
```

Instead, you should use

```
1. margin
2. list_positions( api.futopt_account )
3. list_profit_loss( api.futopt_account )
4. list_profit_loss_detail( api.futopt_account )
5. list_profit_loss_summary( api.futopt_account )
```

For more information, please refer to Account Data section.

Finally, give us support and encouragement on GITHUB

github



Copyright © 2025 SinoPac

# 6.

## 6.0.1

**(MKT) (MKP)**

```
order = api.Order(
    action=sj.constant.Action.Buy,
    price=0, # MKT, MKP will not use price parameter
    quantity=1,
    price_type='MKP', # change to MKT or MKP
    order_type='IOC', # MKT, MKP only accecpt IOC order
    octype=sj.constant.FuturesOCType.Auto,
    account=api.futopt_account
)
```

**( ) ROD**

First, we need to know the `limit up(limit down)` price of the security. Just take a look at the `api.Contracts`, you will find the information you want.

**In**

```
api.Contracts.Stocks.TSE['TSE2330']
```

**Out**

```
Stock(
    exchange=<Exchange.TSE: 'TSE'>,
    code='2330',
    symbol='TSE2330',
    name='    ',
    category='24',
    unit=1000,
    limit_up=653.0,
    limit_down=535.0,
    reference=594.0,
    update_date='2021/08/27',
    margin_trading_balance=6565,
    short_selling_balance=365,
    day_trade=<DayTrade.Yes: 'Yes'>
)
```

Example place LMT and ROD order at limit up price.

**In**

```
contract = api.Contracts.Stocks.TSE['TSE2330']
price = contract.limit_up
order = api.Order(
    action=sj.constant.Action.Buy,
    price=price,
    quantity=1,
    price_type='LMT',
    order_type='ROD',
    order_lot=sj.constant.StockOrderLot.Common,
    account=api.stock_account
)
```



Copyright © 2025 SinoPac

## 6.0.2

If your code something like this, and possibly run code on cmd/terminal with `python stream.py`. Then you definitely won't get any additional ticks, since the python program has already terminated.

**version>=1.0** **version<1.0**

```
import shioaji as sj

api = sj.Shioaji(simulation=True)
api.login('YOUR_API_KEY', 'YOUR_SECRET_KEY')
api.quote.subscribe(
    api.Contracts.Stocks["2330"],
    quote_type = sj.constant.QuoteType.Tick
)

# stream.py
import shioaji as sj

api = sj.Shioaji(simulation=True)
api.login('YOUR_PERSON_ID', '2222')
api.quote.subscribe(
    api.Contracts.Stocks["2330"],
    quote_type = sj.constant.QuoteType.Tick
)
```

If you wish your python program to survive, please modify you python script as below.

**version>=1.0** **version<1.0**

```
# stream.py
import shioaji as sj
from threading import Event

api = sj.Shioaji(simulation=True)
api.login('YOUR_API_KEY', 'YOUR_SECRET_KEY')
api.quote.subscribe(
    api.Contracts.Stocks["2330"],
    quote_type = sj.constant.QuoteType.Tick
)

Event().wait()

# stream.py
import shioaji as sj
from threading import Event

api = sj.Shioaji(simulation=True)
api.login('YOUR_PERSON_ID', '2222')
api.quote.subscribe(
    api.Contracts.Stocks["2330"],
    quote_type = sj.constant.QuoteType.Tick
)

Event().wait()
```

## 6.0.3

**Account not acceptable**

```
-    [  ](https://sinotrade.github.io/zh_TW/tutor/prepare/terms/#_1) [API  ](https://sinotrade.github.io/zh_TW/tutor/prepare/terms/#api)
- [`update_status`](../tutor/order/UpdateStatus)
```



Copyright © 2025 SinoPac

**shioaji.log**

Please add environment variable before import shioaji. `(version >= 0.3.3.dev0)`

linux or Mac OS:

```
export SJ_LOG_PATH=/path/to/shioaji.log
```

windows:

```
set SJ_LOG_PATH=C:\path\to\shioaji.log
```

**contracts**

Please add environment variable before import shioaji. `(version >= 0.3.4.dev2)`

linux or Mac OS:

```
export SJ_CONTRACTS_PATH=MY_PATH
```

windows:

```
set SJ_CONTRACTS_PATH=MY_PATH
```

python:

```
os.environ["SJ_CONTRACTS_PATH"]=MY_PATH
```

**3**

** Note that you only have 2 chances to unlock your account online in a day. **

** We've migrate QA site to Shioaji Forum **



Copyright © 2025 SinoPac

# 7.

## 7.1 version: 1.2.5 (2024-10-01)

- feat: refactor expire time of CA

commit_id: 6621685a

⚡
release_at: 2024-10-01 02:25:01.723

## 7.2 version: 1.2.4 (2024-08-28)

- feat: support py3.12

commit_id: a287f56c

⚡
release_at: 2024-08-28 16:00:00.000

## 7.3 version: 1.2.3 (2024-03-06)

- feat: change default site to bc
- feat: pysolace upgrade 0.9.40(solclient 7.28.0.4)
- feat: support apple silicon chip

commit_id: 8096bbac

⚡
release_at: 2024-03-06 16:00:00.000

## 7.4 version: 1.2.2 (2024-01-09)

- fix: remove column of profitloss in future

commit_id: ca973a81

⚡
release_at: 2024-01-09 02:27:31.383

## 7.5 version: 1.2.1 (2023-12-22)

- fix: windows inject dll issue

commit_id: 2a413848

⚡
release_at: 2023-12-22 01:19:17.043

## 7.6 version: 1.2.0 (2023-12-20)

- feat: vpn
- feat: rust version ca


Copyright © 2025 SinoPac

- refactor: test report flow

commit_id: 856f39ea

⚡
release_at: 2023-12-20 16:00:00.000

## 7.7 version: 1.1.13 (2023-11-01)

feat: impl ca.get_sign on Darwin

commit_id: 729f058e

⚡
release_at: 2023-11-01 05:36:29.553

## 7.8 version: 1.1.12 (2023-08-22)

- feat: usage add limit and available byte info

commit_id: cf5e4628

⚡
release_at: 2023-08-22 16:00:00.000

## 7.9 version: 1.1.11 (2023-08-04)

- fix: custom_field in validator for only support number and alphabet
- fix: pydantic v2 trade issue
- fix: pydantic v2 contracts cache issue

commit_id: cc1da47e

⚡
release_at: 2023-08-04 08:00:37.000

## 7.10 version: 1.1.10 (2023-07-23)

- feat: profit loss detail support unit

commit_id: a62d1f6a

⚡
release_at: 2023-07-23 16:00:00.000

## 7.11 version: 1.1.9 (2023-07-20)

**yanked**

commit_id: f9f03cff

⚡
release_at: 2023-07-20 07:43:46.000


Copyright © 2025 SinoPac

## 7.12 version: 1.1.8 (2023-07-18)

- feat: query usage
- feat: profit_loss support unit
- feat: support pydantic v2

commit_id: 3dc8568e

⚡
release_at: 2023-07-18 09:08:42.000

## 7.13 version: 1.1.7 (2023-07-18)

**yanked**

commit_id: fb490a9a

⚡
release_at: 2023-07-18 07:02:20.000

## 7.14 version: 1.1.6 (2023-06-19)

- feat: solace reconnect with sub 2500 user

commit_id: eeaeeb5f

⚡
release_at: 2023-06-19 16:00:00.000

## 7.15 version: 1.1.5 (2023-06-07)

- fix: simulation sign check
- fix: handle pickle load error

commit_id: 1def691c

⚡
release_at: 2023-06-07 16:00:00.000


Copyright © 2025 SinoPac

# 8.

In order to avoid affecting other users' connections, please follow the following usage rules.

**Traffic**

• Stock :

| Trading volume by API in the past 30 days | Daily Traffic Limit |
|---|---|
| 0 | 500MB |
| 1 - 1E | 2GB |
| > 1E | 10GB |

• Future :

| Trading volume by API in the past 30 days | Daily Traffic Limit |
|---|---|
| 0 | 500MB |
| 1 - TXF 1000 contracts / MXF 4000 contracts | 2GB |
| > TXF 1000 contracts / MXF 4000 contracts | 10GB |

**Traffic query**

```
api.usage()
```

**Out**

```
UsageStatus(connections=1, bytes=41343260, limit_bytes=2147483648, remaining_bytes=2106140388)
```

```
connection: connection count.
bytes: traffic.
limit_bytes: limit bytes of daily.
remaining_bytes: remaining bytes of daily.
```



Copyright © 2025 SinoPac

**Counts**

- Data :

  `credit_enquire`, `short_stock_sources`, `snapshots`, `ticks`, `kbars`
- The total amount of inquiries above is limited to 50 times within 5 seconds.
- During trading hours, it is prohibited to query `ticks` more than 10 times.
- During trading hours, it is prohibited to query `kbars` more than 270 times.
- Portfolio :

  `list_profit_loss_detail`,`account_balance`, `list_settlements`, `list_profit_loss`, `list_positions`, `margin`

  The total amount of inquiries above is limited to 25 times within 5 seconds.
- Order :

  `place_order`, `update_status`, `update_qty`, `update_price`, `cancel_order`

  The total amount of inquiries above is limited to 250 times within 10 seconds.
- Subscribe :

  Number of `api.subscribe()` is 200.
- Connect :

  The same SinoPac Securities `person_id` can only use up to 5 connections.

  note. `api.login()` create a connection.
- Login :

  Up to 1000 times per day.

**Warn**

- If the traffic exceeds the limit, query requests for market data such as ticks, snapshots, and kbars will return empty values, while other functionalities remain unaffected.
- If the usage exceeds the limit, the service will be suspended for one minute.
- If the limit is exceeded multiple times in a row on the same day, the company will suspend the right to use the IP and ID.
- If the ID is suspended, please contact Shioaji management staff



Copyright © 2025 SinoPac