

CREATING A HIGHLY AVAILABLE SERVICE GROUP USING VCS

Sample Process Script:

Copy and Save the below script under your mount point
(Eg: /Linux/Modular)

```
#!/bin/ksh
```

```
# Modular script for VCS class.
```

```
#####
```

```
#
```

```
# $1 is Service Group name
```

```
# $0 is name of shell script being executed
```

```
#
```

```
while true
```

```
do
```

```
echo `date` ${1} Modular is alive >> ${0}out
```

```
sleep 4
```

```
echo `date` ${1} Modular is still alive >> ${0}out
```

```
sleep 4
```

```
done
```

Service Group Name: Linuxsg
Participating Nodes: Redhat-1 and SLES-1

Resources:

Network Resources:
NIC Resource Name: Linuxnic
IP Resource Name: Linuxip

Disk Resources:
DiskGroup Name: Linuxdg
Volume Name: Linuxvol
Mount Point: Linuxmount

Process Resource:
Process Name: Linuxprocess

Creating Service Group.

+++++

```
# haconf -makerw
# hagr -add Linuxsg
# hagr -modify Linuxsg SystemList Redhat-1 0 SLES-1 1
# hagr -modify Linuxsg AutoStartList Redhat-1
# hagr -display Linuxsg
# haconf -dump
# view /etc/VRTSvcs/conf/config/main.cf
```

Adding a NIC resource to a service group

+++++

```
# hares -add Linuxnic NIC Linuxsg
# hares -modify Linuxnic Critical 0
# hares -modify Linuxnic Device hme0
# hares -modify Linuxnic NetworkHosts 192.168.1.11
# hares -modify Linuxnic Enabled 1
# hares -state Linuxnic
```

Adding a IP resource

+++++

```
# hares -add Linuxip IP Linuxsg
# hares -modify Linuxip Critical 0
# hares -modify Linuxip Device hme0
# hares -modify Linuxip Address 192.168.1.92
# hares -modify Linuxip Address 192.168.1.93
# hares -modify Linuxip Enabled 1
# hares -online Linuxip -sys Redhat-1
# hares -state Linuxip
# hastatus -sum
# haconf -dump
```

Adding a DiskGroup resource

+++++

```
# hares -add Linuxdg DiskGroup Linuxsg
# hares -modify Linuxdg Critical 0
# hares -modify Linuxdg DiskGroup Linuxsg
# hares -modify Linuxdg Enabled 1
# hares -online Linuxdg -sys Redhat-1
# hares -state Linuxdg
# vxdg list | grep Linuxdg
# haconf -dump
# view main.cf
```

Adding Volume resource

```
+++++
# hares -add Linuxvol Volume Linuxsg
# hares -modify Linuxvol Critical 0
# hares -modify Linuxvol Volume Linuxvol
# hares -modify Linuxvol DiskGroup Linuxdg
# hares -modify Linuxvol Enabled 1
# hares -display Linuxvol
# hares -online Linuxvol -sys Redhat-1
# hares -state Linuxvol
# vxprint -g Linuxdg
# haconf -dump
```

Adding a MountPoint resource

```
+++++
# hares -add Linuxmount mount Linuxsg
```

```
# hares -modify Linuxmount Critical 0
# hares -modify Linuxmount MountPoint /Linux
# hares -modify Linuxmount BlockDevice
/dev/vx/dsk/Linuxdg/Linuxvol
# hares -modify Linuxmount FSType vxfs
# hares -modify Linuxmount FSCKopt %-y
# hares -modify Linuxmount Enabled 1
# hares -display Linuxmount
# hares -online Linuxmount -sys Redhat-1
# hares -state Linuxmount
# haconf -dump
# view main.cf
```

Adding a Process Resource

```
+++++
# hares -add Linuxprocess Process Linuxsg
# hares -modify Linuxprocess Critical 0
# hares -modify Linuxprocess PathName /bin/sh
# hares -modify Linuxprocess Arguments
"/Linux/Modular Linuxsg"
# hares -modify Linuxprocess Enabled 1
# hares -display Linuxprocess
# hares -online Linuxprocess -sys Redhat-1
# hares -state Linuxprocess

# ps -ef | grep Modular
# haconf -dump
```

```
# view main.cf
```

Linking Resources in the service group

```
+++++
```

```
# hares -link Linuxip Linuxnic
```

```
# hares -link Linuxvol Linuxdg
```

```
# hares -link Linuxmount Linuxvol
```

```
# hares -link Linuxprocess Linuxip
```

```
# hares -link Linuxprocess Linuxmount
```

```
# hares -dep | grep Linuxsg
```

```
# haconf -dump -makerw
```

Testing the Service Group

```
+++++
```

```
#hastatus -sum
```

```
#hagrp -switch Linuxsg -to SLES-1
```

```
#hagrp -state Linuxsg
```

```
#hagrp -switch Linuxsg -to Redhat-1
```

```
#hagrp -state Linuxsg
```

Good Luck