

Project Proposal: Portable Smart Braille Printer

Namare Shakib Angkon¹, Abdullah Al Nafiz², Golam Bari Fardeen³, Md. Masum Mizi⁴, Shinthia Rahman⁵

011222131¹, 011222141², 0112230321³, 0112230339⁴, 0112230345⁵

Department of Computer Science & Engineering
United International University, Dhaka, Bangladesh

Abstract

Access to printed information is a fundamental right, yet for the visually impaired, it remains a significant challenge. Commercial Braille embossers are often expensive, bulky, and lack modern input methods, limiting their accessibility and practicality. This project aims to solve these issues by developing a **low-cost, portable, and intelligent Braille embosser**. The system leverages the computational power of a Raspberry Pi to create a standalone device capable of converting digital text into tangible Braille on standard A4 paper. Key innovations include multiple input methods, such as **Wi-Fi/Bluetooth file transfer** and an integrated **Optical Character Recognition (OCR) system** that allows the device to scan and emboss printed documents on the fly. By combining open-source 3D-printed mechanical designs with a modern, Pi-based control system and advanced software features, this project will deliver a versatile and affordable tool to significantly enhance information access for the visually impaired community.

Project Overview

The primary goal of this project is to engineer a functional, portable, and feature-rich Braille embosser at a fraction of the cost of commercial alternatives. Our design builds upon the foundational mechanical framework of the open-source "BrailleRAP" project but fundamentally replaces its core control system. Instead of a traditional 3D printer board like the MKS Gen L, we are implementing a **Raspberry Pi 3 B** as the central processing unit. This architectural shift unlocks the potential for advanced, standalone functionalities that are not possible with simpler microcontrollers.

The project will deliver three core functionalities:

1. **Digital Text Embossing:** The device will accept digital text files (e.g., .txt, .docx) sent wirelessly via a Wi-Fi or Bluetooth connection, convert them to Grade 1 Braille using the Liblouis library, and emboss them accurately.

2. **OCR "Scan-to-Braille"**: Utilizing a Raspberry Pi Camera Module, the embosser will feature an integrated document scanning function. Users can place a standard printed page, and the system will perform Optical Character Recognition (OCR) to extract the text and immediately begin the embossing process, effectively turning any printed document into a Braille page.


The mechanical system, comprised of 3D-printed parts, NEMA 17 stepper motors, and a solenoid-based embossing head, will be precisely controlled by the Raspberry Pi's GPIO pins through dedicated driver boards. This ensures accurate paper feeding (Y-axis) and print head movement (X-axis), resulting in high-quality Braille output.

Hardware & Software Components

This project integrates a range of electrical and mechanical components, controlled by a powerful central processor and custom software. Below is a detailed breakdown of each component, its specifications, and its specific role within the Braille Embosser system.

A. Central Processing Unit (The Brain)

Component: Raspberry Pi 3 B



- **Overview:** The Raspberry Pi 3 B is a powerful, credit-card-sized single-board computer (SBC) featuring a quad-core processor, 1GB of RAM, and built-in Wi-Fi and Bluetooth connectivity. It runs a full-fledged Linux operating system, allowing for complex software execution.
- **Role in Project & Connection Details:**
 - **The System Controller:** The Pi 3 serves as the central brain of the entire embosser, replacing the less powerful microcontroller boards typically used in 3D printers.

Responsibilities: It will run the main Python application that manages all other components. Its tasks include:

1. Receiving files via Wi-Fi/Bluetooth.
2. Executing the OCR process on images captured by the camera.
3. Running the `Liblouis` software to translate text into Braille dot patterns.
4. Sending precise step-and-direction signals to the motor drivers.
5. Activating the solenoid for embossing.

Connection: It will be powered by a stable **5V DC** supply, connected to its Micro-USB power input. It will interface with all other electronic modules via its 40-pin GPIO (General-Purpose Input/Output) header.


B. Power System

Component: 3S LiPo Battery, 11.1V (e.g., 2200mAh)



- **Overview:** A Lithium Polymer (LiPo) battery is a rechargeable battery known for its high power density, making it ideal for portable applications that require significant current draw. A "3S" configuration means it has three cells in series, providing a nominal voltage of 11.1V.
- **Role in Project & Connection Details:**
 - This is the **primary power source** for the entire device, enabling its portability.
 - It will directly power the high-load components: the two **DRV8825 stepper motor drivers**, which require a higher voltage (VMOT pin) to provide adequate torque to the NEMA 17 motors.
 - It will also serve as the input voltage for the 5V buck converter.
 - **(Safety Note):** All connections will include appropriate gauging and fusing to protect against short circuits.

Component: 5V Buck Converter



- **Overview:** A buck converter is a highly efficient voltage regulator that steps down DC voltage.
- **Role in Project & Connection Details:**
 - This is a critical component for system stability. It takes the **11.1V input** from the LiPo battery and converts it into a clean, stable **5V output**.
 - This regulated 5V rail will be used to power the **Raspberry Pi 3** and potentially other 5V logic components like the IR sensor and servo motor. This prevents the high and fluctuating voltage of the battery from damaging the sensitive electronics.

C. Motion & Mechanical System

Component: NEMA 17 Stepper Motors (2x)




- **Overview:** Stepper motors are brushless DC motors that move in discrete, precise steps. This allows for excellent position control without needing a feedback sensor. NEMA 17 is a standard faceplate size.

- **Role in Project & Connection Details:**

- **X-Axis Motor:** One motor will be connected via a timing belt and pulley system to move the embossing head carriage left and right across the page.
- **Y-Axis Motor:** The second motor will drive the paper feed rollers, advancing the paper up or down with high precision to position each line of Braille correctly.
- **Connection:** The four wires from each motor will connect to the A1, A2, B1, B2 outputs on its corresponding DRV8825 driver.

Component: DRV8825 Stepper Motor Drivers (2x)



- **Overview:** The DRV8825 is a microstepping driver that translates low-power control signals into the high-current signals required to drive a stepper motor.
- **Role in Project & Connection Details:**
 - This module acts as the muscle behind the Pi's brain. The Pi cannot directly power the motors.
 - The Raspberry Pi will send two types of signals to each driver from its GPIO pins: a **STEP** signal (a pulse for each step to move) and a **DIR** signal (a HIGH/LOW signal to set direction).
 - **Connection:**
 - **VMOT and GND:** Connect to the **11.1V** from the LiPo battery.
 - **STEP, DIR, ENABLE:** Each will connect to a dedicated **GPIO pin** on the Raspberry Pi.
 - **VDD:** Connects to the Pi's **3.3V or 5V** logic supply.
 -

Component: Mechanical Parts (3D Prints, Rods, Bearings, Belts)

- **Overview:** This includes the 3D printed chassis, along with smooth rods for linear motion, LM8UU bearings to ensure low-friction movement, and GT2 timing belts and pulleys.
- **Role in Project:** These components form the physical structure of the embosser. They translate the rotational motion of the stepper motors into the precise linear X-Y positioning of the embossing head and paper, which is fundamental to the machine's operation.

D. Embossing System

Component: Solenoid Actuator (e.g., 5V or 12V)



- **Overview:** A solenoid is an electromagnetic device that converts electrical energy into a linear pushing or pulling motion.
- **Role in Project & Connection Details:**
 - This is the **embossing head**. It will be mounted on the X-axis carriage.
 - When the Raspberry Pi determines a dot needs to be made, it will send a signal to activate the solenoid. The solenoid's plunger will rapidly extend, striking a pin which then embosses a single Braille dot onto the paper below.
 - **Connection:** A solenoid requires more current than a GPIO pin can provide. It will be controlled via a **MOSFET driver circuit**. A GPIO pin from the Pi will trigger the MOSFET's gate, which in turn will switch the higher power (e.g., 5V or 12V) to activate the solenoid.

E. Input & Sensing System

Component: Raspberry Pi Camera Module 3



- **Overview:** A high-resolution camera designed specifically for the Raspberry Pi, featuring autofocus.
- **Role in Project & Connection Details:**
 - This is the "eye" of the OCR system. It will be mounted on the device to capture a clear, focused image of a printed document placed beneath it.
 - **Connection:** The camera's ribbon cable connects directly into the dedicated **CSI (Camera Serial Interface) port** on the Raspberry Pi.

Component: IR Proximity Sensor



Overview: An infrared (IR) sensor that detects the presence of an object by emitting and receiving an IR beam.

Role in Project & Connection Details:

- **Paper Presence Detection:** This sensor is critical for reliable operation. It will be positioned along the paper path.
- The system will use it to know if paper has been loaded correctly before starting a job, and to detect when the end of the page has been reached.
- **Connection:** The module will be powered by **3.3V** from the Pi. Its digital **OUT** pin will connect to a single **GPIO pin**, sending a signal to the Pi indicating if paper is present or not.

F. User Feedback System

Component: Mini Speaker (8 Ohm, 0.5W) & Vibration Motor



Overview: These are simple output devices to provide non-visual cues to the user.

Role in Project & Connection Details:

- **Audio Feedback:** The speaker will be used with the `eSpeak` text-to-speech library to announce system status audibly (e.g., "Ready", "Embossing file 'mydoc.txt'", "Error: Paper out"). This is essential for independent use by the visually impaired.
- **Haptic Feedback:** The vibration motor provides tactile alerts. For instance, a short buzz could indicate a successful file upload, while a continuous vibration could signal an error condition that needs attention.
- **Connection:** Both components will be driven by simple transistor-based driver circuits, which will be triggered by dedicated **GPIO pins** on the Raspberry Pi.

G. Software

Operating System: Raspberry Pi OS (formerly Raspbian) - A Debian-based Linux distribution optimized for the Pi.

Primary Language: Python 3 - A versatile, high-level language with excellent library support.

Key Libraries:

- The core open-source translation library that will convert standard text into Braille dot patterns according to established standards.
- These libraries will work together to perform the OCR. Pillow will handle the image data from the camera, and Pytesseract will be the Python interface to the Tesseract OCR engine.
- The modern, official Python library for controlling the Raspberry Pi Camera Module.
- Python libraries for controlling the Raspberry Pi's GPIO pins to manage the motors, solenoid, and sensors.
- A command-line text-to-speech engine that will be called by the Python script to generate audio feedback.

System Features & Functionality

The Portable OCR-Enabled Braille Embosser is designed to be a comprehensive, standalone solution. The integration of the Raspberry Pi allows for a rich set of features that address the limitations of traditional devices. The core functionalities are detailed below.

1. Multi-Format Digital Text Embossing

The primary function of the device is to translate digital text documents into embossed Braille.

- **Process:** The user will send a digital file (e.g., `.txt`, `.docx`) from a computer or smartphone to the Raspberry Pi.
- **Translation:** The Pi's software will automatically receive the file, extract the text content, and process it through the `Liblouis` translation library to generate the corresponding Grade 1 Braille dot patterns.
- **Output:** The system will then manage the entire mechanical process: moving the embossing head and paper via the stepper motors and activating the solenoid to precisely punch each dot onto an A4 sheet of paper.

2. "Scan-to-Braille" with Optical Character Recognition (OCR)

This is the system's flagship feature, providing unparalleled utility. It allows users to convert any physical printed document into a tangible Braille copy without needing an external computer or scanner.

- **Process:** A user places a printed document under the integrated Raspberry Pi Camera Module.
- **Capture & Analysis:** Through a simple command (e.g., a physical button press or a software trigger), the system captures a high-resolution image of the document. This image is then processed by the Tesseract OCR engine running on the Pi.
- **Immediate Embossing:** The text extracted by the OCR engine is immediately passed to the Liblouis translator and then sent to the embossing mechanism. This creates a seamless workflow from physical page to Braille page.

3. Wireless Connectivity & File Management

To ensure ease of use and portability, the device will operate without requiring a constant physical connection to a computer.

- **Wi-Fi & Bluetooth:** The Raspberry Pi 3's built-in wireless capabilities will be utilized to allow users to send files directly from their laptops, tablets, or smartphones. This will likely be implemented via a simple web interface hosted on the Pi or a Bluetooth file transfer profile.
- **Onboard Storage:** The Pi's SD card will be used to store incoming files, allowing for a queue of print jobs and the ability to re-print documents without needing to re-upload them.
-

4. Intelligent Paper Handling & Control

The system will manage the paper supply intelligently to prevent errors and ensure smooth operation.

- **Paper Presence Detection:** An IR sensor placed along the paper path allows the Pi to know if a sheet of paper is loaded. The system will not attempt to start a job if no paper is present, preventing wasted motion and alerting the user.
- **End-of-Page Detection:** The same sensor can be used to detect when the current page has been fully embossed and fed through, allowing the system to stop and wait for a new sheet to be loaded for multi-page documents.

System Design & Architecture

The architecture of the Portable Braille Embosser is designed around a central Raspberry Pi controller that manages distinct sub-systems. The system's logic is best represented through a flowchart that details the operational sequence from user input to final output.

