



TXAPI FUSION FEED

User Guide

Document version 1.24

November 2025

Table of Contents

TXAPI FUSION FEED	1
KEY FACTS.....	5
OVERVIEW	5
CONTENT.....	5
TECHNOLOGY	5
ROADMAP AND PLANNED FUTURE ENHANCEMENTS.....	6
LEGACY SYSTEMS	6
GENERAL ARCHITECTURE.....	6
BASIC FUSION STREAMING FEATURES.....	7
SECURITY	7
TIME SENSITIVITY	7
DATA ON DEMAND	7
CONTEXT & UPDATES ONLY	7
TIMESTAMPS AND DAYLIGHT SAVINGS.....	8
GETTING STARTED	9
ACCESS AND AUTHENTICATION.....	9
FIREWALL	9
ENVIRONMENTS.....	9
FUSION RELEASE PROCEDURES	9
SUPPORT ENQUIRIES.....	9
AUTHENTICATION.....	10
EVENT TYPES & MESSAGE FORMAT	11
MESSAGE FORMAT.....	11
MESSAGE EVENTS	11
<i>live</i>	11
<i>context</i>	11
<i>synthetics</i>	11
<i>heartbeat</i>	11
<i>bookmakers</i>	12
<i>sports</i>	12
<i>countries</i>	12
<i>oddstypes</i>	12
<i>Additional event types</i>	12
FUSION BASIC SUBSCRIPTION QUERY DSL	13
ODDS.....	13
SYNTHETIC ODDS	14
FIXTURES	15
FIXTURE GROUPS.....	15
COMPETITIONS.....	16
PLAYERS	16
TEAMS.....	16
MATCHDATA.....	17
SCORES DATA.....	17
SPORTS.....	18
BOOKMAKERS.....	18
COUNTRIES	19
ODDSTYPES.....	19
FUSION ADVANCED SUBSCRIPTION QUERY DSL.....	20
MARKETPERIODS	20
MARKETPARAMETERS	20

ADVANCED QUERY	20
EXACT MATCH (EQUALS) EXAMPLES	21
PARTIAL MATCH (INCLUDE) EXAMPLE	22
FURTHER EXAMPLE	22
ITEMS OF INTEREST	23
CONTEXT SHIPPING.....	24
USING TIMESTAMP	24
<i>Full Context</i>	24
<i>Partial Context</i>	24
USING LAST EVENT ID	25
USING DAYS AND HOURS FILTERS	26
<i>Hours=n Usage</i>	26
<i>Days=n Usage</i>	26
TXODDS STABLE PRICE.....	27
OVERVIEW	27
FEATURES	27
LIMITATIONS	27
STABLEPRICE BOOKMAKER NAMES.....	28
SPORTS AND MARKETS SUPPORTED	28
<i>Soccer</i>	28
<i>Tennis</i>	28
<i>Basketball</i>	29
<i>Baseball</i>	29
<i>US Football</i>	29
<i>Ice Hockey</i>	30
<i>Handball</i>	30
<i>Volleyball</i>	30
USAGE	30
SYNTHETIC BOOKMAKERS	32
OVERVIEW	32
SYNTHETIC QUERY DSL	32
MODES OF OPERATION	33
<i>Weighted Average</i>	33
<i>Evensline</i>	33
CONDITIONS	34
<i>Delay</i>	34
<i>Probability</i>	35
<i>Combining both Delay and Probability conditions</i>	36
DEMARGIN	36
DAMPEN	37
MULTIPLE SYNTHETIC BOOKMAKERS PER SUBSCRIPTION	37
SYNTHETIC DETAILS (DEBUG INFORMATION)	38
LINE HANDLING.....	40
FIXTURE NAMES AND PARTICIPANTS	41
OFF THE BOARDS - OTBS.....	42
MONITORING	43
APPENDICES	44
SAMPLE CLIENTS	44
MESSAGE EXAMPLES.....	45
ODDS	45
SYNTHETIC ODDS	47
FIXTURES	51

FIXTURE GROUPS.....	53
COMPETITIONS.....	54
PLAYERS	56
TEAMS.....	56
MATCHDATA.....	57
SCORES DATA.....	58
BOOKMAKERS.....	60
SPORTS	60
COUNTRIES	61
ODDSTYPES.....	61
MESSAGE IDENTIFICATION AND SEQUENCING.....	63
MESSAGEID.....	63
LASTEVENTID.....	63
TIMESTAMP - Ts.....	63
OFFERID AND OFFERIDHASH.....	64
SUPERODDSTYPES EXPLANATION.....	65
MATCH RESULT	65
TOTAL GOALS.....	66
OVER UNDER GOALS.....	67
EUROPEAN GOAL HANDICAP	68
ASIAN GOAL HANDICAP.....	69
PLAYER PROPS.....	70
SUPERODDSTYPES.....	71
DOCUMENT HISTORY	77
CHANGES	77
Version 1.24.....	77
Version 1.23.....	77
Version 1.22.....	77
Version 1.21.....	77
Version 1.20.....	77
Version 1.19.....	77
Version 1.18.....	78
Version 1.17.....	78
Version 1.16.....	78
Version 1.15.....	78
Version 1.13.....	78
Version 1.12.....	78
Version 1.11.....	78
Version 1.10.....	79
Version 1.09.....	79
Version 1.08.....	79
Version 1.07.....	79
Version 1.06.....	79
Version 1.05 DRAFT.....	79
Version 1.01 DRAFT.....	80
Version 1.00 DRAFT.....	80

Key Facts

Overview

- Fusion is a new product designed for streaming extremely low-latency odds.
- Reference data required to support the odds (fixtures, fixturegroups, competitions, matchdata, teams, players, bookmakers, sports, countries, and odds types) is supplied by the same mechanism and in the same format.
- Data for odds, fixtures, fixturegroups, competitions, teams, players and matchdata is supplied in a similar manner, and both context information and updates are available from the respective endpoints.
- Odds are classified using SuperOddsTypes an extensible method of concisely classifying odds to avoid issues encountered when mapping traditional odds types.

Content

- Low-latency data streams shipped via subscriber-specific channels.
- Integration, de-duplication and normalisation of raw source data into a unified representation known as SuperOddsTypes.
- A unique subscription query mechanism based on client-selected data cubes according to such dimensions as sports, bookmakers or odds types.
- Concurrent client subscriptions can be started or stopped independently. Each new subscription can start by optionally shipping a fully consistent context, i.e., all the offers corresponding to the specified subscription query or alternative options for “gap-filling”, i.e., to request messages between your last subscription and now.

All other offers (and associated timestamps) for the bookmakers specified in the query included with each update, simplifying the logic on the clients.

- Always adding new improvements to data consistency, sports coverage and latency optimisation.

Technology

- Fusion utilizes HTTP / Server-Sent Events (SSE) as a transport mechanism to stream the odds.
- This uses regular HTTP requests for the persistent connection, not a special protocol greatly simplifying the integration process.
- Connections are initiated by the client, and once connected the server will send events in text/event-stream format without closing the connection.
- Similar to WebSockets in that they happen in real time, SSE are a one-way read-only communication method from the server.
- SSE allows clients to automatically re-connect if the connection is interrupted and the data stream can be continued from the point of interruption, so no messages are lost.
- Unique IDs are sent with each message from the server allowing the client to send the most recent when reconnecting.
- It is possible to have many streams open at the same time with the SSE streams being multiplexed over the same physical connection.
- Compression can also be requested by the client to further reduce bandwidth consumption and decrease latency.
- Highly available, resilient and load tested Odds Distributor endpoints from which to consume data.
- Heartbeats are published by the Odds Distributor so Clients can monitor the status of the service.

Roadmap and Planned Future Enhancements

Future releases will optionally provide:

- Outright markets in addition to head to heads.
- TXPrice - industry standard price offered by TXODDS.
- Schema/key less messages i.e., if the consumer knows the message fields and order we can remove the keys and just send the values.
- Versioning.

Legacy Systems

TXODDS has several different feeds Trader (AHC), Market (xml2) & Push that can deliver information about competitions, fixtures, and odds. Although these systems are designed to inter-operate there are inevitably some issues e.g., AHC and xml2 both maintain their own identifier for the fixture. Most of the information across the feeds is consistent, so competitions, leagues, participants, countries, bookmakers, and sports will have the same identifiers and names across all feeds.

As the new fixtures system Merlin is introduced there will be a new identifier for fixtures, fixturegroups and competitions. These are referred to in this documentation as the Merlin IDs. In time Merlin will become the new source for all other information such as participants, countries, bookmakers, and sports and as such these will have a Merlin ID. For a period, many Merlin IDs will be the same as the AHC and xml2 IDs, however in time they will diverge the aim being Merlin will become the single authoritative source for all IDs across TXODDS.

Fusion makes use of Merlin IDs, but to protect existing customers investment in AHC and xml2 integration, the IDs generated by these systems will be available in the Fusion feed but marked as Legacy. Although this increases the payload of the messages, functionality in the system for "Items of Interest" allows customers to select which fields they would like to be supplied in the feed, and if not required Legacy fields do not need to be included in the subscription.

Users of Fusion will therefore be able to obtain all required information to support the odds subscriptions from Fusion itself without having to rely on other feeds. The customer experience and integration effort will be greatly simplified as all feeds will be delivered in a single, consistent manner.

General Architecture

The service allows a client to have one or more subscriptions concurrently, with each subscription's scope (or interest) expressed in a very simple subscription DSL.

The client application communicates with the server-side Odds Distributor component that authorises and manages all the current customer subscriptions.

Basic Fusion Streaming Features

Security

Odds Distributor endpoints are available only via HTTPS to provide encryption to ensure your requests are being sent to our servers and to protect the privacy and integrity of the exchanged data from malicious attacks or being read by a third party.

Customers will need to supply external facing IP addresses from which they will connect as these will have to be added to the allow list on the firewall.

Customer subscriptions will be required to supply credentials for authentication and access to the feeds.

Time Sensitivity

Each data request is time stamped to the millisecond, so you immediately know:

- when the data was last verified as accurate on our server whether the price has moved or is simply still the same as before.
- if a bookmaker site is down for maintenance or is currently overloaded and we can't get the price we won't update the timestamp until we can verify it again.
- allows you to decide what information you act upon. If you want to filter out anything over 10 minutes old, you can do so.

Data on Demand

TXODDS data is broken down into different market segments to allow you full control over what information you get and when you get it.

For example, you can request information by:

- sport e.g. Football/soccer by country or American football NCAA
- league or event e.g. English Premiership, Champions League etc.
- odds type e.g. Asian Handicap or 3Way Odds
- bookmaker e.g. only Ladbrokes and William Hill
- by time e.g. only updated odds since your last request

this allows the request size to be kept to a minimum and speed to a maximum.

Of course, if you want all international football league matches for all odds types and all bookmakers currently being quoted then you can have that too.

Depending on how much server resource and bandwidth you have you may want to split the requests into multiple sessions/requests for each sport.

Context & Updates Only

You can request only updates to the odds you are interested in, so no need to refresh the entire catalogue of event(s) constantly thereby reducing your server bandwidth and processing resources.

As mentioned earlier each odds price on our server has a timestamp declaring when it was last updated. Each time you make a request from our server we also send our server timestamp along with that request too. So, for example, you can request data from us that has changed in the last 30 seconds, 30 minutes as required, using the server timestamp.

Additionally, the Fusion feed transport uses Server Side Events/Eventsource which can provide an automatic request of missed messages. This may depend on the client language used, so please discuss with your support channel for further information.

Note: *For consumers that are used to the Push context shipping, Fusion has extended functionality that will also ship suspended/OTB messages from the past 2 hours.*

We send our server timestamp which is set to GMT to you to ensure that there are no time zone or clock synchronization problems. Wherever you are in the world or whatever time your local PC or server is set to will not affect the data we send you.

Timestamps and Daylight Savings

Please note feed times are always displayed in the UTC+0/GMT+0 time zone which does not change for daylight savings.

UTC/GMT is not the same as UK time, as during the summer months the UK changes to BST (British Summer time) which is GMT+1 hour.

Getting Started

TXODDS will supply you with a welcome email providing you with the following details:

Access and Authentication

- URLs for the UAT and Production environments.
- Credentials for authentication and access to the systems.
- Sample clients to get your integration effort started.

Firewall

Client external facing IP addresses will be required so they can be added to the Allow List.

Environments

Two separate environments are available for customers to use:

- UAT - <https://fusion-uat.txodds.com>
- Production - <https://fusion.txodds.com>

Customers will be provided with separate sets of credentials to use on the UAT and Production environments.

The UAT environment should be used for development and testing of client application integrations. Once these applications are debugged, signed off and working as expected with no performance issues the application may be deployed against the production environment.

Fusion Release Procedures

Customers will be notified in advance about releases to the UAT and Production environments.

Notifications will include details of additions and/or changes to the functionality, whether changes are breaking or not and a list of bug fixes. The dates and times of the release plus the expected duration of any downtime will also be included in the notification.

The notification will be sent out two weeks in advance for planned Production Releases.

Notifications will be sent two weeks in advance for UAT releases that contain changes to customer facing functionality allowing customers sufficient time to update and test their integrations prior to the production release.

Notifications for any unplanned Emergency Production Releases will be sent, however due to their nature these are to inform customers of impending emergency action to rectify serious production issues affecting the service quality.

Customers should provide a role-based email address which is monitored that notifications may be sent to.

Support Enquiries

Any questions please contact us via our support portal [TXODDS Support Service Desk](#)

Authentication

Customers will be required to authenticate with a username and password that will be supplied by TXODDS.

In addition, customers will have to supply their external facing IP address(es) that their subscription requests will be sent from.

These IP address(es) will be added to the Allow List on the TXODDS endpoints.

Event Types & Message format

The Fusion transport is based upon the HTML5 Server Side Events/Eventsource specification.

Message format

Once a session/connection is established, a stream of messages will be sent in the following format:

```
id: <messageId - optional>
event: <eventType - optional>
data: <event data - plain text, JSON, ... - mandatory>
```

id: A unique ID for this event (optional). The client can track these and request that the server stream events after the last one received in the event of the client becoming disconnected from the stream and reconnecting again. This is also known as the **Last-Event-ID**

event: Specifies the type of event in the case where one event stream may have distinctly different event types. This is optional and can be helpful for processing events on the client.

data: The message body, there can be one or more data key/pairs in a single event message.

Message Events

There are the following events available:

live

The live event will only ever have real-time messages i.e. a new offer/price is added or has changed, or is suspended.

context

The context event will only ever have messages sent from the context or last price cache. These should only be seen when the consumer asks for last price data.

Note: For consumers that are used to the Push context shipping, Fusion has extended functionality that will also ship suspended/OTB messages from the past 2 hours.

synthetics

The synthetics event will only provide real-time messages for synthetic bookmaker subscriptions.

heartbeat

The heartbeat event will only ever have messages that show that the stream is still active/connected to the server. It may be possible at certain times there will not be real-time updates, so the consumer can use this event to determine if they are still connected.

Note: *For consumers that are used to the Push heartbeats, Fusion heartbeats show the current stream/session is still active as opposed to Push where heartbeats are based on the server being active*

bookmakers

The bookmakers event will return a list of bookmakers but will not stream any updates.

sports

The sports event will return a list of sports but will not stream any updates.

countries

The countries event will return a list of countries but will not stream any updates.

oddstypes

The oddstypes event will return a list of oddstypes but will not stream any updates.

Additional event types

Other events may be added in the future.

Fusion Basic Subscription Query DSL

Requests in the form *.* for all sports, all bookmakers, all markets are no longer supported. Parameters are case-sensitive, values are case-insensitive.

Non ascii characters and spaces in values should be escaped, e.g. Sport=ice%20hockey.

Valid values for required and optional parameters can be obtained from the /fixtures, /fixturegroups, /competitions, /sports, /bookmakers, /oddstypes and /countries endpoints.

Odds

To subscribe to the /odds endpoint and receive a stream of odds messages:

Required parameters:

- Bookmaker
- Sport
- SuperOddsType
- InRunning (true,false,all)

Optional parameters:

- CompetitionId
- Competition (wildcard)
- FixtureGroupId
- FixtureGroup (wildcard)
- Country
- ExtraFields
- Days
- Hours
- Ts (timestamp)

Wildcard queries:

- "xxx_" starts with "xxx_", "*_yyy" ends with "_yyy", "*_zzz_" includes "_zzz_"

Multiple parameters as comma separated values:

- Sport=x,y,z

E.g. return all updates where:

- Bookmaker: bwin, 1Xbet, ladbrokes
- Sport: Table tennis, Soccer, Tennis
- SuperOddsType: MONEYLINE_PARTICIPANT_RESULT
- InRunning: pre-game
- CompetitionId: 66, 1550366, 1550361

```
"/odds?Bookmaker=bwin,1Xbet,ladbrokes&Sport=Tennis,Soccer,Table%20tennis&SuperOddsType=MONEYLINE_PARTICIPANT_RESULT&InRunning=false&CompetitionId=66,1550366,1550361"
```

E.g. return all updates where:

- Bookmaker: bwin, 1XBet, ladbrokes
- Sport: Table tennis, Soccer, Tennis
- SuperOddsType: MONEYLINE_PARTICIPANT_RESULT, CORRECTSCORE_PARTICIPANT_GOALS

- InRunning: pre-game and in-play
- Country: International

```
"/odds?Bookmaker=bwin,1xBet,ladbrokes&Sport=Table%20tennis,Soccer,Tennis&SuperOddsType=
MONEYLINE_PARTICIPANT_RESULT,CORRECTSCORE_PARTICIPANT_GOALS&InRunning=all&Country=Intern
ational"
```

E.g. return all updates where:

- Bookmaker: bwin, 1xBet, ladbrokes, betway
- Sport: Table tennis
- SuperOddsType: ASIANHANDICAP_PARTICIPANT_GOALS, OVERUNDER_PARTICIPANT_GOALS
- InRunning: in-play only
- Competition: TT*, Pro*

```
"/odds?Bookmaker=bwin,1xBet,ladbrokes,betway&Sport=Table%20tennis&SuperOddsType=
ASIANHANDICAP_PARTICIPANT_GOALS, OVERUNDER_PARTICIPANT_GOALS
&InRunning=true&Competition=TT*,Pro*"
```

Synthetic Odds

Required parameters:

- Sport
- SuperOddsType
- InRunning (True/False/All)
- Synth (Id and bookmaker weighting definition)

Optional parameters:

- CompetitionId
- Competition (wildcard)
- FixtureGroupId
- FixtureGroup (wildcard)
- Country (wildcard)
- ExtraFields
- Days
- Hours
- Delay
- Prob

Wildcard queries:

- "yyy_*" starts with "yyy_ "

Multiple parameters as comma separated values:

- Sport=x,y,z

E.g. return all synthetic average price updates where:

- Sport: soccer
- SuperOddsType: 1X2_PARTICIPANT_RESULT
- InRunning: All
- Synth: 17+42+84 (Ladbrokes, William Hill, Paddy Power)

```
"/synthetic_odds?Sport=soccer&SuperOddsType=1X2_PARTICIPANT_RESULT&InRunning=All&Synth=8
888:17+42+84"
```

Fixtures

To subscribe to the /fixtures endpoint and receive a stream of fixtures messages:

Required parameters:

- Sport

Optional parameters:

- CompetitionId
- Competition (wildcard)
- FixtureGroupId
- FixtureGroup (wildcard)
- Country (wildcard)
- ScoresCaptureTracking
- ExtraFields
- Days
- Hours
- Ts (timestamp)

Wildcard queries:

- "yyy_*" starts with "yyy_"

Multiple parameters as comma separated values:

- Sport=x,y,z

To get a list of currently available soccer and tennis fixtures:

```
"/fixtures?Sport=soccer,tennis&Ts=0"
```

To find out which fixtures might have Scores Data coverage:

```
"/fixtures?Sport=us%20football&Ts=0&ScoresCaptureTracking=true&ExtraFields=CoverageStatus,CoverageType,CoverageSecondaryData"
```

Fixture Groups

To subscribe to the /fixturegroups endpoint and receive a stream of fixturegroups messages:

Required parameters:

- Sport

Optional parameters:

- CompetitionId
- Competition (wildcard)
- FixtureGroupId
- FixtureGroup (wildcard)
- Country (wildcard)
- ExtraFields
- Ts (timestamp)

Wildcard queries:

- “yyy_” starts with “yyy_”

Multiple parameters as comma separated values:

- Sport=x,y,z

```
"/fixturegroups?Sport=soccer,tennis"
```

Competitions

To subscribe to the /competitions endpoint and receive a stream of competitions messages:

Required parameters:

- Sport

Optional parameters:

- CompetitionId
- Competition (wildcard)
- Country (wildcard)
- ExtraFields
- Ts (timestamp)

Wildcard queries:

- “yyy_” starts with “yyy_”

Multiple parameters as comma separated values:

- Sport=x,y,z

```
"/competitions?Sport=soccer,tennis"
```

Players

To subscribe to the /players endpoint and receive a stream of player messages:

Required parameters:

- Sport

Optional parameters:

- Gender
- Ts (timestamp)
- ExtraFields

Multiple parameters as comma separated values:

- Sport=x,y,z

```
"/players?Sport=soccer,tennis&Ts=0"
```

Teams

To subscribe to the /teams endpoint and receive a stream of team messages:

Required parameters:

- Sport
-

Optional parameters:

- Gender (male, female, mixed)
- Ts (timestamp)

Multiple parameters as comma separated values:

- Sport=x,y,z

```
"/teams?Sport=soccer,tennis&Ts=0"
```

Matchdata

To subscribe to the /matchdata endpoint and receive a stream of regular time soccer matchdata messages:

Optional parameters:

- Ts (timestamp)

```
"/matchdata"
```

Note: Matchdata is consensus data originating from several different sources. The matchdata is provided with the caveat that it is not from an agent feed and so should be used with caution and maybe not for trading purposes.

Scores Data

To subscribe to the /scores endpoint and receive a stream of scores messages:

Optional parameters:

- Sport
- Ts (timestamp)
- FixtureId
- VirtualFixtures (True/False) False assumed by default
- CompetitionId
- Competition (wildcard e.g. abc*)
- FixtureGroupId
- FixtureGroup (wildcard e.g. abc*)
- CountryId
- Country (wildcard e.g. abc*)
- Days
- Hours
- ExtraFields

Multiple parameters as comma separated values:

- FixtureId=x,y,z

To get live updates for any basketball fixture that has Score Data available:

```
"/scores?Sport=basketball"
```

To get the history and live updates for specific fixtures that have Score Data available:

```
"/scores?Ts=0&FixtureId=123456789,234567890"
```

To get history and updates for any NBA basketball fixture that has Score Data available:

```
"/scores?Sport=basketball&Ts=0&CompetitionId=300013"
```

Note: *CompetitionId's are available from the /competitions endpoint.*

To request replay of an historic fixture with scores data:

```
"/scores?Ts=0&VirtualFixtures=true&FixtureId=1016714924"
```

Note: *to request replay of historic scores fixtures please contact the support team via your Slack channel or TXODDS Support Service Desk:*

<https://txodds.atlassian.net/servicedesk/customer/portals>

Note: *when requesting replay of historic scores fixtures, the FixtureId value should use the VirtualFixtureId available in the Client Viewer.*

Note: *Check the /fixtures endpoint **ScoresCaptureTracking=True** and **ExtraFields CoverageType** and **CoverageStatus** to see if ScoresData coverage for the fixture might be available.*

Note: *There is a slight difference in the response when requesting Full Context using Ts=0. All other endpoints will provide the current state e.g. the Odds endpoint will return the current state of all available offers. The Scores endpoint will however provide a history of the messages rather than current state, but otherwise Ts works the same, messages greater than or equal to the timestamp will be returned.*

Sports

To obtain an up to date and current, static list of sport names that can be used when requesting Odds, Fixtures, FixtureGroups and Competition subscriptions. **Note:** *this is not a streaming endpoint.*

```
"/sports"
```

Bookmakers

To obtain an up to date and current, static list of bookmaker names that can be used when requesting Odds subscriptions. **Note:** *this is not a streaming endpoint.*

```
"/bookmakers"
```

Countries

To obtain an up to date and current, static list of country names that can be used when requesting Odds, Fixtures, Fixturegroups and Competition subscriptions. **Note:** *this is not a streaming endpoint.*

```
"/countries"
```

Oddstypes

To obtain an up to date and current, static list of oddstypes that can be used when requesting Odds subscriptions. **Note:** *this is not a streaming endpoint.*

```
"/oddstypes"
```

Fusion Advanced Subscription Query DSL

Advanced Query allows the SuperOddsTypes MarketPeriod and MarketParameters to be filtered in conjunction with the basic parameters discussed in the previous section, giving a far greater degree of control over which offers are returned by the subscription.

MarketPeriods

These are absolutely defined or indirectly identifiable characteristics of the betting market in question and are expressed as comma delimited flags or key=value pairs, examples in the table below.

Sport	Time Period	SuperOddsType MarketPeriod
Soccer	first half	half=1
	second half	half=2
	full time	null
	extra time	et
	extra time first half	et,half=1
	after the first 15 minutes	between=[00:00;14:59]
Tennis	first set	set=1
	current set	set=current
	set, game	set=2,game=5
	set, game, point	set=4,game=3,point=2

Note: currently full-time markets are not explicitly identified unlike say first-half or second-half markets, e.g. a soccer full-time result market (1X2_PARTICIPANT_RESULT) will have MarketPeriod: null and first-half result market will have MarketPeriod: half=1.

MarketParameters

A market can have zero or more parameters depending on the nature of the market and these are expressed as comma delimited key=value pairs, examples in the table below.

Sport	Parameter	SuperOddsType MarketParameters
Soccer	home team	participants=part1
	away team	participants=part2
	correct score	correctscore=1:0
	over under goal line	line=3.5
	asian handicap line	line=-1.25
	away team over under goal line	line=2.5,participants=part2
Tennis	player one	participants=part1
	player two over under games	line=12.5,participants=part2
	winning score	winningscore=7:6

Advanced Query

Advanced Query is based on Disjunctive Normal Form (DNF) and allows MarketPeriod and MarketParameters to be filtered using the following operators:

- "," = AND
- "|" = OR
- [] = partial match - must contain fields listed but can contain more.
- < > = exact match - fields requested and fields present in the message must match.

Exact Match (Equals) Examples

If only soccer full time match result markets are required:

```
Sport=soccer
SuperOddsType=1X2_PARTICIPANT_RESULT
MarketPeriod=<null>
```

full time OR first half match result markets:

```
Sport=soccer
SuperOddsType=1X2_PARTICIPANT_RESULT
MarketPeriod=<null|half=1>
```

full time OR first half OR second half match result markets:

```
Sport=soccer
SuperOddsType=1X2_PARTICIPANT_RESULT
MarketPeriod=<null|half=1|half=2> alternatively MarketPeriod=<null|half=*>
```

Notes

If any (all) values for a particular key are required then it is possible to request key=*, or as in the example above half=* for both halves.

In the examples above markets for other periods of play such as first fifteen minutes result "between=[00:00;14:59]" would be omitted. Use of the < > brackets mean an exact match only will be returned.

soccer fulltime over under 1.5 goals market only is required:

```
Sport=soccer
SuperOddsType=OVERUNDER_PARTICIPANT_GOALS
MarketPeriod=<null>
MarketParameters=<line=1.5>
```

If tennis match result OR set result OR current game result markets are required:

```
Sport=tennis
SuperOddsType=MONEYLINE_PARTICIPANT_RESULT
MarketPeriod=<null|set=*|game=current>
```

any set AND the game has gone to a tiebreak:

```
Sport=tennis
SuperOddsType=MONEYLINE_PARTICIPANT_RESULT
MarketPeriod=<set=*,game=tiebreak>
```

set 1 only markets:

```
Sport=tennis
SuperOddsType=MONEYLINE_PARTICIPANT_RESULT
MarketPeriod=<set=1>
```

Partial Match (Include) Example

If **any** tennis result markets from the first set are required:

```
Sport=tennis
SuperOddsType=MONEYLINE_PARTICIPANT_RESULT
MarketPeriod=[set=1]
```

this will return any message where “set=1” is included in the MarketPeriod:

MarketPeriod: set=1	will be sent
MarketPeriod: set=1,game=1	will be sent
MarketPeriod: set=1,game=1,point=1	will be sent
MarketPeriod: set=1,game=1,tiebreak	will be sent
MarketPeriod: set=2	will not be sent
MarketPeriod: set=2,game=1	will not be sent
MarketPeriod: set=current	will not be sent
MarketPeriod: set=next	will not be sent
MarketPeriod: null	will not be sent

Further Example

A more complicated example requesting soccer full time OR first half periods plus 1X2, over under and asian handicap markets.

This time in addition to the MarketPeriods, MarketParameters should be filtered to allow markets that have empty MarketParameters OR over under goal/asian handicap line-based markets of the form line=*

The null value will allow the 1X2 markets to be returned, line=* allows the overunder goal lines and asian handicap lines to be returned.

Additionally the line=* will exclude home and away team over under markets of the form line=0.5,participants=part1 as an exact match is being requested.

Putting it all together:

```
Sport=soccer&
Bookmaker=188bet&
SuperOddsType=1X2_PARTICIPANT_RESULT,OVERUNDER_PARTICIPANT_GOALS,ASIANHANDICAP_PARTICIPANT_GOALS&
InRunning=All&
MarketPeriod=<null|half=1>&
MarketParameters=<null|line=*>
```

Note: subscriptions such as the above will need to be URL Encoded.

Note: when submitting queries, MarketPeriod and MarketParameter values are case sensitive.

Items of Interest

Items of Interest allow customers to control the fields that are included in the message response from the odds, synthetic_odds, fixtures, fixturegroups and competitions endpoints. Particularly where odds are concerned the payload of the message is important when considering how to reduce latency as much as possible.

By default, each of the relevant Fusion endpoints has had its payload reduced to the bare minimum by no longer shipping redundant data and removing non-essential information. If customers require additional fields to be included in the response, then they can specify these using the optional ExtraFields parameter.

Looking at the odds message for instance, there is information about sports, competitions, fixturegroups, fixtures, participants, legacy Id's, 3rdparty Id's etc. all of which could be obtained from other endpoints, with only the FixtureId being necessary to link to the other data.

Details of which fields are included as default in each of the message types are documented in the Appendices of this guide.

In the example query below the default odds message is requested along with the additional fields Country, Competition and OfferIdHash specified in the ExtraFields parameter:

```
"/odds?Sport=soccer&Bookmaker=ladbrokes&SuperOddsType=1X2&InRunning=All&Ts=0&ExtraFields=Country,Competition,OfferIdHash"
```

The message response will be as follows:

```
{
  "FixtureId":10852670,
  "Participant1IsHome":true,
  "BookmakerParticipantsReordered":false,
  "BookmakerId":17,
  "InRunning":false,
  "Country":"England",
  "Competition":"Premier League",
  "IsTeam":true,
  "StartTime":"2021-08-22T15:30:00Z",
  "MessageId": "1681406235:00001:006687",
  "SuperOddsType":"1X2_PARTICIPANT_RESULT",
  "MarketPeriod":"half=1",
  "MarketParameters":null,
  "PriceNames":["part1","draw","part2"],
  "Prices":[4.800,2.050,2.450],
  "LineId":1,
  "Ts":1629128718269,
  "OfferIdHash":"f85dff6c7d82dadb050fb1e72a8f6cc54d6498f2"
}
```

The ExtraFields parameter is available for use on the following endpoints - /odds, synthetic_odds, /fixtures, /fixturegroups and /competitions.

Context Shipping

When a client subscribes to Fusion, by default all that is returned will be a live stream of new offer updates that match the subscription DSL constraints.

For example, if you are subscribing to sport = soccer, bookmaker = sbobet and offer = full-time match result, then only live odds for these constraints will be shipped.

This is intentional and is designed to keep the amount of information transferred to a minimum and ensure the best possible latency.

In order to request messages from the context or price cache there are currently 2 options to provide the consumer control of what data is shipped.

Note: For consumers that are used to Push context shipping, Fusion has extended functionality that will also ship suspended/OTB messages from the past 2 hours.

Using Timestamp

If context information is required, then it is possible to request this using the Ts timestamp filter.

Full Context

If you want the full context shipped i.e. the current state of all available offers, then Ts should be set to zero:

```
"/odds?Sport=Soccer&Bookmaker=sbobet&SuperOddsType=1X2_PARTICIPANT_RESULT&InRunning=All&Ts=0"
```

If clients are connecting for the first time or if they have been disconnected for a period of time greater than 2hrs, then it is recommended they reconnect using Ts=0.

While the context is being shipped, the event status field in the message will be set to the value "context" and once the context has been shipped the value in the field will change to "live":

```
data:
{
  "FixtureId":10314740,
  "ParticipantIsHome":true,
  "BookmakerId":327,
  "InRunning":false,
  "IsTeam":true,
  "StartTime":"2021-01-17T16:30:00z",
  "MessageId": "1681406407:00001:011400",
  "SuperOddsType":"1X2_PARTICIPANT_RESULT",
  "MarketPeriod":null,
  "MarketParameters":null,
  "PriceNames":["part1","draw","part2"],
  "Prices":[2.820,3.110,2.660],
  "LineId":1,
  "Ts":1610899268359
}
event: context
id: 4281108427.0
```

Partial Context

The subscription query filter called Ts limits the messages sent to only those messages that have the value of the timestamp Ts greater than the specified value in the Javascript epoch time (UNIX timestamp*1000) in milliseconds.

For example, the following query will only ship the messages with Ts > 1610899268358

```
"/odds?Sport=Soccer&Bookmaker=sbobet&SuperOddsType=1X2_PARTICIPANT_RESULT&InRunning=All&Ts=1610899268358"
```

Note: The Ts option only affects the context message shipment, you will still receive all new updates to all offers, for all matches, based on your client subscription.

Note: The Ts filter will supply the current state of all available offers, it will not supply Suspensions and OTBs. This is identical to the way the existing Push feed works. If Suspensions and OTBs are required, please use the Last-Event-Id as documented in the following section.

Note: When requesting context, the sequence the messages are delivered in has no deterministic ordering whatsoever.

Note: When requesting context, both context and live messages are shipped in parallel, logic has been implemented however to ensure live messages are not overwritten by subsequent "stale" context messages.

Note: There is a slight difference in the response when requesting Full Context using Ts=0 and the Scores endpoint. All other endpoints will provide the current state e.g. the Odds endpoint will return the current state of all available offers. The Scores endpoint will however provide a history of the messages rather than current state, but otherwise Ts works the same, messages greater than or equal to the timestamp will be returned.

Using Last Event ID

Each message in the odds stream is sent with a Unique Id, see below:

```
data:{
  "Ts":1762178263147,
  "Prices":[2.820,3.110,2.660],
  "PriceNames":["part1","draw","part2"],
  "MarketParameters":null,
  "MarketPeriod":null,
  "SuperOddsType":"1X2_PARTICIPANT_RESULT",
  "MessageId":"1800678285:00003:000130",
  "StartTime":"2025-11-03T20:00:00Z",
  "IsTeam":true,
  "InRunning":false,
  "BookmakerId":327,
  "Participant1IsHome":true,
  "Participant2":"Everton",
  "Participant1":"Sunderland",
  "FixtureId":16948081
}
event:live
id:1762178263147.65
```

The client application should keep track of this Id and if it disconnects for some reason, when it reconnects, it can send the Last-Event-Id and will receive all messages from the point of interruption onwards, so no messages are lost.

In the example message above the value "id:1762178263147.65" would be sent in the Last-Event-Id field to the server.

As mentioned previously, Fusion uses SSE and Last-Event-Id is part of the SSE protocol which allows servers to push updates to clients over HTTP. Each message from the server will include a unique Last-Event-Id. Use of Last-Event-Id ensures reliability and that clients don't miss events during disconnections. Servers will send only missed events rather than resending all data reducing bandwidth and processing overhead.

Fusion maintains a cache of offers including Suspensions and OTBs for approximately the last 2 hours. If all the messages in the cache are required, the client should request these by sending Last-Event-Id = 0. If clients are disconnected for more than 2 hrs it is recommended they acquire Full Context again - the current state of all available offers, see previous section.

Examples of how to send the Last-Event-Id value to the server are included in the example clients that TXODDS provides.

Note: *It is recommended that clients use Last-Event-Id when reconnecting, if they have been disconnected for less than 2 hrs.*

Note: *When Last-Event-Id is used the response will contain Suspensions/Off the Boards (OTBs).*

Using Days and Hours Filters

When sending subscriptions for fixtures and odds, by default all available future fixture updates or odds updates for all available future fixtures will be supplied. If requesting context too this can result in a large amount of data being returned and this may not be what is required.

The Days and Hours filters allow control over how far into the future the subscription will return fixtures and odds for related to the start time of the fixture. A "sliding window" will be created that is constantly moving into the future from now until the time-period defined in the filter.

For example, sending a fixtures subscription with a filter Days=2 will return fixture updates whose fixture start time is between now and 2 days from now. The sliding window created will continue to return fixture updates as time progresses whose fixture start-times are no greater than 2 days from now.

Similarly, a subscription for odds with a filter Hours=6 will only return odds updates for fixtures whose start time is between now and 6 hours from now. As before a sliding window is created constantly moving into the future.

If context is requested (using Ts=timestamp or Ts=0) in conjunction with the Days or Hours filter, then only context for the fixtures or odds that are a result of the Days or Hours filter will be returned.

Hours=n Usage

Where n is a positive integer 1 or greater.

The following example subscription is for 1X2 pre-game and in-play odds from Ladbrokes for soccer fixtures whose start time is in the next 12 hours together with the context.

```
"/odds?Sport=Soccer&Bookmaker=Ladbrokes&SuperOddsType=1X2_PARTICIPANT_RESULT&InRunning=A11&Ts=0&Hours=12"
```

Days=n Usage

Where n is a positive integer 1 or greater.

The following example subscription requests soccer fixtures whose start times are in the next 7 days along with the context.

```
"/fixtures?Sport=Soccer&Ts=0&Days=7"
```

TXODDS Stable Price

Overview

- TXStableprice will provide both a de-marginated and marginated average market price using a blend of bookmaker's prices for core markets based upon a variety of factors leveraged by analysis from our market intelligence and historical data product set.
- Stability/availability - from our analytics we track and report on the bookmakers uptime i.e. frequency and length of pricing and OTBs plus the source website/feed availability metrics.
- Coverage - which bookmakers also cover the most events and markets.
- Market experience - the global betting know which bookmakers price "accurately" and are less prone to errors or delays in updating / repricing following goals and in-play incidents.
- Best of Breed - use different blends of bookmakers per sport.
- By knowing where the market is pricing a match customers can track whether their own pricing is "in or out" of the market in real-time by re-margining based on their models and act accordingly (re-price and / or suspend until they find the issue or notify traders to make a call on the risk).

Features

The Pipeline is as follows:

- TXStablePrice will be available no earlier than 3 days prior to the fixture although updates are processed up to 8 days before the fixture.
- Baseline price availability - i.e. we set a limit to say we must have X out of Y bookmakers to produce a price for further calculations to be made and that these prices are within the defined time windows for pre-game and in-play. The time windows vary (shorten) depending on the proximity of the fixture in question.
- The Baseline / Incoming prices are then *demargined*.
- The demargined prices are then converted to *implied probabilities*.
- We check there is a consensus i.e. supremacy probabilities are within a defined range and are similarly aligned otherwise we send an OTB.
- Further defensive measures are applied to remove outliers and arbitrage opportunities and ensure a consensus.
- Consensus probability is then converted back to a price and emitted as the TXStablePrice.

Limitations

- Not all markets are supported see the sports and markets section below.
- Incomplete markets, i.e. we need all legs to have a valid price, so where for example there is no home price when a team is leading 6-0 with 5 minutes to go etc.
- All bookmakers need to be offering the same market legs to achieve a consensus.

Note: *There used to be a limitation whereby lengthy delays to in-play updates from bookmakers (caused by VAR, injuries and period breaks) might cause the price to go OTB as a time window is used to determine validity. This limitation has been removed, and an algorithm employing a sliding time window now mitigates this issue.*

StablePrice Bookmaker Names

The earlier sport specific naming convention e.g. TXStablePriceSoccer or TXStablePriceTennisDemargined will continue for the time being so existing subscriptions will be unaffected. These names will however be removed during Q1 2024, notifications will be sent in advance. Client applications should use the new naming convention going forward. There are now just two bookmaker names that should be used in subscriptions. Use of the mandatory Sport parameter in the subscription will determine which odds are returned for which sport in a similar way to other bookmakers:

- TXStablePrice
- TXStablePriceDemargined

Sports and Markets Supported

Soccer

In addition to StablePrice bookmakers with a three day lead in time, there are also StablePrice bookmakers with an fourteen day lead in time for soccer only.

TXStablePrice and TXStablePriceDemargined (three day) SuperOddsTypes supported:

- 1X2_PARTICIPANT_RESULT
- ASIANHANDICAP_PARTICIPANT_GOALS
- ASIANHANDICAP_PARTICIPANT_CORNERS
- ASIANHANDICAP_PARTICIPANT_BOOKINGS
- OVERUNDER_PARTICIPANT_GOALS
- OVERUNDER_PARTICIPANT_CORNERS
- OVERUNDER_PARTICIPANT_BOOKINGS
- EUROHANDICAP_PARTICIPANT_GOALS
- 3WAYHANDICAP_PARTICIPANT_GOALS

TXStablePriceEarly and TXStablePriceEarlyDemargined (fourteen day) SuperOddsTypes supported:

- 1X2_PARTICIPANT_RESULT
- ASIANHANDICAP_PARTICIPANT_GOALS
- OVERUNDER_PARTICIPANT_GOALS

The following market periods are supported:

- Full-time
- First-half

Tennis

StablePrice bookmakers with a three day lead in time are available for tennis.

TXStablePrice and TXStablePriceDemargined SuperOddsTypes supported:

- MONEYLINE_PARTICIPANT_RESULT
- EUROHANDICAP_PARTICIPANT_GAMES
- OVERUNDER_PARTICIPANT_GAMES

The following market periods are supported:

- Full-time

Basketball

StablePrice bookmakers with a three day lead in time are available for basketball.

TXStablePrice and TXStablePriceDemargined SuperOddsTypes supported:

- MONEYLINE_PARTICIPANT_RESULT
- EUROHANDICAP_PARTICIPANT_POINTS
- OVERUNDER_PARTICIPANT_POINTS

The following market periods are supported:

- Full-time
- First-quarter
- First-half

Baseball

StablePrice bookmakers with a three day lead in time are available for baseball.

TXStablePrice and TXStablePriceDemargined SuperOddsTypes supported:

- MONEYLINE_PARTICIPANT_RESULT
- EUROHANDICAP_PARTICIPANT_RUNS
- OVERUNDER_PARTICIPANT_RUNS

The following market periods are supported:

- Full-time
- First-five innings

US Football

StablePrice bookmakers with a six week lead in time are available for US Football.

TXStablePrice and TXStablePriceDemargined SuperOddsTypes supported:

- MONEYLINE_PARTICIPANT_RESULT
- EUROHANDICAP_PARTICIPANT_POINTS
- OVERUNDER_PARTICIPANT_POINTS

The following market periods are supported:

- Full-time
- First-half
- First-quarter

Ice Hockey

StablePrice bookmakers with a three day lead in time are available for ice hockey.

TXStablePrice and TXStablePriceDemargined SuperOddsTypes supported:

- 1X2_PARTICIPANT_RESULT
- MONEYLINE_PARTICIPANT_RESULT
- EUROHANDICAP_PARTICIPANT_GOALS
- OVERUNDER_PARTICIPANT_GOALS

The following market periods are supported:

- Full-time
- Full-time including overtime
- First-period

Handball

StablePrice bookmakers with a three day lead in time are available for Handball.

TXStablePrice and TXStablePriceDemargined SuperOddsTypes supported:

- 1X2_PARTICIPANT_RESULT
- EUROHANDICAP_PARTICIPANT_GOALS
- OVERUNDER_PARTICIPANT_GOALS

The following market periods are supported:

- Full-time

Volleyball

StablePrice bookmakers with a three day lead in time are available for Volleyball.

TXStablePrice and TXStablePriceDemargined SuperOddsTypes supported:

- MONEYLINE_PARTICIPANT_RESULT
- EUROHANDICAP_PARTICIPANT_POINTS
- OVERUNDER_PARTICIPANT_POINTS

The following market periods are supported:

- Full-time

Usage

Example subscriptions are shown below to demonstrate the usage of the StablePrice bookmakers.

Soccer three-day lead in time and marginated prices:

```
"/odds?Sport=soccer&Bookmaker=TXStablePrice&SuperOddsType=1X2_PARTICIPANT_RESULT,
ASIANHANDICAP_PARTICIPANT_GOALS, OVERUNDER_PARTICIPANT_GOALS,
EUROHANDICAP_PARTICIPANT_GOALS, 3WAYHANDICAP_PARTICIPANT_GOALS&InRunning=All&Ts=0"
```

Soccer eight-day lead in time demarginated prices:

```
"/odds?Sport=soccer&Bookmaker=TXStablePriceEarlyDemargined&SuperOddsType=1X2_PARTICIPANT
_RESULT, ASIANHANDICAP_PARTICIPANT_GOALS, OVERUNDER_PARTICIPANT_GOALS&InRunning=All&Ts=0"
```

Basketball three-day lead in time marginated and demarginated prices:

```
"/odds?Sport=basketball&Bookmaker=TXStablePrice, TXStablePriceDemargined&
SuperOddsType=MONEYLINE_PARTICIPANT_RESULT, EUROHANDICAP_PARTICIPANT_POINTS, OVERUNDER_PAR
TICIPANT_POINTS&InRunning=All&Ts=0"
```

The number of price updates emitted by StablePrice can be dampened (see Synthetic Bookmakers, Dampen section) as follows:

```
"/synthetic_odds?Sport=soccer&SuperOddsType=1X2_PARTICIPANT_RESULT&InRunning=True&Synth=
8888:10010 and dampen=percent_diff"
```

Where:

BookmakerId = 10010

Bookmaker = TXStablePrice

Synthetic Bookmakers

Overview

Fusion synthetics allows customers to define a consensus view of the market based on subscriptions to underlying bookmakers. Certain bookmaker prices may be considered better than others for a particular application and synthetics allows you to define a formula to create a new synthetic bookmaker price based on these chosen bookmakers.

You can subscribe to this synthetic bookmaker and when any of the chosen bookmaker prices change, the synthetic bookmaker's consensus price will be recalculated, and updates delivered in the same way as for a standard bookmaker.

It is possible to add a weighting to bookmakers to reflect their relative importance in certain modes of operation. Conditions for delay periods and probabilities can also be added to the definition to further control the offers that are admitted into the consensus allowing a fine degree of control over the pre-game and in-play synthetic prices that are generated.

Note: *Unlike Push synthetics, messages for the underlying bookmakers in Fusion synthetics are not returned by the subscription, only the synthetic bookmaker messages are supplied substantially reducing the volume of data that needs to be consumed by client applications.*

Synthetic Query DSL

This is a basic extension of the Fusion Query DSL already outlined in earlier sections of this guide. The Synthetic Query DSL works in a similar manner to that of the /odds endpoint, the main differences are detailed below:

- A synthetic parameter is required which details the synthetic Bookmaker Id that will be used, the standard bookmakers to include in the calculations and optional weightings to be applied to the bookmakers.
- The Bookmakers parameter is no longer required, bookmakers are specified in the synthetic definition.
- Bookmaker Ids are used in the synthetic definition rather than the Bookmaker Names to keep the definition as compact as possible.
- Bookmaker Ids can be obtained from the /bookmakers endpoint.
- The Ts parameter used for requesting context information is not applicable in this situation. Prices are only emitted for live updates and are not available from the context.
- Synthetic subscriptions will need to be URL encoded.

To define a new synthetic bookmaker add a synthetic definition to the subscription in the form:

```
Synth=Synthetic BookmakerId:[weighting*] BookmakerId + [weighting*] BookmakerId + ...
```

- Synthetic BookmakerId - a number in the range 1001 to 9999
- Bookmaker weighting definition - a string of "+" separated BookmakerIds with optional weightings.
- Weighting - if the BookmakerId is prefixed by a positive integer and a "*" a weighting will be applied to that bookmaker. If the BookmakerId has no prefix then the bookmaker will be included without any weighting, a value of 1 is implied.

To create a synthetic bookmaker synth8888 based on bookmakers Ladbrokes (17), William Hill, (42) and PaddyPower (84) with weightings 1, 3 and 5 respectively the definition would be as follows:


```
Synth=8888:17+3*42+5*84
```

Modes of Operation

Fusion synthetics currently has two basic modes of operation, either (weighted) average mode or evensline mode.

Weighted Average

In this mode it is possible to define which bookmakers are to be included in the synthetic calculation and an optional weighting that can be applied to each bookmaker. Absence of any weighting value being specified implies a weighting of one.

To calculate average synthetic prices with the following definition:

- Sport = Soccer
- Market = 1X2_PARTICIPANT_RESULT
- InRunning = pregame and in-play
- Synthetic Bookmaker Id = 8888
- Bookmakers = Ladbrokes (17), William Hill, (42) and PaddyPower (84)
- Weighting = 1 to be applied to each bookmaker.
- Mode = average (this is the default mode and can in practice be omitted if desired)

```
"/synthetic_odds?Sport=soccer&SuperOddsType=1X2_PARTICIPANT_RESULT&InRunning=All&Synth=8888:17+42+84 and mode=average"
```

To calculate weighted average synthetic prices with the following definition:

- Sport = Soccer
- Markets = 1X2_PARTICIPANT_RESULT, ASIANHANDICAP_PARTICIPANT_GOALS, OVERUNDER_PARTICIPANT_GOALS
- InRunning = in-play only
- Synthetic Bookmaker Id = 7777
- Bookmakers = IBCbet (285), SBObet (327), and 188bet (365)
- Weightings = 1, 3 and 5 to be applied respectively to the bookmakers above
- Mode = average (this is the default mode and can in practice be omitted if desired)

```
"/synthetic_odds?Sport=soccer&SuperOddsType=1X2_PARTICIPANT_RESULT,ASIANHANDICAP_PARTICIPANT_GOALS,OVERUNDER_PARTICIPANT_GOALS&InRunning=True&Synth=7777:285+3*327+5*365"
```

Evensline

This mode of operation allows definition of the bookmaker to be included in the calculation of the evens (best, main, most equitable) line on markets with multiple lines e.g. Over Unders or Asian Handicaps. The evensline is defined as the line with the smallest pips value. The pips value is the absolute value of the following expression:

| odds_home - odds_away |

Only a single bookmaker can be included in the synthetic query if the evensline mode is being used.

Markets with only single lines such as 1X2_PARTICIPANT_RESULT or multi-line markets such as CORRECTSCORE_PARTICIPANT_GOALS (even if requested in the subscription) will be ignored by the calculation and no odds messages will be returned for those markets. Weightings in the evensline synthetic definition will be ignored as they are not relevant in the calculation.

To calculate evensline with the following definition:

- Sport = Soccer
- Markets = ASIANHANDICAP_PARTICIPANT_GOALS, OVERUNDER_PARTICIPANT_GOALS
- InRunning = pre-game and in-play
- Synthetic Bookmaker Id = 8888
- Bookmaker = IBCbet (285)
- Weightings = not relevant
- Mode = evensline (this is required)

```
"/synthetic_odds?Sport=soccer&SuperOddsType=ASIANHANDICAP_PARTICIPANT_GOALS,OVERUNDER_PARTICIPANT_GOALS&InRunning=All&Synth=8888:285 and mode=evensline"
```

Conditions

The delay and probability conditions are effectively filters that can be applied when using either of the average or evensline modes. The purpose of the conditions is to further restrict the eligibility into the consensus when calculating the synthetic odds. Each time one of the offers in the synthetic updates the conditions are evaluated and offers that don't meet the conditions will be considered off the board and excluded from the calculation. Delay and Probability conditions can be combined in subscriptions if desired.

Delay

The Delay condition allows offers older than a certain age to be excluded from the consensus and not included in the synthetic calculation. The maximum delay period allowed is evaluated against the current time i.e. the time when any one of the offers in the synthetic updates. A different delay period can be defined for each bookmaker in the synthetic subscription if desired. A common usage pattern is to have separate synthetic subscriptions per sport for pre-game and in-play with different Delay periods set.

Delay periods are expressed as follows:

```
Delay (BookmakerId) < x [SECONDS], [MINUTES], [HOURS], [DAYS]
```

Time periods can have the following abbreviations:

- SECONDS - s, sec, secs, second, seconds
- MINUTES - m, min, mins, minute, minutes
- HOURS - h, hr, hrs, hour, hours
- DAYS - d, day, days

Note: Mixed time units are not allowed, so for example 2 minutes 30 seconds should not be used. To calculate weighted average synthetic prices with the following definition:

- Sport = Soccer
- Market = 1X2_PARTICIPANT_RESULT
- InRunning = pre-game
- Synthetic Bookmaker Id = 8888
- Bookmakers = Ladbrokes (17), William Hill, (42) and PaddyPower (84)
- Weighting = 1, 3 and 5 to be applied to each bookmaker above respectively
- Mode = average (this is the default mode and can in practice be omitted if desired)
- Delay period = 6 hours for Ladbrokes and William Hill, 12 hours for PaddyPower

```
"/synthetic_odds?Sport=soccer&SuperOddsType=1X2_PARTICIPANT_RESULT&InRunning=False&Synth=8888:17+3*42+5*84 and mode=average where delay(17)<6 hours and delay(42)<6 hours and delay(84)<12 hours"
```

To calculate the evensline with the following definition:

- Sport = Soccer
- Market = ASIANHANDICAP_PARTICIPANT_GOALS, OVERUNDER_PARTICIPANT_GOALS
- InRunning = in-play
- Synthetic Bookmaker Id = 7777
- Bookmakers = IBCbet (285)
- Weighting = not relevant
- Mode = evensline
- Delay period = 30 seconds for bookmaker

```
"/synthetic_odds?Sport=soccer&SuperOddsType=ASIANHANDICAP_PARTICIPANT_GOALS,OVERUNDER_PARTICIPANT_GOALS&InRunning=True&Synth=7777:285 and mode=evensline where delay(285)<30 seconds"
```

Probability

The Probability condition only allows offers with a probability (overround) less than or equal to a certain value to be admitted to the consensus and the subsequent synthetic calculation. A different probability value can be defined for each bookmaker in the synthetic subscription if desired. Each time any one of the offers in the synthetic subscription updates this condition will be evaluated, offers not meeting the conditions will be considered OTB.

Probability conditions are expressed as follows:

```
prob (BookmakerId) < x
```

Where x is expressed in decimal format e.g. 1.07 (equivalent to percentage =107% or profit margin = 7%), only offers with probability less than or equal to 1.07 will be included in the consensus.

To calculate weighted average synthetic prices with the following definition:

- Sport = Soccer
- Market = 1X2_PARTICIPANT_RESULT
- InRunning = pre-game
- Synthetic Bookmaker Id = 8888
- Bookmakers = Ladbrokes (17), William Hill, (42) and PaddyPower (84)
- Weighting = 1, 3 and 5 to be applied to each bookmaker above respectively

- Mode = average (this is the default mode and can in practice be omitted if desired)
- Probability = 1.06 for Ladbrokes and 1.07 for William Hill and PaddyPower

```
"/synthetic_odds?Sport=soccer&SuperOddsType=1X2_PARTICIPANT_RESULT&InRunning=False&Synth=8888:17+3*42+5*84 and mode=average where prob(17)<1.06 and prob(42)<1.07 and prob(84)<1.07"
```

To calculate the evensline with the following definition:

- Sport = Soccer
- Market = ASIANHANDICAP_PARTICIPANT_GOALS, OVERUNDER_PARTICIPANT_GOALS
- InRunning = in-play
- Synthetic Bookmaker Id = 7777
- Bookmakers = IBCbet (285)
- Weighting = not relevant
- Mode = evensline
- Probability = 1.07 for bookmaker

```
"/synthetic_odds?Sport=soccer&SuperOddsType=ASIANHANDICAP_PARTICIPANT_GOALS,OVERUNDER_PARTICIPANT_GOALS&InRunning=True&Synth=7777:285 and mode=evensline where prob(285)<1.07"
```

Combining both Delay and Probability conditions

Both Delay and Probability conditions can be combined in the same weighted average or evensline subscription if required as the following example illustrates.

To calculate weighted average synthetic prices with the following definition:

- Sport = Soccer
- Market = 1X2_PARTICIPANT_RESULT
- InRunning = pre-game
- Synthetic Bookmaker Id = 8888
- Bookmakers = Ladbrokes (17), William Hill, (42) and PaddyPower (84)
- Weighting = 1, 3 and 5 to be applied to each bookmaker above respectively
- Mode = average (this is the default mode and can in practice be omitted if desired)
- Delay period = 6 hours for Ladbrokes and William Hill, 12 hours for PaddyPower
- Probability = 1.06 for Ladbrokes and 1.07 for William Hill and PaddyPower

```
"/synthetic_odds?Sport=soccer&SuperOddsType=1X2_PARTICIPANT_RESULT&InRunning=False&Synth=8888:17+3*42+5*84 and mode=average where delay(17)<6 hours and delay(42)<6 hours and delay(84)<12 hours and prob(17)<1.06 and prob(42)<1.07 and prob(84)<1.07"
```

Demargin

There is an option available in Fusion synthetics to request that the odds are demargined using the odds ratio method. Further details of this method can be found in the following article:

[Introduction to the Implied Package](#)

Demargining can be used with either weighted average or evensline mode and in both cases demargining takes place first before the synthetic price is calculated according to the selected mode. Demargining can be used in conjunction with Delay and Probability conditions too if required.

To demargin and then calculate weighted average synthetic prices with the following definition:

- Sport = Soccer
- Market = 1X2_PARTICIPANT_RESULT
- InRunning = pre-game
- Synthetic Bookmaker Id = 8888
- Bookmakers = Ladbrokes (17), William Hill, (42) and PaddyPower (84)
- Weighting = 1, 3 and 5 to be applied to each bookmaker above respectively
- Demargin = use odds ratio method
- Mode = average (this is the default mode and can in practice be omitted if desired)
- Delay period = 6 hours for Ladbrokes and William Hill, 12 hours for PaddyPower
- Probability = 1.06 for Ladbrokes and 1.07 for William Hill and PaddyPower

```
"/synthetic_odds?Sport=soccer&SuperOddsType=1X2_PARTICIPANT_RESULT&InRunning=False&Synth=8888:17+3*42+5*84 and demargin=odds_ratio and mode=average where delay(17)<6 hours and delay(42)<6 hours and delay(84)<12 hours and prob(17)<1.06 and prob(42)<1.07 and prob(84)<1.07"
```

Dampen

Synthetic queries recalculate the consensus price each time there is a price update from any of the bookmakers that have been included in the synthetic definition. This can on occasions result in an excessive number of price updates that are not particularly meaningful. There is an option within Fusion to dampen the number of price updates emitted, so that only price changes above a certain threshold value are emitted. The threshold value also varies with the probabilities, with higher probabilities having a higher threshold value.

To calculate the weighted average and then dampen the output so only meaningful price updates are emitted:

- Sport = Soccer
- Market = 1X2_PARTICIPANT_RESULT
- InRunning = in-play
- Synthetic Bookmaker Id = 8888
- Bookmakers = Ladbrokes (17), William Hill, (42) and PaddyPower (84)
- Weighting = 1, 3 and 5 to be applied to each bookmaker above respectively
- Mode = average (this is the default mode and can in practice be omitted if desired)

```
"/synthetic_odds?Sport=soccer&SuperOddsType=1X2_PARTICIPANT_RESULT&InRunning=True&Synth=8888:17+3*42+5*84 and dampen=percent_diff"
```

Multiple Synthetic Bookmakers per Subscription

It is possible to define more than one synthetic bookmaker within the same subscription if required and the various options of modes, conditions and de-margining mentioned above may be used. Alternatively, if you don't want to calculate the weighted average or evensline or apply any conditions you could just simply demargin the individual bookmakers as in the following example.

To demargin the odds for selected markets from three bookmakers:

- Sport = Soccer
- Market = 1X2_PARTICIPANT_RESULT, ASIANHANDICAP_PARTICIPANT_GOALS, OVERUNDER_PARTICIPANT_GOALS
- InRunning = pre-game and in-play
- Synthetic Bookmaker Id = 8888,777,6666
- De-margin = use odds ratio method
- Bookmakers = IBCbet (285), SBObet (327), and 188bet (365)
- Weighting = not required
- Mode = not required
- Delay period = not required
- Probability = not required

```
"/synthetic_odds?Sport=soccer&SuperOddsType=1X2_PARTICIPANT_RESULT,ASIANHANDICAP_PARTICIPANT_GOALS,OVERUNDER_PARTICIPANT_GOALS&InRunning=All&Synth=8888:285 and demargin=odds_ratio,7777:327 and demargin=odds_ratio,6666:365 and demargin=odds_ratio"
```

Synthetic Details (Debug Information)

Use of this parameter allows control over whether details of the synthetic calculation are included in the output messages or not. When this option is chosen a lot of additional information is added to the messages which may lead to latency issues.

Note: *It is recommended that this option is only used on the UAT environment and not in production.*

Please refer to the Items of Interest section of this User Guide for an explanation of how the ExtraFields parameter can be used to request information that does not appear by default in the messages. The fields that appear by default in the message and those that have to be requested with the ExtraFields parameter are documented in the Appendices of this guide. See Message Examples, Synthetic Odds for further details.

To request the synthetic debug information is displayed in the message:

```
"&ExtraFields=SynthDetails"
```

To calculate weighted average synthetic prices with the following definition and request the debug details in the response:

- Sport = Soccer
- Market = 1X2_PARTICIPANT_RESULT
- InRunning = pre-game
- Synthetic Bookmaker Id = 8888
- Bookmakers = Ladbrokes (17), William Hill, (42) and PaddyPower (84)
- Weighting = 1, 3 and 5 to be applied to each bookmaker above respectively
- Mode = average (this is the default mode and can in practice be omitted if desired)
- Delay period = 6 hours for Ladbrokes and William Hill, 12 hours for PaddyPower
- Probability = 1.06 for Ladbrokes and 1.07 for William Hill and PaddyPower
- ExtraFields = SynthDetails

```
"/synthetic_odds?Sport=soccer&SuperOddsType=1X2_PARTICIPANT_RESULT&InRunning=False&Extra
Fields=SynthDetails&Synth=8888:17+3*42+5*84 and demargin=odds_ratio and mode=average
where delay(17)<6 hours and delay(42)<6 hours and delay(84)<12 hours and prob(17)<1.06
and prob(42)<1.07 and prob(84)<1.07"
```

The example below shows the synthetic details section of the message:

```
"SynthDetails":{
  "ExcludedBookmakerPrices":{
    "887":{
      "ExclusionReason":"no_prices",
      "Price":{
        "Ts":0,
        "Prices":[
          ],
        "PricesNames":[
          "part1",
          "draw",
          "part2"
        ],
        "Line":null
      }
    }
  },
  "IncludedBookmakerPrices":{
    "619":{
      "Ts":1686049359421,
      "Prices":[
        3.1,
        3.5,
        2.05
      ],
      "PricesNames":[
        "part1",
        "draw",
        "part2"
      ],
      "Line":""
    },
    "539":{
      "Ts":1686049346861,
      "Prices":[
        3.16,
        3.6,
        2.04
      ],
      "PricesNames":[
        "part1",
        "draw",
        "part2"
      ],
      "Line":""
    }
  },
  "Calculation":{
    "part1":"(1*3.16+1*3.1)/2",
    "draw":"(1*3.6+1*3.5)/2",
    "part2":"(1*2.04+1*2.05)/2"
  }
}
```

Line Handling

For odds types such as Asian Handicap, Over/Under, Totals, Spreads bookmakers will usually provide several different lines per match.

For example, for Soccer, you may have Over/Under goal lines from 1.5, 2.5, 3.5 and for Basketball you may have Point spreads at 2.5, 4.5, 8.5, 10.5 and so on.

Within each offer we provide the offer LineId field so that multiple lines can be identified per bookmaker/odds type.

Fixture Names and Participants

Fixtures are usually referred to by the names of the teams participating in the fixture, e.g. a typical friendly international soccer fixture might be England vs Brazil.

There are occasions when the name of the fixture reverses, this often happens with friendly fixtures played at neutral venues in the off season. It is not clear who is the “home” team and who is the “away” team.

Historically this has been handled by feed providers cancelling the original fixture (and Id) and creating a new fixture (and Id) but with the team names reversed.

Fusion handles this problem differently using the Participant1IsHome flag. The odds and fixtures messages in Fusion contain fields for:

- FixtureId
- Participant1Id
- Participant1 - (name)
- Participant2Id
- Participant2 (name)
- Pricenames - (in Participant1, Participant2 order)
- Prices - (in Participant1, Participant2 order)
- Participant1IsHome - True/False

Taking the Engand vs Brazil example mentioned above a typical odds message might look like:

```
{
  "Ts":1710975925099,
  "Prices":[1.910, 3.500, 3.800],
  "PriceNames":["part1", "draw", "part2"],
  "MarketParameters":null,
  "MarketPeriod":null,
  "SuperOddsType":"1X2_PARTICIPANT_RESULT",
  "MessageId":"1721882599:00001:000369",
  "StartTime":"2024-03-23T19:00:00Z",
  "IsTeam":true,
  "Sport":"soccer",
  "InRunning":false,
  "BookmakerId":17,
  "Bookmaker":"ladbrokes",
  "Participant1IsHome":true,
  "Participant2Id":1634,
  "Participant2":"Brazil",
  "Participant1Id":1888,
  "Participant1":"England",
  "FixtureId":14658214
}
```

In this example Participant1IsHome = True, so England are considered the home team. If subsequently Brazil were considered the home team all the details in the message would remain the same only Participant1IsHome would change to False. The following points should be noted:

- The FixtureId will remain the same.
- Team names will not change Participant1 / Participant2 order.
- PriceNames reflect Participant1 and Participant2.
- Prices will remain in the Participant1 / Participant2 order.
- Only Participant1IsHome will change from True to False.

Client applications should inspect the Participant1IsHome flag on consuming the message and determine the appropriate action to be taken in customer systems.

Off The Boards - OTBs

The example excerpt from a Fusion message below illustrates how the result after 15 minutes market would be taken OTB:

Active

```
"SuperOddsType": "1X2_PARTICIPANT_RESULT",  
"MarketPeriod": "after_minutes=15",  
"MarketParameters": "",  
"PriceNames": ["part1", "draw", "part2"],  
"Prices": [26.000, 1.030, 51.000],  
"LineId": "1"
```

OTB

```
"SuperOddsType": "1X2_PARTICIPANT_RESULT",  
"MarketPeriod": "after_minutes=15",  
"MarketParameters": "",  
"PriceNames": ["part1", "draw", "part2"],  
"Prices": [],  
"LineId": "1"
```

The prices will be sent as an empty array `"Prices": []` indicating the market is no longer being offered.

Monitoring

Heartbeats are sent continuously every few seconds along with the odds messages and client applications should monitor these. Even if no odds messages are being sent, heartbeats will continue to be delivered.

These let the client applications know that the Fusion stream is still alive and well even though no odds updates are available as can happen on certain days of the week or times of the day.

The example below shows a heartbeat message and associated timestamp being sent after an odds message:

```
data:
{
  "FixtureId":10314740,
  "ParticipantIsHome":true,
  "BookmakerParticipantsReordered":false,
  "BookmakerId":285,
  "InRunning":false,
  "IsTeam":true,
  "StartTime":"2021-01-17T16:30:00Z",
  "MessageId": "1681128553:00001:000380",
  "SuperOddsType": "1X2_PARTICIPANT_RESULT",
  "MarketPeriod": "half=2",
  "MarketParameters":null,
  "PriceNames":["part1","draw","part2"],
  "Prices":[2.860,2.380,2.860],
  "LineId":1,
  "Ts":1610900452888
}
event: live
id: 4284143909.781

data: {"Ts":1610900454}
event: heartbeat

data: {"Ts":1610900459}
event: heartbeat
```

Appendices

Sample Clients

Sample clients are available in the following languages to illustrate basic principles of integration:

- C#
- Java
- JavaScript
- Python
- Scala
- Curl

Please contact your support channel for further information.

Message Examples

Odds

Notes

The odds endpoint provides a streaming response, clients can connect and request optional context information thereafter odds updates will be streamed continuously.

Example of a Fusion Odds message in JSON format:

```
{
  "FixtureId":10314552,
  "LegacyFixtureId":6589352,
  "Participant1":"Burnley",
  "Participant1Id":1664,
  "LegacyParticipant1Id":1664,
  "Participant2":"Manchester Utd",
  "Participant2Id":2520,
  "LegacyParticipant2Id":2520,
  "Participant1IsHome":true,
  "BookmakerParticipantsReordered":false,
  "Bookmaker":"ladbrokes",
  "BookmakerId":17,
  "InRunning":false,
  "Sport":"soccer",
  "SportId":1,
  "LegacySportId":1,
  "Country":"England",
  "CountryId":382,
  "LegacyCountryId":382,
  "Competition":"Premier League",
  "CompetitionId":8,
  "LegacyCompetitionId":8,
  "FixtureGroup":"Premier League > Regular Season",
  "FixtureGroupId":10004084,
  "LegacyFixtureGroupId":101727,
  "IsTeam":true,
  "StartTime":"2021-01-12T20:15:00Z",
  "GameState":null,
  "MessageId":"1681447413:00001:000132",
  "SuperOddsType":"1X2_PARTICIPANT_RESULT",
  "MarketPeriod":null,
  "MarketParameters":null,
  "PriceNames":["part1","draw","part2"],
  "Prices":[2.400,3.100,3.100],
  "LineId":1,
  "Ts":1610471514002
}
```

Column	Default	Type	Example	Explanation
Bookmaker	N	String	"ladbrokes"	Name of the bookmaker
BookmakerId	Y	Numeric	17	Merlin ID of the bookmaker
BookmakerParticipants Reordered	N	Boolean	false	Bookmaker has fixture reversed c/w TXODDS. Information only Fusion will resolve this issue automatically.
Competition	N	String	"Premier League"	Competition name e.g. Premier League
CompetitionId	N	Numeric	8	Merlin Competition ID
Country	N	String	"England"	Country where the competition takes place

CountryId	N	Numeric	382	Merlin Country ID
FixtureGroup	N	String	"Premier League > Regular Season"	Fixture Group name e.g. Premier League Season 20/21
FixtureGroupId	N	Numeric	10004084	Merlin Fixture Group ID
FixtureId	Y	Numeric	10314552	Merlin Fixture ID
GameState	N	String	"scheduled"	Third Party match status information: Cancelled Finished Postponed Scheduled Suspended Walkover Blank (Null) if not provided by 3 rd party.
InRunning	Y	Boolean	false	Pre-game=false In-play=true
IsTeam	Y	Boolean	true	Team sport e.g. Soccer = true Tennis = false
LegacyCompetitionId	N	Numeric	8	AHC/xml2 Competition ID
LegacyCountryId	N	Numeric	382	AHC/xml2 Country ID
LegacyFixtureGroupId	N	Numeric	101727	AHC/xml2 Fixture Group ID
LegacyFixtureId	N	Numeric	6589352	AHC/xml2 Fixture ID
LegacyMessageId	N	String	"3880651836"	Unique identifier for the message. INTERNAL USE ONLY. Note: Please do not confuse this with the message 'Last-Event-ID'
LegacyParticipant1Id	N	Numeric	1664	AHC/xml2 Participant1 ID
LegacyParticipant2Id	N	Numeric	2520	AHC/xml2 Participant2 ID
LegacySportId	N	Numeric	1	AHC/xml2 Sport ID
LineId	N	Numeric	1	See Line Handling. Where offers have multiple lines e.g. O/U Goals, ID of the line
MarketParameters	Y	String	null	SuperOddsType e.g. if the offer has > 1 line this will contain the value
MarketPeriod	Y	String	null	SuperOddsType e.g. 1 st half, 2 nd half
MessageId	Y	String	"1681447413:00001:000132"	Unique identifier for the message. INTERNAL USE ONLY. Note: Please do not confuse this with the message 'Last-Event-ID'
OfferId	N	String	"10314552 17 1X2_PARTICIPANT_RESULT "	Unique identifier for a bookmaker's offer, consisting of a concatenation of FixtureId, BookmakerId,

				SOT, MarketPeriod, MarketParameter.
OfferIdHash	<i>N</i>	<i>String</i>	"a2d9e74f82225931eb678d25d30b091803ba5160"	Unique identifier for a bookmaker's offer, consisting of an sha-1 hash of FixtureId, BookmakerId, SOT, MarketPeriod, MarketParameter.
Participant1	<i>N</i>	<i>String</i>	"Burnley"	Name of the first participant
Participant1Id	<i>N</i>	<i>Numeric</i>	1664	Merlin ID of the first participant
Participant1IsHome	<i>Y</i>	<i>Boolean</i>	true	Which participant is playing at home
Participant2	<i>N</i>	<i>String</i>	"Manchester Utd"	Name of the second participant
Participant2Id	<i>N</i>	<i>Numeric</i>	2520	Merlin ID of the second participant
PriceNames	<i>Y</i>	<i>String Array</i>	["part1", "draw", "part2"]	Array of price names
Prices	<i>Y</i>	<i>Numeric Array</i>	[2.010, 3.600, 2.920]	Array of prices
Sport	<i>N</i>	<i>String</i>	"soccer"	Name of the sport
SportId	<i>N</i>	<i>Numeric</i>	1	Merlin Sport ID
StartTime	<i>Y</i>	<i>UTC DateTime</i>	"2021-01-12T20:15:00Z"	Published start time of the fixture. YYYY-MM-DDTHH:MM:SSZ
SuperOddsType	<i>Y</i>	<i>String</i>	"1X2_PARTICIPANT_RESULT"	SuperOddsType
Ts	<i>Y</i>	<i>Numeric</i>	1610471514002	UNIX Epoch time in milliseconds. Time the price was updated/changed, (same as Push "ts").

Synthetic Odds

Notes

The synthetic odds endpoint provides a streaming response, clients connect to the endpoint and odds updates will be streamed continuously as and when they become available.

Example of a Fusion Synthetics message in JSON format:

```
{
  "SynthDetails":{
    "ExcludedBookmakerPrices":{
      "887":{
        "ExclusionReason":"no_prices",
        "Price":{
          "Ts":0,
          "Prices":[
            ],
          "PricesNames":[
            "part1",
            "draw",

```

```

        "part2"
      ],
      "Line": null
    }
  },
  "IncludedBookmakerPrices": {
    "619": {
      "Ts": 1686049359421,
      "Prices": [
        3.1,
        3.5,
        2.05
      ],
      "PricesNames": [
        "part1",
        "draw",
        "part2"
      ],
      "Line": ""
    },
    "539": {
      "Ts": 1686049346861,
      "Prices": [
        3.16,
        3.6,
        2.04
      ],
      "PricesNames": [
        "part1",
        "draw",
        "part2"
      ],
      "Line": ""
    }
  },
  "Calculation": {
    "part1": "(1*3.16+1*3.1)/2",
    "draw": "(1*3.6+1*3.5)/2",
    "part2": "(1*2.04+1*2.05)/2"
  }
},
"OfferIdHash": "462ac84a1a91af70e78a0c2cbe04f71faed56e5a",
"OfferId": "12985683|619|1X2_PARTICIPANT_RESULT||",
"GameState": null,
"Ts": 1686049359421,
"LineId": 1,
"Prices": [
  3.13,
  3.55,
  2.045
],
"PriceNames": [
  "part1",
  "draw",
  "part2"
],
"MarketParameters": null,
"MarketPeriod": null,
"SuperOddsType": "1X2_PARTICIPANT_RESULT",
"MessageId": "1686442245:00001:000024-8888-synth",
"StartTime": "2023-06-06T10:30:00Z",
"IsTeam": true,
"LegacyFixtureGroupId": 136642,
"FixtureGroupId": 10045214,
"FixtureGroup": "Queensland Premier League > Regular Season",
"LegacyCompetitionId": 1878,
"CompetitionId": 1878,
"Competition": "Queensland Premier League",
"LegacyCountryId": 454,
"CountryId": 454,
"Country": "Australia",
"LegacySportId": 1,
"SportId": 1,
"Sport": "soccer",
"InRunning": true,
"BookmakerId": 8888,
"Bookmaker": "synth8888",
"BookmakerParticipantsReordered": false,
"Participant1IsHome": true,
"LegacyParticipant2Id": 91350,
"Participant2Id": 91350,
"Participant2": "Logan Lightning",
"Participant1Id": 616328,
"Participant1": "Caboolture",
"LegacyFixtureId": 9821201,

```



```
"FixtureId":12985683
}
```

Column	Default	Type	Example	Explanation
Bookmaker	<i>N</i>	<i>String</i>	"synth8888"	Name of the bookmaker
BookmakerId	<i>Y</i>	<i>Numeric</i>	8888	Merlin ID of the bookmaker
BookmakerParticipants Reordered	<i>N</i>	<i>Boolean</i>	false	Bookmaker has fixture reversed c/w TXODDS. Information only Fusion will resolve this issue automatically.
Competition	<i>N</i>	<i>String</i>	"Queensland Premier League"	Competition name e.g. Premier League
CompetitionId	<i>N</i>	<i>Numeric</i>	1878	Merlin Competition ID
Country	<i>N</i>	<i>String</i>	"Australia"	Country where the competition takes place
CountryId	<i>N</i>	<i>Numeric</i>	454	Merlin Country ID
FixtureGroup	<i>N</i>	<i>String</i>	"Queensland Premier League > Regular Season"	Fixture Group name e.g. Premier League Season 20/21
FixtureGroupId	<i>N</i>	<i>Numeric</i>	10045214	Merlin Fixture Group ID
FixtureId	<i>Y</i>	<i>Numeric</i>	12985683	Merlin Fixture ID
GameState	<i>N</i>	<i>String</i>	"scheduled"	Third Party match status information: Cancelled Finished Postponed Scheduled Suspended Walkover Blank (Null) if not provided by 3 rd party.
InRunning	<i>Y</i>	<i>Boolean</i>	true	Pre-game=false In-play=true
IsTeam	<i>Y</i>	<i>Boolean</i>	true	Team sport e.g. Soccer = true Tennis = false
LegacyCompetitionId	<i>N</i>	<i>Numeric</i>	1878	AHC/xml2 Competition ID
LegacyCountryId	<i>N</i>	<i>Numeric</i>	454	AHC/xml2 Country ID
LegacyFixtureGroupId	<i>N</i>	<i>Numeric</i>	136642	AHC/xml2 Fixture Group ID
LegacyFixtureId	<i>N</i>	<i>Numeric</i>	9821201	AHC/xml2 Fixture ID
LegacyParticipant1Id	<i>N</i>	<i>Numeric</i>	616328	AHC/xml2 Participant1 ID
LegacyParticipant2Id	<i>N</i>	<i>Numeric</i>	91350	AHC/xml2 Participant2 ID
LegacySportId	<i>N</i>	<i>Numeric</i>	1	AHC/xml2 Sport ID
LineId	<i>N</i>	<i>Numeric</i>	1	See Line Handling. Where offers have multiple lines e.g. O/U Goals, ID of the line

MarketParameters	Y	String	null	SuperOddsType e.g. if the offer has > 1 line this will contain the value
MarketPeriod	Y	String	null	SuperOddsType e.g. 1 st half, 2 nd half
MessageId	Y	String	"1686442245:00001:000024-8888-synth"	Unique identifier for the message. INTERNAL USE ONLY. Note: based on the last message to update the synthetic.
OfferId	N	String	"12985683 619 1X2_PARTICIPANT_RESULT "	Unique identifier for a bookmaker's offer, consisting of a concatenation of FixtureId, BookmakerId, SOT, MarketPeriod, MarketParameter.
OfferIdHash	N	String	"462ac84a1a91af70e78a0c2cbe04f71faed56e5a"	Unique identifier for a bookmaker's offer, consisting of an sha-1 hash of FixtureId, BookmakerId, SOT, MarketPeriod, MarketParameter.
Participant1	N	String	"Caboolture"	Name of the first participant
Participant1Id	N	Numeric	616328	Merlin ID of the first participant
Participant1IsHome	Y	Boolean	true	Which participant is playing at home
Participant2	N	String	"Logan Lightning"	Name of the second participant
Participant2Id	N	Numeric	91350	Merlin ID of the second participant
PriceNames	Y	String Array	["part1", "draw", "part2"]	Array of price names
Prices	Y	Numeric Array	[3.13, 3.55, 2.045]	Array of prices
Sport	N	String	"soccer"	Name of the sport
SportId	N	Numeric	1	Merlin Sport ID
StartTime	Y	UTC DateTime	"2023-06-06T10:30:00Z"	Published start time of the fixture. YYYY-MM-DDTHH:MM:SSZ
SuperOddsType	Y	String	"1X2_PARTICIPANT_RESULT"	SuperOddsType
SynthDetails	N	JSON	"SynthDetails":{ "ExcludedBookmakerPrices":{ "887":{ "ExclusionReason":"no_prices", "Price":{ "Ts":0, "Prices":[], "PricesNames":["part1", "draw", "part2"], "Line":null	Details of included and excluded bookmakers plus reasons and the calculation e.g. weighted average.

			<pre> } }, "IncludedBookmakerPrices":{ "619":{ "Ts":1686049359421, "Prices":[3.1, 3.5, 2.05], "PricesNames":["part1", "draw", "part2"], "Line":"" }, "539":{ "Ts":1686049346861, "Prices":[3.16, 3.6, 2.04], "PricesNames":["part1", "draw", "part2"], "Line":"" } }, "Calculation":{ "part1":"(1*3.16+1*3.1)/2", "draw":"(1*3.6+1*3.5)/2", "part2":"(1*2.04+1*2.05)/2" } } } </pre>	
Ts	Y	<i>Numeric</i>	1686049359421	UNIX Epoch time in milliseconds. Time the price was updated/changed, (same as Push "ts").

Fixtures

Notes

The fixtures endpoint provides a streaming response, clients can connect and request optional context information thereafter fixture updates will be streamed continuously.

Deleted fixtures will be identified as such in the **EntityStatus** field, the value being set to "deleted".

Example of a Fusion Fixture message in JSON format:

```

{
  "FixtureId":10194904,
  "LegacyFixtureId":6420694,
  "Participant1":"Apoei Nicosia",
  "Participant1Id":1482,
  "LegacyParticipant1Id":1482,
  "Participant2":"AEK Larnaca",
  "Participant2Id":6034,
  "LegacyParticipant2Id":6034,

```

```

    "ParticipantIsHome":true,
    "Sport":"soccer",
    "SportId":1,
    "LegacySportId":1,
    "Country":"Cyprus",
    "CountryId":425,
    "LegacyCountryId":425,
    "Competition":"1. Division",
    "CompetitionId":75,
    "LegacyCompetitionId":75,
    "FixtureGroup":"1. Division > Regular Season",
    "FixtureGroupId":10002370,
    "LegacyFixtureGroupId":100229,
    "IsTeam":true,
    "StartTime":"2021-01-13T14:00:00Z",
    "EntityStatus":"active",
    "GameState":"finished",
    "MessageId":"0013403660:00001:000004",
    "Delta":{
      "GameState":"finished"
    },
    "Ts":1610553767684
  }
}

```

Column	Default	Type	Example	Explanation
Competition	N	String	"1. Division"	Competition name e.g. Premier League
CompetitionId	Y	Numeric	75	Merlin Competition ID
Country	N	String	"Cyprus"	Country where the competition takes place
CountryId	Y	Numeric	425	Merlin ID of the country
CoverageSecondaryData	N	Boolean	true	Is additional player data available: True False Null e.g. for a completed pass - passer, receiver, yards.
CoverageStatus	N	String	"Approved"	The status of the Scores Data fixture coverage: Not Approved Approved Cancelled Null
CoverageType	N	String	"Venue"	The Scores Data coverage that will be available if approved: Venue TV/Stream Null
Delta	Y	JSON	{"GameState":"finished"}	When the fixture is updated, this will contain details of the field(s) and value(s) that have been changed otherwise Null.
EntityStatus	Y	String	"Active"	Has the fixture been deleted? Value will be "deleted" if so, else "active"
FixtureGroup	N	String	"1. Division > Regular Season"	Fixture Group name e.g. Premier League Season 20/21
FixtureGroupId	Y	Numeric	10002370	Merlin ID of the Fixture Group
FixtureId	Y	Numeric	10194904	Merlin ID of the Fixture
GameState	Y	String	"finished"	Third Party match status information: Cancelled Finished Postponed Scheduled Suspended

				Walkover Blank (Null) if not provided by 3 rd party.
IsTeam	Y	Boolean	true	Team sport e.g. Soccer = true Tennis = false
LegacyCompetitionId	N	Numeric	75	AHC/xml2 Competition ID
LegacyCountryId	N	Numeric	425	AHC/xml2 Country ID
LegacyFixtureGroupId	N	Numeric	100229	AHC/xml2 Fixture Group ID
LegacyFixtureId	N	Numeric	6420694	AHC/xml2 Fixture ID
LegacyParticipant1Id	N	Numeric	1482	AHC/xml2 Participant1 ID
LegacyParticipant2Id	N	Numeric	6034	AHC/xml2 Participant2 ID
LegacySportId	N	Numeric	1	AHC/xml2 Sport ID
MessageId	Y	String	"0013403660:00001:000004"	Unique ID of the message
Participant1	N	String	"Apoel Nicosia"	Name of the first participant
Participant1Id	Y	Numeric	1482	Merlin ID of the first participant
Participant1IsHome	Y	Boolean	true	Which participant is playing at home
Participant2	N	String	"AEK Larnaca"	Name of the second participant
Participant2Id	Y	Numeric	6034	Merlin ID of the second participant
Sport	N	String	"soccer"	Name of the sport
SportId	Y	Numeric	1	Merlin ID of the sport
StartTime	Y	UTC DateTime	"2020-09-12T00:00:00Z"	Published start time of the fixture YYYY-MM-DDTHH:MM:SSZ
Ts	Y	Numeric	1610553767684	UNIX Epoch time in milliseconds. Time the fixture was updated/changed.

Fixture Groups

Notes

The fixturegroups endpoint provides a streaming response, clients can connect and request optional context information thereafter fixturegroup updates will be streamed continuously.

Example of a Fusion Fixture Group message in JSON format:

```
{
  "FixtureGroupId":10004084,
  "LegacyFixtureGroupId":101727,
  "Name":"Premier League > Regular Season",
  "StartDate":"2020-09-12T00:00:00Z",
  "EndDate":"2021-05-23T00:00:00Z",
  "SportId":1,
  "LegacySportId":1,
  "Sport":"soccer",
  "CountryId":382,
  "Country":"England",
  "LegacyCountryId":382,
  "Competition":"Premier League",
  "CompetitionId":8,
  "LegacyCompetitionId":8,
```

```

"MessageId":"0010051648:00001:000003",
"Ts":1597916743513,
"EntityStatus":"active",
"Delta":null
}

```

Column	Default	Type	Example	Explanation
Competition	Y	String	"Premier League"	Competition name
CompetitionId	Y	Numeric	8	Merlin Competition ID
Country	Y	String	"England"	Country where the competition takes place
CountryId	Y	Numeric	382	Merlin ID of the country
Delta	Y	JSON	null	When the fixture is updated, this will contain details of the field(s) and value(s) that have been changed.
EndDate	Y	UTC DateTime	"2021-05-23T00:00:00Z"	Published end date of the fixturegroup YYYY-MM-DDTHH:MM:SSZ
EntityStatus	Y	String	"active"	Has the fixture been deleted? Value will be "deleted" if so, else "active"
FixtureGroup	Y	String	"Premier League > Regular Season"	FixtureGroup name
FixtureGroupId	Y	Numeric	10004084	Merlin ID of the FixtureGroup
LegacyCompetitionId	N	Numeric	8	AHC/xml2 Competition ID
LegacyCountryId	N	Numeric	382	AHC/xml2 Country ID
LegacyFixtureGroupId	N	Numeric	101727	AHC/xml2 FixtureGroup ID
LegacySportId	N	Numeric	1	AHC/xml2 Sport ID
MessageId	Y	String	"0010051648:00001:000003"	Unique ID of the message
Sport	Y	String	"soccer"	Name of sport
SportId	Y	Numeric	1	Merlin Sport ID
StartDate	Y	UTC DateTime	"2020-09-12T00:00:00Z"	Published start date of the fixturegroup YYYY-MM-DDTHH:MM:SSZ
Ts	Y	Numeric	1597916743513	UNIX Epoch time in milliseconds. Time the fixturegroup was updated/changed.

Competitions

Notes

The competitions endpoint provides a streaming response, clients can connect and request optional context information thereafter competition updates will be streamed continuously. Example of a Fusion Competition message in JSON format:

```

{
  "EntityStatus":"active",
  "Delta":null,
  "MessageId":"0000000010:00001:000000",
  "Ts":1688971371454,

```

```

"ParticipantTypes":[
  "male-team"
],
"SportId":1,
"CountryId":678,
"CompetitionId":10,
"Competition":"UEFA Champions League"
}

```

Column	Default	Type	Example	Explanation
Competition	Y	String	"UEFA Champions League"	Competition name
CompetitionId	Y	Numeric	10	Merlin Competition ID
Country	N	String	"Europe"	Country(ies) where the Competition takes place
CountryId	Y	Numeric	678	Merlin ID of the country
Delta	Y	JSON	null	When the Competition is updated, this will contain details of the field(s) and value(s) that have been changed.
EntityStatus	Y	String	"active"	Has the fixture been deleted? Value will be "deleted" if so, else "active"
LegacyCompetitionId	N	Numeric	10	AHC/xml2 Competition ID
LegacyCountryId	N	Numeric	678	AHC/xml2 Country ID
LegacySportId	N	Numeric	1	AHC/xml2 Sport ID
MessageId	Y	String	"0000000010:00001:000000"	Unique ID of the message
ParticipantTypes	Y	String Array	["male-team"]	e.g. Tennis ["male-player", "male-team", "mixed-team", "female-team", "female-player"]
Sport	N	String	"soccer"	Name of sport
SportId	Y	Numeric	1	Merlin Sport ID
Ts	Y	Numeric	1584779157544	UNIX Epoch time in milliseconds. Time the fixturegroup was updated/changed.

Players

Notes

The players endpoint provides a streaming response, clients can connect and request optional context information thereafter player updates will be streamed continuously.

Example of a Fusion Player message in JSON format:

```
{
  "Gender": "male",
  "DateOfBirth": "1990-01-31",
  "Team": [
    {
      "Id": 4885,
      "Name": "Barcelona"
    }
  ],
  "Country": "Italy",
  "Sport": "basketball",
  "Player": "Laprovittola, Nicolas",
  "PlayerId": 10083176
}
```

Column	Default	Type	Example	Explanation
Country	N	String	"Italy"	Nationality of player
DateOfBirth	Y	String	"1990-01-31"	Player's date of birth YYYY-MM-DD
Gender	Y	String	"male"	Player's gender
Player	Y	String	"Laprovittola, Nicolas"	Player's surname, forename
PlayerId	Y	Numeric	10083176	Merlin Player ID
Sport	Y	String	"basketball"	Name of sport
Team Array Id Name	Y	Numeric String	4885 "Barcelona"	Id and Name of teams' player plays for

Teams

Notes

The teams endpoint provides a streaming response, clients can connect and request optional context information thereafter team updates will be streamed continuously.

Example of a Fusion Team message in JSON format:

```
{
  "Gender": "male",
  "Sport": "soccer",
  "Country": "England",
  "PreferredName": "Crystal Palace",
  "TeamId": 1771
}
```

Column	Default	Type	Example	Explanation
Country	Y	String	"England"	Country team plays in
Gender	Y	String	"male"	Gender of team
PreferredName	Y	String	"Crystal Palace"	Common team name
Sport	Y	String	"soccer"	Sport

TeamId	Y	<i>Numeric</i>	1771	Merlin Team Id
---------------	---	----------------	------	----------------

Matchdata

Notes

The matchdata endpoint provides a streaming response, clients can connect and request optional context information thereafter matchdata updates will be streamed continuously.

Example of a Fusion Matchdata message in JSON format:

```
{
  "FixtureId":13848575,
  "Participant1":"Al Ettifaq",
  "Participant1Id":10285,
  "Participant2":"Al Ittihad",
  "Participant2Id":10040,
  "Participant1IsHome":true,
  "FixtureGroup":"Pro League > Regular Season",
  "FixtureGroupId":10059026,
  "MessageId":"0013848575:00001:000039",
  "Ts":1700840504216,
  "Score":[1,0],
  "RedCards":[0,0],
  "Corners":[2,3],
  "GameState":{"gameTime":42,"state":"1"}
}
```

Column	Default	Type	Example	Explanation
Corners	Y	<i>String</i>	[2,3]	Running total of the corners awarded in the order participant1, participant2
FixtureGroup	Y	<i>Numeric</i>	Pro League > Regular Season	FixtureGroup name
FixtureGroupId	Y	<i>Numeric</i>	10059026	Merlin ID of the FixtureGroup
FixtureId	Y	<i>Numeric</i>	13848575	Merlin ID of the Fixture
GameState	Y	<i>String</i>	{"gameTime":42,"state":"1"}	Minute of the game and state, where allowable regular time state values are: 1 - first-half 2 - half-time 3 - second-half 4 - full-time
MessageId	Y	<i>String</i>	"0013848575:00001:000039"	Unique ID of the message
Participant1	Y	<i>String</i>	"Al Ettifaq"	Name of the first participant
Participant1Id	Y	<i>Numeric</i>	10285	Merlin ID of the first participant
Participant1IsHome	Y	<i>Boolean</i>	true	Which participant is playing at home
Participant2	Y	<i>String</i>	"Al Ittihad"	Name of the second participant
Participant2Id	Y	<i>Numeric</i>	10040	Merlin ID of the second participant
RedCards	Y	<i>String</i>	[0,0]	Running total of the red cards awarded in the order participant1, participant2
Score	Y	<i>String</i>	[1,0]	Running total of the goals scored in the order participant1, participant2
Ts	Y	<i>Numeric</i>	1700840504216	UNIX Epoch time in milliseconds. Time the

				matchdata was updated/changed.
--	--	--	--	--------------------------------

Scores Data

The Scores endpoint provides a streaming response, clients can connect and request optional history information thereafter scores updates will be streamed continuously.

Note: *There is a slight difference in the response when requesting Full Context using Ts=0. All other endpoints will provide the current state e.g. the Odds endpoint will return the current state of all available offers. The Scores endpoint will however provide a history of the messages rather than current state, but otherwise Ts works the same, messages greater than or equal to the timestamp will be returned.*

Note: *the Scores "Action": "kickoff_outcome" in the following example is one of many possible actions, please see the*

Example of a Fusion Scores message in JSON format:

```
{
  "FixtureInfo":{
    "GameState":"scheduled",
    "StartTime":"2024-06-08T21:00:00Z",
    "IsTeam":true,
    "FixtureGroupId":10074357,
    "FixtureGroup":"NCAA Division I FBS > Regular Season",
    "CompetitionId":500005,
    "Competition":"NCAA Division I FBS",
    "CountryId":459,
    "Country":"USA",
    "SportId":6,
    "Sport":"us football",
    "Participant1IsHome":true,
    "Participant2Id":38298,
    "Participant2":"Cal Poly",
    "Participant1Id":4433,
    "Participant1":"Ohio State Buckeyes",
    "FixtureId":14790158
  },
  "Update":{
    "Action":"kickoff_outcome",
    "StatusId":2,
    "Participant":2,
    "Data":{
      "Type":"fair_catch"
    },
    "Confirmed":true,
    "Down":{
      "Number":0,
      "YardsToGo":0,
      "ScrimmageLine":25,
      "Possession":2,
      "Side":"offensive"
    },
    "KickoffInfo":{
      "Team":1,
      "Type":"regular",
      "Outcome":"fair_catch",
      "SafetyHappened":false
    },
    "InPlayInfo":{
      "BallSnapped":true,
      "PlayersLiningUp":false,
      "Outcome":"fair_catch"
    },
    "Clock":{
      "Running":false,
      "Seconds":756
    },
    "FixtureId":14790158,
    "GlobalSeq":262,
    "Id":241,
    "Ts":1718033066851,
  }
}
```

<pre> "ServerId": "3e5e4790-6260-4dd3-858e-dd9c100c122e", "Seq": 245 } </pre>				
Column	Default	Type	Example	Explanation
Competition	N	Text	"NCAA Division I FBS"	Competition name e.g. Premier League
CompetitionId	Y	Numeric	500005	Merlin Competition ID
Country	N	Text	"USA"	Country where the competition takes place
CountryId	Y	Numeric	459	Merlin ID of the country
FixtureGroup	N	Text	"NCAA Division I FBS > Regular Season"	Fixture Group name e.g. Premier League Season 20/21
FixtureGroupId	Y	Numeric	10074357	Merlin ID of the Fixture Group
FixtureId	Y	Numeric	14790158	Merlin ID of the Fixture
GameState	Y	Text	"scheduled"	Third Party match status information: Cancelled Finished Live Postponed Scheduled Suspended Retired Walkover Blank if not provided by 3rd party
GlobalSeq	Y	Numeric	262	Global Sequence
Id	Y	Numeric	241	Id
IsTeam	Y	Boolean	true	Team sport e.g. Soccer = true Tennis = false
Participant1	N	Text	"Ohio State Buckeyes"	Name of the first participant
Participant1Id	Y	Numeric	4433	Merlin ID of the first participant
Participant1IsHome	Y	Boolean	true	Which participant is playing at home
Participant2	N	Text	"Cal Poly"	Name of the second participant
Participant2Id	Y	Numeric	38298	Merlin ID of the second participant
ServerId	Y	GUID	"3e5e4790-6260-4dd3-858e-dd9c100c122e"	Id of the server
Seq	Y	Numeric	245	Sequence number
Sport	N	Text	"us football"	Name of the sport
SportId	Y	Numeric	6	Merlin ID of the sport
StartTime	Y	UTC DateTime	"2024-06-08T21:00:00Z"	Published start time of the fixture YYYY-MM-DDTHH:MM:SSZ
Ts	Y	Numeric	1718033066851	UNIX Epoch time in milliseconds. Time the fixture was updated/changed.

Update	Y	JSON	<pre> "Update":{ "Action": "kickoff_outcome", "StatusId":2, "Participant":2, "Data":{ "Type": "fair_catch" }, "Confirmed":true, "Down":{ "Number":0, "YardsToGo":0, "ScrimmageLine":25, "Possession":2, "Side": "offensive" }, "KickoffInfo":{ "Team":1, "Type": "regular", "Outcome": "fair_catch", "SafetyHappened":false }, "InPlayInfo":{ "BallSnapped":true, "PlayersLiningUp":false, "Outcome": "fair_catch" }, "Clock":{ "Running":false, "Seconds":756 } } </pre>	Scores Data System update message. Further details and documentation of the data points available separately from - Scores Product API Documentation for American Football.
--------	---	------	---	---

Bookmakers

The bookmakers endpoint provides a static response, when clients connect they will be sent the data and then the response ends. Bookmakers data does not change frequently, so there is no requirement for a streaming response, customers should request data from this endpoint weekly or daily at most.

Example of a Fusion bookmakers list in JSON format, **note** this is not the complete list:

```
[
  {
    "BookmakerId":17, "Name": "ladbrokes", "BookmakerType": "SportsBook",
  },
  {
    "BookmakerId":10010, "Name": "txstableprice", "BookmakerType": "SportsBook",
  },
  {
    "BookmakerId":365, "Name": "188bet", "BookmakerType": "SportsBook",
  },
  {
    "BookmakerId":928, "Name": "artemis", "BookmakerType": "ExchangeBook",
  },
  {
    "BookmakerId":282, "Name": "singbet", "BookmakerType": "SportsBook"
  }
]
```

Column	Type	Example	Explanation
BookmakerId	Numeric	17	Merlin Bookmaker ID
Name	String	"ladbrokes"	Bookmaker name
BookmakerType	String	"SportsBook"	Indicates whether the bookmaker is an exchange type book or regular sports book

Sports

The sports endpoint provides a static response, when clients connect they will be sent the data and then the response ends. Sports data does not change frequently, so there is no requirement for a streaming response, customers should request data from this endpoint weekly or daily at most.

Example of a Fusion sports list in JSON format, **note** this is not the complete list:

```
[{"SportId":26,"Name":"aussie rules","LegacySportId":26},
{"SportId":47,"Name":"badminton","LegacySportId":47},
{"SportId":7,"Name":"baseball","LegacySportId":7},
{"SportId":3,"Name":"basketball","LegacySportId":3},
{"SportId":14,"Name":"cricket","LegacySportId":14},
{"SportId":8,"Name":"handball","LegacySportId":8},
{"SportId":2,"Name":"ice hockey","LegacySportId":2},
{"SportId":1,"Name":"soccer","LegacySportId":1},
{"SportId":15,"Name":"table tennis","LegacySportId":15},
{"SportId":5,"Name":"tennis","LegacySportId":5},
{"SportId":6,"Name":"us football","LegacySportId":6},
{"SportId":13,"Name":"volleyball","LegacySportId":13}]
```

Column	Type	Example	Explanation
SportId	Numeric	26	Merlin Sport ID
Name	String	"aussie rules"	Sport name
LegacySportId	Numeric	26	AHC/xml2 Country ID

Countries

The countries endpoint provides a static response, when clients connect they will be sent the data and then the response ends. Countries data does not change frequently, so there is no requirement for a streaming response, customers should request data from this endpoint weekly or daily at most.

Example of a Fusion countries list in JSON format, **note** this is not the complete list:

```
[{"CountryId":417,"Name":"AFL","LegacyCountryId":417},
{"CountryId":651,"Name":"Afganistan","LegacyCountryId":651},
{"CountryId":677,"Name":"Africa","LegacyCountryId":677},
{"CountryId":508,"Name":"African Cup","LegacyCountryId":508},
{"CountryId":375,"Name":"Albania","LegacyCountryId":375},
{"CountryId":469,"Name":"Algeria","LegacyCountryId":469},
{"CountryId":537,"Name":"Alpine Skiing","LegacyCountryId":537}]
```

Column	Type	Example	Explanation
CountryId	Numeric	611	Merlin Country ID
Name	String	"Antigua And Barbuda"	Country name
LegacyCountryId	Numeric	611	AHC/xml2 Country ID

Oddstypes

The oddstype endpoint provides a static response, when clients connect they will be sent the data and then the response ends. Oddstype data does not change frequently, so there is no requirement for a streaming response, customers should request data from this endpoint weekly or daily at most.

Example of a Fusion oddstypes list in JSON format, **note** this is not the complete list:

```
[
  {
    "Sport": "Soccer",
    "SOT": "1X2_PARTICIPANT_RESULT",
    "MarketParameters": "",
    "MarketPeriod": "",
    "PriceNames": [
      "part1",
      "draw",
      "part2"
    ]
  },
  {
    "Sport": "Soccer",
    "SOT": "ASIANHANDICAP_PARTICIPANT_GOALS",
    "MarketParameters": "line",
    "MarketPeriod": "half",
    "PriceNames": [
      "part1",
      "part2"
    ]
  }
]
```

Column	Type	Example	Explanation
Sport	String	Soccer	Sport name.
SOT	String	ASIANHANDICAP_PARTICIPANT_GOALS	SuperOddsType
MarketParameters	String	line	e.g. Handicap line
MarketPeriod	String	half	Time period the market is applicable for.
PriceNames	String Array	["part1","part2"]	Array of price names applicable to the market.

Message Identification and Sequencing

The following is further explanation of some of the fields in the Odds message that can be used to identify a message, group messages and determine in which sequence to process the messages.

MessageId

- This is a globally unique identifier for the odds message across subscriptions.
- The value of MessageId always increases for new prices.
- The value for an OTB will however refer back to the original MessageId so you know which line is being set OTB.

e.g. if the original line had "MessageId": "1681453252:00001:000399" the message setting the line OTB will have "MessageId": "1681453252:00001:000399-1".

- Even though the first number of the MessageId can be less than previous values in the global stream of price updates, within the same line, it is always going to be:
 - a) the same or increasing,
 - b) if the first part of the message id is the same, the second part will be always increasing.
- Thus, the message id can be used to tell the exact order of messages within the scope of a price updates line.
- An OTB could be received several days after the original line/price was sent.
- If you re-subscribe or have more than one subscription the MessageId will be the same for a given line/price.
- The format of this message is planned to change in the near future, and the timeframe of this is likely to be a matter of months.
- We will provide details of the change in due course in advance of any release to the uat environment.

LastEventId

- The value is unique for the lifetime of the subscription.
- The format of the message is a timestamp followed by an always increasing number sequence e.g. 1642616419715.268764.
- If you re-subscribe there will be a new timestamp and the number sequence will be reset to 1 and start increasing again.
- This value can be relied on to determine the correct sequence in which to process messages.

Timestamp - Ts

- Is a timestamp of when the price was updated.
- More than one message can have the same timestamp.

- This field **cannot** be relied on to determine the correct sequence in which to process messages.

OfferId and OfferIdHash

- The former is a concatenation of FixtureId, BookmakerId, SuperOddsType, MarketPeriod & MarketParameter, the latter is a hash of the same fields.
- This allows any line to be tracked.
- You can group by this value if desired.

SuperOddsTypes Explanation

Due to the increasing numbers of online bookmakers and associated markets, TXODDS has had to rationalize the way these markets are presented to customers so they may be easily understood and integrated in a straightforward manner into customer systems.

A typical soccer full time match result market can be referred to in various ways by different bookmakers:

1. Match Betting
2. Full Time Result
3. 1x2
4. Win-Draw-Win
5. 90 Minutes
6. Match Odds
7. Money Line - Match
8. Match Winner - 3 way

TXODDS replaces all these different naming conventions with a new *SuperOddsType* that consists of:

Market Type	what type of betting rules the market follows, e.g. result, handicap, moneyline
Market Subject	who is involved in the market, e.g. teams or players
Market Object	what is being bet on, e.g. result, corners, cards, bookings

For the soccer match full time result this would be represented by the following SuperOddsType:

- 1X2_PARTICIPANT_RESULT

A SuperOddsType can be further defined by optional:

Market Periods	a period to which the betting applies e.g. full-time, first-half, after 10 mins
Market Parameters	correct score 2:1, over/under line 2.5, total goals range 2-3

Match Result

A full-time match result market is therefore represented by:

SuperOddsType	1X2_PARTICIPANT_RESULT
MarketPeriod	""
MarketParameters	""
LineId	1
PriceNames	[part1, draw, part2]
Prices	[1.970, 3.200, 3.760]

The half-time result market would be represented by:

SuperOddsType	1X2_PARTICIPANT_RESULT
MarketPeriod	half=1
MarketParameters	""
LineId	1
PriceNames	[part1, draw, part2]
Prices	[2.630, 2.050, 4.000]

The result after 30 minutes market would be:

SuperOddsType	1X2_PARTICIPANT_RESULT
MarketPeriod	after_minutes=30
MarketParameters	""
LineId	1
PriceNames	[part1, draw, part2]
Prices	[2.630, 2.050, 4.000]

Total Goals

The total goals market would require several different odds messages being sent, with a line for each separate goal range:

SuperOddsType	EXACTTOTAL_PARTICIPANT GOALS
MarketPeriod	""
MarketParameters	range 0-1
LineId	1
PriceNames	exactmatch
Prices	2.050

SuperOddsType	EXACTTOTAL_PARTICIPANT GOALS
MarketPeriod	""
MarketParameters	range2-3
LineId	2
PriceNames	exactmatch
Prices	1.950

SuperOddsType	EXACTTOTAL_PARTICIPANT GOALS
MarketPeriod	""
MarketParameters	range4-6
LineId	3
PriceNames	exactmatch
Prices	6.800

SuperOddsType	EXACTTOTAL_PARTICIPANT GOALS
MarketPeriod	""
MarketParameters	range7+
LineId	4
PriceNames	exactmatch
Prices	11.5

The above example is for 90 minutes, however if first-half and second-half markets were being offered, then this would be achieved by using the same SuperOddsType in conjunction with the optional Market Period parameter:

SuperOddsType	EXACTTOTAL_PARTICIPANT GOALS
MarketPeriod	half=1

SuperOddsType	EXACTTOTAL_PARTICIPANT GOALS
MarketPeriod	half=2

Over Under Goals

The over under goals market would require several different odds messages being sent, with a line for each separate over under goal line:

SuperOddsType	OVERUNDER_PARTICIPANT GOALS
MarketPeriod	""
MarketParameters	line=0.5
LineId	1
PriceNames	["over", "under"]
Prices	[1.050, 10.000]

SuperOddsType	OVERUNDER_PARTICIPANT GOALS
MarketPeriod	""
MarketParameters	line=1.5
LineId	2
PriceNames	["over", "under"]
Prices	[1.250, 3.400]

SuperOddsType	OVERUNDER_PARTICIPANT GOALS
MarketPeriod	""
MarketParameters	line=2.5
LineId	3
PriceNames	["over", "under"]
Prices	[1.800, 1.830]

SuperOddsType	OVERUNDER_PARTICIPANT GOALS
MarketPeriod	""
MarketParameters	line=3.5
LineId	4
PriceNames	["over", "under"]
Prices	[3.000, 1.300]

European Goal Handicap

A European Goal Handicap market Home Team -0.5 Away Team +0.5 would be represented as:

SuperOddsType	EUROHANDICAP_PARTICIPANT_GOALS
MarketPeriod	""
MarketParameters	line=-0.5
LineId	1
PriceNames	[part1, part2]
Prices	[1.670, 2.100]

Asian Goal Handicap

An example Full Time Asian Goal Handicap market with eight lines is given below:

Home Team Handicap	Price	Away Team Handicap	Price
+0.5	1.245	-0.5	4.190
0	1.369	0	3.200
-0.25	1.588	+0.25	2.420
-0.5	1.813	+0.5	2.040
-0.75	2.070	+0.75	1.787
-1.0	2.540	+1.0	1.537
-1.5	3.340	+1.5	1.343
-2.5	7.230	+2.5	1.112

The SuperOddsType representation would result in eight odds messages as follows:

SuperOddsType	ASIANHANDICAP_PARTICIPANT_GOALS
MarketPeriod	""

The above information would be sent in each message together with the following lines:

MarketParameters	line=0.5
LineId	2
PriceNames	[part1, part2]
Prices	[1.245, 4.190]

MarketParameters	line=0.0
LineId	3
PriceNames	[part1, part2]
Prices	[1.369, 3.200]

MarketParameters	line=-0.25
LineId	4
PriceNames	[part1, part2]
Prices	[1.588, 2.420]

MarketParameters	line=-0.5
LineId	1
PriceNames	[part1, part2]
Prices	[1.813, 2.040]

MarketParameters	line=-0.75
------------------	------------

LineId	5
PriceNames	[part1, part2]
Prices	[2.070, 1.787]

MarketParameters	line=-1.0
LineId	6
PriceNames	[part1, part2]
Prices	[2.540, 1.537]

MarketParameters	line=-1.5
LineId	7
PriceNames	[part1, part2]
Prices	[3.340, 1.343]

MarketParameters	line=-2.5
LineId	8
PriceNames	[part1, part2]
Prices	[7.230, 1.112]

Player Props

A typical player prop market for Touchdowns would be represented as:

SuperOddsType	OVERUNDER_PLAYER_TOUCHDOWNS
MarketPeriod	“ ”
MarketParameters	line=15.5,player=Niemann; Nick,playerId=10037329
PriceNames	[over, under]
Prices	[1.662, 1.686]

SuperOddsTypes

The available SuperOddsTypes are:

1X2_PARTICIPANT_180S
1X2_PARTICIPANT_2POINTS
1X2_PARTICIPANT_3POINTS
1X2_PARTICIPANT_ACES
1X2_PARTICIPANT_ASSISTS
1X2_PARTICIPANT_BOOKINGS
1X2_PARTICIPANT_BREAKOFSERVES
1X2_PARTICIPANT_BREAKPOINTS
1X2_PARTICIPANT_CORNERS
1X2_PARTICIPANT_DOUBLEFAULTS
1X2_PARTICIPANT_FACEOFFS
1X2_PARTICIPANT_FOULS
1X2_PARTICIPANT_FREETHROWS
1X2_PARTICIPANT_GOALKICKS
1X2_PARTICIPANT_HIGHESTCHECKOUT
1X2_PARTICIPANT_HITS
1X2_PARTICIPANT_HITWOODWORK
1X2_PARTICIPANT_KILLS
1X2_PARTICIPANT_MINORPENALTIES
1X2_PARTICIPANT_OFFSIDES
1X2_PARTICIPANT_OPENINGPARTNERSHIP
1X2_PARTICIPANT_PENALTYTHROWS
1X2_PARTICIPANT_PERIODS
1X2_PARTICIPANT_POWERPLAYGOALS
1X2_PARTICIPANT_REBOUNDS
1X2_PARTICIPANT_REDCARDS
1X2_PARTICIPANT_RESULT
1X2_PARTICIPANT_SHOTS
1X2_PARTICIPANT_SHOTSBLOCKED
1X2_PARTICIPANT_SIXES
1X2_PARTICIPANT_STEALS
1X2_PARTICIPANT_THROWINS
1X2_PARTICIPANT_YELLOWCARDS
3WAYHANDICAP_PARTICIPANT_CORNERS
3WAYHANDICAP_PARTICIPANT_GAMES
3WAYHANDICAP_PARTICIPANT_GOALS
3WAYHANDICAP_PARTICIPANT_POINTS
3WAYHANDICAP_PARTICIPANT_RUNS
3WAYOVERUNDER_PARTICIPANT_GAMES
3WAYOVERUNDER_PARTICIPANT_GOALS
3WAYOVERUNDER_PARTICIPANT_RUNS
ASIANHANDICAP_PARTICIPANT_BOOKINGS
ASIANHANDICAP_PARTICIPANT_CORNERS
ASIANHANDICAP_PARTICIPANT_GOALS
ASIANHANDICAP_PARTICIPANT_POINTS
ASIANOVERUNDER_PARTICIPANT_POINTS
BONTS_PARTICIPANT_GOALS
BTTSANDOVERUNDER_PARTICIPANT_GOALS
BTTSANDOVERUNDER_PARTICIPANT_POINTS
BTTSANDOVERUNDER_PARTICIPANT_RUNS
BTTSANDOVERUNDER_PARTICIPANT_SETS
CORRECTSCORE_PARTICIPANT_CORNERS
CORRECTSCORE_PARTICIPANT_GAMES
CORRECTSCORE_PARTICIPANT_GOALS

CORRECTSCORE_PARTICIPANT_LEGS
CORRECTSCORE_PARTICIPANT_MAPS
CORRECTSCORE_PARTICIPANT_POINTS
CORRECTSCORE_PARTICIPANT_ROUNDS
CORRECTSCORE_PARTICIPANT_RUNS
CORRECTSCORE_PARTICIPANT_SETS
CORRECTSCORE_PARTICIPANT_YELLOWCARDS
CORRECTSCORE_SERIES_GAMES
DNB_PARTICIPANT_180S
DNB_PARTICIPANT_CORNERS
DNB_PARTICIPANT_HIGHESTCHECKOUT
DNB_PARTICIPANT_RESULT
DOUBLECHANCE_PARTICIPANT_RESULT
EUROHANDICAP_PARTICIPANT_180S
EUROHANDICAP_PARTICIPANT_2POINTS
EUROHANDICAP_PARTICIPANT_3POINTS
EUROHANDICAP_PARTICIPANT_ACES
EUROHANDICAP_PARTICIPANT_ASSISTS
EUROHANDICAP_PARTICIPANT_BREAKOFSERVES
EUROHANDICAP_PARTICIPANT_BREAKPOINTS
EUROHANDICAP_PARTICIPANT_CORNERS
EUROHANDICAP_PARTICIPANT_DISTANCECOVERED
EUROHANDICAP_PARTICIPANT_DOUBLEFAULTS
EUROHANDICAP_PARTICIPANT_FACEOFFS
EUROHANDICAP_PARTICIPANT_FOULS
EUROHANDICAP_PARTICIPANT_FREETHROWS
EUROHANDICAP_PARTICIPANT_GAMES
EUROHANDICAP_PARTICIPANT_GOALKICKS
EUROHANDICAP_PARTICIPANT_GOALS
EUROHANDICAP_PARTICIPANT_HITS
EUROHANDICAP_PARTICIPANT_HITWOODWORK
EUROHANDICAP_PARTICIPANT_HOMERUNS
EUROHANDICAP_PARTICIPANT_KILLS
EUROHANDICAP_PARTICIPANT_LEGS
EUROHANDICAP_PARTICIPANT_MAPS
EUROHANDICAP_PARTICIPANT_MINORPENALTIES
EUROHANDICAP_PARTICIPANT_OFFSIDES
EUROHANDICAP_PARTICIPANT_PENALTYTHROWS
EUROHANDICAP_PARTICIPANT_POINTS
EUROHANDICAP_PARTICIPANT_POWERPLAYGOALS
EUROHANDICAP_PARTICIPANT_QUARTERS
EUROHANDICAP_PARTICIPANT_REBOUNDS
EUROHANDICAP_PARTICIPANT_REDCARDS
EUROHANDICAP_PARTICIPANT_ROUNDS
EUROHANDICAP_PARTICIPANT_RUNS
EUROHANDICAP_PARTICIPANT_SETS
EUROHANDICAP_PARTICIPANT_SHOTS
EUROHANDICAP_PARTICIPANT_SHOTSBLOCKED
EUROHANDICAP_PARTICIPANT_STEALS
EUROHANDICAP_PARTICIPANT_THROWINS
EUROHANDICAP_PARTICIPANT_TOWERS
EUROHANDICAP_PARTICIPANT_TURNOVERS
EUROHANDICAP_PARTICIPANT_UNFORCEDERRORS
EUROHANDICAP_PARTICIPANT_YELLOWCARDS
EUROHANDICAP_SERIES_GAMES
EVENT_PARTICIPANT_BREAKOFSERVES
EVENT_PARTICIPANT_CLEANSHEET
EVENT_PARTICIPANT_GOALS
EXACTTOTAL_PARTICIPANT_GOALS
EXACTTOTAL_PLAYER_GOALS

MONEYLINE_PARTICIPANT_RESULT
MONEYLINE_PARTICIPANT_TOQUALIFY
MONEYLINE_PARTICIPANT_WINTOSS
MONEYLINE_SERIES_RESULT
NTH_PARTICIPANT_180S
NTH_PARTICIPANT_3POINTS
NTH_PARTICIPANT_BOOKINGS
NTH_PARTICIPANT_BREAKOFSERVES
NTH_PARTICIPANT_CORNERS
NTH_PARTICIPANT_FIELDGOALS
NTH_PARTICIPANT_FREETHROWS
NTH_PARTICIPANT_GOALS
NTH_PARTICIPANT_KILLS
NTH_PARTICIPANT_POINTS
NTH_PARTICIPANT_RUNS
NTH_PLAYER_2POINTS
NTH_PLAYER_3POINTS
NTH_PLAYER_FIELDGOALS
NTH_PLAYER_GOALS
NTH_PLAYER_POINTS
NTH_PLAYER_TOUCHDOWNS
NTH3WAY_PARTICIPANT_CORNERS
NTH3WAY_PARTICIPANT_FIELDGOALS
NTH3WAY_PARTICIPANT_GOALS
NTH3WAY_PARTICIPANT_RUNS
NTH3WAY_PARTICIPANT_TOUCHDOWNS
ODDEVEN_PARTICIPANT_2POINTS
ODDEVEN_PARTICIPANT_3POINTS
ODDEVEN_PARTICIPANT_ACES
ODDEVEN_PARTICIPANT_ASSISTS
ODDEVEN_PARTICIPANT_BOOKINGS
ODDEVEN_PARTICIPANT_BREAKOFSERVES
ODDEVEN_PARTICIPANT_BREAKPOINTS
ODDEVEN_PARTICIPANT_CORNERS
ODDEVEN_PARTICIPANT_DOUBLEFAULTS
ODDEVEN_PARTICIPANT_FOULS
ODDEVEN_PARTICIPANT_GAMES
ODDEVEN_PARTICIPANT_GOALS
ODDEVEN_PARTICIPANT_HITS
ODDEVEN_PARTICIPANT_HOMERUNS
ODDEVEN_PARTICIPANT_KILLS
ODDEVEN_PARTICIPANT_LEGS
ODDEVEN_PARTICIPANT_MAPS
ODDEVEN_PARTICIPANT_POINTS
ODDEVEN_PARTICIPANT_REBOUNDS
ODDEVEN_PARTICIPANT_ROUNDS
ODDEVEN_PARTICIPANT_RUNS
ODDEVEN_PARTICIPANT_SETS
ODDEVEN_PARTICIPANT_TRIES
ODDEVEN_PARTICIPANT_YELLOWCARDS
OVER_PLAYER_GOALS
OVER_PLAYER_OFFSIDES
OVER_PLAYER_PASSES
OVER_PLAYER_SHOTSOUTSIDEBOX
OVER_PLAYER_TACKLES
OVER_PLAYER_TOUCHDOWNS
OVERUNDER_MATCH_TIEBREAKS
OVERUNDER_PARTICIPANT_180S
OVERUNDER_PARTICIPANT_2POINTS
OVERUNDER_PARTICIPANT_3POINTS

OVERUNDER_PARTICIPANT_ACES
OVERUNDER_PARTICIPANT_ASSISTS
OVERUNDER_PARTICIPANT_BOOKINGS
OVERUNDER_PARTICIPANT_BREAKOFSERVES
OVERUNDER_PARTICIPANT_BREAKPOINTS
OVERUNDER_PARTICIPANT_CHECKOUT
OVERUNDER_PARTICIPANT_CONSECUTIVEPOINTS
OVERUNDER_PARTICIPANT_CORNERS
OVERUNDER_PARTICIPANT_DEUCEGAMES
OVERUNDER_PARTICIPANT_DISTANCECOVERED
OVERUNDER_PARTICIPANT_DOUBLEFAULTS
OVERUNDER_PARTICIPANT_EXTRABASEHITS
OVERUNDER_PARTICIPANT_FACEOFFS
OVERUNDER_PARTICIPANT_FIELDGOALS
OVERUNDER_PARTICIPANT_FOULS
OVERUNDER_PARTICIPANT_FOURS
OVERUNDER_PARTICIPANT_FREETHROWS
OVERUNDER_PARTICIPANT_GAMES
OVERUNDER_PARTICIPANT_GOALKICKS
OVERUNDER_PARTICIPANT_GOALS
OVERUNDER_PARTICIPANT_HIGHESTCHECKOUT
OVERUNDER_PARTICIPANT_HITS
OVERUNDER_PARTICIPANT_HITWOODWORK
OVERUNDER_PARTICIPANT_HOMERUNS
OVERUNDER_PARTICIPANT_KILLS
OVERUNDER_PARTICIPANT_LEGS
OVERUNDER_PARTICIPANT_MAPDURATION
OVERUNDER_PARTICIPANT_MAPS
OVERUNDER_PARTICIPANT_MINORPENALTIES
OVERUNDER_PARTICIPANT_OFFSIDES
OVERUNDER_PARTICIPANT_PENALTYKICKSMISSED
OVERUNDER_PARTICIPANT_PENALTYKICKSTAKEN
OVERUNDER_PARTICIPANT_PENALTYTHROWS
OVERUNDER_PARTICIPANT_POINTS
OVERUNDER_PARTICIPANT_POWERPLAYGOALS
OVERUNDER_PARTICIPANT_REBOUNDS
OVERUNDER_PARTICIPANT_REDCARDS
OVERUNDER_PARTICIPANT_ROUNDS
OVERUNDER_PARTICIPANT_RUNS
OVERUNDER_PARTICIPANT_SACKS
OVERUNDER_PARTICIPANT_SETS
OVERUNDER_PARTICIPANT_SHOTS
OVERUNDER_PARTICIPANT_SHOTSBLOCKED
OVERUNDER_PARTICIPANT_SHOTSONGOAL
OVERUNDER_PARTICIPANT_SIXES
OVERUNDER_PARTICIPANT_STEALS
OVERUNDER_PARTICIPANT_SUBSTITUTIONS
OVERUNDER_PARTICIPANT_THROWINS
OVERUNDER_PARTICIPANT_TOUCHDOWNS
OVERUNDER_PARTICIPANT_TOWERS
OVERUNDER_PARTICIPANT_TRIES
OVERUNDER_PARTICIPANT_TURNOVERS
OVERUNDER_PARTICIPANT_UNFORCEDERRORS
OVERUNDER_PARTICIPANT_VIDOREVIEWS
OVERUNDER_PARTICIPANT_YELLOWCARDS
OVERUNDER_PLAYER_3POINTS
OVERUNDER_PLAYER_AGG
OVERUNDER_PLAYER_ASSISTS
OVERUNDER_PLAYER_BASES
OVERUNDER_PLAYER_BATTERSTRIKEOUTS

OVERUNDER_PLAYER_BLOCKEDSHOTS
OVERUNDER_PLAYER_BLOCKS
OVERUNDER_PLAYER_DOUBLES
OVERUNDER_PLAYER_EARNEDRUNS
OVERUNDER_PLAYER_EARNEDRUNSALLOWED
OVERUNDER_PLAYER_EXTRAPPOINTS
OVERUNDER_PLAYER_FIELDGOALS
OVERUNDER_PLAYER_FOURS
OVERUNDER_PLAYER_GOALS
OVERUNDER_PLAYER_GOALSAGAINST
OVERUNDER_PLAYER_HITS
OVERUNDER_PLAYER_HITSALLOWED
OVERUNDER_PLAYER_HOMERUNS
OVERUNDER_PLAYER_HOMERUNSALLOWED
OVERUNDER_PLAYER_INTERCEPTIONS
OVERUNDER_PLAYER_KICKINGPOINTS
OVERUNDER_PLAYER_LONGESTPASSINGCOMPLETION
OVERUNDER_PLAYER_LONGESTRECEPTION
OVERUNDER_PLAYER_LONGESTRUSH
OVERUNDER_PLAYER_OUTS
OVERUNDER_PLAYER_PASSINGATTEMPTS
OVERUNDER_PLAYER_PASSINGCOMPLETIONS
OVERUNDER_PLAYER_PASSINGTOUCHDOWNS
OVERUNDER_PLAYER_PASSINGYARDS
OVERUNDER_PLAYER_PITCHERSTRIKEOUTS
OVERUNDER_PLAYER_PITCHOUTS
OVERUNDER_PLAYER_POINTS
OVERUNDER_PLAYER_POWERPLAYPOINTS
OVERUNDER_PLAYER_RBIS
OVERUNDER_PLAYER_REBOUNDS
OVERUNDER_PLAYER_RECEIVINGTOUCHDOWNS
OVERUNDER_PLAYER_RECEIVINGYARDS
OVERUNDER_PLAYER_RECEPTIONS
OVERUNDER_PLAYER_RUNS
OVERUNDER_PLAYER_RUSHINGATTEMPTS
OVERUNDER_PLAYER_RUSHINGTOUCHDOWNS
OVERUNDER_PLAYER_RUSHINGYARDS
OVERUNDER_PLAYER_SAVES
OVERUNDER_PLAYER_SHOTS
OVERUNDER_PLAYER_SHOTSONGOAL
OVERUNDER_PLAYER_SINGLES
OVERUNDER_PLAYER_STEALS
OVERUNDER_PLAYER_STOLENBASES
OVERUNDER_PLAYER_TACKLES
OVERUNDER_PLAYER_TOUCHDOWNRECEPTIONS
OVERUNDER_PLAYER_TOUCHDOWNS
OVERUNDER_PLAYER_TRIPLES
OVERUNDER_PLAYER_TURNOVERS
OVERUNDER_SERIES_GAMES
RACETO_PARTICIPANT_GAMES
RACETO_PARTICIPANT_GOALS
RACETO_PARTICIPANT_KILLS
RACETO_PARTICIPANT_LEGS
RACETO_PARTICIPANT_POINTS
RACETO_PARTICIPANT_ROUNDS
RACETO3WAY_PARTICIPANT_CORNERS
RACETO3WAY_PARTICIPANT_GOALS
RACETO3WAY_PARTICIPANT_POINTS
RACETO3WAY_PARTICIPANT_RUNS
TOLEAD_PARTICIPANT_GOALS

WINFROMBEHIND_PARTICIPANT_GOALS
WINNINGSCORE_PARTICIPANT_GAMES
WINNINGSCORE_PARTICIPANT_GOALS
YESNO_GAME_DEUCE
YESNO_MATCH_EXTRAINNINGS
YESNO_MATCH_GODISTANCE
YESNO_MATCH_OVERTIME
YESNO_MATCH_PENALTYKICKS
YESNO_MATCH_SETS
YESNO_MATCH_SUDDENDEATH
YESNO_MATCH_TIEBREAK
YESNO_PARTICIPANT_BOMBPLANTED
YESNO_PARTICIPANT_GOALS
YESNO_PARTICIPANT_RAMPAGE
YESNO_PARTICIPANT_WICKETS
YESNO_PLAYER_DOUBLEDDOUBLE
YESNO_PLAYER_GOALIEWIN
YESNO_PLAYER_RECORDAWIN
YESNO_PLAYER_SHUTOUT
YESNO_PLAYER_TRIPLEDDOUBLE
YESNO_SET_EXTRAPPOINTS
YESNO_SET_TIEBREAK

Note: As SuperOddsTypes are added regularly this list may be out of date so please use the /oddstypes endpoint to obtain a current up to date list.

Document History

Changes

This section is intended to give a quick overview over the most important and / or obvious changes to the feed formatting and features for each release of this User guide document.

Version 1.24

GameState values updated for odds, synthetic odds and fixtures messages. Message Examples section updated to indicate more clearly where fields may contain Null. Fixtures, CoverageStatus=Rejected removed. Instances of "" replaced by "" . EUROPEAN_GOAL_HANDICAP explanation updated. Context Shipping section re-written to recommend Last-Event-Id should be used in reconnecting.	AP	04/11/2025
---	----	------------

Version 1.23

Scores endpoint additional filters	AP	28/05/2025
------------------------------------	----	------------

Version 1.22

Stable Price - ice hockey added Scores replay of virtual fixtures	AP	26/03/2025
--	----	------------

Version 1.21

Fixtures message ExtraFields CoverageSecondaryData added.	AP	26/06/2024
---	----	------------

Version 1.20

Scores endpoint added. Fixtures message contains new ScoresCaptureTracking parameter and ExtraFields CoverageStatus and CoverageType. Bookmakers message updated to differentiate between regular and exchange books. TXStablePrice - baseball added, US football updated	AP	21/06/2024
--	----	------------

Version 1.19

TXStablePrice - Volleyball and Handball added. Participant1IsHome section added. SuperOddsType prefix based subscriptions to be removed.	AP	08/04/2024
--	----	------------

Version 1.18

Entity Status explanation updated. Players endpoint updated. Teams endpoint added. Matchdata endpoint added. TXStablePrice section added. Dampening added to Synthetics. Evensline improvements and scope reduced to a single bookmaker. Optald, SDAPI and RunningballId references removed. SuperOddsTypes list updated.	AP	19/01/2024
---	----	------------

Version 1.17

Players endpoint added Snapshot deprecated	AP	14/09/2023
---	----	------------

Version 1.16

Example Player Prop market added	AP	04/08/2023
----------------------------------	----	------------

Version 1.15

Synthetics - new section added Fusion Basic Subscription Query DSL synthetics added. Event Types & Message Format synthetics added. Appendices, Message Examples, synthetic odds section added. References to ASIANOVERUNDER markets removed. Fusion UAT release procedures updated. Contact email address changed. MessageId and LegacyMessageId changes. GameState list updated.	AP	25/07/2023
--	----	------------

Version 1.13

Copyright information changed.	AP	14/02/2023
--------------------------------	----	------------

Version 1.12

General Enquiries, Phone section removed. Context Shipping Advance query market periods case sensitive	AP	03/12/2022
--	----	------------

Version 1.11

Odds snapshot endpoint added New section - Message Identifiers and Sequencing Items of Interest - RunningballIds available using ExtraFields parameter.	AP	15/02/2022
---	----	------------

Version 1.10

Runningball Ids - Message Examples, Odds & Fixtures Message examples - streaming vs static endpoints	AP	13/12/2021
---	----	------------

Version 1.09

Fusion Subscription Query DSL, Odds and Fixtures, Optional Parameters Days and Hours added. Fusion Advanced Query DSL section added. Context Shipping - Days and Hours filters section added.	AP	31/10/2021
--	----	------------

Version 1.08

Getting Started - Environments and Release Procedures sections added. Fusion Subscription Query DSL - ExtraFields query parameter added to /odds, /fixtures, /fixturegroups, /competitions endpoints. Items of Interest section added. Message Examples - message default fields, OfferId and OfferIdHash fields added.	AP	04/09/2021
---	----	------------

Version 1.07

Roadmap, versioning. Messageld, INTERNAL USE ONLY Ts and LEI should not be combined. p14 typo fixtureGroups -> fixturegroups	AP	11/07/2021
---	----	------------

Version 1.06

Oddstypes endpoint added.	AP	26/03/21
---------------------------	----	----------

Version 1.05 DRAFT

Use of wildcards for SuperOddsTypes in queries removed and replaced by use of SuperOddsType prefix or full name. OTBs explanation. Ts filter no OTBs or suspensions, current state only. LEI contains Suspensions and OTBs approx. 2 hrs worth. New event types. Roadmap Legacy systems Query DSL - InRunning parameter values changed to true/false/all Bookmakers endpoint Countries endpoint Sports endpoint Competitions endpoint Using Last-Event-Id change to Id and example message Updated examples of odds, fixtures, fixturegroups message schemas	AP	27/02/21
---	----	----------

New examples of competitions, sports, bookmakers, countries message schemas		
---	--	--

Version 1.01 DRAFT

Fixed typos where `MarketParameters` was shown as `MarketParams`	MC	22/09/20
--	----	----------

Version 1.00 DRAFT

Initial document drafted	AP	11/09/20
Reviewed and formatting	MC	12/09/20