9" x 49" VERTICAL MILL W/POWER FEED

- Motor: 2 HP, 110/220V, Single Phase, TEFC
- Spindle travel: 5"
- Table size: 9" x 49"
- Table travel (longitudinal): 303/4"
- Max. dist. spindle to table: 18"
- Max, dist, spindle to column: 20°
- Knee travel: 16"
- Head tilt: 45" both ways
- Head swivel: 90" both ways
- T-slots: T-slots: Three 1/6" slots, 21/2" on center
- Range of speeds (RPM): 78, 98, 197, 278, 670, 850, 1700 and 2400
- Approximate shipping weight: 2405 lbs.

G9902 ONLY \$569500



13" x 40" GEAR-HEAD FLOOR LATHE

PURVEYORS OF FINE MACHINERY®, SINCE 1983!

. TRAINED SERVICE TECHNICIANS AT ALL 3 LOCATIONS . MOST ORDERS SHIP THE SAME DAY

· Net weight: 1320 lbs.

. Motor: 2 HP, 220 Volt, single phase

Height: 53½" • Length: 71½" • Width: 30"

 OVER A MILLION SQUARE FEET PACKED TO THE RAFTERS WITH MACHINERY & TOOLS . 2 OVERSEAS QUALITY CONTROL OFFICES STAFFED WITH QUALIFIED GRIZZLY ENGINEERS . HUGE PARTS FACILITY WITH OVER 1 MILLION PARTS IN STOCK AT ALL TIMES

- Swing over bed: 13"
- Swing over gap: 183/4"
- Swing over saddle: 73/4"
- Distance between centers: 40" . Approx. shipping
- Bed width: 73/6"
- Hole through spindle: 17/16"
- Taper of spindle nose: MT#5
- Spindle nose: D1-4
- Cross slide travel: 61/1" Compound travel: 21/16"
- Tailstock barrel taper: MT#3
- Tailstock barrel travel: 33/4"
- Number of speeds: 8

CABINET

Range of speeds: 70, 115, 190, 300, 460, 755, 1255, 2000 RPM





G9036 ONLY \$479500 - 3550

Blast compartment door size: 371/2" wide x 291/4" tall

INDUSTRIAL SAND BLASTING

Dust collection motor: 11/2 HP, 110V

Overall dimensions: 511/2" wide x

Working pressure: 60-125 PSI

Approximate shipping weight: 436 lbs.

125 max. PSI @ 5-35 CFM

691/2" high x 47" deep

50" DELUXE PAN AND BOX BRAKE

- Maximum working width: 50°
- Maximum sheet metal thickness: 16-gauge mild steel at full width
- Maximum height of pan/box sides: 2"
- Minimum reverse bend: 3/4"
- Maximum bending angle: 135°
- Overall dimensions: 63" W x 443/4" H x 38" D
- Approximate shipping weight: 945 lbs



G0714 ONLY \$129500

Detailed instruction manual



TO EXACTING

SPECIFICATIONS

T10718 ONLY \$147500 4 HP, 220V, 3-PHASE METALWORKING PROFESSIONAL PLANISHING HAMMER

- BELT SANDER
- 4 HP, 220V, 3-phase, 11A motor · 8" rubber contact wheel
- · Quick release belt
- . 3" x 201/2" graphite-backed platen
- 3" x 79" belt size
- · Work stop for use with the platen
- · Work rest for use with the contact wheel
- Overall size: 39"W x 22½"D x 48"H (head raised)
- Approximate shipping weight: 248 lbs.



1-800-523-4777

Overall dimensions: 62"H x 301/4"W x Frame tube size: 4" x 4"

- Throat: 24"
- Head opening: 2½* Air requirements: 15-120 PSI
- CFM requirements: 12
- Blows per minute: 4,600 Height adjustment: 11/2"
- Includes a water filter, regulator and
- in-line oiler unit Approximate shipping weight: 213 lbs.









3 GREAT SHOWROOMS! BELLINGHAM, WA . MUNCY, PA . SPRINGFIELD, MO



TECHNICAL SERVICE: 570-546-9663 FAX: 800-438-5901



Eagle Machine Tool Tree Machine Tool Co.



www.eaglemachinetool.com

Serving the metal and wood working

industries for 22 years

CONTACT US

(P): 231-798-8473 | (F): 231-798-7679 | (E): eagle1cnc@aol.com

Purchased assets of Tree Machine in April, 2009:

Tree Mill parts, wiring prints and operation manuals available

CNC Retrofits - Boring Mills (80+)

Grinders, Lathes, Routers, Machining Centers, Rotary Tables Sales and Service of Mitsubishi PLC and CNC Controls

CNC Custom Machines

PC2100 support and hard drive repair Laser Calibration

Renishaw Ball Bar analysis

ZF Gearbox conversions

Heidenhain and Fagor Scales

Custom Jog Boxes and machine operation panels

Pushbuttons and BCD switches Replacement Handwheels (5volt and 12volt)

Examples of Recently Completed Retrofits:







