

Modelling the effects of domestication in Wheat through novel computer vision techniques

Author: Nathan Hughes (nah26@aber.ac.uk)
Supervisor: Dr. Wayne Aubrey (waa2@aber.ac.uk)
Degree Scheme G401 (Computer Science)

Date: April 5, 2018
Revision: 0.1
Status: Draft

This report was submitted as partial fulfilment
of a BSc degree in Computer Science (G401)

Declaration of originality

I confirm that:

- This submission is my own work, except where clearly indicated.
- I understand that there are severe penalties for Unacceptable Academic Practice, which can lead to loss of marks or even the withholding of a degree.
- I have read the regulations on Unacceptable Academic Practice from the University's Academic Quality and Records Office (AQRO) and the relevant sections of the current Student Handbook of the Department of Computer Science.
- In submitting this work I understand and agree to abide by the University's regulations governing these issues.

Name

Date

Consent to share this work

By including my name below, I hereby agree to this dissertation being made available to other students and academic staff of the Aberystwyth Computer Science Department.

Name

Date

Contents

1	Introduction, Analysis and Objectives	7
1.1	Background	7
1.2	Problem Analysis	7
1.3	Objectives	7
2	Method Design	8
2.1	Improvements to 3D imaging software	8
2.1.1	New Watershed Algorithm	8
2.2	Testing of Software	8
3	Software Design, Testing and Implementation	9
3.1	Software Development Methodology	9
3.2	Data Pipeline	9
4	Results	11
4.1	Improved accuracy of imaging software	11
4.1.1	Effect of enhanced watershedding algorithm	11
5	Discussion	12
6	Critical Evaluation	13
6.1	Organisational Methods	13
6.2	Relevance to Degree	13
6.3	Time Management	13
6.4	Collaborative Work	13
6.5	Other Issues	13
7	<i>Code Segments and Examples</i>	14
7.1	MATLAB Watershedding	14
	References	15

List of Tables

List of Figures

3.1	Image Processing Pipeline	9
3.2	Data Pipeline and Information Flow	10
4.1	<i>A</i> showing the chessboard method, <i>B</i> improved quasi-euclidean method	11

List of Listings

1	MATLAB Watershedding function	14
---	---	----

Chapter 1

Introduction, Analysis and Objectives

Background

Problem Analysis

Objectives

Chapter 2

Method Design

Improvements to 3D imaging software

New Watershed Algorithm

In order to solve the problem of misidentified and joint seeds, from the primitive collection, I implemented a *quasi-euclidean* distance transform into the analysis pipeline [1]. This provided much better results than the previous *chessboard* transform which had been successful on more uniform data.

Quasi-Euclidean algorithm

This algorithm measures the total euclidean distance along a set of horizontal, vertical and diagonal line segments [2].

$$|x_1 - x_2| + (\sqrt{2} - 1) \cdot |x_1 - x_2| > |y_1 - y_2| (\sqrt{2} - 1) |x_1 - x_2|, \text{ otherwise} \quad (2.1)$$

In order to apply this to a 3D space Kleinberg's method is used [3]. This allows for nearest neighbour pixels to be sorted by k -dimensional trees and enabling fast distance transforms via Rosenfeld and Pfaltz's *quasi-euclidean* method stated in equation:2.1.

Testing of Software

Chapter 3

Software Design, Testing and Implementation

Software Development Methodology

Data Pipeline




Figure 3.1: Image Processing Pipeline




Figure 3.2: Data Pipeline and Information Flow

Chapter 4

Results

Improved accuracy of imaging software

Effect of enhanced watershedding algorithm




Figure 4.1: *A* showing the chessboard method, *B* improved quasi-euclidean method

Chapter 5

Discussion

Chapter 6

Critical Evaluation

Organisational Methods

Relevance to Degree

Time Management

Collaborative Work

Other Issues

Chapter 7

Code Segments and Examples

MATLAB Watershedding

```
function [W] = watershedSplit3D(A)
    % Takes image stack A and splits it into stack W
    % Convert to BW
    bw = logical(A);
    % Create variable for opening and closing
    se = strel('disk', 5);
    % Minimise object misshapen-ness
    bw = imerode(bw, se);
    bw = imdilate(bw, se);
    % Fill in any left over holes
    bw = imfill(bw,4,'holes');
    % Use chessboard for distance calculation for more refined splitting
    chessboard = -bwdist(~bw, 'quasi-euclidean');
    % Modify the intensity of our bwdist to produce chessboard2
    mask = imextendedmin(chessboard, 2);
    chessboard2 = imimposemin(chessboard, mask);
    % Calculate watershed based on the modified chessboard
    Ld2 = watershed(chessboard2);
    % Take original image and add on the lines calculated for splitting
    W = A;
    W(Ld2 == 0) = 0;
end
```

Listing 1: MATLAB Watershedding function

References

- [1] N. Hughes, K. Askew, C. P. Scotson, K. Williams, C. Sauze, F. Corke, J. H. Doonan, and C. Nibau, “Non-destructive, high-content analysis of wheat grain traits using X-ray micro computed tomography,” *Plant Methods*, vol. 13, 2017.
- [2] J. L. Pfaltz, “Sequential Operations in Digital Picture Processing,” *Journal of the ACM*, vol. 13, no. 4, pp. 471–494, oct 1966. [Online]. Available: <http://portal.acm.org/citation.cfm?doid=321356.321357>
- [3] J. M. Kleinberg, “Two algorithms for nearest-neighbor search in high dimensions,” in *Proceedings of the twenty-ninth annual ACM symposium on Theory of computing - STOC '97*. New York, New York, USA: ACM Press, 1997, pp. 599–608. [Online]. Available: <http://dl.acm.org/citation.cfm?id=258533.258653>