VIT-AP UNIVERSITY

SCOPE

REGISTER NUMBER	23BCE20070
STUDENT NAME	Bonala Shanmukesh

WEB TECHNOLOGIES LAB

CSE 4004

RECORD BOOK

WIN-SEM:2025-26

INDEX

S.No.	Name of the Experiment	Page No.	Date of Conduction
1	Designing Portfolio Webpage	3	12-12-2025
2	Student Registration Page Design using HTML5	6	18-12-2025
3	Pattern Creation using HTML & CSS	9	09-01-2026
4	Implementation of Drag and Drop Feature in HTML5	10	23-01-2026
5	Implementation of Calculator using JavaScript and CSS	12	30-01-2026
6	Implementation of Income Tax Calculator using JavaScript and CSS	14	13=02-2026
7	Demonstration of CRUD Operations Using MongoDB	17	27-02-2026
8	Formulation of Queries Using Aggregation Pipeline in MongoDB	21	13-03-2026
9	Implementation of AJAX program to read data from JSON File	23	20-03-2026
10	Create a web application to simulate an online shopping order process using ES6 features such as arrow functions, callbacks, and async/await.	24	10-03-2026
11	Deploying React and building simple application	26	10-04-2026

Experiment No. 01

Aim: Design a Portfolio webpage consisting of the following

i. **Student Name**
ii. **Profile Pic**
iii. **Career Objective**
iv. **Short Introduction**
v. **Educational Qualifications**
vi. **Technical Skills**
vii. **Project Details**
viii. **Internship/Certifications**
ix. **Hobbies**
x. **Achievements**
xi. **Contact Information (email, link to social media pages)**

Program:

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <title>Student Portfolio</title>
  </head>
  <body>
    <!-- Header Section -->
    <header>
      <h1>Student Portfolio</h1>
      <center>
        <h1>SHANMUKESH BONALA</h1>
        <figure>
          <img src="images/image.png" alt="Profile Picture" title="Profile Picture"
height="200px">
          <figcaption>Shanmukesh</figcaption>
        </figure>
      </center>
      <h3>Career Objective</h3>
      <p>I am a passionate and dedicated student pursuing a Bachelor's degree in Computer
Science. My goal is to leverage my technical skills and creativity to contribute to innovative
projects and drive impactful solutions in the field of technology.</p>

      <h3>Short Introduction</h3>
      <p>Hello! I'm John Doe, a final-year B.Tech student specializing in Computer Science and
Engineering. I enjoy solving complex problems, exploring new technologies, and working on
projects that make a difference. My interests lie in artificial intelligence, web development, and
data science.</p>
    </header>

    <!-- Main Content -->
```

```
<main>
  <!-- Educational Qualifications -->
  <section>
    <h2>Educational Qualifications</h2>
    <table border="1">
      <tr>
        <th>Degree</th>
        <th>Institution</th>
        <th>Year</th>
        <th>CGPA/Percentage</th>
      </tr>
      <tr>
        <td>B.Tech in Computer Science</td>
        <td>VIT-AP University</td>
        <td>2023 - 2027</td>
        <td>9.26 CGPA</td>
      </tr>
      <tr>
        <td>Intermediate (12th)</td>
        <td>Bheeram Sridhar  Reddy Junior college</td>
        <td>2023</td>
        <td>97.3%</td>
      </tr>
      <tr>
        <td> (10th)</td>
        <td>Sri Chaitanya School</td>
        <td>2021</td>
        <td>100%</td>
      </tr>
    </table>
  </section>

  <!-- Technical Skills -->
  <section>
    <h2>Technical Skills</h2>
    <ol type="I">
      <li>Programming Languages: Python, Java, C++</li>
      <li>Web Development: HTML, JavaScript (Basic)</li>
      <li>Databases: MySQL, MongoDB</li>
      <li>Tools: Git, VS Code, Jupyter Notebook</li>
      <li>Other Skills: Machine Learning, Data Analysis</li>
    </ol>
  </section>

  <!-- Project Details -->
  <section>
    <h2>Project Details</h2>
    <ul>
      <li><strong>Project 1:</strong> Weather Forecasting App (Python, Flask)</li>
      <li><strong>Project 2:</strong> E-Commerce Website (HTML, CSS, JavaScript)</li>
      <li><strong>Project 3:</strong> Chatbot for Customer Support (Python, NLP)</li>
```

```
            </ul>
        </section>

        <!-- Internship/Certifications -->
        <section>
            <h2>Internship/Certifications</h2>
            <dl>
                <dt>Internship at Tech Solutions Pvt. Ltd</dt>
                <dt>Certification in Machine Learning</dt>
            </dl>
        </section>

        <!-- Hobbies -->
        <section>
            <h2>Hobbies</h2>
            <ul>
                <li>Reading books</li>
                <li>Playing chess</li>
                <li>Coding</li>
                <li>Photography</li>
            </ul>
        </section>

        <!-- Achievements -->
        <section>
            <h2>Achievements</h2>
            <ul>
                <li>1st Prize in National Level Coding Competition</li>
                <li>Published a research paper on "AI in Healthcare"</li>
                <li>Volunteered for community service projects</li>
            </ul>
        </section>
    </main>

    <!-- Footer with Contact Information -->
    <footer>
        <h2>Contact Information</h2>
        <p>Email: <a
href="mailto:john.doe@example.com">shanmukesh.bonala@gmail.com</a></p>
        <p>LinkedIn: <a href="https://linkedin.com/in/johndoe" target="_blank">LinkedIn
Profile</a></p>
        <p>GitHub: <a href="https://github.com/johndoe" target="_blank">GitHub Profile</a></p>
        <p>Location: Ananthapur, Andhra Pradesh, India</p>
    </footer>
  </body>
</html>
```

Output:

Student Portfolio

SHANMUKESH BONALA

Shanmukesh

Career Objective

I am a passionate and dedicated student pursuing a Bachelor's degree in Computer Science. My goal is to leverage my technical skills and creativity to contribute to innovative projects and drive impactful solutions in the field of technology.

Short Introduction

Hello! I'm John Doe, a final-year B.Tech student specializing in Computer Science and Engineering. I enjoy solving complex problems, exploring new technologies, and working on projects that make a difference. My interests lie in artificial intelligence, web development, and data science.

Educational Qualifications

Degree	Institution	Year	CGPA/Percentage
B.Tech in Computer Science	VIT-AP University	2023 - 2027	9.26 CGPA
Intermediate (12th)	Bheeram Sridhar Reddy Junior college	2023	97.3%
(10th)	Sri Chaitanya School	2021	100%

Project Details

- **Project 1:** Weather Forecasting App (Python, Flask)
- **Project 2:** E-Commerce Website (HTML, CSS, JavaScript)
- **Project 3:** Chatbot for Customer Support (Python, NLP)

Internship/Certifications

Internship at Tech Solutions Pvt. Ltd
Certification in Machine Learning

Hobbies

- Reading books
- Playing chess
- Coding
- Photography

Achievements

- 1st Prize in National Level Coding Competition
- Published a research paper on "AI in Healthcare"
- Volunteered for community service projects

Contact Information

Email: shanmukesh.bonala@gmail.com

LinkedIn: LinkedIn Profile

GitHub: GitHub Profile

Location: Ananthapur, Andhra Pradesh, India

Experiment No. 02

Design a Student Registration Form

Program:

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <title>Student Registration Form</title>
  </head>
  <body>
    <center>
      <h1>Student Registration Form</h1>
      <form>
        <!-- Username -->
        <label for="username">Username:</label>
```

```
        <input type="text" id="username" name="username" placeholder="Enter your username"
required><br><br>
        <!-- Password -->
        <label for="password">Password:</label>
        <input type="password" id="password" name="password" placeholder="Enter your password"
required><br><br>
        <!-- Date of Birth -->
        <label>Date of Birth:</label>
        <select id="day" name="day" required>
          <option value="">Day</option>
          <option value="1">1</option>
          <option value="2">2</option>
          <option value="3">3</option>
          <!-- Add more days -->
        </select>
        <select id="month" name="month" required>
          <option value="">Month</option>
          <option value="January">January</option>
          <option value="February">February</option>
          <option value="March">March</option>
          <!-- Add more months -->
        </select>
        <select id="year" name="year" required>
          <option value="">Year</option>
          <option value="2000">2000</option>
          <option value="2001">2001</option>
          <option value="2002">2002</option>
          <!-- Add more years -->
        </select><br><br>          <label>Gender:</label>
        <input type="radio" id="male" name="gender" value="male" required>
        <label for="male">Male</label>
        <input type="radio" id="female" name="gender" value="female">
        <label for="female">Female</label>
        <input type="radio" id="other" name="gender" value="other">
        <label for="other">Other</label><br><br>
        <!-- Address -->
        <label for="address">Address:</label><br>
        <textarea id="address" name="address" rows="4" cols="50" placeholder="Enter your address"
required></textarea><br><br>
        <!-- Email -->
        <label for="email">Email:</label>
        <input type="email" id="email" name="email" placeholder="Enter your email" required><br><br>
        <!-- Phone Number -->
        <label for="phone">Phone Number:</label>
        <input type="tel" id="phone" name="phone" placeholder="Enter your phone number"
required><br><br>
        <!-- Department -->
        <label for="department">Department:</label>
        <select id="department" name="department" required>
          <option value="">Select Department</option>
          <option value="CSE">Computer Science</option>
          <option value="ECE">Electronics and Communication</option>
          <option value="ME">Mechanical Engineering</option>
          <option value="CE">Civil Engineering</option>
        </select><br><br>
        <!-- Course -->
        <label for="course">Course:</label>
```

```
            <select id="course" name="course" required>
              <option value="">Select Course</option>
              <option value="B.Tech">B.Tech</option>
              <option value="M.Tech">M.Tech</option>
              <option value="PhD">PhD</option>
            </select><br><br>
            <!-- Languages Known -->
            <label>Languages Known:</label><br>
            <input type="checkbox" id="english" name="languages" value="english">
            <label for="english">English</label>
            <input type="checkbox" id="hindi" name="languages" value="hindi">
            <label for="hindi">Hindi</label>
            <input type="checkbox" id="tamil" name="languages" value="tamil">
            <label for="tamil">Tamil</label>
            <input type="checkbox" id="other_lang" name="languages" value="other">
            <label for="other_lang">Other</label><br><br>
            <!-- Submit and Reset Buttons -->
            <input type="submit" value="Submit">
            <input type="reset" value="Reset">
          </form>
        </center>
      </body>
    </html>
```

Output:



Experiment No. 03

Create the following patterns using HTML and CSS only.

Program:

```
<!DOCTYPE HTML>
<html>
  <head>
    <style>
      .container{
        color:red;
        /* background-color: brown; */
        display: grid;
        /* border: 1px solid black; */
        padding: 2px;

        /* margin: auto; */
        grid-template-columns: repeat(5, 60px);
        grid-auto-flow: row;
        grid-gap: 5px;
      }
      .child{
        background-color: aqua;
        text-align: center;
        justify-content: center;
        height: 50px;
        width: 50px;
        padding: 2px;
        margin: 1px;
        border: 1px solid black;
      }
      .brown1{
        background-color: rgb(238, 174, 90);
      }
      .brown2{
        background-color: rgb(241, 123, 12);
      }
      .brown3{
        background-color: rgb(207, 205, 74);
      }
    </style>
  </head>
  <body>
    <div class="container">
      <div class="child brown1"></div>
      <div class="child brown2"></div>
      <div class="child brown3"></div>
      <div class="child brown1"></div>
      <div class="child brown2"></div>

      <div class="child brown2"></div>
      <div class="child brown3"></div>
      <div class="child brown1"></div>
      <div class="child brown2"></div>
      <div class="child brown3"></div>
```

```
        <div class="child brown3"></div>
        <div class="child brown1"></div>
        <div class="child brown2"></div>
        <div class="child brown3"></div>
        <div class="child brown1"></div>

        <div class="child brown1"></div>
        <div class="child brown2"></div>
        <div class="child brown3"></div>
        <div class="child brown1"></div>
        <div class="child brown2"></div>

        <div class="child brown2"></div>
        <div class="child brown3"></div>
        <div class="child brown1"></div>
        <div class="child brown2"></div>
        <div class="child brown3"></div>
    </div>
  </body>
</html>
```

Output:



Experiment No. 04

Implement Drag n Drop feature in HTML 5

Program:

```
<!DOCTYPE html>
<html lang="en">
<head>
  <title>Drag and Drop Demo</title>
  <style>
    /* Minimal styling for clarity (optional) */
    #dropBox {
      width: 400px;
      height: 400px;
      border: 2px dashed black;
      margin: 20px auto;
    }
    .draggable {
      height: 100px;
      width: 100px;
```

```
        margin: 10px;
        cursor: move;
      }
    </style>
</head>
<body>
    <div id="dropBox" ondragover="dragOver(event)" ondrop="drop(event)"></div>

    <div>
      <img src="images/image1.png" class="draggable" id="image1" draggable="true"
ondragstart="dragStart(event)">
      <img src="images/image2.png" class="draggable" id="image2" draggable="true"
ondragstart="dragStart(event)">
      <img src="images/image.png" class="draggable" id="image3" draggable="true"
ondragstart="dragStart(event)">
    </div>

    <script>
      // Allow drop by preventing default
      function dragOver(event) {
        event.preventDefault();
      }

      // Handle drop
      function drop(event) {
        event.preventDefault();
        const data = event.dataTransfer.getData("text");
        const draggedElement = document.getElementById(data);
        event.target.appendChild(draggedElement);
      }

      // Set data on drag start
      function dragStart(event) {
        event.dataTransfer.setData("text", event.target.id);
      }
    </script>
</body>
</html>
```

Output:



Experiment No. 05

Design a Calculator using Java script and relevant CSS

Program:

```
<!DOCTYPE>
<html>
  <head>

    <style>
      .outerBox{
        display: grid;
        border: 1px solid black;
        padding: 10px;
        background-color: rgb(161, 144, 144);
        width: 320px;
      }
      .row{
        display: flex;
      }
      .ele{
        display: flex;
        height: 50px;
        width: 50px;
        background-color: rgb(200, 200, 236);
        margin: 5px;
        justify-content: center;
        text-align: center;
        padding: 10px;
      }
      .display{
        width: 350px;
        height: 50px;
        background-color: rgb(179, 238, 233);
      }

    </style>
  </head>
  <body>
    <div class="display" id="display">

    </div>
    <div class="outerBox">
      <div class="row">
        <div class="ele" id="_1">(</div>
        <div class="ele" id="_2">CE</div>
        <div class="ele" id="_3">)</div>
        <div class="ele" id="_4">C</div>
      </div>
      <div class="row">
        <div class="ele" id="_5">1</div>
        <div class="ele" id="_6">2</div>
        <div class="ele" id="_7">3</div>
        <div class="ele" id="_8">+</div>
      </div>
      <div class="row">
```

```
            <div class="ele" id="_9">4</div>
            <div class="ele" id="_10">5</div>
            <div class="ele" id="_11">6</div>
            <div class="ele" id="_12">-</div>
        </div>
        <div class="row">
            <div class="ele" id="_13">7</div>
            <div class="ele" id="_14">8</div>
            <div class="ele" id="_15">9</div>
            <div class="ele" id="_16">*</div>
        </div>
        <div class="row">
            <div class="ele" id="_17">.</div>
            <div class="ele" id="_18">0</div>
            <div class="ele" id="_19">=</div>
            <div class="ele" id="_20">/</div>
        </div>
    </div>
  </body>
  <script>
    const display = document.getElementById("display");
    const buttons = document.querySelectorAll(".ele");

    buttons.forEach(button => {
        button.addEventListener( "click",() =>{
            const value = button.textContent;
            // display.textContent = value;
            console.log(value);
            if(value=="C"){
                display.textContent = "";
            }else if(value=="="){
                display.textContent = eval(display.textContent);
            }else{
                display.textContent += value;
            }
        })
    })
  </script>
</html>
```

Output:



Experiment No. 06

Design an Income Tax Calculator using Java script and CSS.

Program:

```
<!DOCTYPE html>
<html lang="en">
<head>
  <title>Income Tax Calculator</title>
  <style>
    body {
      font-family: Arial, sans-serif;
      margin: 20px;
    }
    .container {
      width: 500px;
      margin: 0 auto;
      border: 1px solid #ccc;
      padding: 20px;
      border-radius: 5px;
      background-color: #f9f9f9;
    }
    h2 {
      color: #333;
      text-align: center;
    }
    .form-group {
      margin-bottom: 15px;
    }
    label {
      display: block;
      margin-bottom: 5px;
      font-weight: bold;
    }
    input[type="text"], input[type="number"] {
      width: 100%;
      padding: 8px;
      border: 1px solid #ccc;
      border-radius: 4px;
      box-sizing: border-box;
    }
    button {
      background-color: #4CAF50;
      color: white;
      padding: 10px 15px;
      border: none;
      border-radius: 4px;
      cursor: pointer;
      font-size: 16px;
    }
    button:hover {
      background-color: #45a049;
    }
    .result {
      margin-top: 20px;
      padding: 10px;
```

```
        background-color: #e9e9e9;
        border-radius: 4px;
    }
    .result-item {
        margin-bottom: 8px;
    }
  </style>
</head>
<body>
  <div class="container">
    <h2>Income Tax Calculator</h2>

    <div class="form-group">
        <label for="name">Name:</label>
        <input type="text" id="name" placeholder="Enter Your Name">
    </div>

    <div class="form-group">
        <label for="salary">Gross Annual Salary:</label>
        <input type="number" id="salary" placeholder="Enter your salary">
    </div>

    <div class="form-group">
        <label for="deduction">Standard Deduction:</label>
        <input type="number" id="deduction" value="75000" placeholder="Enter deduction">
    </div>

    <button onclick="calculateTax()">Calculate Tax</button>

    <div class="result" id="result">
        <h3>Result:</h3>
        <div class="result-item">Gross Income: ₹ <span id="grossIncome">0</span></div>
        <div class="result-item">Standard Deduction: ₹ <span id="standardDeduction">0</span></div>
        <div class="result-item">Taxable Income: ₹ <span id="taxableIncome">0</span></div>
        <div class="result-item">Income Tax: ₹ <span id="incomeTax">0</span></div>
        <div class="result-item">Cess (4%): ₹ <span id="cess">0</span></div>
        <div class="result-item">Final Tax Payable: ₹ <span id="finalTax">0</span></div>
    </div>
  </div>

  <script>
    function calculateTax() {
        // Get input values
        const name = document.getElementById('name').value;
        const grossIncome = parseFloat(document.getElementById('salary').value) || 0;
        const standardDeduction = parseFloat(document.getElementById('deduction').value) || 0;

        // Calculate taxable income
        const taxableIncome = grossIncome - standardDeduction;
        document.getElementById('grossIncome').textContent = grossIncome.toFixed(2);
        document.getElementById('standardDeduction').textContent = standardDeduction.toFixed(2);
        document.getElementById('taxableIncome').textContent = taxableIncome.toFixed(2);

        // Calculate income tax based on slabs
        let incomeTax = 0;
        if (taxableIncome <= 400000) {
            incomeTax = 0;
```

```
        } else if (taxableIncome <= 800000) {
          incomeTax = (taxableIncome - 400000) * 0.05;
        } else if (taxableIncome <= 1200000) {
          incomeTax = 20000 + (taxableIncome - 800000) * 0.10;
        } else if (taxableIncome <= 1600000) {
          incomeTax = 60000 + (taxableIncome - 1200000) * 0.15;
        } else if (taxableIncome <= 2000000) {
          incomeTax = 120000 + (taxableIncome - 1600000) * 0.20;
        } else if (taxableIncome <= 2400000) {
          incomeTax = 200000 + (taxableIncome - 2000000) * 0.25;
        } else {
          incomeTax = 300000 + (taxableIncome - 2400000) * 0.30;
        }

        // Calculate cess (4%)
        const cess = incomeTax * 0.04;

        // Calculate final tax
        const finalTax = incomeTax + cess;

        // Display results
        document.getElementById('incomeTax').textContent = incomeTax.toFixed(2);
        document.getElementById('cess').textContent = cess.toFixed(2);
        document.getElementById('finalTax').textContent = finalTax.toFixed(2);
      }
    </script>
  </body>
  </html>
```

Output:



Experiment No. 07

Demonstrate CRUD operations using MongoDB

Suppose you are managing a university database. There is a collection called students with documents containing rollNumber, name, age and cgpa.

i. Create Database University_DB

```
test> show dbs
admin   40.00 KiB
config  12.00 KiB
local   40.00 KiB
test> use University_DB
switched to db University_DB
University_DB> show dbs
admin   40.00 KiB
config  12.00 KiB
local   40.00 KiB
University_DB>
```

ii. Create Collection Students

```
University_DB> db.createCollection("Students")
{ ok: 1 }
University_DB> show collections
Students
University_DB>
```

iii. Insert Documents

{ rollNumber: 1, name: "Alice", age: 20, cgpa: 8.5 }

{ rollNumber: 2, name: "Bob", age: 21, cgpa: 7.8 }

{ rollNumber: 3, name: "Charlie", age: 19, cgpa: 9.0 }

```
University_DB> db.Students.insertMany([   { rollNumber: 1, name: "Alice", age: 20, cgpa: 8.5 },   { rollNumber: 2, name:
 "Bob", age: 21, cgpa: 7.8 },   { rollNumber: 3, name: "Charlie", age: 19, cgpa: 9.0 } ])
{
  acknowledged: true,
  insertedIds: {
    '0': ObjectId('69bcee0f92f97dcd0611402a'),
    '1': ObjectId('69bcee0f92f97dcd0611402b'),
    '2': ObjectId('69bcee0f92f97dcd0611402c')
  }
}
```

iv. Write a query to insert a new student named "David" with roll number 4, age

22, and CGPA 8.2.

```
University_DB> db.Students.insertOne({ rollNumber: 4, name: "David", age: 22, cgpa: 8.2 })
{
  acknowledged: true,
  insertedId: ObjectId('69bcee1892f97dcd0611402d')
}
```

v. Write a query to insert multiple students at once:

- Eve, roll number 5, age 20, CGPA 7.9
- Frank, roll number 6, age 23, CGPA 8.0

```
University_DB> db.Students.insertMany([
|   { rollNumber: 5, name: "Eve", age: 20, cgpa: 7.9 },
|   { rollNumber: 6, name: "Frank", age: 23, cgpa: 8.0 }
| ])
{
  acknowledged: true,
  insertedIds: {
    '0': ObjectId('69bcee1d92f97dcd0611402e'),
    '1': ObjectId('69bcee1d92f97dcd0611402f')
  }
}
University_DB>
```

vi. Write a query to find all students in the collection.

```
University_DB> db.Students.find()
[
  {
    _id: ObjectId('69bcee0f92f97dcd0611402a'),
    rollNumber: 1,
    name: 'Alice',
    age: 20,
    cgpa: 8.5
  },
  {
    _id: ObjectId('69bcee0f92f97dcd0611402b'),
    rollNumber: 2,
    name: 'Bob',
    age: 21,
    cgpa: 7.8
  },
  {
    _id: ObjectId('69bcee0f92f97dcd0611402c'),
    rollNumber: 3,
    name: 'Charlie',
    age: 19,
    cgpa: 9
  },
  {
    _id: ObjectId('69bcee1892f97dcd0611402d'),
    rollNumber: 4,
    name: 'David',
    age: 22,
    cgpa: 8.2
  },
  {
    _id: ObjectId('69bcee1d92f97dcd0611402e'),
    rollNumber: 5,
    name: 'Eve',
    age: 20,
    cgpa: 7.9
  },
  {
    _id: ObjectId('69bcee1d92f97dcd0611402f'),
    rollNumber: 6,
    name: 'Frank',
    age: 23,
    cgpa: 8
  }
]
University_DB>
```

vii. Write a query to find the student named "Alice".

```
University_DB> db.Students.find({ name: "Alice" })
[
  {
    _id: ObjectId('69bcee0f92f97dcd0611402a'),
    rollNumber: 1,
    name: 'Alice',
    age: 20,
    cgpa: 8.5
  }
]
University_DB>
```

viii. Write a query to find all students older than 20.

```
University_DB> db.Students.find({ age: { $gt: 20 } })
[
  {
    _id: ObjectId('69bcee0f92f97dcd0611402b'),
    rollNumber: 2,
    name: 'Bob',
    age: 21,
    cgpa: 7.8
  },
  {
    _id: ObjectId('69bcee1892f97dcd0611402d'),
    rollNumber: 4,
    name: 'David',
    age: 22,
    cgpa: 8.2
  },
  {
    _id: ObjectId('69bcee1d92f97dcd0611402f'),
    rollNumber: 6,
    name: 'Frank',
    age: 23,
    cgpa: 8
  }
]
University_DB>
```

ix. Write a query to find students with CGPA greater than 8.0.

```
University_DB> db.Students.find({ cgpa: { $gt: 8.0 } })
[
  {
    _id: ObjectId('69bcee0f92f97dcd0611402a'),
    rollNumber: 1,
    name: 'Alice',
    age: 20,
    cgpa: 8.5
  },
  {
    _id: ObjectId('69bcee0f92f97dcd0611402c'),
    rollNumber: 3,
    name: 'Charlie',
    age: 19,
    cgpa: 9
  },
  {
    _id: ObjectId('69bcee1892f97dcd0611402d'),
    rollNumber: 4,
    name: 'David',
    age: 22,
    cgpa: 8.2
  }
]
University_DB>
```

x. Write a query to find students with CGPA between 7.5 and 9.0.

```
University_DB> db.Students.find({ cgpa: { $gte: 7.5, $lte: 9.0 } })
[
  {
    _id: ObjectId('69bcee0f92f97dcd0611402a'),
    rollNumber: 1,
    name: 'Alice',
    age: 20,
    cgpa: 8.5
  },
  {
    _id: ObjectId('69bcee0f92f97dcd0611402b'),
    rollNumber: 2,
    name: 'Bob',
    age: 21,
    cgpa: 7.8
  },
  {
    _id: ObjectId('69bcee0f92f97dcd0611402c'),
    rollNumber: 3,
    name: 'Charlie',
    age: 19,
    cgpa: 9
  },
  {
    _id: ObjectId('69bcee1892f97dcd0611402d'),
    rollNumber: 4,
    name: 'David',
    age: 22,
    cgpa: 8.2
  },
  {
    _id: ObjectId('69bcee1d92f97dcd0611402e'),
    rollNumber: 5,
    name: 'Eve',
    age: 20,
    cgpa: 7.9
University_DB>
```

xi. Write a query to update Alice's CGPA to 8.7.

```
University_DB> db.Students.updateOne({ name: "Alice" }, { $set: { cgpa: 8.7 } })
{
  acknowledged: true,
  insertedId: null,
  matchedCount: 1,
  modifiedCount: 1,
  upsertedCount: 0
}
University_DB>
```

xii. Write a query to increase the CGPA by 0.2 for all students with CGPA less than 8.0.

```
University_DB> db.Students.updateMany({ cgpa: { $lt: 8.0 } }, { $inc: { cgpa: 0.2 } })
{niversity_DB>
  acknowledged: true,
  insertedId: null,
  matchedCount: 2,
  modifiedCount: 2,
  upsertedCount: 0
}
University_DB>
```

xiii. Write a query to delete the student named "Bob".

```
University_DB> db.Students.deleteOne({ name: "Bob" })
{ acknowledged: true, deletedCount: 1 }
University_DB> A
```

xiv. Write a query to delete all students with CGPA less than 7.5.

```
University_DB> db.Students.deleteMany({ cgpa: { $lt: 7.5 } })
{ acknowledged: true, deletedCount: 0 }
University_DB>
```

Experiment No. 08

8. Download a zip code dataset at http://media.mongodb.org/zips.json. Use mongo import to import the zip code dataset into Mongo DB. After importing the data, answer the following questions by using aggregation pipelines:

```
C:\Users\VIT-AP>mongoimport --db zips_DB --collection zips --file "C:\Users\VIT-AP\Downloads\zips.json"
2026-03-20T12:33:49.906+0530    connected to: mongodb://localhost/
2026-03-20T12:33:50.261+0530    29353 document(s) imported successfully. 0 document(s) failed to import.

C:\Users\VIT-AP>
```

(i) Find all the states that have a city called "BOSTON".

```
zips_DB> db.zips.aggregate([
|    { $match: { city: "BOSTON" } },
|    { $group: { _id: "$state" } }
| ])
[
  { _id: 'VA' },
  { _id: 'PA' },
  { _id: 'MA' },
  { _id: 'NY' },
  { _id: 'GA' },
  { _id: 'KY' },
  { _id: 'TX' }
]
zips_DB>
```

(ii) Find all the states and cities whose names include the string "BOST".

```
zips_DB> db.zips.aggregate([
|    { $match: { city: { $regex: /BOST/ } } },
|    { $group: { _id: { state: "$state", city: "$city" } } }
| ])
[
  { _id: { state: 'MA', city: 'BOSTON COLLEGE' } },
  { _id: { state: 'TX', city: 'BOSTON' } },
  { _id: { state: 'NH', city: 'NEW BOSTON' } },
  { _id: { state: 'PA', city: 'BOSTON' } },
  { _id: { state: 'NC', city: 'BOSTIC' } },
  { _id: { state: 'OH', city: 'NEW BOSTON' } },
  { _id: { state: 'MO', city: 'NEW BOSTON' } },
  { _id: { state: 'KY', city: 'BOSTON' } },
  { _id: { state: 'MA', city: 'SOUTH BOSTON' } },
  { _id: { state: 'MA', city: 'BOSTON' } },
  { _id: { state: 'MA', city: 'EAST BOSTON' } },
  { _id: { state: 'IL', city: 'NEW BOSTON' } },
  { _id: { state: 'NY', city: 'BOSTON' } },
  { _id: { state: 'GA', city: 'BOSTON' } },
  { _id: { state: 'VA', city: 'SOUTH BOSTON' } },
  { _id: { state: 'MI', city: 'NEW BOSTON' } },
  { _id: { state: 'VA', city: 'BOSTON' } }
]
zips_DB>
```

(iii) Count zip codes and population for each city in each state.

```
zips_DB> db.zips.aggregate([
|     { $group: {
|         _id: { state: "$state", city: "$city" },
|         zip_count: { $sum: 1 },
|         total_pop: { $sum: "$pop" }
|     }}
| ])
[
  {
    _id: { state: 'SC', city: 'LYNCHBURG' },
    zip_count: 1,
    total_pop: 2091
  },
  {
    _id: { state: 'KS', city: 'ANTELOPE' },
    zip_count: 1,
    total_pop: 562
  },
  {
    _id: { state: 'WV', city: 'BRANDYWINE' },
    zip_count: 1,
    total_pop: 941
  },
  { _id: { state: 'LA', city: 'BUECHE' }, zip_count: 1, total_pop: 504 },
  {
    _id: { state: 'NH', city: 'CENTER TUFTONBOR' },
    zip_count: 1,
    total_pop: 885
  },
  {
    _id: { state: 'MA', city: 'LUNENBURG' },
    zip_count: 1,
    total_pop: 9117
```

```
  },
  {
    _id: { state: 'OK', city: 'BOKOSHE' },
    zip_count: 1,
    total_pop: 3931
  },
  {
    _id: { state: 'TX', city: 'SOUTH PADRE ISLA' },
    zip_count: 1,
    total_pop: 1796
  },
  {
    _id: { state: 'WI', city: 'TWO RIVERS' },
    zip_count: 1,
    total_pop: 16768
  },
  {
    _id: { state: 'NC', city: 'PURLEAR' },
    zip_count: 1,
    total_pop: 1102
  },
  { _id: { state: 'MO', city: 'BENDAVIS' }, zip_count: 1, total_pop: 44 },
  { _id: { state: 'KS', city: 'MORRILL' }, zip_count: 1, total_pop: 591 },
  {
    _id: { state: 'CA', city: 'KINGS CANYON NAT' },
    zip_count: 1,
    total_pop: 472
  },
  {
    _id: { state: 'NY', city: 'TUCKAHOE' },
    zip_count: 1,
    total_pop: 15275
```

```
  },
  {
    _id: { state: 'MI', city: 'GLENNIE' },
    zip_count: 1,
    total_pop: 1153
  },
  { _id: { state: 'TX', city: 'FRED' }, zip_count: 1, total_pop: 1973 },
  {
    _id: { state: 'MD', city: 'FALLSTON' },
    zip_count: 1,
    total_pop: 10230
  },
  {
    _id: { state: 'FL', city: 'GROVELAND' },
    zip_count: 1,
    total_pop: 8692
  },
  {
    _id: { state: 'NH', city: 'EAST SULLIVAN' },
    zip_count: 1,
    total_pop: 169
  },
  {
    _id: { state: 'LA', city: 'GRAND CHENIER' },
    zip_count: 1,
    total_pop: 696
  }
]
Type "it" for more
zips_DB>
```

(iv) Find the city with the maximum zip codes in each state and rank by population.

```
zips_DB> db.zips.aggregate([
|    { $group: { _id: { state: "$state", city: "$city" }, zip_count: { $sum: 1 }, pop: { $sum: "$pop" } } },
|    { $sort: { zip_count: -1 } },
|    { $group: { _id: "$_id.state", city: { $first: "$_id.city" }, max_zips: { $first: "$zip_count" }, population: { $first: "$pop" } } },
|    { $sort: { population: -1 } }
| ])
[
  { _id: 'IL', city: 'CHICAGO', max_zips: 47, population: 2452177 },
  { _id: 'CA', city: 'LOS ANGELES', max_zips: 56, population: 2102295 },
  { _id: 'TX', city: 'HOUSTON', max_zips: 93, population: 2095918 },
  { _id: 'PA', city: 'PHILADELPHIA', max_zips: 48, population: 1610956 },
  { _id: 'NY', city: 'NEW YORK', max_zips: 40, population: 1476790 },
  { _id: 'MI', city: 'DETROIT', max_zips: 26, population: 963243 },
  { _id: 'AZ', city: 'PHOENIX', max_zips: 33, population: 890853 },
  { _id: 'FL', city: 'MIAMI', max_zips: 34, population: 825232 },
  { _id: 'MD', city: 'BALTIMORE', max_zips: 21, population: 733081 },
  { _id: 'TN', city: 'MEMPHIS', max_zips: 26, population: 632837 },
  { _id: 'GA', city: 'ATLANTA', max_zips: 31, population: 609591 },
  { _id: 'DC', city: 'WASHINGTON', max_zips: 23, population: 606879 },
  { _id: 'NV', city: 'LAS VEGAS', max_zips: 24, population: 597557 },
  { _id: 'WI', city: 'MILWAUKEE', max_zips: 20, population: 597324 },
  { _id: 'WA', city: 'SEATTLE', max_zips: 24, population: 520096 },
  { _id: 'OR', city: 'PORTLAND', max_zips: 26, population: 518543 },
  { _id: 'LA', city: 'NEW ORLEANS', max_zips: 17, population: 496937 },
  { _id: 'NC', city: 'CHARLOTTE', max_zips: 24, population: 465833 },
  { _id: 'CO', city: 'DENVER', max_zips: 22, population: 451182 },
  { _id: 'NM', city: 'ALBUQUERQUE', max_zips: 17, population: 449584 }
]
Type "it" for more
zips_DB>
```

Experiment No. 09

9. Implement a JavaScript program that reads data from a JSON file using AJAX and displays the retrieved information dynamically on a webpage.

Program:

```html
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta http-equiv="X-UA-Compatible" content="IE=edge">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>AJAX</title>

</head>
<body>
  <div id="demo">
    <h2>AJAX</h2>
    <button type="button" onclick="loadDoc()">Change Content</button>
  </div>
  <div id="demo2">
      <h2>AJAX</h2>
      <button type="button" onclick="loadDoc2()">Change Content</button>
  </div>

  <script>
    function loadDoc() {
      const xhttp = new XMLHttpRequest();
      xhttp.onload = function() {
        document.getElementById("demo").innerHTML =
        this.responseText;
      }
      xhttp.open("GET", "AJAX_info.txt");
      xhttp.send();
    }
```

```
    function loadDoc2() {
      const xhttp = new XMLHttpRequest();
      xhttp.onload = function() {
        document.getElementById("demo2").innerHTML =
        this.responseText;
      }
      xhttp.open("GET", "AJAX_info.txt");
      xhttp.send();
    }
  </script>
</body>
</html>
```

Output:





Experiment No. 10

Aim: Create a web application to simulate an online shopping order process using ES6 features such as arrow functions, callbacks, and async/await.

Program:

```
<!DOCTYPE html>
<html>
<head>
  <title>Online Shopping Demo</title>
  <style>
    body {
      font-family: Arial;
      padding: 20px;
    }
    #output {
```

```
        margin-top: 20px;
        padding: 10px;
        border: 2px solid #333;
        width: 400px;
      }
    </style>
</head>

<body>

<h2>Online Shopping System</h2>

<button onclick="orderProcess('Smartphone')">
   Place Order
</button>

<div id="output"></div>

<script>
   const outputDiv = document.getElementById("output");

   // Arrow function to display on browser
   const showMessage = (message) => {
      outputDiv.innerHTML += message + "<br>";
   };

   // Callback function
   function placeOrder(product, callback) {
      showMessage(`Order placed for: ${product}`);
      callback(product);
   }

   // Promise for payment
   function processPayment() {
      return new Promise((resolve) => {
         setTimeout(() => {
            resolve("Payment Successful");
         }, 2000);
      });
   }

   // Async/Await main function
   async function orderProcess(product) {
      outputDiv.innerHTML = ""; // clear previous output

      showMessage("Starting order process...");

      placeOrder(product, (item) => {
         showMessage(`Order confirmed for: ${item}`);
      });

      const paymentStatus = await processPayment();
      showMessage(paymentStatus);

      showMessage("Order will be delivered soon");
   }
</script>
```

```
</body>
</html>
```

Output:





Experiment No. 11

Deploying React JS and building simple application.

A company is developing an online shopping application using React. The user interface is divided into small reusable parts such as Header, ProductList, ProductItem, Cart, and Footer. Design suitable components for this application. The ProductList component passes product details to the ProductItem component.

Project:

Header.js

```
function Header() {
return <h1>Online Shopping App</h1>;
}
export default Header;
```

ProductItem.js

```
function ProductItem(props) {
return (
<div>
<h3>{props.name}</h3>
<p>Price: ₹{props.price}</p>
<button>Add to Cart</button>
</div>);
```

```
}
export default ProductItem;
```

ProductList.js

```
import ProductItem from './ProductItem';
function ProductList() {
  return (
    <div>
      <ProductItem name="Mobile" price="15000" />
      <ProductItem name="Laptop" price="50000" />
    </div>
  );
}
Export default ProductList;
```

Cart.js

```
function Cart() {
return <h2>Your Cart is Empty</h2>;
}
export default Cart;
```

Footer.js

```
function Footer() {
  return <p>© 2026 Shopping App</p>;
}
export default Footer;
```

App.js

```
import Header from './Header';
import ProductList from './ProductList';
import Cart from './Cart';
import Footer from './Footer';
function App() {
  return (
    <div>
      <Header />
      <ProductList />
      <Cart />
      <Footer />
    </div>
  );
} export default App;
```

Output: