

Manuscript Number:

Title: The Generalized Maximum Belief Entropy Model

Article Type: Research Paper

Section/Category: Other topics in Statistical Physics

Keywords: Entropy; Uncertainty measure; Tsallis entropy; Reny entropy;
Shannon entropy; Deng entropy

Corresponding Author: Professor Rui Cai,

Corresponding Author's Institution: Southwest University

First Author: Siran Li

Order of Authors: Siran Li; Rui Cai

Abstract: In evidence theory, the generalized belief entropy model unifies Reny entropy, Tsallis entropy, and Deng entropy. In order to further unify the maximum values of Reny entropy, Tsallis entropy, and Deng entropy, this paper proposes a maximum model of generalized belief entropy by analyzing the generalized belief entropy model, and the maximum values of R-D entropy and T-D entropy are obtained through this model. In addition, the applicability of the proposed model is obtained through verification tests and sensitivity analysis of the model.

Suggested Reviewers: Khosravi Tanak
Ferdowsi University of Mashhad
khosravi.a_66@yahoo.com
Dr. Tanak has the relative works on maximum Tsallis entropy model.

Aurélien Hazan
Université Paris-Est
aurelien.hazan@u-pec.fr
Dr. Hazan has the relative works on maximum entropy model.

Kanzo Okada
Kyushu University
okada@imi.kyushu-u.ac.jp
Dr. Okada has the relative works on maximum entropy model.

Andrej Dobovišek
University of Maribor
andrej.dobovisek@um.si
Dr. Dobovišek has the relative works on maximum entropy.

Mohtashami Borzadaran
Ferdowsi University of Mashhad
grmohtashami@um.ac.ir
Dr. Borzadaran has the relative works on maximum Tsallis entropy model.

- The generalized maximum belief entropy model is presented by Lagrange Multiplier.
- Existing maximum entropy models including Reny entropy, Tsallis entropy, Deng entropy and Shannon entropy are the special case of proposed maximum entropy.
- Some properties of the proposed maximum entropy are illustrated.

The Generalized Maximum Belief Entropy Model

Siran Li^a, Rui Cai^{a,*}

^a*Business College, Southwest University, Rongchang District, Chongqing, 402460, China*

Abstract

In evidence theory, the generalized belief entropy model unifies Reny entropy, Tsallis entropy, and Deng entropy. In order to further unify the maximum values of Reny entropy, Tsallis entropy, and Deng entropy, this paper proposes a maximum model of generalized belief entropy by analyzing the generalized belief entropy model, and the maximum values of R-D entropy and T-D entropy are obtained through this model. In addition, the applicability of the proposed model is obtained through verification tests and sensitivity analysis of the model.

Keywords: Entropy; Uncertainty measure; Tsallis entropy; Reny entropy; Shannon entropy; Deng entropy

1. Introduction

Entropy is a measure of uncertainty, and many studies have focused on the essence of entropy[1]. When the classical thermodynamic entropy is evolving[2, 3], the concept of entropy is also widely used in various disciplines[4–10] and industries[11–13]. In the field of information theory, Shannon proposed information entropy[14], classical information entropy is often used to compare with the newly proposed entropy[15, 16], literature[17] followed up on the aforementioned literature[15] and made some notes.

For further processing of uncertain information, Dempster and Shafer proposed the Dempster-Shafer evidence theory[18]. In evidence theory, the main factor describing uncertainty is BPA (basic probability assignment function). An important operation for BPA in evidence theory is the combination of evidence and the corresponding rule is also called the evidence combination rule. Evidence combination rules, as an important part of D-S evidence theory, are also constantly developing. Many researchers have improved the evidence combination rules[19–21]. And there are also many scholars who apply the combination of evidence to technical practice[22–24]. Evidence theory itself has a wide range of applications such as information fusion[25–29], decision making[30, 31], prediction[32] and pattern recognition[33, 34], while developing[35], it also maintains a good integration with other subjects[36, 37]. There are many theories developed based on evidence theory, the generalized evidence theory[38], which extended the carrier defining the discernment framework to the open world, was proposed. It better solves the problems of classical evidence theory in the case of incomplete discernment framework.

Both evidence theory and information entropy can be used to process information. How to apply classic information entropy to evidence theory has been the work of some scholars. In this process, more entropies have been proposed[39–48], Reny proposed the Reny entropy[49], which is widely used in statistics[50]. As a kind of extension of Boltzmann entropy, Tsallis entropy[51] is a non-scalable entropy that also has a wide range of applications[52]. Recently, Deng entropy[53] was proposed as a new kind of entropy used to measure the uncertainty of BPA, Deng entropy better solves the problem of uncertainty measurement of multi-element sets. The greater the Deng entropy, the higher the degree of uncertainty. We often discuss entropy based on the principle of maximum entropy, the principle of maximum retains all the uncertainty and minimizes the unknown, it is often used in statistics[54–57], especially parameter estimation[58, 59] and some aspects of biochemistry[60], some theories[61–63] are also improved based on it. It is also reflected in the field of information theory: the maximum Deng entropy model[64] gives the necessary and sufficient conditions for the maximum Deng entropy to appear and the model of the maximum Deng entropy. Given that Shannon entropy is a special case of Reny entropy, Tsallis entropy, and Deng entropy, scholars have begun to study the relationship between the three. Masi's work[65] unifies Reny and Tsallis entropy. Lately, the generalized belief entropy model[66] was proposed as a unified model of Reny entropy, Tsallis entropy, and Deng entropy.

According to the previous ideas, a natural question will be asked: what is the maximum value of the generalized belief entropy model? and under what conditions does the generalized belief entropy achieve this maximum, this subject has not been covered by too many scholars. In this paper, we will discuss the conditions when the generalized belief entropy reaches a maximum value, and give the maximum generalized belief entropy based on the results of the discussion. Through the work of this paper, the maximum Shannon entropy, the maximum Renyi-Deng entropy, and the maximum Tsallis-Deng entropy can be unified.

*Corresponding author: Prof. Dr. Cairui, Business College of Southwest University. Tel(Fax): 86(23)-46751399
Email addresses: 15108249673@163.com (Siran Li), cairui686@swu.edu.cn (Rui Cai)

The structure of this paper is as follows: The Preliminaries in the second section introduce the related concepts of evidence theory, Deng entropy, Reny entropy, Tsallis entropy, generalized belief entropy (R-D entropy, T-D entropy). In section 3, the generalized maximum belief entropy model is proposed, and the maximum values of R-D entropy and T-D entropy are obtained according to this model. The fourth section is the conclusion of this paper.

2. Preliminaries

2.1. Dempster Shafer Evidence Theory

D-S evidence theory[18] is a theory that can be used to describe the uncertainty of a system. It can deal with the uncertainty caused by the unknown prior probability. Evidence theory models uncertainty by studying multiple-element subsets, so compared to probability theory, where the research field is a single element subset, evidence theory adapts to weaker axiom systems than probability theory. Some basic concepts of evidence theory are introduced below.

Let Ω be a finite set of all possible values of a variable X , and each element in Ω is mutually exclusive. It is called an frame of discernment and Ω is defined as:

$$\Omega = \{x_1, x_2, \dots, x_n\}$$

2^Ω is the power set of Ω :

$$2^\Omega = \{\{\emptyset\}, \{x_1\}, \dots, \{x_n\}, \{x_1, x_2\}, \dots, \{x_1, \dots, x_i\}, \Omega\}$$

the probability assignment $m(A_i)$ of the frame of discernment Ω is a mapping from 2^Ω to $[0, 1]$ defined on a power set in the form:

$$m(A_i) : 2^\Omega \rightarrow [0, 1]$$

A_i is a subset of the frame of discernment. $m(A_i)$ is the probability assignment function (BPA), which satisfies the following conditions:

$$m(\emptyset) = 0, \sum_{A_i \subseteq \Omega} m(A_i) = 1$$

2.2. Deng Entropy

The form of Deng entropy[53] in evidence theory is as follows:

$$E_d = - \sum_{A_i \subseteq \Omega} m(A_i) \times \log_2 \frac{m(A_i)}{2^{|A_i|} - 1}$$

where A_i is a subset of the frame of discernment Ω , and $|A_i|$ is the cardinality of the set A_i . Another form of Deng Entropy is:

$$E_d = \sum_{A_i \subseteq \Omega} m(A_i) \log_2(2^{|A_i|} - 1) - \sum_{A_i \subseteq \Omega} m(A_i) \log_2 m(A_i)$$

The formula $\sum_{A_i \subseteq \Omega} m(A_i) \log_2(2^{|A_i|} - 1)$ represents the non-specificity of the entire system, and the formula $\sum_{A_i \subseteq \Omega} m(A_i) \log_2 m(A_i)$ represents the inconsistency, that is, the conflict, of the entire system. when it is a single-element subset, Deng entropy degenerates to Shannon entropy[14]:

$$E_d = - \sum_{A_i \subseteq \Omega} m(A_i) \log_2 m(A_i)$$

2.3. Reny Entropy

Assuming $P_\theta = \{p_i | i = 1, 2, 3, \dots\}$ is the probability distribution of the discrete random variable θ , then Reny[49] entropy can be defined as:

$$H_\alpha(p_1, p_2, p_3, \dots, p_n) = \frac{1}{1 - \alpha} \log_2 \left(\sum_{k=1}^n p_k^\alpha \right)$$

where $\alpha > 0$ and $\alpha \neq 1$. In particular, Reny entropy degenerates to Shannon entropy when $\alpha > 1$:

$$\lim_{\alpha \rightarrow 1} H_\alpha(p_1, p_2, p_3, \dots, p_n) = \sum_{k=1}^n p_k \log_2 \frac{1}{p_k}$$

2.4. Tsallis Entropy

Given a discrete random variable Y and its probability distribution is $\{p_i | i = 1, 2, 3, \dots\}$, then the Tsallis entropy[51] can be expressed as:

$$S_q(p_i) = \frac{k}{q-1} \left(1 - \sum_{i=1}^n p_i^q\right)$$

where k, q are parameters, and k is often set to 1 in statistics. And q reflects the degree of non-extensiveness. In particular, when $q \rightarrow 1$, Tsallis entropy degenerates to Shannon entropy:

$$\lim_{q \rightarrow 1} S_q(p_i) = S_1(p_i) \equiv - \sum_i p_i \log_2 p_i$$

It should be noted that the literature[67] suggests that the Tsallis entropy can be used to replace Shannon entropy when $q = 2$, so that logarithmic operations can be avoided. In the latter part of this article, the situation of $q = 2$ will also be included in the discussion, so $q = 2$ is a special case of this article.

2.5. Generalized Belief Entropy

Let A_i be a subset of the frame of discernment Ω , $|A_i|$ denote the cardinality of the set A_i , and $m(A_i)$ be the probability assignment function on the power set 2^Ω . Then the definition of generalized belief entropy[66] is as follows:

$$E_{t,r}(m(A_i)) = \frac{1}{1-r} \left[\left[\sum_i \left(\frac{m(A_i)}{2^{|A_i|}-1} \right)^t (2^{|A_i|}-1) \right]^{\frac{1-r}{1-t}} - 1 \right]$$

where r, t are parameters. When $r \rightarrow 1$, generalized belief entropy degenerates to R-D entropy:

$$E_\alpha(m(A_i)) = \frac{1}{1-\alpha} \ln \left[\sum_i \left(\frac{m(A_i)}{2^{|A_i|}-1} \right)^\alpha (2^{|A_i|}-1) \right]$$

when $r \rightarrow q$, the generalized belief entropy degenerates to T-D entropy:

$$E_q(m(A_i)) = \frac{1}{q-1} \left[1 - \sum_i \left(\frac{m(A_i)}{2^{|A_i|}-1} \right)^q (2^{|A_i|}-1) \right]$$

in particular, when $q \rightarrow 1$ or $\alpha \rightarrow 1$, the T-D entropy and R-D entropy degenerate to Deng entropy:

$$\lim_{q \rightarrow 1} E_q(m(A_i)) = \lim_{\alpha \rightarrow 1} E_\alpha(m(A_i)) = \sum_i m(A_i) \ln \left(\frac{m(A_i)}{2^{|A_i|}-1} \right)$$

3. Generalized Maximum Belief Entropy Model

Let A_i be a subset of the frame of discernment Ω , $|A_i|$ denote the cardinality of the set A_i , and $m(A_i)$ be the probability assignment function on the power set 2^Ω .

3.1. The Necessary And Sufficient Condition Of The Maximum Generalized Belief Entropy

Theorem 1. The maximum generalized belief entropy achieves the maximum value if and only if: $m(A_i) = \frac{2^{|A_i|}-1}{\sum_j 2^{|A_j|}-1}$

PROOF.

$$E_{t,r}(m(A_i)) = \frac{1}{1-r} \left[\left[\sum_i \left(\frac{m(A_i)}{2^{|A_i|}-1} \right)^t \times (2^{|A_i|}-1) \right]^{\frac{1-r}{1-t}} - 1 \right]$$

$$\sum_{A_i \subseteq \Omega} m(A_i) = 1$$

its Lagrange function can be defined as follows:

$$F_{t,r}(m(A_i)) = \frac{1}{1-r} \left[\left[\sum_i \left(\frac{m(A_i)}{2^{|A_i|}-1} \right)^t (2^{|A_i|}-1) \right]^{\frac{1-r}{1-t}} - 1 \right] + \lambda \left(\sum_i m(A_i) - 1 \right)$$

then we can get:

$$\begin{aligned} & \frac{\partial F_{t,r}(m(A_i))}{\partial m(A_i)} \\ &= \frac{1}{1-t} \left[\sum_i \left(\frac{m(A_i)}{2^{|A_i|}-1} \right)^t (2^{|A_i|}-1) \right]^{\frac{1-r}{1-t}} t \left(\frac{m(A_i)}{2^{|A_i|}-1} \right)^{t-1} + \lambda = 0 \end{aligned}$$

where t and λ are constants, then we can get:

$$t \times \left(\frac{m(A_i)}{2^{|A_i|}-1} \right)^{t-1} \times \sum_i \left(\frac{m(A_i)}{2^{|A_i|}-1} \right)^t \times (2^{|A_i|}-1) = \mu$$

in the formula above, the value of the term $\sum_i \left(\frac{m(A_i)}{2^{|A_i|}-1} \right)^t$ is fixed. So we can get:

$$\frac{m(A_1)}{2^{|A_1|}-1} = \frac{m(A_2)}{2^{|A_2|}-1} = \dots = \frac{m(A_i)}{2^{|A_i|}-1}$$

and according to the ratio property, we can get:

$$\frac{m(A_1) + m(A_2) + \dots + m(A_n)}{(2^{|A_1|}-1) + (2^{|A_2|}-1) + \dots + (2^{|A_n|}-1)} = \frac{m(A_i)}{(2^{|A_i|}-1)}$$

then we can get:

$$\frac{1}{\sum_j 2^{|A_j|}-1} = \frac{m(A_i)}{2^{|A_i|}-1}$$

so we can finally get:

$$m(A_i) = \frac{2^{|A_i|}-1}{\sum_j 2^{|A_j|}-1}$$

So based on the process of inference above, the necessary and sufficient condition for the generalized belief entropy to reach the maximum is:

$$m(A_i) = \frac{2^{|A_i|}-1}{\sum_j 2^{|A_j|}-1}$$

3.2. The Generalized Maximum Belief Entropy Model

We substitute the obtained necessary and sufficient condition:

$$m(A_i) = \frac{2^{|A_i|}-1}{\sum_j 2^{|A_j|}-1}$$

into the generalized belief entropy model:

$$E_{t,r}(m(A_i)) = \frac{1}{1-r} \left[\left[\sum_i \left(\frac{m(A_i)}{2^{|A_i|}-1} \right)^t \times (2^{|A_i|}-1) \right]^{\frac{1-r}{1-t}} - 1 \right]$$

then we can get the generalized maximum belief entropy model:

$$E_r(A_i)_{max} = \frac{1}{1-r} \left[\left(\sum_j 2^{|A_j|}-1 \right)^{1-r} - 1 \right]$$

3.3. The Maximum R-D entropy and Maximum T-D entropy

The proposition A_i in the generalized maximum belief entropy model proposed above is objective, so we mainly discuss the value of parameter r to obtain the maximum value of the generalized maximum belief entropy model. We find the partial derivative about r for the generalized maximum belief entropy model obtained, that is:

$$\begin{aligned} & \frac{\partial E_r(A_i)_{max}}{\partial r} \\ &= \frac{\left(\sum_j 2^{|A_j|}-1 \right)^{1-r} \left[-\ln \left(\sum_j 2^{|A_j|}-1 \right) (1-r) - 1 \right]}{(1-r)^2} = 0 \end{aligned}$$

then we can get two values of r :

$$r = 1 + \frac{1}{\ln\left(\sum_j 2^{|A_j|} - 1\right)}, r = 1$$

we first substitute the first r value into the generalized maximum belief entropy model and we can get:

$$\begin{aligned} E_r(A_i)_{max} &= \ln\left(\sum_j 2^{|A_j|} - 1\right) \left[1 - \left(\sum_j 2^{|A_j|} - 1\right)^{-\ln\left(\sum_j 2^{|A_j|} - 1\right)^{-1}} \right] \end{aligned} \quad (1)$$

we simplify the equation (1) to get:

$$E_r(A_i)_{max} = \ln\left(\sum_j 2^{|A_j|} - 1\right) \left(1 - \frac{1}{e}\right) < \ln\left(\sum_j 2^{|A_j|} - 1\right)$$

while $r \rightarrow 1$, we can get the maximum of the the generalized maximum belief entropy model in the form of limit:

$$\begin{aligned} &\lim_{r \rightarrow 1} \frac{1}{1-r} \left[\left(\sum_j 2^{|A_j|} - 1\right)^{1-r} - 1 \right] \\ &= \lim_{r \rightarrow 1} \frac{\left(\sum_j 2^{|A_j|} - 1\right)^{1-r} \times \ln\left(\sum_j 2^{|A_j|} - 1\right)}{1} \\ &= \ln\left(\sum_j 2^{|A_j|} - 1\right) \end{aligned}$$

Therefore, the maximum value of the generalized maximum belief entropy model can be described as follows:

$$E_r(A_i)_{max} = \ln\left(\sum_j 2^{|A_j|} - 1\right)$$

Since our model is based on the generalized belief entropy model[66], the generalized belief entropy shows that when $r \rightarrow 1$, the generalized belief entropy degenerates to R-D entropy, when $r \rightarrow q$, the generalized belief entropy degenerates to T-D entropy. In order to prove that our model is equally applicable to these two cases, we discuss the corresponding two cases separately:

When $r \rightarrow 1$, this situation is the same as what we have discussed above, so we will not go into details.

And when $r \rightarrow q$, we can get:

$$\begin{aligned} &\lim_{r \rightarrow q} \frac{1}{1-r} \left[\left(\sum_j 2^{|A_j|} - 1\right)^{1-r} - 1 \right] \\ &= \frac{1}{1-q} \left[\left(\sum_j 2^{|A_j|} - 1\right)^{1-q} - 1 \right] \\ &= \frac{1}{1-q} \left[e^{(1-q) \ln\left(\sum_j 2^{|A_j|} - 1\right)} - 1 \right] \end{aligned} \quad (2)$$

then we perform power series expansion on equation above to get:

$$\begin{aligned} (2) &= \frac{1}{1-q} \left[1 + (1-q) \ln\left(\sum_j 2^{|A_j|} - 1\right) \right. \\ &\quad \left. + \sum_{i=2}^n \frac{(1-q)^i \left[\ln\left(\sum_j 2^{|A_j|} - 1\right) \right]^i}{i!} - 1 \right] \end{aligned}$$

next we can get:

$$(2) = \ln\left(\sum_j 2^{|A_j|} - 1\right) + \frac{1}{1-q} \sum_{i=2}^n \frac{(1-q)^n \left[\ln\left(\sum_j 2^{|A_j|} - 1\right) \right]^n}{n!} \quad (3)$$

for the Eq.3 we discuss the scope of q in two cases:

- 1) when $0 \leq q < 2$, that is $1 - q \in [-1, 1)$, and for a definite frame of discernment Ω , $\left(\sum_j 2^{|A_j|} - 1\right)$ is also definite, so we can get:

$$\lim_{n \rightarrow \infty} \sum_{i=2}^n \frac{(1-q)^n \left[\ln\left(\sum_j 2^{|A_j|} - 1\right) \right]^n}{n!} = 0$$

so in this situation, the maximum value of T-D entropy is: $\ln\left(\sum_j 2^{|A_j|} - 1\right)$

- 2) when $q \geq 2$, we can transform Eq.3 and get the following expression:

$$\ln\left(\sum_j 2^{|A_j|} - 1\right) + \frac{1}{1-q} \left[e^{(1-q) \ln\left(\sum_j 2^{|A_j|} - 1\right)} - (1-q) \ln\left(\sum_j 2^{|A_j|} - 1\right) - 1 \right] \quad (4)$$

and let us consider the expression :

$$e^{(1-q) \times \ln\left(\sum_j 2^{|A_j|} - 1\right)} - (1-q) \ln\left(\sum_j 2^{|A_j|} - 1\right) - 1$$

let :

$$x = (1-q) \ln\left(\sum_j 2^{|A_j|} - 1\right) (x < 0)$$

then we can rewrite the expression above to get a function about x :

$$f(x) = e^x - x - 1 (x < 0) \quad (5)$$

now we consider the monotonicity of Eq.5:

$$\frac{df(x)}{dx} = e^x - 1 = 0$$

then we can get $x = 0$, that is, the Eq.5 decreases monotonically when $x < 0$, so we can get:

$$f(x) > f(0) = 0$$

so $\frac{f(x)}{1-q} < 0$, and for Eq.3, we can get:

$$(3) < \ln\left(\sum_j 2^{|A_j|} - 1\right)$$

so, when $r \rightarrow q$, the maximum value of T-D entropy demonstrates as follows:

$$T - D_{max} = \ln\left(\sum_j 2^{|A_j|} - 1\right)$$

In summary, the maximum value of both entropies expressed as:

$$E_{max} = \ln\left(\sum_j 2^{|A_j|} - 1\right)$$

The transformation of these kinds of entropy is shown in Fig.1:




Figure 1: Relationship between several maximum entropy models.

4. Numerical Examples

4.1. Example 1




Figure 2: The Generalized Belief Entropy changing with x y

Based on the model proposed in Ref.[66], which is the basis of our work, we select the discernment frame with the elements $\{a, b\}$, and the parameter r, t in the Ref.[66] model is set to 2. Then we obtained the figure above.

From the above figure, we can see that the maximum value of the generalized belief entropy in the this case is obtained when $x = y = 0.2$, and the maximum value is 0.8. We apply the above conditions to our proposed model, namely:

$$E(A_i) = 1 - \frac{1}{\sum_j 2^{|A_j|} - 1}$$

under the premise that the power set is $\{\{a\}, \{b\}, \{a, b\}, \emptyset\}$, the value of formula $\sum_j 2^{|A_j|} - 1$ is 5, therefore, we can calculate the maximum value of generalized belief entropy under our model: $E(A_i)_{max} = 0.8$. And according to the conditions when it reaches the maximum value, it can be obtained: $m(\{a\}) = m(\{b\}) = 1/5 = 0.2$ therefore, our model is consistent with Ref.[66] in the actual situation.

4.2. Example 2

In the third section, we derive the maximum values of R-D entropy and T-D entropy through the obtained model, and here we verify it.

In Ref.[66], it is mentioned that the condition for R-D entropy and T-D entropy to achieve the maximum value is:

$$m(A_i) = \frac{2^{|A_i|} - 1}{\sum_j 2^{|A_j|} - 1} \quad (6)$$

We substitute Eq.6 into R-D entropy[66] and we can get the maximum model of R-D as:

$$R - D_{max} = \ln \left(\sum_j 2^{|A_j|} - 1 \right)$$

this is consistent with the conclusion drawn by our model on the issue of maximum R-D. Then we substitute Eq.6 into T-D entropy[66] too, and what we can actually get is:

$$T - D_{max} = \frac{1}{q-1} \left[1 - \frac{1}{\left[\sum_j \left(2^{|A_i|} - 1 \right) \right]^{q-1}} \right]$$

in fact, the equation above and Eq.2 are essentially the same. Therefore, the maximum R-D entropy and T-D entropy have been verified.

4.3. Example 3




Figure 3: The Comparison Of Three Kinds Of Maximum Entropy

In order to discuss the relationship between the maximum values of the three entropies, we fixed the value of the parameter r so that our model was determined. Further, we discuss the difference in the maximum values of the three types of entropy under different discernment frames, and draw the above figure. From the above figure, we can see that although our model and the maximum entropy value under different discernment frames are the same in the overall trend, the specific value is not very satisfactory. Therefore, we consider the effect of the value of parameter r on this experiment.




Figure 4: The Adaptability Of Max Gen Entropy

Under the change of r , our model also changes accordingly. From Figure 2, we can see that the value of r is between 0-2. When r equals 2, the value calculated by our model under each discernment frame tends to be gentle. When the value of r is within 1-2, we can see that our model is approaching the maximum R-D entropy and the maximum T-D entropy. In particular, when $r = 1$, our model coincides with the maximum R-D entropy and maximum T-D entropy models, which is consistent with what we described in Section III. It is worth mentioning that $r = 1$ is a singularity of our model, so at this point the values under different discernment frames are obtained by the limit. When the value of r is within 0-1, our model is approaching the maximum Deng entropy. In particular, when $r = 0$, our model basically coincides with the maximum Deng entropy model. What needs to be explained here is that in the experiment with $r \leq 1$, we performed log processing on the obtained data.




Figure 5: Different Maximum Value Of Entropy Under Changing FOD

In view of the change in the value of r will cause changes in our model, we discuss the relationship between the maximum R-D entropy, maximum T-D entropy and maximum Deng entropy model. Their relationship is shown in Fig.5. From the above figure, we can see that the maximum R-D entropy, maximum T-D entropy, and maximum Deng entropy are consistent under different discernment frames. But the maximum Deng entropy value is higher than the maximum R-D entropy and maximum T-D entropy.

Scale of FOD	R-D&T-D Entropy	Deng Entropy	R-D&T-D/Deng
2	1.6094	2.3219	1.4427
3	2.9444	4.2479	1.4427
4	4.1744	6.0224	1.4427
5	5.3519	7.7211	1.4427
6	6.4998	9.3772	1.4427
7	7.6300	11.0077	1.4427
8	8.7491	12.6223	1.4427
9	9.8612	14.2266	1.4427
10	10.9686	15.8244	1.4427

Table 1: The quantitative relationship between entropy

From the data in the above table, we can see that the mutiple between maximum R-D entropy, the maximum T-D entropy and the maximum Deng entropy is 1.4427.s This is due to the calculation method of the two. The maximum R-D entropy and maximum T-D entropy calculated by our model do the logarithm of the natural logarithm base e at the end, and the maximum Deng entropy is based on the logarithm of 2 bases,so the difference between the two will be $\log_2(e)$ times.

4.4. Example 4




Figure 6: Generalized Maximum Belief Entropy Model Changing With r And FOD

From the above figure, we can see that our model performs the same under different discernment frame and different r , from this perspective, our model is insensitive to r . At the same time, we can see that at $r = 1$, the convergence rate of the model slows down rapidly, and at $r = 2$, for the same model, the difference between the maximum values calculated by different discernment frame through this model is not particularly obvious. Therefore, we determined the value of r as 2 in Example 1, which helps the generality of Example 1. In fact from Example.3, we recommend that the value of r is between $0 - 2$.

5. Conclusion

In this article, we propose the generalized maximum belief entropy model, and use this model to derive the analytical solutions of maximum R-D entropy and maximum T-D entropy. At the same time, the relationship between the generalized maximum belief entropy model, maximum R-D entropy, maximum T-D entropy, maximum Deng entropy, and maximum Shannon entropy is revealed. We have not discussed the practical significance of r in the generalized maximum belief entropy model, which can become the direction of future work.

Acknowledgment

This research is supported by the Fundamental Research Funds for the Central Universities, SWU1909785.

References

- [1] A. L. Kuzemsky, Temporal evolution, directionality of time and irreversibility, *RIVISTA DEL NUOVO CIMENTO* 41 (10) (2018) 513–574. doi:10.1393/ncr/i2018-10152-0.
- [2] R. H. Swendsen, The definition of the thermodynamic entropy in statistical mechanics, *Physica A: Statistical Mechanics and its Applications* 467 (2017) 67 – 73. doi:https://doi.org/10.1016/j.physa.2016.10.032.
- [3] R. H. Swendsen, J.-S. Wang, Negative temperatures and the definition of entropy, *Physica A: Statistical Mechanics and its Applications* 453 (2016) 24 – 34. doi:https://doi.org/10.1016/j.physa.2016.01.068.
- [4] I.-M. Dragan, A. Isaic-Maniu, An innovative model of reliability—the pseudo-entropic model, *Entropy* 21 (9) (2019) 846.
- [5] T. S. Biró, Z. Nédá, A. Telcs, Entropic divergence and entropy related to nonlinear master equations, *Entropy* 21 (10) (2019) 993.
- [6] J. Shen, J. Zhou, Calculation formulas and simulation algorithms for entropy of function of lr fuzzy intervals, *Entropy* 21 (3). doi:10.3390/e21030289.
- [7] J. Abellan, J. G. Castellano, Improving the Naive Bayes Classifier via a Quick Variable Selection Method Using Maximum of Entropy, *ENTROPY* 19 (6). doi:10.3390/e19060247.
- [8] J. Das, B. C. Bag, Bounds of the entropy production of the irreversible thermodynamics and its relation with the non-equilibrium temperature, *Physica A: Statistical Mechanics and its Applications* 520 (2019) 433 – 449. doi:https://doi.org/10.1016/j.physa.2019.01.010.
- [9] L. M. Martyushev, S. N. Zubarev, Entropy production and luminosity–effective temperature relation for main-sequence stars, *Physica A: Statistical Mechanics and its Applications* 528 (2019) 121403. doi:https://doi.org/10.1016/j.physa.2019.121403.
- [10] S. Viaggiu, Entropy, temperature and internal energy of trapped gravitons and corrections to the black hole entropy, *Physica A: Statistical Mechanics and its Applications* 488 (2017) 72 – 84. doi:https://doi.org/10.1016/j.physa.2017.07.009.
- [11] A. Mehri, H. Agahi, H. Mehri-Dehnavi, A novel word ranking method based on distorted entropy, *Physica A: Statistical Mechanics and its Applications* 521 (2019) 484 – 492. doi:https://doi.org/10.1016/j.physa.2019.01.080.
- [12] G. de Novaes Pires Leite, A. M. Araújo, P. A. C. Rosas, T. Stosic, B. Stosic, Entropy measures for early detection of bearing faults, *Physica A: Statistical Mechanics and its Applications* 514 (2019) 458 – 472. doi:https://doi.org/10.1016/j.physa.2018.09.052.
- [13] T. Dimpfl, F. J. Peter, Group transfer entropy with an application to cryptocurrencies, *Physica A: Statistical Mechanics and its Applications* 516 (2019) 543 – 551. doi:https://doi.org/10.1016/j.physa.2018.10.048.
- [14] C. SHANNON, A MATHEMATICAL THEORY OF COMMUNICATION, *BELL SYSTEM TECHNICAL JOURNAL* 27 (3) (1948) 379–423. doi:10.1002/j.1538-7305.1948.tb01338.x.
- [15] A. Karci, Fractional order entropy: New perspectives, *Optik* 127 (20) (2016) 9172–9177.
- [16] İ. Tuğal, A. Karci, Comparisons of karci and shannon entropies and their effects on centrality of social networks, *Physica A: Statistical Mechanics and its Applications* 523 (2019) 352–363.
- [17] A. Karci, Notes on the published article “fractional order entropy: New perspectives” by ali karci, *optik-international journal for light and electron optics*, volume 127, issue 20, october 2016, pages 9172–9177, *Optik* 171 (2018) 107–108.
- [18] A. DEMPSTER, UPPER AND LOWER PROBABILITIES INDUCED BY A MULTIVALUED MAPPING, *ANNALS OF MATHEMATICAL STATISTICS* 38 (2) (1967) 325–&. doi:10.1214/aoms/1177698950.
- [19] J. Wang, K. Qiao, Z. Zhang, An improvement for combination rule in evidence theory, *Future Generation Computer Systems* 91 (2019) 1–9.

- [20] J. An, M. Hu, L. Fu, J. Zhan, A novel fuzzy approach for combining uncertain conflict evidences in the dempster-shafer theory, *IEEE Access* 7 (2019) 7481–7501.
- [21] C. LUO, Y. CHEN, H. XIANG, W. WANG, Z. WANG, Evidence combination method in time domain based on reliability and importance, *Journal of Systems Engineering and Electronics* 29 (6) (2018) 1308–1316.
- [22] Y. Zhang, Y. Liu, Z. Zhang, H.-C. Chao, J. Zhang, Q. Liu, A weighted evidence combination approach for target identification in wireless sensor networks, *IEEE Access* 5 (2017) 21585–21596.
- [23] Y. Zhang, Y. Liu, Z. Zhang, N. Zhao, Collaborative fusion for distributed target classification using evidence theory in iot environment, *IEEE Access* 6 (2018) 62314–62323.
- [24] N. Khan, S. Anwar, Time-domain data fusion using weighted evidence and dempster-shafer combination rule: Application in object classification, *Sensors* 19 (23) (2019) 5187.
- [25] X. Fan, Y. Guo, Y. Ju, J. Bao, W. Lyu, Multisensor fusion method based on the belief entropy and ds evidence theory, *Journal of Sensors* 2020. doi:10.1155/2020/7917512.
- [26] Y. Tang, D. Zhou, F. T. S. Chan, An extension to deng’s entropy in the open world assumption with an application in sensor data fusion, *Sensors* 18 (6). doi:10.3390/s18061902.
- [27] W. Jiang, B. Wei, C. Xie, D. Zhou, An evidential sensor fusion method in fault diagnosis, *ADVANCES IN MECHANICAL ENGINEERING* 8 (3). doi:10.1177/1687814016641820.
- [28] A. D. Jaunzemis, M. J. Holzinger, M. W. Chan, P. P. Shenoy, Evidence gathering for hypothesis resolution using judicial evidential reasoning, *Information Fusion* 49 (2019) 26–45.
- [29] H. Seiti, A. Hafezalkotob, Developing pessimistic–optimistic risk-based methods for multi-sensor fusion: An interval-valued evidence theory approach, *Applied Soft Computing* 72 (2018) 609–623.
- [30] D. Zhou, Y. Tang, W. Jiang, An improved belief entropy and its application in decision-making, *Complexity*-doi:10.1155/2017/4359195.
- [31] Z. He, W. Jiang, An evidential Markov decision making model, *INFORMATION SCIENCES* 467 (2018) 357–372. doi:10.1016/j.ins.2018.08.013.
- [32] G. L. Prajapati, R. Saha, Reeds: Relevance and enhanced entropy based dempster shafer approach for next word prediction using language model, *Journal of Computational Science* 35 (2019) 1–11.
- [33] H. Cui, Q. Liu, J. Zhang, B. Kang, An Improved Deng Entropy and Its Application in Pattern Recognition, *IEEE ACCESS* 7 (2019) 18284–18292. doi:10.1109/ACCESS.2019.2896286.
- [34] J. Vandoni, E. Aldea, S. Le Hégarat-Masclé, Evidential query-by-committee active learning for pedestrian detection in high-density crowds, *International Journal of Approximate Reasoning* 104 (2019) 166–184.
- [35] R. Jirousek, P. P. Shenoy, A new definition of entropy of belief functions in the Dempster-Shafer theory, *INTERNATIONAL JOURNAL OF APPROXIMATE REASONING* 92 (2018) 49–65. doi:10.1016/j.ijar.2017.10.010.
- [36] Y. Wang, F. Liu, A. Zhu, Bearing fault diagnosis based on a hybrid classifier ensemble approach and the improved dempster-shafer theory, *Sensors* 19 (9) (2019) 2097.
- [37] W. Zhu, H. Yang, Y. Jin, B. Liu, A method for recognizing fatigue driving based on dempster-shafer theory and fuzzy neural network, *Mathematical Problems in Engineering* 2017.
- [38] Y. Deng, Generalized evidence theory, *APPLIED INTELLIGENCE* 43 (3) (2015) 530–543. doi:10.1007/s10489-015-0661-2.
- [39] H. Cui, Q. Liu, J. Zhang, B. Kang, An improved deng entropy and its application in pattern recognition, *Ieee Access* 7 (2019) 18284–18292. doi:10.1109/access.2019.2896286.
- [40] W. Jiang, S. Wang, An uncertainty measure for interval-valued evidences, *International Journal of Computers Communications & Control* 12 (5) (2017) 631–644. doi:10.15837/ijccc.2017.5.2950.
- [41] R. Jirousek, P. P. Shenoy, A new definition of entropy of belief functions in the dempster-shafer theory, *International Journal of Approximate Reasoning* 92 (2018) 49–65. doi:10.1016/j.ijar.2017.10.010.
- [42] M. D. Mambe, T. N’Takpe, N. G. Anoh, S. Oumtanaga, A new uncertainty measure in belief entropy framework, *International Journal of Advanced Computer Science and Applications* 9 (11) (2018) 600–606.

- [43] Y. Tang, D. Zhou, S. Xu, Z. He, A weighted belief entropy-based uncertainty measure for multi-sensor data fusion, *Sensors* 17 (4). doi:10.3390/s17040928.
- [44] D. Wang, J. Gao, D. Wei, A new belief entropy based on deng entropy, *Entropy* 21 (10). doi:10.3390/e21100987.
- [45] X. Wang, Y. Song, Uncertainty measure in evidence theory with its applications, *Applied Intelligence* 48 (7) (2018) 1672–1688. doi:10.1007/s10489-017-1024-y.
- [46] Y. Zhao, D. Ji, X. Yang, L. Fei, C. Zhai, An improved belief entropy to measure uncertainty of basic probability assignments based on deng entropy and belief interval, *Entropy* 21 (11). doi:10.3390/e21111122.
- [47] D. Zhou, Y. Tang, W. Jiang, A modified belief entropy in dempster-shafer framework, *Plos One* 12 (5). doi:10.1371/journal.pone.0176832.
- [48] Q. Pan, D. Zhou, Y. Tang, X. Li, J. Huang, A Novel Belief Entropy for Measuring Uncertainty in Dempster-Shafer Evidence Theory Framework Based on Plausibility Transformation and Weighted Hartley Entropy, *ENTROPY* 21 (2). doi:10.3390/e21020163.
- [49] A. Reny, On measures of entropy and information, *Symposium on Mathematics Statistics and Probabilities* (1961) 547–561.
- [50] K. Ghoshal, M. Kumbhakar, V. P. Singh, Distribution of sediment concentration in debris flow using rényi entropy, *Physica A: Statistical Mechanics and its Applications* 521 (2019) 267 – 281. doi:https://doi.org/10.1016/j.physa.2019.01.081.
- [51] C. TSALLIS, POSSIBLE GENERALIZATION OF BOLTZMANN-GIBBS STATISTICS, *JOURNAL OF STATISTICAL PHYSICS* 52 (1-2) (1988) 479–487. doi:10.1007/BF01016429.
- [52] A. Gholami, H. Bonakdari, A. Mohammadian, A method based on the tsallis entropy for characterizing threshold channel bank profiles, *Physica A: Statistical Mechanics and its Applications* 526 (2019) 121089. doi:https://doi.org/10.1016/j.physa.2019.121089.
- [53] Y. Deng, Deng entropy, *CHAOS SOLITONS & FRACTALS* 91 (2016) 549–553. doi:10.1016/j.chaos.2016.07.014.
- [54] L. H. Gunn, H. Gzyl, E. ter Horst, M. J. Ariza, G. Molina, Maximum entropy in the mean methods in propensity score matching for interval and noisy data, *Communications in Statistics-Theory and Methods* 48 (18) (2019) 4581–4597. doi:10.1080/03610926.2018.1497656.
URL <Go to ISI>://WOS:000478058200008
- [55] H. Gzyl, Construction of contingency tables by maximum entropy in the mean, *Communications in Statistics-Theory and Methods* doi:10.1080/03610926.2020.1723639.
URL <Go to ISI>://WOS:000512794400001
- [56] A. Hazan, A maximum entropy network reconstruction of macroeconomic models, *Physica A: Statistical Mechanics and its Applications* 519 (2019) 1 – 17. doi:https://doi.org/10.1016/j.physa.2018.12.020.
- [57] A. K. Tanak], G. M. Borzadaran], J. Ahmadi, Maximum tsallis entropy with generalized gini and gini mean difference indices constraints, *Physica A: Statistical Mechanics and its Applications* 471 (2017) 554 – 560. doi:https://doi.org/10.1016/j.physa.2016.12.018.
- [58] P. Macedo, Ridge regression and generalized maximum entropy: An improved version of the ridge-gme parameter estimator, *Communications in Statistics-Simulation and Computation* 46 (5) (2017) 3527–3539. doi:10.1080/03610918.2015.1096378.
URL <Go to ISI>://WOS:000402090000015
- [59] P. Macedo, M. Scotto, E. Silva, Regularization with maximum entropy and quantum electrodynamics: The merg(e) estimators, *Communications in Statistics-Simulation and Computation* 45 (3) (2016) 1143–1157. doi:10.1080/03610918.2014.957838.
URL <Go to ISI>://WOS:000372527900022
- [60] A. Dobovišek, R. Markovič, M. Brumen, A. Fajmut, The maximum entropy production and maximum shannon information entropy in enzyme kinetics, *Physica A: Statistical Mechanics and its Applications* 496 (2018) 220 – 232. doi:https://doi.org/10.1016/j.physa.2017.12.111.
- [61] O. Parkash, Mukesh, Contribution of maximum entropy principle in the field of queueing theory, *Communications in Statistics-Theory and Methods* 45 (12) (2016) 3464–3472. doi:10.1080/03610926.2013.875574.
URL <Go to ISI>://WOS:000375864900005

- [62] L. Khribi, M. Fredette, B. Macgibbon, The poisson maximum entropy model for homogeneous poisson processes, *Communications in Statistics-Simulation and Computation* 45 (9) (2016) 3435–3456. doi:10.1080/03610918.2014.944827. URL <Go to ISI>://WOS:000382518900022
- [63] K. Okada, Gyarmati's principle and edelen representation of thermodynamic forces in the maximum entropy formalism, *Physica A: Statistical Mechanics and its Applications* 489 (2018) 40 – 46. doi:https://doi.org/10.1016/j.physa.2017.07.021.
- [64] B. Kang, Y. Deng, The Maximum Deng Entropy, *IEEE ACCESS* 7 (2019) 120758–120765. doi:10.1109/ACCESS.2019.2937679.
- [65] M. Masi, A step beyond Tsallis and Renyi entropies, *PHYSICS LETTERS A* 338 (3-5) (2005) 217–224. doi:10.1016/j.physleta.2005.01.094.
- [66] F. Liu, X. Gao, J. Zhao, Y. Deng, Generalized Belief Entropy and Its Application in Identifying Conflict Evidence, *IEEE ACCESS* 7 (2019) 126625–126633. doi:10.1109/ACCESS.2019.2939332.
- [67] M. S. Tabass, G. R. M. Borzadaran, The generalized maximum tsallis entropy estimators and applications to the portland cement dataset, *Communications in Statistics-Simulation and Computation* 46 (4) (2017) 3284–3293. doi:10.1080/03610918.2015.1082589. URL <Go to ISI>://WOS:000400186200051

LaTeX Souce Files

[Click here to download LaTeX Souce Files: theGenEntropy.zip](#)

Declaration of interests

☒ The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

☐ The authors declare the following financial interests/personal relationships which may be considered as potential competing interests: