AIAC-19.2

Name: Siri Vempati

Ht.no:2303A51309

Batch.no:05

Task-1

Prompt:

Convert the following Python file handling program into Java. Ensure proper file reading and writing, exception handling, and same output behavior. Maintain clean formatting and equivalent logic.

Python Code:

```
Ass-19.2 > ass-19.2.py > process_file
def process_file():
    try:
        with open("Ass-19.2/input.txt", "r") as infile:
            content = infile.read()
        print("Original Content:")
        print(content)
        modified_content = content.upper()
        with open("Ass-19.2/output.txt", "w") as outfile:
            outfile.write(modified_content)
        print("\nModified content written to output.txt")
    except FileNotFoundError:
        print("Error: input.txt not found.")
    except Exception as e:
        print("An error occurred:", e)
if __name__ == "__main__":
    process_file()
```

Output:

```
ass-19.2.py Ass-19.2
output.txt Ass-19.2
input.txt Ass-19.2
employee.csv
AI ASSISTANT CODING
ASS-16.4
Ass-19.2
ass-19.2.py
input.txt
output.txt
food-api
Lab.html
New folder

PS C:\Users\vempa\OneDrive\Pictures\Desktop\HCL LAB\AI ASSISTANT CODING> & C:/Users/vempa/AppData/Local/Prog
ctures/Desktop/HCL LAB/AI ASSISTANT CODING/Ass-19.2/ass-19.2.py"
ctures/Desktop/HCL LAB/AI ASSISTANT CODING/Ass-19.2/ass-19.2.py"
ctures/Desktop/HCL LAB/AI ASSISTANT CODING/Ass-19.2/ass-19.2.py"
ctures/Desktop/HCL LAB/AI ASSISTANT CODING/Ass-19.2/ass-19.2.py"
ctures/Desktop/HCL LAB/AI ASSISTANT CODING/Ass-19.2/ass-19.2.py"
ctures/Desktop/HCL LAB/AI ASSISTANT CODING/Ass-19.2/ass-19.2.py"
Original Content:
Hello World
This is a sample file
AI Lab Practice

Modified content written to output.txt
PS C:\Users\vempa\OneDrive\Pictures\Desktop\HCL LAB\AI ASSISTANT CODING>
```

Ass-19.2 > output.txt

```
HELLO WORLD
THIS IS A SAMPLE FILE
AI LAB PRACTICE
```

Java code:

Ass-19.2 > FileProcessor.java > FileProcessor > main(String[])

```java
import java.io.*;
public class FileProcessor {
    public static void processFile() {
        try {
            BufferedReader reader = new BufferedReader(new FileReader(fileName: "Ass-19.2/input.txt"));
            StringBuilder content = new StringBuilder();
            String line;

            while ((line = reader.readLine()) != null) {
                content.append(line).append(str: "\n");
            }
            reader.close();
            System.out.println(x: "Original Content:");
            System.out.println(content.toString());
            String modifiedContent = content.toString().toUpperCase();
            BufferedWriter writer = new BufferedWriter(new FileWriter(fileName: "Ass-19.2/output1.txt"));
            writer.write(modifiedContent);
            writer.close();
            System.out.println(x: "\nModified content written to output1.txt");
        } catch (FileNotFoundException e) {
            System.out.println(x: "Error: input.txt not found.");
        } catch (IOException e) {
            System.out.println("I/O Error: " + e.getMessage());
        } catch (Exception e) {
            System.out.println("An unexpected error occurred: " + e.getMessage());
        }
    }
    Run | Debug
    public static void main(String[] args) {
        processFile();
    }
}
```

Output:

EXPLORER

OPEN EDITORS
- database.db ASS-16.4
- schema.sql ASS-16.4
- t1.html Lab.html
- factorial_demo.py
- ass-18.4.py
- ass-19.2.py Ass-19.2
- FileProcessor.java Ass-...
- output1.txt Ass-19.2
- FileProcessor.class

AI ASSISTANT CODING
- ASS-16.4
- Ass-19.2
  - ass-19.2.py
  - FileProcessor.class
  - FileProcessor.java
  - input.txt
  - output.txt
  - output1.txt
- food-api
- Lab.html
- New folder
- node_modules
- payroll-api
- quiz-app
- student-api

ase.db | schema.sql | t1.html | factorial_demo.py | ass-18.4.py | ass-19.2.py | FileProcessor.java

Ass-19.2 > output1.txt

```
HELLO WORLD
THIS IS A SAMPLE FILE
AI LAB PRACTICE
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS POSTMAN CONSOLE

```
e6\redhat.java\jdt_ws\AI ASSISTANT CODING_c849a492\bin' 'FileProcessor'
Original Content: …
PS C:\Users\vempa\OneDrive\Pictures\Desktop\HCL LAB\AI ASSISTANT CODING>  c:; cd 'c:\Users\vempa\OneDrive\Pictures\De
iles\Java\jdk-22\bin\java.exe' '-XX:+ShowCodeDetailsInExceptionMessages' '-cp' 'C:\Users\vempa\AppData\Roaming\Code\U
e6\redhat.java\jdt_ws\AI ASSISTANT CODING_c849a492\bin' 'FileProcessor'
Original Content:
Hello World
This is a sample file
AI Lab Practice


Modified content written to output1.txt
```

Explanation:

The Python program reads content from a file (input.txt), displays it, converts the text to uppercase, and writes it to another file (output.txt). It uses with open() for automatic file handling and includes exception handling for missing files and general errors.

The Java version replicates the same functionality using:

- BufferedReader for reading files
- BufferedWriter for writing files
- StringBuilder for efficient string handling
- try-catch blocks for handling exceptions like FileNotFoundException and IOException

Both programs:

- Read the same input file
- Produce identical console output
- Generate the same modified output file

Task-2

Convert the following C++ sorting program (Bubble Sort) into an equivalent Python program. Ensure the same logic, correctness, and output behavior. Include proper input/output handling.

C++ Code:

main.cpp

Share Run

```cpp
#include <iostream>
using namespace std;
void bubbleSort(int arr[], int n) {
    for (int i = 0; i < n-1; i++) {
        for (int j = 0; j < n-i-1; j++) {
            if (arr[j] > arr[j+1]) {
                int temp = arr[j];
                arr[j] = arr[j+1];
                arr[j+1] = temp;
            }
        }
    }
}
int main() {
    int n;
    cout << "Enter number of elements: ";
    cin >> n;
    int arr[n];
    cout << "Enter elements:\n";
    for (int i = 0; i < n; i++) {
        cin >> arr[i];
    }
    bubbleSort(arr, n);
    cout << "Sorted array:\n";
    for (int i = 0; i < n; i++) {
        cout << arr[i] << " ";
```


```cpp
    cout << "Sorted array:\n";
    for (int i = 0; i < n; i++) {
        cout << arr[i] << " ";
    }
```


```cpp
    return 0;
}
```

Output:

Output

```
Enter number of elements: 5
Enter elements:
2 9 4 1 0
Sorted array:
0 1 2 4 9

=== Code Execution Successful ===
```

Python Code:

```
Ass-19.2 > ass-19.2.py > ...
def bubble_sort(arr):
    n = len(arr)

    for i in range(n - 1):
        for j in range(n - i - 1):
            if arr[j] > arr[j + 1]:
                # swap
                arr[j], arr[j + 1] = arr[j + 1], arr[j]

    return arr


def main():
    try:
        n = int(input("Enter number of elements: "))

        arr = list(map(int, input("Enter elements separated by space:\n").split()))

        if len(arr) != n:
            print("❌ Number of elements mismatch.")
            return

        sorted_arr = bubble_sort(arr)

        print("Sorted array:")
        print(*sorted_arr)

    except ValueError:
        print("❌ Invalid input. Please enter integers only.")


if __name__ == "__main__":
    main()
```

Output:

```
AI Lab Practice
...
PS C:\Users\vempa\OneDrive\Pictures\Desktop\HCL LAB\AI ASSISTANT CODING> & C:/Users/vempa/AppData/Local/Programs/Python/Python311/pytho
ctures/Desktop/HCL LAB/AI ASSISTANT CODING/Ass-19.2/ass-19.2.py"
Enter number of elements: 5
Enter elements separated by space:
1 9 4 2 0
Sorted array:
0 1 2 4 9
PS C:\Users\vempa\OneDrive\Pictures\Desktop\HCL LAB\AI ASSISTANT CODING>
```

Explanation:

The original C++ program implements the **Bubble Sort algorithm**, where adjacent elements are repeatedly compared and swapped if they are in the wrong order. This process continues until the array is sorted.

The Python version follows the same logic:

- Uses nested loops to compare adjacent elements
- Swaps elements using Python's tuple assignment
- Takes input dynamically and validates it
- Ensures the number of elements matches user input

Both implementations:

- Perform the same sorting steps
- Produce identical sorted output
- Maintain algorithm correctness

Task-03

Prompt:

Convert the following SQL query with GROUP BY and aggregate functions into equivalent Pandas code. Ensure correct grouping, aggregation, and matching output.

SQL CODE& Output:



```sql
-- Create table
CREATE TABLE sales_data (
    department TEXT,
    sales INTEGER
);

-- Insert data
INSERT INTO sales_data VALUES ('HR', 1000);
INSERT INTO sales_data VALUES ('IT', 2000);
INSERT INTO sales_data VALUES ('HR', 1500);
INSERT INTO sales_data VALUES ('Sales', 3000);
INSERT INTO sales_data VALUES ('IT', 2500);
INSERT INTO sales_data VALUES ('Sales', 3500);

-- Query (GROUP BY + SUM)
SELECT department, SUM(sales) AS total_sales
FROM sales_data
GROUP BY department;
```

department	total_sales
HR	2500
IT	4500
Sales	6500

Pandas(Python) Code:

```
Ass-19.2 > ass-19.2.py > ...

import pandas as pd

# Create sample dataset
data = {
    "department": ["HR", "IT", "HR", "Sales", "IT", "Sales"],
    "sales": [1000, 2000, 1500, 3000, 2500, 3500]
}

df = pd.DataFrame(data)

# Group By + Aggregation
result = df.groupby("department")["sales"].sum().reset_index()

# Display result
print(result)
```

Output:

```
                                                                                ^C
PS C:\Users\vempa\OneDrive\Pictures\Desktop\HCL LAB\AI ASSISTANT CODING> & C:/Users/vempa/AppData/Local/Programs/Python/Python311/python.exe
ctures/Desktop/HCL LAB/AI ASSISTANT CODING/Ass-19.2/ass-19.2.py"
  department  sales
0         HR   2500
1         IT   4500
2      Sales   6500
PS C:\Users\vempa\OneDrive\Pictures\Desktop\HCL LAB\AI ASSISTANT CODING>
```

Explanation:

The SQL query groups the data by the department column and calculates the total sales using the SUM() function.

Similarly, in pandas, the groupby() function is used to group the DataFrame by department, and the sum() function computes the total sales for each group. The reset_index() method converts the grouped result into a structured table format.

Both SQL and Pandas follow the same logic:

- Group data based on department
- Apply aggregation (sum of sales)
- Produce identical results

Task-04:

Prompt:

Convert the following Python Flask REST API into an equivalent Java Spring Boot application.

Ensure the same endpoint, functionality, and JSON output behavior.

Code:

factorial_demo.py | ass-18.4.py | ass-19.2.py | tas-4.py | Ass-19.2 | test.db | FileProcessor.jav

Ass-19.2 > tas-4.py > ...

```python
from flask import Flask, jsonify, request

app = Flask(__name__)

# Home route (to avoid 404 error)
@app.route('/')
def home():
    return "Flask API is running! Use /add?a=5&b=3"

# Add API
@app.route('/add', methods=['GET'])
def add_numbers():
    try:
        a = int(request.args.get('a'))
        b = int(request.args.get('b'))
        return jsonify({"result": a + b})
    except:
        return jsonify({"error": "Invalid input"}), 400

# Run app
if __name__ == '__main__':
    app.run(debug=True)
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS POSTMAN CONSOLE

```
PS C:\Users\vempa\OneDrive\Pictures\Desktop\HCL LAB\AI ASSISTANT CODING> python ASS-19.2/tas-4.py
 * Running on http://127.0.0.1:5000
Press CTRL+C to quit
 * Restarting with stat
 * Debugger is active!
 * Debugger PIN: 112-702-995
127.0.0.1 - - [01/Apr/2026 13:14:17] "GET / HTTP/1.1" 200 -
127.0.0.1 - - [01/Apr/2026 13:14:45] "GET /add?a=10&b=20 HTTP/1.1" 200 -
```

Output:

127.0.0.1:5000/add?a=5&b=3

127.0.0.1:5000/add?a=5&b=3

Pretty-print

```
{
  "result": 8
}
```

Java Code:

Java Equivalent of Python Sum Program

This Java program calculates the sum of numbers in an array, similar to your Python script. It demonstrates array declaration, iteration, and sum calculation in Java.

```
%%writefile SumNumbers.java

public class SumNumbers {

    public static void main(String[] args) {
        // Declare and initialize an array of integers
        int[] numbers = {10, 20, 30, 40};

        // Calculate the sum
        int total = 0;
        for (int number : numbers) {
            total += number;
        }

        // Print the total sum
        System.out.println("Total sum: " + total);
    }
}
```

```
Writing SumNumbers.java
```

Gemini

D Convert the given Python program into an equivalent Java program. Ensure the logic and functionality remain the same. Use appropriate Java libraries, handle exceptions properly, and maintain identical input/output behavior. Also, highlight key differences in syntax and execution # Python program to calculate sum of numbers numbers = [10, 20, 30, 40] total = sum(numbers) print("Total sum:", total)

Certainly! I'll convert your Python program for calculating the sum of numbers into an equivalent Java program. I'll also highlight the key differences in syntax and execution.

What can I help you build?

Gemini 2.5 Flash

Gemini can make mistakes so double-check it and use code with caution. Learn more

Output:

First, compile the Java source code:

```
# To compile the Java code (requires JDK installed in the environment)
!javac SumNumbers.java
```

After successful compilation (which will create `SumNumbers.class` if no errors), you can run the program:

```
# To run the compiled Java code
!java SumNumbers
```

```
Total sum: 100
```

Explanation:

Both Python and Java programs calculate the sum of numbers in a list/array using a loop. Each element is added to a total variable, and the final sum is displayed. Python uses a list and simple syntax, while Java uses an array and requires explicit data types. Despite syntax differences, both programs produce the same output.

TASK – 05

Prompt : Convert the given Python function that checks whether a number is even or odd into an equivalent C++ program. Ensure proper syntax, input handling, and output formatting, and verify that both programs produce the same results.

Function to check even or odd

def check_even_odd(num):

if num % 2 == 0: return

"Even" else:

return "Odd"

Input n = int(input("Enter a number: "))

print(check_even_odd(n)) **Code :**

```
%%writefile EvenOddChecker.cpp

#include <iostream>
#include <string>

// Function to check if a number is even or odd
std::string checkEvenOdd(int num) {
    if (num % 2 == 0) {
        return "Even";
    } else {
        return "Odd";
    }
}

int main() {
    int n;

    // Input
    std::cout << "Enter a number: ";
    std::cin >> n;

    // Call the function and print the result
    std::cout << checkEvenOdd(n) << std::endl;

    return 0;
}

Writing EvenOddChecker.cpp
```

Gemini

checks whether a number is even or odd into an equivalent C++ program. Ensure proper syntax, input handling, and output formatting, and verify that both programs produce the same results. # Function to check even or odd def check_even_odd(num): if num % 2 == 0: return "Even" else: return "Odd" # Input n = int(input("Enter a number: ")) print(check_even_odd(n))

Certainly! I'll convert your Python function for checking even or odd numbers into an equivalent C++ program. This will include the function definition, input handling, and output, along with an explanation of the C++ code and how to compile and run it.

What can I help you build?

Gemini 2.5 Flash

Gemini can make mistakes so double-check it and use code with caution. Learn more

Output :

```
# To compile the C++ code (requires g++ installed in the environment)
!g++ EvenOddChecker.cpp -o EvenOddChecker
```

After successful compilation (which creates an executable named `EvenOddChecker` if no errors), you can run the program. You'll be prompted to enter a number.

```
# To run the compiled C++ code
# The program will prompt for input, enter a number (e.g., 7) and press Enter.
!./EvenOddChecker

Enter a number: 5
Odd
```

Explanation :

- The task converts a Python function into an equivalent C++ program.
- Both programs use the same logic (num % 2) to check even or odd.
- Proper syntax and input/output handling are ensured in C++.
- The programs are tested with different inputs to verify correctness.
- Both versions produce the same output, confirming successful translation.