

TECHNICAL BULLETIN

DIXIE FUNCTIONAL ADDITIVES

10601 Bay Area Blvd.
Pasadena, TX 77507
Tel: (281) 474-3271
Fax: (281) 291-3384
E-Mail: info@dixiechemicalgroup.com

JP-10 (Octahydro-1H-4,7-methanoindene, CAS# 2825-82-3)

Property	Typical Values*
Appearance	Clear Colorless Liquid
Total JP-10, %	98.5 - 100
Flash Point, °C	55 - 65
Heat of Combustion, MJ/kg	42.1 min
Kinematic Viscosity @ -18°C, cSt	< 10
Kinematic Viscosity @ -54°C, cSt	< 40
Specific Gravity 60/60F	0.934 -0.943
Saybolt Color	25 +

*These are not specifications

Applications

JP-10 is a jet fuel and a gas turbine fuel for missiles. Its high energy density and low freezing point make it ideal for military aerospace applications.

Handling & Storage

JP-10 is very stable under normal conditions. It should be stored away from moisture, high temperatures, ignition sources, or oxidizing materials.

Health Hazards

Avoid contact with skin, eyes, and clothing. Use only with adequate ventilation. In case of contact, immediately flush the affected skin or eyes

The data contained herein are furnished for information only and are believed to be reliable. This information is provided only as guidance and is not to be considered a warranty or quality specification. Dixie Chemical Company, Inc. makes no warranties (expressed or implied) as to its accuracy and assumes no liability in connection with any use of this product.

TECHNICAL BULLETIN

JP-10

with copious amounts of water for at least 15 minutes. In the case of eye contact, get medical attention. Wash contaminated clothing before reuse.

The minimum personal protective equipment when handling these materials typically includes protective chemical goggles, impenetrable gloves, and measures to avoid breathing chemical vapors.

Availability

JP-10 is available from Dixie Chemical Company, Inc.'s plant in Pasadena, Texas. Contact your Dixie Chemical Company representative for details.