

C4T2066 / 4E-PGT 2-06 H CL

Specifications and rack part list

Batteries	0 units; model not specified
Length	600.00 mm
Width	960.00 mm
Height	1958.00 mm
Height above battery (catalogue)	1958.00 mm
Width B	890.00 mm
Battery weight	0.00 kg
Rack weight	130.00 kg
Total weight	130.00 kg
Projected surface load	225.69 kg/m ²
Load per isolator	32.50 kg
Clearance WR	402.00 mm
Center of gravity: x	480.00 mm
Center of gravity: y	300.00 mm
Center of gravity: z	979.00 mm

Rack part list (manufacturer data)

Packages	Article	Length, mm	Width, mm	Height, mm	Weight, kg
2.0	5EPGL4	1943.00	930.00	50.00	18.50
4.0	604	625.00	115.00	90.00	7.50
1.0	CFP5E06	1860.00	520.00	15.00	18.00
1.0	CSP5EPGL4	1860.00	970.00	90.00	40.00
1.0	CTPPGL406	600.00	990.00	15.00	5.00

Source state: empty rack. These are not permissible load ratings.


Row dimensions and weights are copied from the manufacturer catalogue; fasteners are not listed.

Manufacturer images may be shared by several rack lengths.

C4T2066 / 4E-PGT 2-06 H CL

Dimension drawing and footprint

Dimension drawing



Footprint



L = length; B = width between supports; H = height. Dimensions in mm.

C4T2066 / 4E-PGT 2-06 H CL

Visualization and clearance

Manufacturer photo / visualization



Clearance: generic explanatory illustration



The generic illustration does not show your battery arrangement.

C4T2066 / 4E-PGT 2-06 H CL

Center of gravity and sources

Center of gravity: generic illustration



Card information

Article: C4T2066

Manufacturer catalogue data.

Images are embedded for offline printing.