

CSS3125 / E-SGS 3-12 CL

Specifications and rack part list

Batteries	0 units; model not specified
Length	1200.00 mm
Width	960.00 mm
Height	2190.00 mm
Height above battery (catalogue)	2190.00 mm
Width B	890.00 mm
Battery weight	0.00 kg
Rack weight	201.00 kg
Total weight	201.00 kg
Projected surface load	174.48 kg/m ²
Load per isolator	50.25 kg
Clearance WR	960.00 mm
Center of gravity: x	480.00 mm
Center of gravity: y	600.00 mm
Center of gravity: z	1095.00 mm

Rack part list (manufacturer data)

Packages	Article	Length, mm	Width, mm	Height, mm	Weight, kg
2.0	CESGS3	2185.00	930.00	50.00	32.50
2.0	1206	1225.00	160.00	90.00	21.00
1.0	CFP6E12	2095.00	1125.00	15.00	40.00
1.0	CSP6EPGL4	2095.00	970.00	90.00	45.00
1.0	CTPPGL412	1200.00	990.00	15.00	9.00

Source state: empty rack. These are not permissible load ratings.


Row dimensions and weights are copied from the manufacturer catalogue; fasteners are not listed.

Manufacturer images may be shared by several rack lengths.

CSS3125 / E-SGS 3-12 CL

Dimension drawing and footprint

Dimension drawing



Footprint



L = length; B = width between supports; H = height. Dimensions in mm.


CSS3125 / E-SGS 3-12 CL

Visualization and clearance

Manufacturer photo / visualization



Clearance: generic explanatory illustration



The generic illustration does not show your battery arrangement.

CSS3125 / E-SGS 3-12 CL

Center of gravity and sources

Center of gravity: generic illustration



Card information

Article: CSS3125

Manufacturer catalogue data.

Images are embedded for offline printing.