Setting up PostgreSQL on ktppg.vsshp.net

Document Author: arho.virkki@vtt.fi & anna.hammais@tyks.fi

To simplify things, we set up ssh keys such that logging into *ktppg.vsshp.net* does need password. Since the private and public keys are already generated with *ssh-keygen*, we only need to copy the public key to *ktppg*:

```
ssh-copy-id -i ~/.ssh/id_rsa.pub ktppg.vsshp.net
```

Now we can access *ktppg* simply with

```
ssh ktppg.vsshp.net
```

Installing PostgreSQL

For details, see http://www.postgresql.org/download/linux/ubuntu/

Find out the PostgreSQL version included in your version of Ubuntu by issuing

```
apt-cache search postgresql | less
```

If this is not the version you want, issue

```
sudo su -c 'echo "deb http://apt.postgresql.org/pub/repos/apt/ trusty-pgdg main" >
   /etc/apt/sources.list.d/pgdg.list'
```

Then import the repository key

```
wget --quiet -0 - https://www.postgresql.org/media/keys/ACCC4CF8.asc | sudo apt-key add -
sudo apt-get update
```

After this, or if the default PostgreSQL version was the one that you wanted, instakk bt issuing

```
sudo apt-get install postgresql-9.4
```

or

```
# default version
sudo apt-get install postgresql
```

The most important PostreSQL files and directories are

```
/etc/postgresq1/9.4/
/etc/postgresq1-common/
/usr/lib/postgresq1/9.4/
/usr/share/postgresq1/9.4/
/usr/share/postgresq1-common/
/usr/share/doc/postgresq1/
```

Entering PostgreSQL shell

```
sudo su - postgres
psql
```

First we set a password for the *postgres* account for doing remote backups. (For now, the password will be same as *ktp* system users password.)

```
postgres=# \password
Enter new password:
Enter it again:
```

Then, create a ktp user and default database

2018-01-18 Subtopic Page 1/2

```
CREATE USER ktp SUPERUSER PASSWORD 'write pwd here';
CREATE DATABASE ktp WITH OWNER = ktp;
```

Now we access PostgreSQL with

```
psql -d postgres -- connect to database postgres
```

To simplify privilege management, revoke all rights from the public role in the new database, so that they cannot be inherited by new roles that will be created in the future

```
REVOKE ALL ON DATABASE ktp FROM PUBLIC;
\c ktp -- connect to database ktp
REVOKE ALL ON SCHEMA public FROM PUBLIC;
```

Enable remote connections

Become root again and issue

```
sudo vi /etc/postgresql/9.4/main/postgresql.conf
```

and change the line

```
#listen_addresses = 'localhost'
```

to

listen_addresses = '*'

and also change the line:

```
#password_encryption = on
```

to

password_encryption = on

Then, edit the host-based authentication file with

```
sudo vi /etc/postgresql/9.4/main/pg_hba.conf
```

and add the lines

```
# Connections for a range of PCs on the vsshp subnet
host all all 10.150.0.0/16 md5
host all all 10.145.0.0/16 md5
```

and restart the service with

```
sudo service postgresql restart
```

to allow access from the vsshp network.

Install PgAdmin III

Install PgAdmin III (e.g. with sudo apt-get install pgadmin3) on the client machine and enable the Extension pack on the server:

```
sudo -u postgres psql
\c ktp
CREATE EXTENSION adminpack;
```

To see a list of installed extensions, issue

```
SELECT * FROM pg_extension;
```

Remember that the extensions are installed per database.

2018-01-18