

Code Review Report

Language: python | Review mode: hybrid | Model: llama-3.3-70b-versatile | Generated: 2026-08-13 17:33 UTC

Overall Assessment

PR summary generation was skipped because Groq rate limited the request.

Merge readiness: unknown

Code health: 0/100

Findings Summary

Total findings: 12

Risk score: 45

Severity breakdown: Low 0, Medium 0, High 3, Critical 9

Type	Severity	Line	Message	Recommendation
Hardcoded Password	High	1	password = "admin123"	Store passwords in environment variables.
Hardcoded API Key	High	3	api_key = "123456789"	Store secrets securely.
SQL Injection	Critical	7	query = "SELECT * FROM users WHERE name='" + name + "'"	Use parameterized queries.
Dangerous Dynamic Execution	Critical	9	eval(input())	Avoid dynamic code execution.
Dangerous Dynamic Execution	Critical	11	exec("print('Hello')")	Avoid dynamic code execution.
Command Injection	Critical	15	subprocess.run("dir", shell=True)	Do not use shell=True with user input.
Security	Critical	1	Hardcoded password	Use environment variables or a secure secrets management system to store sensitive information
Security	Critical	2	Hardcoded API key	Use environment variables or a secure secrets management system to store sensitive information
Security	Critical	5	SQL injection vulnerability	Use parameterized queries or prepared statements to prevent SQL injection attacks
Security	Critical	6	Use of eval function with user input	Avoid using eval function with user input, as it can lead to code injection attacks. Use a safer alternative, such as ast.literal_eval or json.loads

Type	Severity	Line	Message	Recommendation
Security	Critical	7	Use of exec function	Avoid using exec function, as it can lead to code injection attacks. Use a safer alternative, such as a templating engine or a configuration file
Security	High	10	Use of subprocess with shell=True	Avoid using subprocess with shell=True, as it can lead to shell injection attacks. Use a safer alternative, such as subprocess.run with the 'args' parameter

Remediation Roadmap

Finding	Severity	Impact	Suggested Action
---------	----------	--------	------------------

Source Code Snapshot

```
password = "admin123"

api_key = "123456789"

name = input()

query = "SELECT * FROM users WHERE name='" + name + "'"

eval(input())

exec("print('Hello')")

import subprocess

subprocess.run("dir", shell=True)
```