Multi-Core CPU Benchmarking & Operating Systems Monitor

Comprehensive Academic & Engineering Project Report

Project Title

Multi-Core CPU Benchmarking & Operating Systems Monitor for Android: An Empirical Investigation of Linux CFS Scheduling, ARM big.LITTLE Topology, Concurrency Hazards, Amdahl's Law, and Asynchronous Java-Kotlin Architecture

Team Members Details

S. No	Student Name	Registration Number	Academic Role
1	**M. Ahmad Aniz**	**25BCE1139**	Lead Concurrency Architect & Systems Programmer
2	**G S Mithul Kruthik**	**25BCE1560**	Operating Systems Kernel & Scheduling Specialist
3	**Siva Kumar P**	**25BCE5735**	Mathematical Modeling, Visualization & Multimedia Lead

Abstract

Modern mobile platforms run on sophisticated heterogeneous multi-core System-on-Chips (SoCs) governed by Linux kernel scheduling policies. This project develops a comprehensive, production-grade Android benchmarking and operating systems analysis suite written collaboratively in **Java** and **Kotlin**.

The application quantitatively executes compute-bound workloads (deterministic Prime Number Searching and (300 \times 300) Matrix Multiplication) across variable thread pools (1, 2, 4, and 8 concurrent workers). To satisfy academic **Requirement R3**, the software directly interrogates the Linux kernel's virtual task accounting subsystem (`/proc/self/task/[TID]/stat` , field 39) to detect and visually highlight hardware core affinity in real time, exposing how the Linux Completely Fair Scheduler (CFS) maps POSIX threads to heterogeneous ARM big.LITTLE (efficiency vs. performance) core clusters.

Furthermore, the project validates **Amdahl's Law** through rigorous mathematical derivations and interactive simulation, quantifies concurrency hazards by measuring lost update frequencies and lock synchronization overhead in deliberate race condition stress tests, establishes the architectural bridge between Object-Oriented Listeners and Functional Lambdas via Single Abstract Method (SAM) conversion, and provides an in-app 60 FPS vector animated video with offline spoken audio narration. The resulting platform delivers an end-to-end, pedagogical tool for operating systems education.

Modules of the Project

The application is structured into five distinct, loosely coupled architectural modules:



1. **Module 1: Kernel Task Probing & Real-Time CPU Core Grid Monitor (Requirement R3)**:
   - Probes Linux `/proc/self/task/[TID]/stat` to determine the physical CPU core assigned to each thread.
   - Discovers heterogeneous core topology from `/sys/devices/system/cpu/` , separating LITTLE (efficiency) cores from BIG (performance) cores.
   - Renders an 8-core dynamic grid in the UI with active glowing borders (`bg_core_active.xml`) and live thread badges (`T0 [TID 2381]`).
   - Provides runtime toggling of Linux CFS scheduling priorities: Normal (Nice 0), Background (Nice +10), and Urgent (Nice -16).
2. **Module 2: Multi-Threaded Benchmark Execution Engine & Java-Kotlin Bridge**:
   - Pure Java execution engine utilizing `java.util.concurrent.ExecutorService` , `Callable` , and `Future` .
   - Cross-language interoperability demonstrating the relation between traditional Java Observer Listeners (`BenchmarkListener.java`) and Kotlin Functional Lambdas (`BenchmarkProgressListener.java` via SAM conversion).
   - Supports deterministic workloads: prime counting and matrix row decomposition.
3. **Module 3: Concurrency Safety & Race Condition / Critical Section Analyzer**:
   - Evaluates memory hazards: unsynchronized mutable memory accumulation (`total++`) vs. hardware atomic memory synchronization (`AtomicLong`).
   - Measures lost updates count, error percentage, and synchronization lock overhead across single and repeated 5-run stress tests.
4. **Module 4: Amdahl's Law Mathematical Speedup Modeling & Interactive Simulator**:

    - Analyzes empirical runtimes to calculate the parallel fraction (P), serial bottleneck (1 - P), and asymptotic maximum speedup limit (\frac{1}{1-P}).
    - Incorporates an interactive SeekBar slider (50% to 99%) projecting speedups up to 64 virtual cores.
    - Renders combined bar and line charts via `MPAndroidChart` comparing measured time with theoretical trajectories.
5. **Module 5: Multimedia Pedagogy & Offline Audio Guide**:
    - Implements a custom 60 FPS vector animation player (`AnimatedVideoCanvasView.kt`) illustrating CPU core dispatching, race conditions, Amdahl diminishing returns, and Looper thread boundaries.
    - Incorporates native spoken audio narration via Android's `TextToSpeech` service and acoustic sound cues (`TutorialAudioManager.kt`), working 100% offline.
    - Includes an in-app Code & OS Architecture Study Guide bottom sheet dialog.

Sample Code

1. Linux Kernel Hardware Core & Scheduling Policy Probing (`CpuTopologyHelper.java`)

This method parses `/proc/self/task/[TID]/stat` without requiring elevated root permissions, reading token index 36 (Field 39) to determine the exact physical CPU core:

```
public static int getCpuForTid(int tid, int fallbackCoreIndex) {
    if (tid <= 0) {
        try {
            tid = Process.myTid();
        } catch (Throwable ignored) {
            tid = 1;
        }
    }
    String path = "/proc/self/task/" + tid + "/stat";
    try (BufferedReader reader = new BufferedReader(new FileReader(path))) {
        String line = reader.readLine();
        if (line != null) {
            int lastParen = line.lastIndexOf(')');
            if (lastParen != -1 && lastParen + 2 < line.length()) {
                String rest = line.substring(lastParen + 2).trim();
                String[] tokens = rest.split("\\s+");
                // Token index 36 corresponds to field 39 (processor core)
                if (tokens.length > 36) {
                    int cpu = Integer.parseInt(tokens[36]);
                    if (cpu >= 0 && cpu < 64) {
                        return cpu;
                    }
                }
            }
        }
    } catch (Throwable ignored) { }

    int coreCount = getAvailableProcessors();
    return (coreCount > 0 && fallbackCoreIndex >= 0) ? (fallbackCoreIndex % coreCount) : 0;
}
```

2. Java Multi-Threaded Concurrency & Core Tracking (`CpuBenchmarkEngine.java`)

Demonstrates Java thread pool execution, applying Linux nice priorities via `Process.setThreadPriority`, capturing thread metrics, and dispatching progress to listeners:

```
futures.add(executor.submit(new Callable<Void>() {
    @Override
    public Void call() {
        int tid = threadIndex;
        try {
            Process.setThreadPriority(policy.getNicePriority());
            tid = Process.myTid();
        } catch (Throwable ignored) {
            tid = (int) Thread.currentThread().getId();
        }
        tids.add(tid);

        int initialCore = CpuTopologyHelper.getCpuForTid(tid, threadIndex);
        String coreType = (initialCore >= 4) ? "BIG" : "LITTLE";
        int priority = Process.getThreadPriority(tid);
        String schedPolicy = CpuTopologyHelper.getSchedulingPolicyName(tid);

        ThreadExecutionInfo info = new ThreadExecutionInfo(
                threadIndex, tid, initialCore, coreType, priority, schedPolicy
        );
        executions.add(info);

        if (listener != null) listener.onThreadScheduled(info);
        if (progressListener != null) progressListener.onProgress(info);

        long chunkStart = System.currentTimeMillis();
        long units = executeChunk(type, start, end);
        long chunkElapsed = System.currentTimeMillis() - chunkStart;

        info.setWorkUnits(units);
        info.setElapsedMs(chunkElapsed);
        info.setCpuCore(CpuTopologyHelper.getCpuForTid(tid, initialCore));

        totalWorkUnits.addAndGet(units);
        if (listener != null) listener.onThreadProgress(threadIndex, 1.0f);
        return null;
    }
}));
```

3. Single Abstract Method (SAM) Conversion: Bridging Functions & Listeners (`BenchmarkProgressListener.java` & `MainActivity.kt`)

Demonstrates how a Java Single Abstract Method listener interface is consumed as a pure lambda function in Kotlin:

```
// Java Interface Definition (SAM)
@FunctionalInterface
public interface BenchmarkProgressListener {
    void onProgress(ThreadExecutionInfo info);
}
```

```
// Kotlin Consumer in MainActivity.kt
// A first-class Kotlin lambda is passed directly where a Java Listener is expected:
engine.setOnProgressListener { info ->
    // Dispatched safely to the Main UI Thread via runOnUiThread
    highlightCore(info.cpuCore, info.threadIndex, info.tid)
}
```

4. Amdahl's Law Mathematical Derivation (`AmdahlAnalysis.java`)

Computes the parallel fraction (P) from single-thread baseline and multi-thread measured time, calculating theoretical speedups and asymptotic limits:

```
public static double estimateParallelFraction(long baselineMs, int threadCount, long measuredMs) {
    if (baselineMs <= 0 || measuredMs <= 0 || threadCount <= 1) return 0.90;
    double measuredSpeedup = (double) baselineMs / (double) measuredMs;
    double denom = 1.0 - (1.0 / threadCount);
    if (denom <= 0.0) return 0.90;

    double p = (1.0 - (1.0 / measuredSpeedup)) / denom;
    return Math.max(0.05, Math.min(0.999, p));
}

public static double theoreticalSpeedup(double parallelFraction, int threadCount) {
    if (threadCount <= 1) return 1.0;
    double serialFraction = 1.0 - parallelFraction;
    return 1.0 / (serialFraction + (parallelFraction / threadCount));
}

public static double theoreticalMaxSpeedup(double parallelFraction) {
    double serialFraction = 1.0 - parallelFraction;
    return (serialFraction <= 0.0001) ? 999.0 : (1.0 / serialFraction);
}
```

5. Deliberate Race Condition Execution (`CpuBenchmarkEngine.java`)

Omits locks and atomic primitives to trigger concurrent read-modify-write collisions on an unsynchronized accumulator:

```
final long[] sharedCounter = new long[]{0}; // Unsynchronized mutable memory
for (int i = 0; i < threadCount; i++) {
    futures.add(executor.submit(() -> {
        for (int n = start; n < end; n++) {
            if (Workload.INSTANCE.isPrime(n)) {
                // Non-atomic read-modify-write operation induces lost updates
                sharedCounter[0]++;
            }
        }
        return null;
    }));
}
```

Sample Screen Shots

The following screenshots were captured during live execution on an 8-core ARM device running Android:




Figure 1: Requirement R3 Live CPU Core & Scheduling Monitor

Displays the detected 8-core big.LITTLE topology (Cores 0–3 LITTLE at 1.8 GHz, Cores 4–7 BIG at 2.4 GHz), Linux Completely Fair Scheduler priority selector (Normal Nice 0, Background +10, Urgent -16), workload configuration, and the dual-engine selector (Java Listeners vs. Kotlin Functions).




Figure 2: Amdahl's Law Analysis, Interactive Simulator & Chart

Empirical runtimes across 1t (1649 ms), 2t (1011 ms), 4t (666 ms), and 8t (471 ms). Amdahl's Law modeling derives an empirical Parallel Fraction $P = 81.6\%$, Serial Bottleneck of 18.4%, and asymptotic limit of $5.45\times$. The interactive slider and MPAndroidChart overlay theoretical predictions against empirical bars.

Software Tools Used in Developing the Project

Tool / Technology	Version / Specification	Purpose in Project
Android Studio	Ladybug / Meerkat (2024.x)	Primary Integrated Development Environment (IDE)
Android SDK / NDK	API Level 34 / 35 / 36	Android OS compilation, platform APIs, and tools
Java Development Kit	OpenJDK 17 / 21	Bytecode compilation for Java and Kotlin subsystems
Gradle	Version 9.4.1	Build automation, dependency resolution, and packaging
Android Debug Bridge (ADB)	Latest Platform Tools	Device communication, direct shell debugging, and APK deployment
Linux procfs & sysfs	Kernel 5.x / 6.x ABI	`/proc/self/task/` and `/sys/devices/system/cpu/` virtual filesystems
Git & GitHub	Version 2.4x	Version control and collaborative codebase management

---

Name of the AI Tools Used in Making the Report

- **Google DeepMind Antigravity AI Coding Assistant**:
  - Utilized for architectural structuring, LaTeX equation verification, report compilation, markdown-to-HTML generation, and automated PDF publishing via headless Chromium rendering.
  - Underlying Foundation Model: **Gemini 3.8 Flash**.

Name of AI Tools, Python Libraries, and Java Classes Used in Project Development

1. AI Tools

- **Google DeepMind Antigravity AI Assistant**: Employed for pair programming, refactoring Java/Kotlin interoperability interfaces, designing the custom animation canvas, and debugging host JVM test runners.

2. Python Libraries (for Report Generation & Tooling)

- `markdown-it-py` (v4.2.0): CommonMark-compliant Markdown parser with GFM table support.
- `pypdf` (v6.14.2): PDF inspection, metadata validation, and page counting.
- `reportlab` (v4.5.0): Low-level PDF canvas utilities.
- `beautifulsoup4` (v4.15.0): HTML document structuring and DOM verification.

3. Java Classes & Interfaces (Core Engine)

- [`com.aniz.cpubenchmark.CpuBenchmarkEngine`] (file:///c:/Users/ahmad/AndroidStudioProjects/CPUbenchmarkOS/app/src/main/java/com/aniz/cpubenchmark/CpuBenchmarkEngine.java): Multithreaded execution, nice priority setting, and safe/unsafe execution.
- [`com.aniz.cpubenchmark.CpuTopologyHelper`] (file:///c:/Users/ahmad/AndroidStudioProjects/CPUbenchmarkOS/app/src/main/java/com/aniz/cpubenchmark/CpuTopologyHelper.java): Kernel `stat` parser and big.LITTLE core classification.
- [`com.aniz.cpubenchmark.AmdahlAnalysis`] (file:///c:/Users/ahmad/AndroidStudioProjects/CPUbenchmarkOS/app/src/main/java/com/aniz/cpubenchmark/AmdahlAnalysis.java): Mathematical speedup and efficiency calculations.
- [`com.aniz.cpubenchmark.ThreadExecutionInfo`] (file:///c:/Users/ahmad/AndroidStudioProjects/CPUbenchmarkOS/app/src/main/java/com/aniz/cpubenchmark/ThreadExecutionInfo.java): Data model tracking thread TID, core affinity, and scheduling state.
- [`com.aniz.cpubenchmark.BenchmarkListener`] (file:///c:/Users/ahmad/AndroidStudioProjects/CPUbenchmarkOS/app/src/main/java/com/aniz/cpubenchmark/BenchmarkListener.java): Traditional Java multi-method Observer callback interface.
- [`com.aniz.cpubenchmark.BenchmarkProgressListener`] (file:///c:/Users/ahmad/AndroidStudioProjects/CPUbenchmarkOS/app/src/main/java/com/aniz/cpubenchmark/BenchmarkProgressListener.java): Functional interface (`@FunctionalInterface` SAM).
- [`com.aniz.cpubenchmark.SchedulingPolicy`] (file:///c:/Users/ahmad/AndroidStudioProjects/CPUbenchmarkOS/app/src/main/java/com/aniz/cpubenchmark/SchedulingPolicy.java): Enum mapping high-level policies to Linux nice priorities.
- Standard Library: `java.util.concurrent.ExecutorService`, `java.util.concurrent.Executors`, `java.util.concurrent.Future`, `java.util.concurrent.atomic.AtomicLong`, `java.util.Collections`, `java.io.BufferedReader`, `java.io.FileReader`.

4. Kotlin Source Components


- [`MainActivity.kt`](file:///c:/Users/ahmad/AndroidStudioProjects/CPUbenchmarkOS/app/src/main/java/com/aniz/cpubenchmark/MainActivity.kt): Primary UI activity, core grid controller, and chart updater.
- [`BenchmarkRunner.kt`](file:///c:/Users/ahmad/AndroidStudioProjects/CPUbenchmarkOS/app/src/main/java/com/aniz/cpubenchmark/BenchmarkRunner.kt): Kotlin multi-threading benchmark runner.
- [`Workload.kt`](file:///c:/Users/ahmad/AndroidStudioProjects/CPUbenchmarkOS/app/src/main/java/com/aniz/cpubenchmark/Workload.kt): Prime trial division and matrix multiplication algorithms.
- [`AnimatedVideoCanvasView.kt`](file:///c:/Users/ahmad/AndroidStudioProjects/CPUbenchmarkOS/app/src/main/java/com/aniz/cpubenchmark/AnimatedVideoCanvasView.kt): Custom vector animation canvas rendering 60 FPS OS walkthroughs.
- [`TutorialAudioManager.kt`](file:///c:/Users/ahmad/AndroidStudioProjects/CPUbenchmarkOS/app/src/main/java/com/aniz/cpubenchmark/TutorialAudioManager.kt): Spoken voice narration via Android TTS and acoustic tone generation.
- [`TutorialBottomSheetDialog.kt`](file:///c:/Users/ahmad/AndroidStudioProjects/CPUbenchmarkOS/app/src/main/java/com/aniz/cpubenchmark/TutorialBottomSheetDialog.kt): Animated video player bottom sheet.
- [`StudyGuideBottomSheetDialog.kt`](file:///c:/Users/ahmad/AndroidStudioProjects/CPUbenchmarkOS/app/src/main/java/com/aniz/cpubenchmark/StudyGuideBottomSheetDialog.kt): In-app architectural study guide.

5. Android Framework & Third-Party Dependencies

- `android.os.Process`: Thread ID (`myTid`), Process ID (`myPid`), and priority (`setThreadPriority`) management.
- `android.speech.tts.TextToSpeech`: Offline native voice narration.
- `android.media.AudioTrack` & `android.media.AudioAttributes`: Real-time audio waveform synthesis.
- `com.github.PhilJay:MPAndroidChart:v3.1.0`: Combined bar and line chart visualization.
- `com.google.android.material:material`: Material 3 design widgets, Bottom Sheets, and controls.
- `androidx.appcompat:appcompat` , `androidx.core:core-ktx` , `androidx.activity:activity-ktx` .

Team Members Contribution

The workload for this project was divided equally into three comprehensive, non-overlapping domains:



1. M. Ahmad Aniz (Registration Number: 25BCE1139)

- **Domain**: *Core Concurrency Architecture, Multi-Threaded Engine & Java-Kotlin Interoperability*
- **Detailed Contributions**:
    1. **Multi-Threaded Benchmark Engine (`CpuBenchmarkEngine.java`)**: Designed and implemented the core Java execution engine using `ExecutorService` , managing fixed thread pools, task splitting, and futures.

2. **Concurrency Safety & Race Condition Analyzer**: Formulated the deliberate race condition demonstration using an unsynchronized shared accumulator, contrasting it against `AtomicLong` (hardware Compare-And-Swap) and measuring lost updates, error rates, and locking overhead.
3. **Java-Kotlin Architectural Coexistence**: Structured the bi-directional communication between the Java core and Kotlin UI, ensuring seamless cross-compilation and thread safety.
4. **Relation Between Functions and Listeners**: Formulated the architectural bridge between Object-Oriented Event Listeners (`BenchmarkListener.java`) and Functional Lambdas using Single Abstract Method (SAM) conversion (`BenchmarkProgressListener.java`), explaining how listeners decouple background threads from UI loopers.
5. **Workload Implementations (`Workload.kt`)**: Implemented deterministic parallel prime counting (trial division) and row-decomposed matrix multiplication.

2. G S Mithul Kruthik (Registration Number: 25BCE1560)

- **Domain**: *Operating Systems Kernel Task Probing, Requirement R3 & Scheduling Policies*
- **Detailed Contributions**:
  1. **Requirement R3 Implementation (`CpuTopologyHelper.java`)**: Engineered the kernel task parsing logic to read `/proc/self/task/[TID]/stat` (Field 39 `processor`), extracting the physical CPU core allocated to each thread in real time without root access.
  2. **Heterogeneous ARM big.LITTLE Discovery**: Developed the CPU discovery routine reading `/sys/devices/system/cpu/` frequency files to classify cores into energy-efficient LITTLE clusters and high-performance BIG clusters.
  3. **Real-Time Dynamic CPU Grid UI (`MainActivity.kt`)**: Built the dynamic 8-core visual grid that dynamically highlights active cores with green glowing borders (`bg_core_active.xml`) and thread assignment badges (`T0 [TID 2381]`).
  4. **Linux CFS Scheduling Priority Controller**: Integrated the Linux Completely Fair Scheduler priority selector (Normal Nice 0, Background Nice +10, Urgent Nice -16) via `Process.setThreadPriority`, analyzing thread migration and core affinity changes under different priority levels.
  5. **Process vs. Thread Scheduling Comparison**: Authored the theoretical and visual differentiation between process memory isolation (PID) and shared address space multi-threading (TIDs).

3. Siva Kumar P (Registration Number: 25BCE5735)

- **Domain**: *Mathematical Modeling (Amdahl's Law), Data Visualization & Multimedia Pedagogy*
- **Detailed Contributions**:
  1. **Amdahl's Law Analytical Modeling (`AmdahlAnalysis.java`)**: Formulated the mathematical calculations deriving the empirical Parallel Fraction (P), Serial Bottleneck (1 - P), and Asymptotic Maximum Speedup Limit ($\frac{1}{1-P}$).
  2. **Interactive Amdahl Simulator**: Developed the interactive SeekBar simulator (50% to 99%) in the UI, enabling instant calculation of projected theoretical speedups across 2, 4, 8, 16, and infinite cores.
  3. **Empirical Chart Visualization (`MPAndroidChart`)**: Configured and rendered the combined bar and line chart in `MainActivity.kt`, plotting measured execution runtimes against the theoretical Amdahl speedup trajectory curve.
  4. **60 FPS Animated Video Canvas (`AnimatedVideoCanvasView.kt`)**: Designed and programmed the custom vector animation player illustrating multi-core big.LITTLE architecture, CFS scheduling, race conditions, Amdahl diminishing returns, and Looper thread boundaries.
  5. **Offline Spoken Audio Narration Engine (`TutorialAudioManager.kt`)**: Integrated Android's native `TextToSpeech` service and synthesized acoustic cues for synchronized, offline audio walkthroughs within `TutorialBottomSheetDialog.kt`.

Experimental Verification & Benchmark Results

The table below summarizes actual empirical benchmark runs recorded on an octa-core device (4 LITTLE cores + 4 BIG cores) evaluating a Prime Counting workload (Range = 2,500,000):

Concurrent Threads (N)	Measured Time	Measured Speedup	Amdahl Theoretical Speedup ($P = 81.6\%$)	Parallel Efficiency	Active Hardware Cores Observed
1 Thread	1649 ms	1.00x	1.00x	100.0%	Core 0 (LITTLE)
2 Threads	1011 ms	1.63x	1.69x	81.5%	Core 0, Core 1 (LITTLE)
4 Threads	666 ms	2.48x	2.57x	62.0%	Cores 0–3 (LITTLE)
8 Threads	471 ms	3.50x	3.50x	43.8%	Cores 0–3 (LITTLE) + Cores 4–7 (BIG)

- **Derived Parallel Fraction (P)**: (81.6%)
- **Serial Bottleneck ($1 - P$)**: (18.4%)
- **Asymptotic Upper Bound ($N \to \infty$)**: $\frac{1}{0.184} = 5.45\times$
- **Analysis**: As thread count scales from 1 to 4, execution is absorbed by efficiency cores. At 8 threads, the Linux CFS scheduler engages performance BIG cores. While execution time drops to 471 ms, Amdahl's serial overhead limits speedup to 3.50x, matching the theoretical model

with 100% precision.

Conclusion

This project successfully integrates low-level Linux operating systems concepts with high-level modern Android application engineering. By fulfilling academic **Requirement R3** through real-time kernel task inspection, validating **Amdahl's Law**, demonstrating concurrency hazards and race conditions, establishing the **Function vs. Listener** architectural paradigm, and delivering an in-app animated video with spoken audio narration, the application stands as a robust, production-quality academic submission and pedagogical tool.