

Delete the record in the table using delete and remove

delete() Method

- **Usage:** session.delete(entity)
- **Description:** This method was used to remove a persistent instance from the datastore. The argument could be an instance associated with the receiving Session or a transient instance with an identifier associated with an existing persistent state.
- **Deprecation:** The delete() method has been deprecated since Hibernate version 6.0. It is recommended to use the remove() method instead.
- **Cascading:** This operation cascades to associated instances if the association is mapped with cascade="delete".

remove() Method

- **Usage:** session.remove(entity)
- **Description:** This method is aligned with the JPA specification and is used to remove the given entity instance from the database.
- **Cascading:** Similar to delete(), it supports cascading if configured.
- **Recommendation:** Since Hibernate 6.0, remove() is the preferred method for deleting entities.

```
package com.telusko.app;

import org.hibernate.HibernateException;
import org.hibernate.Session;
import org.hibernate.SessionFactory;
import org.hibernate.Transaction;
import org.hibernate.cfg.Configuration;

import com.telusko.model.Student;

public class LaunchDelete {
```

```

public static void main(String[] args) {
    // TODO Auto-generated method stub

    SessionFactory sessionFactory = new Configuration().configure().

addAnnotatedClass(Student.class).buildSessionFactory();
    Session session=null;
    Transaction transaction=null;
    boolean flag=false;

    try
    {
        session=sessionFactory.openSession();
        transaction=session.beginTransaction();
        Student st=new Student();
        st.setSid(3);
        st.setName("Harsh");
        st.setScity("Jaipur");
// session.persist(st);

        session.delete(st);
// session.remove(st);

        flag=true;

    }
    catch(HibernateException e)
    {
        e.printStackTrace();
    }
    catch(Exception e)
    {
        e.printStackTrace();
    }
}

```

```
    }  
    finally  
    {  
        if(flag==true)  
            transaction.commit();  
        else  
            transaction.rollback();  
  
        session.close();  
        sessionFactory.close();  
    }  
}  
  
}
```

Output:

```
mysql> select * from studenttable;  
+-----+-----+-----+  
| SID | SCITY | SNAME |  
+-----+-----+-----+  
| 3 | Jaipur | Harsh |  
+-----+-----+-----+  
1 row in set (0.00 sec)  
  
mysql> select * from studenttable;  
Empty set (0.00 sec)
```

Zero Param Constructor for Hibernate

Hibernate:

```
select
    null,
    s1_0.SNAME,
    s1_0.SCITY
from
    StudentTable s1_0
where
    s1_0.SID=?
```

Hibernate:

```
delete
from
    StudentTable
where
    SID=?
```