

13: Crud Operation with Single execute() method

- The `execute()` method in JDBC is versatile, allowing for the execution of both SELECT and non-SELECT SQL statements (such as INSERT, UPDATE, and DELETE).
- The method's return type is boolean, which indicates the type of query executed.
 - o true if a SELECT query is executed, indicating that a ResultSet is available.
 - o false if a non-SELECT query (such as INSERT, UPDATE, or DELETE) is executed, indicating that the query affected some rows.
- If the query was a SELECT, you can use the `getResultSet()` method to retrieve the ResultSet containing the query results.
- If the query was a non-SELECT, use the `getUpdateCount()` method to determine how many rows were affected by the query.

Example:

```
// String sql = "SELECT * FROM studentinfo";
String sql = "UPDATE studentinfo SET sage = 16 WHERE id = 1";

// Execute the SQL query
boolean status = statement.execute(sql);

if (status) {
    // Query was a SELECT, retrieve and process the ResultSet
    ResultSet rs = statement.getResultSet();
    while (rs.next()) {
        System.out.println(rs.getInt(1) + " " + rs.getString(2) + " " + rs.getInt(3) +
            " " + rs.getString(4));
    }
    rs.close(); // Always close the ResultSet
} else {
```

```
// Query was non-SELECT, retrieve the number of affected rows
int rows = statement.getUpdateCount();
if (rows == 0) {
    System.out.println("Operation failed!");
} else {
    System.out.println("Operation successful! Rows affected: " + rows);
}
}
```