

//print hello AliaBhatt

```
#include <stdio.h>
void main(){
    printf("Hello..! Alia Bhatt");
}
```

Output:

Hello..! Alia Bhatt

//Addition of 2 numbers

```
#include <stdio.h>
void main(){
    int a,b,sum;
    printf("Enter a & b values= ");
    scanf("%d %d",&a,&b);
    sum=a+b;
    printf("sum=%d",sum);
}
```

Output:

Enter a & b values= 4 5

sum=9

// C -Program to swap two variables using third variable

```
#include <stdio.h>
void main(){
    int a,b,temp;
    printf("Enter a & b values= ");
    scanf("%d %d",&a,&b);
    printf("\nBefore Swapping a=%d , b=%d",a,b);
    temp=a;
    a=b;
    b=temp;
    printf("\nAfter Swapping a=%d , b=%d",a,b);
}
```

output:

Enter a & b values= 3 4

Before Swapping a=3 , b=4

After Swapping a=4 , b=3

//Check entered number is even or odd

```
#include <stdio.h>
void main(){
    int num;
    printf("Enter number= ");
    scanf("%d",&num);
    if(num%2==0)
```

```

printf("\n %d is even number",num);
else
printf("\n %d is odd number",num);

}

```

output:

Enter number= 6
6 is even number

//C-Program using Quadratic equation

```

#include <stdio.h>
#include<math.h>
void main() {
    // Write C code here
    float a,b,c,d,root1,root2;
    printf("Enter a, b & c values= ");
    scanf("%f %f %f",&a,&b,&c);
    // printf("Quadratic equation is %.0fX^2+%.0fX+%.0f",a,b,c);
    d=(b*b)-(4*a*c);
    if(d>0){
        root1=-b+(sqrt(d)/(2*a));
        root2=-b-(sqrt(d)/(2*a));
        printf("\nRoots are imaginary and different root1=%.f & root2=%.f ",root1,root2);
    }
    else if(d==0){
        root1=-b/(2*a);
        root2=-b/(2*a);
        printf("\nRoots are imaginary and same root1=%.f & root2=%.f ",root1,root2);
    }
    else{ //d<0
        printf("\nRoots are imaginary");
    }
}

```

output:

Enter a, b & c values= 2 4 5
Roots are imaginary

Enter a, b & c values= 1 3 2
Roots are imaginary and different root1=-2 & root2=-4

//Print Prime number or not

```

#include <stdio.h>
void main(){
    int num,count=0;
    printf("Enter number= ");
    scanf("%d",&num);

```

```

for(int i=1;i<=num;i++){
    if(num%i==0){
        count++;
    }
}
if(count==2){
    printf("%d is a Prime number",num);
}
else{
    printf("%d is not a Prime number",num);
}

```

output:

Enter number= 7
7 is a Prime number

Enter number= 58
58 is not a Prime number

//C-Program to print prime number in given range

```

#include <stdio.h>
void main(){
    int min,max,count;
    printf("Enter minimum &maximum numbers=");
    scanf("%d %d",&min,&max);
    for(int i=min;i<=max;i++){
        count=0;
        for(int j=1;j<=i;j++){
            if(i%j==0){
                count++;
            }
        }
        if(count==2){
            printf("\n%d",i);
        }
    }
}

```

output:

Enter minimum &maximum numbers=1 10
2
3
5
7

// C- Program to check given number is Perfect or not

```
#include <stdio.h>
void main(){
    int num,sum=0;
    printf("Enter a number= ");
    scanf("%d",&num);
    printf("\ndivisors are :");
    for(int i=1;i<num;i++){ //for(int i=1;i<=num/2;i++)
        if(num%i==0){
            sum+=i;
            printf("%d ",i);
        }
    }
    if(num==sum){
        printf("\n%d is Perfect",num);
    }
    else{
        printf("\n%d is not a perfect number",num);
    }
}
```

output:

Enter a number= 496

divisors are :1 2 4 8 16 31 62 124 248

496 is Perfect number

//sum of even numbers in a given range

```
#include <stdio.h>
void main(){
    int min,max,sum=0;
    printf("Enter min & max = ");
    scanf("%d %d",&min,&max);

    for(int i=min;i<=max;i++){
        if(i%2==0){
            sum+=i;
        }
    }
    printf("Sum of Even numbers =%d",sum);
}
```

output:

Enter min & max = 1 10

Sum of Even numbers =30

//reverse a number

```
#include <stdio.h>
```

```

void main(){
    int num,rev=0,rem;
    printf("Enter number = ");
    scanf("%d",&num);
    printf("\nBefore Reverse number =%d ",num);
    while(num>0){
        rem=num%10;    //remove last digit & store in rem
        rev=rev*10+rem;
        num=num/10;
    }
    printf("\nAfter reversed = %d",rev);
}

```

output:

```

Enter number = 12345
Before Reverse number =12345
After reversed = 54321

```

// Print average and grade for given marks

```

#include <stdio.h>
void main(){
    int tel,eng,hin,maths,sc,soc,total_marks;
    float avg;
    printf("Enter tel,eng,hin,maths,sc,soc marks =\n");
    scanf("%d %d %d %d %d %d",&tel,&eng,&hin,&maths,&sc,&soc);
    total_marks=(tel+eng+hin+maths+sc+soc);
    avg=total_marks/6.0;
    printf("Total obtained marks %d/600 \naverage =%.2f \n",total_marks,avg);

    if(avg>=90 && avg<=100){
        printf("A+ Grade");
    }
    else if(avg>=80 && avg<90){
        printf("A Grade");
    }
    else if(avg>=70 && avg<80){
        printf("B Grade");
    }
    else if(avg>=60 && avg<70){
        printf("C Grade");
    }
    else if(avg>=44 && avg<60){
        printf("D Grade");
    }
    else if(avg>=0 && avg<44){
        printf("Fail");
    }
    else{
        printf("Invalid Marks");
    }
}

```

```
}
```

```
}
```

output:

Enter tel,eng,hin,maths,sc,soc marks =

45 78 98 99 80 70

Total obtained marks 470/600

average =78.33

B Grade