

CORE-RTR-01

cisco_ios · 15.7

52 PASSED	0 FAILED	0 NEEDS REVIEW
---------------------	--------------------	--------------------------

52 control result(s) across 4 framework(s). A control evaluated under two frameworks is counted once per framework.

Compliance Summary

FRAMEWORK	PASS	FAIL	REVIEW	TOTAL	SCORE	ADJUDICATED
CIS	13	0	0	13	100.0%	100.0%
NIST SP 800-53	13	0	0	13	100.0%	100.0%
DISA STIG	13	0	0	13	100.0%	100.0%
ISO/IEC 27001	13	0	0	13	100.0%	100.0%

Device Identification

Hostname	CORE-RTR-01	L11: hostname CORE-RTR-01
Vendor	cisco_ios	detected by parser selection
OS family	ios	declared by the parser
OS version	15.7	L4: version 15.7
Model	null	Hardware model is not present in a cisco ios configuration file; it requires show-command output (show version / show inventory).
Serial number	null	Serial number is not present in a cisco ios configuration file; it requires show-command output (show version / show inventory).

A configuration file does not carry the hardware serial number. Fields shown as null were not present in the ingested file and were not inferred; the evidence column names the show command that would establish them.

Source and Provenance

Source file	samples/hardened_ios.conf	
SHA-256	cb27a258c2cd2438c71dd4e563c0480c3de8dc5781a4d72854ab39d8776d007d	of the ingested bytes
Ingested	2026-08-23 19:21:29 UTC	
Status	audited	
Parser	cisco_ios v1.0.0	detection confidence 1.00
Config lines	89	

Control Results

FRAMEWORK	CONTROL	SEV	RESULT	TITLE	EVIDENCE
CIS	1.2	high	PASS	Restrict management access by source IP	L79: access-class 99 in
CIS	1.2.2	high	PASS	Restrict VTY transport to secure protocols only	L80: transport input ssh

FRAMEWORK	CONTROL	SEV	RESULT	TITLE	EVIDENCE
CIS	1.4.1, 1.4.2	high	PASS	Store privileged credential as hash and encrypt passwords	L21: enable secret 9 \$9\$Xk2mR7vQpLb3Nc\$8rTfYh1WqZd6JsEuA4iKmpNvxCbGyRt
CIS	1.5	high	PASS	Do not configure read-write SNMP communities	L61: snmp-server community Str0ng-R0-C0mmun1ty R0 99
CIS	1.5.2, 1.5.3	high	PASS	Unset default SNMP community names	L61: snmp-server community Str0ng-R0-C0mmun1ty R0 99
CIS	2.1.1.6	high	PASS	Enforce SSH protocol version 2	L28: ip ssh version 2
CIS	1.1	medium	PASS	Enforce minimum password length	L9: security passwords min-length 8
CIS	1.1.1	medium	PASS	Enable AAA Authentication	L16: aaa new-model
CIS	1.2.9	medium	PASS	Set VTY session idle timeout	L77: exec-timeout 5 0
CIS	2.1	medium	PASS	Disable HTTP management server	L32: no ip http server
CIS	2.2.2, 2.2.4	medium	PASS	Configure a logging destination	L56: logging host 10.20.30.40
CIS	2.3	medium	PASS	Configure at least one NTP server	L87: ntp server 10.20.30.41
CIS	1.6	low	PASS	Configure a login banner	L65: banner login ^C
NIST SP 800-53	no_default_snmp_community *	high	PASS	Unset default SNMP community names	L61: snmp-server community Str0ng-R0-C0mmun1ty R0 99
NIST SP 800-53	no_write_snmp_community *	high	PASS	Do not configure read-write SNMP communities	L61: snmp-server community Str0ng-R0-C0mmun1ty R0 99
NIST SP 800-53	AC-17	high	PASS	Restrict VTY transport to secure protocols only	L80: transport input ssh
NIST SP 800-53	AC-3	high	PASS	Restrict management access by source IP	L79: access-class 99 in
NIST SP 800-53	IA-5	high	PASS	Store privileged credential as hash and encrypt passwords	L21: enable secret 9 \$9\$Xk2mR7vQpLb3Nc\$8rTfYh1WqZd6JsEuA4iKmpNvxCbGyRt
NIST SP 800-53	SC-13	high	PASS	Enforce SSH protocol version 2	L28: ip ssh version 2
NIST SP 800-53	AC-12	medium	PASS	Set VTY session idle timeout	L77: exec-timeout 5 0
NIST SP 800-53	AC-2	medium	PASS	Enable AAA Authentication	L16: aaa new-model
NIST SP 800-53	AU-2	medium	PASS	Configure a logging destination	L56: logging host 10.20.30.40
NIST SP 800-53	AU-8	medium	PASS	Configure at least one NTP server	L87: ntp server 10.20.30.41
NIST SP 800-53	IA-5(1)	medium	PASS	Enforce minimum password length	L9: security passwords min-length 8
NIST SP 800-53	SC-7	medium	PASS	Disable HTTP management server	L32: no ip http server
NIST SP 800-53	AC-8	low	PASS	Configure a login banner	L65: banner login ^C
DISA STIG	management_acl *	high	PASS	Restrict management access by source IP	L79: access-class 99 in

FRAMEWORK	CONTROL	SEV	RESULT	TITLE	EVIDENCE
DISA STIG	no_default_snmp_community *	high	PASS	Unset default SNMP community names	L61: snmp-server community Str0ng-R0-C0mmunity R0 99
DISA STIG	no_write_snmp_community *	high	PASS	Do not configure read-write SNMP communities	L61: snmp-server community Str0ng-R0-C0mmunity R0 99
DISA STIG	CCI-000068	high	PASS	Enforce SSH protocol version 2	L28: ip ssh version 2
DISA STIG	CCI-000200	high	PASS	Store privileged credential as hash and encrypt passwords	L21: enable secret 9 \$9\$Xk2mR7vQpLb3Nc\$8rTfYh1WqZd6JsEuA4iKpNvxCbGyRt
DISA STIG	CCI-000366	high	PASS	Restrict VTY transport to secure protocols only	L80: transport input ssh
DISA STIG	CCI-000015	medium	PASS	Enable AAA Authentication	L16: aaa new-model
DISA STIG	CCI-000057	medium	PASS	Set VTY session idle timeout	L77: exec-timeout 5 0
DISA STIG	CCI-000130	medium	PASS	Configure a logging destination	L56: logging host 10.20.30.40
DISA STIG	CCI-000159	medium	PASS	Configure at least one NTP server	L87: ntp server 10.20.30.41
DISA STIG	CCI-000200	medium	PASS	Enforce minimum password length	L9: security passwords min-length 8
DISA STIG	CCI-000381	medium	PASS	Disable HTTP management server	L32: no ip http server
DISA STIG	CCI-000048	low	PASS	Configure a login banner	L65: banner login ^C
ISO/IEC 27001	enable_secret_encrypted *	high	PASS	Store privileged credential as hash and encrypt passwords	L21: enable secret 9 \$9\$Xk2mR7vQpLb3Nc\$8rTfYh1WqZd6JsEuA4iKpNvxCbGyRt
ISO/IEC 27001	ssh_version_2 *	high	PASS	Enforce SSH protocol version 2	L28: ip ssh version 2
ISO/IEC 27001	management_acl *	high	PASS	Restrict management access by source IP	L79: access-class 99 in
ISO/IEC 27001	no_default_snmp_community *	high	PASS	Unset default SNMP community names	L61: snmp-server community Str0ng-R0-C0mmunity R0 99
ISO/IEC 27001	no_write_snmp_community *	high	PASS	Do not configure read-write SNMP communities	L61: snmp-server community Str0ng-R0-C0mmunity R0 99
ISO/IEC 27001	A.8.20	high	PASS	Restrict VTY transport to secure protocols only	L80: transport input ssh
ISO/IEC 27001	ntp_configured *	medium	PASS	Configure at least one NTP server	L87: ntp server 10.20.30.41
ISO/IEC 27001	http_server_disabled *	medium	PASS	Disable HTTP management server	L32: no ip http server
ISO/IEC 27001	A.5.17	medium	PASS	Enforce minimum password length	L9: security passwords min-length 8
ISO/IEC 27001	A.8.10	medium	PASS	Configure a logging destination	L56: logging host 10.20.30.40
ISO/IEC 27001	A.8.19	medium	PASS	Set VTY session idle timeout	L77: exec-timeout 5 0
ISO/IEC 27001	A.8.2	medium	PASS	Enable AAA Authentication	L16: aaa new-model
ISO/IEC 27001	login_banner *	low	PASS	Configure a login banner	L65: banner login ^C

* Internal semantic mapping, not an official framework clause number. The control intent is the framework's; the identifier is this tool's, because the clause could not be verified against a licensed copy of the benchmark.

Findings

No findings: every evaluated control passed on this device.

Notes

- NEEDS_REVIEW means the configuration carried no conclusive evidence either way. It is not a pass, and it is not a failure: it is an escalation to a human.
- Every line number cited above refers to the ingested configuration file identified under Source and Provenance.
- No hardware serial number was available for this device. Supply the output of the vendor's show-version command alongside the configuration to record one.