



Sir C.R.Reddy (A) College

Aided & Autonomous

ELURU-534 007, W.G.DIST. A.P., INDIA

Affiliated to Adikavi Nannaya University, Rajamahendravaram

***THRICE ACCREDITED AT 'A' LEVEL BY NAAC, BANGALURU :: COLLEGE WITH POTENTIAL FOR EXCELLENCE
An ISO 9001:2015 Certified Institution***

Core JAVA

Siva Krishna Siripurapu

Siripurapusivakrishna29@gmail.com

Department of Computer Science



JAVA - INTERFACES

An interface is a reference type in Java. It is similar to class. It is a collection of abstract methods. A class implements an interface, thereby inheriting the abstract methods of the interface.

Along with abstract methods, an interface may also contain constants, default methods, static methods, and nested types. Method bodies exist only for default methods and static methods.

Writing an interface is similar to writing a class. But a class describes the attributes and behaviours of an object. And an interface contains behaviours that a class implements.

Unless the class that implements the interface is abstract, all the methods of the interface need to be defined in the class.



JAVA - INTERFACES

An interface is similar to a class in the following ways –

- An interface can contain any number of methods.
- An interface is written in a file with a .java extension, with the name of the interface matching the name of the file.
- The byte code of an interface appears in a .class file.
- Interfaces appear in packages, and their corresponding bytecode file must be in a directory structure that matches the package name.



JAVA - INTERFACES

However, an interface is different from a class in several ways, including –

- You cannot instantiate an interface.
- An interface does not contain any constructors.
- All of the methods in an interface are abstract.
- An interface cannot contain instance fields. The only fields that can appear in an interface must be declared both static and final.
- An interface is not extended by a class; it is implemented by a class.
- An interface can extend multiple interfaces.



JAVA - INTERFACES

Declaring Interfaces

The **interface** keyword is used to declare an interface. Here is a simple example to declare an interface

```
/* File name : NameOfInterface.java */
import java.lang.*;
// Any number of import statements

public interface NameOfInterface {
    // Any number of final, static fields
    // Any number of abstract method declarations\
}
```

Interfaces have the following properties –

- An interface is implicitly abstract. You do not need to use the **abstract** keyword while declaring an interface.



JAVA - INTERFACES

Interfaces have the following properties –

- Each method in an interface is also implicitly abstract, so the abstract keyword is not needed.
- Methods in an interface are implicitly public.

Example :

```
/* File name : Animal.java */  
interface Animal {  
    public void eat();  
    public void travel();  
}
```




JAVA - INTERFACES

Implementing Interfaces

When a class implements an interface, you can think of the class as signing a contract, agreeing to perform the specific behaviours of the interface. If a class does not perform all the behaviours of the interface, the class must declare itself as abstract.

A class uses the implements keyword to implement an interface. The implements keyword appears in the class declaration following the extends portion of the declaration.



JAVA - INTERFACES

```
/* File name : MammalInt.java */
public class MammalInt implements Animal {

    public void eat() {
        System.out.println("Mammal eats");
    }

    public void travel() {
        System.out.println("Mammal travels");
    }

    public int noOfLegs() {
        return 0;
    }

    public static void main(String args[]) {
        MammalInt m = new MammalInt();
        m.eat();
        m.travel();
    }
}
```

Output - Mammal eats
Mammal travels



JAVA - INTERFACES

When overriding methods defined in interfaces, there are several rules to be followed –

- Checked exceptions should not be declared on implementation methods other than the ones declared by the interface method or subclasses of those declared by the interface method.
- The signature of the interface method and the same return type or subtype should be maintained when overriding the methods.
- An implementation class itself can be abstract and if so, interface methods need not be implemented.

When implementing interfaces, there are several rules –

- A class can implement more than one interface at a time.
- A class can extend only one class, but implement many interfaces.
- An interface can extend another interface, in a similar way as a class can extend another class.



JAVA - INTERFACES

Extending Interfaces

An interface can extend another interface in the same way that a class can extend another class. The **extends** keyword is used to extend an interface, and the child interface inherits the methods of the parent interface.

The following Sports interface is extended by Hockey and Football interfaces.

```
// Filename: Sports.java
public interface Sports {
    public void setHomeTeam(String name);
    public void setVisitingTeam(String name);
}

// Filename: Football.java
public interface Football extends Sports {
    public void homeTeamScored(int points);
    public void visitingTeamScored(int points);
    public void endOfQuarter(int quarter);
}
```

```
// Filename: Hockey.java
public interface Hockey extends Sports {
    public void homeGoalScored();
    public void visitingGoalScored();
    public void endOfPeriod(int period);
    public void overtimePeriod(int ot);
}
```




JAVA - INTERFACES

The Hockey interface has four methods, but it inherits two from Sports; thus, a class that implements Hockey needs to implement all six methods. Similarly, a class that implements Football needs to define the three methods from Football and the two methods from Sports.

Extending Multiple Interfaces

A Java class can only extend one parent class. Multiple inheritance is not allowed. Interfaces are not classes, however, and an interface can extend more than one parent interface.

The extends keyword is used once, and the parent interfaces are declared in a comma-separated list.

For example, if the Hockey interface extended both Sports and Event, it would be declared as –



JAVA - INTERFACES

Example `public interface Hockey extends Sports, Event`

Tagging Interfaces

The most common use of extending interfaces occurs when the parent interface does not contain any methods. For example, the `MouseListener` interface in the `java.awt.event` package extended `java.util.EventListener`, which is defined as –

Example

```
package java.util;
public interface EventListener
{}
```

An interface with no methods in it is referred to as a tagging interface. There are two basic design purposes of tagging interfaces –



JAVA - INTERFACES

Creates a common parent –

As with the `EventListener` interface, which is extended by dozens of other interfaces in the Java API, you can use a tagging interface to create a common parent among a group of interfaces. For example, when an interface extends `EventListener`, the JVM knows that this particular interface is going to be used in an event delegation scenario.

Adds a data type to a class –

This situation is where the term, tagging comes from. A class that implements a tagging interface does not need to define any methods (since the interface does not have any), but the class becomes an interface type through polymorphism.

Thank You !