

Design Patterns and Principles

Exercise 1: Implementing the Singleton Pattern

```
class Logger {  
  
    private static Logger instance;  
  
    private Logger() {  
        System.out.println("Initialized Logger");  
    }  
    public static Logger getInstance() {  
        if (instance == null) {  
            instance = new Logger();  
        }  
        return instance;  
    }  
  
    public void log(String message) {  
        System.out.println("Log message: " + message);  
    }  
}  
  
public class Singleton {  
  
    public static void main(String[] args) {  
        Logger logger1 = Logger.getInstance();  
        logger1.log("First log message");  
  
        Logger logger2 = Logger.getInstance();  
        logger2.log("Second log message");  
  
        if (logger1 == logger2) {  
            System.out.println("Singleton present");  
        } else {  
            System.out.println("Different instances");  
        }  
    }  
}
```

Output:

```
Initialized Logger  
Log message: First log message  
Log message: Second log message  
Singleton present
```

Exercise 2: Implementing the Factory Method Pattern

```
interface Document {
    void open();
}

class WordDocument implements Document {
    public void open() {
        System.out.println("Opening a Word");
    }
}

class PdfDocument implements Document {
    public void open() {
        System.out.println("Opening a PDF");
    }
}

class ExcelDocument implements Document {
    public void open() {
        System.out.println("Opening an Excel");
    }
}

abstract class DocumentFactory {
    public abstract Document createDocument();
}

class WordDocumentFactory extends DocumentFactory {
    public Document createDocument() {
        return new WordDocument();
    }
}

class PdfDocumentFactory extends DocumentFactory {
    public Document createDocument() {
        return new PdfDocument();
    }
}

class ExcelDocumentFactory extends DocumentFactory {
    public Document createDocument() {
        return new ExcelDocument();
    }
}


public class FileFactoryMethod{
    public static void main(String[] args) {
```

```
DocumentFactory wordFactory = new WordDocumentFactory();
Document wordDoc = wordFactory.createDocument();
wordDoc.open();

DocumentFactory pdfFactory = new PdfDocumentFactory();
Document pdfDoc = pdfFactory.createDocument();
pdfDoc.open();

DocumentFactory excelFactory = new ExcelDocumentFactory();
Document excelDoc = excelFactory.createDocument();
excelDoc.open();
}
}
```

Output:



```
Opening a Word
Opening a PDF
Opening an Excel
```

Algorithms and Data Structures

Exercise 2: E-commerce Platform Search Function

```
import java.util.Arrays;
import java.util.Comparator;

class Product {
    int productId;
    String productName;
    String category;

    public Product(int productId, String productName, String category) {
        this.productId = productId;
        this.productName = productName;
        this.category = category;
    }

    @Override
    public String toString() {
        return "[" + productId + ", " + productName + ", " + category + "]";
    }
}

public class ECommerceSearch {

    public static Product linearSearch(Product[] products, String name) {
        for (Product p : products) {
            if (p.productName.equalsIgnoreCase(name)) {
                return p;
            }
        }
        return null;
    }

    public static Product binarySearch(Product[] products, String name) {
        int low = 0, high = products.length - 1;

        while (low <= high) {
            int mid = (low + high) / 2;
            int compare = products[mid].productName.compareToIgnoreCase(name);

            if (compare == 0) return products[mid];
            else if (compare < 0) low = mid + 1;
            else high = mid - 1;
        }
        return null;
    }

    public static void main(String[] args) {
        Product[] products = {
```

```

        new Product(101, "Carrot", "Vegetable"),
        new Product(102, "Milk", "Dairy"),
        new Product(103, "Grape", "Fruit"),
        new Product(104, "Cheese", "Dairy"),
        new Product(105, "Lays", "Snack")
    };

    System.out.print("Linear Search: ");
    Product result1 = linearSearch(products, "Milk");
    System.out.println(result1 != null ? result1 : "Product not found.");

    Arrays.sort(products, Comparator.comparing(p -> p.productName.toLowerCase()));

    System.out.print("Binary Search: ");
    Product result2 = binarySearch(products, "Milk");
    System.out.println(result2 != null ? result2 : "Product not found.");
}
}

```

Output:

```

Linear Search: [102, Milk, Dairy]
Binary Search: [102, Milk, Dairy]

```

Exercise 7: Financial Forecasting

```
public class FinancialForecasting {  
  
    public static double futureValue(double principal, double rate, int years) {  
        if (years == 0) {  
            return principal;  
        } else {  
            return futureValue(principal, rate, years - 1) * (1 + rate);  
        }  
    }  
  
    public static void main(String[] args) {  
        double initialAmount = 50000;  
        double growthRate = 0.12;  
        int years = 7;  
  
        double recursiveResult = futureValue(initialAmount, growthRate, years);  
  
        System.out.printf("Future value after %d years is %.2f%n", years, recursiveResult);  
    }  
}
```

Output:

```
Future value after 7 years is 110534.07
```