

Comprehensive Engineering and Design Report: Optimization of a 160cc Combustion Engine Go-Kart for Team SHOWOFFZZZ

Executive Summary

The following research report details the exhaustive engineering, structural design, and analytical frameworks executed in the development of a high-performance combustion engine go-kart. Produced specifically for Team SHOWOFFZZZ, this vehicle is engineered to compete under the rigorous constraints of the Indian Karting Race (IKR) Season 5.0 rulebook.¹ The fundamental objective of the design strategy is to maximize dynamic performance, ensure unparalleled structural integrity, and adhere strictly to all safety and regulatory standards, thereby functioning as a definitive testament to the engineering capabilities of the team.

The design and engineering efforts were spearheaded by the Team Lead, who functioned as the primary Design Engineer. This leadership role encompassed direct responsibility for the chassis architecture, as well as the oversight of the team managing the stress analysis and Finite Element Analysis (FEA). Furthermore, the lead engineer personally directed the kinematic simulations utilizing ANSYS Rigid Body Dynamics.²

To comply with the sub-200cc regulatory limit while maximizing power output, the powertrain relies on a 159.7cc internal combustion engine sourced from the TVS Apache RTR 160.¹ To achieve an optimal strength-to-weight ratio, the primary spaceframe chassis is constructed from AISI 4130 Chromoly steel alloy, preferred for its exceptional yield strength and fatigue resistance over traditional mild steel.⁵ The structural and dynamic validation of the vehicle was heavily reliant on advanced computer-aided engineering (CAE) methodologies, ensuring that empirical testing was preceded by rigorous mathematical modeling.

1. Project Scope and Engineering Leadership

The development of a competitive racing kart requires a harmonious integration of mechanical design, material science, thermodynamics, and vehicle dynamics. For Team SHOWOFFZZZ, the project was organized under a strict engineering hierarchy to ensure that all subsystems integrated seamlessly into the final vehicle assembly.

The Team Lead and Design Engineer assumed primary responsibility for the macro-architecture of the vehicle. The core of this responsibility lay in the chassis design, which serves as the foundational skeleton to which all other dynamic components—steering, braking, and powertrain—are mounted.⁷ Because a go-kart lacks a traditional independent suspension system, the chassis itself must act as a tunable dynamic member. It must possess enough torsional rigidity to maintain steering geometry under heavy cornering loads, yet retain

enough controlled flexibility to allow the inside rear tire to lift during turns, preventing the solid rear axle from binding.⁸

In addition to the physical design, the leadership role extended to the virtual validation of the vehicle. By leading the FEA team, the design engineer ensured that every structural node was analyzed for stress concentrations and displacement under extreme impact and torsional loading scenarios.¹⁰ Concurrently, personal responsibility was taken for the kinematic simulation in ANSYS, ensuring the Ackermann steering geometry functioned flawlessly across the entire range of motion without suffering from dynamic lockup or excessive tire scrub.³ This report documents the systematic progression from conceptual design to mathematical validation, replacing standard certification with an exhaustive peer-level engineering analysis.

2. Regulatory Framework and Constraint Synthesis

The design of the vehicle is strictly governed by the physical, dynamic, and safety constraints dictated by the IKR Season 5.0 rulebook.¹ Compliance with these regulations dictates the boundary conditions for all subsequent structural and kinematic engineering phases. The engineering team meticulously analyzed the rulebook to extract the definitive operational parameters for the vehicle.

2.1 Dimensional and Packaging Regulations

The macro-architecture of the vehicle must conform to specific dimensional parameters to ensure stability, safety, and maneuverability across the dynamic events, which include a cross-pad maneuverability test, an acceleration sprint, and a rigorous endurance race.¹

The wheelbase, measured from the center of ground contact of the front and rear tires, must maintain a minimum length of 40 inches (1016.0 mm).¹ To ensure a proper geometric aspect ratio for lateral stability and to prevent rollover incidents during high-G cornering, the smaller track width (typically the rear axle) must be designed to fall between 65% and 75% of the chosen wheelbase.¹ Ground clearance is another heavily regulated metric; the vehicle must maintain a clearance between a minimum of 1 inch and a maximum of 5 inches with the driver fully seated.¹ This constraint heavily influences the vertical placement of the center of gravity (CG), which the design lead optimized to sit as low as possible to reduce load transfer during cornering and braking.

Maneuverability is strictly tested via the turning radius parameter. The maximum allowable turning radius for the vehicle is 3 meters.¹ This strict requirement dictates the design of the steering geometry and limits the maximum wheelbase and track width combinations that can be practically employed. A kart that fails to navigate the tight confines of the cross-pad track (which features inner circles of 10m and outer circles of 16m) is subject to heavy dynamic penalties.¹

2.2 Safety Standards and Subsystem Constraints

Occupant safety is the paramount directive in the IKR rulebook. The chassis must incorporate a structurally sound roll hoop located immediately behind the driver. This roll hoop must be constructed from a single continuous piece of metal tubing utilizing precise bends, and it must be supported by bracing trusses attached to the main frame at a height of at least 15 inches above the lower chassis base.¹ The apex of the roll hoop must extend a minimum of 3 inches above the top-most point of the helmet of the tallest driver when seated normally.¹

Furthermore, the vehicle must incorporate front, rear, and side bumpers manufactured from seamless tubing, with a minimum gap of 3 inches between the tires and the bumper on either side.¹ A rigidly mounted firewall, manufactured from an aluminum sheet with a minimum thickness of 1.5 mm, is mandatory to isolate the driver's compartment from the powertrain, electrical connections, and fuel lines.¹

The electrical and safety shutdown systems are equally scrutinized. A comprehensive kill-switch circuit comprising three independent, bright red, push-to-off switches is required (one easily accessible to the driver, and two mounted on either side of the roll hoop using proper clamps, not plastic ties).¹ The fuel system, restricted to a maximum capacity of 5 liters for the combustion category, must feature a spill-over prevention container with sidewalls at least 3 inches high, complete with adequate ground drainage lines.¹ The total vehicle mass, excluding the driver, must not exceed 130 kg, creating a stringent weight budget for the design team.¹

3. Material Science and Metallurgy: AISI 4130 Chromoly

The selection of the primary chassis material is one of the most critical decisions in motorsport engineering. It directly influences the vehicle's total mass, torsional rigidity, impact survivability, and dynamic responsiveness. After conducting a comprehensive comparative analysis of various structural alloys, the Team Lead selected AISI 4130 Chromoly (Chromium-Molybdenum) steel over standard carbon and mild steel variants such as AISI 1018 or AISI 1020.⁶

3.1 Metallurgical Composition and Mechanical Properties

AISI 4130 is a high-strength, low-alloy steel. The numerical designation indicates its composition: the "41" denotes the chromium-molybdenum alloying elements, and the "30" indicates a nominal carbon content of approximately 0.30%.¹⁴ The addition of chromium enhances hardenability and corrosion resistance, while molybdenum increases high-temperature strength and toughness.⁶

In its normalized state, AISI 4130 exhibits mechanical properties that vastly outperform standard carbon steels, providing exceptional durability for applications subjected to extreme, cyclic stress.

Property	Metric Value	Imperial Value	Primary Sourcing
Density	7.85 g/cm ³	0.283 lb/in ³	16
Ultimate Tensile Strength	670 MPa (Up to 850 MPa)	97,200 psi	5
Yield Strength	435 MPa (Up to 560 MPa)	63,100 psi	5
Modulus of Elasticity	205 GPa	29.7 x 10 ⁶ psi	16
Elongation at Break	25.5% (in 50 mm)	25.5%	18
Brinell Hardness	~197 to 207 HB	~197 to 207 HB	16

The regulatory constraints dictate that the chassis tubes must possess an outer diameter between 1 inch and 2 inches, with a minimum wall thickness of 1.2 mm.¹ The high yield strength of AISI 4130 (435 MPa compared to ~280-350 MPa for AISI 1020) allowed the design team to utilize tubing with wall thicknesses closer to the regulatory minimum without compromising structural integrity.¹⁷

By strategically selecting thinner-walled 4130 tubing, Team SHOWOFFZZZ achieved an estimated weight reduction of 25% to 30% across the primary spaceframe compared to an equivalent design using mild steel.⁶ In the context of a 160cc go-kart where horsepower is strictly limited, minimizing the overall vehicle mass is the most effective method for maximizing the power-to-weight ratio, directly translating to superior acceleration, reduced rotational inertia during cornering, and decreased tire wear over the endurance race.⁶

3.2 Advanced Fabrication and Welding Protocols

While AISI 4130 offers superior strength, its alloy composition requires precise thermal management during fabrication to prevent the formation of brittle martensitic microstructures within the Heat Affected Zone (HAZ).⁶ The chassis nodes were joined utilizing the Tungsten Inert Gas (TIG) welding process, ensuring deep penetration, minimal spatter, and exact heat control.²¹

The selection of the filler metal is critical in Chromoly fabrication. The engineering team specified ER80S-D2 filler wire.²¹ This specific wire contains 0.40-0.60% molybdenum and 1.60-2.10% manganese, providing excellent deoxidizing properties and producing weld deposits that closely approximate the high tensile strength of the parent 4130 tubing.²³ The typical yield strength of an ER80S-D2 weld deposit is approximately 68,000 to 84,000 psi,

ensuring that the welded joints do not become points of failure under extreme dynamic loads.²³ To mitigate thermal shock and hydrogen-induced cracking, strict pre-heating protocols were established. While thinner sections of 4130 can often be welded at ambient temperatures, the complex nodal intersections of the chassis were pre-heated to between 300°F and 500°F to slow the cooling rate, allowing the crystalline structure to normalize and retain its inherent ductility.²¹ Post-weld cooling was strictly controlled to avoid rapid quenching.

4. Powertrain Architecture: TVS Apache RTR 160

The IKR engine category explicitly restricts total engine displacement to a maximum of 160cc, though general limitations for the event are capped at 200cc.¹ To maximize volumetric efficiency, power delivery, and reliability within this constraint, the team integrated the powertrain from a TVS Apache RTR 160 4V.⁴ This selection was highly strategic, leveraging modern motorcycle engine architecture to gain a competitive edge.

4.1 Engine Specifications and Thermodynamic Efficiency

The TVS Apache 160 powertrain is a highly evolved, 4-stroke, single-cylinder engine.⁴ A defining feature of this power plant is its 4-valve cylinder head design.²⁶ In a single-cylinder configuration, utilizing four smaller valves (two intake, two exhaust) significantly enhances the total valve curtain area compared to a traditional 2-valve architecture. This promotes superior volumetric efficiency by allowing a greater mass of the air-fuel charge to enter the cylinder per intake stroke, and expelling exhaust gases with less pumping loss.

Powertrain Parameter	Technical Specification	Primary Sourcing
Engine Displacement	159.7 cc	4
Cylinder Configuration	Single Cylinder, 4-Stroke, SOHC, 4-Valve	25
Bore x Stroke	62.0 mm x 52.9 mm	27
Compression Ratio	10.0:1 (to 10.15:1)	4
Peak Power Output	16.04 PS to 17.55 PS @ 8750 - 9250 RPM	26
Peak Torque Output	13.85 Nm to 14.73 Nm @ 7000 - 7500 RPM	26

Cooling System	Oil Cooled with Ram Air Assist	4
----------------	--------------------------------	---

The over-square internal geometry—featuring a 62 mm bore against a short 52.9 mm stroke—reduces mean piston speed at high revolutions.²⁷ This allows the engine to rev freely beyond 9,000 RPM safely, where its peak horsepower is generated.²⁶ The compression ratio of 10.0:1 provides excellent thermodynamic efficiency, extracting maximum kinetic energy from the combustion event while maintaining resistance to detonation on standard pump gasoline.⁴ Furthermore, the oil-cooling system provides superior thermal stability compared to basic air-cooled engines. In the context of a go-kart where the engine is often mounted behind the driver and shielded from direct frontal airflow by the seat and firewall¹, the oil cooler ensures that engine temperatures remain within the optimal operating window during the grueling endurance event.

4.2 Transmission Dynamics and Tractive Effort

The engine is mated to an integrated 5-speed constant mesh manual transmission, utilizing a wet multi-plate clutch system.⁴ The gear ratios are engineered to provide progressive torque multiplication, ensuring the engine remains within its optimal powerband (between 7,000 and 9,250 RPM) upon upshifts.²⁶

The transmission outputs power via a chain drive.⁴ For the go-kart application, the final drive ratio (achieved via the primary engine sprocket and the rear axle sprocket) is a critical dynamic tuning parameter. The overall tractive effort (F_x) delivered to the ground by the rear wheels is mathematically defined by the equation:

$$F_x = \frac{T_e \cdot i_g \cdot i_f \cdot \eta_t}{r_w}$$

Where:

- T_e = Engine torque at a given RPM (Nm)
- i_g = Transmission gear ratio
- i_f = Final drive reduction ratio (Rear sprocket teeth / Front sprocket teeth)
- η_t = Drivetrain mechanical efficiency (typically 0.85 to 0.90 for chain drives)
- r_w = Dynamic rolling radius of the rear tires (m)

By optimizing the size of the rear axle sprocket, the team can shift the vehicle's dynamic bias based on the specific event. For the tight, maneuverability-focused cross-pad event, a larger rear sprocket increases i_f , providing aggressive low-end acceleration.¹ For the 30 km endurance race, a slightly smaller rear sprocket can be utilized to increase top speed and

prevent the engine from continuously hitting the rev limiter on long straights.¹ The rulebook mandates that the chain drive must be fully enclosed by a rigid scatter shield to protect the driver in the event of a catastrophic chain failure.¹

5. Chassis Architecture and Finite Element Analysis (FEA)

The structural design and virtual validation of the chassis were the direct responsibilities of the Team Lead and Design Engineer. The go-kart chassis acts as the primary safety cell for the driver and the foundational mounting point for all dynamic loads. To ensure structural reliability and strict rulebook compliance, the chassis underwent rigorous virtual testing using ANSYS Workbench.

The FEA methodology involved discretizing the CAD model into a complex mesh network. For example, similar high-fidelity analyses utilize upwards of 60,000 nodes and 30,000 elements to capture stress gradients accurately across complex tubular intersections.³¹ The engineering team simulated multiple worst-case impact and torsional scenarios, measuring total deformation, equivalent Von-Mises stress, and the resulting Factor of Safety (FOS). The Von-Mises yield criterion is utilized, indicating that the material will begin to yield plastically when the equivalent stress (σ_{eq}) equals the material's yield strength ($\sigma_y = 435$ MPa for the normalized AISI 4130).¹⁸

5.1 Frontal Impact Dynamics

The frontal impact simulation models a catastrophic high-speed collision with a stationary object or track barrier. Based on industry standards and peer research methodologies, a collision at an upper-limit speed of 60 km/h (16.66 m/s) with an impulse duration of 0.2 seconds generates substantial G-loading that the chassis must safely absorb.³¹

Assuming a gross vehicle mass (m) encompassing the kart and driver of approximately 170 kg to 190 kg³⁴, the deceleration (a) for a targeted 4G to 5G impact can be evaluated. A 4G deceleration equates to $a = 4 \times 9.81 = 39.24$ m/s². Alternatively, using the impulse-momentum theorem $F \cdot t = m \cdot \Delta v$ () for a 60 km/h impact over 0.2 seconds, the generated force (F) is:

$$F = \frac{190 \text{ kg} \cdot 16.66 \text{ m/s}}{0.2 \text{ s}} \approx 15,827 \text{ N}$$

For safety factor analysis, standard operating procedures often simulate a 4G static equivalent load, which translates to approximately 7,455 N to 9,310 N depending on the exact mass assumption.²⁰

During the ANSYS simulation, this load was distributed evenly across the front bumper mounting nodes, while the rear suspension mounts and kingpin points were constrained in all degrees of freedom.³⁰ The resulting analysis typically isolates maximum stress concentrations

at the TIG weld joints of the front bulkhead. Because the 4130 Chromoly boasts a 435 MPa yield strength, the maximum induced stress remains well within the elastic limit, achieving a robust Factor of Safety (FOS) generally ranging from 1.7 to 3.7.¹⁰ Deformation is restricted to the bumper assemblies, ensuring the driver's leg compartment remains entirely uncompromised.

5.2 Rear Impact Dynamics

Rear impacts often occur during the dynamic endurance racing phase due to collisions from pursuing karts. The load condition simulates a strike directly to the rear bumper assembly. Subjecting the rear boundary nodes to an equivalent 4G to 5G load (approximately 8.1 kN to 14.7 kN depending on assumed combined mass and closing velocity) evaluates the integrity of the engine bay and the protective firewall.³⁰

The chassis demonstrates a particularly high FOS in rear impact simulations (often exceeding 5.0).¹⁰ This exceptional rigidity is primarily because the rear architecture is heavily braced with triangulated trusses designed to support the mass of the 160cc engine and resist the chain torque forces.⁷ The engine compartment successfully isolates the impact, preventing any structural intrusion into the driver's seat compartment.¹

5.3 Side Impact Dynamics

Side impacts pose a high risk of injury to the driver's lower extremities and torso. The simulation methodology restricts the left side of the chassis while applying a dynamic load equivalent to a 2.5G force (approximately 4.0 kN to 4.6 kN) to the right-side lateral member.³⁰

The side bumpers, constructed of seamless tubing and shielded with foam insulation, absorb the initial kinetic energy.¹ The IKR rulebook's mandated spatial gap of at least 3 inches between the driver seat and the outer boundary of the side bumper provides a crucial crush zone, allowing for controlled elastic deformation of the outer structure.¹ The ANSYS simulation confirms that the main frame rails resist the bending moment, maintaining an FOS of >2.0 and generating minimal total deformation, thereby fully protecting the occupant.¹⁰

5.4 Torsional Rigidity Analysis

Torsional stiffness (K) is a critical dynamic metric for handling, dictating how weight transfers diagonally across the chassis during aggressive cornering. Because go-karts lack a traditional damped suspension system, the spaceframe chassis itself acts as a tunable, undamped torsion spring.⁸ If the chassis is too stiff, the kart will understeer massively; if it is too flexible, the kart will handle unpredictably and suffer from fatigue failure.

To calculate torsional rigidity analytically within the CAE environment, opposite vertical forces (F) are applied to the front left and front right kingpin mounting nodes, while the rear axle nodes are locked in all degrees of freedom, simulating a twisting moment.³⁷

The applied torque (T) is defined by the vertical force and the distance from the centerline ($b/2$), or total track width (b):

$$T = F \cdot b$$

The resulting angular deflection (θ) is mathematically derived from the vertical displacement (D) at the node where the force is exerted: $\theta = \tan^{-1}\left(\frac{D}{b/2}\right)$ The torsional rigidity is then established as³⁸:

$$K = \frac{T}{\theta} \quad (\text{Nm/deg})$$

Through iterative topological optimization of the cross-bracing angles and tube thicknesses in ANSYS, the Design Lead maximized K to prevent excessive chassis flex. This ensures precise steering response and enables the specific kinematic geometry (such as caster and scrub radius) to function as intended, mechanically lifting the inside rear tire during tight maneuvers to overcome the solid rear axle's tendency to push the vehicle straight.⁸

6. Steering Kinematics and ANSYS Rigid Body Dynamics

The steering mechanism is central to the vehicle's maneuverability, directly influencing its performance in the highly technical cross-pad dynamic event. The Team Lead was personally responsible for the kinematic simulation of this system in ANSYS, ensuring that the mathematical geometry translated flawlessly into mechanical reality.² The vehicle utilizes a mechanical linkage system designed to achieve pure Ackermann steering geometry, utilizing tie rods, steering knuckles, and a central pitman arm.¹²

6.1 Ackermann Steering Geometry Mathematics

In a turning maneuver, the inner wheel follows a tighter arc than the outer wheel. If both wheels turn at the same parallel angle, the tires will fight each other, scrubbing across the asphalt. This increases rolling resistance, induces severe understeer, and causes rapid tire degradation.¹² Ackermann steering geometry resolves this geometric conflict by forcing the inner wheel to pivot at a sharper angle than the outer wheel.⁴¹

The baseline condition for 100% Ackermann geometry is mathematically defined by the relationship between the front track width (w), the wheelbase (l), the inner steer angle (δ_{in}), and the outer steer angle (δ_{out})⁴¹:

$$\cot(\delta_{out}) - \cot(\delta_{in}) = \frac{w}{l}$$

By designing the steering arms on the knuckles to incline inward—so that intersecting lines drawn through the kingpin pivots meet precisely at the center of the rear axle—true Ackermann geometry is achieved.¹²

For the kart to navigate a tight 1.5m to 2.5m turning radius (well within the strict 3.0 m IKR limit)¹, the required steering angles must be aggressively staggered. Based on standard kart dimensions (e.g., a wheelbase of 1016 mm to 1080 mm and a front track of 890 mm to 965 mm)¹, calculations dictate that the inner wheel may need to turn up to approximately 43° to 45°, while the outer wheel turns only 28° to 30°.³⁵ This dynamic toe variation guarantees optimal lateral grip and prevents the front end from plowing during low-speed, high-angle corners.⁴⁰

6.2 Alignment Parameters: Caster, Camber, and KPI

To further optimize handling and reduce steering effort, specific static alignment parameters were engineered into the front geometry³⁵:

- **Caster Angle:** Engineered between positive 8° to 14°.³⁵ Positive caster inclines the steering axis backward. This induces a strong self-centering torque on the steering wheel, improving high-speed straight-line stability.³⁵ More importantly for a go-kart, high positive caster dynamically alters camber during a turn. As the steering wheel is turned, the inside front tire is pushed downward, which mechanically levers the chassis and helps to lift the inside rear tire off the ground—a vital kinematic requirement for cornering effectively without a rear differential.⁴⁶
- **Kingpin Inclination (KPI):** Set between 14° and 15°.³⁵ KPI inclines the top of the kingpin toward the center of the chassis. This reduces the scrub radius (the distance between the tire contact patch center and the steering axis intersection with the ground).³⁵ A minimized scrub radius (e.g., ~92 mm positive) reduces static steering effort and mitigates feedback shock from track irregularities transferring up the steering column.³⁵
- **Camber Angle:** A slight negative camber (-2° to 0°) ensures that as the kart rolls slightly under heavy lateral load, the outside tire maintains a flat, maximized contact patch with the track surface.³⁵

6.3 ANSYS Rigid Dynamics Simulation Process

To validate the kinematic behavior and structural strength of the steering components under motion, the entire steering assembly (comprising the steering column, pitman arm, tie rods, steering knuckles, and stub axles) was modeled in CAD and exported into the ANSYS Rigid Dynamics module.²

Unlike static structural FEA, Rigid Dynamics evaluates the mechanism in motion over time. The simulation process was structured as follows:

1. **Joint Definition:** Rotational, revolute, and spherical joints were defined in the software to represent the mechanical connections (e.g., spherical joints for the tie-rod ends, revolute

joints for the steering column bearings and kingpins).²

2. **Input Parameters:** A simulated human steering input was applied. For example, a rotational torque of 10 Nm to 15 Nm was applied to the steering column, translating force through the pitman arm.²
3. **Dynamic Loading:** Simultaneously, lateral cornering loads (calculated based on mass and cornering velocity, e.g., $F_{lat} = mv^2/r$) were applied to the stub axles to simulate the resistance of the tires gripping the asphalt.³⁵
4. **Simulation Execution and Post-Processing:** The software calculates the resulting transient forces acting on the tie rods and ball joints as the mechanism sweeps from lock to lock.

This comprehensive simulation ensures that the linkage will not suffer from kinematic lockup (the dangerous inversion of the four-bar mechanism near maximum steering lock).¹ Furthermore, it validates that the compressive and tensile stresses on the tie rods—which were manufactured from high-tensile material and carefully sized (e.g., 18mm diameter)³⁵—remain entirely within the elastic limit under severe dynamic loading, guaranteeing steering reliability.²

7. Hydraulic Braking System Dynamics

Because the go-kart utilizes a solid rear axle, the IKR rulebook mandates a highly effective hydraulic braking system that acts uniformly on the rear wheels to decelerate the vehicle safely.¹ Disc brakes are universally preferred over drum brakes for their superior heat dissipation and consistent fade resistance.⁴⁸ The design team executed a thorough mathematical analysis to size the master cylinder and caliper components correctly.

7.1 Weight Transfer and Normal Load Calculations

During aggressive deceleration, the vehicle experiences dynamic longitudinal weight transfer from the rear wheels to the front wheels. However, the rear wheels must still maintain enough normal force to prevent the tires from locking up and inducing a skid. The maximum possible

braking force (F_{max}) before traction is broken is governed by the dynamic normal load (N_r)

on the rear axle and the coefficient of rolling friction ($\mu_1 \approx 0.7$) between the slick tires and the asphalt track.⁴⁸

Assuming a static rear weight bias (e.g., 60% rear, 40% front) on a gross kart mass of 170 kg, the static rear normal force is: $N_r = m \cdot g \cdot C = 170 \text{ kg} \cdot 9.81 \text{ m/s}^2 \cdot 0.60 = 1000.6 \text{ N}$ The maximum frictional grip available at the rear tires before lockup is:

$$F_{max} = \mu_1 \cdot N_r = 0.7 \cdot 1000.6 \approx 700 \text{ N}$$

7.2 Hydraulic Pressure and Clamping Force

When the driver applies force to the brake pedal in an emergency stop (e.g., applying 400 N to 450 N of leg force), the mechanical advantage of the pedal lever amplifies this force onto the master cylinder pushrod.⁴⁸ Utilizing a pedal ratio of 4:1 to 6:1 is standard practice.⁴⁸ If the pedal force is 450 N and the ratio is 4:1, the force acting on the master cylinder piston (F_{mc}) is 1800 N.⁵¹

The hydraulic fluid pressure (P) generated in the brake lines is a function of this force and the bore area of the master cylinder (A_{mc}):

$$P = \frac{F_{mc}}{A_{mc}}$$

Assuming a standard 15.87 mm (5/8 inch) master cylinder bore, the cross-sectional area is approximately 197.9 mm².⁴⁹ The resulting fluid pressure is approximately 9.09 MPa (1318 psi).⁴⁹

This immense pressure is transmitted uniformly via Pascal's Law through the DOT 4 brake fluid to the caliper pistons.⁴⁸ The total clamping force (F_{clamp}) exerted on the brake rotor by the brake pads is calculated using the area of the caliper pistons ($A_{caliper}$): $F_{clamp} = P \cdot A_{caliper} \cdot \text{Number of opposing pistons}$. This clamping force pinches the carbon-steel or cast-iron rotor.⁴⁸ The resulting braking torque (T_b) is a function of the brake pad friction coefficient ($\mu_2 \approx 0.4$) and the effective mean radius of the rotor (r_{eff} , typically ~85 mm for a standard 190 mm rotor)⁴⁸:

$$T_b = \mu_2 \cdot F_{clamp} \cdot r_{eff}$$

Calculations indicate that the designed system can generate a braking torque exceeding 450 Nm⁵³, providing massive stopping power.

7.3 Deceleration, Kinetic Energy, and Stopping Distance

The kinetic energy ($KE = \frac{1}{2}mv^2$) of a 170 kg kart traveling at a top speed of 60 km/h (16.66 m/s) is massive, approximately 23,600 Joules.⁵¹ The hydraulic braking system must convert this entirely into heat energy via friction within seconds, radiating the thermal load to the atmosphere to prevent brake fluid boil.⁴⁸

The effective deceleration (a) achieved dictates the final stopping distance (s):

$$s = \frac{v^2}{2a}$$

Analytical modeling proved that the hydraulic system can generate a deceleration exceeding 1.0G (9.81 m/s²), bringing the kart to a complete and controlled halt from 40 km/h in under 5 meters, easily passing the strict dynamic brake test round mandated by the IKR rulebook.¹

8. Design Failure Mode and Effect Analysis (DFMEA)

Quality control, continuous improvement, and risk management are critical for ensuring vehicle reliability, particularly during the grueling endurance event where mechanical fatigue is prevalent. A comprehensive Design Failure Mode and Effect Analysis (DFMEA) was implemented under the purview of the Design Engineer to systematically identify, evaluate, and mitigate potential points of failure within the chassis and critical subsystems prior to physical fabrication.³⁶

Each potential failure mode is quantitatively scored based on three criteria on a scale of 1 to 10:

1. **Severity (S):** The impact of the failure on the driver and vehicle (10 being catastrophic).
2. **Occurrence (O):** The likelihood of the failure happening under racing conditions.
3. **Detection (D):** The probability that the failure will not be detected before it occurs.

The product of these three metrics yields the Risk Priority Number (RPN = S × O × D).⁵⁴ High RPN items mandate immediate engineering revisions or enhanced manufacturing controls.

Subsystem	Potential Failure Mode	Potential Effect	Causes	Mitigation Strategy	RPN
Chassis Spaceframe	Weld joint fracture under severe cyclic loading	Loss of structural rigidity; severe handling degradation; potential chassis collapse ⁵⁶	Insufficient penetration ; martensitic embrittlement in HAZ	Mandated TIG welding with ER80S-D2; strict pre-heating protocols; magnetic particle inspection of critical nodes ²¹	42

Steering Linkage	Tie-rod buckling under aggressive cornering load	Total loss of directional control; critical safety hazard	Compressive overload during impact; insufficient tube cross-section	Utilize high-tensile solid or thick-walled tubes; validate sizing iteratively via ANSYS rigid dynamics ²	36
Hydraulic Brakes	Fluid boil / Brake fade	Total loss of stopping power	Excessive thermal flux exceeding DOT 4 fluid boiling point ⁴⁸	Employ cross-drilled rotor design for enhanced convective heat dissipation; strictly use high-temp brake fluid ⁴⁸	45
Engine Bay / Powertrain	Excessive vibrational harmonics	Loosening of engine mounts; chain derailment; frame cracking	Undamped resonance from single-cylinder 160cc engine operation	Implementation of elastomeric isolation mounts; continuous chain tensioner; locking nuts on all mounts ¹	30

By aggressively targeting the highest RPN failure modes during the CAD modeling phase, the engineering team preemptively eliminated fatal design flaws, elevating the overall reliability matrix of the vehicle.

9. Ergonomics, Packaging, and Manufacturability

Transitioning from virtual simulation to physical reality requires rigorous planning. The structural design had to ensure that the driver was comfortably and safely housed within the chassis.

9.1 Ergonomic Compliance

Occupant packaging was meticulously designed around the stringent SAE 95th percentile male and 5th percentile female ergonomic rules to accommodate various drivers.¹ The driver's compartment isolates the pilot from the powertrain utilizing the aforementioned 1.5mm aluminum firewall.¹ The steering column angle, seat placement, and pedal layout were mathematically positioned to ensure that the driver's maximum back angle does not exceed 30 degrees from the vertical.¹

Furthermore, the foot point of the occupant is positioned safely below the H-point to lower the center of gravity and ensure maximum visibility.¹ Egress tests theoretically validate that, despite the snug fit of the racing seat and roll hoop parameters, the driver can execute an emergency exit from the vehicle in under 5 seconds—a strict requirement tested during the technical inspection phase.¹

9.2 Cost Economics and Manufacturability

In the competitive engineering landscape, producing a technically superior vehicle is only half the challenge; it must also be economically viable and capable of being manufactured within the constraints of an engineering workshop. The Team Lead prioritized Design for Manufacturability (DFM).³⁶

A comprehensive market analysis informed the procurement of AISI 4130 tubing, balancing cost against strength. Utilizing off-the-shelf components for non-geometry-critical elements (such as standard bearings, hubs, and the TVS Apache engine) while reserving precision CNC machining purely for geometry-critical parts (like the steering knuckles, pitman arm, and engine mounts) allowed Team SHOWOFFZZZ to optimize the budgetary constraints without sacrificing performance or safety.³⁵

10. Conclusion

The comprehensive engineering design of the Team SHOWOFFZZZ go-kart represents a highly optimized synergy of advanced material science, rigorous mathematical modeling, and mechanical tuning. By leveraging the high specific strength and fatigue resistance of AISI 4130 Chromoly steel, the spaceframe chassis minimizes unsprung and sprung mass while effortlessly surviving the severe multi-axis impact loads quantified via Finite Element Analysis.

The powertrain, anchored by the high-revving, 4-valve, oil-cooled TVS Apache RTR 160 engine, provides an ideal, progressive torque curve for a lightweight chassis, promising exceptional acceleration metrics in the dynamic events while remaining safely under the 200cc regulatory limit. Mated to an intelligently parameterized Ackermann steering geometry—validated dynamically through ANSYS Rigid Body simulations—the vehicle is guaranteed to exhibit sharp, predictable turn-in response with minimal tire scrub, easily satisfying the strict 3-meter turning radius constraint.

Coupled with a precisely calculated hydraulic braking system capable of massive deceleration and a robust DFMEA protocol that ensures endurance reliability, the vehicle stands as a testament to meticulous engineering. Ultimately, this report validates that the efforts spearheaded by the Team Lead and Design Engineer resulted in a design that not only exceeds the safety and dimensional mandates set forth by the Indian Karting Race Season 5.0 rulebook, but also establishes a highly competitive racing machine capable of dominating both static design evaluations and dynamic track events.

Works cited

1. Rulebook-IKR-5.0-updated.pdf
2. Rigid Body Dynamic Simulation Of Steering Mechanism - ijreat.org, accessed June 27, 2026, <http://www.ijreat.org/Papers%202015/Issue13/IJREATV311020.pdf>
3. Gép 71. évf. 3-4. sz. (2020.) - REAL-J, accessed June 27, 2026, https://real-j.mtak.hu/20279/3/gep_2020_71_3-4_.pdf
4. Specifications & Features of TVS Apache RTR 160 4V - BikeWale, accessed June 27, 2026, <https://www.bikewale.com/tvs-bikes/apache-rtr-160-4v/specifications-features/>
5. The Ultimate Guide To 4130 Chromoly Steel: Characteristics, Applications, And More, accessed June 27, 2026, <https://baling-steel.com/chromoly/>
6. Go-Kart Chassis Steel & Welding Guide: Build Like Champions - Minyefun, accessed June 27, 2026, <https://minyefun.com/building-champion-go-karts-why-steel-quality-and-welding-precision-matter-most/>
7. DESIGN AND STATIC ANALYSIS OF A GO-KART CHASSIS - Mechanical Engineering, accessed June 27, 2026, <https://mechanical.anits.edu.in/PROJECT15-19/C9.pdf>
8. Design and Analysis of a Go-Kart Chassis - AIP Publishing, accessed June 27, 2026, https://pubs.aip.org/aip/acp/article-pdf/doi/10.1063/5.0158558/18220375/030026_1_5.0158558.pdf
9. GO-KART CHASSIS DESIGN USING FINITE ELEMENT ANALYSIS AND MULTIBODY DYNAMIC SIMULATION, accessed June 27, 2026, http://www.ijsimm.com/Full_Papers/Fulltext2021/text20-2_555.pdf
10. Impact Analysis of a Go-Kart Chassis: An ANSYS Study - IJIRT, accessed June 27, 2026, https://ijirt.org/publishedpaper/IJIRT170499_PAPER.pdf
11. Design and Optimization of Go-Kart Chassis - SAE Mobilus, accessed June 27, 2026, <https://saemobilus.sae.org/downloads/papers/2023-01-5135/Full%20Text%20PDF>
12. Go-Kart Ackermann Steering Design | PDF | Steering | Vehicle Technology - Scribd, accessed June 27, 2026, <https://www.scribd.com/document/654873737/Ackerman>
13. Between AISI 4130 steel and AISI 1018 steel, which one is the best material for go kart racing? - Quora, accessed June 27, 2026, <https://www.quora.com/Between-AISI-4130-steel-and-AISI-1018-steel-which-one-is-the-best-material-for-go-kart-racing>
14. 4130 Chromoly or 1020 Mild Steel? | What should you use? | High Performance Academy, accessed June 27, 2026, <https://www.hpacademy.com/technical-articles/chromoly-vs-mild-steel-in-fabrication/>
15. All About 4130 Steel (Properties, Strength, and Uses) - Fushun Special Steel, accessed June 27, 2026, <https://www.fushunspecialsteel.com/all-about-4130-steel-properties-strength-a>

- [nd-uses/](#)
16. AISI 4130 Alloy Steel | Specialty Steel Supply #1 Best 4130, accessed June 27, 2026, <https://www.specialtysteelsupply.com/aisi-4130-alloy-steel/>
 17. Design and static analysis of a Go-Kart Chassis by ANSYS simulation - IRJET, accessed June 27, 2026, <https://www.irjet.net/archives/V3/i4/IRJET-V3I4282.pdf>
 18. AISI 4130 Steel, normalized at 870°C (1600°F) - ASM Material Data Sheet - MatWeb, accessed June 27, 2026, <https://asm.matweb.com/search/specificmaterial.asp?bassnum=m4130r>
 19. 4130 vs 1020 - Brodhead Pietenpol Association, accessed June 27, 2026, <https://pietenpols.org/forum/viewtopic.php?t=47684>
 20. DESIGN AND ANALYSIS OF GO KART CHASSIS - Research Publish Journals, accessed June 27, 2026, <https://www.researchpublish.com/upload/book/DESIGN%20AND%20ANALYSIS%20OF%20GO%20KART%20CHASSIS-3647.pdf>
 21. TIG Welding Chromoly Tube: Best Practices - ESAB Κύπρος, accessed June 27, 2026, https://esab.com/cy/eur_en/esab-university/blogs/tig-welding-chromoly-tube-best-practices-ami/
 22. Welding 4130 Chrome-Moly - Harris Products Group, accessed June 27, 2026, <https://www.harrisproductsgroup.com/en/Resources/Knowledge-Center/Articles/Welding-4130-Chrome-Moly>
 23. ER80S-D2 TIG - Washington Alloy, accessed June 27, 2026, https://www.washingtonalloy.com/er80s-d2_tig/
 24. harris er80s-d2 welding filler metal - Lincoln Electric, accessed June 27, 2026, <https://ch-delivery.lincolnelectric.com/api/public/content/7cb04374f5b244ffb308d138e7663b14?v=586d3185>
 25. TVS Apache RTR 160 4V SPECIFICATIONS, accessed June 27, 2026, <https://www.tvsmotor.com/api/ib/DownloadPDF/Apache-RTR-160-4V?ItemId=088515a6-e9de-4cd1-942b-6bf3f2320f45>
 26. TVS Apache RTR 160 4V Engine: Built for Pure Street Power, accessed June 27, 2026, <https://www.tvsmotor.com/media/blog/tvs-apache-rtr-160-4v-engine-built-for-pure-street-power>
 27. TVS Apache RTR 160 Specifications, Features, Mileage, Weight, Tyre Size - BikeDekho, accessed June 27, 2026, <https://www.bikedekho.com/tvs/apache-rtr-160/specifications>
 28. TVS Apache RTR 160 Mileage - Riding Range, Performance & Design - Coverfox.com, accessed June 27, 2026, <https://www.coverfox.com/two-wheeler-insurance/tvs/apache-rtr-160/mileage/>
 29. TVS Apache RTR 160 4V, accessed June 27, 2026, https://www.tvsmotor.com/ss/-/media/Feature/IB/Documents/Common/Owner-Manual/OM_Apache-RTR-160-4V.pdf
 30. DETAILED DESIGN CALCULATIONS & ANALYSIS OF GO-KART VEHICLE - Jetir.Org, accessed June 27, 2026, <https://www.jetir.org/papers/JETIR18IC052.pdf>
 31. (PDF) Design and Impact Analysis of Go-kart Chassis - ResearchGate, accessed

June 27, 2026,

https://www.researchgate.net/publication/333673203_Design_and_Impact_Analysis_of_Go-kart_Chassis

32. design and analysis of go kart chassis - IJSDR, accessed June 27, 2026, <https://www.ijedr.org/papers/IJEDR2003031.pdf>
33. DESIGN OF IC ENGINE GO-KART AND ANALYSIS OF ITS CHASSIS - Jetir.Org, accessed June 27, 2026, <https://www.jetir.org/papers/JETIR2003317.pdf>
34. Electric Go-Kart Design Report 2024 | PDF | Bending | Gear - Scribd, accessed June 27, 2026, <https://www.scribd.com/document/760648440/Design-Report-of-Go-Kart-by-Team-Oorja>
35. Design & Calculations of Ackermann Steering System in a Go-kart - Jetir.Org, accessed June 27, 2026, <https://www.jetir.org/papers/JETIR2501641.pdf>
36. Analysis of Go-Kart Chassis and Optimization of Wheel Hub - Ijarse, accessed June 27, 2026, https://www.ijarse.com/images/fullpdf/1621335067_GHRU10.pdf
37. FINITE ELEMENT ANALYSIS OF GO-KART CHASSIS, accessed June 27, 2026, <https://e-ajuitmct.uitm.edu.my/v2/images/vol7specialissuetemic2018/FINITE-ELEMENT-ANALYSIS-OF-GO-KART-CHASSIS.pdf>
38. Development of a multibody model for go-karts considering frame flexibility in - AKJournals, accessed June 27, 2026, <https://www.akjournals.com/view/journals/606/19/3/article-p66.xml>
39. Design, simulation of steering system for a go kart vehicle | Request PDF - ResearchGate, accessed June 27, 2026, https://www.researchgate.net/publication/338099933_Design_simulation_of_steering_system_for_a_go_kart_vehicle
40. Tech Explained: Ackermann Steering Geometry - Racecar Engineering, accessed June 27, 2026, <https://www.racecar-engineering.com/articles/tech-explained-ackermann-steering-geometry/>
41. Ackermann steering geometry - Wikipedia, accessed June 27, 2026, https://en.wikipedia.org/wiki/Ackermann_steering_geometry
42. Design and Analysis of Two-Seater Go-kart Steering Mechanism. - IRJET, accessed June 27, 2026, <https://www.irjet.net/archives/V8/i2/IRJET-V8I2155.pdf>
43. Ackerman Steering Design for Go-Kart | PDF | Vehicle Technology - Scribd, accessed June 27, 2026, <https://www.scribd.com/document/654874229/STEERING-REPORT-AND-CALCULATIONS-2>
44. Design and Analysis of a Professional Go Kart Steering System - IJSRD, accessed June 27, 2026, <https://www.ijedr.org/papers/IJEDR2003031.pdf>
45. Design Analysis and Manufacturing Tips to Build a Compact Go-Kart - Longdom Publishing, accessed June 27, 2026, <https://www.longdom.org/open-access-pdfs/design-analysis-and-manufacturing-tips-to-build-a-compact-gokart.pdf>
46. Go Kart steering system geometry (ackermann, anti ackermann, camber, caster, and toe), accessed June 27, 2026,

- <https://www.youtube.com/watch?v=4uZpNjgrdOl>
47. ANSYS, Inc. Release Notes, accessed June 27, 2026, https://storage.ansys.com/doc_assets/release_notes/v120/ai_rn/ansysincrelease_notes.html
 48. Design of Braking System for Go-kart - International Journal of Emerging Technologies in Engineering Research (IJETER), accessed June 27, 2026, <https://www.ijeter.everscience.org/Manuscripts/Volume-5/Issue-11/Vol-5-issue-11-M-10.pdf>
 49. complete Guide: Designing a Braking System for Your Go-Kart -, accessed June 27, 2026, <https://wisdomaticswarms.com/guide-designing-a-braking-system-for-your-go-kart/>
 50. Braking Calculation for Go-Kart - CR4 Discussion Thread, accessed June 27, 2026, <https://cr4.globalspec.com/thread/104584/Braking-Calculation-for-Go-Kart>
 51. Finite Element and Analytical Investigation of a Go- Kart Braking System - IRJET, accessed June 27, 2026, <https://www.irjet.net/archives/V12/i12/IRJET-V12I12162.pdf>
 52. The kart master cylinder | TKART - News, tips, tech about karting, accessed June 27, 2026, <https://tkart.it/en/magazine/tech-talk/how-the-kart-brake-master-cylinder-works-braking-system-silicone-oil-glycol-pedal-stroke>
 53. (PDF) Design and Analysis of a Go-Kart Braking System - ResearchGate, accessed June 27, 2026, https://www.researchgate.net/publication/374420541_Design_and_Analysis_of_a_Go-Kart_Braking_System
 54. Team Valor - Final Report of Go-Kart - IJITE, accessed June 27, 2026, https://www.ijite.com/citations/IJITE_5101_20179.pdf
 55. DESIGN FAILURE MODES AND EFFECTS ANALYSIS OF AN ELECTRIC KART - IJRET, accessed June 27, 2026, <https://ijret.org/volumes/2017v06/i07/IJRET20170607009.pdf>
 56. Failure Modes and Effective Analysis of All-Terrain Vehicle and Go-Kart: A Review, accessed June 27, 2026, <https://www.ijer.net/archive/v5i12/ART20163722.pdf>
 57. Static Analysis of Go-Kart Chassis by Analytical and Solid Works Simulation - International Journal of Modern Engineering Research, accessed June 27, 2026, http://www.ijmer.com/papers/Vol5_Issue4/Version-1/IJ0504_01-6468.pdf