IND320 Project Work Part 2

This notebook continues the same project from Part 1. I now read the reservoir data directly from NVE and prepare cross-border power transfer data through Cassandra, Spark and MongoDB.

GitHub repository: https://github.com/Sivan00/IND320-Sivan00-Project1
Streamlit app: https://ind320-sivan00-project1.streamlit.app/
Screencast: Part 2 screencast on GitHub

Setting up the notebook

I keep the imports together here so it is easier to see which packages are used in the local workflow.

In [1]:
```
import os
import tomllib
from pathlib import Path
from dotenv import load_dotenv

# The private settings load here without printing passwords or API keys.
# Existing environment variables take priority over my local file.
load_dotenv(Path(".env"), override=False)

import matplotlib.dates as mdates
import matplotlib.pyplot as plt
import pandas as pd
import requests

from data_utils import COLUMN_NAMES, MEASUREMENTS

# I reuse the app's local settings so I only need to keep one MongoDB password up to date.
# An environment variable still takes priority when running on another computer.
secrets_path = Path(".streamlit/secrets.toml")
if not os.environ.get("MONGODB_URI") and secrets_path.exists():
    with secrets_path.open("rb") as settings_file:
        settings = tomllib.load(settings_file)
    os.environ["MONGODB_URI"] = settings["mongo"]["uri"]

plt.style.use("seaborn-v0_8-whitegrid")
COLORS = ["#2F6F73", "#A45A52", "#947340", "#5D6699", "#77915F"]
```

```
2026-10-08 12:22:13.676 WARNING streamlit.runtime.caching.cache_data_api: No runtime found, using MemoryCacheStorageManager
2026-10-08 12:22:13.676 WARNING streamlit.runtime.caching.cache_data_api: No runtime found, using MemoryCacheStorageManager
```

Reading the reservoir data from NVE

The CSV from Part 1 is no longer used. This request goes to NVE's public Magasinstatistikk endpoint, and the original Norwegian headers are renamed in memory.

In [2]:
```
NVE_URL = (
    "https://biapi.nve.no/magasinstatistikk/api/"
    "Magasinstatistikk/HentOffentligData"
)

# A timeout prevents the notebook from waiting forever if the API is unavailable.
response = requests.get(NVE_URL, timeout=30)
response.raise_for_status()

reservoirs = pd.DataFrame(response.json()).rename(columns=COLUMN_NAMES)
reservoirs["date"] = pd.to_datetime(reservoirs["date"])
reservoirs = reservoirs.sort_values(
    ["date", "area_type", "area_number"]
).reset_index(drop=True)

print(f"Rows: {len(reservoirs):,}")
print(f"Period: {reservoirs['date'].min():%Y-%m-%d} to {reservoirs['date'].max():%Y-%m-%d}")
reservoirs.head()
```

```
Rows: 14,913
Period: 1995-01-08 to 2026-10-04
```

	date	area_type	area_number	iso_year	iso_week	fill_fraction	capacity_twh	stored_energy_twh	next_publication_date	previous_week_fill_fraction	weekly_change_fill_fraction
0	1995-01-08	EL	1	1995	1	0.617574	6.003264	3.707457	0001-01-01T00:00:00	0.583705	0.033869
1	1995-01-08	EL	2	1995	1	0.630947	34.043590	21.479713	0001-01-01T00:00:00	0.777604	-0.146657
2	1995-01-08	EL	3	1995	1	0.602376	8.920932	5.373754	0001-01-01T00:00:00	0.596027	0.006349
3	1995-01-08	EL	4	1995	1	0.558864	21.079208	11.780413	0001-01-01T00:00:00	0.801348	-0.242484
4	1995-01-08	EL	5	1995	1	0.616448	17.390587	10.720388	0001-01-01T00:00:00	0.614288	0.002160

Understanding the NVE areas and download interval

I checked the area definitions in NVE's HentOmråder endpoint. EL means electricity bidding zones: EL 1 is NO1 (south-east), EL 2 is NO2 (south-west), EL 3 is NO3 (central), EL 4 is NO4 (north), and EL 5 is NO5 (west). The API type NO with number 0 means the whole country, so it should not be confused with the bidding-zone names NO1 to NO5.

VASS means watercourse regions. NVE describes VASS 1 as Østlandet, Agder and parts of Rogaland; VASS 2 as the rest of Rogaland and Vestland; VASS 3 as Møre og Romsdal, Trøndelag and southern Nordland; and VASS 4 as the rest of Nordland and further north. These boundaries differ from the electricity zones. At this check, the metadata listed VASS 4 but the measurement response only contained VASS 1 to 3. I report that gap instead of adding an empty region to the chart.

The documented HentOffentligData request has no date parameters. Following the updated assignment from 12 October, the Streamlit table and plot pages use a selection slider for the download interval. NVE first returns the full public history, and the app retains only the selected months locally. The same area radio buttons control both the main lines and the row-wise LineChartColumn graphics.

Sources: NVE API and area definitions and NVE's explanation of the reservoir statistics.

In [3]:
```
from data_utils import load_reservoir_areas

# I compare the area catalogue with the rows actually returned by NVE.
# A missing measurement series is different from a reservoir with zero water.
area_catalogue = load_reservoir_areas()
area_counts = reservoirs.groupby(["area_type", "area_number"]).size().rename("Rows returned")
area_check = area_catalogue.merge(
    area_counts.reset_index(), on=["area_type", "area_number"], how="left",
)
area_check["Rows returned"] = area_check["Rows returned"].fillna(0).astype(int)
display(area_check[["area_type", "area_number", "Area", "Coverage", "Rows returned"]])
```

```
2026-10-08 12:22:14.951 WARNING streamlit.runtime.caching.cache_data_api: No runtime found, using MemoryCacheStorageManager
2026-10-08 12:22:14.952 WARNING streamlit.runtime.scriptrunner_utils.script_run_context: Thread 'MainThread': missing ScriptRunContext! This warning can be ignored when running in bare mode.
```

	area_type	area_number	Area	Coverage	Rows returned
0	EL	1	NO1: South-eastern Norway	Eastern Østlandet from Buskerud northwards, ex...	1657
1	EL	2	NO2: South-western Norway	Most of Vestfold, Telemark, Agder and Rogaland...	1657
2	EL	3	NO3: Central Norway	Northern and western Vestland, Innlandet west ...	1657
3	EL	4	NO4: Northern Norway	The rest of Trøndelag and Northern Norway.	1657
4	EL	5	NO5: Western Norway	Central Vestland up to Sognefjorden, Indre Sog...	1657
5	NO	0	Norway	The whole country.	1657
6	VASS	1	South-eastern Norway	Østlandet, Agder and parts of Rogaland.	1657
7	VASS	2	Western Norway	The rest of Rogaland and Vestland.	1657
8	VASS	3	Central Norway	Møre og Romsdal, Trøndelag and southern Nordland.	1657
9	VASS	4	Northern Norway	The rest of Nordland and the areas further north.	0

Recreating the reservoir plots

The national NO/0 series gives one observation per week. This avoids connecting several area systems in the same line and keeps the plots comparable with Part 1.


In [4]:
```
# NO/0 is the national total used for the time plots.
national = reservoirs.loc[
    (reservoirs["area_type"] == "NO") & (reservoirs["area_number"] == 0)
].copy()

fig, axes = plt.subplots(len(MEASUREMENTS), 1, figsize=(11, 14), sharex=True)

for ax, ((column, (title, unit, multiplier)), color) in zip(
    axes, zip(MEASUREMENTS.items(), COLORS)
):
    ax.plot(national["date"], national[column] * multiplier, color=color, linewidth=1.7)
    ax.set_title(title, loc="left", fontweight="bold")
    ax.set_ylabel(unit)
    ax.grid(axis="y", color="#E7E7E7", linewidth=0.7)
    ax.spines[["top", "right"]].set_visible(False)

axes[-1].set_xlabel("Date")
```


```
axes[-1].xaxis.set_major_locator(mdates.AutoDateLocator(minticks=5, maxticks=9))
axes[-1].xaxis.set_major_formatter(
    mdates.ConciseDateFormatter(axes[-1].xaxis.get_major_locator())
)
fig.suptitle("National reservoir measurements from the NVE API", x=0.08, ha="left", fontsize=15)
fig.tight_layout()
plt.show()
```



In [5]:
```
# The measurements use different units, so I scale each one to its own
# historical 0–1 range before placing them in the same figure.
fig, ax = plt.subplots(figsize=(11, 6))
track_gap = 1.25

for track, ((column, (label, _, _)), color) in enumerate(
    zip(MEASUREMENTS.items(), COLORS)
):
    values = national[column]
    spread = values.max() - values.min()
    scaled = (values - values.min()) / spread if spread else pd.Series(0.0, index=values.index)
    baseline = track * track_gap
    ax.axhline(baseline, color="#E7E7E7", linewidth=0.7)
    ax.plot(national["date"], scaled + baseline, color=color, linewidth=1.8)

ax.set_yticks(
    [track * track_gap for track in range(len(MEASUREMENTS))],
    [label for label, _, _ in MEASUREMENTS.values()],
)
ax.set_title("Reservoir measurements on separate normalized tracks", loc="left", fontweight="bol
d")
ax.set_xlabel("Date")
ax.set_ylabel("0–1 within each measurement")
ax.spines[["top", "right"]].set_visible(False)
fig.tight_layout()
plt.show()
```



Testing Cassandra and Spark

Cassandra runs in the local Docker container named my_cassandra. I use the Python driver to create the table, then start Spark with the same connector version used in the course material.

In [6]:
```
from cassandra.cluster import Cluster

# A short connection test confirms that the local container is reachable.
cluster = Cluster(["127.0.0.1"], port=9042, connect_timeout=10)
```

```
cassandra_session = cluster.connect()
print("Connected to Cassandra:", cassandra_session.cluster.metadata.cluster_name)

cassandra_session.execute(
    """
    CREATE KEYSPACE IF NOT EXISTS ind320
    WITH replication = {'class': 'SimpleStrategy', 'replication_factor': 1}
    """
)
cassandra_session.execute(
    """
    CREATE TABLE IF NOT EXISTS ind320.cross_border_flows (
        connection text,
        year int,
        direction text,
        timestamp timestamp,
        month int,
        value_mw double,
        transfer_mwh double,
        PRIMARY KEY ((connection, year), direction, timestamp)
    ) WITH CLUSTERING ORDER BY (direction ASC, timestamp ASC)
    """
)
print("The ind320.cross_border_flows table is ready.")
```

```
Connected to Cassandra: Test Cluster
The ind320.cross_border_flows table is ready.
```

In [7]:

```
import os
import subprocess
import sys

# Spark's workers need the same Python version as this notebook kernel.
os.environ["PYSPARK_PYTHON"] = sys.executable
os.environ["PYSPARK_DRIVER_PYTHON"] = sys.executable
os.environ["SPARK_LOCAL_IP"] = "127.0.0.1"

# Spark 3.5 did not run with Java 24 on my Mac, so I ask macOS for Java 17 here.
# This keeps the setup inside the notebook instead of changing the whole computer.
java_home = subprocess.run(
    ["/usr/libexec/java_home", "-v", "17"],
    check=True,
    capture_output=True,
    text=True,
).stdout.strip()
os.environ["JAVA_HOME"] = java_home

from pyspark.sql import SparkSession

# I use the same connector version as the course notebook so the Spark and
# Scala versions match instead of leaving that choice to the computer.
spark = (
    SparkSession.builder
    .appName("IND320Project2")
    .config("spark.sql.session.timeZone", "UTC")
    .config(
        "spark.jars.packages",
        "com.datastax.spark:spark-cassandra-connector_2.12:3.5.1",
    )
    .config("spark.cassandra.connection.host", "localhost")
    .config("spark.cassandra.connection.port", "9042")
    .config(
        "spark.sql.extensions",
        "com.datastax.spark.connector.CassandraSparkExtensions",
    )
    .getOrCreate()
)
spark.sparkContext.setLogLevel("ERROR")

# I read the table created in the cell above before adding the API rows.
# Seeing its schema here confirms that Spark is actually using the connector.
cassandra_test = spark.read.format("org.apache.spark.sql.cassandra").options(
    table="cross_border_flows", keyspace="ind320"
```

```
    ).load()
cassandra_test.printSchema()
cassandra_test.limit(1).show(truncate=False)
```

```
/Users/sivanhadji/IND320/.venv/lib/python3.12/site-packages/pyspark/bin/load-spark-env.sh: line 68: /bin/ps: Operation not permitted
:: loading settings :: url = jar:file:/Users/sivanhadji/IND320/.venv/lib/python3.12/site-packages/pyspark/jars/ivy-2.5.1.jar!/org/apache/ivy/core/settings/ivysettings.xml
Ivy Default Cache set to: /Users/sivanhadji/.ivy2/cache
The jars for the packages stored in: /Users/sivanhadji/.ivy2/jars
com.datastax.spark#spark-cassandra-connector_2.12 added as a dependency
:: resolving dependencies :: org.apache.spark#spark-submit-parent-ff253319-f9cc-4868-86f9-66a7f25aa304;1.0
        confs: [default]
        found com.datastax.spark#spark-cassandra-connector_2.12;3.5.1 in central
        found com.datastax.spark#spark-cassandra-connector-driver_2.12;3.5.1 in central
        found org.scala-lang.modules#scala-collection-compat_2.12;2.11.0 in central
        found org.apache.cassandra#java-driver-core-shaded;4.18.1 in central
        found com.datastax.oss#native-protocol;1.5.1 in central
        found com.datastax.oss#java-driver-shaded-guava;25.1-jre-graal-sub-1 in central
        found com.typesafe#config;1.4.1 in central
        found org.slf4j#slf4j-api;1.7.26 in central
        found io.dropwizard.metrics#metrics-core;4.1.18 in central
        found org.hdrhistogram#HdrHistogram;2.1.12 in central
        found org.reactivestreams#reactive-streams;1.0.3 in central
        found org.apache.cassandra#java-driver-mapper-runtime;4.18.1 in central
        found org.apache.cassandra#java-driver-query-builder;4.18.1 in central
        found org.apache.commons#commons-lang3;3.10 in central
        found com.thoughtworks.paranamer#paranamer;2.8 in central
        found org.scala-lang#scala-reflect;2.12.19 in central
:: resolution report :: resolve 193ms :: artifacts dl 6ms
        :: modules in use:
        com.datastax.oss#java-driver-shaded-guava;25.1-jre-graal-sub-1 from central in [default]
        com.datastax.oss#native-protocol;1.5.1 from central in [default]
        com.datastax.spark#spark-cassandra-connector-driver_2.12;3.5.1 from central in [default]
        com.datastax.spark#spark-cassandra-connector_2.12;3.5.1 from central in [default]
        com.thoughtworks.paranamer#paranamer;2.8 from central in [default]
        com.typesafe#config;1.4.1 from central in [default]
        io.dropwizard.metrics#metrics-core;4.1.18 from central in [default]
        org.apache.cassandra#java-driver-core-shaded;4.18.1 from central in [default]
        org.apache.cassandra#java-driver-mapper-runtime;4.18.1 from central in [default]
        org.apache.cassandra#java-driver-query-builder;4.18.1 from central in [default]
        org.apache.commons#commons-lang3;3.10 from central in [default]
        org.hdrhistogram#HdrHistogram;2.1.12 from central in [default]
        org.reactivestreams#reactive-streams;1.0.3 from central in [default]
        org.scala-lang#scala-reflect;2.12.19 from central in [default]
        org.scala-lang.modules#scala-collection-compat_2.12;2.11.0 from central in [default]
        org.slf4j#slf4j-api;1.7.26 from central in [default]
        ---------------------------------------------------------------------
        |                  |            modules            ||   artifacts   |
        |       conf       | number| search|dwnlded|evicted|| number|dwnlded|
        ---------------------------------------------------------------------
        |      default     |   16  |   0   |   0   |   0   ||   16  |   0   |
        ---------------------------------------------------------------------
:: retrieving :: org.apache.spark#spark-submit-parent-ff253319-f9cc-4868-86f9-66a7f25aa304
        confs: [default]
        0 artifacts copied, 16 already retrieved (0kB/6ms)
26/10/08 12:22:16 WARN NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java classes where applicable
Setting default log level to "WARN".
To adjust logging level use sc.setLogLevel(newLevel). For SparkR, use setLogLevel(newLevel).
root
 |-- connection: string (nullable = false)
 |-- year: integer (nullable = false)
 |-- direction: string (nullable = true)
 |-- timestamp: timestamp (nullable = true)
 |-- month: integer (nullable = true)
 |-- transfer_mwh: double (nullable = true)
 |-- value_mw: double (nullable = true)
```

```
+----------+----+----------+-------------------+-----+------------+--------+
|connection|year|direction  |timestamp          |month|transfer_mwh|value_mw|
+----------+----+----------+-------------------+-----+------------+--------+
|NO3-SE2   |2025|Into Norway|2024-12-31 23:00:00|1    |527.5975    |527.5975|
+----------+----+----------+-------------------+-----+------------+--------+
```

Downloading the last two complete years from ENTSO-E

The token is read from the private local settings, never printed or written in this notebook. I use the last two complete calendar years, 2024 and 2025 for this hand-in. I request each border in both directions and keep Norwegian calendar years while storing timestamps in UTC.

These are physical flows, not electricity production. ENTSO-E reports average power in MW. For a complete hour, multiplying the hourly mean by one hour gives energy in MWh. I use MW in the line plots and summed MWh in the yearly pie. Source: ENTSO-E physical flows.

In [8]:
```
from entsoe import EntsoeRawClient
from entsoe_utils import fetch_norwegian_transfers

api_key = os.environ.get("ENTSOE_API_KEY")
if not api_key:
    raise ValueError(
        "Set ENTSOE_API_KEY in the local environment before running this section."
    )

current_year = pd.Timestamp.now(tz="Europe/Oslo").year
start = pd.Timestamp(f"{current_year - 2}-01-01", tz="Europe/Oslo")
end = pd.Timestamp(f"{current_year}-01-01", tz="Europe/Oslo")

# The helper converts the API's XML response into a table and caches each year.
client = EntsoeRawClient(api_key=api_key, timeout=60, retry_count=1)
transfers = fetch_norwegian_transfers(client, start, end)
print(f"Downloaded {len(transfers):,} hourly rows from {start.date()} to {end.date()}.")
display(transfers.head())

# I check coverage before treating the sums as yearly totals.
coverage = transfers.groupby(["connection", "direction", "year"])["value_mw"].count().rename("re
corded_hours").reset_index()
coverage["expected_hours"] = coverage["year"].map(
    lambda year: len(pd.date_range(f"{year}-01-01", f"{year + 1}-01-01",
                                   freq="h", tz="Europe/Oslo", inclusive="left"))
)
coverage["missing_hours"] = coverage["expected_hours"] - coverage["recorded_hours"]
assert not transfers.duplicated(["connection", "direction", "timestamp"]).any()
assert transfers["value_mw"].dropna().ge(0).all()
display(coverage)
```

```
Checked NO1-SE3, Out of Norway.
Checked NO1-SE3, Into Norway.
Checked NO2-DK1, Out of Norway.
Checked NO2-DK1, Into Norway.
Checked NO2-NL, Out of Norway.
Checked NO2-NL, Into Norway.
Checked NO2-DE-LU, Out of Norway.
Checked NO2-DE-LU, Into Norway.
Checked NO2-GB, Out of Norway.
Checked NO2-GB, Into Norway.
Checked NO3-SE2, Out of Norway.
Checked NO3-SE2, Into Norway.
Checked NO4-SE1, Out of Norway.
Checked NO4-SE1, Into Norway.
Checked NO4-SE2, Out of Norway.
Checked NO4-SE2, Into Norway.
Checked NO4-FI, Out of Norway.
```

```
Checked NO4-FI, Into Norway.
Downloaded 315,792 hourly rows from 2024-01-01 to 2026-01-01.
```

	timestamp	value_mw	connection	direction	transfer_mwh	year	month
17544	2023-12-31 23:00:00+00:00	1655.6900	NO1-SE3	Into Norway	1655.6900	2024	1
0	2023-12-31 23:00:00+00:00	0.0000	NO1-SE3	Out of Norway	0.0000	2024	1
122808	2023-12-31 23:00:00+00:00	1399.0425	NO2-DE-LU	Into Norway	1399.0425	2024	1
105264	2023-12-31 23:00:00+00:00	0.0000	NO2-DE-LU	Out of Norway	0.0000	2024	1
52632	2023-12-31 23:00:00+00:00	1637.5200	NO2-DK1	Into Norway	1637.5200	2024	1

	connection	direction	year	recorded_hours	expected_hours	missing_hours
0	NO1-SE3	Into Norway	2024	8784	8784	0
1	NO1-SE3	Into Norway	2025	8760	8760	0
2	NO1-SE3	Out of Norway	2024	8784	8784	0
3	NO1-SE3	Out of Norway	2025	8760	8760	0
4	NO2-DE-LU	Into Norway	2024	8784	8784	0
5	NO2-DE-LU	Into Norway	2025	8760	8760	0
6	NO2-DE-LU	Out of Norway	2024	8784	8784	0
7	NO2-DE-LU	Out of Norway	2025	8760	8760	0
8	NO2-DK1	Into Norway	2024	8784	8784	0
9	NO2-DK1	Into Norway	2025	8760	8760	0
10	NO2-DK1	Out of Norway	2024	8784	8784	0
11	NO2-DK1	Out of Norway	2025	8760	8760	0
12	NO2-GB	Into Norway	2024	8784	8784	0
13	NO2-GB	Into Norway	2025	8760	8760	0
14	NO2-GB	Out of Norway	2024	8784	8784	0
15	NO2-GB	Out of Norway	2025	8760	8760	0
16	NO2-NL	Into Norway	2024	8784	8784	0
17	NO2-NL	Into Norway	2025	8760	8760	0
18	NO2-NL	Out of Norway	2024	8784	8784	0
19	NO2-NL	Out of Norway	2025	8760	8760	0
20	NO3-SE2	Into Norway	2024	8784	8784	0
21	NO3-SE2	Into Norway	2025	8760	8760	0
22	NO3-SE2	Out of Norway	2024	8784	8784	0
23	NO3-SE2	Out of Norway	2025	8760	8760	0
24	NO4-FI	Into Norway	2024	8784	8784	0
25	NO4-FI	Into Norway	2025	8760	8760	0
26	NO4-FI	Out of Norway	2024	8784	8784	0
27	NO4-FI	Out of Norway	2025	8760	8760	0
28	NO4-SE1	Into Norway	2024	8784	8784	0
29	NO4-SE1	Into Norway	2025	8760	8760	0
30	NO4-SE1	Out of Norway	2024	8784	8784	0
31	NO4-SE1	Out of Norway	2025	8760	8760	0
32	NO4-SE2	Into Norway	2024	8784	8784	0
33	NO4-SE2	Into Norway	2025	8760	8760	0
34	NO4-SE2	Out of Norway	2024	8784	8784	0
35	NO4-SE2	Out of Norway	2025	8760	8760	0

Storing the API rows in Cassandra with Spark

In [9]:
```
# I pass timezone-aware Python datetimes so Spark keeps the same instant.
# An explicit schema also avoids differences between pandas and Spark versions.
```

```
spark_input = [
    (row.timestamp.to_pydatetime(), row.connection, row.direction,
     float(row.value_mw), float(row.transfer_mwh), int(row.year), int(row.month))
    for row in transfers.itertuples(index=False)
]

spark_transfers = spark.createDataFrame(
    spark_input,
    "timestamp timestamp, connection string, direction string, "
    "value_mw double, transfer_mwh double, year int, month int",
)
(
    spark_transfers.write
    .format("org.apache.spark.sql.cassandra")
    .mode("append")
    .options(table="cross_border_flows", keyspace="ind320")
    .save()
)
print("The ENTSO-E rows were written to local Cassandra.")
```

```
[Stage 1:>                                                          (0 + 10) / 10]
The ENTSO-E rows were written to local Cassandra.
```

Extracting the columns needed later

I read the table back through Spark instead of continuing with the original Pandas object. This makes the Cassandra-to-Spark step visible and keeps only the columns needed for plots and MongoDB.

In [10]:
```
from pyspark.sql import functions as F

raw_spark = (
    spark.read
    .format("org.apache.spark.sql.cassandra")
    .options(table="cross_border_flows", keyspace="ind320")
    .load()
)

curated_spark = (
    raw_spark
    .select(
        "timestamp", "connection", "direction", "value_mw",
        "transfer_mwh", "year", "month"
    )
    .filter(F.col("year").isin([current_year - 2, current_year - 1]))
    .dropDuplicates(["connection", "direction", "timestamp"])
    .orderBy("timestamp", "connection", "direction")
)
curated_spark.show(8, truncate=False)
# collect() keeps this compatible with the local pandas 3 installation.
# Epoch seconds avoid a second conversion through the Mac's local timezone.
export_rows = curated_spark.withColumn("timestamp", F.col("timestamp").cast("long"))
curated = pd.DataFrame([row.asDict() for row in export_rows.collect()])
curated["timestamp"] = pd.to_datetime(curated["timestamp"], unit="s", utc=True)
```

```
[Stage 2:===================>                                          (7 + 10) / 20]
[Stage 2:========================================>                     (14 + 6) / 20]
```

```
+-------------------+----------+-------------+---------+------------+----+-----+
|timestamp          |connection|direction    |value_mw |transfer_mwh|year|month|
+-------------------+----------+-------------+---------+------------+----+-----+
|2023-12-31 23:00:00|NO1-SE3   |Into Norway  |1655.69  |1655.69     |2024|1    |
|2023-12-31 23:00:00|NO1-SE3   |Out of Norway|0.0      |0.0         |2024|1    |
|2023-12-31 23:00:00|NO2-DE-LU |Into Norway  |1399.0425|1399.0425   |2024|1    |
|2023-12-31 23:00:00|NO2-DE-LU |Out of Norway|0.0      |0.0         |2024|1    |
|2023-12-31 23:00:00|NO2-DK1   |Into Norway  |1637.52  |1637.52     |2024|1    |
|2023-12-31 23:00:00|NO2-DK1   |Out of Norway|0.0      |0.0         |2024|1    |
|2023-12-31 23:00:00|NO2-GB    |Into Norway  |0.0      |0.0         |2024|1    |
|2023-12-31 23:00:00|NO2-GB    |Out of Norway|463.78   |463.78      |2024|1    |
+-------------------+----------+-------------+---------+------------+----+-----+
only showing top 8 rows
```


Making the yearly direction plot

In [11]:

```python
# I use one connection and the latest complete year as a clear example.
chosen_connection = "NO2-DK1"
chosen_year = current_year - 1

annual = curated.loc[
    (curated["connection"] == chosen_connection)
    & (curated["year"] == chosen_year)
]
direction_totals = annual.groupby("direction")["transfer_mwh"].sum()

fig, ax = plt.subplots(figsize=(6, 5))
ax.pie(
    direction_totals,
    labels=direction_totals.index,
    autopct="%1.1f%%",
    startangle=90,
    colors=["#2F6F73", "#D58A5C"],
    wedgeprops={"linewidth": 1, "edgecolor": "white"},
)
ax.set_title(f"{chosen_connection}: transfer direction in {chosen_year}")
plt.show()
```




Making the first-month line plot

In [12]:
```
from zoneinfo import ZoneInfo

# I keep the same connection as the pie chart and show January.
# Two separate lines make imports and exports easier to compare.
first_month = 1
first_month_rows = curated.loc[
    (curated["year"] == chosen_year) & (curated["month"] == first_month)
    & (curated["connection"] == chosen_connection)
].copy()

fig, ax = plt.subplots(figsize=(11, 4.5))
for (connection, direction), rows in first_month_rows.groupby(
    ["connection", "direction"]
):
    ax.plot(
        rows["timestamp"], rows["value_mw"],
        label=f"{connection} | {direction}", linewidth=1.2,
        color="#2F6F73" if direction == "Into Norway" else "#D58A5C",
    )

ax.set_title(f"{chosen_connection}: hourly transfers in January {chosen_year}", loc="left", font
weight="bold")
ax.set_xlabel("Date (Norwegian time)")
ax.set_ylabel("MW")
ax.spines[["top", "right"]].set_visible(False)
locator = mdates.AutoDateLocator(minticks=4, maxticks=7, tz=ZoneInfo("Europe/Oslo"))
ax.xaxis.set_major_locator(locator)
ax.xaxis.set_major_formatter(mdates.ConciseDateFormatter(locator, tz=ZoneInfo("Europe/Oslo")))
ax.legend(ncols=2, frameon=False, fontsize=9, loc="upper center", bbox_to_anchor=(0.5, -0.2))
fig.tight_layout()
plt.show()
```



Writing the curated rows to MongoDB

The MongoDB address is read from the private local settings. I insert new hours together and only update rows whose values have changed. The unique index prevents the same connection, direction and timestamp from being stored twice.

In [13]:

```python
from pymongo import MongoClient, ReplaceOne

mongo_uri = os.environ.get("MONGODB_URI")
if not mongo_uri:
    raise ValueError(
        "Set MONGODB_URI in the local environment before running this section."
    )

mongo_client = MongoClient(mongo_uri, serverSelectionTimeoutMS=20000, tz_aware=True)
collection = mongo_client["ind320"]["power_transfers"]
collection.create_index(
    [("connection", 1), ("direction", 1), ("timestamp", 1)],
    unique=True,
)

# Each timestamp is converted to a Python datetime before sending it to MongoDB.
mongo_rows = curated.to_dict("records")
# I compare existing rows first, so rerunning does not rewrite unchanged hours.
existing = {
    (row["connection"], row["direction"], row["timestamp"]): row
    for row in collection.find({}, {"_id": 0})
}
new_rows = []
changes = []
for row in mongo_rows:
    row["timestamp"] = row["timestamp"].to_pydatetime()
    key = {
        "connection": row["connection"],
        "direction": row["direction"],
        "timestamp": row["timestamp"],
    }
    previous = existing.get((row["connection"], row["direction"], row["timestamp"]))
    if previous is None:
        new_rows.append(row)
    elif previous != row:
        changes.append(ReplaceOne(key, row))

# Batching new documents is much quicker than one upsert per hour.
for start_row in range(0, len(new_rows), 5000):
```

```
        collection.insert_many(new_rows[start_row:start_row + 5000], ordered=False)
for start_row in range(0, len(changes), 1000):
    collection.bulk_write(changes[start_row:start_row + 1000], ordered=False)

print(f"Added {len(new_rows):,} new rows and changed {len(changes):,} existing rows.")
print(f"MongoDB now contains {collection.count_documents({}):,} transfer rows.")
```

```
Added 229,792 new rows and changed 0 existing rows.
MongoDB now contains 315,792 transfer rows.
```

AI use

I used ChatGPT and Codex as learning support when I needed help understanding some of the Spark, Cassandra and MongoDB functions. They also helped me check the project structure and explain how the different components connect. I reviewed the suggestions, rewrote parts of the code and made my own changes. Codex also helped with the practical setup in VS Code and will help publish the finished branch to GitHub and Streamlit, which saves time on those steps.

Work log

I continued from Part 1 in the same repository and developed the new work on the project-part-2 branch. This kept the reviewed version on main while I changed the notebook and app. After peer review and feedback, I merged the finished branch into main.

I started by removing reservoirs.csv and reading the reservoir data directly from NVE's Magasinstatistikk API. The English column names from Part 1 could still be used, so I mainly had to sort the dates and make sure the plots used the new response correctly. The assignment was updated while I was working, and I added radio buttons to both reservoir pages for EL, NO and VASS. Looking at NVE's area catalogue made the difference between these area systems clearer. One thing I noticed was that VASS 4 is listed in the catalogue but has no series in the measurement response. Since this API returns the full history, the interval slider filters the downloaded rows to the months I choose.

Getting the ENTSO-E data took more work. After my account was approved, I downloaded physical power flows for nine Norwegian cross-border connections in both directions, using 2024 and 2025 as the last two complete years. Some of the monthly requests timed out, so I switched to yearly requests and cached each successful download. The finished data contains 315,792 hourly rows and the coverage check found no missing hours. Timestamps are stored in UTC, but I use Norwegian time when creating the month and year columns. This keeps the first Norwegian hour of January in the correct year. I then used Spark to write the rows to local Cassandra and read the table back again, keeping only the columns needed later. The local setup only worked properly after I used Java 17 and matched the Python versions for the notebook and Spark workers. MongoDB receives the prepared rows in batches, which is faster than updating one hour at a time and avoids changing rows that are already correct.

The new Streamlit page reads the transfer data from MongoDB. On the left I can choose a connection and year, and the month pills on the right decide what appears in the line plot. I tested all nine connections, both years and different month combinations. The pie chart uses yearly energy in MWh, while the lines show hourly power flow in MW. For the notebook example I kept January and one connection because this makes the two directions easier to compare.

Before publishing, I ran every notebook cell and checked the tables and figures. I first pushed the finished version to project-part-2, then merged it into main after the review stage. The Streamlit address stayed the same. MongoDB is configured through Streamlit Secrets, while local credentials are ignored by Git. I also checked the published navigation and every data page after deployment.