

(MANUFACTURERS OF MACHINE TOOLS)

T SIVARAMAKRISHNA ME., MBA.

TMT/ khammam/S0349/2025

01-07-2025

To Sai,

Khammam

Mobile: 9885991911

Sir,

<u>Subject</u>: Design, Manufacturing, Supply, Supervision of Erection and Commissioning of 3 Ton EOT Crane - Reg.

Design, Fabrication, Supply and Erection of Per Set Rs. 6,80,000/- (Six lakh Eighty thousand only) all fabricated parts into your account

### **General Specifications**

Type of EOT : Single Girder Electrically Operated

Crane

Conforming to IS 3177 and 807

• Capacity of the EOT Crane : 3 Tons

• Span of the EOT : 13.7 mts

• Lift of the EOT : 3.5 mts

• Type of Service : Indoor

Class (Mech /Elec ) : Class II

Mode of Operation : Pendent Operated

• Type of Arrangement : Single Girder Box Type

Ambient Temp. Considered : 50 Deg C

### **Lifting Equipment Specifications for 3 ton Unit**

Type of Crab Proposed : 3 Ton Cap Wire Rope Crab

• Type of Gear Box Casing Used : Totally Enclosed type Fabricated

**Stress** 

Relieved and Machined

Material used for gears used in crane : Machine Cut Helical Gears Hardened

and Tempered



(MANUFACTURERS OF MACHINE TOOLS)

#### T SIVARAMAKRISHNA ME., MBA.

Lubrication Provided for Gear Box : Splash Type Lubrication

Bearing Used in the Gear Box : Self Aligned Anti Friction type

**Spherical** 

**Roller Bearings** 

• Size and Make of Wire Rope : Dia 8 mm x 6/36 Const FM Core-Usha

Martin

• Hoisting Speed : 3 mts/min

• Type of Hook : C type Hook conforming to IS 3815

• Class ( Mech / Elec ) : Class II

• Lift of the Crab : 3.5 mts

• No. of Falls : 4 falls

Rope Drum : Fabricated using Low Carbon Steel /

Seam less

Pipe conforming to IS 2062 and duly

stress relieved

• Motor Used : Sq Cage Induction Motor Crane duty-

6 pole

Class F/3 HP/40% CDF/150 Starts/hr

BB/Siemens Make

• Type of Brake Used : EHT Brake- Dia 150 mm - 1 no of

**SOC Make** 

• Type of Limit Switch Provided : Rotary Geared Type

**Cross Travel Trolley** 

• Class of Duty ( Mech / Elec) : Class II

• No. Of Driver : 1 no

• CT speed : 5 mts/min

Motor Used : Sq Cage Induction Motor Crane duty-

6 pole

Class F/1 HP/40% CDF/150 Starts/hr

-



(MANUFACTURERS OF MACHINE TOOLS)

#### T SIVARAMAKRISHNA ME., MBA.

**BB** Make

Type of Drive Proposed for Cross Travel : Floating Shaft Type Drive

Wheel Housings used for CT : Bracket Type

• Type of Limit Switch Provided : Shunt -2 Way Roller Leaver Type

• Specification of Wheels Used for CT : C

Hardened to

C 55 Mn 75 Forged Steel and

30 HRC with diameter of 280 mm

**Long Travel Trolley** 

Class of Duty ( Mech /Elec) : Class II

• No. Of Driver : 1 no

• L T Speed : 10 mts/min

• Type of Drive Proposed for Long Travel : Twin Drive

• Motor Used : Sq Cage Induction Motor Crane duty-

6 pole

Class F/1 HP/40% CDF/150 Starts/hr

BB Make

• Wheel Housings used for LT : Bracket Type

• Specification of Wheels Used for LT : C 55 Mn 75 Forged Steel and

Hardened to

30 HRC with diameter of 350 mm

• Rail Size Considered for LT : 40 lbs Rail

Structure Considered

Platform : Full length on one side & Two Short

on other

• Girder for C T beam : Fabricated box type using M S plates

• End Carriages : Fabricated box type using M S Plates

• Type of Trail Cabling for Cross Travel : Through Flexible Trail Cabling



(MANUFACTURERS OF MACHINE TOOLS)

T SIVARAMAKRISHNA ME., MBA.

Material used for Fabrication of crane : M S Conforming to IS 2062

Painting Details
Two Coats of ROMP – two Coats

**Enamel** paint

Safety features incorporated in system : Limit Switches for Hoist, LT, CT will

be

provided

**Electrical and Other Specifications** 

Control Panel : Own make fabricated

• Cables used : Flexible copper cables

• Limit Switches : Reputed Makes will be used

2. Fabrication and Supply of Bus Bar Arrangement for Electrical supply as per the Following Specs.

Total Length of the Bus Bar : As Per Your Requirement

Safe track type of enclosed Bus Bar : Safe track

• Capacity of the Bus Bar : 50 amps - GI

Section used for the Bus Bar Brackets : Enclosed U type channel

#### **GENERAL TERMS & CONDITIONS:**

1. Price quoted per unit ex-work. Hyderabad.

2. Following charges are additional to your account.

✓ Freight Charge : As actual to be borne by you.

✓ Excise : Extra As Applicable✓ Sales Tax : Extra as applicable

✓ Packing charge : As actual to be borne by you.✓ Insurance : As actual to be borne by you.

Payment& Delivery : 50% advance delivery within one 45 days.
Validity : One month from the date of submission.
Inspection : Inspection at our works prior to dispatch.

6. Warranty : The machine is warranted for a period of 12 months from

the date of dispatch against any manufacturing defects/ faulty material or bad workmanship of any part or component but not against any kind of abnormal or

\_\_\_\_\_



(MANUFACTURERS OF MACHINE TOOLS)

T SIVARAMAKRISHNA ME., MBA.

improper use of machine. Defective part or component will be replaced or repaired free of cost. Electrical components are outside the scope of this warranty.

7. Commissioning

: Erection & commissioning done by you, but required technical support & guidance provide by us at additional cost.

#### **NOTE**:

- 1. Oil is not in our scope of supply.
- 2. Raw material for trial is to be arranged by you at your cost.

We are sure you will find our offer in line with your requirements. Should you require any further clarification please contact 9246221106/9849207176 email: techno9246221106@gmail.com

Thanking you and assuring you of our best services.

**For Techno Machine Tools** 

T.SIVARAMAKRISHNA

Survey pol 126/A/1 DOOD NO. 4 122 0/A/2 Condination was V Dood Modeled Mellongini