

Techno Machine Tools

Survey no:126/A/1, DOOR NO: 4-132-9/A/2, Gandimaisamma X Road,
Medchal Malkajgeri, Hyderabad-500043. Telangana, India.

(Machine tool manufacturers)

T.SIVARAMAKRISHNA

ME., MBA.

TMT/Bihar/S0656/2026

23-01-2026

TO,

Dhirendra kumar.gupta

Mobile: [+919006390167](tel:+919006390167),

City : 'Rohtas', Bihar.

Sir,

Subject: Design, Manufacturing, Supply, (including structure) of 7 Ton Cap gantry Crane - Reg.

**1. Design, Fabrication, Supply and Erection of Per Set Rs. 11,00,000/-
7ton EOT Crane as per following Specs.**

General Specifications

- | | | |
|----------------------------|---|--|
| • Type of Crane | : | Single Girder Electrically Operated Crane
Conforming to IS 3177 and 807 |
| • Capacity of the gantry | : | 7 Tons |
| • Span of the gantry | : | 10 mts |
| • Lift of the gantry | : | 8.5 mts |
| • Type of Service | : | Indoor |
| • Class (Mech / Elec) | : | Class II |
| • Mode of Operation | : | Pendent Operated |
| • Type of Arrangement | : | Single Girder Box Type |
| • Ambient Temp. Considered | : | 45 Deg C |



Lifting Equipment Specifications for 7 ton Unit

- Type of Hoist Proposed : 7 Ton Cap Wire Rope Hoist
- Type of Gear Box Casing Used : Totally Enclosed type Fabricated Stress Relieved and Machined
- Material used for gears used in crane : Machine Cut Helical Gears Hardened and Tempered
- Lubrication Provided for Gear Box : Splash Type Lubrication
- Bearing Used in the Gear Box : Self Aligned Anti Friction type Spherical Roller Bearings
- Size and Make of Wire Rope : Dia 12 mm x 6/36 Const FM Core-Usha Martin
- Hoisting Speed : 3 mts/min
- Type of Hook : C type Hook conforming to IS 3815
- Class (Mech / Elec) : Class II
- Lift of the Hoist : 6 mts
- No. of Falls : 4 falls

- Rope Drum less : Fabricated using Low Carbon Steel / Seam
Pipe conforming to IS 2062 and duly stress relieved
- Motor Used : Sq Cage Induction Motor Crane duty– 6 pole
Class F/5 HP/40% CDF/150 Starts/hr -
BB/Siemens Make
- Type of Brake Used : EHT Brake– Dia 150 mm – 1 no of SOC Make
- Type of Limit Switch Provided : Rotary Geared Type

Cross Travel Trolley

- Class of Duty (Mech /Elec) : Class II
- No. Of Driver : 1 no
- C T speed : 12 mts/min
- Motor Used : Sq Cage Induction Motor Crane duty– 6 pole
Class F/2 HP/40% CDF/150 Starts/hr -
BB Make
- Type of Drive Proposed for Cross Travel : Floating Shaft Type Drive
- Wheel Housings used for CT : Bracket Type
- Type of Limit Switch Provided : Shunt –2 Way Roller Leaver Type
- Specification of Wheels Used for CT : C 55 Mn 75 Forged Steel and Hardened to
30 HRC with diameter of 160 mm

Long Travel Trolley

- Class of Duty (Mech /Elec) : Class II
- No. Of Driver : 1 no
- L T Speed : 15 mts/min
- Type of Drive Proposed for Long Travel : Twin Drive
- Motor Used : Sq Cage Induction Motor Crane duty– 6 pole
Class F/2 HP/40% CDF/150 Starts/hr -
BB Make
- Wheel Housings used for LT : Bracket Type
- Specification of Wheels Used for LT : C 55 Mn 75 Forged Steel and Hardened to
30 HRC with diameter of 300 mm
- Rail Size Considered for LT : 50 mm Sq Bar

Structure Considered for fabrication

- Platform : NA
- Girder for C T beam : Fabricated box type using M S plates
- End Carriages : Fabricated box type using M S Plates
- Type of Trail Cabling for Cross Travel : Through Flexible Trail Cabling
- Material used for Fabrication of crane : M S Conforming to IS 2062
- Painting Details : Two Coats of ROMP – two Coats Enamel paint
- Safety features incorporated in system : Limit Switches for Hoist, LT, CT will be provided

Electrical and Other Specifications

- Control Panel : Own make fabricated
- Cables used : Flexible copper cables
- Limit Switches : Reputed Makes will be used

2. Fabrication and Supply of Bus Bar Arrangement for Electrical supply as per the Following Specs. Rs. 1600/mt

- Total Length of the Bus Bar : As Per Your Requirement
- Safe track type of enclosed Bus Bar : Safe track
- Capacity of the Bus Bar : 60 amps - GI
- Section used for the Bus Bar Brackets : Enclosed U type channel

GENERAL TERMS & CONDITIONS:

1. Price quoted per unit ex-work. Hyderabad.
2. **Following charges are additional to your account.**
 - ✓ Freight Charge : As actual to be borne by you.
 - ✓ Sales Tax : **18% Extra as applicable**
 - ✓ Packing charge : **As actual to be borne by you.**
 - ✓ Insurance : As actual to be borne by you.
3. **Payment : 50% advance along with order balance before delivery but after inspection at our works.**
4. **Delivery : with 50% advance with in 3 months.**
5. **Validity : One month from the date of submission.**
6. **Inspection : Inspection at our works prior to dispatch.**
7. **Warranty : The machine is warranted for a period of 12 months from the date of dispatch against any manufacturing defects/faulty material or bad workmanship of any part or component but not against any kind of abnormal or improper use of machine. Defective part or component will be replaced or repaired free of cost. Electrical components are outside the scope of this warranty.**

8. **Commissioning** : Erection & commissioning done by you, but required technical support & guidance provide by us at additional cost.

NOTE:

1. Oil is not in scope of our supply.
2. Raw material for trial is to be arranged by you at your cost.

We are sure you will find our offer in line with your requirements. Should you require any further clarification please contact sivaramakrishna 9246221106.Email: md@technomachinetools.in

Thanking you and assuring you of our best services.

For Techno Machine Tools

T.SIVARAMAKRISHNA

Techno Machine Tools

Survey no:126/A/1, DOOR NO: 4-132-9/A/2, Gandimaisamma X Road,
Medchal Malkajgeri, Hyderabad-500043. Telangana, India

T.SIVARAMAKRISHNA

ME., MBA.

TMT/Bihar/S0656/2026

23-01-2026

TO,

Dhirendra kumar.gupta

Mobile: [+919006390167](tel:+919006390167),

City : 'Rohtas', Bihar.

Dear Sir,

Sub: - SUPPLY OF ROOFING PROFILE ROLL FORMING MACHINE

With reference to our telephonic conversation regarding your requirement of roll forming machine mainly for Color Coated Roofing Section. We are glad to inform you that we would be in a position to supply you the required equipment. Given below are the required specifications and description of the machine and our terms and conditions.

Prices

The cost of Roll forming machine with roofing profile tooling along with Entry guide, Main Roll Forming Machine, Side Guides, Drive System, Cutting Unit and Cutting Die Sets for Rs **23,00,000/- (Rupees Twenty Three Lakh Only)**

With tile profile arrangement Rs 2,25,000/- Two lakhs twenty-five thousand only)

LIST OT EQUIPMENT

- 1) MANUAL DE COILER 5 MT CAPACITY WITH 5 HP DRIVE
- 2) ROLL FORMING MACHINE WITH 21 PASSES
- 3) EN 31 ROOFING PROFILE TOOLING
- 4) 7.5 HP DRIVE WITH REDUCTION GEAR BOX.
- 5) COMPLETE ELECTRICALS ALONG WITH AUTOMATION – PLC
- 6) DELIVERY CUTOFF UNIT WITH 5 HP POWERPACK
- 7) TILE PROFILE UNIT
- 8) RUNOUT TABLE
- 9) FILM REEL UNIT
- 10) INTRU SHEAR

TECHNICAL SPECIFICATION:

GENERAL DATA

Productivity	: ROLL FORMING CUT TO SIZE PROFILE
Manpower required	: ONE OPERATOR TWO ASST. REQUIRED
Total Power Required	: 17.5 HP
Set up time	: COIL LOADING 2-3 MIN, SHEET FEEDING 3-4 MIN
Production capacity	: 20000 KG PER SHIFT 8 HOURS
Working hours per day	: 8-12
Line direction	: LEFT TO RIGHT
Overall floor space required	: 13 METERS (L) 2 METERS (W) 1.2 METERS (H)
Approx weight	: 9000 KG
Line speed	: 3-15 MPM
Model No	: TM/RF/111
Model Type	: CRFM

MATERIAL SPECIFICATIONS

Type of material to be processed	: CR/COLOR COATED/GI/AL
uts	: 32-42 KG/MM ²
% Elongation	: 18-25
Shear strength	: 40-45 KG/MM ²
Maximum width can be processed	: 1220 MM
Minimum width can be processed	: 1020 MM
Maximum thickness can be processed	: 0.6 MM
Minimum thickness can be processed	: 0.36 MM

ENTRY COIL SPECIFICATIONS

Maximum weight of coil	: 5 TON
Maximum od of coil at entry	: 1600 MM
Minimum od of coil at entry	: 600 MM

DE COILER SPECIFICATIONS

Model	: SINGLE ARM
Load - capacity	: 5000 KG MAX.
width	: 1220MM
Mandrel movement	: DIA 450 MM - 550 MM
Mandrel Height from ground	: 1100 MM
Mandrel expansion	: MANUAL
Construction	: M. S. FABRICATED.
Mandrel rotation	: WITH 5 HP GEARED MOTOR



MILL SPECIFICATIONS

Roll shaft diameter	: DIA 70 MM
The vertical distance between shafts	: 330 MM
The horizontal distance between shafts	: 550 MM
Number of forming stations	: 21 NOS
Drive (AC)	: 7.5 HP
Delivery shear	: 5 HP {power pack}
Speed of the machine	: 0-15 meters/max
Shaft material	: EN9
Rollers Material	: EN31
Hydraulic tank capacity	: 300 liters



Description of the equipment

Roll Forming Machine

Main Base

The main base is MS fabricated structure and adequately ribbed to minimize the distortion. It is accurately machined on top and bottom surfaces the threaded holes are made on the bed for positioning the stands.

Entry Guide

The entry side of the machine will be equipped with guide table and the guide wheels bar which will be responsible for centering the leading ends of the strip into the first pass.

Mill stands

The stands are mounted on the bed of the machine the line alignment can be easily done due to guide ways arranged on the bed of the machine. Each forming head consists of a fixed housing and sliding type out board housing. The mill stands will be arranged to locate shafts mounted on anti-friction bearings. For the top shafts the bearings are housed in the cartridge type bearing blocks. The bottom shaft bearings are located in the bored

machined in the housings. The bottom arbors are fixed in position whereas the top arbors along with cartridge blocks could be raised or lowered in vertical guides machined in housings.

Roll shafts

The roll shafts will be manufactured from quality steel and will be keyed to locate tooling.

Drive

The drive to the roll former will be by means of a gear box system. The main drive will be provided by means of 7.5 HP motor. The speed of the roll former is variable.

Delivery runout table

The delivery runout table is with four meters length.

Cutoff unit

The cutoff unit with hydraulic press along with cutting die set will be placed in the machine delivery side.

GENERAL TERMS & CONDITIONS:

9. Price quoted per unit ex-work. Hyderabad.
10. Following charges are additional to your account.
 - ✓ Freight Charge : As actual to be borne by you.
 - ✓ Sales Tax : 18% Extra as applicable
 - ✓ Packing charge : As actual to be borne by you.
 - ✓ Insurance : As actual to be borne by you.
11. Payment : 50% advance along with order,
: balance 50% after installation and before delivery
12. Delivery : within 8 weeks from date of advance received
13. Validity : One month from the date of submission.
14. Inspection : Inspection at our works prior to dispatch.
15. Warranty : The machine is warranted for a period of 12 months from the date of dispatch against any manufacturing defects/ faulty material or bad workmanship of any part or component but not against any kind of abnormal or improper use of machine. Defective part or component will be replaced or repaired free of cost. Electrical components are outside the scope of this warranty.
16. Commissioning : Erection & commissioning done by you, but required technical support & guidance provide by us at additional cost.

NOTE:

3. Oil is not in scope of our supply.
4. Raw material for trial is to be arranged by you at your cost.

We are sure you will find our offer in line with your requirements. Should you require any further clarification please contact T. Sivaramakrishna, 9246221106.

Email: md@technomachinetools.in WhatsApp No: 9849207176

Thanking you and assuring you of our best services.

For TECHNO MACHINE TOOLS

(T. SIVARAMAKRISHNA)

Techno Machine Tools

Survey no:126/A/1, DOOR NO: 4-132-9/A/2, Gandimaisamma X Road,
Medchal Malkajgeri, Hyderabad-500043, Telangana, India

(Machine tool manufacturers)

T.SIVARAMAKRISHNA

ME., MBA.

TMT/Bihar/S0656/2026

23-01-2026

TO,

Dhirendra kumar.gupta

Mobile: [+919006390167](tel:+919006390167),

City : 'Rohtas', Bihar.

Sir,

Sub: - SUPPLY OF Edge Crimping / Arch Crimping MACHINE

Thank you very much for your enquiry regarding your requirement of Crimping machine mainly for color coated Sections. We are glad to inform you that we would be in a position to supply you the required equipment. Given below are the required specifications and description of the machine and our terms and conditions.

Prices

The cost of Crimping machine along with Power Pack 5 HP and crimping Tool suitable to your profile is **Rs 6,50,000=00 (Six Lakhs Fifty Thousand Only)**

Technical Specifications:

- **Product's feature:**

This crimping roll forming machine is used to curve panel for formed sheet from ZYYX30-200-1000 / suitable profile.

- **Main technical parameters**

1) Max. Width of Formed steel sheet: Suitable Profile

2) Material thickness: 0.3-0.8mm color coated steel sheet.

3) Main motor power : 2.2kw (Depend on final design)

- 4) Hydraulic station power : 3.75 kw (Depend on final design)
- 5) Min. bending radium : 300mm
- 6) Crimping length : min. 25mm, max. Crimping length - no limit.
- 7) Crimping strokes : 12-15 strokes /minute
- 8) Bending : By hydraulic
- 9) Control : PLC control
- 10) Curving roller material : Cr12 mould steel.
- 11) Size of machine : 2500 mm X 1100 mm X 1600 mm (Ht)

GENERAL TERMS & CONDITIONS:

17. Price quoted per unit ex-work. Hyderabad.
18. Following charges are additional to your account.
- ✓ Freight Charge : As actual to be borne by you.
 - ✓ Sales Tax : 18% Extra as applicable
 - ✓ Packing charge : As actual to be borne by you.
 - ✓ Insurance : As actual to be borne by you.
19. Payment : 50% advance along with order balance before delivery but after inspection at our works.
20. Delivery : with 50% advance with in 3 months.
21. Validity : One month from the date of submission.
22. Inspection : Inspection at our works prior to dispatch.
23. Warranty : The machine is warranted for a period of 12 months from the date of dispatch against any manufacturing defects/faulty material or bad workmanship of any part or component but not against any kind of abnormal or improper use of machine. Defective part or component will be replaced or repaired free of cost. Electrical components are outside the scope of this warranty.
24. Commissioning : Erection & commissioning done by you, but required technical support & guidance provide by us at additional cost.

NOTE:

5. Oil is not in scope of our supply.
6. Raw material for trial is to be arranged by you at your cost.

We are sure you will find our offer in line with your requirements. Should you require any further clarification please contact sivaramakrishna 9246221106.Email:

md@technomachinetools.in

Thanking you and assuring you of our best services.



For TECHNO MACHINE TOOLS

(T. SIVARAMAKRISHNA)

Our Bank details

TECHNO MACHINE TOOLS

A/C NO: 11534015002032

IFSC CODE: PUNB0115310

BRANCH: BALANAGAR, HYDERABAD

GST NO: 36AELPT9784K1ZC