

# TECHNO MACHINE TOOLS

A/15, CO-OPERATIVE INDUSTRIAL ESTATE, BALANAGAR, HYDERABAD

(Machine tool manufacturers)

**T.SIVARAMAKRISHNA**

ME., MBA.

REF :TM/Achuta Reddy /2026-27/355106

DATED: 02-04-2026

to,  
Mr. Achuta Reddy  
M 8985724365

Sir,

**Subject : Design, Manufacturing, Supply, (including structure) of 7 Ton Cap gantry Crane - Reg.**

**1. Design, Fabrication, Supply and Erection of  
7 ton EOT Crane as per following Specs.**

**Per Set Rs. 13,00,000/-**

## **General Specifications**

- |                            |   |                                                                            |
|----------------------------|---|----------------------------------------------------------------------------|
| • Type of Crane            | : | Single Girder Electrically Operated Crane<br>Conforming to IS 3177 and 807 |
| • Capacity of the gantry   | : | 7 Tons                                                                     |
| • Span of the gantry       | : | 10 mts                                                                     |
| • Lift of the gantry       | : | 8.5 mts                                                                    |
| • Type of Service          | : | Indoor                                                                     |
| • Class ( Mech / Elec )    | : | Class II                                                                   |
| • Mode of Operation        | : | Pendent Operated                                                           |
| • Type of Arrangement      | : | Single Girder Box Type                                                     |
| • Ambient Temp. Considered | : | 45 Deg C                                                                   |



### **Lifting Equipment Specifications for 7 ton Unit**

- Type of Hoist Proposed : 7 Ton Cap Wire Rope Hoist
- Type of Gear Box Casing Used : Totally Enclosed type Fabricated Stress Relieved and Machined
- Material used for gears used in crane : Machine Cut Helical Gears Hardened and Tempered
- Lubrication Provided for Gear Box : Splash Type Lubrication
- Bearing Used in the Gear Box : Self Aligned Anti Friction type Spherical Roller Bearings
- Size and Make of Wire Rope : Dia 12 mm x 6/36 Const FM Core-Usha Martin
- Hoisting Speed : 3 mts/min
- Type of Hook : C type Hook conforming to IS 3815
- Class ( Mech / Elec ) : Class II
- Lift of the Hoist : 6 mts
- No. of Falls : 4 falls

- Rope Drum less : Fabricated using Low Carbon Steel / Seam  
Pipe conforming to IS 2062 and duly stress relieved
- Motor Used : Sq Cage Induction Motor Crane duty– 6 pole  
Class F/5 HP/40% CDF/150 Starts/hr -  
BB/Siemens Make
- Type of Brake Used : EHT Brake– Dia 150 mm – 1 no of SOC Make
- Type of Limit Switch Provided : Rotary Geared Type

### **Cross Travel Trolley**

- Class of Duty ( Mech /Elec) : Class II
- No. Of Driver : 1 no
- C T speed : 12 mts/min
- Motor Used : Sq Cage Induction Motor Crane duty– 6 pole  
Class F/2 HP/40% CDF/150 Starts/hr -  
BB Make
- Type of Drive Proposed for Cross Travel : Floating Shaft Type Drive
- Wheel Housings used for CT : Bracket Type
- Type of Limit Switch Provided : Shunt –2 Way Roller Leaver Type
- Specification of Wheels Used for CT : C 55 Mn 75 Forged Steel and Hardened to  
30 HRC with diameter of 160 mm

### **Long Travel Trolley**

- Class of Duty ( Mech /Elec) : Class II
- No. Of Driver : 1 no
- L T Speed : 15 mts/min
- Type of Drive Proposed for Long Travel : Twin Drive
- Motor Used : Sq Cage Induction Motor Crane duty– 6 pole  
Class F/2 HP/40% CDF/150 Starts/hr -  
BB Make
- Wheel Housings used for LT : Bracket Type
- Specification of Wheels Used for LT : C 55 Mn 75 Forged Steel and Hardened to  
30 HRC with diameter of 300 mm
- Rail Size Considered for LT : 50 mm Sq Bar

### **Structure Considered for fabrication**

- Platform : NA
- Girder for C T beam : Fabricated box type using M S plates
- End Carriages : Fabricated box type using M S Plates
- Type of Trail Cabling for Cross Travel : Through Flexible Trail Cabling
- Material used for Fabrication of crane : M S Conforming to IS 2062
- Painting Details : Two Coats of ROMP – two Coats Enamel paint
- Safety features incorporated in system : Limit Switches for Hoist, LT, CT will be provided

### **Electrical and Other Specifications**

- Control Panel : Own make fabricated
- Cables used : Flexible copper cables
- Limit Switches : Reputed Makes will be used

#### **2. Fabrication and Supply of Bus Bar Arrangement for Electrical supply as per the Following Specs. Rs. 1600/mt**

- Total Length of the Bus Bar : As Per Your Requirement
- Safe track type of enclosed Bus Bar : Safe track
- Capacity of the Bus Bar : 60 amps - GI
- Section used for the Bus Bar Brackets : Enclosed U type channel

### **GENERAL TERMS & CONDITIONS:**

1. Price quoted per unit ex-work. Hyderabad.
2. **Following charges are additional to your account.**
  - ✓ Freight Charge : As actual to be borne by you.
  - ✓ Sales Tax : 18% Extra as applicable
  - ✓ Packing charge : As actual to be borne by you.
  - ✓ Insurance : As actual to be borne by you.
3. **Payment : 50% advance along with order balance before delivery but after inspection at our works.**
4. **Delivery : with 50% advance with in 3 months.**
5. **Validity : One month from the date of submission.**
6. **Inspection : Inspection at our works prior to dispatch.**
7. **Warranty : The machine is warranted for a period of 12 months from the date of dispatch against any manufacturing defects/faulty material or bad workmanship of any part or component but not against any kind of abnormal or improper use of machine. Defective part or component will be replaced or repaired free of cost. Electrical components are outside the scope of this warranty.**

8. **Commissioning** : Erection & commissioning done by you, but required technical support & guidance provide by us at additional cost.

NOTE:

1. Oil is not in scope of our supply.
2. Raw material for trial is to be arranged by you at your cost.

We are sure you will find our offer in line with your requirements. Should you require any further clarification please contact sivaramakrishna 9246221106.Email: md@technomachinetools.in  
Thanking you and assuring you of our best services.

**For Techno Machine Tools**

**T.SIVARAMAKRISHNA**

# TECHNO MACHINE TOOLS

A/15, CO-OPERATIVE INDUSTRIAL ESTATE, BALANAGAR, HYDERABAD

(Machine tool manufacturers)

**T.SIVARAMAKRISHNA**

ME., MBA.

REF :TM/Achuta Reddy /2026-27/355106

DATED: 02-04-2026

to,  
Mr.Achuta Reddy  
M 8985724365

Dear Sir,

**Sub: - SUPPLY OF ROOFING PROFILE ROLL FORMING MACHINE**

With reference to our telephonic conversation regarding your requirement of roll forming machine mainly for Color Coated Roofing Section. We are glad to inform you that we would be in a position to supply you the required equipment. Given below are the required specifications and description of the machine and our terms and conditions.

**Prices**

The cost of Roll forming machine with roofing profile tooling along with Entry guide, Main Roll Forming Machine, Side Guides, Drive System, Cutting Unit and Cutting Die Sets for Rs **22,50,000/- ( Rupees Twenty Two Lakhs Fifty Thousand Only)**

**LIST OT EQUIPMENT**

- 1) MANUAL DE COILER 5 MT CAPACITY WITH 5 HP DRIVE
- 2) ROLL FORMING MACHINE WITH 21 PASSES
- 3) EN 31 ROOFING PROFILE TOOLING
- 4) 7.5 HP DRIVE WITH REDUCTION GEAR BOX.
- 5) COMPLETE ELECTRICALS ALONG WITH AUTOMATION – PLC
- 6) DELIVERY CUTOFF UNIT WITH 5 HP POWERPACK
- 7) TILE PROFILE UNIT
- 8) RUNOUT TABLE
- 9) FILM REEL UNIT
- 10) INTRU SHEAR

## TECHNICAL SPECIFICATION:

## GENERAL DATA

|                              |                                               |
|------------------------------|-----------------------------------------------|
| Productivity                 | : ROLL FORMING CUT TO SIZE PROFILE            |
| Manpower required            | : ONE OPERATOR TWO ASST. REQUIRED             |
| Total Power Required         | : 17.5 HP                                     |
| Set up time                  | : COIL LOADING 2-3 MIN, SHEET FEEDING 3-4 MIN |
| Production capacity          | : 20000 KG PER SHIFT 8 HOURS                  |
| Working hours per day        | : 8-12                                        |
| Line direction               | : LEFT TO RIGHT                               |
| Overall floor space required | : 13 METERS (L) 2 METERS (W) 1.2 METERS (H)   |
| Approx weight                | : 9000 KG                                     |
| Line speed                   | : 3-15 MPM                                    |
| Model No                     | : TM/RF/111                                   |
| Model Type                   | : CRFM                                        |

## MATERIAL SPECIFICATIONS

|                                    |                            |
|------------------------------------|----------------------------|
| Type of material to be processed   | : CR/COLOR COATED/GI/AL    |
| Yield strength                     | : 32-42 KG/MM <sup>2</sup> |
| % Elongation                       | : 18-25                    |
| Shear strength                     | : 40-45 KG/MM <sup>2</sup> |
| Maximum width can be processed     | : 1220 MM                  |
| Minimum width can be processed     | : 1020 MM                  |
| Maximum thickness can be processed | : 0.6 MM                   |
| Mnimum thickness can be processed  | : 0.36 MM                  |

## ENTRY COIL SPECIFICATIONS

|                             |           |
|-----------------------------|-----------|
| Maximum weight of coil      | : 5 TON   |
| Maximum od of coil at entry | : 1600 MM |
| Minimum od of coil at entry | : 600 MM  |

## DE COILER SPECIFICATIONS

|                            |                          |
|----------------------------|--------------------------|
| Model                      | : SINGLE ARM             |
| Load - capacity            | : 5000 KG MAX.           |
| width                      | : 1220MM                 |
| Mandrel movement           | : DIA 450 MM - 550 MM    |
| Mandrel Height from ground | : 1100 MM                |
| Mandrel expansion          | : MANUAL                 |
| Construction               | : M. S. FABRICATED.      |
| Mandrel rotation           | : WITH 5 HP GEARED MOTOR |





## **MILL SPECIFICATIONS**

|                                        |                     |
|----------------------------------------|---------------------|
| Roll shaft diameter                    | : DIA 70 MM         |
| The vertical distance between shafts   | : 330 MM            |
| The horizontal distance between shafts | : 550 MM            |
| Number of forming stations             | : 21 NOS            |
| Drive (AC)                             | : 7.5 HP            |
| Delivery shear                         | : 5 HP {power pack} |
| Speed of the machine                   | : 0-15 meters/max   |
| Shaft material                         | : EN9               |
| Rollers Material                       | : EN31              |
| Hydraulic tank capacity                | : 300 liters        |



## **Description of the equipment**

### **Roll Forming Machine**

#### **Main Base**

The main base is MS fabricated structure and adequately ribbed to minimize the distortion. It is accurately machined on top and bottom surfaces the threaded holes are made on the bed for positioning the stands.

#### **Entry Guide**

The entry side of the machine will be equipped with guide table and the guide wheels bar which will be responsible for centering the leading ends of the strip into the first pass.

#### **Mill stands**

The stands are mounted on the bed of the machine the line alignment can be easily done due to guide ways arranged on the bed of the machine. Each forming head consists of a fixed housing and sliding type out board housing. The mill stands will be arranged to locate shafts mounted on anti-friction bearings. For the top shafts the bearings are housed in the cartridge type bearing blocks. The bottom shaft bearings are located in the bored machined in the housings. The bottom arbors are fixed in position whereas the top arbors along with cartridge blocks could be raised or lowered in vertical guides machined in housings.

#### **Roll shafts**

The roll shafts will be manufactured from quality steel and will be keyed to locate tooling.

#### **Drive**

The drive to the roll former will be by means of a gear box system. The main drive will be provided by means of 7.5 HP motor. The speed of the roll former is variable.

#### **Delivery runout table**

The delivery runout table is with four meters length.

### **Cutoff unit**

The cutoff unit with hydraulic press along with cutting die set will be placed in the machine delivery side.

### **GENERAL TERMS & CONDITIONS:**

9. Price quoted per unit ex-work. Hyderabad.
10. Following charges are additional to your account.
  - ✓ Freight Charge : As actual to be borne by you.
  - ✓ Sales Tax : 18% Extra as applicable
  - ✓ Packing charge : As actual to be borne by you.
  - ✓ Insurance : As actual to be borne by you.
11. Payment : 50% advance along with order,  
: balance 50% after installation and before delivery
12. Delivery : within 8 weeks from date of advance received
13. Validity : One month from the date of submission.
14. Inspection : Inspection at our works prior to dispatch.
15. Warranty : The machine is warranted for a period of 12 months from the date of dispatch against any manufacturing defects/ faulty material or bad workmanship of any part or component but not against any kind of abnormal or improper use of machine. Defective part or component will be replaced or repaired free of cost. Electrical components are outside the scope of this warranty.
16. Commissioning : Erection & commissioning done by you, but required technical support & guidance provide by us at additional cost.

#### **NOTE:**

3. Oil is not in scope of our supply.
4. Raw material for trial is to be arranged by you at your cost.

We are sure you will find our offer in line with your requirements. Should you require any further clarification please contact T. Sivaramakrishna, 9246221106. Email: [md@technomachinetools.in](mailto:md@technomachinetools.in) WhatsApp No: 9849207176

Thanking you and assuring you of our best services.

**For TECHNO MACHINE TOOLS**

**( T. SIVARAMAKRISHNA)**

# TECHNO MACHINE TOOLS

A/15, CO-OPERATIVE INDUSTRIAL ESTATE, BALANAGAR, HYDERABAD

(Machine tool manufacturers)

**T.SIVARAMAKRISHNA**

ME., MBA.

REF :TM/Achuta Reddy /2026-27/355106

DATED: 02-04-2026

to,  
Mr.Achuta Reddy  
M 8985724365

DEAR SIR,

**Sub: - SUPPLY OF Edge Crimping / Arch Crimping MACHINE**

Thank you very much for your enquiry regarding your requirement of Crimping machine mainly for color coated Sections. We are glad to inform you that we would be in a position to supply you the required equipment. Given below are the required specifications and description of the machine and our terms and conditions.

## **Prices**

The cost of Crimping machine along with Power Pack 5 HP and crimping Tool suitable to your profile is **Rs 6,50,000=00 (Six Lakhs Fifty Thousand Only)**

## **Technical Specifications:**

- **Product's feature:**

This crimping roll forming machine is used to curve panel for formed sheet from ZYYX30-200-1000 / suitable profile.

- **Main technical parameters**

- 1) Max. Width of Formed steel sheet: Suitable Profile
- 2) Material thickness: 0.3-0.8mm color coated steel sheet.
- 3) Main motor power : 2.2kw (Depend on final design)

- 4) Hydraulic station power : 3.75 kw (Depend on final design)
- 5) Min. bending radium : 300mm
- 6) Crimping length: min. 25mm, max. Crimping length - no limit.
- 7) Crimping strokes : 12-15 strokes /minute
- 8) Bending : By hydraulic
- 9) Control : PLC control
- 10) Curving roller material : Cr12 mould steel.
- 11) Size of machine : 2500 mm X 1100 mm X 1600 mm (Ht)

#### **GENERAL TERMS & CONDITIONS:**

17. Price quoted per unit ex-work. Hyderabad.
18. **Following charges are additional to your account.**
- ✓ Freight Charge : As actual to be borne by you.
  - ✓ Sales Tax : 18% Extra as applicable
  - ✓ Packing charge : As actual to be borne by you.
  - ✓ Insurance : As actual to be borne by you.
19. **Payment : 50% advance along with order balance before delivery but after inspection at our works.**
20. **Delivery : with 50% advance with in 3 months.**
21. **Validity : One month from the date of submission.**
22. **Inspection : Inspection at our works prior to dispatch.**
23. **Warranty : The machine is warranted for a period of 12 months from the date of dispatch against any manufacturing defects/faulty material or bad workmanship of any part or component but not against any kind of abnormal or improper use of machine. Defective part or component will be replaced or repaired free of cost. Electrical components are outside the scope of this warranty.**
24. **Commissioning : Erection & commissioning done by you, but required technical support & guidance provide by us at additional cost.**

#### **NOTE:**

5. Oil is not in scope of our supply.
6. Raw material for trial is to be arranged by you at your cost.

We are sure you will find our offer in line with your requirements. Should you require any further clarification please contact sivaramakrishna 9246221106.Email: md@technomachinetools.in

Thanking you and assuring you of our best services.

**For Techno Machine Tools**

**T.SIVARAMAKRISHNA**



# ***Techno Machine Tools***

**A/15, CO-OPERATIVE INDUSTRIAL ESTATE, BALANAGAR, HYDERABAD**

(Mfg of shearing machines and press brakes)

**T.SIVARAMAKRISHNA**

**ME,MBA.**

REF :TM/Achuta Reddy /2026-27/355106

DATED: **02-04-2026**

to,  
Mr.Achuta Reddy  
M 8985724365

**Dear Sir,**

**Sub: - QUOTATION FOR HYDRAULIC SHEARING MACHINE**

Thank you very much for your enquiry regarding your requirement of Hydraulic Shearing Machine mainly for MS Sheets. We are glad to inform you that we would be in a position to supply you the required equipment. Given below are the required specifications and description of the machine and our terms and conditions.

| <b>S<br/>No</b> | <b>Description of the unit</b>                                                                                                                                                                   | <b>Offer</b>                                                                  |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|
| 1.              | <b>Conventional</b><br><br>Hydraulic shearing machine with fixed rake angle and shearing capacity 3 Meters and 4 mm MS Sheet, along with Power pack 10.0 HP motor and other electrical fittings. | <b>Rs 8,75,000/-</b><br>(Rupees Eight Lakes<br>Seventy Five<br>Thousand Only) |



**SPECIFICATIONS FOR THE HYDRAULIC SHEARING MACHINE WITH CUTTING  
CAPACITY 3000 M.M. WIDTH AND 4 M.M. THICKNESS.**

- |    |                        |   |                  |
|----|------------------------|---|------------------|
| 1. | CUTTING CAPACITY IN MS | : | 3000 X 4 MM.     |
| 2. | RAKE ANGLE (variable)  | : | 1.5 DEGREES      |
| 3. | STROKES PER MINUTE     | : | 4-6 Nos          |
| 4. | NUMBER OF HOLD DOWNS   | : | 13 Nos           |
| 5. | BACK GAUGE ( manual)   | : | 550 M.M.         |
| 6. | MOTOR HP               | : | 10 HP (Crompton) |
| 7  | OVERALL DIMMENSIONS    | : |                  |
|    | a) LENGTH              | : | 3500 M.M.        |
|    | b) BREADTH             | : | 1200 M.M.        |
|    | c) HEIGHT              | : | 1800 M.M.        |
| 8. | BED SIZE.              | : | 3000 X 550 M.M.  |
| 9. | Balade Thickness       | : | 24 mm            |

**GENERAL TERMS & CONDITIONS:**

25. Price quoted per unit ex-work. Hyderabad.
26. Following charges are additional to your account.
- ✓ Freight Charge : As actual to be borne by you.
  - ✓ Sales Tax : 18% Extra as applicable
  - ✓ Packing charge : As actual to be borne by you.
  - ✓ Insurance : As actual to be borne by you.
27. Payment : 50% advance along with order balance before delivery but after inspection at our works.
28. Delivery : with 75% advance 1 months / With 50% advance 2 months / With 30% - 3 months from date of advance received
29. Validity : One month from the date of submission.
30. Inspection : Inspection at our works prior to dispatch.
31. Warranty : The machine is warranted for a period of 12 months from the date of dispatch against any manufacturing defects/ faulty material or bad workmanship of any part or component but not against any kind of abnormal or improper use of machine. Defective part or component will be replaced or repaired free of cost. Electrical components are outside the scope of this warranty.
32. Commissioning : Erection & commissioning done by you, but required technical support & guidance provide by us at additional cost.



NOTE:

7. Oil is not in scope of our supply.
8. Raw material for trial is to be arranged by you at your cost.

We are sure you will find our offer in line with your requirements. Should you require any further clarification please contact 9246221106

Thanking you and assuring you of our best services

**For Techno Machine Tools**

**( T. Sivaramakrishna)**



# **Techno Machine Tools**

**A/15, CO-OPERATIVE INDUSTRIAL ESTATE, BALANAGAR, HYDERABAD**

(Mfg of shearing machines and press brakes)

**T.SIVARAMAKRISHNA  
ME., MBA.**

---

REF :TM/Achuta Reddy /2026-27/355106

DATED: **02-04-2026**

to,  
Mr.Achuta Reddy  
M 8985724365

**Dear sir,**

**Sub :- Supply of HYDRAULIC PRESS BRAKE MACHINE.**

Thank you very much for your enquiry regarding your requirement of hydraulic press brake. We are glad to inform you that we would be in a position to supply you the required equipment. Given below are the required specifications and description of the machine and our terms and conditions.

**PRESS BRAKE :**

- 1) Size : 3000 X 4 M.M.  
2) Tonnage : 100 M.T.

| S No | Description of the unit                                                                                                                                                  | Offer                                                            |
|------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------|
| 1.   | Hydraulic Press Brake with bending capacity 3.0 Meters and 4 mm MS Sheet, 100 MT load capacity with Power pack of 10 HP motor along with one set Standard Die and Punch. | <b>Rs 8,50,000/-</b><br>(Rupees Eight Lakhs fifty Thousand Only) |

**GENERAL TERMS & CONDITIONS:**

33. Price quoted per unit ex-work. Hyderabad.  
34. **Following charges are additional to your account.**

- ✓ Freight Charge : As actual to be borne by you.
- ✓ Sales Tax :18% Extra as applicable
- ✓ Packing charge : As actual to be borne by you.
- ✓ Insurance : As actual to be borne by you.
- 35. Payment : 50% advance along with order balance before delivery but after inspection at our works.
- 36. Delivery : with in 8-10 weeks
- 37. Validity : One month from the date of submission.
- 38. Inspection : Inspection at our works prior to dispatch.
- 39. Warranty : The machine is warranted for a period of 12 months from the date of dispatch against any manufacturing defects/ faulty material or bad workmanship of any part or component but not against any kind of abnormal or improper use of machine. Defective part or component will be replaced or repaired free of cost. Electrical components are outside the scope of this warranty.
- 40. Commissioning : Erection & commissioning done by you, but required technical support & guidance provide by us at additional cost.

**NOTE:**

- 9. Oil is not in scope of our supply.
- 10. Raw material for trial is to be arranged by you at your cost.

We are sure you will find our offer in line with your requirements. Should you require any further clarification please contact 9246221106  
Thanking you and assuring you of our best services

**For Techno Machine Tools**

**( T. Sivaramakrishna)**

**SPECIFICATIONS FOR THE HYDRAULIC PRESS BRAKE MACHINE WITH 3000 M.M. WIDTH AND 4M.M. THICKNES.**

- 1. Tonnage : 100 M.T.
- 2. Clearance between Housings : 2500 M.M.
- 3. Bending capacity in M.S. : 3000 x 0M.M.
- 4. Ram stroke. : 150 M.M.

|     |                  |   |                                               |
|-----|------------------|---|-----------------------------------------------|
| 5.  | Open height.     | : | 350 M.M.                                      |
| 6.  | Closed height.   | : | 200 M.M.                                      |
| 7.  | Depth of Throat. | : | 300 M.M.                                      |
| 8.  | Ram speeds.      |   |                                               |
|     | a) Approach.     | : | 22 M.M. per Sec.                              |
|     | b) Pressing.     | : | 3 M.M. per Sec.                               |
|     | c) Return.       | : | 40 M.M. per Sec.                              |
| 9.  | Motor capacity.  | : | 10 H.P. (Crompton)                            |
| 10. | Punch.           | : | 3000 x 185 x 65 M.M.<br>( 'GROOSE NECK' type) |
| 11. | Bed size.        | : | 3000 x 255 x 75 M.M.                          |
| 12. | Cost of Mechine. | : | Rs.8,50,000/- + Taxes.                        |
| 13. | Mode of payment. | : | As per the quotation.                         |
| 14. | Delivery.        | : | As per the quotation.                         |



**For Techno Machine Tools**

**( T. Sivaramakrishna)**