



Techno Machine Tools

(MANUFACTURERS OF MACHINE TOOLS)

T SIVARAMAKRISHNA
ME., MBA.

TMT/ INDHAN GREEN ENERGIES/S0596/2025

09-12-2025

To,
INDHAN GREEN ENERGIES
Email: Indhangreenenergies@zohomail.in
Address: Bramilli compound street,
West Godavari Dist, Andhra Pradesh-534275
GSTIN: 37AAKFI5458E1Z5
Mobile : +91 80967 00556

Dear Sir,

SUB: SUPPLY OF Shredders

We thank you for your inquiry regarding Conveyor's with capacity of 10 TPD.

Capacity : 10 TPD	
Type of shredder	Single shaft
Application of shredder	Shredder for Municipal Solid Waste containing various objects such as plastic bottles, plastic waste thrash waste, organic waste etc.
Capacity of shredder taking 8 hrs per day operation in tones(1000 Kg)	10
Type of Drive for shredder	Electrical
Type of Rotary Shaft	Cylindrical - Solid router with blades fitted
Input Electrical Supply	Three phase (440 V, 50 Hz)
Motor Power for main drive in HP @ 1440 rpm	7.5 HP
Motor power for pusher drive in HP, 1440 RPM	1
Motor class	IE2
Type of control panel	Manual Based
Warranty (with free spare parts and free service) on machine	1
Number of preventative maintenance visits during warranty (number per annum)	2
Tool kit for Repair and maintenance to be supplied	NO
Gear box for speed reduction	YES
Availability of Door Open Cut off switch	NO
Material of Housing Enclosure	Mild steel
Material of Rotary Shaft	Mild steel
Type of Conveyor provided with Single shaft shredding machine	Slider Bed Type or sorting conveyor
Range of Capacity handled by Conveyor in TPD taking 8 hrs duty per day	6-10
Width of Belt for slider bed type / trough conveyor in mm (with tolerance ± 10 mm)	600
Diameter of Driving Pulley for slider bed type/ trough conveyor in mm (with tolerance ± 10 mm)	220
Diameter of Driven Pulley for slider bed type/trough conveyor in mm (with tolerance ± 5 mm)	230
Type of Screw Conveyor	Horizontal Type Screw Conveyor

The price details of the Shredders for 10TPD are **Rs 8,00,000(Eight Lakhs only)**.

Capacity : 50 TPD

Parameter	Specification
Type of Shredder	Twin Shaft
Shape of Shaft	Horizontal Hexagonal Shaped
Material of Housing Enclosure	Mild Steel (confirming to IS:2062)
Capacity	2 TPH
Motor specification	44.7kW (66HP), copper wiring, 4 pole, 3 phase
Hopper	Mild Steel (confirming to IS: 2062)
Base Frame	Mild Steel wide-flange beam of welded construction
Material of Construction of Mulcher	Shredder blades of tool steel having high wearing resistance and shock proof
Mulcher Cleaner	Made of alloy steel to clean the shredder knives.
Painting	Primer Coated with gloss finishing
Housing	Outdoor weather protection metal sheet Housing c/w double layer panel's door .
Inside dimensions of shredder chamber in mm x mm with tolerance ± 10 mm (W x H)	1218 x 250
Opening of loading hopper in mm x mm with tolerance ± 10 mm	600 x 800
Material of Shaft	Mild Steel confirming to IS: 3688- 2004 (1990)
Rotation Speed (Max)	200 RPM
Over all Dimensions of shredding machine in LxWxH in mm	3757 x 1050 x 2054
Advanced Control Panel	Includes slow start VFD control, full function control panel, run/trip indicating light, start/stop push button, emergency push button stop, yellow light indicator on reverse motion, optical indicator to show operation, main switch, auto-reverse and stop in case of overfeeding, control panel, manual push button to reverse and forward motions, low power consumption yet high output, robust construction and easy maintenance design, minimum cutting knife wear, operator friendly, etc.

The price details of the Shredders Of 50TPD are **Rs 18,00,000(Eighteen Lakhs only)**.

Capacity : 100 TPD

Parameter	Specification
Type of Shredder	Twin Shaft
Shape of Shaft	Horizontal Hexagonal Shaped
Material of Housing Enclosure	Mild Steel (confirming to IS:2062)
Capacity in TPH	2TPH
Motor Power (kW)	44.7kW (66HP), copper wiring, 4 pole, 3 phase
Hopper	Mild Steel (confirming to IS: 2062)
Base Frame	Mild Steel wide-flange beam of welded construction
Material of Construction of Mulcher	Shredder blades of tool steel having high wearing resistance and shock proof
Mulcher Cleaner	Made of alloy steel to clean the shredder knives.
Painting	Primer Coated with gloss finishing
Housing	Outdoor weather protection metal sheet Housing c/w double layer panel's door.
Inside dimensions of shredder chamber in mm x mm with tolerance ± 10 mm (W x H)	1218 x 250
Opening of loading hooper in mm x mm with tolerance +10 mm	600 x 800
Material of Shaft	Mild Steel confirming to IS: 3688-2004 (1990)
Rotation Speed (Max)	200 RPM
Over all Dimensions of shredding machine in LxWxH in mm	3757 x 1050 x 2054
Advanced Control Panel	Includes slow start VFD control, full function control panel, run/trip indicating light, start/stop push button, emergency push button stop, yellow light indicator on reverse motion, optical indicator to show operation, main switch, auto-reverse and stop in case of overfeeding, low power consumption on no feeding, control panel to fix problem without entering the shredding machine, manual push button to reverse and forward motions, low power consumption yet high output, robust construction and easy maintenance design, minimum cutting knife wear, operator friendly, etc.

The price details of the Shredders Of 100TPD are Rs **28,00,000(Twenty-Eight Lakhs only)**.

GENERAL TERMS & CONDITIONS:

- Price quoted per unit ex-work. Hyderabad.
Following charges are additional to your account.
 - ✓ Freight Charge : As actual to be borne by you.
 - ✓ Sales Tax : 18% GST
 - ✓ Packing charge : As actual to be borne by you.

- ✓ Insurance : As actual to be borne by you.
- 1. Payment : 75% advance along with order balance before delivery but after inspection at our works.
- 2. Delivery : with 75% advance 1month / With 50% advance 2 months / With 30% - 4 months from date of advance received
- 3. Validity : One month from the date of submission.
- 4. Inspection : Inspection at our works prior to dispatch.
- 5. Warranty : The machine is warranted for a period of 12 months from the date of dispatch against any manufacturing defects/ faulty material or bad workmanship of any part or component but not against any kind of abnormal or improper use of machine. Defective part or component will be replaced or repaired free of cost. Electrical components are outside the scope of this warranty.
- 6. Commissioning : Erection & commissioning done by you, but required technical support & guidance provide by us at additional cost.

NOTE:

- 1. Oil is not in scope of our supply.
- 2. Raw material for trial is to be arranged by you at your cost.

We are sure you will find our offer in line with your requirements. Should you require any further clarification please contact 9246221106

Thanking you and assuring you of our best services.

For TECHNO MACHINE TOOLS

(T. SIVARAMAKRISHNA)