

Hive UDF

•••

User Defined Functions in Hive

IMPORTANT

Copyright Infringement and Illegal Content Sharing Notice

All course content designs, video, audio, text, graphics, logos, images are Copyright© and are protected by India and international copyright laws. All rights reserved.


Permission to download the contents (wherever applicable) for the sole purpose of individual reading and preparing yourself to crack the interview only. Any other use of study materials – including reproduction, modification, distribution, republishing, transmission, display – without the prior written permission of Author is strictly prohibited.

Trendytech Insights legal team, along with thousands of our students, actively searches the Internet for copyright infringements. Violators subject to prosecution.



Create a UDF to convert String to Upper case

Open eclipse & Create a new java Project (udf_example)
Inside that create a New Class




Package name: udf_example

Class Name: DataStandardization



What was the pain point?

Copy the given code in this DataStandardization.java file



You will see few errors because some of the relevant jars are missing



Below is the Code


```
package udf_example;
import org.apache.hadoop.hive.ql.exec.UDF;
public class DataStandardization extends UDF {
public String evaluate(String input){
if(input==null)
return null;
return (input.toString().toUpperCase());
```



Download the necessary jar


Link to download the jar:


https://mvnrepository.com/artifact/org.apache.hive/hive-exec/1.2.2





Add the Jar hive-exec-1.2.2.jar





After adding the jar, you can see the errors are gone.



Let us create a Hive Table & Load Data

use trendytech;

create table if not exists sample_table(name string,count int) row format delimited fields terminated by ',' lines terminated by '\n' stored as textfile;

load data local inpath '/home/cloudera/Downloads/sample_data.txt' overwrite into

table sample_table;


```
hives create table if not exists sample table[same string.count int) row format delimited fields terminated by "," lime taken 0.328 seconds
Time taken 1.517 seconds
Time taken 1.517 seconds
Time taken 1.517 seconds
Time taken 1.517 seconds
Time taken 1.527 seconds
Time taken 1.527 seconds
Time taken 1.527 seconds
Time taken 1.537 seconds
Time taken 1.537 seconds
Time taken 1.537 seconds
Time taken 1.538 seconds, Fetched: 16 row(s)
```



export the jar file for the java project

Right click project -> export -> jar file

With this give the desktop path and jar will be created on Desktop.





Add the Jar & Create temporary function

ADD JAR /home/cloudera/Desktop/udf_example.jar;

create temporary function standardize as 'udf_example.DataStandardization';

```
hive> ADD JAR /home/cloudera/Desktop/udf_example.jar;
Added [/home/cloudera/Desktop/udf_example.jar] to class path
Added resources: [/home/cloudera/Desktop/udf_example.jar]
hive> [/home/cloudera/Desktop/udf_example.jar]
hive> create temporary function standardize as 'udf_example.DataStandardization';
DK
Time taken: 0.003 seconds
hive> []
```



Now we are all set, try calling this UDF on a column in a table

select standardize(name) from sample_table;

```
hive> select standardize(name) from sample table;
OK
NHOL
ALBERT
MARK
FRANK
LOOPA
LUI
JOHN
NHOL
LESA
LESA
PARS
LEO
LEO
LOCK
BHUT
LIO
Time taken: 0.205 seconds, Fetched: 16 row(s)
hive>
```



What's the issue?

These are temporary things. This jar & function is valid only for current session. That means if you come out of hive and go back in, then you won't be able to call this function.



Create a permanent function

For this we need to have our jar in HDFS

Let us transfer the jar to HDFS

hadoop fs -put udf_example.jar /user/cloudera

[cloudera@quickstart Desktop]\$ hadoop fs -put udf_example.jar /user/cloudera
[cloudera@quickstart Desktop]\$



Create a permanent function

Now in Hive create a permanent function

CREATE FUNCTION standardize_permanent AS 'udf_example.DataStandardization' using JAR 'hdfs://localhost:8020/user/cloudera/udf_example.jar';

```
hive> CREATE FUNCTION standardize_permanent AS 'udf_example.DataStandardization' using JAR 'hdfs://localhost:8020/user/cloudera/udf_example.jar';
converting to local hdfs://localhost:8020/user/cloudera/udf_example.jar
Added [/tmp/dcee3d91-a797-48fb-8dcb-c598c7629416_resources/udf_example.jar] to class path
Added resources: [hdfs://localhost:8020/user/cloudera/udf_example.jar]
OK
Time taken: 0.075 seconds
hive> |
```



Try calling the function now.

select standardize_permanent(name) from sample_table;

```
hive> select standardize permanent(name) from sample table;
oĸ
JOHN
ALBERT
MARK
FRANK
LOOPA
LUI
NHOL
JOHN
LESA
LESA
PARS
LEO
LEO
LOCK
BHUT
LIO
Time taken: 0.085 seconds, Fetched: 16 row(s)
hive>
```



We learnt to Create a Hive UDF

Happy Learning!!!



5 Star Google Rated Big Data Course

LEARN FROM THE EXPERT



9108179578

Call for more details



Follow US

Trainer Mr. Sumit Mittal **Phone** 9108179578 **Email** trendytech.sumit@gmail.com https://trendytech.in/courses/big-data-online-training/ Website https://www.linkedin.com/in/bigdatabysumit/ LinkedIn **Twitter** @BigdataBySumit bigdatabysumit Instagram https://www.facebook.com/trendytech.in/ **Facebook** Youtube TrendyTech