PRELIMINARY DESIGN – FOR MDR INTEGRATION

Raspberry Pi Pico Electronics Architecture

Process flow, component rationale and 3K design-criteria fit

RTC 2027 Student 3K | Mission Design Report: electronics contribution | 4 November 2026

Scope and status. This is the electronics team's contribution draft to the team's single MDR; it is not a separately submitted report and not a completed flight design. Competition constraints are attributed to the organiser documents [1], [2], [3]. Thresholds, rates, pin allocations, power figures and the thermal payload are *team proposals* marked as such, and require simulation, approval and later testing in line with the MDR/PDR/CDR maturity expectations [3], [4]. Manufacturer figures are quoted from the cited datasheets and should be re-checked against the exact module purchased.

1. MDR deliverable coverage and ownership

The nine deliverables A1–A9 below are the *electronics-team handover requirements* identified from the organiser's MDR template and scoring matrix. They are not nine separate submission files. All elements are addressed in this technical annex, but some entries remain provisional until the responsible team confirms the subsystem choices. The final team MDR remains a single slide-style, searchable PDF with the organiser's page limit [3], [5].

ID	MDR deliverable	Included evidence and location	Completion status
A1	Functional requirements	Numbered, source-linked system and subsystem requirements; §2.	Draft complete
A2	Architecture	Three power domains, sensors, storage, recovery and GPS boundaries; §5.	Draft complete
A3	Component selection	Pico rationale, alternatives, datasheet limits, interfaces; §7.	Draft complete
A4	Performance specifications	Sampling and measurement assumptions; power/data budgets; decision parameters.	Provisional / simulation pending
A5	Flight/recovery sequence	Detailed launch–apogee–descent, fault paths and dual-stage release flows; §9.	Draft complete
A6	Redundancy and safety	Independent power/control and *provisional* release-interface baseline; §10, §11.	Mechanism approval pending
A7	Mass, power and cost	Costed Shopee-linked BOM, assumptions, allowances, unquoted items and subsystem mass; §17.	Provisional / quotes pending
A8	Development/verification	Dated pre-MDR actions, owners, later-stage roadmap, tests and acceptance criteria; §21.	Owners to assign
A9	Preliminary FMEA	Scored failure modes and mitigations with owners; §20.	Provisional rankings

Proposed measurable mission success definitions

These are **team targets for MDR**, not thresholds imposed by the organiser. Their final values shall be approved alongside the complete rocket mission objectives and revised from simulation and risk assessment [3], [5].

Objective	Proposed measurable success	Evidence
Flight-data evidence	Timestamped altitude, derived velocity, acceleration and official GPS track retrievable, with completeness and quality flags reported.	Flight logs + organiser beacon
Dual-stage recovery	Drogue event at verified apogee and main event at team-selected lower altitude; intended final descent $< 12\,\mathrm{m/s}$, demonstrated later by analysis and testing.	Deployment test + flight review
Electrical continuity	Each operating domain has a measured endurance of at least 1.5 h; present preliminary budget at MDR.	Power calculation, later test
Additional thermal mission	Two timestamped DS18B20 series valid for $\geq 90\%$ of each required phase; phasewise ΔT and uncertainty documented.	Retrieved data + completeness report
Post-landing tracking	Official beacon reports location and can be used to recover or track the rocket.	Beacon integration/range test

2. Numbered functional requirements and traceability

Each requirement is expressed as a *shall* statement and identifies (i) its RTC source or team-proposed status, (ii) the accountable subsystem and (iii) a planned verification activity. The source clauses are regulatory bases; sampling

rates and payload thresholds are preliminary team choices. Structure follows the requirements-matrix example [6].

ID	Requirement	Source / status	Owner; verification
AV-01	The rocket shall obtain and retain altitude, velocity, acceleration and GPS-trajectory records.	App. 03, Sec. 2.1 [1]	Avionics + GPS; V-02, V-10
AV-02	The avionics shall distinguish launch, ascent, apogee, descent and landing states and record event times.	App. 03, Sec. 4.2; team method	Avionics; V-01
AV-03	The flight logger shall use a Raspberry Pi Pico with provision for sensing, timestamping and local storage.	Team design choice; [7]	Avionics; V-02
AV-04	The system shall preserve flight data despite a radio-link outage or unavailable radio link.	Team design choice supporting AV-01	Avionics; V-02, V-10
AV-05	The design shall address impact, vibration and sensor error and plan representative ground tests.	App. 03, Sec. 4.1.2 [1]	Avionics; V-01, V-09
RC-01	The recovery system shall provide a drogue release at apogee.	App. 03, Sec. 4.2.2.4	Recovery; V-01, V-05
RC-02	The recovery system shall provide a main release at a selected lower descent altitude, within the organiser's permitted range.	App. 03, Sec. 4.2.2.4; App. 08	Recovery; V-01, V-05
RC-03	Recovery activation shall be independent or redundant, including relevant sensors, power and activation functions.	App. 03, Sec. 4.1.3	Recovery; V-05
RC-04	Recovery release arrangements shall have appropriate redundancy against single failures.	App. 03, Sec. 4.2.2.2	Recovery; V-05, FMEA
RC-05	A safe/armed method and observable status shall prevent unintended activation during preparation.	App. 03, Sec. 4.6	Recovery; V-05, V-11
RC-06	The parachute/recovery system shall be designed for water-contact descent speed below 12 m/s.	App. 03, Sec. 4.2.4	Recovery + structures; analysis
PW-01	The rocket electrical systems shall operate for more than 1.5 hours in normal operation.	App. 03, Sec. 4.7; App. 08	Electronics; V-06
PW-02	Batteries and critical wiring shall remain secured under expected launch accelerations and vibration.	App. 03, Secs. 4.4, 4.7	Electronics + structures; V-06, V-11
PW-03	Independent recovery channels shall not share a power supply whose loss disables both channels.	Team mitigation for RC-03	Recovery; V-04, V-05
GPS-01	The rocket shall carry the organiser-standard 3K GPS beacon.	App. 03, Sec. 5.1	GPS lead; inspection
GPS-02	The GPS integration shall permit position transmission and retrieval of the position history.	App. 03, Sec. 5.1; App. 08	GPS lead; V-10
RF-01	Any team-installed transmitter shall comply with applicable frequency and power rules.	App. 03, Sec. 4.1.4	GPS/communications; inspection
PL-01	The rocket shall carry an additional mission payload distinct from the standard GPS beacon.	App. 03, Sec. 2.2	Payload lead; inspection
PL-02	The payload shall follow an allowed operational/retention configuration and not interfere with recovery.	App. 03, Sec. 7.1.1	Payload + integration; inspection
PL-03	The additional payload shall not contain prohibited stored-energy devices or living vertebrates.	App. 03, Secs. 7.1.2, 7.1.5	Payload lead; inspection
PL-04	The proposed thermal payload shall obtain two aligned temperature histories and meet declared mission success criteria.	Team mission proposal; [3]	Payload; V-08
INT-01	Electrical interfaces, wiring and mounting shall be identified, supported and strain relieved.	App. 03, Sec. 4.4	Integration; V-11
INT-02	The MDR shall include a BOM, schedule, responsibility allocation, risks and verification plan.	App. 01; App. 07 [3], [5]	Team lead; review

3. Technical issue closure checklist

The review of the previous draft raised six technical issues. This revision addresses each one as follows. "Status" states honestly what is closed in the document and what still needs team input or hardware evidence.

ID	Technical issue	Closure action in this revision	Status	Where
☐ A	Three Picos are not automatically independent recovery channels.	Common-cause analysis; diverse barometer and algorithm in channel B; release-interface requirements R1–R4; fault-injection tests.	Analysis done; release mechanism still TBD (recovery lead).	Sec. 10
☐ B	MPU6050 ±16 g range is not justified against the flight.	Specific-force equation, input list and a numerical decision gate for adding the ±200 g ADXL375; saturation flag.	Rule defined; needs Pioneer-10K thrust curve and simulation TBD.	Sec. 12

ID	Issue	Closure action (continued)	Status	Where
☐ C	Watchdog scratch registers do not protect against power loss.	Corrected claim; reset-cause table; FRAM checkpoint with CRC and double slots; hold-up capacitance; cold-boot rules; revised Fig. 2.	Design defined; to be demonstrated by V-04.	Sec. 13
☐ D	Thermal payload lacks a defined scientific objective.	Research question, hypothesis, uncertainty budget, completeness and retrieval criteria, and what new information results.	Defined; accuracy to be demonstrated by V-08.	Sec. 14
☐ E	Budget omits recovery controllers, protection, mounting and verification.	Tiered budget separating Shopee-priced parts, allowances and unquoted items, with spares, test costs, contingency and mass estimate.	Provisional; release hardware and GPS beacon unquoted.	Sec. 17
☐ F	GPS and flight-data outputs lack a defined interface.	Post-flight data pipeline, time-alignment method, merged table and per-output availability criteria.	Defined; beacon file retrieval method to confirm with organiser.	Sec. 18

4. Design drivers: how the Pico design meets the 3K criteria

The design uses **three separate Raspberry Pi Pico boards** (RP2040) [7], [8]: one *logger/payload* Pico that never commands recovery, and two *independent recovery* Picos (primary and backup), each with its own barometer and battery. This keeps required flight-data logging and the thermal experiment from sharing a failure path with parachute deployment, while using one familiar, low-cost, well-documented platform for every computer in the rocket.

3K criterion	Design response	Basis / status
Record altitude, velocity, acceleration, GPS trajectory	Logger Pico records BMP280 pressure-altitude and MPU6050 acceleration with timestamps; velocity is derived by filtering/fusion; GPS track is taken from the organiser beacon and merged post-flight (Sec. 18).	[1] Sec. 2.1; proposed method
Detect launch, apogee, descent	Multi-condition state machine (Figs. 2–3) with lock-outs and time-out back-ups.	[1] Sec. 4.2.2.4; proposed
Two-stage recovery: drogue at apogee, main at lower altitude	Two recovery Picos each execute both events; main altitude selected in the 150–450 m window, below the 500 m inspection criterion.	[1] 4.2.2.4; [9] Row 8
Independent / redundant activation, release redundancy	Primary and backup recovery Picos, separate batteries, separate barometers, diverse barometer and algorithm in B, outputs held low in hardware (Fig. 5); common-cause analysis in Sec. 10.	[1] 4.1.3, 4.2.2.2; mechanism TBD
Safe/armed states, arming confirmation	Arming switch gates power; outputs forced low by pull-downs; launch-inhibit logic; buzzer/LED status code.	[1] 4.6.3–4.6.7
Vibration, impact, sensor error	Plausibility gates, filtering, CRC records, strain-relieved connectors, watchdog restart and FRAM state checkpoint (Sec. 13).	[1] 4.1.2, 4.4
> 1.5 h electrical operation	Single Li-ion cell per Pico; load ≈56 mA estimated, 200 mA design basis (Sec. 16).	[1] 4.7.2; [9] Row 6
Official GPS tracker	Separate, organiser-standard beacon, own power, no electrical dependence on Pico boards.	[1] 2.2, 5.1
Additional payload	Two DS18B20 probes read by the logger Pico: internal avionics-bay vs inner-wall temperature difference with defined research question (Sec. 14); retained in rocket, no radio, no stored-energy device.	[1] 7.1; team proposal
No unapproved radio emissions	Plain Pico (not Pico W): no on-board radio.	[1] 4.1.4; [7]

5. System architecture

Critical interface rule. The logger never commands recovery, and nothing on Domain L (SD card, thermal probes, buzzer) can block a recovery decision. Cross-links between domains are limited to a common ground reference at the release interface if the recovery team requires it; no shared supply [1].




Figure 1: Electronics architecture. Three Pico boards in three power domains; the logger can fail without affecting recovery, and recovery A can fail without affecting recovery B. A FRAM checkpoint memory on each Pico (I^2C1, Sec. 13) is omitted for clarity. Illustrative; wiring and fault independence remain to be approved.

6. Why the Raspberry Pi Pico

RP2040 / Pico feature	What it provides	Benefit to the 3K rocket
Dual Cortex-M0+ cores, up to 133 MHz	Two independent cores sharing memory [8].	Core 0 senses and decides; core 1 does slow SD writes, so storage latency cannot delay sampling (Fig. 4).
264 kB on-chip SRAM	Fast RAM for buffers [8].	A 5 s pre-trigger and write-ahead buffer at 24 B × 200 Hz uses about 24 kB (≈9% of SRAM).
Hardware I^2C, SPI, UART, ADC	Two I^2C, two SPI, two UART, 12-bit ADC inputs [8].	Covers IMU/baro (I^2C), SD (SPI) and battery-voltage monitoring without extra chips.
Programmable I/O (PIO)	Eight state machines for custom protocols [8].	Cycle-exact 1-Wire for DS18B20 without blocking the CPU.
Watchdog with scratch registers	Reset timer; scratch registers survive a watchdog reset but not a power-on reset [8].	A watchdog reset recovers flight state (Fig. 2); genuine power loss needs separate checkpointing (Sec. 13).
Wide supply: VSYS 1.8–5.5 V	On-board buck-boost supply to 3.3 V [7].	A single 3.0–4.2 V Li-ion cell powers the board directly; the rail holds as the cell discharges.

Feature	What it provides	Benefit (continued)
No radio (Pico, not Pico W)	Plain board without Wi-Fi/Bluetooth [7].	Avoids unapproved emissions from the rocket [1].
Open C/C++ SDK, SWD debug, UF2 boot	Free toolchain and bootloader [10].	Rapid iteration, scripted builds, and the same toolchain on all three boards.
Low cost and availability	Retail boards at a few ringgit, drop-in spares.	Three flight computers plus spares fit a student budget; identical hardware simplifies sparing.

Alternatives considered. An 8-bit AVR such as the ATmega328P has only 2 kB of SRAM [11], too little for a buffered logger plus filtering. ESP32 devices offer more processing but include Wi-Fi/Bluetooth radios [12] that must be disabled or justified under the radio rules [1]. The Pico gives enough memory and I/O without a radio at similar cost.

Known Pico limits and mitigations. The Cortex-M0+ has no hardware FPU [8]; at 200 Hz the filter workload is small, but fixed-point or measured float timing will be checked. Flash is external (XIP), so *no flash writes during flight*; recovery events are kept in RAM and dumped after landing [8], [10]. A Pico dev board is not qualified flight hardware: the independence of A and B, the watchdog, hard-wired pull-downs and testing are what give confidence, not the board itself. The Pico operating range is −20 to +85 °C [7]; the bay temperature is measured by the payload.

7. Component-by-component rationale

Component	Role	Rationale and fit to 3K criteria	Limit / mitigation
Pico L (logger)	Flight data, state estimate, thermal payload, status.	Satisfies mandatory output list [1]; isolates non-safety functions from recovery.	Not a recovery path. Verified by Fig. 1 separation.
Pico A / Pico B (recovery)	Independent apogee and main-altitude logic and output control.	Redundant activation and release redundancy [1]; identical code base reduces effort, separate boards and cells remove single points of failure.	Common-cause risk reduced by diversity, not eliminated (Sec. 10).
BMP280 (logger, recovery A)	Pressure/temperature → altitude.	Pressure range 300–1100 hPa covers sea level to well above 3 km (≈701 hPa at 3 km in a standard atmosphere); relative accuracy about ±0.12 hPa (≈ ±1 m) [13]. Barometric altitude is the standard method for apogee and main-deployment decisions.	Port must see static pressure, vented away from fast airflow; lock-out near burnout/transonic transients; absolute offset removed by pad baseline.
MPU6050	Acceleration (and angular rate) for launch/burnout detection and acceleration record.	16-bit ADC, programmable ±2 to ±16 g, 400 kHz I^{2}C [14], [15]; ±16 g gives 2048 LSB/g, ample resolution.	Range decision gate for the ±200 g ADXL375 [16] in Sec. 12; saturation flagged; gyro ±2000°/s limits roll-rate capture.
DS18B20 ×2	Payload temperatures: avionics bay and inner airframe wall.	Digital 1-Wire, factory calibrated, −55 to +125 °C, ±0.5 °C (from −10 to +85 °C), selectable resolution up to 12-bit [17]; many sensors share one wire; 1 Hz sampling matches the conversion time.	Probe thermal lag; mounting bias; cable strain relief. Powered normally (not parasitic).
microSD + SPI module	Non-volatile flight log.	SD cards support SPI mode [18] and are handled by the open FatFs library [19]; ≈26 MB for 90 min at 4.8 kB/s, so even small cards are oversized.	Use a 3.3 V-native socket and a ≤32 GB FAT32 card; log with 512 B blocks and 1 s syncs; test under vibration.
1S Li-ion cell per board (A, B, L)	Power.	Compact, high energy; 3.0–4.2 V maps to the Pico VSYS window [7]; separate cells keep faults isolated (battery safety per [1] 4.7).	Needs protection circuit, fuse, secure holder; verify endurance > 1.5 h.
MS5611 barometer (recovery B)	Diverse second barometer for channel B.	A different sensor part avoids a shared systematic fault or supply-chain defect in a single part number [20], [21].	Different driver and calibration maths; allowance in budget, price unquoted.
I^{2}C FRAM (each Pico)	Non-volatile state checkpoint.	Survives power loss, writes in well under 1 ms and is not subject to the flash-write restriction in flight [8], [22].	Separate bus (I^{2}C1); CRC and double-slot writes (Sec. 13).

Component	Role	Rationale (continued)	Limit / mitigation
Arming switch + pull-downs	Safe/armed states.	Hard power gate and gate pull-downs keep outputs low regardless of software state, supporting the safe/armed rules [1].	Accessible from outside the rocket; status code on buzzer/LED.
MOSFET gate drivers + continuity sense	Switch the release device, check the circuit.	Logic-level MOSFETs let 3.3 V GPIO switch higher currents; low-current continuity check proves wiring without activating the release.	Device current and voltage TBD; flyback/EMI protection required.
Buzzer + LED	Self-test and locator.	Immediate pad confirmation of normal operation/arming status [1]; post-landing locator aid.	Not relied on for any flight decision.
JST-XH, labelled harness, PCB/protoboard	Interconnect.	Locking connectors, strain relief and labelled wiring support the vibration and wiring rules [1].	Retention and pull tests.
Official GPS beacon	Location after landing.	Required organiser equipment; kept electrically separate [1].	Installation and cost to confirm.

8. Interfaces and pin allocation (proposed)

Pico	Signal group	Proposed allocation and notes
Logger (L)	I^2C0 (GP4 SDA, GP5 SCL), 400 kHz	BMP280 and MPU6050 on one bus; 4.7 kΩ pull-ups (breakouts may already add them). Keep leads short [15].
Logger (L)	SPI0 (GP16–GP19)	microSD, 3.3 V logic; CS pull-up.
Logger (L)	1-Wire via PIO (GP15)	4.7 kΩ pull-up; both DS18B20 on one bus, addressed by ROM code, conversion started for both together.
Logger (L)	ADC0 (GP26)	Cell voltage via resistor divider.
Logger (L)	GP14 buzzer, GP25 LED	Status codes only.
Recovery A/B	I^2C0 (GP4/GP5)	Own barometer per board (A: BMP280, B: MS5611 [20]); not shared with L.
Recovery A/B	GP10 drogue, GP11 main	To MOSFET gates; external 100 kΩ pull-down on each gate in addition to internal pulls.
Recovery A/B	GP12/GP13, ADC0	Continuity sense inputs and cell voltage.
All Picos	I^2C1 (GP6 SDA, GP7 SCL)	FRAM checkpoint memory on a bus separate from the sensors, so a sensor-bus fault cannot block state saving [22].

9. Process flowcharts

Figures 2–5 describe the software processes. Rounded boxes are start/end, rectangles are processes, diamonds are decisions, and amber boxes are fault or degraded paths. Parameters are in Sec. 9.1.

9.1 Decision parameters (initial placeholders pending simulation)

Symbol	Meaning	Starting value / source
a_L, t_L	Launch acceleration threshold and duration (logger and recovery).	e.g. 2.5 g for 50 ms (10 IMU samples); set from motor thrust-to-weight in simulation.
h_L	Altitude rise confirming launch.	e.g. 10 m above baseline within 2 s.
t_{lock}	Apogee lock-out after burnout.	Simulation-derived, e.g. 1–2 s, to avoid pressure disturbances near burnout/transonic flight.
N	Consecutive filtered samples with $\dot{h}_f \leq 0$.	5 samples at 25 Hz (0.2 s).
$T_{apo,max}$	Apogee time-out from launch.	Simulated apogee time + margin.
h_d (A / B)	Drop below peak that confirms apogee on recovery boards.	A: small (e.g. 3 m); B: larger (e.g. 8 m) plus delay Δt_B.
h_{main} (A / B)	Main-parachute deployment altitude (AGL).	Within 150–450 m [1], [9]; B set about 30 m lower than A.
t_{pulse}	Output pulse duration.	From release-device specification TBD.
v_{max}	Baro plausibility limit on $\lvert dh/dt \rvert$.	Simulated peak speed × margin TBD.




Figure 2: Logger Pico start-up with reset-cause discrimination: a watchdog reset restores state from scratch registers; a power loss restores it from the FRAM checkpoint; otherwise a normal self-test and pad-idle run until launch detect.




Figure 3: Logger Pico in-flight state machine. Left column: anomaly handling that applies in all states.




Figure 4: Logger Pico dual-core task flow with fault handling and the cross-core watchdog supervisor. Core 1 absorbs SD latency so core 0 timing is never blocked.




Figure 5: Independent recovery controllers. B uses a different barometer part, a later apogee trigger, a lower main altitude and an additional time-since-launch back-up compared with A (Secs. 9.1 and 10).

10. Recovery independence and common-cause failure analysis

Separate boards, cells and barometers remove many single-point failures, but they do not by themselves make two channels independent: a shared design defect, a shared pressure environment or a shared release element can defeat both. Software "independence" in particular should not be assumed, because independently written programs have been shown to fail on the same inputs more often than independence would predict [21]. The design therefore combines *diversity*, a *qualitative common-cause analysis* and *fault-injection tests*. Redundancy reduces common-cause risk; it does not eliminate it.

Shared element	Common-cause failure	Countermeasure	Residual / evidence
Software logic	Same defect or same wrong threshold in A and B.	Separate firmware builds written and reviewed by different members; B adds a time-since-launch back-up and different h_d and h_{main} (Sec. 9.1).	Diversity helps but is imperfect [21]; V-01 replay, V-05.
Barometer part	Systematic offset, noise or supply defect in one part number.	A uses BMP280 [13], B uses MS5611 [20]; different drivers and calibration code.	Both read the same atmosphere; see port row.
Static pressure port	Blocked or disturbed port, bay leak, transonic or burnout pressure transient.	Separate ports at different circumferential positions; lock-out t_{lock}; B back-up timer; vented-bay pressure test.	Residual common pressure field; V-09.
Power	Single cell or connector failure.	Separate cells, switches and harnesses; no shared supply; common ground only at the release interface if required.	V-06, V-08.
Release mechanism	One mechanical or electrical element defeats both channels.	Requirements R1–R4 below; independent initiators per channel.	Mechanism TBD; V-05.
Environment	Vibration, shock, temperature or EMI affects both boards.	Separate mounting, distance between boards, strain-relieved wiring, measured bay temperature.	Vibration and thermal tests.
Human error	Wrong thresholds, wiring or arming sequence on both boards.	Configuration checksum shown on the status code at arming, labelled harnesses, two-person checklist.	Inspection at integration.

Release-interface requirements (proposed).

R1. Each channel (A and B) shall be able to release both drogue and main without the other channel's power or logic.

R2. No single mechanical or electrical element shall prevent both channels from releasing, consistent with the release-redundancy rule [1] (Sec. 4.2.2.2); if a mechanism is shared, the shared element and its redundant initiators shall be documented.

R3. All outputs are de-energised by default, and each channel's supply passes through its own arming switch.

R4. Compliance is shown by fault injection: A disabled, B disabled, and both enabled, each with safe test loads (V-05).

Candidate arrangements, to be selected with the recovery lead: (i) a common release mechanism with two independent initiators, one per channel; or (ii) two separate mechanisms, subject to the rules. The choice is needed before the MDR text is frozen so that this interface is no longer TBD.

11. Preliminary recovery release interface and safe integration

Provisional MDR baseline (not a qualified release design). The recovery team will evaluate a *non-pyrotechnic, spring-assisted retained-door / latch concept* with two electrically independent initiation paths for each parachute stage. The primary recovery controller A and backup controller B will each have their own protected supply and individually isolated switching interface. Either channel must be capable of initiating the relevant stage without the other controller. Spring/servo, latch geometry, actuation current, release force, mechanical redundancy and compatibility with organiser rules are PENDING RECOVERY-LEAD APPROVAL [1], [23].

Interface	MDR-level design requirement	Evidence / owner
Electrical initiators	A and B shall have independently powered means to request drogue and main release; no shared active component may block both.	Recovery lead; schematic at PDR
Safe/armed control	Both circuits default to a non-energised safe state; arming and status confirmation remain accessible when the rocket is assembled.	Recovery lead; bench demonstration
Mechanical interfaces	Release modules, chute bays and harness mounts shall be dimensioned and checked for opening under load and vibration.	Recovery + structures; CAD and tests
Electrical envelope	Release-device voltage, stall/peak current, energy requirement and protective devices shall be calculated once the hardware is selected.	Electronics; driver and battery design
Fault injection	Verify with safe inert loads: A disabled, B disabled, bus faults, reset and short supply interruptions.	Recovery; V-04 and V-05

This baseline closes the MDR need to *explain a candidate interface*, not the later requirement to qualify it. The actual release mechanism must be agreed with the recovery team and approved by the organiser before construction; the present report does not claim that a consumer servo or untested spring arrangement is flight-qualified.

12. Accelerometer range decision

The MPU6050 offers programmable ranges up to ±16 g [14]. Whether that is enough depends on the rocket. An accelerometer measures specific force along its axis, which in g is

$$a_{sf}(t) = \frac{T(t) - D(t)}{m(t)\, g_0}, \tag{1}$$

where T is thrust, D drag, m the (decreasing) mass and $g_0 = 9.81\,\mathrm{m/s^2}$. Parachute-deployment shock must also be included. The inputs are listed below; the Pioneer-10K thrust curve and the team flight simulation were not part of the material used for this revision, so the numerical result is TBD.

Input	Use	Status
Pioneer-10K thrust curve $T(t)$ and burn time	Peak thrust and thrust tolerance.	TBD
Mass history $m(t)$, burnout mass	Peak a_{sf} occurs near low mass.	TBD
Drag $D(t)$ from flight simulation	Net specific force, transonic region.	TBD
Drogue and main deployment shock	Short-duration peaks that may exceed boost peak.	TBD (analysis, later test)
Margin factor k	Covers thrust variation and simulation error.	$k = 1.25$ (team assumption)

Decision rule. Let a_{pk} be the largest predicted $|a_{sf}|$ over the whole flight including deployment shock. If $k\,a_{pk} \le 16\,\mathrm{g}$, the MPU6050 alone is adequate for the acceleration record. If $k\,a_{pk} > 16\,\mathrm{g}$, a ±200 g ADXL375 [16] is added to the logger as a second acceleration channel (budget line in Sec. 17). In every case the logger sets a saturation flag when a raw sample reaches full scale, and launch detection still works because it is a threshold crossing well below full scale. Barometric velocity and altitude remain available even if the acceleration record clips. Verification is analysis V-07.

13. State preservation across resets and power interruption

A watchdog is not a power-loss protection. The RP2040 watchdog scratch registers persist through a *watchdog reset*, but they must not be assumed to survive a power-on reset, a loss of supply or a brown-out [8]; the exact behaviour for an external reset (RUN pin) should be re-read in the datasheet before the design is frozen. The design therefore treats the reset causes separately.

Event	Scratch registers	State-preservation strategy
Software lock-up caught by watchdog	Retained [8]	Restore from scratch registers only if magic number and CRC are valid; otherwise fall through to the FRAM checkpoint.
Brief supply dip or brown-out	Not relied on	Hold-up capacitance rides through short dips; if the Pico still restarts, restore from the FRAM checkpoint.

Event	Scratch registers	Strategy (continued)
Complete power interruption (cell or connector)	Lost	Cold boot, restore from the FRAM checkpoint (if valid), set POWER_LOSS flag, open a new log segment.
External reset line pulse	Do not assume	Same as complete power interruption.
No valid checkpoint	Lost	Logger: restart as PAD or fallback per rule below. Recovery boards: see cold-boot rules.

Checkpoint record. A 16-byte record is written to an I^2C FRAM [22] on a bus (I^2C1) separate from the sensors: magic and version, flight state, launch-detect time, baseline pressure, peak altitude h_{max}, event flags, sequence counter and CRC-16. It is written at every state transition and at least every 250 ms, alternating between two slots so that a write cut short by power loss leaves the other slot intact. At 400 kHz a 16-byte write with 3 bytes of address overhead takes about $(16 + 3) \times 9/400\,000 \approx 0.43$ ms [15]. No flash is written in flight [8].

Hold-up. A bulk capacitor across the board supply keeps the rail up during a brief interruption: $C \approx I\,\Delta t/\Delta V$. For example, 60 mA for 20 ms with 0.5 V allowable droop needs about 2.4 mF. The value is to be sized and tested, not assumed.

Cold-boot rules for recovery boards (proposed).

- Outputs are held low from the first instant of boot by the hardware pull-downs; software never energises an output during start-up.
- With a valid checkpoint in an in-flight state, restore state and continue the normal logic; outputs stay inhibited until their trigger conditions are satisfied again.
- With no valid checkpoint, the board cannot know the pad baseline. A fallback rule is needed from the recovery lead; one candidate is to inhibit the drogue unless a sustained descent is measured, and to use the main-altitude trigger with the nominal site pressure. The other channel provides primary protection rule TBD.

Verification is by supply-interruption tests in every state (V-04).

14. Additional payload: thermal-environment mission definition

Research question. How does the temperature difference between the avionics bay and the inside surface of the airframe wall evolve through the pad, ascent, coast and descent phases of the 3K flight?

Hypothesis and null result. The difference $\Delta T(t) = T_{wall}(t) - T_{bay}(t)$ changes between phases by more than the measurement uncertainty. A flight in which no change larger than the uncertainty is observed is also a valid, reportable result.

New information. The data show whether the avionics bay stays well inside the Pico operating range of −20 to +85 °C [7], how large the bay-to-wall gradient is during flight, and how quickly the bay follows the structure. This supports placement and thermal margin decisions for later flights. The payload stays inside the rocket, is read by the logger and has no radio or stored-energy device; the in-body configuration with avionics communication throughout flight is the one proposed [1] (Sec. 7.1.1).

Item	Definition (team proposal)
Measurements	T_{bay} and T_{wall} from two DS18B20 probes [17], 1 Hz each, 12-bit, with sensor ID, timestamp, flight state and validity flag.
Phases	Pad (baseline), ascent (launch to burnout), coast (burnout to apogee), descent (apogee to landing), all from the logger state record (Fig. 3).
Recording window	From arming through landing plus a post-landing period; expected duration from flight simulation, well inside the > 1.5 h battery endurance.
Accuracy	Each probe is specified at ±0.5 °C from −10 to +85 °C [17]; uncalibrated, ΔT is within ±1.0 °C worst case (≈ 0.7 °C root-sum-square). After both probes are offset-calibrated in a common stable bath, the target is a ΔT uncertainty of ≤ 0.3 °C, to be demonstrated in V-08.
Response time	Probe step response measured on the bench so that lag between bay and wall probes is not mistaken for a physical gradient.
Success	Both channels valid for ≥ 90% of expected samples in each of the ascent, coast and descent phases; records retrieved with CRC pass ≥ 99%; phase-mean ΔT and uncertainty reported.
Partial success	One channel valid ≥ 90%, or both channels valid for 50–89% of expected samples in at least two phases.

Item	Definition (continued)
Failure	Fewer than 50% valid samples in the flight window, no retrieved file, or data that cannot be aligned to flight events.
Retrieval evidence	Recovered SD card, intact raw file with hash, processed $\Delta T(t)$ plot per phase, completeness table and quality log (Sec. 18).

15. Robustness and fault handling

Failure mode	Consequence	Mitigation (see flowcharts)
Logger lock-up	Gaps in data or payload record.	Watchdog restart with scratch-register restore; 1 s sync.
Power interruption in flight	Cold boot, loss of state and baseline.	FRAM checkpoint, hold-up capacitance, new log segment with POWER_LOSS flag (Sec. 13).
Barometer noise, spike or port blockage	False apogee or main trigger.	Plausibility gate, IIR filter, multi-condition apogee, lock-out, time-out.
IMU saturation	Bad launch/burnout and acceleration data.	Range decision gate (Sec. 12), saturation flag, baro cross-check.
SD write stall or removal	Missing records.	Core-1 offload, 24 kB buffer, retry/remount, next-file segment.
Recovery A failure	No or late deployment.	Backup B: separate board, diverse sensor, cell, later trigger and time back-up.
Common-cause failure of A and B	No deployment on both channels.	Diversity, release requirements R1–R4, fault-injection tests (Sec. 10).
Beacon track missing or misaligned	Incomplete flight-data package.	Redundant altitude sources, time-alignment check, quality flags (Sec. 18).
Premature output from noise/boot	Unsafe activation.	Outputs held low by pull-downs, arming switch, launch-inhibit logic.
Thermal probe detaches	Invalid payload data; loose object.	Mechanical retention, strain relief, flag in record.
Connector loosening	Intermittent power/data.	Locking connectors, strain relief, vibration test [1].

The full FMEA follows the organiser template [24]; classical FMECA practice is described in [25].

16. Power and data budgets

Load estimate (logger). Values are datasheet-typical or assumed, and must be replaced by measurements.

Item	mA	Basis
Pico L at 125 MHz, both cores	30	Assumed; measure [8]
MPU6050 (gyro + accel)	3.9	Datasheet typical [14]
BMP280	< 0.1	Datasheet [13]
2× DS18B20 active	2	About 1 mA each [17]
microSD module average	20	Assumed; write peaks higher
Total estimate	**≈56**	Design basis kept at **200 mA**

At 56 mA the 1.5 h minimum [1] needs about 84 mAh. Using the conservative 200 mA at 3.3 V through an assumed 85% efficient converter, the demand is $3.3 \times 0.2 \times 1.5/0.85 \approx 1.16$ Wh, against about 9.6 Wh stored in a nominal 3.7 V, 2.6 Ah cell (≈8× margin). The margin is only a sizing indicator; a measured endurance test of more than 1.5 h is required. Recovery boards use the same method plus the release-device pulse load TBD.

Data budget. 24 B × 200 Hz = 4.8 kB/s; 90 min = 5400 s ⇒ about 26 MB. SPI at 12.5 MHz and 512 B block writes leave large margin, and the 24 kB buffer covers about 5 s of SD latency.

17. Preliminary electronics budget and mass

Price provenance. Prices below reproduce the component listing figures documented in the earlier Shopee-linked MDR draft (retrieval recorded 4 November 2026). They are **indicative**, exclude shipping and may depend on a listing variation. This update has *not* established a new live quote or guaranteed stock. Links are to identifiable Shopee Malaysia product listings; verify item variant, authenticity, checkout price and voltage ratings before ordering.

Budget allowances are not retailer quotes. Detailed purchase and safety decisions belong to later design reviews [3], [5].

ID	Component	Qty	Unit RM	RM	Source status
B01	Raspberry Pi Pico-compatible RP2040	3	15.27	45.81	**Shopee S1**
B02	BMP280 breakout (logger + recovery A)	2	4.47	8.94	**Shopee S2**
B03	MPU6050 GY-521 breakout	1	6.60	6.60	**Shopee S3**
B04	SPI microSD reader module	1	5.20	5.20	**Shopee S4**
B05	MicroSD card, selected capacity TBD	1	22.00	22.00	**Shopee S5**
B06	DS18B20 thermal probes	2	5.80	11.60	**Shopee S6**
B07	18650 2600 mAh Li-ion cells	3	29.99	89.97	**Shopee S7**
B08	Active buzzer/status indicator	1	1.69	1.69	**Shopee S8**
B09	Prototype PCBs	3	4.49	13.47	**Shopee S9**
B10	JST-XH connector kit	2	4.40	8.80	**Shopee S10**
	Shopee-linked component subtotal			**214.08**	Recorded listings
B11	MS5611 barometer B	1	15.00	15.00	Allowance, no Shopee quote
B12	FRAM checkpoint modules	3	10.00	30.00	Allowance
B13	Arming/safety switches, drivers, status	3	25.00	75.00	Allowance
B14	Battery protection, fuses and mounts	3	25.00	75.00	Allowance
B15	Electronics bay mounts, wiring, seals	3	20.00	60.00	Allowance
B16	Non-energetic test loads and consumables	1	40.00	40.00	Allowance
B17	Spares: Pico, BMP280, MPU6050, Li-ion cell	1 set	56.33	56.33	Recorded listing values
	Preliminary subtotal			**565.41**	
	25% contingency (rounded)			**141.35**	
	Preliminary cost envelope (partial)			**706.76**	Excludes items below

Not priced / required before a complete cost claim: dual-stage mechanical release assemblies and independent initiators, any additional approved actuators and their high-load supply demands, the organiser's official GPS beacon/antenna (if not supplied), optional ADXL375, shipping, specialist environmental test access and custom manufacturing. The *RM706.76 is not a final flight-ready total.* The verified source category and allowance status must be retained in the final team's BOM.

Preliminary mass envelope. The following values are *engineering allowances*, not measured masses; assume at least ±30% uncertainty until the physical bay drawing and component variants are fixed.

Domain	Mass (g)	Included items
Logger + thermal payload	119	Pico L, BMP280, MPU6050, microSD, two probes, battery, mount, wiring
Recovery A	96	Pico A, BMP280, battery, drivers, mounting
Recovery B	96	Pico B, MS5611, battery, drivers, mounting
FRAM boards	3	Three small modules
Electronics allowance	**314**	**Excludes GPS, physical release devices, long harness and airframe hardware**

Mass/power integration note. Assign a maximum electronics-bay allocation with structures and verify against the rocket total-mass limit. Battery temperature, vibrational retention, connector strength and operating endurance are pending bench and environmental qualification [1], [9].

18. Flight-data interface and post-flight evidence package

The organiser beacon is physically independent of the Pico boards, but the four required outputs (altitude, velocity, acceleration and GPS trajectory [1], Sec. 2.1) must end up as one usable evidence package. The interface is therefore defined at the data level.

Output	Primary source	Cross-check	Availability criterion
Altitude	Logger barometer, filtered	Recovery A and B barometers; beacon altitude if provided	Valid for $\geq$ 90% of the flight window

Output	Primary source	Cross-check	Criterion (continued)
Velocity	Derivative of filtered barometric altitude	Integrated acceleration; beacon-derived speed if provided	Valid for $\geq$ 90% of the flight window
Acceleration	MPU6050 (and ADXL375 if fitted)	Second derivative of altitude (coarse)	$\geq$ 90% valid, saturation flagged
GPS trajectory	Organiser beacon track file	Barometric altitude trend	Track covers launch to landing; retrieval method to confirm with the organiser

Time alignment. The logger stamps every record with its own microsecond timer and records the launch-detect event T_0. The beacon track carries UTC. The two are aligned at T_0 and refined by correlating barometric altitude with beacon altitude during ascent. A crystal tolerance assumed to be 50 ppm would give up to $5400 \times 50 \times 10^{-6} \approx 0.27$ s drift over 90 min, which is small compared with the beacon update interval. An operator-noted UTC at ignition (to about 1 s) is kept as an independent check. The achieved residual is reported with the data.

19. Verification plan

Methods follow the usual inspection, analysis, demonstration and test categories [4]; MDR needs the plan, not the results [3].

ID	Method	Planned evidence	Initial pass criterion (team target)
V-01	Test	Replay recorded and simulated histories through the A and B logic with injected noise and spikes.	No false apogee or main trigger in $\geq$ 1000 randomised replays.
V-02	Test	Logger timing: loop jitter, buffer occupancy, SD latency, forced SD errors.	Jitter $<$ 10% of the 5 ms period; no overruns; buffer $<$ 50% full.
V-03	Demonstration	Force a core stall mid-sequence; confirm watchdog restart and state restore from scratch registers.	State correct; log gap $\leq$ 3 s.
V-04	Test	Interrupt supply for 1 ms, 20 ms, 100 ms and 1 s in every flight state on logger and recovery boards.	Correct state restored from FRAM; outputs stay low throughout; POWER_LOSS flagged.
V-05	Demonstration	Fault injection with safe test loads: A disabled, B disabled, both enabled.	Each channel alone releases drogue then main in 10 of 10 trials.
V-06	Test	Power endurance with realistic logging; connector pull and vibration retention.	Runs $\geq$ 1.5 h with $\geq$ 25% capacity margin.
V-07	Analysis	Acceleration envelope against thrust curve, mass and deployment shock (Sec. 12).	$k\,a_{pk} \leq$ 16 g, or ADXL375 fitted.
V-08	Test	Thermal probes: common-bath offset calibration, step response, 1 h data-completeness run.	ΔT uncertainty $\leq$ 0.3 °C; completeness $\geq$ 99%.
V-09	Test	Barometer ports: pressure chamber or vented-bay test with representative pressure profile.	A and B altitude agree within $\pm$5 m.
V-10	Demonstration	Dry run of the post-flight pipeline (Fig. 6) on a ground or simulated data set.	All four outputs produced; alignment residual $\leq$ 1 s.
V-11	Inspection	Wiring, labels, strain relief, arming-switch access and polarity [1].	No findings.
V-12	Analysis	Mass, power and cost budget and FMEA update for PDR [24].	Budget and FMEA approved by lead.

20. Preliminary scored electronics FMEA

This is the MDR-level *initial* risk register, following the organiser's FMEA example [24]. Ratings are team assumptions, not measured reliabilities: Severity (S), Occurrence (O) and Detectability (D) range from 1 (low) to 5 (high or difficult to detect); risk priority is $RPN = S \times O \times D$. High-severity hazards still receive priority even when their RPN is low. Final criteria and residual risk acceptance belong to the team safety/recovery leads.




Figure 6: Post-flight data pipeline that turns the logger files and the organiser beacon track into one evidence package covering all four required outputs.

ID	Failure mode	Effect	S	O	D	RPN	Mitigation / owner
F01	Common-mode recovery software defect	Both stages delayed or fail	5	3	4	60	Diverse channel B, review, replay tests; Recovery lead
F02	Release mechanism jams	Chute not deployed	5	3	4	60	Independent initiation; mechanical load tests; Recovery + structures
F03	Static-port blockage or transient	Wrong altitude/recovery event	5	3	3	45	Port separation, plausibility, chamber test; Recovery
F04	Recovery cell/connector fails	One recovery channel lost	5	2	3	30	Separate cells and wiring; endurance + vibration; Electronics
F05	Spurious arming/output	Premature release or hazardous event	5	2	3	30	Physical arming, default low outputs, continuity checks; Recovery
F06	MCU reset/brownout	Data lost or recovery state uncertain	4	3	3	36	FRAM checkpoint, reset discrimination, fault injection; Avionics
F07	IMU saturation	Missing acceleration peaks	3	4	2	24	Simulated envelope and optional high-g sensor; Avionics
F08	SD-card write failure	Lost flight/payload evidence	3	3	2	18	Buffering, CRC, sync and recovery test; Logger lead
F09	GPS beacon/radio failure	Rocket location unavailable	4	3	3	36	Independent beacon test, antenna placement, range check; GPS lead
F10	Thermal probes detach/drift	Invalid payload result	2	3	2	12	Probe retention and calibration; Payload lead
F11	Wiring/PCB mount loosens	Intermittent signals or loss of power	4	3	3	36	Labelled locking connectors, strain relief; Integration

Risk-closure expectations: Document the recovery-lead decision on F01–F05 before design freeze; update S/O/D after preliminary testing; and attach V-01 to V-12 test identifiers to the final FMEA worksheet. All named owners are *roles*, not confirmed individual assignments.

21. Development roadmap, responsibility allocation and MDR slide handover

The following dates use the stated MDR closing date of **13 November 2026**; they are an internal *proposal*. The team leader must assign named members before submission. Later PDR/CDR month references are planning windows, not exact confirmed organiser dates [3], [5].

Target	Task / deliverable	Responsible role	Stage
4–5 Nov 2026	Freeze initial AV/RC/PW/GPS/PL requirements and thermal mission criteria	Avionics + payload leads (assign names)	MDR
5–7 Nov 2026	Confirm three-power-domain interfaces and preliminary recovery-release concept	Recovery + integration leads	MDR
6–8 Nov 2026	Compile supplier-link BOM, cost estimates and mass/power allocations	Procurement + electrical leads	MDR
7–9 Nov 2026	Insert rocket flight-simulation bounds, or flag missing inputs and decision gate	Flight dynamics + avionics	MDR
8–10 Nov 2026	Complete numbered verification plan and initial FMEA; risk review	Safety + avionics leads	MDR
10–11 Nov 2026	Extract two/three concise slides into the master MDR	MDR editor + electronics leads	MDR
12 Nov 2026	Internal design review, source audit and final PDF export	Team leader + reviewers	MDR
13 Nov 2026	Submit the *single team* searchable MDR PDF	Team leader	MDR
After MDR (dates TBD)	Prototype logger + both recovery paths; review components against simulation	Avionics + recovery	PDR
Before CDR (dates TBD)	Integrated bench, actuation, fault injection, endurance and environmental tests; revise verification matrix	All electronics teams	CDR
Flight readiness (TBD)	Demonstrate safe arming, GPS reporting and launch checklist compliance	Recovery + GPS + team lead	FRR

Proposed MDR integration map (electronics contribution)

Template location	Material to extract	Responsible editor
Slide 2	Avionics, recovery and payload objectives and measurable success criteria	Team lead / payload
Slides 3–5	Named responsibilities and electronics milestones/Gantt	Team lead
Slides 6–7	Hardware choices, Shopee-linked costed BOM, contingency and power/mass assumptions	Procurement + avionics
Slide 8	Annotated avionics-bay/recovery/GPS/payload placement with mass interfaces	Integration + structures
Slide 9	Numbered functional requirements plus one simplified architecture figure	Avionics lead
Slide 10	Expected flight event sequence and recovery/payload timing (link simulation)	Flight dynamics + avionics
Slide 11	Development dependencies, verification plan and integration stages	Avionics + recovery
Slide 12	Initial high-priority FMEA and risk reduction plan	Safety + recovery

For the *final MDR*, condense this engineering annex into the team's master presentation rather than submitting all detailed flowcharts and tables independently. The design remains provisional where the mechanism, rocket simulation, complete GPS arrangement or confirmed pricing is unavailable.

22. Decisions needed from the team

1. Select the release-interface arrangement (R1–R4) with the recovery lead, and approve the diverse channel B (MS5611, separate firmware, time back-up).
2. Provide the Pioneer-10K thrust curve, mass history and flight simulation so that a_{pk} and the ADXL375 decision (Sec. 12) can be made, and so that a_L, t_{lock}, v_{max} and $T_{apo,max}$ can be fixed.
3. Approve the FRAM checkpoint and agree the recovery-board fallback rule when no valid checkpoint exists.
4. Approve the thermal research question and success criteria, or replace them with an agreed payload using the same format.
5. Obtain quotes for release hardware and the GPS beacon, and confirm how the beacon track file is retrieved.
6. Confirm bay dimensions, mounting, battery protection and measured current before procurement.

References

[1] RTC 2027 Organiser, *Appendix 03: Rocket design specifications*, Competition document, `appendix_03.pdf`, 2026.

[2] RTC 2027 Organiser, *Appendix 06: Competition rules explanation, version 2*, Competition document, `appendix_06.pdf`, 2026.

[3] RTC 2027 Organiser, *Appendix 07: Mdr scoring and design maturity matrix*, Competition document, `appendix_07.xlsx`, 2026.

[4] NASA, *NASA systems engineering handbook*, NASA/SP-2016-6105 Rev2, 2016. Accessed: Nov. 4, 2026. [Online]. Available: https://www.nasa.gov/reference/systems-engineering-handbook/

[5] RTC 2027 Organiser, *Appendix 01: Mission plan report example and slide template*, Competition document, `appendix_01.pptx`, 2026.

[6] RTC 2027 Organiser, *Appendix 10: Requirements matrix example*, Competition document, appendix_10.xlsx, 2026.

[7] Raspberry Pi Ltd, *Raspberry Pi Pico datasheet: An RP2040-based microcontroller board*, 2024. Accessed: Nov. 4, 2026. [Online]. Available: https://datasheets.raspberrypi.com/pico/pico-datasheet.pdf

[8] Raspberry Pi Ltd, *RP2040 datasheet: A microcontroller by Raspberry Pi*, 2024. Accessed: Nov. 4, 2026. [Online]. Available: https://datasheets.raspberrypi.com/rp2040/rp2040-datasheet.pdf

[9] RTC 2027 Organiser, *Appendix 08: Launch permit inspection checklist*, Competition document, `appendix_08.xlsx`, 2026.

[10] Raspberry Pi Ltd, *Raspberry Pi Pico-series C/C++ SDK*, 2024. Accessed: Nov. 4, 2026. [Online]. Available: https://datasheets.raspberrypi.com/pico/raspberry-pi-pico-c-sdk.pdf

[11] Microchip Technology, *ATmega328P data sheet*, DS40002061, 2020. Accessed: Nov. 4, 2026. [Online]. Available: https://www.microchip.com/en-us/product/ATmega328P

[12] Espressif Systems, *ESP32 series datasheet*, 2024. Accessed: Nov. 4, 2026. [Online]. Available: https://www.espressif.com/en/support/documents/technical-documents

[13] Bosch Sensortec GmbH, *BMP280 digital pressure sensor datasheet*, BST-BMP280-DS001, 2018. Accessed: Nov. 4, 2026. [Online]. Available: https://www.bosch-sensortec.com/products/environmental-sensors/pressure-sensors/bmp280/

[14] InvenSense Inc., *MPU-6000 and MPU-6050 product specification, revision 3.4*, PS-MPU-6000A-00, 2013. Accessed: Nov. 4, 2026. [Online]. Available: https://invensense.tdk.com/products/motion-tracking/6-axis/mpu-6050/

[15] NXP Semiconductors, *I2C-bus specification and user manual, rev. 7.0*, UM10204, 2021. Accessed: Nov. 4, 2026. [Online]. Available: https://www.nxp.com/docs/en/user-guide/UM10204.pdf

[16] Analog Devices, *ADXL375: 3-axis, ±200 g digital MEMS accelerometer*, 2020. Accessed: Nov. 4, 2026. [Online]. Available: https://www.analog.com/en/products/adxl375.html

[17] Maxim Integrated, *DS18B20 programmable resolution 1-wire digital thermometer*, 2019. Accessed: Nov. 4, 2026. [Online]. Available: https://www.analog.com/media/en/technical-documentation/data-sheets/ds18b20.pdf

[18] SD Association, *SD specifications part 1: Physical layer simplified specification*, Use the current published version; SPI-mode command set is defined in this document, 2020. Accessed: Nov. 4, 2026. [Online]. Available: https://www.sdcard.org/downloads/pls/

[19] H. Chan, *FatFs – generic FAT filesystem module*, Online documentation. Accessed: Nov. 4, 2026. [Online]. Available: http://elm-chan.org/fsw/ff/

[20] TE Connectivity, *MS5611-01BA03 barometric pressure sensor datasheet*, Revision and date to be confirmed against the purchased module. Accessed: Nov. 4, 2026. [Online]. Available: https://www.te.com/en/product-CAT-BLPS0036.html

[21] J. C. Knight and N. G. Leveson, "An experimental evaluation of the assumption of independence in multiversion programming," *IEEE Transactions on Software Engineering*, vol. SE-12, no. 1, pp. 96–109, 1986.

[22] Fujitsu Semiconductor, *MB85RC256V: 256 kbit I2C FRAM datasheet*, Part choice illustrative; any I2C FRAM with equivalent features may be used; revision to be confirmed.

[23] M. Bakirci and M. M. Ozer, "Electrical architecture of the recovery system of a high powered rocket with payload," in *2022 International Congress on Human-Computer Interaction, Optimization and Robotic Applications (HORA)*, 2022, pp. 1–4. DOI: 10.1109/HORA55278.2022.9800024 [Online]. Available: https://doi.org/10.1109/HORA55278.2022.9800024

[24] RTC 2027 Organiser, *Appendix 12: Fmea example*, Competition document, `appendix_12.xlsx`, 2026.

[25] US Department of Defense, *Procedures for performing a failure mode, effects and criticality analysis*, MIL-STD-1629A, 1980.