Namespace SixLabors.ImageSharp.Web.AWS

Classes

AmazonS3BucketClient

Represents a scoped Amazon S3 client instance that is explicitly associated with a single S3 bucket. This wrapper provides a strongly-typed link between the client and the bucket it operates on, and optionally manages the lifetime of the underlying Amazon.S3.AmazonS3Client.

Interfaces

IAWSS3BucketClientOptions

Provides a common interface for AWS S3 Bucket Client Options.

Class AmazonS3BucketClient

Namespace: SixLabors.ImageSharp.Web.AWS

Assembly: SixLabors.ImageSharp.Web.Providers.AWS.dll

Represents a scoped Amazon S3 client instance that is explicitly associated with a single S3 bucket. This wrapper provides a strongly-typed link between the client and the bucket it operates on, and optionally manages the lifetime of the underlying Amazon.S3.AmazonS3Client.

```
public sealed class AmazonS3BucketClient : IDisposable
```

Inheritance

object ← AmazonS3BucketClient

Implements

IDisposable

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

AmazonS3BucketClient(string, AmazonS3Client, bool)

Initializes a new instance of the AmazonS3BucketClient class.

```
public AmazonS3BucketClient(string bucketName, AmazonS3Client client, bool disposeClient
= true)
```

Parameters

`bucketName` string

The bucket name associated with this client instance.

`client` AmazonS3Client

The underlying Amazon S3 client instance. This should be an already configured instance of Amazon.S3.AmazonS3Client.

`disposeClient` bool

A value indicating whether the underlying client should be disposed when this instance is disposed.

Properties

BucketName

Gets the bucket name associated with this client instance.

```
public string BucketName { get; }
```

Property Value

string

Client

Gets the underlying Amazon S3 client instance.

```
public AmazonS3Client Client { get; }
```

Property Value

AmazonS3Client

Methods

Dispose()

Performs application-defined tasks associated with freeing, releasing, or resetting unmanaged resources.

```
public void Dispose()
```

Interface IAWSS3BucketClientOptions

Namespace: SixLabors.ImageSharp.Web.AWS

Assembly: SixLabors.ImageSharp.Web.Providers.AWS.dll

Provides a common interface for AWS S3 Bucket Client Options.

```
public interface IAWSS3BucketClientOptions
```

Properties

AccessKey

Gets or sets the AWS key - Can be used to override keys provided by the environment. If deploying inside an EC2 instance AWS keys will already be available via environment variables and don't need to be specified. Follow AWS best security practices on https://docs.aws.amazon.com/general/latest/gr/aws-access-keys-best-practices.html.

```
string? AccessKey { get; set; }
```

Property Value

string

AccessSecret

Gets or sets the AWS endpoint - used to override the default service endpoint. If deploying inside an EC2 instance AWS keys will already be available via environment variables and don't need to be specified. Follow AWS best security practices on https://docs.aws.amazon.com/general/latest/gr/aws-access-keys-best-practices.html.

```
string? AccessSecret { get; set; }
```

Property Value

string

BucketName

Gets or sets the AWS bucket name. Cannot be null when S3ClientFactory is not set.

```
string BucketName { get; set; }
```

Property Value

string

Endpoint

Gets or sets the AWS endpoint - used for testing to over region endpoint allowing it to be set to localhost.

```
string? Endpoint { get; set; }
```

Property Value

string

Region

Gets or sets the AWS region endpoint (us-east-1/us-west-1/ap-southeast-2).

```
string? Region { get; set; }
```

Property Value

string

S3ClientFactory

Gets or sets a custom factory method to create an AmazonS3BucketClient.

```
Func<IAWSS3BucketClientOptions, IServiceProvider, AmazonS3BucketClient>? S3ClientFactory {
get; set; }
```

Property Value

Func<IAWSS3BucketClientOptions, IServiceProvider, AmazonS3BucketClient>

Timeout

Gets or sets a value indicating the timeout for the S3 client. If the value is set, the value is assigned to the Timeout property of the HttpWebRequest/HttpClient object used to send requests.

```
TimeSpan? Timeout { get; set; }
```

Property Value

TimeSpan?

UseAccelerateEndpoint

Gets or sets a value indicating whether the S3 accelerate endpoint is used. The feature must be enabled on the bucket. Follow AWS instruction on https://docs.aws.amazon.com/AmazonS3/latest/userguide/transfer-acceleration.html.

```
bool UseAccelerateEndpoint { get; set; }
```

Property Value

bool

Namespace SixLabors.ImageSharp.Web.AWS.Caching

Classes

AWSS3StorageCache
: Implements an AWS S3 Storage based cache.

AWSS3StorageCacheOptions
: Configuration options for the AWSS3StorageCache provider.

Class AWSS3StorageCache

Namespace: SixLabors.ImageSharp.Web.AWS.Caching

Assembly: SixLabors.ImageSharp.Web.Providers.AWS.dll

Implements an AWS S3 Storage based cache.

```
public class AWSS3StorageCache : IImageCache, IDisposable
```

Inheritance

object ← AWSS3StorageCache

Implements

IImageCache, IDisposable

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

AWSS3StorageCache(IOptions<AWSS3StorageCacheOptions>, IServiceProvider)

Initializes a new instance of the AWSS3StorageCache class.

```
public AWSS3StorageCache(IOptions<AWSS3StorageCacheOptions> cacheOptions,
IServiceProvider serviceProvider)
```

Parameters

`cacheOptions` IOptions<AWSS3StorageCacheOptions>

The cache options.

`serviceProvider` IServiceProvider

The current service provider.

Methods

CreateIfNotExists(AWSS3StorageCacheOptions, S3CannedACL)

Creates a new bucket under the specified account if a bucket with the same name does not already exist.

```
public static PutBucketResponse? CreateIfNotExists(AWSS3StorageCacheOptions options,
S3CannedACL acl)
```

Parameters

`options` AWSS3StorageCacheOptions

The AWS S3 Storage cache options.

`acl` S3CannedACL

Specifies whether data in the bucket may be accessed publicly and the level of access. Amazon.S3.S3CannedACL.PublicRead specifies full public read access for bucket and object data. Amazon.S3.S3CannedACL.Private specifies that the bucket data is private to the account owner.

Returns

PutBucketResponse

If the bucket does not already exist, a Amazon.S3.Model.PutBucketResponse describing the newly created bucket. If the container already exists, null.

Dispose()

Performs application-defined tasks associated with freeing, releasing, or resetting unmanaged resources.

```
public void Dispose()
```

Dispose(bool)

Releases the unmanaged resources used by the AWSS3StorageCache and optionally releases the managed resources.

```
protected virtual void Dispose(bool disposing)
```

Parameters

`disposing` bool

true to release both managed and unmanaged resources; false to release only unmanaged resources.

GetAsync(string)

Gets the image resolver associated with the specified key.

```
public Task<IImageCacheResolver?> GetAsync(string key)
```

Parameters

`key` string

The cache key.

Returns

Task<IImageCacheResolver>

The IImageResolver.

SetAsync(string, Stream, ImageCacheMetadata)

Sets the value associated with the specified key.

```
public Task SetAsync(string key, Stream stream, ImageCacheMetadata metadata)
```

Parameters

`key` string

The cache key.

`stream` Stream

The stream containing the image to store.

`metadata` ImageCacheMetadata

The ImageCacheMetadata associated with the image to store.

Returns

Task

The task.

Class AWSS3StorageCacheOptions

Namespace: SixLabors.ImageSharp.Web.AWS.Caching

Assembly: SixLabors.ImageSharp.Web.Providers.AWS.dll

Configuration options for the AWSS3StorageCache provider.

```
public class AWSS3StorageCacheOptions : IAWSS3BucketClientOptions
```

Inheritance

object ← AWSS3StorageCacheOptions

Implements

IAWSS3BucketClientOptions

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Properties

AccessKey

Gets or sets the AWS key - Can be used to override keys provided by the environment. If deploying inside an EC2 instance AWS keys will already be available via environment variables and don't need to be specified. Follow AWS best security practices on https://docs.aws.amazon.com/general/latest/gr/aws-access-keys-best-practices.html.

```
public string? AccessKey { get; set; }
```

Property Value

string

AccessSecret

Gets or sets the AWS endpoint - used to override the default service endpoint. If deploying inside an EC2 instance AWS keys will already be available via environment variables and don't need to be specified. Follow AWS best security practices on https://docs.aws.amazon.com/general/latest/gr/aws-access-keys-best-practices.html.

```
public string? AccessSecret { get; set; }
```

Property Value

string

BucketName

Gets or sets the AWS bucket name. Cannot be null when S3ClientFactory is not set.

```
public string BucketName { get; set; }
```

Property Value

string

CacheFolder

Gets or sets the cache folder's name that'll store cache files under the configured bucket.

```
public string? CacheFolder { get; set; }
```

Property Value

string

Endpoint

Gets or sets the AWS endpoint - used for testing to over region endpoint allowing it to be set to localhost.

```
public string? Endpoint { get; set; }
```

Property Value

string

Region

Gets or sets the AWS region endpoint (us-east-1/us-west-1/ap-southeast-2).

```
public string? Region { get; set; }
```

Property Value

string

S3ClientFactory

Gets or sets a custom factory method to create an AmazonS3BucketClient.

```
public Func<IAWSS3BucketClientOptions, IServiceProvider, AmazonS3BucketClient>?
S3ClientFactory { get; set; }
```

Property Value

Func<IAWSS3BucketClientOptions, IServiceProvider, AmazonS3BucketClient>

Timeout

Gets or sets a value indicating the timeout for the S3 client. If the value is set, the value is assigned to the Timeout property of the HttpWebRequest/HttpClient object used to send requests.

```
public TimeSpan? Timeout { get; set; }
```

Property Value

TimeSpan?

UseAccelerateEndpoint

Gets or sets a value indicating whether the S3 accelerate endpoint is used. The feature must be enabled on the bucket. Follow AWS instruction on https://docs.aws.amazon.com/AmazonS3/latest/userguide/transfer-acceleration.html.

```
public bool UseAccelerateEndpoint { get; set; }
```

Property Value

bool

Namespace SixLabors.ImageSharp.Web.AWS.Providers

Classes

AWSS3BucketClientOptions
: Configuration options for the AWSS3StorageImageProvider provider.

AWSS3StorageImageProvider
: Returns images stored in AWS S3.

AWSS3StorageImageProviderOptions
: Configuration options for the AWSS3StorageImageProviderOptions provider.

Class AWSS3BucketClientOptions

Namespace: SixLabors.ImageSharp.Web.AWS.Providers

Assembly: SixLabors.ImageSharp.Web.Providers.AWS.dll

Configuration options for the AWSS3StorageImageProvider provider.

```
public class AWSS3BucketClientOptions : IAWSS3BucketClientOptions
```

Inheritance

object ← AWSS3BucketClientOptions

Implements

IAWSS3BucketClientOptions

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Properties

AccessKey

Gets or sets the AWS key - Can be used to override keys provided by the environment. If deploying inside an EC2 instance AWS keys will already be available via environment variables and don't need to be specified. Follow AWS best security practices on https://docs.aws.amazon.com/general/latest/gr/aws-access-keys-best-practices.html.

```
public string? AccessKey { get; set; }
```

Property Value

string

AccessSecret

Gets or sets the AWS endpoint - used to override the default service endpoint. If deploying inside an EC2 instance AWS keys will already be available via environment variables and don't need to be specified. Follow AWS best security practices on https://docs.aws.amazon.com/general/latest/gr/aws-access-keys-best-practices.html.

```
public string? AccessSecret { get; set; }
```

Property Value

string

BucketName

Gets or sets the AWS bucket name. Cannot be null when S3ClientFactory is not set.

```
public string BucketName { get; set; }
```

Property Value

string

Endpoint

Gets or sets the AWS endpoint - used for testing to over region endpoint allowing it to be set to localhost.

```
public string? Endpoint { get; set; }
```

Property Value

string

Region

Gets or sets the AWS region endpoint (us-east-1/us-west-1/ap-southeast-2).

```
public string? Region { get; set; }
```

Property Value

string

S3ClientFactory

Gets or sets a custom factory method to create an AmazonS3BucketClient.

```
public Func<IAWSS3BucketClientOptions, IServiceProvider, AmazonS3BucketClient>?
S3ClientFactory { get; set; }
```

Property Value

Func<IAWSS3BucketClientOptions, IServiceProvider, AmazonS3BucketClient>

Timeout

Gets or sets a value indicating the timeout for the S3 client. If the value is set, the value is assigned to the Timeout property of the HttpWebRequest/HttpClient object used to send requests.

```
public TimeSpan? Timeout { get; set; }
```

Property Value

TimeSpan?

UseAccelerateEndpoint

Gets or sets a value indicating whether the S3 accelerate endpoint is used. The feature must be enabled on the bucket. Follow AWS instruction on

https://docs.aws.amazon.com/AmazonS3/latest/userguide/transfer-acceleration.html.

```
public bool UseAccelerateEndpoint { get; set; }
```

Property Value

bool

Class AWSS3StorageImageProvider

Namespace: SixLabors.ImageSharp.Web.AWS.Providers

Assembly: SixLabors.ImageSharp.Web.Providers.AWS.dll

Returns images stored in AWS S3.

```
public class AWSS3StorageImageProvider : IImageProvider, IDisposable
```

Inheritance

object ← AWSS3StorageImageProvider

Implements

IImageProvider, IDisposable

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

AWSS3StorageImageProvider(IOptions<AWSS3StorageImageProviderOptions>, FormatUtilities, IServiceProvider)

Initializes a new instance of the AWSS3StorageImageProvider class.

```
public AWSS3StorageImageProvider(IOptions<AWSS3StorageImageProviderOptions> storageOptions,
FormatUtilities formatUtilities, IServiceProvider serviceProvider)
```

Parameters

`storageOptions` IOptions<AWSS3StorageImageProviderOptions>

The S3 storage options

`formatUtilities` FormatUtilities

Contains various format helper methods based on the current configuration.

`serviceProvider` IServiceProvider

The current service provider.

Properties

Match

Gets or sets the method used by the resolver to identify itself as the correct resolver to use.

```
public Func<HttpContext, bool> Match { get; set; }
```

Property Value

Func<HttpContext, bool>

ProcessingBehavior

Gets the processing behavior.

```
public ProcessingBehavior ProcessingBehavior { get; }
```

Property Value

ProcessingBehavior

Methods

Dispose()

Performs application-defined tasks associated with freeing, releasing, or resetting unmanaged resources.

```
public void Dispose()
```

Dispose(bool)

Releases the unmanaged resources used by the AWSS3StorageImageProvider and optionally releases the managed resources.

```
protected virtual void Dispose(bool disposing)
```

Parameters

`disposing` bool

true to release both managed and unmanaged resources; false to release only unmanaged resources.

GetAsync(HttpContext)

Gets the image resolver associated with the context.

```
public Task<IImageResolver?> GetAsync(HttpContext context)
```

Parameters

`context` HttpContext

The current HTTP request context.

Returns

Task<IImageResolver>

The IImageResolver.

IsValidRequest(HttpContext)

Gets a value indicating whether the current request passes sanitizing rules.

```
public bool IsValidRequest(HttpContext context)
```

Parameters

`context` HttpContext

The current HTTP request context.

Returns

bool

The bool

Class AWSS3StorageImageProviderOptions

Namespace: SixLabors.ImageSharp.Web.AWS.Providers

Assembly: SixLabors.ImageSharp.Web.Providers.AWS.dll

Configuration options for the AWSS3StorageImageProviderOptions provider.

```
public class AWSS3StorageImageProviderOptions
```

Inheritance

object ← AWSS3StorageImageProviderOptions

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Properties

S3Buckets

Gets or sets the collection of blob container client options.

```
public ICollection<AWSS3BucketClientOptions> S3Buckets { get; set; }
```

Property Value

ICollection<AWSS3BucketClientOptions>

Namespace SixLabors.ImageSharp.Web.AWS.Resolvers

Classes

AWSS3StorageCacheResolver

Provides means to manage image buffers within the AWSS3StorageCacheResolver.

AWSS3StorageImageResolver

Provides means to manage image buffers within the AWS S3 file system.

Class AWSS3StorageCacheResolver

Namespace: SixLabors.ImageSharp.Web.AWS.Resolvers

Assembly: SixLabors.ImageSharp.Web.Providers.AWS.dll

Provides means to manage image buffers within the AWSS3StorageCacheResolver.

```
public class AWSS3StorageCacheResolver : IImageCacheResolver
```

Inheritance

object ← AWSS3StorageCacheResolver

Implements

IImageCacheResolver

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

AWSS3StorageCacheResolver(IAmazonS3, string, string, MetadataCollection)

Initializes a new instance of the AWSS3StorageCacheResolver class.

```
public AWSS3StorageCacheResolver(IAmazonS3 amazonS3, string bucketName, string imagePath,
MetadataCollection metadata)
```

Parameters

`amazonS3` IAmazonS3

The Amazon S3 Client

`bucketName` string

The bucket name.

`imagePath` string

The image path.

`metadata` MetadataCollection

The metadata collection.

Methods

GetMetaDataAsync()

Asynchronously gets metadata associated with this image.

```
public Task<ImageCacheMetadata> GetMetaDataAsync()
```

Returns

Task<ImageCacheMetadata>

The ImageCacheMetadata.

OpenReadAsync()

Asynchronously gets the input image stream.

```
public Task<Stream> OpenReadAsync()
```

Returns

Task<Stream>

The Task<TResult>.

Class AWSS3StorageImageResolver

Namespace: SixLabors.ImageSharp.Web.AWS.Resolvers

Assembly: SixLabors.ImageSharp.Web.Providers.AWS.dll

Provides means to manage image buffers within the AWS S3 file system.

```
public class AWSS3StorageImageResolver : IImageResolver
```

Inheritance

object ← AWSS3StorageImageResolver

Implements

IImageResolver

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

AWSS3StorageImageResolver(IAmazonS3, string, string, GetObjectMetadataResponse?)

Initializes a new instance of the AWSS3StorageImageResolver class.

```
public AWSS3StorageImageResolver(IAmazonS3 amazonS3, string bucketName, string imagePath,
GetObjectMetadataResponse? metadataResponse = null)
```

Parameters

`amazonS3` IAmazonS3

The Amazon S3 Client

`bucketName` string

The bucket name.

`imagePath` string

The image path.

`metadataResponse` GetObjectMetadataResponse

Optional metadata response.

Methods

GetMetaDataAsync()

Asynchronously gets metadata associated with this image.

```
public Task<ImageMetadata> GetMetaDataAsync()
```

Returns

Task<ImageMetadata>

The ImageMetadata.

OpenReadAsync()

Asynchronously gets the input image stream.

```
public Task<Stream> OpenReadAsync()
```

Returns

Task<Stream>

The Task<TResult>.