Namespace SixLabors.ImageSharp.Web.Azure.Caching

Classes

AzureBlobStorageCache

Implements an Azure Blob Storage based cache.

AzureBlobStorageCacheOptions

Configuration options for the AzureBlobStorageCache.

Class AzureBlobStorageCache

Namespace: SixLabors.ImageSharp.Web.Azure.Caching

Assembly: SixLabors.ImageSharp.Web.Providers.Azure.dll

Implements an Azure Blob Storage based cache.

```
public class AzureBlobStorageCache : IImageCache
```

Inheritance

object ← AzureBlobStorageCache

Implements

IImageCache

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

AzureBlobStorageCache(IOptions<AzureBlobStorageCacheOptions>, IServiceProvider)

Initializes a new instance of the AzureBlobStorageCache class.

```
public AzureBlobStorageCache(IOptions<AzureBlobStorageCacheOptions> cacheOptions,
IServiceProvider serviceProvider)
```

Parameters

`cacheOptions` IOptions<AzureBlobStorageCacheOptions>

The cache options.

`serviceProvider` IServiceProvider

The current service provider.

Methods

CreateIfNotExists(AzureBlobStorageCacheOptions, PublicAccessType)

Creates a new container under the specified account if a container with the same name does not already exist.

```
public static Response<BlobContainerInfo> CreateIfNotExists(AzureBlobStorageCacheOptions
options, PublicAccessType accessType)
```

Parameters

`options` AzureBlobStorageCacheOptions

The Azure Blob Storage cache options.

`accessType` PublicAccessType

Optionally specifies whether data in the container may be accessed publicly and the level of access. BlobContainer specifies full public read access for container and blob data. Clients can enumerate blobs within the container via anonymous request, but cannot enumerate containers within the storage account. Blob specifies public read access for blobs. Blob data within this container can be read via anonymous request, but container data is not available. Clients cannot enumerate blobs within the container via anonymous request. None specifies that the container data is private to the account owner.

Returns

Response<BlobContainerInfo>

If the container does not already exist, a Response<T> describing the newly created container. If the container already exists, null.

GetAsync(string)

Gets the image resolver associated with the specified key.

```
public Task<IImageCacheResolver?> GetAsync(string key)
```

Parameters

`key` string

The cache key.

Returns

Task<IImageCacheResolver>

The IImageResolver.

SetAsync(string, Stream, ImageCacheMetadata)

Sets the value associated with the specified key.

```
public Task SetAsync(string key, Stream stream, ImageCacheMetadata metadata)
```

Parameters

`key` string

The cache key.

`stream` Stream

The stream containing the image to store.

`metadata` ImageCacheMetadata

The ImageCacheMetadata associated with the image to store.

Returns

Task

The task.

Class AzureBlobStorageCacheOptions

Namespace: SixLabors.ImageSharp.Web.Azure.Caching

Assembly: SixLabors.ImageSharp.Web.Providers.Azure.dll

Configuration options for the AzureBlobStorageCache.

```
public class AzureBlobStorageCacheOptions
```

Inheritance

object ← AzureBlobStorageCacheOptions

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Properties

BlobContainerClientFactory

Gets or sets a factory method to create an BlobContainerClient.

```
public Func<AzureBlobStorageCacheOptions, IServiceProvider, BlobContainerClient>?
BlobContainerClientFactory { get; set; }
```

Property Value

Func<AzureBlobStorageCacheOptions, IServiceProvider, BlobContainerClient>

CacheFolder

Gets or sets the cache folder's name that'll store cache files under the configured container. Must conform to Azure Blob Storage directory naming guidelines. https://learn.microsoft.com/en-

us/rest/api/storageservices/naming-and-referencing-containers--blobs--and-metadata#directory-names

```
public string? CacheFolder { get; set; }
```

Property Value

string

ConnectionString

Gets or sets the Azure Blob Storage connection string. https://docs.microsoft.com/en-us/azure/storage/common/storage-configure-connection-string.

```
public string ConnectionString { get; set; }
```

Property Value

string

ContainerName

Gets or sets the Azure Blob Storage container name. Must conform to Azure Blob Storage container naming guidelines. https://docs.microsoft.com/en-us/rest/api/storageservices/naming-and-referencing-containers--blobs--and-metadata#container-names

```
public string ContainerName { get; set; }
```

Property Value

string

Namespace SixLabors.ImageSharp.Web.Azure.Providers

Classes

AzureBlobContainerClientOptions
: Represents a single Azure Blob Storage connection and container.

AzureBlobStorageImageProvider
: Returns images stored in Azure Blob Storage.

AzureBlobStorageImageProviderOptions
: Configuration options for the AzureBlobStorageImageProvider provider.

Class AzureBlobContainerClientOptions

Namespace: SixLabors.ImageSharp.Web.Azure.Providers

Assembly: SixLabors.ImageSharp.Web.Providers.Azure.dll

Represents a single Azure Blob Storage connection and container.

```
public class AzureBlobContainerClientOptions
```

Inheritance

object ← AzureBlobContainerClientOptions

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Properties

BlobContainerClientFactory

Gets or sets a factory method to create an BlobContainerClient.

```
public Func<AzureBlobContainerClientOptions, IServiceProvider, BlobContainerClient>?
BlobContainerClientFactory { get; set; }
```

Property Value

Func<AzureBlobContainerClientOptions, IServiceProvider, BlobContainerClient>

ConnectionString

Gets or sets the Azure Blob Storage connection string. https://docs.microsoft.com/en-us/azure/storage/common/storage-configure-connection-string.

```
public string ConnectionString { get; set; }
```

Property Value

string

ContainerName

Gets or sets the Azure Blob Storage container name. Must conform to Azure Blob Storage container naming guidelines. https://docs.microsoft.com/en-us/rest/api/storageservices/naming-and-referencing-containers--blobs--and-metadata#container-names

```
public string ContainerName { get; set; }
```

Property Value

string

Class AzureBlobStorageImageProvider

Namespace: SixLabors.ImageSharp.Web.Azure.Providers

Assembly: SixLabors.ImageSharp.Web.Providers.Azure.dll

Returns images stored in Azure Blob Storage.

```
public class AzureBlobStorageImageProvider : IImageProvider
```

Inheritance

object ← AzureBlobStorageImageProvider

Implements

IImageProvider

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

AzureBlobStorageImageProvider(IOptions<AzureBlobStorageImageProviderOptions>, FormatUtilities, IServiceProvider)

Initializes a new instance of the AzureBlobStorageImageProvider class.

```
public AzureBlobStorageImageProvider(IOptions<AzureBlobStorageImageProviderOptions>
storageOptions, FormatUtilities formatUtilities, IServiceProvider serviceProvider)
```

Parameters

`storageOptions` IOptions<AzureBlobStorageImageProviderOptions>

The blob storage options.

`formatUtilities` FormatUtilities

Contains various format helper methods based on the current configuration.

`serviceProvider` IServiceProvider

The current service provider

Properties

Match

Gets or sets the method used by the resolver to identify itself as the correct resolver to use.

```
public Func<HttpContext, bool> Match { get; set; }
```

Property Value

Func<HttpContext, bool>

ProcessingBehavior

Gets the processing behavior.

```
public ProcessingBehavior ProcessingBehavior { get; }
```

Property Value

ProcessingBehavior

Methods

GetAsync(HttpContext)

Gets the image resolver associated with the context.

```
public Task<IImageResolver?> GetAsync(HttpContext context)
```

Parameters

`context` HttpContext

The current HTTP request context.

Returns

Task<IImageResolver>

The IImageResolver.

IsValidRequest(HttpContext)

Gets a value indicating whether the current request passes sanitizing rules.

```
public bool IsValidRequest(HttpContext context)
```

Parameters

`context` HttpContext

The current HTTP request context.

Returns

bool

The bool

Class AzureBlobStorageImageProviderOptions

Namespace: SixLabors.ImageSharp.Web.Azure.Providers

Assembly: SixLabors.ImageSharp.Web.Providers.Azure.dll

Configuration options for the AzureBlobStorageImageProvider provider.

```
public class AzureBlobStorageImageProviderOptions
```

Inheritance

object ← AzureBlobStorageImageProviderOptions

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Properties

BlobContainers

Gets or sets the collection of blob container client options.

```
public ICollection<AzureBlobContainerClientOptions> BlobContainers { get; set; }
```

Property Value

ICollection<AzureBlobContainerClientOptions>

Namespace SixLabors.ImageSharp.Web.Azure.Resolvers

Classes

AzureBlobStorageCacheResolver

Provides means to manage image buffers within the AzureBlobStorageCache.

AzureBlobStorageImageResolver

Provides means to manage image buffers within the Azure Blob file system.

Class AzureBlobStorageCacheResolver

Namespace: SixLabors.ImageSharp.Web.Azure.Resolvers

Assembly: SixLabors.ImageSharp.Web.Providers.Azure.dll

Provides means to manage image buffers within the AzureBlobStorageCache.

```
public class AzureBlobStorageCacheResolver : IImageCacheResolver
```

Inheritance

object ← AzureBlobStorageCacheResolver

Implements

IImageCacheResolver

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

AzureBlobStorageCacheResolver(BlobClient)

Initializes a new instance of the AzureBlobStorageCacheResolver class.

```
public AzureBlobStorageCacheResolver(BlobClient blob)
```

Parameters

`blob` BlobClient

The Azure blob.

Methods

GetMetaDataAsync()

Asynchronously gets metadata associated with this image.

```
public Task<ImageCacheMetadata> GetMetaDataAsync()
```

Returns

Task<ImageCacheMetadata>

The ImageCacheMetadata.

OpenReadAsync()

Asynchronously gets the input image stream.

```
public Task<Stream> OpenReadAsync()
```

Returns

Task<Stream>

The Task<TResult>.

Class AzureBlobStorageImageResolver

Namespace: SixLabors.ImageSharp.Web.Azure.Resolvers

Assembly: SixLabors.ImageSharp.Web.Providers.Azure.dll

Provides means to manage image buffers within the Azure Blob file system.

```
public class AzureBlobStorageImageResolver : IImageResolver
```

Inheritance

object ← AzureBlobStorageImageResolver

Implements

IImageResolver

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

AzureBlobStorageImageResolver(BlobClient)

Initializes a new instance of the AzureBlobStorageImageResolver class.

```
public AzureBlobStorageImageResolver(BlobClient blob)
```

Parameters

`blob` BlobClient

The Azure blob.

Methods

GetMetaDataAsync()

Asynchronously gets metadata associated with this image.

```
public Task<ImageMetadata> GetMetaDataAsync()
```

Returns

Task<ImageMetadata>

The ImageMetadata.

OpenReadAsync()

Asynchronously gets the input image stream.

```
public Task<Stream> OpenReadAsync()
```

Returns

Task<Stream>

The Task<TResult>.