

Namespace SixLabors.ImageSharp.Web. Azure.Caching

Classes

AzureBlobStorageCache

Implements an Azure Blob Storage based cache.

AzureBlobStorageCacheOptions

Configuration options for the [AzureBlobStorageCache](#).

Class AzureBlobStorageCache

Namespace: [SixLabors.ImageSharp.Web.Azure.Caching](#)

Assembly: [SixLabors.ImageSharp.Web.Providers.Azure.dll](#)

Implements an Azure Blob Storage based cache.

```
public class AzureBlobStorageCache : IImageCache
```

Inheritance

[object](#)  ← [AzureBlobStorageCache](#)

Implements

[IImageCache](#)

Inherited Members

[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  , [object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  , [object.ToString\(\)](#) 

Constructors

AzureBlobStorageCache(IOptions<AzureBlobStorageCacheOptions>, IServiceProvider)

Initializes a new instance of the [AzureBlobStorageCache](#) class.

```
public AzureBlobStorageCache(IOptions<AzureBlobStorageCacheOptions> cacheOptions,  
    IServiceProvider serviceProvider)
```

Parameters

cacheOptions [IOptions](#)  <[AzureBlobStorageCacheOptions](#)>

The cache options.

serviceProvider [IServiceProvider](#) 

The current service provider.

Methods

CreateIfNotExists(AzureBlobStorageCacheOptions, PublicAccessType)

Creates a new container under the specified account if a container with the same name does not already exist.

```
public static Response<BlobContainerInfo> CreateIfNotExists(AzureBlobStorageCacheOptions options, PublicAccessType accessType)
```

Parameters

options [AzureBlobStorageCacheOptions](#)

The Azure Blob Storage cache options.

accessType [PublicAccessType](#) 

Optionally specifies whether data in the container may be accessed publicly and the level of access. [BlobContainer](#)  specifies full public read access for container and blob data. Clients can enumerate blobs within the container via anonymous request, but cannot enumerate containers within the storage account. [Blob](#)  specifies public read access for blobs. Blob data within this container can be read via anonymous request, but container data is not available. Clients cannot enumerate blobs within the container via anonymous request. [None](#)  specifies that the container data is private to the account owner.

Returns

[Response](#)  [<BlobContainerInfo>](#) 

If the container does not already exist, a [Response<T>](#)  describing the newly created container. If the container already exists, [null](#) .

GetAsync(string)

Gets the image resolver associated with the specified key.

```
public Task<IImageCacheResolver?> GetAsync(string key)
```

Parameters

key [string](#)

The cache key.

Returns

[Task](#) <[IImageCacheResolver](#)>

The [IImageResolver](#).

SetAsync(string, Stream, ImageCacheMetadata)

Sets the value associated with the specified key.

```
public Task SetAsync(string key, Stream stream, ImageCacheMetadata metadata)
```

Parameters

key [string](#)

The cache key.

stream [Stream](#)

The stream containing the image to store.

metadata [ImageCacheMetadata](#)

The [ImageCacheMetadata](#) associated with the image to store.

Returns

[Task](#)

The task.

Class AzureBlobStorageCacheOptions

Namespace: [SixLabors.ImageSharp.Web.Azure.Caching](#)

Assembly: SixLabors.ImageSharp.Web.Providers.Azure.dll

Configuration options for the [AzureBlobStorageCache](#).

```
public class AzureBlobStorageCacheOptions
```

Inheritance

[object](#)  ← [AzureBlobStorageCacheOptions](#)

Inherited Members

[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  ,
[object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  ,
[object.ToString\(\)](#) 

Properties

BlobContainerClientFactory

Gets or sets a factory method to create an [BlobContainerClient](#) .

```
public Func<AzureBlobStorageCacheOptions, IServiceProvider, BlobContainerClient>?  
BlobContainerClientFactory { get; set; }
```

Property Value

[Func](#)  <[AzureBlobStorageCacheOptions](#), [IServiceProvider](#) , [BlobContainerClient](#)  >

CacheFolder

Gets or sets the cache folder's name that'll store cache files under the configured container. Must conform to Azure Blob Storage directory naming guidelines. <https://learn.microsoft.com/en->

[us/rest/api/storageservices/naming-and-referencing-containers--blobs--and-metadata#directory-names](https://docs.microsoft.com/en-us/rest/api/storageservices/naming-and-referencing-containers--blobs--and-metadata#directory-names)

```
public string? CacheFolder { get; set; }
```

Property Value

[string](#)

ConnectionString

Gets or sets the Azure Blob Storage connection string. <https://docs.microsoft.com/en-us/azure/storage/common/storage-configure-connection-string>.

```
public string ConnectionString { get; set; }
```

Property Value

[string](#)

ContainerName

Gets or sets the Azure Blob Storage container name. Must conform to Azure Blob Storage container naming guidelines. <https://docs.microsoft.com/en-us/rest/api/storageservices/naming-and-referencing-containers--blobs--and-metadata#container-names>

```
public string ContainerName { get; set; }
```

Property Value

[string](#)

Namespace SixLabors.ImageSharp.Web. Azure.Providers

Classes

AzureBlobContainerClientOptions

Represents a single Azure Blob Storage connection and container.

AzureBlobStorageImageProvider

Returns images stored in Azure Blob Storage.

AzureBlobStorageImageProviderOptions

Configuration options for the [AzureBlobStorageImageProvider](#) provider.

Class AzureBlobContainerClientOptions

Namespace: [SixLabors.ImageSharp.Web.Azure.Providers](#)

Assembly: [SixLabors.ImageSharp.Web.Providers.Azure.dll](#)

Represents a single Azure Blob Storage connection and container.

```
public class AzureBlobContainerClientOptions
```

Inheritance

[object](#)  ← [AzureBlobContainerClientOptions](#)

Inherited Members

[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  ,
[object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  ,
[object.ToString\(\)](#) 

Properties

BlobContainerClientFactory

Gets or sets a factory method to create an [BlobContainerClient](#) .

```
public Func<AzureBlobContainerClientOptions, IServiceProvider, BlobContainerClient>?  
BlobContainerClientFactory { get; set; }
```

Property Value

[Func](#)  <[AzureBlobContainerClientOptions](#), [IServiceProvider](#) , [BlobContainerClient](#)  >

ConnectionString

Gets or sets the Azure Blob Storage connection string. <https://docs.microsoft.com/en-us/azure/storage/common/storage-configure-connection-string>. 

```
public string ConnectionString { get; set; }
```

Property Value

string 

ContainerName

Gets or sets the Azure Blob Storage container name. Must conform to Azure Blob Storage container naming guidelines. <https://docs.microsoft.com/en-us/rest/api/storageservices/naming-and-referencing-containers--blobs--and-metadata#container-names> 

```
public string ContainerName { get; set; }
```

Property Value

string 

Class AzureBlobStorageImageProvider

Namespace: [SixLabors.ImageSharp.Web.Azure.Providers](#)

Assembly: [SixLabors.ImageSharp.Web.Providers.Azure.dll](#)

Returns images stored in Azure Blob Storage.

```
public class AzureBlobStorageImageProvider : IImageProvider
```

Inheritance

[object](#)  ← [AzureBlobStorageImageProvider](#)

Implements

[IImageProvider](#)

Inherited Members

[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  ,
[object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  ,
[object.ToString\(\)](#) 

Constructors

AzureBlobStorageImageProvider(IOptions<AzureBlobStorageImageProviderOptions>, FormatUtilities, IServiceProvider)

Initializes a new instance of the [AzureBlobStorageImageProvider](#) class.

```
public AzureBlobStorageImageProvider(IOptions<AzureBlobStorageImageProviderOptions>  
    storageOptions, FormatUtilities formatUtilities, IServiceProvider serviceProvider)
```

Parameters

[storageOptions](#) [IOptions](#)  <[AzureBlobStorageImageProviderOptions](#)>

The blob storage options.

formatUtilities FormatUtilities

Contains various format helper methods based on the current configuration.

serviceProvider IServiceProvider

The current service provider

Properties

Match

Gets or sets the method used by the resolver to identify itself as the correct resolver to use.

```
public Func<HttpContext, bool> Match { get; set; }
```

Property Value

Func<HttpContext, bool>

ProcessingBehavior

Gets the processing behavior.

```
public ProcessingBehavior ProcessingBehavior { get; }
```

Property Value

ProcessingBehavior

Methods

GetAsync(HttpContext)

Gets the image resolver associated with the context.

```
public Task<IImageResolver?> GetAsync(HttpContext context)
```

Parameters

context [HttpContext](#)

The current HTTP request context.

Returns

[Task](#) <[IImageResolver](#)>

The [IImageResolver](#).

IsValidRequest(HttpContext)

Gets a value indicating whether the current request passes sanitizing rules.

```
public bool IsValidRequest(HttpContext context)
```

Parameters

context [HttpContext](#)

The current HTTP request context.

Returns

[bool](#)

The [bool](#)

Class

AzureBlobStorageImageProviderOptions

Namespace: [SixLabors.ImageSharp.Web.Azure.Providers](#)

Assembly: [SixLabors.ImageSharp.Web.Providers.Azure.dll](#)

Configuration options for the [AzureBlobStorageImageProvider](#) provider.

```
public class AzureBlobStorageImageProviderOptions
```

Inheritance

[object](#)  ← [AzureBlobStorageImageProviderOptions](#)

Inherited Members

[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  ,
[object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  ,
[object.ToString\(\)](#) 

Properties

BlobContainers

Gets or sets the collection of blob container client options.

```
public ICollection<AzureBlobContainerClientOptions> BlobContainers { get; set; }
```

Property Value

[ICollection](#)  <[AzureBlobContainerClientOptions](#)>

Namespace SixLabors.ImageSharp.Web. Azure.Resolvers

Classes

AzureBlobStorageCacheResolver

Provides means to manage image buffers within the [AzureBlobStorageCache](#).

AzureBlobStorageImageResolver

Provides means to manage image buffers within the Azure Blob file system.

Class AzureBlobStorageCacheResolver

Namespace: [SixLabors.ImageSharp.Web.Azure.Resolvers](#)

Assembly: [SixLabors.ImageSharp.Web.Providers.Azure.dll](#)

Provides means to manage image buffers within the [AzureBlobStorageCache](#).

```
public class AzureBlobStorageCacheResolver : IImageCacheResolver
```

Inheritance

[object](#)  ← [AzureBlobStorageCacheResolver](#)

Implements

[IImageCacheResolver](#)

Inherited Members

[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  , [object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  , [object.ToString\(\)](#) 

Constructors

AzureBlobStorageCacheResolver(BlobClient)

Initializes a new instance of the [AzureBlobStorageCacheResolver](#) class.

```
public AzureBlobStorageCacheResolver(BlobClient blob)
```

Parameters

blob [BlobClient](#) 

The Azure blob.

Methods

GetMetadataAsync()

Asynchronously gets metadata associated with this image.

```
public Task<ImageCacheMetadata> GetMetadataAsync()
```

Returns

Task<[ImageCacheMetadata](#)>

The [ImageCacheMetadata](#).

OpenReadAsync()

Asynchronously gets the input image stream.

```
public Task<Stream> OpenReadAsync()
```

Returns

Task<[Stream](#)>

The [Task<TResult>](#).

Class AzureBlobStorageImageResolver

Namespace: [SixLabors.ImageSharp.Web.Azure.Resolvers](#)

Assembly: [SixLabors.ImageSharp.Web.Providers.Azure.dll](#)

Provides means to manage image buffers within the Azure Blob file system.

```
public class AzureBlobStorageImageResolver : IImageResolver
```

Inheritance

[object](#)  ← [AzureBlobStorageImageResolver](#)

Implements

[IImageResolver](#)

Inherited Members

[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  ,
[object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  ,
[object.ToString\(\)](#) 

Constructors

AzureBlobStorageImageResolver(BlobClient)

Initializes a new instance of the [AzureBlobStorageImageResolver](#) class.

```
public AzureBlobStorageImageResolver(BlobClient blob)
```

Parameters

blob [BlobClient](#) 

The Azure blob.

Methods

GetMetadataAsync()

Asynchronously gets metadata associated with this image.

```
public Task<ImageMetadata> GetMetadataAsync()
```

Returns

Task<[ImageMetadata](#)>

The [ImageMetadata](#).

OpenReadAsync()

Asynchronously gets the input image stream.

```
public Task<Stream> OpenReadAsync()
```

Returns

Task<[Stream](#)>

The [Task<TResult>](#).