

# SixDesk

Version 1.0

the Simulation Environment for SixTrack

## User's Reference Manual

R. De Maria, M. Giovannozzi, E. McIntosh, A. Mereghetti, F. Schmidt, I. Zacharov

Updated by: P. D. Hermes, D. Pellegrini, S. Kostoglou

### Abstract

SixTrack is a single particle tracking code widely used at CERN. One of the most important applications is the estimation of the dynamic aperture available in large storage rings like the Large Hadron Collider (LHC) or the Future Circular Collider (FCC). These studies require massive computing resources, consisting of scans over large parameter spaces probing non-linear beam dynamics over long times. The SixDesk environment is the simulation framework used to manage and control the large amount of information necessary for and produced by the studies.



# Acknowledgement

Some acknowledgements.



# Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
1.1	Work Flow . . . . .	1
1.2	The BOINC Platform for Volunteering Computing . . . . .	1
1.3	Pre-requisites . . . . .	1
<b>2</b>	<b>Giudelines and Common Pitfalls</b>	<b>3</b>
2.1	Choice of Platform . . . . .	3

## CONTENTS

# Chapter 1

## Introduction

### 1.1 Work Flow

Show workflow of production of results, both for BOINC (including “processed” folder) and HTCondor.

Retrieval of results depends on the submission platform:

- `run_results`: BOINC
- `run_status`: HTCondor, HTBoinc

### 1.2 The BOINC Platform for Volunteering Computing

BOINC vs local batch system (e.g. HTCondor)

### 1.3 Pre-requisites

SIXDESK is native to `lxplus.cern.ch`. Hence, for running in such an environment, the user does not need to set up anything. On the contrary, in case of a local machine or other distributed resources,

Table 1.1: Pre-Requisites

Component	reason
kerberos	to renew/check credentials via <code>klist</code> and <code>kinit</code>
AFS (local mount)	retrieval of optics files submission to BOINC via <code>spooldir</code>
HTCondor (local installation)	submission of jobs to local batch system
python2.7	SixDB computation of floating point scan parameters





## Chapter 2

# Guidelines and Common Pitfalls

### 2.1 Choice of Platform

HTCondor is convenient when:

1. results should be collected quickly. This can be the case when the user has short time to collect data or the simulation set-up is being defined. In the second case, indeed, one does not want to wait too long for proceeding;
2. short or few jobs per study. This can be the case when re-submission of selected cases is necessary, e.g. to complete a study when few points in the scan are missing;

The BOINC platform for volunteer computing is convenient in case of large simulation campaigns, i.e. when simulations are long or they are in high number (e.g. hundreds of thousands of jobs).

