

PART A: INNER JOINS
SIXOLISE KLAAS
11 SEPTEMBER 2026

Question 1:

```
1  --Question 1: Show every user who has a subscription. Match users to subscriptions.
2
3  ✓ SELECT a.user_id,
4          user_name,
5          subscription_id,
6          start_date
7  FROM joins.default.users AS a
8  INNER JOIN joins.default.subscriptions AS b
9  ON a.user_id = b.user_id
10
11
12
```

Add parameter

Table ▾ +

	¹ ₂ ³ user_id	^A _B ^C user_name	¹ ₂ ³ subscription_id	 start_date	
1	1	Nomvula	503	2026-03-10T00:00:00.000+00:00	
2	2	David	502	2026-02-01T00:00:00.000+00:00	
3	3	Anele	505	2026-04-05T00:00:00.000+00:00	
4	1	Nomvula	501	2026-01-15T00:00:00.000+00:00	

Question 2:

```
11  --Question 2: Show every subscription with its matching plan name and monthly price.
12  ✓ SELECT a.subscription_id,
13          user_id,
14          plan_name,
15          monthly_price
16  FROM joins.default.subscriptions AS a
17  INNER JOIN joins.default.plans AS b
18  ON a.plan_id = b.plan_id
19
20  |
21
```

Add parameter

Table ▾ +

	¹ ₂ ³ subscription_id	¹ ₂ ³ user_id	^A _B ^C plan_name	¹ ₂ ³ monthly_price	
1	501	1	Basic	79	
2	504	6	Standard	129	
3	503	1	Premium	199	
4	505	3	Family	249	
5	502	2	Standard	129	

Question 3:

20 --Question 3: Show every viewing session that has a matching show. Include the show title and genre.
21 SELECT a.session_id,
22 user_id,
23 show_title,
24 genre,
25 watch_minutes
26 FROM joins.default.viewing_sessions AS a
27 INNER JOIN joins.default.shows AS b
28 ON a.show_id = b.show_id
29

Add parameter

Table +

	¹ ₃ session_id	¹ ₃ user_id	^A _C show_title	^A _C genre	¹ ₃ watch_minutes
1	904	7	Comedy Hour	Comedy	20
2	903	1	Crime Time	Drama	60
3	902	2	Tech Tales	Documentary	30
4	901	1	Comedy Hour	Comedy	45

Question 4:

30 --Question 4: Show every viewing session with the user who watched it. Only show sessions with a matching user
31 SELECT a.user_name,
32 country,
33 session_id,
34 show_id,
35 watch_minutes
36 FROM joins.default.users AS a
37 INNER JOIN joins.default.viewing_sessions AS b
38 ON a.user_id = b.user_id
39

Add parameter

Table +

Q F I □

	^A _C user_name	^A _C country	¹ ₃ session_id	¹ ₃ show_id	¹ ₃ watch_minutes
1	Nomvula	Johannesburg	903	702	60
2	David	Cape Town	902	703	30
3	Anele	Durban	905	705	90
4	Nomvula	Johannesburg	901	701	45

Question 5:

```

40  --Question 5: Show users along with their subscriptions, the plan name, and the price. Use only users who have both a
    subscription and a valid plan
41  SELECT a.user_name,
42         country,
43         plan_name,
44         monthly_price,
45         start_date
46  FROM joins.default.users AS a
47  INNER JOIN joins.default.subscriptions AS b
48  ON a.user_id = b.user_id
49  INNER JOIN joins.default.plans AS c
50  ON b.plan_id = c.plan_id
51

```

Add parameter

Table ▼ +

	^A _C user_name	^A _C country	^A _C plan_name	¹ ₃ monthly_price	¹ ₃ start_date
1	Nomvula	Johannesburg	Premium	199	2026-03-10T00:00:00.000+00:00
2	David	Cape Town	Standard	129	2026-02-01T00:00:00.000+00:00
3	Anele	Durban	Family	249	2026-04-05T00:00:00.000+00:00
4	Nomvula	Johannesburg	Basic	79	2026-01-15T00:00:00.000+00:00

PART B: LEFT JOIN
 SIXOLISE KLAAS
 11 SEPTEMBER 2026

Question 6:

```

53  --PART B: LEFT JOINS
54  --Show every user and any subscriptions they have. Users without subscriptions must still appear
55
56  SELECT a.user_id,
57         user_name,
58         subscription_id,
59         start_date
60  FROM joins.default.users AS a
61  LEFT JOIN joins.default.subscriptions AS b
62  ON a.user_id = b.user_id
63  |

```

Add parameter

Table ▼ +

	¹ ₃ user_id	^A _C user_name	¹ ₃ subscription_id	¹ ₃ start_date
1	1	Nomvula	503	2026-03-10T00:00:00.000+00:00
2	2	David	502	2026-02-01T00:00:00.000+00:00
3	3	Anele	505	2026-04-05T00:00:00.000+00:00
4	4	Kabelo	null	null
5	5	Lerato	null	null
6	1	Nomvula	501	2026-01-15T00:00:00.000+00:00

Question 7:

```

64 --Question 7: Show every plan and the subscriptions on it. Plans with no subscribers must still appear.
65
66 ✓ SELECT a.plan_id,
67         plan_name,
68         subscription_id,
69         user_id
70 FROM joins.default.plans AS a
71 LEFT JOIN joins.default.subscriptions AS b
72 ON a.plan_id = b.plan_id

```

Add parameter

	1 ² plan_id	A ^B plan_name	1 ² subscription_id	1 ² user_id
1	10	Basic	501	1
2	11	Standard	504	6
3	12	Premium	503	1
4	13	Family	505	3
5	14	Mobile	null	null
6	11	Standard	502	2

Question 8:

```

74 --Question 8: Show every show and any viewing sessions on it. Shows that were never watched must still appear.
75
76 SELECT a.show_id,
77        show_title,
78        session_id,
79        watch_minutes
80 FROM joins.default.shows AS a
81 LEFT JOIN joins.default.viewing_sessions AS b
82 ON a.show_id = b.show_id

```

Add parameter

	1 ² show_id	A ^B show_title	1 ² session_id	1 ² watch_minutes
1	701	Comedy Hour	904	20
2	702	Crime Time	903	60
3	703	Tech Tales	902	30
4	704	Cooking Lab	null	null
5	706	Wild Earth	null	null
6	701	Comedy Hour	901	45

Question 9:

```

84  --Question 9: Show every viewing session and the user who watched it. Sessions referencing users that do not exist must still
    appear (with NULL user details).
85
86  SELECT a.session_id,
87         show_id,
88         watch_minutes,
89         a.user_id,
90         user_name
91  FROM joins.default.viewing_sessions AS a
92  LEFT JOIN joins.default.users AS b
93  ON a.user_id = b.user_id

```

Add parameter

	1 ² session_id	1 ² sho...	1 ² watch_minutes	1 ² user_id	1 ² user_name
1	901	701	45	1	Nomvula
2	902	703	30	2	David
3	903	702	60	1	Nomvula
4	904	701	20	7	null
5	905	705	90	3	Anele

Question 10:

```

95  --Question 10: Show every user, the plan they are on (if any), and the monthly price. Users without a subscription must still
    appear.
96
97  SELECT a.user_name,
98         country,
99         plan_name,
100        monthly_price
101  FROM joins.default.users AS a
102  LEFT JOIN joins.default.subscriptions AS b
103  ON a.user_id = b.user_id
104  LEFT JOIN joins.default.plans as c
105  ON b.plan_id = c.plan_id
106

```

Add parameter

	1 ² user_name	1 ² country	1 ² plan_name	1 ² monthly_price
1	Nomvula	Johannesburg	Premium	199
2	David	Cape Town	Standard	129
3	Anele	Durban	Family	249
4	Kabelo	Pretoria	null	null
5	Lerato	Port Elizabeth	null	null
6	Nomvula	Johannesburg	Basic	79

Part C: FULL OUTER JOIN
SIXOLISE KLAAS
11 SEPTEMBER 2026

Question 11:

```

107 --Part C – FULL OUTER JOIN
108 --Question 11: Show every user and every subscription, including users without subscriptions AND subscriptions referencing
109 --users that do not exist.
110 SELECT a.user_id,
111        user_name,
112        subscription_id,
113        start_date
114 FROM joins.default.users AS a
115 FULL OUTER JOIN joins.default.subscriptions AS b
116 ON a.user_id = b.user_id

```

Add parameter

	1 ² user_id	A ³ user_name	1 ² subscription_id	start_date
1	3	Anele	505	2026-04-05T00:00:00.000+00:00
2	4	Kabelo	null	null
3	2	David	502	2026-02-01T00:00:00.000+00:00
4	5	Lerato	null	null
5	1	Nomvula	503	2026-03-10T00:00:00.000+00:00
6	1	Nomvula	501	2026-01-15T00:00:00.000+00:00
7	null	null	504	2026-03-20T00:00:00.000+00:00

Question 12:

```

119 --Question 12: Show every plan and every subscription, including plans without subscribers AND any subscription referencing a
120 --plan that does not exist.
121 SELECT a.plan_id,
122        plan_name,
123        subscription_id,
124        user_id
125 FROM joins.default.plans AS a
126 FULL OUTER JOIN joins.default.subscriptions AS b
127 ON a.plan_id = b.plan_id

```

Add parameter

	1 ² plan_id	A ³ plan_name	1 ² subscription_id	1 ² user_id
1	11	Standard	504	6
2	14	Mobile	null	null
3	13	Family	505	3
4	12	Premium	503	1
5	10	Basic	501	1
6	11	Standard	502	2

Question 13:

```

128 --Question 13: Show every show and every viewing session, including shows that were never watched AND sessions referencing
    shows that do not exist.
129 SELECT a.show_id,
130         show_title,
131         session_id,
132         watch_minutes
133 FROM joins.default.shows AS a
134 FULL OUTER JOIN joins.default.viewing_sessions AS b
135 ON a.show_id = b.show_id

```

Add parameter

	¹ ₃ show_id	^B _C show_title	¹ ₃ session_id	¹ ₃ watch_minutes
1	704	Cooking Lab	null	null
2	701	Comedy Hour	904	20
3	703	Tech Tales	902	30
4	702	Crime Time	903	60
5	706	Wild Earth	null	null
6	701	Comedy Hour	901	45
7	null	null	905	90

Question 14:

```

137 --Question 14: Show every user and every viewing session, including users with no sessions AND sessions referencing users who
    do not exist.
138 SELECT a.user_id,
139         user_name,
140         session_id,
141         show_id,
142         watch_minutes
143 FROM joins.default.users AS a
144 FULL OUTER JOIN joins.default.viewing_sessions AS b
145 ON a.user_id = b.user_id

```

Add parameter

	¹ ₃ user_id	^B _C user_name	¹ ₃ session_id	¹ ₃ show_id	¹ ₃ watch_minutes
1	3	Anele	905	705	90
2	2	David	902	703	30
3	null	null	904	701	20
4	1	Nomvula	901	701	45
5	1	Nomvula	903	702	60
6	4	Kabelo	null	null	null
7	5	Lerato	null	null	null

Question 15:

```

147 --Question 15: Show every user, every subscription, and every plan in one query – using FULL OUTER JOIN throughout. This is
    the hardest question – get all gaps visible at once.
148 SELECT a.user_id,
149         user_name,
150         subscription_id,
151         b.plan_id,
152         plan_name
153 FROM joins.default.users AS a
154 FULL OUTER JOIN joins.default.subscriptions AS b
155 ON a.user_id = b.user_id
156 FULL OUTER JOIN joins.default.plans as c
157 ON b.plan_id = c.plan_id

```

Add parameter

Table

+

Q 🔍 📄 📊 📅 ^ ✕

	¹ ₃ user_id	^A ₀ user_name	¹ ₃ subscription_id	¹ ₃ plan_id	^A ₀ plan_name
1	2	David	502	11	Standard
2	null	null	504	11	Standard
3	3	Anele	505	13	Family
4	1	Nomvula	503	12	Premium
5	4	Kabelo	null	null	null
6	5	Lerato	null	null	null
7	1	Nomvula	501	10	Basic
8	null	null	null	null	Mobile