
5.28Enhanced Photocatalytic Activity of Hierarchical TiO₂ Structuressubsection.5.2

www.SurveyX.cn

Kinetics and Factors in Slurry or Immobilized Photocatalytic Membrane Reactors for Environmental Remediation: A Survey

www.surveyx.cn

Abstract

This survey paper provides a comprehensive analysis of the kinetics and influencing factors in slurry and immobilized photocatalytic membrane reactors, emphasizing their critical role in environmental remediation. Photocatalytic membrane reactors (PMRs) integrate photocatalysis with membrane technology, offering a sustainable solution for degrading pollutants such as volatile organic compounds. The study highlights the significance of understanding reaction kinetics and material properties, particularly the use of hierarchical TiO_2 structures, which enhance photocatalytic efficiency. The survey explores various kinetic models, including stochastic and deterministic approaches, and advanced analytical methods like non-negative matrix factorization, to elucidate reaction dynamics and improve reactor performance. Factors such as material properties, reaction conditions, and reactor design are scrutinized for their impact on photocatalytic efficiency. The comparison between slurry and immobilized reactors reveals distinct advantages and challenges, with implications for optimizing system design and operation. Recent advancements in material science and kinetic modeling are discussed, underscoring their potential to enhance the applicability and effectiveness of PMRs in environmental cleanup efforts. The paper concludes by identifying future research directions, including the development of more accurate kinetic models and novel analytical techniques, to further advance the field of photocatalytic membrane reactors.

1 Introduction

1.1 Relevance to Environmental Remediation

Photocatalytic membrane reactors (PMRs) are crucial in mitigating environmental pollution by providing sustainable solutions for degrading harmful pollutants. The synergy between photocatalysis and membrane technology enhances the breakdown of contaminants, such as volatile organic compounds (VOCs), which pose significant health risks even at low concentrations [1]. Understanding the complexity of catalytic processes and their kinetics is vital for elucidating reaction mechanisms and improving catalyst efficiency [2]. This knowledge is essential for optimizing PMR performance in environmental applications. Additionally, ensuring the long-term stability of these systems requires establishing necessary and sufficient conditions for effective pollution mitigation [3]. By overcoming these challenges, PMRs significantly contribute to sustainable practices aimed at reducing environmental pollution and protecting public health.

1.2 Structure of the Survey

This survey offers a comprehensive analysis of the kinetics and factors influencing slurry or immobilized photocatalytic membrane reactors in environmental remediation. It begins with an introduction




Figure 1: chapter structure

that highlights the importance of PMRs in addressing environmental pollution and promoting sustainability. The subsequent background and core concepts section covers the foundational principles of photocatalysis and membrane technology, emphasizing their integration in environmental cleanup. The kinetics section investigates the critical role of kinetics in these systems, discussing various models and theories that clarify reaction rates and mechanisms. Following this, factors affecting photocatalytic efficiency, including material properties, reaction conditions, and operational parameters, are examined. A comparative analysis of slurry versus immobilized PMRs is presented, focusing on design considerations and photocatalyst support structures. The applications section illustrates practical examples and recent advancements in utilizing these reactors for environmental remediation. The conclusion summarizes key findings and suggests future research directions, underscoring the ongoing development and optimization of these innovative systems. The following sections are organized as shown in Figure 1.

2 Background and Core Concepts

2.1 Fundamental Concepts of Photocatalysis

Photocatalysis accelerates chemical reactions using light energy and a photocatalyst, with titanium dioxide (TiO_2) being widely used due to its stability, non-toxicity, and effectiveness in degrading organic pollutants under UV light [4]. Enhancements in TiO_2 surface area and porosity can significantly boost its photocatalytic performance by improving reactant interaction and light absorption [4]. Understanding the distribution of residence times (DTS) is crucial for optimizing reactor design to maximize pollutant and photocatalyst contact while maintaining fluid dynamics and reaction kinetics [1].

Advanced analytical techniques, such as time-resolved Raman spectroscopy, are instrumental in identifying species and analyzing reaction kinetics, thereby elucidating complex interactions and transformation pathways in photocatalytic processes [5]. Integrating non-equilibrium thermodynamics with electron transfer kinetics provides a comprehensive framework for assessing the stability and efficiency of electrochemical interfaces in photocatalytic systems, which is vital for developing effective environmental remediation processes, including VOC degradation [6].

2.2 Membrane Technology in Environmental Remediation

Membrane technology is essential in environmental remediation, facilitating efficient pollutant removal and resource recovery. By integrating membranes with photocatalytic systems, simultaneous contaminant degradation and product separation are achieved, enhancing overall cleanup efficiency. Membranes selectively permeate specific molecules, concentrating pollutants for subsequent treatment, especially beneficial for complex waste streams where traditional methods may be inadequate [1].

Photocatalytic membrane reactors (PMRs) combine the strengths of photocatalysis and membrane filtration, creating a synergistic effect that enhances organic pollutant degradation. In PMRs, the membrane serves as both a barrier and a support for the photocatalyst, facilitating interactions among light, catalyst, and pollutants, resulting in higher reaction rates and improved pollutant removal compared to standalone systems [2]. Advanced membrane materials, such as hierarchical TiO_2 structures, enhance photocatalytic activity by increasing surface area and light absorption [4]. These materials are designed to withstand harsh conditions, ensuring long-term stability and reduced maintenance costs.

Membrane technology supports sustainable development goals by minimizing energy consumption and chemical use, operating typically at ambient conditions, thus lowering energy requirements compared to thermal or chemical treatments [3]. Innovations in design and materials also address membrane fouling, enhancing applicability across diverse environmental contexts.

2.3 Slurry and Immobilized Photocatalytic Membrane Reactors

Slurry and immobilized photocatalytic membrane reactors present distinct approaches to integrating photocatalysis with membrane technology, each offering specific advantages and challenges. Slurry reactors, with dispersed photocatalyst particles, maximize catalyst-pollutant contact, enhancing mass transport and degradation efficiency [4]. However, they require additional filtration to separate catalyst particles from treated effluent, preventing secondary pollution.

Conversely, immobilized reactors feature a fixed photocatalyst on or within the membrane surface, simplifying separation and enhancing catalyst stability and reusability, thereby reducing operational costs. Yet, immobilization can limit surface area and hinder mass transport, potentially affecting photocatalytic efficiency [4].

The choice between slurry and immobilized reactors depends on specific applications and desired outcomes. Slurry reactors are suitable for high reaction rates, while immobilized systems offer straightforward operation and catalyst recovery. Both reactor types significantly advance photocatalytic membrane technology, providing adaptable solutions for various environmental remediation challenges. They optimize photocatalytic processes, such as VOC degradation in air purification, through detailed analysis of gas flow behavior and chemical kinetics. Advancements in nanostructured TiO_2 materials, known for their superior photocatalytic properties due to hierarchical microstructures, further enhance reaction kinetics and mass transport, making them suitable for diverse applications in environmental cleanup and energy-related fields [5, 4, 6, 2, 1].

In recent years, the study of kinetics has gained significant attention, particularly in the context of photocatalytic membrane reactors. Understanding the underlying kinetic principles is crucial for optimizing process efficiency and developing effective models. As illustrated in Figure 2, the hierarchical structure of key concepts related to kinetics in these systems is depicted, emphasizing the importance of kinetics in enhancing process efficiency. This figure highlights not only the role of various kinetic models and theories but also the critical choice between stochastic and deterministic approaches, alongside novel analytical methods that contribute to a deeper understanding of kinetic behavior in photocatalytic processes. By synthesizing these elements, we can better appreciate the

complexities involved in kinetic analysis and its implications for future research and application in the field.




Figure 2: This figure shows the hierarchical structure of key concepts related to kinetics in photocatalytic membrane reactors, highlighting the importance of kinetics in process efficiency, the role of kinetic models and theories, the choice between stochastic and deterministic models, and novel analytical methods for enhancing kinetic understanding.

3 Kinetics in Photocatalytic Membrane Reactors

3.1 Importance of Kinetics in Photocatalytic Processes

Kinetics is pivotal in photocatalytic processes, impacting both efficiency and effectiveness in environmental remediation. The rate at which reactants transform into products, dictated by kinetic parameters, is crucial for optimizing reaction efficiency and maintaining system stability [3]. In photocatalytic membrane reactors, understanding flow dynamics and kinetics is essential for pollutant degradation, with tubular reactor flow modes highlighting the importance of kinetics in design and operation [1]. The development of TiO_2 films with controlled parameters enhances photocatalytic activity, especially with hierarchically organized nanostructures [4].

In multicomponent systems, complex interactions create unique dynamics, necessitating a deep understanding for performance prediction and enhancement [7]. The morphology of electrochemical interfaces also affects energy applications, influencing photocatalytic process efficiency and stability [6]. Thus, a solid grasp of kinetic principles is vital for designing and optimizing photocatalytic membrane reactors, ensuring effective pollutant degradation and advancing sustainable practices through improved mass transport and photon absorption [2, 4, 1].

3.2 Kinetic Models and Theories

Kinetic models and theories are instrumental in elucidating photocatalytic processes by detailing reaction mechanisms and rates. The Langmuir-Hinshelwood model, for instance, quantifies the mineralization of stearic acid over time, offering insights into reaction kinetics [4]. This model effectively describes reactant adsorption onto photocatalyst surfaces, a critical catalytic step.

In multicomponent systems, a framework accommodating multiple timescales and interactions is necessary, emphasizing the importance of these factors for accurate modeling [7]. Stochastic models, capturing inherent randomness and fluctuations, provide an alternative to deterministic models, particularly in systems where precise control is challenging [8].

Numerical nonlinear analysis allows for deriving kinetic parameters, determining rate constants without precise initial concentration values [9]. Advanced analytical techniques, such as non-negative

matrix factorization (NMF), enhance the study of reaction kinetics by recovering component spectra and kinetics from time-resolved Raman data [5]. Non-equilibrium thermodynamic stability theory offers a novel perspective on electrochemical interface morphology, contrasting traditional kinetics and optimizing photocatalytic efficiency [6]. These models and theories, along with detailed analyses, significantly enhance our understanding of photocatalytic processes, optimizing air purification systems through precise control over parameters like gas flow and chemical kinetics [2, 1].

3.3 Stochastic vs. Deterministic Kinetic Models

Choosing between stochastic and deterministic models is crucial for accurately capturing reaction dynamics in photocatalytic membrane reactors. Stochastic models excel in understanding molecular-level fluctuations, gaining relevance with advancements in experimental techniques observing single-cell reaction networks. Deterministic models, based on ordinary differential equations, predict overall system behavior under steady conditions. The model choice affects reactor performance characterization and kinetic parameters related to space time, concentration, and humidity [4, 3, 8, 1].

Deterministic models provide straightforward representations under uniform conditions, but the randomness and complexity of reactions challenge their applicability. Stochastic models incorporate random variables to account for fluctuations, suitable for complex systems with significant noise [8]. They represent variability in reaction rates and external effects, crucial for multicomponent systems. The choice depends on system attributes, with stochastic models preferred for significant fluctuations or molecular analyses, and deterministic models for stable systems capturing average behaviors. Integrating both approaches enhances understanding and prediction of photocatalytic processes, optimizing reactors for environmental remediation [2, 7, 3, 8].

3.4 Novel Analytical Methods for Kinetics

Innovative analytical methods have emerged to enhance understanding of kinetics in photocatalytic systems. Theoretical modeling explores kinetic examples aligned with local and global boundedness, evaluating process stability and efficiency [3]. Non-negative matrix factorization (NMF) applied to time-resolved data decomposes a non-negative matrix into spectra and kinetics, revealing intricate reaction details [5]. This method enhances understanding of efficiencies and interactions in photocatalytic systems.

These methods improve understanding of photocatalytic kinetics by providing insights into reactor characterization, material properties, and advanced kinetic analysis. They enable systematic analysis of gas flow behavior, optimize TiO_2 microstructure for enhanced performance, and apply sophisticated data analysis for accurate rate constant determination. This comprehensive approach facilitates reactor design and parameter optimization, leading to efficient photocatalytic processes for applications like air purification [5, 4, 9, 2, 1].

As illustrated in Figure 3, the hierarchical classification of these novel analytical methods emphasizes the interplay between theoretical modeling, non-negative matrix factorization, and the optimization of TiO_2 microstructure. By integrating theoretical modeling with advanced data analysis, these approaches advance photocatalysis and its environmental remediation applications.

4 Factors Influencing Photocatalytic Efficiency

4.1 Material Properties and Structural Factors

The efficiency of photocatalytic membrane reactors is heavily influenced by the material properties and structural characteristics employed. The stability of these systems is contingent upon materials that maintain structural integrity under diverse operational conditions, as highlighted by Koleva et al. [3]. Advances in three-dimensional hierarchical morphologies of TiO_2 have significantly improved photocatalytic performance by enhancing surface area and reactant interactions [4]. Monolithic supports coated with TiO_2 in tubular reactors exemplify how material properties contribute to photocatalytic efficiency by optimizing light exposure and reactant interaction [1]. The complexity of phase coexistence and kinetic constraints necessitates sophisticated theoretical approaches to further enhance material performance [7]. Numerical nonlinear analysis (NLA) offers advantages in determining rate constants, especially in scenarios with ambiguous data [9]. Innovations in




Figure 3: This figure illustrates the hierarchical classification of novel analytical methods for understanding kinetics in photocatalytic systems, emphasizing theoretical modeling, non-negative matrix factorization, and TiO₂ microstructure optimization.

material science, particularly in synthesizing nanostructured TiO₂ with hierarchical microstructures, are critical for developing efficient and sustainable photocatalytic systems. These advancements optimize reaction kinetics and mass transport, crucial for applications such as VOC degradation in air purification systems. Understanding the interplay between morphology and electron transfer dynamics can further optimize photocatalytic performance, leading to more reliable designs for environmental remediation technologies [4, 2, 6, 1].

4.2 Reaction Conditions and Kinetic Modeling

Reaction conditions critically affect kinetic modeling and reactor performance, influencing factors such as temperature, pressure, light intensity, and reactant concentration. Koleva et al. provide a theoretical framework emphasizing the importance of stability under varying conditions [3]. Traditional kinetic models often assume constant rate constants, which can lead to discrepancies between predicted and actual performance [9]. Stochastic models offer a solution by incorporating randomness to account for fluctuations in reaction environments, though they pose computational challenges, particularly for large systems [8]. The interaction between operational conditions and electron transfer kinetics is crucial for optimizing reactor performance and ensuring stability [6]. Integrating insights from these studies can lead to robust kinetic models that accurately reflect the complexities of photocatalytic reactions, enhancing environmental remediation efforts.

4.3 Operational Parameters and Reactor Design

The efficiency of photocatalytic processes in membrane reactors is significantly influenced by operational parameters and reactor design. Key parameters such as flow rate, light intensity, and reactant concentration are critical for optimizing reaction kinetics and pollutant degradation efficiency. Understanding these parameters is essential for optimizing reactor design and improving VOC degradation rates, as variations can lead to changes in reaction rates and mechanisms [2, 9, 1]. Reactor design, including geometry and photocatalyst support arrangement, impacts fluid dynamics and light distribution. Tubular reactors with monolithic supports coated with TiO₂ enhance performance by providing stable platforms and facilitating optimal light penetration [1]. Numerical Nonlinear Analysis (NLA) offers insights into the effects of operational parameters on reaction kinetics, accounting for variability and enabling more accurate models [9]. Incorporating advanced insights into reactor design and operation, such as optimizing photocatalytic materials like nanostructured TiO₂, can enhance efficiency. Understanding the relationships between reactor kinetics, photocatalyst properties, and mass transport dynamics is crucial for optimizing VOC degradation in air purification applications [5, 4, 6, 2, 1]. By optimizing both physical and operational aspects of the reactor, pollutant degradation can be enhanced, leading to more sustainable environmental remediation outcomes.

4.4 External Interferences and Kinetic Analysis

External interferences significantly influence the kinetic analysis of photocatalytic processes, complicating accurate modeling and measurement of reaction dynamics. The complexity in multicomponent

systems, where interactions among chemical species result in unique kinetic behaviors, presents challenges for prediction and quantification [7]. Stochastic processes, modeled through Markov Chains, provide a framework for understanding the variability and randomness in these systems [8]. This approach captures the probabilistic nature of reactions, addressing fluctuations often overlooked by deterministic models. Extracting individual component spectra from measured data is hindered by interference among vibrational bands of different species. Advanced techniques like non-negative matrix factorization enable the decomposition of complex data into distinct spectral components, enhancing kinetic analyses [5]. A comprehensive strategy integrating theoretical modeling, stochastic analysis, and advanced data processing is essential to address external interferences in kinetic analysis. This approach improves the accuracy of component identification and reaction kinetics, adapting to challenges posed by varying concentrations and interactions among multiple species [5, 7, 8, 9, 6]. By integrating these strategies, researchers can enhance the reliability of kinetic analyses and gain deeper insights into factors influencing photocatalytic efficiency, advancing the development of effective environmental remediation technologies.

5 Slurry vs. Immobilized Photocatalytic Membrane Reactors

5.1 Reactor Design and Photocatalyst Support

The design of photocatalytic membrane reactors and the development of photocatalyst support structures are crucial to enhancing system efficiency. Optimizing these processes for air purification necessitates a comprehensive understanding of reactor behavior, including gas flow dynamics and chemical kinetics, as influenced by variables such as space time, relative humidity, and reactant concentrations. Advances in synthesizing nanostructured TiO_2 with hierarchical organization have shown that morphological properties, tailored through precise deposition techniques, significantly boost photocatalytic performance by improving reaction kinetics, mass transport, and photon absorption [4, 1].

Different reactor configurations, like slurry and immobilized reactors, require specific design considerations. In slurry reactors, the photocatalyst is dispersed within the reaction medium, enhancing mass transport and light penetration for effective contaminant degradation, though catalyst recovery from the treated effluent may necessitate additional filtration. Conversely, immobilized reactors feature photocatalysts coated or embedded on the membrane surface, improving separation efficiency by keeping the catalyst stationary. This design enhances photocatalytic reactions through advanced materials like hierarchically organized TiO_2 , engineered for high surface area and porosity [4, 2, 6, 1]. While immobilization reduces costs and maintenance, it may limit surface area available for reactions, affecting efficiency.

A notable design is the use of tubular reactors with monolithic supports covered in TiO_2 , which maximizes light exposure and reaction efficiency [1]. The monolithic support provides a stable platform for the photocatalyst, optimizing interaction with light and reactants. Additionally, the hierarchical structure of TiO_2 enhances activity by increasing surface area and light absorption.

Reactor design and photocatalyst support selection must align with specific application requirements, balancing reaction rate, catalyst recovery, and operational stability. By analyzing gas flow, chemical kinetics, and the unique hierarchical structures of photocatalytic materials, highly efficient and sustainable reactors for environmental remediation can be designed. This approach leverages advanced properties of nanostructured TiO_2 , optimizing mass transport and maximizing performance in air purification and VOC degradation applications [4, 6, 1].

5.2 Enhanced Photocatalytic Activity of Hierarchical TiO_2 Structures

The development of hierarchical TiO_2 structures has significantly advanced photocatalysis, particularly in membrane reactors. These structures, synthesized through innovative methods like template-free reactive Pulsed Laser Deposition (PLD), enhance light absorption and mass transport capabilities [4]. Their hierarchical organization increases surface area, providing more active sites for reactions and promoting efficient reactant interaction.

Hierarchical TiO_2 's unique morphology allows superior light harvesting, as increased surface roughness and porosity facilitate multiple light scattering events, enhancing photon absorption and electron-hole pair generation crucial for photocatalytic activity. Enhanced mass transport properties accelerate

pollutant degradation by providing efficient access to active sites. The 3D multi-scale morphology maximizes surface area-to-volume ratio and creates effective distribution channels, optimizing both mass transport and photon absorption [4, 7, 6, 1].

In photocatalytic membrane reactors, hierarchical TiO₂ structures offer high efficiency and stability, ensuring long-term performance under operational conditions and reducing maintenance needs. These nanostructured materials, synthesized via template-free PLD, exhibit superior degradation kinetics and enhanced photocatalytic properties compared to standard TiO₂ powders. Their high porosity and thermal stability contribute to consistent performance across various conditions, reinforcing the reliability and effectiveness of photocatalytic reactors for environmental applications [4, 1].

6 Applications in Environmental Remediation

6.1 Examples of Pollutants Degraded by Photocatalytic Membrane Reactors

Photocatalytic membrane reactors are highly effective in degrading a variety of environmental pollutants, showcasing their potential in remediation efforts. These reactors efficiently decompose volatile organic compounds such as methanol and ethanol, which are prevalent in industrial effluents and pose significant environmental and health risks [1]. The successful degradation of these alcohols highlights the practical utility of photocatalytic technology in reducing pollution from organic solvents and hazardous substances. By leveraging the distinctive properties of photocatalysts like TiO₂, these systems transform harmful pollutants into less toxic byproducts, thereby contributing to a safer and cleaner environment. This capability underscores the versatility and efficacy of photocatalytic membrane reactors in addressing a wide range of contamination issues.

6.2 Case Studies and Recent Advancements

Recent advancements in photocatalytic membrane reactors focus on optimizing material properties and reaction kinetics to enhance environmental remediation applications. Notably, hierarchically organized nanostructured TiO₂ films have been developed, exhibiting superior photocatalytic activity due to increased surface area and enhanced light absorption. These films, produced through methods like template-free reactive Pulsed Laser Deposition (PLD), show potential beyond traditional photocatalysis, with ongoing research aimed at improving their mechanical stability and deposition parameters [4].

Kinetic analysis has progressed with the adoption of Numerical Nonlinear Analysis (NLA), which provides robust rate constant determination in photocatalytic processes. This method yields consistent and accurate rate constants, comparable to traditional approaches, and offers flexibility in cases with uncertain initial concentration values, making it a valuable tool for kinetic studies in complex systems [9].

Additionally, the development of stochastic models offers a detailed representation of chemical kinetics in photocatalytic systems, accounting for inherent randomness and fluctuations in reaction environments. Future research may focus on expanding these models' mathematical foundations and addressing computational challenges in large systems to enhance their predictive capabilities [8].

These advancements reflect ongoing efforts to refine materials, methods, and models in photocatalytic membrane reactors. By integrating advanced photocatalytic techniques, including reactor behavior characterization and chemical kinetics optimization in multicomponent mixtures, researchers aim to develop innovative environmental remediation systems. These systems are designed to effectively target a wide range of pollutants while overcoming operational challenges, utilizing hierarchical nanostructured TiO₂ to enhance reaction kinetics and maximize surface area for improved mass transport and photon absorption. Furthermore, the application of non-negative matrix factorization in time-resolved Raman spectroscopy facilitates precise identification of constituent species and reaction rates, enhancing the effectiveness and sustainability of these remediation efforts [5, 4, 7, 6, 1].

7 Conclusion

This survey has delved into the intricacies of slurry and immobilized photocatalytic membrane reactors, underscoring their pivotal role in environmental remediation efforts. By integrating pho-

photocatalysis with membrane technology, these reactors offer a potent solution for the degradation of diverse pollutants, with materials such as TiO_2 playing a crucial role in enhancing reaction efficiency. The exploration of kinetics has highlighted the importance of balanced energy and matter exchanges for maintaining stability and optimizing reactor performance. Advanced kinetic models, encompassing stochastic approaches and nonlinear numerical analysis, provide critical insights into the dynamics of these reactions, accommodating the complexities encountered in practical applications.

The investigation also identified the significant impact of material properties and reactor design on photocatalytic efficiency, with hierarchical TiO_2 structures emerging as a key advancement. The study further examined the influence of external interferences and operational parameters on reaction kinetics, emphasizing the need for robust kinetic models that can accurately predict reactor behavior across varying conditions. Moving forward, research should focus on refining these models to bolster predictive accuracy, which is essential for optimizing photocatalytic processes. Additionally, the development of innovative analytical techniques, such as non-negative matrix factorization, holds promise for effectively recovering component spectra and reaction kinetics, even amidst challenging noisy environments. Advancing these areas will enhance the efficiency and sustainability of photocatalytic membrane reactors, fostering their broader application in environmental remediation.

References

- [1] Marie Faure, Mark Furman, Serge Corbel, Marie-Christiane Carré, Fabien Gérardin, and Orfan Zahraa. Caractérisation de réacteurs photocatalytiques utilisés pour le traitement de l'air, 2009.
- [2] Ib Chorkendorff and Johannes W Niemantsverdriet. *Concepts of modern catalysis and kinetics*. John Wiley & Sons, 2017.
- [3] Maria K. Koleva and L. A. Petrov. "chaotic" kinetics, macroscopic fluctuations and long-term stability of the catalytic systems, 2004.
- [4] F. Di Fonzo, C. S. Casari, V. Russo, M. F. Brunella, A. Li Bassi, and C. E. Bottani. Hierarchically organized nanostructured tio2 for photocatalysis applications, 2008.
- [5] Robert Luce, Peter Hildebrandt, Uwe Kuhlmann, and Jörg Liesen. Using separable non-negative matrix factorization techniques for the analysis of time-resolved raman spectra, 2017.
- [6] Dimitrios Fraggedakis and Martin Z. Bazant. Tuning the stability of electrochemical interfaces by electron transfer reactions, 2020.
- [7] Filipe C. Thewes, Matthias Krüger, and Peter Sollich. Mobility-induced kinetic effects in multicomponent mixtures, 2024.
- [8] Enrico Bibbona. Stochastic chemical kinetics. theory and (mostly) systems biological applications, p. erdi, g. lente. springer (2014), 2014.
- [9] Christopher G. Jesudason. I. determination of chemical reaction rate constants by numerical nonlinear analysis: differential methods, 2011.

Disclaimer:

SurveyX is an AI-powered system designed to automate the generation of surveys. While it aims to produce high-quality, coherent, and comprehensive surveys with accurate citations, the final output is derived from the AI's synthesis of pre-processed materials, which may contain limitations or inaccuracies. As such, the generated content should not be used for academic publication or formal submissions and must be independently reviewed and verified. The developers of SurveyX do not assume responsibility for any errors or consequences arising from the use of the generated surveys.

www.SurveyX.cn