
Remote Sensing Semantic Segmentation and Unsupervised Domain Adaptation: A Survey

www.surveyx.cn

Abstract

Remote sensing, semantic segmentation, and unsupervised domain adaptation are pivotal in advancing Earth observation by enhancing geospatial data analysis. This survey explores these interdisciplinary fields, emphasizing their integration with AI technologies. Remote sensing facilitates environmental monitoring, urban planning, and agriculture through high-resolution imagery and data fusion. Semantic segmentation techniques, leveraging deep learning, improve pixel-level classification despite challenges like class imbalance and object scale variation. Unsupervised domain adaptation addresses domain shifts, enhancing model generalization across diverse datasets. The survey highlights the significance of advanced methodologies, such as attention mechanisms and generative models, in refining segmentation accuracy and feature extraction. Applications in urban planning benefit from detailed land use mapping, while agriculture leverages multispectral data for precision farming. Environmental conservation is supported by robust monitoring strategies, and disaster management utilizes real-time data analysis for effective response. Challenges persist in data quality, computational complexity, and model efficiency, necessitating technological advancements and comprehensive datasets. Future research should focus on integrating multi-modal data and improving model adaptability through unsupervised learning. These developments underscore the transformative impact of remote sensing technologies on sustainable development and environmental stewardship, promising further enhancements in accuracy and applicability across various sectors.

1 Introduction

1.1 Interdisciplinary Nature of Remote Sensing

Remote sensing embodies a quintessential interdisciplinary field, merging environmental science, computer vision, and artificial intelligence (AI) to enhance applications such as land cover mapping and semantic segmentation of remote sensing images. The incorporation of AI extends beyond conventional deep learning to include explainable AI (XAI) techniques, which improve the interpretability and efficiency of remote sensing tasks [1].

Collaboration between remote sensing and computer vision communities is essential for addressing challenges in scene classification, as noted in recent studies [2]. This is exemplified by comprehensive frameworks that apply deep learning techniques to remote sensing imagery, effectively linking user-level tools with advanced analytical capabilities [3].

AI technologies significantly enhance object detection in optical remote sensing images, highlighting the necessity for interdisciplinary approaches [4]. Efficient deep learning methods have been developed to tackle real-time semantic segmentation challenges, which are critical for prompt and accurate image analysis [5].

The scarcity of high-quality labeled data poses substantial challenges for understanding remote sensing images, prompting the use of weakly supervised learning methods to bridge knowledge gaps




Figure 1: chapter structure

and facilitate effective training of deep learning models. Generative models are also employed to fuse multispectral image data, mitigating the need for extensive ground truth data and showcasing innovative methodologies within this interdisciplinary domain [6].

Moreover, the application of general-domain Vision-Language Models (VLMs) in remote sensing is complicated by high-resolution imagery and diverse scale changes, necessitating tailored solutions [7]. The effective training of VLMs is further challenged by the limited availability of large, paired datasets of remote sensing imagery and semantic-rich captions, underscoring the need for interdisciplinary collaboration to overcome these obstacles [8].

1.2 Significance in Earth Observation

Remote sensing is a vital technology in Earth Observation (EO), enabling comprehensive monitoring and management of Earth's resources and environments. Its importance is particularly pronounced in urban studies, where it aids in understanding urban areas and informing policies related to urbanization, thus addressing the complexities of urban growth [9]. In environmental monitoring, mapping land use and land cover changes (LUCC) is critical for assessing the impacts of large infrastructure projects, such as the Three Gorges Dam, on surrounding ecosystems [10].

The agricultural sector has experienced significant advancements through remote sensing, especially with the integration of imaging spectroscopy missions that enhance spectral fidelity and CubeSat constellations that improve spatial and temporal resolution [11]. These innovations are essential for precise agricultural monitoring and management, facilitating efficient crop mapping and production optimization.

Remote sensing also mitigates the limitations of traditional census-based methods for population distribution, such as poor temporal resolution and the Modifiable Areal Unit Problem (MAUP). By employing advanced remote sensing techniques and deep learning models, it provides more accurate and timely population distribution data [12].

Furthermore, remote sensing plays a critical role in environmental conservation, particularly in monitoring deforestation and degradation in tropical regions. Robust monitoring strategies are essential for preserving these vulnerable ecosystems, with domain adaptation techniques vital for

overcoming spectral shifts between training and testing datasets, ensuring accurate EO data analysis [13].

The diverse applications of remote sensing in EO underscore its crucial role in addressing global challenges, including urbanization, environmental risk management, and sustainable development. By enabling detailed characterization of urban areas, monitoring land cover changes, and analyzing extensive remote sensing data archives, these technologies support various initiatives vital for effective environmental stewardship and informed decision-making in scientific and policy contexts. Additionally, advancements in remote sensing methodologies, such as high-frequency temporal analysis and integration with emerging urban data, promise to enhance our understanding of complex urban dynamics and significantly contribute to achieving the United Nations Sustainable Development Goals (SDGs) [9, 14].

1.3 Structure of the Survey

This survey is meticulously structured to provide a comprehensive exploration of remote sensing, semantic segmentation, and unsupervised domain adaptation, emphasizing their interdisciplinary nature and significance in Earth observation. The introductory section establishes the foundational context, highlighting the integration of AI technologies and their transformative impact on remote sensing applications. Following this, the background and definitions section delves into core concepts, offering precise definitions and explanations of remote sensing, semantic segmentation, and unsupervised domain adaptation.

The subsequent section focuses on the intersection of remote sensing and semantic segmentation, examining the role of remote sensing in data acquisition for Earth observation and advancements in high-resolution segmentation. It also addresses challenges inherent in real-time semantic segmentation and proposes potential solutions. The survey then transitions to unsupervised domain adaptation and cross-domain learning, investigating adversarial and self-training approaches, exploring innovative methodologies, and discussing their applicability in real-world scenarios.

In the image analysis and geospatial data interpretation section, the survey analyzes advanced image segmentation techniques, feature extraction, and integration methods, as well as the utilization of multispectral and hyperspectral data. This is followed by a detailed examination of applications and case studies, showcasing the effectiveness of these technologies in urban planning, environmental monitoring, disaster response, and agriculture.

The penultimate section addresses challenges and future directions in the field, discussing data quality, computational complexity, model efficiency, and the need for technological advancements. The survey concludes by reflecting on the impact of these technologies, summarizing key points, and emphasizing the potential for future research and development in this dynamic and evolving domain. The following sections are organized as shown in Figure 1.

2 Background and Definitions

2.1 Remote Sensing and Earth Observation

Remote sensing, vital for Earth Observation (EO), involves acquiring and interpreting data about objects or phenomena without direct contact. It is crucial for geospatial data analysis and the training of Vision-Language Models (VLMs) [8]. The integration with deep learning has improved spatio-temporal feature extraction from complex datasets [15]. In agriculture, remote sensing facilitates crop classification, phenology prediction, and yield forecasting [16], playing a critical role in assessing natural disasters [12]. However, challenges like data heterogeneity and the need for multi-view integration persist [17].

In urban studies, remote sensing supports policy-making on urbanization and addresses urban growth challenges [9]. High-resolution imagery, such as that used in the Three Gorges Reservoir Area, enables precise land use and cover classification, addressing environmental and developmental issues [10]. In mineral exploration, combining remote sensing data with machine learning is crucial [18]. Detecting and classifying semantic changes in high-resolution or heterogeneous bi-temporal images remains complex [11]. Integrating geospatial data into PyTorch enhances model comparison and geospatial phenomenon analysis [7]. Current image retrieval methods are limited by unimodal queries,

necessitating advanced methodologies for improved data retrieval. As remote sensing evolves, it will increasingly support applications from environmental monitoring to urban planning.

2.2 Semantic Segmentation Techniques

Semantic segmentation classifies each pixel in remote sensing images into predefined categories, essential for detailed geospatial data analysis. Challenges include diverse orientations, scales, and spectral characteristics [19]. Advanced techniques leveraging deep learning have emerged to address these issues. Traditional methods like Fully Convolutional Networks (FCNs) struggle with long-range dependencies and information loss due to encoder-decoder architectures [20, 21]. Innovations such as Pyramid Pooling Mamba (PPMamba) combine CNNs with Mamba to capture local and global relationships [22].

Recent advancements focus on small object segmentation and class imbalance. General-purpose models like PerceiverIO are less effective, prompting the development of models addressing scale variation and class imbalance [23]. Generative adversarial networks (GANs) have been proposed for unsupervised multispectral image fusion, minimizing spectral and spatial distortions [6]. Integrating RGB and normalized digital surface model (nDSM) data improves segmentation accuracy by addressing geometric and spectral diversity [24]. Neural architecture search (NAS) optimizes architectures for remote sensing, enhancing segmentation performance [25]. Unsupervised models using snake models initialized with LiDAR points show high accuracy in building extraction [26].

The SCAttNet method exemplifies advancements by integrating lightweight spatial and channel attention modules for adaptive feature refinement, enhancing segmentation accuracy of high-resolution remote sensing images (HRRSIs) [27]. The IMAFD method classifies pixels into Land, Water, or Cloud for flood detection, illustrating practical applications [1]. Despite advancements, real-time semantic segmentation remains challenging, especially in achieving high-quality results with efficient deep learning methods [5]. Ongoing development is crucial for enhancing remote sensing image analysis, supporting applications from environmental monitoring to urban planning and disaster management.

2.3 Unsupervised Domain Adaptation

Unsupervised Domain Adaptation (UDA) is crucial in remote sensing for transferring knowledge from a labeled source domain to an unlabeled target domain, enhancing model generalization across domains with varying data distributions [28]. A primary challenge in semantic segmentation is pixel misclassification due to domain shifts and class confusion during model adaptation [28]. UDA is vital for applications like population distribution estimation, where traditional benchmarks overlook distribution heterogeneity and neighboring area influences [12]. In agriculture, UDA enables accurate satellite imagery-based cropping parameter prediction, critical given sensor data variability [16].

Existing FCN-based methods' limitations in capturing long-range dependencies in high-resolution remote sensing images highlight UDA's significance in overcoming coarse segmentation results [20]. By aligning feature distributions across domains, UDA enhances model generalization, enabling more accurate remote sensing data analysis. This adaptability is vital for applications like environmental monitoring, disaster management, and resource management, where managing geospatial data complexity and diversity without extensive labeled datasets is critical.

3 Remote Sensing and Semantic Segmentation

The integration of remote sensing and semantic segmentation is pivotal in enhancing geospatial data analysis, facilitating applications in environmental monitoring, urban planning, and disaster response. As illustrated in Figure 2, this figure highlights the role of remote sensing in Earth observation, showcasing advancements in high-resolution segmentation alongside the challenges associated with real-time semantic segmentation. This visual representation encapsulates the applications, challenges, and innovative methodologies that enhance geospatial data analysis and image segmentation accuracy, thereby underscoring the significance of this synergy in advancing segmentation methodologies crucial for Earth Observation (EO).




Figure 2: This figure illustrates the integration of remote sensing and semantic segmentation, highlighting the role of remote sensing in Earth observation, advancements in high-resolution segmentation, and challenges in real-time semantic segmentation. It encapsulates the applications, challenges, and innovative methodologies that enhance geospatial data analysis and image segmentation accuracy.

3.1 Role of Remote Sensing in Earth Observation

Remote sensing is fundamental in EO, enabling comprehensive geospatial data acquisition essential for monitoring Earth’s resources. Satellite missions, such as Sentinel-2, are integral for population estimation and environmental monitoring [12]. The SICKLE dataset exemplifies the capacity of multisensor satellite data to support agricultural monitoring [16]. High-quality hyperspectral data, like the AVIRIS-ng dataset, enhances vegetation analysis, improving crop classification precision [11]. Advanced frameworks such as IMAFD utilize multispectral time series for flood detection, underscoring remote sensing’s role in acquiring critical EO data [1].

Despite the potential of remote sensing foundation models, challenges in learning high-level semantic features persist, necessitating methodological innovations to enhance their EO applicability [18]. Addressing these challenges through automated methods and efficient architectures is crucial for advancing remote sensing capabilities, supporting sustainable development and environmental stewardship.

3.2 Advancements in High-Resolution Segmentation

Recent advancements in high-resolution segmentation have significantly enhanced remote sensing image analysis, addressing challenges related to scale, shape variations, and multispectral data integration. Scalable approaches like Pyramid Pooling Mamba (PPMamba) improve segmentation accuracy using a UNet-like framework with PP-SSM blocks for multi-scale feature extraction [22]. Advanced attention mechanisms, such as those in the bi-temporal Gaussian distribution feature-dependent network (BGFD) and SCAttNet, refine segmentation accuracy through feature characterization and adaptive refinement [29, 27].

Innovative methods, including SSLKD, enhance lightweight models in road segmentation tasks by combining semi-supervised learning with knowledge distillation [30]. Residual encoder-decoder architectures and Swin Transformers with DCFAM advance feature representation and accuracy in

fine-resolution images [31, 20]. Keypoint-based Instance Segmentation Methods (KISM) and 3D convolutional learning further improve segmentation by preserving geometric details and facilitating cross-modal feature learning [21, 23].

These advancements highlight the importance of innovative methodologies in enhancing the accuracy of remote sensing image analysis. Robust object extraction frameworks and Hi-ResNet architecture contribute to improved edge detail and handling of variations in object scale and shape, optimizing performance in segmentation and retrieval tasks across diverse applications [32, 33, 34].

3.3 Challenges in Real-Time Semantic Segmentation

Real-time semantic segmentation in remote sensing is challenged by the high resolution and complexity of geospatial data. Accurate segmentation of high-resolution images is complicated by variations in object scale and shape, alongside complex background environments [12]. Limitations in CNNs' receptive fields and ViTs' computational demands hinder processing capabilities, leading to potential information loss and misinterpretation in complex urban landscapes [12].

Existing benchmarks for interactive segmentation often fail to comprehensively evaluate performance due to the high dimensionality and spectral complexity of the data. Limitations in generating semantically consistent synthetic images affect model performance, necessitating domain adaptation strategies to bridge gaps between diverse datasets. Recent advancements, such as the SemI2I model, improve semantic consistency and per-pixel quality during image style transfer, enhancing model generalization [35]. Human annotator performance studies reveal complexities in segmentation tasks, complicating robust training data creation [36].

Innovative approaches like LOGCAN++ and spatio-spectral morphological segmentation techniques address these challenges by reducing background noise and enhancing segmentation precision through advanced methodologies [36, 37, 38, 39]. These innovations are crucial for improving segmentation accuracy in multi-spectral images, addressing the increasing complexity of remote sensing data.

Ongoing innovation in real-time semantic segmentation is essential for enhancing accuracy and efficiency in remote sensing image analysis, supporting applications from environmental monitoring to disaster management. Despite the traction of efficient deep neural networks, challenges related to inference speed persist, hindering real-time deployment. On-orbit segmentation models and active learning techniques optimize limited labeled data use, significantly improving model performance with minimal training samples. These advancements underscore the necessity for continuous research and refinement to fully leverage remote sensing data potential [40, 41, 5].

4 Unsupervised Domain Adaptation and Cross-Domain Learning

Category	Feature	Method
Adversarial and Self-Training Approaches	Anomaly and Adaptation Methods	IMAFD[1]
	Feature Enhancement Strategies	SCAttNet[27], DC-Swin[20]
	Generative and Adversarial Models	GMU-MIF[6]
Innovative Methodologies for Domain Adaptation	Generative Techniques	SemI2I[42], HDA-CycleGAN[43]
	Cross-Domain Fusion	XM[44]
	Hierarchical Alignment	ISIA[28]
Domain Adaptation in Real-World Applications	Class Imbalance Solutions	GeoMTNet[45]
	Generative Techniques	UniDA[46], DAGAN[47]
	Robustness and Generalization	TSPNL[48], DANN[49]

Table 1: This table provides a comprehensive overview of various methodologies employed in unsupervised domain adaptation and cross-domain learning, emphasizing adversarial and self-training approaches, innovative methodologies for domain adaptation, and real-world applications. It categorizes the methods into distinct features and highlights the specific techniques used, along with references to the original works that introduced these methods.

Unsupervised domain adaptation (UDA) addresses the challenges of domain shifts in remote sensing by enhancing model adaptability across different domains. Table 3 provides a detailed classification of the methods utilized in unsupervised domain adaptation and cross-domain learning, underscoring their significance in addressing domain shifts in remote sensing applications. This section highlights adversarial and self-training approaches that improve feature representation and classification accuracy, detailed further in the subsection "Adversarial and Self-Training Approaches."

4.1 Adversarial and Self-Training Approaches

Adversarial and self-training methods are pivotal in advancing UDA for remote sensing, particularly in mitigating domain shifts due to sensor variations, geography, and temporal changes. Adversarial methods inspired by Generative Adversarial Networks (GANs) generate synthetic images that mimic target domain characteristics, facilitating domain transitions [6]. By combining domain-adversarial neural networks (DANN) with self-attention models, feature distributions are aligned across domains, enhancing land cover classification [9].

The Inter-class Separation and Intra-class Aggregation (ISIA) mechanism refines adversarial techniques by ensuring consistent representations for identical categories while distinguishing different ones [28]. This multi-level alignment—spanning image, feature, category, and instance levels—is crucial for effective domain adaptation [28]. Additionally, the DC-Swin method excels in capturing long-range dependencies and integrating multi-scale features, surpassing ResNet-based methods in segmentation tasks [20].

Self-training approaches leverage both labeled and unlabeled data to enhance feature representation and classification accuracy. The IMAFD method exemplifies domain adaptation for rare events by integrating anomaly detection into flood detection workflows [1]. Similarly, the SCAttNet model enhances feature representation through spatial and channel attention, improving segmentation, especially for small objects [27].

Models such as VGG, ResNet, Xception, and DenseNet demonstrate the efficacy of adversarial and self-training approaches in population estimation benchmarks, showcasing their applicability across various remote sensing tasks [12]. These methodologies are essential for enhancing model adaptability and performance, supporting applications in environmental monitoring, urban planning, and disaster management.

4.2 Innovative Methodologies for Domain Adaptation

Innovative methodologies have significantly enhanced the generalization capabilities of remote sensing models, addressing domain shifts effectively and improving data processing efficiency. The integration of classification and metric alignment losses into the CycleGAN framework, as proposed by Voreiter et al., marks a significant advancement in domain adaptation by addressing label preservation and data alignment issues during generation [43].

The DANN approach, through adversarial training, enhances classifier generalization across domains by aligning feature distributions between source and target domains [49]. The X-ModalNet framework exemplifies this by integrating self-adversarial, interactive learning, and label propagation modules, highlighting the potential of cross-modal approaches in domain adaptation [44].

The ISIA method has set new standards in cross-domain segmentation tasks, emphasizing the importance of multi-level alignment strategies [28]. The SemI2I framework generates semantically consistent training images using adaptive instance normalization and adversarial losses, overcoming limitations of previous methods like ColorMapGAN and enhancing domain adaptation robustness [42].

Future research should focus on developing techniques that improve model performance across diverse data sources and enhance domain generalization capabilities to tackle challenges posed by different sensor types and conditions. Ongoing innovations in remote sensing, particularly in feature extraction, domain adaptation, and classification methods, are crucial for improving the reliability and accuracy of image retrieval and analysis. By leveraging deep learning and domain adaptation strategies, researchers are creating robust systems capable of addressing the complexities of high-resolution remote sensing data, broadening the applicability of these technologies in geological information mining and environmental monitoring [13, 34].

4.3 Domain Adaptation in Real-World Applications

Domain adaptation techniques have proven effective in enhancing the applicability of remote sensing models across diverse real-world scenarios, especially in environments with limited labeled data and varying geographical conditions. Integrating domain adaptation methods into aerial image analysis has significantly improved segmentation accuracy on target datasets, addressing domain

Method Name	Methodological Approaches	Application Scenarios	Data Challenges
DAGAN[47]	Unpaired Image Translation	Aerial Image Analysis	Domain Shift
TSPNL[48]	Task-specific Pretraining	Remote Sensing	Limited Labeled Data
DANN[49]	Adversarial Training Techniques	Land Cover Classification	Domain Gap
UniDA[46]	Synthetic Source Data	Remote Sensing	Limited Labeled Data
GeoMTNet[45]	Domain-adversarial Training	Remote Sensing	Domain Shifts

Table 2: Summary of various domain adaptation methods, their methodological approaches, application scenarios, and data challenges in the context of remote sensing. This table highlights the diversity of techniques employed to address domain shifts and limited labeled data, showcasing their applicability in real-world situations.

shift challenges [47]. This improvement underscores the critical role of domain adaptation in refining model performance and expanding the utility of remote sensing technologies in practical applications.

Task-specific pretraining with noisy labels has further advanced real-world segmentation tasks, enhancing encoder networks' performance across various segmentation tasks, particularly where high-quality labeled data is scarce [48]. Such techniques are invaluable for developing robust models that generalize across diverse datasets.

Moreover, domain-adversarial training with self-attention mechanisms has enhanced model generalization across geographical regions, crucial in situations with limited labeled data, allowing models to maintain performance despite data distribution variations [49]. The ability to adapt to new environments while maintaining accuracy is vital for deploying remote sensing models in real-world applications.

The SICKLE dataset demonstrates the application of domain adaptation techniques by integrating multi-sensor data, supporting model training without labeled data in new domains [16]. This dataset enables models to adapt effectively to novel environments, showcasing domain adaptation's potential across applications like environmental monitoring, urban planning, and agricultural management.

Recent advancements in domain adaptation are crucial for addressing challenges posed by domain shifts in remote sensing applications. These techniques enhance classification algorithms' robustness by mitigating spectral discrepancies from variations in acquisition conditions or object characteristics. Strategies such as invariant feature selection, representation matching, and classifier adaptation have led to successful classification of remotely sensed images across diverse scenarios. Innovative approaches combining knowledge transfer and domain refinement have shown significant improvements in fine-grained segmentation tasks, while universal domain adaptation methods enable effective scene classification without source data. Collectively, these advancements broaden the applicability of remote sensing technologies in real-world contexts, ensuring accurate and reliable data interpretation [46, 13, 50]. By improving model generalization and adaptability, these techniques support the development of robust models capable of tackling complex challenges in diverse environments.

As shown in ??, three illustrative examples provide an overview of methodologies in unsupervised domain adaptation and cross-domain learning within real-world applications. The first example visualizes "Domain and Category Clustering in a Multidimensional Space," highlighting data variability management across domains through distinct color-coded data points in a two-dimensional scatter plot. The second example explores the workings of a Generative Adversarial Network (GAN), illustrating the dynamic interplay between generator and discriminator networks, essential for generating realistic data representations vital for effective domain adaptation. Lastly, the third example presents a detailed diagram of a machine learning model, emphasizing the roles of encoder and decoder in transforming and reconstructing data across domains. Collectively, these examples underscore the complexity and innovation involved in adapting machine learning models to function effectively across diverse and unlabelled domains [46, 47, 45]. Additionally, Table 2 provides a comprehensive overview of domain adaptation methods, illustrating their methodological approaches, application scenarios, and the data challenges they address in remote sensing applications.

Feature	Adversarial and Self-Training Approaches	Innovative Methodologies for Domain Adaptation	Domain Adaptation in Real-World Applications
Approach Type	Adversarial Training	Cyclegan Integration	Task-specific Pretraining
Key Technique	Gans, Dann	Classification, Metric Alignment	Self-attention Mechanisms
Primary Benefit	Feature Alignment	Data Alignment	Segmentation Accuracy

Table 3: This table provides a comparative analysis of various methodologies employed in unsupervised domain adaptation and cross-domain learning. It highlights key features such as approach type, key techniques, and primary benefits, focusing on adversarial and self-training approaches, innovative methodologies for domain adaptation, and their application in real-world scenarios. The table underscores the importance of these methods in addressing domain shifts, particularly in remote sensing applications.

5 Image Analysis and Geospatial Data Interpretation

5.1 Advanced Image Segmentation Techniques

Advanced image segmentation techniques are pivotal for accurate geospatial data analysis in remote sensing, addressing challenges like diverse spectral characteristics and high-resolution data. The IMAFD framework exemplifies improved flood detection through systematic image classification [1]. The SICKLE dataset benchmarks advanced segmentation models such as U-Net 3D, ConvLSTM, and U-TAE, demonstrating the effectiveness of state-of-the-art models in crop segmentation and geospatial analysis [16]. These models harness deep learning to navigate the complexities of high-resolution, multi-spectral data, enhancing segmentation outcomes.

Recent advancements treat segmentation as a regression problem, utilizing 3D convolutions for spectral channel fusion and dense blocks for spatial and spectral processing, significantly improving semantic segmentation accuracy [51, 38, 52, 36, 53]. This approach captures intricate details in multi-spectral data, enhancing segmentation precision. Metrics for multispectral vegetation analysis, as outlined by Sousa et al., highlight the importance of accurate feature extraction in segmentation [11]. Population estimation frameworks further refine segmentation techniques, contributing to model evaluation [12].

Ongoing advancements in segmentation methodologies address the complexities of high-resolution and multi-spectral remote sensing data, improving object outline extraction and image retrieval through enhanced deep feature utilization. These developments support applications such as environmental monitoring, urban planning, and disaster management, meeting critical data needs in rapidly urbanizing regions. By integrating innovative data fusion techniques, multisource spectral data compatibility is enhanced, improving machine learning model performance across various fields [54, 33, 9, 34].

5.2 Feature Extraction and Integration Methods

Feature extraction and integration are crucial in geospatial data analysis, especially in remote sensing, where data complexity and volume present significant challenges. Advanced techniques like deep feature extraction and explainable AI identify and extract significant patterns from raw data, integrating them into robust models that enhance data interpretation and support informed decision-making in geological information mining and precision agriculture [33, 55, 34, 56].

The RSTeller dataset, with approximately 1.2 million remote sensing image patches and multiple captions, exemplifies the importance of semantic richness and contextual accuracy in feature extraction [8]. This dataset aids in developing models that effectively capture geospatial data nuances, improving feature extraction accuracy and relevance. Convolutional neural networks (CNNs) and deep learning frameworks have significantly enhanced feature extraction capabilities in remote sensing image retrieval and scene classification, utilizing deep representations to address high-resolution image complexities and improve performance over traditional methods [51, 2, 57, 34]. The integration of multi-modal data, including multispectral and hyperspectral imagery, enriches the feature extraction process, enhancing model performance.

Vision-Language Models (VLMs) in remote sensing highlight the importance of integrating semantic-rich features into analysis processes. High-resolution imagery and diverse scale changes necessitate tailored solutions for managing geospatial data complexity [8]. By incorporating semantic and contextual information into feature extraction methodologies, these models enhance the interpretability and

utility of geospatial data, supporting applications from environmental monitoring to urban planning and disaster management.

Continuous advancements in feature extraction and integration methods enhance remote sensing technology capabilities, addressing complexities in object delineation, improving retrieval accuracy through deep feature representations, and optimizing model efficiency via techniques like knowledge distillation. These developments lead to more robust applications in various remote sensing tasks [58, 59, 33, 60, 34].

5.3 Utilization of Multispectral and Hyperspectral Data

The utilization of multispectral and hyperspectral data enhances remote sensing image analysis by providing a comprehensive spectrum of information beyond traditional RGB imagery. These data types capture a broad range of wavelengths, enabling detailed characterization of geological and environmental features, essential for applications such as environmental monitoring, precision agriculture, and urban planning [61, 11, 9, 33, 34].

Multispectral data, capturing information across a limited number of spectral bands, is crucial for vegetation analysis, allowing assessments of plant health and biomass through indices like NDVI [11]. Integrating multispectral data with advanced image processing techniques facilitates the extraction of detailed spatial and temporal patterns, crucial for precise agricultural monitoring and management [16].

Hyperspectral data offers high spectral resolution by capturing information across hundreds of narrow bands, vital for distinguishing materials with similar spectral characteristics and enhancing classification accuracy in remote sensing tasks [6]. This capability is invaluable for applications such as mineral exploration and environmental monitoring, where precise material identification is critical [18].

The integration of multispectral and hyperspectral data into remote sensing workflows is facilitated by advanced computational techniques, including deep learning and machine learning models, which effectively process the large volumes of data generated by these sensors. Convolutional neural networks (CNNs) and other deep learning architectures have proven effective in extracting meaningful features from multispectral and hyperspectral data, enhancing the interpretability and utility of the captured information [8].

6 Applications and Case Studies

6.1 Urban Planning and Infrastructure Development

Remote sensing technologies have revolutionized urban planning and infrastructure development by providing essential geospatial data that enhances decision-making processes. High-resolution satellite imagery and advanced analytical techniques facilitate detailed urban mapping, enabling planners to assess land use, monitor urban expansion, and evaluate infrastructure needs, particularly in rapidly growing regions where traditional data collection is inadequate [9]. These technologies support smart city initiatives by delivering timely insights into urban sprawl, traffic patterns, and environmental conditions, while multispectral and hyperspectral imagery allows precise land use classification and zoning, optimizing transportation networks and fostering sustainable urban development [11].

In infrastructure development, remote sensing provides critical data for planning and maintaining roads, bridges, and utilities. High-resolution images enable detailed assessments of existing infrastructure, identifying areas needing repair and monitoring construction progress to ensure regulatory compliance, thus minimizing project delays and cost overruns [10]. The integration of remote sensing with geographic information systems (GIS) enhances urban planning by enabling comprehensive visualization and spatial data analysis. This synergy, coupled with artificial intelligence, allows planners to simulate development scenarios, assess environmental and social impacts, and leverage data-driven insights to promote sustainable urban growth and resilience against climate change [9, 62, 63, 64]. The role of remote sensing in urban planning is poised to expand, driven by advancements in high-frequency temporal analysis and integration with emerging urban datasets, offering deeper insights into urban dynamics and aiding informed decision-making amid rapid urbanization and environmental challenges [65, 9, 33, 66, 34].

6.2 Environmental Monitoring and Conservation

Remote sensing is crucial for environmental monitoring and conservation, providing essential data for natural resource management. The integration of multispectral and hyperspectral data enhances monitoring capabilities, offering insights into land cover dynamics and ecosystem health [67]. This is vital for detecting changes in vegetation cover, water bodies, and urban expansion, which are critical for conservation efforts. The WiCoNet model exemplifies the potential of wide-context networks in environmental assessment, improving segmentation of complex land-cover classes using datasets like the Beijing Land-Use dataset [68]. Additionally, unsupervised multimodal change detection approaches, such as those by Chen et al., demonstrate superior performance in detecting land-cover changes using OpenStreetMap (OSM) data and optical imagery, underscoring the importance of innovative methodologies in enhancing detection capabilities [69].

Advanced content-based image retrieval systems, such as DSS, enhance environmental monitoring by improving classification accuracy and reducing computational demands for processing large satellite images [70]. These systems facilitate efficient analysis of remote sensing data, supporting timely conservation decision-making. Furthermore, comprehensive benchmarks like GeoChat highlight the significance of domain-specific models in achieving robust performance across remote sensing tasks, driving advancements in environmental monitoring and conservation applications [7].

6.3 Disaster Response and Management

Remote sensing technologies play a critical role in disaster response and management, providing essential data that enhances situational awareness and supports timely decision-making during emergencies. Rapid acquisition and analysis of geospatial data are crucial for assessing damage, identifying affected areas, and coordinating relief efforts. Methodologies such as DirectSAM-RS have demonstrated state-of-the-art performance in semantic contour extraction, significantly improving damage assessment accuracy in both zero-shot and fine-tuning scenarios [53]. The integration of automated labeling systems like AutoGeoLabel streamlines data analysis by reducing reliance on manual annotation, enabling real-time applications in disaster response and facilitating rapid generation of necessary geospatial data [71]. This automation enhances data processing efficiency, allowing for quicker resource deployment and informed decision-making during disaster events.

Cross-modal retrieval tasks, exemplified by SSJDN, validate the utility of remote sensing data analysis in disaster response, demonstrating its effectiveness in real-world applications [72]. The ability to retrieve and analyze relevant data from multiple sources is essential for comprehensive insights into disaster impacts, aiding the development of targeted response strategies. Remote sensing enhances the resilience and effectiveness of emergency operations by enabling swift evaluations of disaster impacts through detailed object outline extraction from high-resolution imagery. This capability supports timely and coordinated responses to both natural and man-made disasters, aiding decision-makers in implementing effective mitigation strategies. Furthermore, advancements in machine learning and artificial intelligence facilitate automatic annotation of remote sensing data, providing valuable insights for disaster management and climate adaptation efforts. These innovations improve impact assessment accuracy and support predictive modeling for resource allocation and response planning [33, 73, 34, 64]. As technology advances, the role of remote sensing in disaster management is expected to expand, offering greater capabilities for safeguarding communities and infrastructure.

6.4 Agriculture and Precision Farming

Remote sensing technologies are integral to advancing agriculture and precision farming by providing comprehensive data that enhances crop management and productivity. The integration of high-resolution satellite imagery and UAV (Unmanned Aerial Vehicle) data enables precise monitoring of agricultural fields, facilitating assessments of crop health, soil conditions, and irrigation needs, which are critical for optimizing resource use and improving yield outcomes [74]. Advanced models leveraging multispectral and hyperspectral data monitor key vegetation indices, such as the Normalized Difference Vegetation Index (NDVI), vital for evaluating plant health and biomass. Studies have shown strong correlations between multispectral vegetation indices and hyperspectral endmember fractions, indicating indices like NIRv, DVI, EVI, and EVI2 enhance agronomic assessments and agricultural landscape management [54, 11].

Remote sensing data also supports site-specific management practices in precision farming by identifying spatial variability within fields, facilitating targeted application of inputs such as water, fertilizers, and pesticides, thereby reducing waste and minimizing environmental impacts. The integration of remote sensing with complementary technologies like GIS and the Internet of Things (IoT) enhances agricultural operations' precision and efficiency through accurate data collection and analysis. This synergy allows for effective detection of agricultural patterns via high-resolution imagery and advanced machine learning techniques, providing timely alerts for farmers regarding problematic areas in their fields. Furthermore, robust evaluation frameworks and publicly available datasets support ongoing research and innovation in computer vision applications within agriculture, leading to improved management decisions and outcomes [33, 55].

Future research could focus on enhancing degradation methods to incorporate additional imaging factors, improving the accuracy and applicability of remote sensing data in diverse agricultural settings [74]. Expanding datasets to encompass a broader range of crops and environmental conditions will also contribute to the development of more robust models, supporting the global advancement of precision farming technologies. Remote sensing plays a crucial role in transforming agricultural practices by providing data-driven insights necessary for optimizing productivity and sustainability. The continued integration of remote sensing into agriculture and precision farming is expected to grow significantly, particularly through enhanced techniques and machine learning methods. These innovations are anticipated to improve crop mapping accuracy, facilitate timely identification of agricultural patterns, and enable more effective management decisions, thereby bolstering food security and promoting environmental sustainability. For instance, the development of comprehensive datasets and advanced classifiers has shown potential for high accuracy in crop recognition, while hyperspectral imaging refines monitoring of crop health and biomass. Collectively, these advancements empower farmers with greater insights and tools to optimize practices in an increasingly urbanized and resource-constrained world [9, 75, 55, 11].

7 Challenges and Future Directions

The evolving landscape of remote sensing is fraught with challenges that hinder the advancement of methodologies in this domain. Data quality and annotation complexities, computational demands, and model generalization issues are critical concerns impacting machine learning model reliability and application diversity. Addressing these challenges is imperative for progressing remote sensing technologies. The following subsections delve into these challenges and explore future research directions.

7.1 Data Quality and Annotation Challenges

Data quality and annotation present significant hurdles in remote sensing, affecting model reliability and generalization. The scarcity of high-quality labeled datasets, due to the laborious and costly manual annotation process, is particularly problematic in diverse land cover scenarios where models struggle to learn robust representations [9, 10]. Reliance on small, low-diversity datasets often leads to overfitting, limiting model generalizability across tasks [18]. Class imbalance and variations in object appearance due to viewpoint changes, occlusion, and background clutter further complicate annotation [6, 26].

The complexity of remote sensing images demands expertise in programming and deep learning, limiting accessibility and effective data annotation [1]. While self-supervised learning methods like Cross-Scale MAE reduce the need for labeled data, they may falter in complex scenarios with ambiguous semantic relationships [11]. Dependence on metadata quality can affect performance, as spatiotemporal context may not always be useful [12]. Domain adversarial training's reliance on samples from both source and target domains complicates robust model development [8]. Datasets like SICKLE, using farmer-recalled data for annotations, introduce challenges in data quality and prediction accuracy [16].

Addressing these challenges requires developing comprehensive, diverse datasets, improving annotation practices, and creating models that generalize robustly across conditions. Balanced datasets, effective annotation strategies, and standardized evaluation frameworks are crucial for enhancing object extraction and representation learning [76, 36, 33].

7.2 Computational Complexity and Model Efficiency

Computational complexity and model efficiency significantly influence the deployment and performance of remote sensing methodologies. High-resolution processing demands increase computational load, affecting inference speed and memory usage, posing challenges for real-time applications. The Samba model exemplifies reduced computational complexity while efficiently capturing global semantic information [77]. However, transformer architectures often introduce complexities limiting real-time applicability [20].

The HSiMamba model demonstrates advancements in efficiency, offering enhanced classification accuracy, reduced memory usage, and faster inference times, suitable for real-time applications [78]. Conversely, models like SRC-Net face computational overheads hindering deployment on edge devices [79]. The PPMamba model's multi-branch architecture highlights the trade-off between complexity and resource requirements [22]. Performance issues with augmented training datasets in the MiM model further illustrate computational challenges [80].

Developing efficient computational methods and architectures that deliver high-performance results while minimizing resource consumption is essential for applying remote sensing technologies in resource-limited settings. Continued innovation is crucial for enhancing performance in real-time and resource-constrained environments, particularly in high-resolution remote sensing images where advancements in feature extraction and deep learning techniques can significantly improve object retrieval and extraction [66, 33, 34].

7.3 Model Generalization and Domain Adaptation

Model generalization and domain adaptation in remote sensing are challenged by geospatial data variability across domains. Overfitting to specific datasets limits generalizability, complicating knowledge transfer due to data characteristic variations [81]. Large domain shifts between training and test data further impede maintaining model performance across scenarios [42].

Model robustness across varying conditions and sensor types remains a critical issue, necessitating models that adapt to dynamic and heterogeneous data sources [5]. Distinguishing genuine from pseudo changes in remote sensing images complicates generalization, as existing methods struggle to differentiate these variations [29]. Dependency on semantic segmentation model quality limits effective instance extraction and alignment, impacting domain adaptation success [28]. The reliance on limited attention modules restricts feature discrimination, limiting adaptability across domains [27].

Despite advancements, models like GeoChat face challenges handling complex queries or diverse object types, indicating a need for further refinement [7]. Developing robust and flexible models that generalize across diverse datasets and adapt to varying conditions is essential for applications from environmental monitoring to urban planning and disaster management.

7.4 Technological Advancements and Future Research Directions

Remote sensing is poised for significant advancement, driven by technological innovations and emerging research opportunities. Integrating deep learning with multi-modal data fusion, enhancing image fusion capabilities through foundational models, is expected to improve accuracy and efficiency by leveraging methodologies like deep feature extraction, multimodal image retrieval, and spectral data fusion [58, 54, 65, 33, 34].

Future research will explore robust architectures for transfer learning and unsupervised learning techniques to improve model adaptability and performance across diverse datasets [81]. Advancements in Generative Adversarial Networks for high-dimensional and multi-sensor applications are anticipated to open new avenues [81]. Exploring additional deep learning architectures and spatial resolutions will be crucial for enhancing population estimation accuracy [12].

Embedding the Inter-class Separation and Intra-class Aggregation method into semantic segmentation models and extending Unsupervised Domain Adaptation applications to complex tasks represent promising research directions [28]. Developing hybrid models combining weakly supervised learning paradigms with self-supervised learning will enhance image understanding.

Optimizing archetypal analysis processes and exploring their applicability across remote sensing data types, like hyperspectral imaging for land cover fraction estimation, is crucial. Promising results in urban environments like Berlin suggest high-resolution image retrieval can significantly improve performance through deep feature extraction methods. Developing robust object extraction techniques, supported by comprehensive evaluation frameworks, will advance methodologies in addressing data complexities [33, 82, 34]. Refining filtering mechanisms and enhancing generative models are expected to improve image quality and diversity, presenting new opportunities for applications.

Incorporating spectral imaging’s physical mechanisms into the learning process will enhance model applicability in earth observation tasks, supporting more accurate data analysis. Expanding the search space for encoder architectures and integrating advanced explainability techniques will improve model interpretability, providing valuable insights into their contributions and addressing gaps in understanding model behavior [66, 76, 34, 56].

8 Conclusion

The integration of remote sensing, semantic segmentation, and unsupervised domain adaptation has profoundly advanced Earth observation, enhancing geospatial data analysis and interpretation. The SICKLE dataset illustrates the role of remote sensing and semantic segmentation in agriculture, facilitating significant advancements in agricultural research and the application of machine learning [16]. This underscores how remote sensing technologies optimize agricultural practices and improve crop management.

The RSTeller dataset emphasizes the necessity of large, semantically rich datasets for training and evaluation, which substantially boosts the performance of Vision-Language Models (VLMs) in remote sensing tasks [8]. This highlights the critical contribution of comprehensive datasets in enhancing remote sensing models’ capabilities and their applicability across diverse domains.

Advanced methodologies, including the Swin Transformer and DCFAM, have significantly improved segmentation accuracy for fine-resolution remote sensing images, while SCAttNet has enhanced semantic segmentation through integrated attention mechanisms. These innovations demonstrate the transformative impact of sophisticated segmentation techniques on remote sensing applications, supporting various initiatives from environmental monitoring to urban planning and disaster management.

In change detection, innovative approaches have minimized pseudo changes and improved detail detection, achieving state-of-the-art results across multiple datasets. This reflects the importance of ongoing innovation in remote sensing methodologies to tackle the challenges posed by dynamic and heterogeneous data sources.

These advancements illustrate the transformative effects of remote sensing, semantic segmentation, and domain adaptation on sustainable development and environmental stewardship. The continuous evolution of these methodologies promises further improvements in accuracy, efficiency, and applicability, benefiting a wide array of applications from environmental monitoring to urban planning and disaster management.

References

- [1] Ziyang Zhang, Plamen Angelov, Dmitry Kangin, and Nicolas Longép . Imafd: An interpretable multi-stage approach to flood detection from time series multispectral data, 2024.
- [2] Fan Hu, Gui-Song Xia, Wen Yang, and Liangpei Zhang. Recent advances and opportunities in scene classification of aerial images with deep models, 2018.
- [3] R mi Cresson. A framework for remote sensing images processing using deep learning technique, 2018.
- [4] Gong Cheng and Junwei Han. A survey on object detection in optical remote sensing images, 2016.
- [5] Clifford Broni-Bediako, Junshi Xia, and Naoto Yokoya. Real-time semantic segmentation: A brief survey comparative study in remote sensing, 2023.
- [6] Arian Azarang and Nasser Kehtarnavaz. A generative model method for unsupervised multi-spectral image fusion in remote sensing, 2021.
- [7] Kartik Kuckreja, Muhammad Sohail Danish, Muzammal Naseer, Abhijit Das, Salman Khan, and Fahad Shahbaz Khan. Geochat: Grounded large vision-language model for remote sensing, 2023.
- [8] Junyao Ge, Xu Zhang, Yang Zheng, Kaitai Guo, and Jimin Liang. Rsteller: Scaling up visual language modeling in remote sensing with rich linguistic semantics from openly available data and large language models, 2025.
- [9] Zhe Zhu, Yuyu Zhou, Karen C Seto, Eleanor C Stokes, Chengbin Deng, Steward TA Pickett, and Hannes Taubenb ck. Understanding an urbanizing planet: Strategic directions for remote sensing. *Remote Sensing of Environment*, 228:164–182, 2019.
- [10] Xin Zhang, Bingfang Wu, Liang Zhu, Fuyou Tian, Miao Zhang, and Yuanzeng. Land use mapping in the three gorges reservoir area based on semantic segmentation deep learning method, 2018.
- [11] Daniel Sousa and Christopher Small. Linking common multispectral vegetation indices to hyperspectral mixture models: Results from 5 nm, 3 m airborne imaging spectroscopy in a diverse agricultural landscape, 2022.
- [12] Xiao Huang, Di Zhu, Fan Zhang, Tao Liu, Xiao Li, and Lei Zou. Sensing population distribution from satellite imagery via deep learning: model selection, neighboring effect, and systematic biases, 2021.
- [13] Devis Tuia, Claudio Persello, and Lorenzo Bruzzone. Recent advances in domain adaptation for the classification of remote sensing data, 2021.
- [14] Luigi Mascolo, Marco Quartulli, Pietro Guccione, Giovanni Nico, and Igor G. Olaizola. Distributed mining of large scale remote sensing image archives on public computing infrastructures, 2015.
- [15] Jun Yue, Leyuan Fang, Pedram Ghamisi, Weiying Xie, Jun Li, Jocelyn Chanussot, and Antonio J Plaza. Optical remote sensing image understanding with weak supervision: Concepts, methods, and perspectives, 2022.
- [16] Depanshu Sani, Sandeep Mahato, Sourabh Saini, Harsh Kumar Agarwal, Charu Chandra Devshali, Saket Anand, Gaurav Arora, and Thiagarajan Jayaraman. Sickie: A multi-sensor satellite imagery dataset annotated with multiple key cropping parameters, 2023.
- [17] Francisco Mena, Diego Arenas, and Andreas Dengel. In the search for optimal multi-view learning models for crop classification with global remote sensing data, 2024.
- [18] Fan Liu, Delong Chen, Zhangqingyun Guan, Xiacong Zhou, Jiale Zhu, Qiaolin Ye, Liyong Fu, and Jun Zhou. Remotecclip: A vision language foundation model for remote sensing, 2024.

-
- [19] Qinglong Cao, Yuntian Chen, Chao Ma, and Xiaokang Yang. Open-vocabulary remote sensing image semantic segmentation, 2024.
- [20] Libo Wang, Rui Li, Chenxi Duan, Ce Zhang, Xiaoliang Meng, and Shenghui Fang. A novel transformer based semantic segmentation scheme for fine-resolution remote sensing images, 2022.
- [21] Qingyu Li, Lichao Mou, Yuansheng Hua, Yao Sun, Pu Jin, Yilei Shi, and Xiao Xiang Zhu. Instance segmentation of buildings using keypoints, 2020.
- [22] Yin Hu, Xianping Ma, Jialu Sui, and Man-On Pun. Ppmamba: A pyramid pooling local auxiliary ssm-based model for remote sensing image semantic segmentation, 2024.
- [23] Nhi Kieu, Kien Nguyen, Sridha Sridharan, and Clinton Fookes. General-purpose multimodal transformer meets remote sensing semantic segmentation, 2023.
- [24] Zhitong Xiong, Sining Chen, Yi Wang, Lichao Mou, and Xiao Xiang Zhu. Gamus: A geometry-aware multi-modal semantic segmentation benchmark for remote sensing data, 2023.
- [25] Anthony Cazasnoves, Pierre-Antoine Ganaye, Kévin Sanchis, and Tugdual Ceillier. Neural architecture search in operational context: a remote sensing case-study, 2021.
- [26] Thanh Huy Nguyen, Sylvie Daniel, Didier Gueriot, Christophe Sintès, and Jean-Marc Le Caillec. Unsupervised automatic building extraction using active contour model on unregistered optical imagery and airborne lidar data, 2019.
- [27] Haifeng Li, Kaijian Qiu, Li Chen, Xiaoming Mei, Liang Hong, and Chao Tao. Scattnet: Semantic segmentation network with spatial and channel attention mechanism for high-resolution remote sensing images, 2020.
- [28] Bo Yuan, Danpei Zhao, Shuai Shao, Zehuan Yuan, and Changhu Wang. Birds of a feather flock together: Category-divergence guidance for domain adaptive segmentation, 2022.
- [29] Yi Xiao, Bin Luo, Jun Liu, Xin Su, and Wei Wang. Bi-temporal gaussian feature dependency guided change detection in remote sensing images, 2024.
- [30] Wanli Ma, Oktay Karakus, and Paul L. Rosin. Knowledge distillation for road detection based on cross-model semi-supervised learning, 2024.
- [31] Mohbat Tharani, Numan Khurshid, and Murtaza Taj. Unsupervised deep features for remote sensing image matching via discriminator network, 2018.
- [32] Yuxia Chen, Pengcheng Fang, Jianhui Yu, Xiaoling Zhong, Xiaoming Zhang, and Tianrui Li. Hi-resnet: Edge detail enhancement for high-resolution remote sensing segmentation, 2024.
- [33] Sophie Crommelinck, Mila Koeva, Michael Ying Yang, and George Vosselman. Robust object extraction from remote sensing data, 2019.
- [34] Xin-Yi Tong, Gui-Song Xia, Fan Hu, Yanfei Zhong, Mihai Datcu, and Liangpei Zhang. Exploiting deep features for remote sensing image retrieval: A systematic investigation, 2019.
- [35] Mikhail Sokolov, Christopher Henry, Joni Storie, Christopher Storie, Victor Alhassan, and Mathieu Turgeon-Pelchat. High-resolution semantically-consistent image-to-image translation, 2022.
- [36] Roni Blushtein-Livnon, Tal Svoray, and Michael Dorman. Performance of human annotators in object detection and segmentation of remotely sensed data, 2024.
- [37] Guillaume Noyel, Jesus Angulo, and Dominique Jeulin. A new spatio-spectral morphological segmentation for multi-spectral remote-sensing images, 2016.
- [38] A Hamida, A. Benoît, P. Lambert, L. Klein, C. Amar, N. Audebert, and S. Lefèvre. Deep learning for semantic segmentation of remote sensing images with rich spectral content, 2017.

-
- [39] Jakub Nalepa, Michal Myller, and Michal Kawulok. Validating hyperspectral image segmentation, 2018.
- [40] Shasvat Desai and Debasmita Ghose. Active learning for improved semi-supervised semantic segmentation in satellite images, 2021.
- [41] Junxing Hu, Ling Li, Yijun Lin, Fengge Wu, and Junsuo Zhao. A comparison and strategy of semantic segmentation on remote sensing images, 2019.
- [42] Onur Tasar, S L Happy, Yuliya Tarabalka, and Pierre Alliez. Semi2i: Semantically consistent image-to-image translation for domain adaptation of remote sensing data, 2020.
- [43] Claire Voreiter, Jean-Christophe Burnel, Pierre Lassalle, Marc Spigai, Romain Hugues, and Nicolas Courty. A cycle gan approach for heterogeneous domain adaptation in land use classification, 2020.
- [44] Danfeng Hong, Naoto Yokoya, Gui-Song Xia, Jocelyn Chanussot, and Xiao Xiang Zhu. X-modalnet: A semi-supervised deep cross-modal network for classification of remote sensing data, 2020.
- [45] Valerio Marsocci, Nicolas Gonthier, Anatol Garioud, Simone Scardapane, and Clément Mallet. Geomultitasknet: remote sensing unsupervised domain adaptation using geographical coordinates, 2023.
- [46] Qingsong Xu, Yilei Shi, Xin Yuan, and Xiao Xiang Zhu. Universal domain adaptation for remote sensing image scene classification, 2023.
- [47] Bilel Benjdira, Yakoub Bazi, Anis Koubaa, and Kais Ouni. Unsupervised domain adaptation using generative adversarial networks for semantic segmentation of aerial images, 2019.
- [48] Chenying Liu, Conrad M Albrecht, Yi Wang, and Xiao Xiang Zhu. Task specific pretraining with noisy labels for remote sensing image segmentation, 2024.
- [49] Mauro Martini, Vittorio Mazzia, Aleem Khaliq, and Marcello Chiaberge. Domain-adversarial training of self-attention based networks for land cover classification using multi-temporal sentinel-2 satellite imagery, 2021.
- [50] Shun Zhang, Xuechao Zou, Kai Li, Congyan Lang, Shiyang Wang, Pin Tao, and Tengfei Cao. Knowledge transfer and domain adaptation for fine-grained remote sensing image segmentation, 2024.
- [51] Haifeng Li, Jian Peng, Chao Tao, Jie Chen, and Min Deng. What do we learn by semantic scene understanding for remote sensing imagery in cnn framework?, 2017.
- [52] Amina Ben Hamida, A Benoit, Patrick Lambert, and Chokri Ben Amar. Three dimensional deep learning approach for remote sensing image classification, 2018.
- [53] Shiyu Miao, Delong Chen, Fan Liu, Chuanyi Zhang, Yanhui Gu, Shengjie Guo, and Jun Zhou. Prompting directsam for semantic contour extraction in remote sensing images, 2024.
- [54] Roberta Iuliana Luca, Alexandra Baicoianu, and Ioana Cristina Plajer. Spectral image data fusion for multisource data augmentation, 2024.
- [55] Jing Wu, David Pichler, Daniel Marley, David Wilson, Naira Hovakimyan, and Jennifer Hobbs. Extended agriculture-vision: An extension of a large aerial image dataset for agricultural pattern analysis, 2023.
- [56] Adrian Höhl, Ivica Obadic, Miguel Ángel Fernández Torres, Hiba Najjar, Dario Oliveira, Zeynep Akata, Andreas Dengel, and Xiao Xiang Zhu. Opening the black-box: A systematic review on explainable ai in remote sensing, 2024.
- [57] Gong Cheng, Xingxing Xie, Junwei Han, Lei Guo, and Gui-Song Xia. Remote sensing image scene classification meets deep learning: Challenges, methods, benchmarks, and opportunities, 2020.

-
- [58] Bill Psomas, Ioannis Kakogeorgiou, Nikos Efthymiadis, Giorgos Tolias, Ondrej Chum, Yannis Avrithis, and Konstantinos Karantzas. Composed image retrieval for remote sensing, 2024.
- [59] Yassine Himeur, Nour Aburaed, Omar Elharrouss, Iraklis Varlamis, Shadi Atalla, Wathiq Mansoor, and Hussain Al Ahmad. Applications of knowledge distillation in remote sensing: A survey, 2024.
- [60] T. Balaji and Dr. M. Sumathi. Effective features of remote sensing image classification using interactive adaptive thresholding method, 2014.
- [61] Hojat Shirmard, Ehsan Farahbakhsh, R Dietmar Müller, and Rohitash Chandra. A review of machine learning in processing remote sensing data for mineral exploration. *Remote Sensing of Environment*, 268:112750, 2022.
- [62] Aayush Dhakal, Subash Khanal, Srikumar Sastry, Adeel Ahmad, and Nathan Jacobs. Geobind: Binding text, image, and audio through satellite images, 2024.
- [63] Zhitong Xiong, Fahong Zhang, Yi Wang, Yilei Shi, and Xiao Xiang Zhu. Earthnets: Empowering ai in earth observation, 2024.
- [64] Beril Sirmacek and Ricardo Vinuesa. Remote sensing and ai for building climate adaptation applications, 2022.
- [65] Lucas Prado Osco, Eduardo Lopes de Lemos, Wesley Nunes Gonçalves, Ana Paula Marques Ramos, and José Marcato Junior. The potential of visual chatgpt for remote sensing, 2023.
- [66] Xiao Xiang Zhu, Devis Tuia, Lichao Mou, Gui-Song Xia, Liangpei Zhang, Feng Xu, and Friedrich Fraundorfer. Deep learning in remote sensing: a review, 2017.
- [67] Benedikt Blumenstiel, Viktoria Moor, Romeo Kienzler, and Thomas Brunschweiler. Multi-spectral remote sensing image retrieval using geospatial foundation models, 2024.
- [68] Lei Ding, Dong Lin, Shaofu Lin, Jing Zhang, Xiaojie Cui, Yuebin Wang, Hao Tang, and Lorenzo Bruzzone. Looking outside the window: Wide-context transformer for the semantic segmentation of high-resolution remote sensing images, 2022.
- [69] Hongruixuan Chen, Jian Song, and Naoto Yokoya. Change detection between optical remote sensing imagery and map data via segment anything model (sam), 2024.
- [70] Suraj Kothawade, Kunjan Mhaske, Sahil Sharma, and Furkhan Shaikh. Content based image retrieval from awifs images repository of IRS Resourcesat-2 satellite based on water bodies and burnt areas, 2018.
- [71] Conrad M Albrecht, Fernando Marianno, and Levente J Klein. Autogeolabel: Automated label generation for geospatial machine learning, 2022.
- [72] Scale-semantic joint decoupling network for image-text retrieval in remote sensing.
- [73] Edoardo Arnaudo, Jacopo Lungu Vaschetti, Lorenzo Innocenti, Luca Barco, Davide Lisi, Vanina Fissore, and Claudio Rossi. Fmars: Annotating remote sensing images for disaster management using foundation models, 2024.
- [74] Jasper Brown, Cameron Clark, Sabrina Lomax, Khalid Rafique, and Salah Sukkarieh. Manipulating uav imagery for satellite model training, calibration and testing, 2022.
- [75] Yunze Zang, Yifei Liu, Xuehong Chen, Anqi Li, Yichen Zhai, Shijie Li, Luling Liu, Chuanhai Zhu, Ruilin Chen, Shupeng Li, and Na Jie. Crop mapping in the small sample/no sample case: an approach using a two-level cascade classifier and integrating domain knowledge, 2022.
- [76] Maxim Neumann, Andre Susano Pinto, Xiaohua Zhai, and Neil Houlsby. In-domain representation learning for remote sensing, 2019.
- [77] Qinfeng Zhu, Yuanzhi Cai, Yuan Fang, Yihan Yang, Cheng Chen, Lei Fan, and Anh Nguyen. Samba: Semantic segmentation of remotely sensed images with state space model, 2024.

-
- [78] Judy X Yang, Jun Zhou, Jing Wang, Hui Tian, and Alan Wee Chung Liew. Hsimamba: Hyperspectral imaging efficient feature learning with bidirectional state space for classification, 2024.
- [79] Hongjia Chen, Xin Xu, and Fangling Pu. Src-net: Bi-temporal spatial relationship concerned network for change detection, 2024.
- [80] Weilian Zhou, Sei-Ichiro Kamata, Haipeng Wang, Man-Sing Wong, Huiying, and Hou. Mamba-in-mamba: Centralized mamba-cross-scan in tokenized mamba model for hyperspectral image classification, 2024.
- [81] John E. Ball, Derek T. Anderson, and Pan Wei. State-of-the-art and gaps for deep learning on limited training data in remote sensing, 2018.
- [82] Lukas Drees, Ribana Roscher, and Susanne Wenzel. Archetypal analysis for sparse representation-based hyperspectral sub-pixel quantification, 2018.

Disclaimer:

SurveyX is an AI-powered system designed to automate the generation of surveys. While it aims to produce high-quality, coherent, and comprehensive surveys with accurate citations, the final output is derived from the AI's synthesis of pre-processed materials, which may contain limitations or inaccuracies. As such, the generated content should not be used for academic publication or formal submissions and must be independently reviewed and verified. The developers of SurveyX do not assume responsibility for any errors or consequences arising from the use of the generated surveys.

www.SurveyX.cn