A Survey of Biomass Gasification for Hydrogen Production: Catalysts, Technologies, and Renewable Energy Integration

Abstract

Biomass gasification is a pivotal technology in the transition towards sustainable energy systems, offering a renewable alternative to fossil fuels by converting organic materials into hydrogen-rich syngas. This survey provides a comprehensive analysis of biomass gasification, focusing on its integration with renewable energy systems, the role of catalysts, and the economic and environmental implications. Key challenges identified include the variability of biomass feedstock characteristics, which affects gasification efficiency, and the need for advanced gasifier designs and process optimization. Recent advancements, such as multifidelity Bayesian optimization and innovative catalyst materials, have shown promise in enhancing process efficiency and syngas yield. The survey also explores the potential of hybrid systems that integrate biomass gasification with solar and wind power, highlighting their capacity to optimize energy generation and storage, reduce reliance on fossil fuels, and promote energy security. Despite the promising potential of biomass gasification, economic challenges such as high capital costs and levelized cost of hydrogen (LCOH) remain significant barriers to scalability. Addressing these challenges requires strategic planning, investment in advanced gasification technologies and infrastructure, and the development of comprehensive models for optimizing hydrogen production costs. Furthermore, the survey emphasizes the importance of sustainable land management practices to ensure the long-term viability of biomass as a renewable energy resource, balancing its use with food production and biodiversity conservation. By addressing these multifaceted challenges and leveraging innovative technologies and strategies, biomass gasification can play a crucial role in the global transition towards a low-carbon energy future. The continued development and optimization of biomass gasification processes, along with strategic investments in renewable energy infrastructure, will be essential for the future success of the hydrogen economy, contributing to the reduction of greenhouse gas emissions and promoting energy security. This survey aims to inform policy and decision-making processes, ultimately supporting the transition to a sustainable energy future.

1 Introduction

1.1 Importance of Biomass Gasification

Biomass gasification is crucial for advancing renewable energy systems and reducing carbon emissions. As anthropogenic CO2 emissions contribute to climate change, converting biomass into hydrogen-rich syngas offers a sustainable alternative to fossil fuels. Biomass currently accounts for about 10% of global energy consumption, with projections indicating it could provide 33-50% by 2050. This process utilizes advanced hydrothermal conversion technologies that efficiently handle high-moisture biomass, eliminating the need for drying. This aligns with the urgent goal of decreasing

Figure 1: chapter structure

fossil fuel dependency and facilitates renewable hydrogen production, essential for decarbonizing hard-to-electrify sectors [1, 2, 3, 4, 5].

The integration of biomass gasification into hydrogen production systems emphasizes its significance in the global energy transition. For instance, the oxidation of biomass-derived aldehydes can generate

hydrogen gas, highlighting biomass's role in renewable hydrogen production [6]. Additionally, producing hydrogen-rich gas for portable solid oxide fuel cells (-SOFCs) illustrates the technological advancements necessary to surpass the limitations of traditional fuels and reforming methods [7].

Optimizing modular electrolysis plants is essential for producing green hydrogen from renewable sources, enhancing the economic feasibility of biomass gasification [8]. Furthermore, exploring carbon-based photocathodes for solar hydrogen production provides efficient alternatives to conventional semiconductor materials, supporting the integration of biomass gasification into renewable energy strategies [9].

Biomass gasification also addresses economic and environmental challenges in hydrogen production. For example, evaluating direct seawater electrolysis for hydrogen production underscores the need for sustainable and economically viable methods [10]. Modeling global levelized costs for hydrogen production highlights the necessity for low-emission methods that consider country-specific investment risks [11].

This process not only harnesses biomass's vast potential—currently contributing to 10% of global energy consumption, with projections suggesting an increase to $150 x 10^{19} kJ by 2050 - but also tackles pressing environmental issues associated with fossil fuel reliance. By utilizing innov[...]$ 12, 4].

1.2 Motivation for the Survey

This survey is driven by the urgent need to tackle the challenges and seize the opportunities presented by biomass gasification for hydrogen production. A primary challenge is the inefficiency and high energy demand of conventional hydrogen production methods, highlighting the necessity for sustainable alternatives like biomass gasification [6]. Developing reliable methods for on-demand hydrogen production, particularly for applications such as micro-solid oxide fuel cells (-SOFCs), is vital for the broader commercialization of these technologies [7].

The survey also investigates biomass's potential as a sustainable energy resource through advanced hydrothermal processing techniques, aligning with global objectives such as the European Union's goal to produce 10 Mt of green hydrogen by 2030 [3]. However, the lack of long-term targets beyond 2030 creates uncertainties regarding the future of green hydrogen [13].

Advancements in solar hydrogen production technologies are another focus, particularly the development of stable and efficient carbon-based photocathodes for photoelectrochemical (PEC) processes [9]. The enhancement of electrocatalyst performance through surface overcoating engineering is vital for advancing electrochemical transformation reactions [14].

Economic challenges, such as the impact of country-specific investment risks on the levelized cost of hydrogen (LCOH), are also central to this survey, as these risks hinder the global competitiveness of hydrogen production [11]. By optimizing electrolysis module coordination under varying operational conditions, the survey aims to provide insights into overcoming these economic barriers [8].

Moreover, the survey emphasizes developing efficient photocatalysts for hydrogen evolution reactions (HER) using sulfide materials, which are critical for advancing clean energy technologies [15]. It also addresses challenges faced by combined heat and power (CHP) operators in optimizing biomass supply contracts amidst demand and pricing uncertainties [16].

Finally, the survey explores seawater electrolysis technologies, particularly the integration of seawater reverse osmosis (SWRO) with proton exchange membrane (PEM) electrolysis, as a promising approach for sustainable hydrogen production [10]. By addressing these multifaceted challenges and opportunities, this survey aims to inform policy and decision-making processes, ultimately supporting the transition to a sustainable energy future.

1.3 Objectives of the Survey

This survey aims to bridge the critical gap between the increasing research publications and stagnant patent activities in green technologies, particularly in hydrogen production and logistics [17]. By focusing on optimizing transportation delivery schedules and inventory management, the survey seeks to enhance the efficiency of hydrogen logistics [18].

A core objective is to analyze the interplay between green hydrogen production and the power sector, emphasizing alternative supply chains and their implications for decarbonization efforts [19]. This analysis is crucial for benchmarking hydrogen production costs and guiding strategic investments and policy decisions, especially as countries like the US pursue comprehensive decarbonization strategies [20].

The survey investigates innovative production methods, addressing inefficiencies in hydrogen production from water splitting using TiO2, where high costs and noble metal co-catalysts such as Pt present significant challenges [21]. A hybrid hydrogen production system model (HPSM) is proposed to optimize production based on local conditions and investment risks [11].

Additionally, the survey explores the potential of carbon-based materials for photocathodes, emphasizing advancements in material stability and efficiency to enable practical applications in photoelectrochemical systems [9]. The role of co-catalysts and structural modifications in enhancing photocatalytic activity is also examined, focusing on significantly improving hydrogen production rates [15].

Furthermore, the survey proposes a decentralized scheduling model utilizing the Alternating Direction Method of Multipliers (ADMM) within a Multi-Agent System (MAS) framework to optimize hydrogen production [8]. This approach is complemented by a two-phase stochastic programming model that integrates biomass contract selection with operational planning, aimed at improving decision-making for CHP operators [16].

Finally, the survey underscores the importance of prioritizing research and development investments in coupled seawater reverse osmosis (SWRO) and proton exchange membrane (PEM) systems, as opposed to direct seawater electrolysis, which remains nascent [10]. These comprehensive objectives are designed to inform future research directions and policy-making processes, ultimately supporting the transition to a sustainable energy future.

1.4 Structure of the Survey

This survey is systematically organized to provide a comprehensive understanding of biomass gasification for hydrogen production, emphasizing its integration with renewable energy systems. The initial section introduces the topic, underscoring the importance and motivation behind the survey, followed by clearly defined objectives. Subsequently, the background and definitions section lays the groundwork by elucidating core concepts such as biomass, hydrogen production, catalysts, gasification technology, renewable energy, and syngas.

The third section delves into biomass as a renewable resource, categorizing different types of biomass and discussing their availability, sustainability, and the environmental and economic benefits they offer. This is followed by an exploration of gasification technology, detailing the gasification process, types of gasifiers, and recent technological advancements that enhance efficiency and syngas yield.

In the fifth section, the focus shifts to catalysts in biomass gasification, examining their roles, mechanisms, and recent advancements, as well as the challenges associated with their utilization. The subsequent section analyzes hydrogen production and syngas utilization, highlighting catalytic processes, innovative production techniques, and the economic and operational considerations involved.

Integration with renewable energy is discussed in the seventh section, which explores synergies between biomass gasification and other renewable energy systems, the potential of hybrid systems, and their economic and operational impacts. The penultimate section addresses the challenges and future directions of biomass gasification, covering technical, economic, and environmental aspects, and proposing potential research opportunities.

Finally, the survey concludes with a summary of key findings and reflections on the future of biomass gasification technology in the transition to renewable energy. Throughout the survey, a unique combination of historical data and future demand projections for hydrogen transport is employed, highlighting regional dependencies and production limitations [22].The following sections are organized as shown in Figure 1.

2 Background and Definitions

2.1 Biomass and Its Role in Renewable Energy

Biomass, encompassing materials such as wood, agricultural residues, and energy crops, is integral to renewable energy strategies due to its abundance and versatility. Its utilization in energy production offers significant CO2 sequestration benefits and aligns with policies promoting low-carbon fuel production [23]. Biomass can be converted into energy products like biofuels through processes such as hydrothermal liquefaction (HTL), effectively transforming both dry and wet biomass [24]. Biomass feedstocks are categorized into first-generation (edible crops), second-generation (non-food lignocellulosic materials), and third-generation (microalgae and cyanobacteria), each offering unique opportunities and challenges for sustainable energy production. Lignocellulosic biomass is particularly significant for producing biodegradable, eco-friendly materials [5].

Efficiency in biomass conversion is enhanced by advanced techniques like co-pyrolysis, which boosts liquid fuel production [25]. The development of metal nanoparticles for catalyzing biomass conversion under green chemistry principles, such as supercritical carbon dioxide (scCO2), further advances biomass conversion technologies [26]. However, addressing inefficiencies in converting heterogeneous lignocellulosic materials is crucial for maximizing biomass's potential as a sustainable energy source, as highlighted by the challenges in converting cellulosic materials and low-density polyethylene [27].

As the global energy landscape shifts towards sustainability, biomass is well-positioned to reduce reliance on non-renewable energy sources while advancing the production of biofuels and other renewable energy products. Continuous optimization of biomass conversion processes and the development of innovative technologies are essential for realizing biomass's full potential in a sustainable energy future [23, 5].

2.2 Hydrogen Production Technologies

Hydrogen serves as a vital clean energy carrier, with steam methane reforming (SMR) currently being the predominant production method due to established infrastructure and low costs. However, SMR's significant carbon emissions necessitate the development of more sustainable alternatives. Blue hydrogen technologies, incorporating carbon capture and storage (CCS), offer a potential solution but remain complex and costly [13].

Green hydrogen production via water electrolysis presents a more sustainable alternative. Optimizing electrolysis processes, such as through the Hydrogen Production System Model (HPSM), can enhance production efficiency by considering local conditions and investment risks [11]. The variability of renewable energy sources requires innovative strategies, including scheduling multiple electrolysis modules to maintain consistent hydrogen production [8].

Developing non-precious-metal-based catalysts is crucial for facilitating hydrogen production reactions without the high costs of precious metals [28]. Photocatalytic water splitting presents another promising method for green hydrogen production, facing challenges related to photocathode stability and charge transport [9, 21]. Biomass gasification, particularly of lignocellulosic biomass, offers a viable renewable pathway for hydrogen production, though the heterogeneous nature of lignocellulosic materials poses challenges for efficient conversion [3]. Innovative catalyst development, such as utilizing eggshell waste, can improve the gasification process's efficiency [29].

Addressing multifaceted challenges through technological innovation and strategic investments is vital for realizing hydrogen's potential as a cornerstone of a sustainable energy future. Exploring sustainable and economically viable methods, such as direct seawater electrolysis, is crucial as conventional approaches rely on high-purity water [10].

2.3 Catalysts in Sustainable Energy Processes

Catalysts are pivotal in enhancing energy processes, optimizing the conversion of biomass into hydrogen-rich syngas by reducing the activation energy required for reactions [3, 30]. Recent advancements focus on innovative materials and methodologies to improve catalytic performance, such as the conducting edge states of 2D Topological Insulator (TI) LiMgAs, which have been proposed as novel catalysts [28]. The integration of machine learning with density functional

theory (DFT) calculations, as demonstrated by the catlas framework, facilitates catalyst discovery by automating the generation of adsorbate-surface configurations and predicting DFT energies [31].

Rational design of photocatalysts, such as incorporating cyanamide defects into carbon nitride structures, has improved efficiency in hydrogen evolution reactions (HER) by enhancing photocatalytic activity [32]. Challenges such as low solar energy utilization and rapid charge carrier recombination in sulfide photocatalysts necessitate ongoing advancements in this field [15]. Moreover, integrating piezoelectric and photocatalytic effects has been shown to enhance charge separation and lower the energy barrier for hydrogen production, offering a novel pathway for increasing process efficiency [33].

2.4   Gasification Technology and Syngas

Gasification technology is crucial for converting biomass into valuable energy carriers, particularly hydrogen-rich syngas, which serves as a versatile feedstock for producing clean hydrogen, electricity, and other valuable chemicals [34]. The efficiency of gasification is significantly influenced by factors such as biomass feedstock type, gasifier design, and operating conditions. Optimizing thermodynamic efficiency while minimizing exergy destruction remains a key challenge [34].

Integrating renewable energy sources and utilizing advanced technologies such as Power-to-X (PtX) systems can enhance hydrogen production efficiency and support decarbonization in sectors like transportation [35, 36, 37]. The North Sea region, for example, has been identified as a potential hub for renewable energy generation and storage, emphasizing the importance of integrating gasification technology with other renewable systems to enhance overall energy efficiency and sustainability.

Developing advanced gasification technologies and optimizing process parameters is crucial for maximizing syngas yield and improving process efficiency. Multifidelity Bayesian optimization techniques, combining high and low-fidelity models, represent a significant advancement, enabling more effective exploration of process efficiencies [34, 38]. Gasification not only provides an alternative to fossil fuels but also supports the transition to a sustainable energy future.

In recent years, biomass has emerged as a significant renewable resource, prompting extensive research into its various forms and applications. Understanding the hierarchical structure of biomass is crucial for appreciating its potential as a sustainable energy source. As illustrated in Figure 2, this figure categorizes biomass into distinct types and characteristics, emphasizing its availability and sustainability. Furthermore, it delineates the environmental and economic benefits associated with biomass, while also addressing the challenges that arise in its utilization. Each category is meticulously divided into specific aspects, underscoring the complexity and multifaceted nature of biomass. This comprehensive framework not only enhances our understanding of biomass but also informs future research directions and policy decisions aimed at optimizing its use in energy production.

3   Biomass as a Renewable Resource

3.1   Types of Biomass and Their Characteristics

Biomass, a renewable energy source, consists of diverse organic materials, each possessing distinct properties that influence their suitability for gasification and chemical production. Lignocellulosic biomass, comprising agricultural residues, wood, and energy crops, is notable for its complex structure of cellulose, hemicellulose, and lignin, which are pivotal for efficient gasification [5]. The chemical composition, moisture, ash content, and energy density of these materials are critical factors affecting gasification efficiency. High cellulose and hemicellulose contents in materials like agricultural residues and wood facilitate the production of hydrogen-rich syngas, supporting the global shift towards low-carbon energy [5]. Despite the fibrous nature of lignocellulosic biomass enhancing reaction surface area, the recalcitrant lignin presents conversion challenges. Optimizing gasification requires understanding intrinsic properties and employing pretreatment methods to improve cellulose and hemicellulose accessibility [5].

Figure 2: This figure illustrates the hierarchical structure of biomass as a renewable resource, categorizing its types and characteristics, availability and sustainability, environmental and economic benefits, and challenges in utilization. Each category is further divided into specific aspects, highlighting the complexity and multifaceted nature of biomass as a sustainable energy source.

3.2 Biomass Availability and Sustainability

Biomass resources, including agricultural residues, forestry by-products, and energy crops, are abundant globally, offering a sustainable alternative for energy production [1]. This abundance is closely linked to agricultural and forestry activities, with residues like straw and husks serving as cost-effective feedstocks [5]. Dedicated energy crops, such as switchgrass and miscanthus, further facilitate the transition to a low-carbon economy [1].

To better understand the interconnectedness of these elements, Figure 3 illustrates the hierarchical structure of biomass availability and sustainability, categorizing key sources, sustainability practices, and conversion technologies that contribute to a low-carbon economy. Ensuring sustainability in biomass utilization involves preventing deforestation, biodiversity loss, and environmental degradation through responsible sourcing and management practices [23]. Advanced conversion technologies, like hydrothermal liquefaction and co-pyrolysis, enhance sustainability by improving efficiency and minimizing environmental impacts, contributing to the circular economy and reducing greenhouse gas emissions [1].


Figure 3: This figure illustrates the hierarchical structure of biomass availability and sustainability, categorizing key sources, sustainability practices, and conversion technologies that contribute to a low-carbon economy.

3.3 Environmental and Economic Benefits

Biomass utilization offers significant environmental and economic benefits, such as reducing greenhouse gas emissions and supporting sustainable development. Biomass energy production is often carbon-neutral, with CO_2 emissions offset by absorption during growth, aligning with climate change mitigation efforts [30]. Environmentally, biomass gasification aids in sustainable waste management by converting organic waste into energy, reducing landfill use, and mitigating methane emissions. Biochar, a gasification by-product, can improve soil health and carbon sequestration [23]. Economically, biomass energy production stimulates rural development, creating jobs and revenue for farmers and local communities involved in feedstock production [1]. Producing biofuels from biomass reduces fossil fuel dependency, enhancing energy security and economic resilience. Advanced conversion technologies, such as catalytic upgrading of hydrothermal liquefaction products, improve economic viability by enhancing efficiency and product quality [24]. Integrating biomass energy into existing systems can yield cost savings and operational efficiencies, as seen with two-phase stochastic programming for biomass supply chain optimization [16]. Utilizing biomass in hybrid systems diversifies energy sources and reduces fossil fuel reliance [1].

3.4 Challenges in Biomass Utilization

Biomass energy production faces challenges that must be addressed to maximize its potential in sustainable energy systems. Key challenges include the variability in biomass feedstock characteristics, such as moisture content, energy density, and composition, impacting gasification efficiency [5]. This necessitates advanced processing techniques and robust system designs to accommodate diverse feedstock properties. Sustainability in biomass production is another challenge, requiring a balance between land use for energy crops and food production, alongside biodiversity conservation [23]. Unsustainable practices, like deforestation and monoculture plantations, can lead to environmental degradation and food competition [1]. Sustainable land management practices and policies are vital to align biomass utilization with environmental and food security goals. Economic barriers also hinder biomass adoption, with high costs for collection, transportation, and processing compared to fossil fuels [1]. Research into cost-effective conversion technologies, such as catalytic processes, is essential. Efficient catalyst discovery is crucial for overcoming conversion limitations, as traditional catalysts often rely on costly materials [28]. Innovative approaches, like using eggshell waste as a catalyst, show promise in improving conversion efficiency and cost-effectiveness [29]. Ongoing research focuses on optimizing processes and developing novel, economically viable catalysts. Integrating machine learning with catalyst discovery, as demonstrated by the catlas framework, offers a promising path for identifying materials with enhanced catalytic properties [31].

4 Gasification Technology

4.1 Gasification Process and Principles

Gasification is a thermochemical process converting biomass into synthesis gas (syngas), which primarily consists of hydrogen (H_2), carbon monoxide (CO), and carbon dioxide (CO_2) [34, 3]. This process is crucial for producing hydrogen-rich syngas, a vital component of sustainable energy systems. The process involves partial oxidation of biomass at 700°C to 1500°C using controlled oxygen or air, encompassing drying, pyrolysis, oxidation, and reduction stages. Initially, moisture is removed to improve efficiency [39]. During pyrolysis, biomass thermally decomposes into volatile gases, tar, and char, with the latter undergoing oxidation to generate heat for endothermic reactions, converting volatiles into syngas [34].

Gasification efficiency is affected by factors like biomass type, moisture content, particle size, and gasifier design. Fixed-bed, fluidized-bed, and entrained-flow gasifiers are used to optimize conversion, with fluidized-bed gasifiers enhancing biomass and oxidizing agent contact, thus improving heat and mass transfer rates for higher syngas yields [40]. Advances in gasification technology aim to enhance thermal efficiency and syngas yield while minimizing environmental impacts. Techniques like multifidelity Bayesian optimization integrate models to optimize process parameters, enhancing biomass gasification efficiency [40]. Integrating gasification with renewable systems, such as solar and wind power, further boosts energy efficiency and sustainability, as shown in models for regions like the North Sea.

Gasification is vital for sustainable energy systems, converting biomass into hydrogen to reduce fossil fuel reliance and combat climate change. It leverages biomass resources, projected to significantly increase energy output by 2050, offering a more efficient alternative to methods requiring dry biomass, thus utilizing high-moisture feedstocks. Integrating gasification with other low-carbon hydrogen production pathways is crucial for meeting future energy demands and supporting the transition to renewable sources [35, 3, 41, 13, 36]. Addressing feedstock variability and optimizing process parameters through innovative technologies can significantly reduce fossil fuel dependence and advance renewable energy solutions.

4.2 Types of Gasifiers

Gasification technology includes various gasifier designs, each optimizing biomass conversion into syngas by adjusting operational parameters like temperature and gasifying medium. This diversity is influenced by numerous physical and chemical factors affecting performance and environmental outcomes, as shown through thermodynamic assessments and parametric studies. Advances in methods, including hydrothermal processing, address biomass moisture content challenges and enhance bioenergy production efficiency [1, 3, 34, 42]. The selection of gasifier type significantly impacts efficiency and output.

As illustrated in Figure 4, the classification of gasifier types highlights their designs and key characteristics. Fixed-bed gasifiers, including updraft and downdraft configurations, are traditional designs. In updraft gasifiers, air or oxygen is introduced at the bottom, with biomass descending through pyrolysis, combustion, and reduction phases. This simpler design suits small-scale applications but may have lower efficiency and higher tar production [1].

Fluidized-bed gasifiers enhance heat and mass transfer due to solid particle fluidization, improving biomass and gasifying agent contact. This results in higher conversion efficiencies and better syngas quality compared to fixed-bed systems [40]. Their flexibility in accommodating various feedstock types, including those with higher moisture content, makes them attractive for biomass gasification [34].

Entrained-flow gasifiers, handling fine particles, produce syngas with higher hydrogen content. Operating at elevated temperatures and pressures, these gasifiers achieve higher efficiency and lower tar content in syngas [34]. Advanced modeling techniques, like multifidelity Bayesian optimization, further enhance performance by optimizing operational parameters [40].

The choice of gasifier type is influenced by biomass feedstock characteristics, desired syngas composition, and specific energy requirements. Each type presents distinct advantages and challenges, necessitating careful selection based on feedstock traits and intended syngas application [40].

Figure 4: This figure illustrates the classification of gasifier types, highlighting their designs and key characteristics. Fixed-bed gasifiers include updraft and downdraft designs, fluidized-bed gasifiers are noted for heat transfer and feedstock flexibility, and entrained-flow gasifiers are recognized for high hydrogen content and low tar production.

4.3 Advancements in Gasification Technology

Recent advancements in gasification technology have enhanced the efficiency and sustainability of hydrogen production from biomass, marking a significant evolution in renewable energy processes. Multifidelity Bayesian optimization techniques, integrating high and low-fidelity models, optimize

9

gasification parameters, improving thermodynamic efficiency and reducing exergy destruction [40]. This progress is vital in increasing syngas yield and refining process optimization, making biomass gasification a more viable and sustainable energy production method.

Innovative processes, like the self-energy-sufficient gasification process, improve efficiency and sustainability in hydrogen production from biomass [42]. Advanced catalyst technologies, including those using eggshell waste, enhance the conversion of lignocellulosic biomass into hydrogen-rich syngas [29].

Integrating renewable energy sources, like solar and wind power, into gasification processes significantly advances efficiency and sustainability, as evidenced by comprehensive energy system models for regions such as the North Sea. Hybrid systems, combining biomass gasification with other renewable technologies, hold potential for enhancing energy production efficiency and sustainability [1].

Innovations have led to novel gasification processes that enhance syngas yield and quality. The SDBD method, for instance, shows higher hydrogen production efficiencies and lower energy costs compared to conventional methods, offering a promising solution for waste valorization [27]. Integrating gasification technology with renewable energy systems can bolster the economic viability and sustainability of hydrogen production.

The future of gasification technology is promising, with ongoing research focused on developing efficient catalysts, optimizing process parameters, and integrating renewable systems. These advancements are crucial for enhancing the sustainability and economic viability of hydrogen production from biomass, supporting the global transition to renewable energy sources. Continued exploration of hybrid systems, combining biomass gasification with other renewable technologies, remains a key area of interest, offering substantial potential for improving energy production efficiency and sustainability [1].

5 Catalysts in Biomass Gasification

5.1 Role and Mechanisms of Catalysts

Catalysts play an essential role in biomass gasification by enhancing reaction efficiency and selectivity, thereby increasing the yield of hydrogen-rich syngas. They achieve this by reducing activation energy, facilitating the decomposition of complex organic structures into simpler molecules [3]. Recent advancements in catalyst technology, such as the development of two-dimensional topological insulators like LiMgAs, have shown potential in enhancing catalytic activity for hydrogen evolution reactions (HER) due to their distinct electronic properties [28]. The catlas framework exemplifies progress in catalyst discovery, utilizing machine learning to predict density functional theory (DFT) energies and expedite the identification of effective catalysts for hydrogen production [31].

Innovative structural designs, such as incorporating cyanamide defects into carbon nitride, have improved photocatalytic activity for HER [32]. Challenges like low solar energy utilization and rapid charge carrier recombination in sulfide photocatalysts persist [15]. To mitigate these issues, research is exploring the combination of piezoelectric and photocatalytic effects to enhance charge separation and lower energy barriers for hydrogen production [33]. Additionally, using eggshell waste as a catalyst presents a sustainable, cost-effective method to boost gasification efficiency [29].

Advancements in catalyst technologies are crucial for sustainable energy systems as they enhance biomass gasification efficiency for hydrogen production [3]. By addressing challenges related to selectivity, stability, and operational efficiency through innovative methods like hybrid optimization and machine learning, the full potential of catalysts in energy processes can be realized.

As depicted in Figure 5, catalysts are integral to optimizing biomass gasification, significantly improving efficiency and syngas yield. The first image illustrates a chemical reaction mechanism for methanol conversion to formaldehyde, showing a 14-step transformation process. The second image offers a structural analysis of binary mixtures, crucial for understanding catalytic behavior, focusing on elemental interactions like oxygen and hydrogen. The third image highlights the impact of adsorbate-electrode interactions on methanol conversion to acetaldehyde across various metal catalysts, underlining the importance of these interactions in shaping catalytic pathways. Collectively,

10

(a) The image depicts a chemical reaction mechanism for the conversion of methanol to formaldehyde.[43]

(b) Structural Analysis of Binary Mixtures[44]

(c) Effect of adsorbate-electrode interaction on the selectivity of methanol to acetaldehyde on various metal catalysts[31]

Figure 5: Examples of Role and Mechanisms of Catalysts

these visuals emphasize the complex mechanisms in catalytic biomass gasification and their role in advancing sustainable energy solutions [43, 44, 31].

5.2 Gasification Process and Principles

Gasification is a thermochemical process that converts carbonaceous materials, such as biomass, into synthesis gas (syngas) through partial oxidation at high temperatures [34]. The process includes four stages: drying, pyrolysis, oxidation, and reduction. Initially, moisture is removed to enhance reaction efficiency, followed by pyrolysis, where biomass decomposes into volatile gases, tar, and char. The char undergoes oxidation, generating heat that drives endothermic reactions to transform volatile gases into syngas, primarily composed of carbon monoxide (CO), hydrogen (H_2), and carbon dioxide (CO_2) [39].

Gasification efficiency is affected by factors such as biomass feedstock type, moisture content, particle size, and gasifier design. Fluidized-bed gasifiers, for instance, improve heat and mass transfer rates by enhancing contact between biomass and the oxidizing agent, thus increasing syngas yields [40]. Recent technological innovations, including multifidelity Bayesian optimization techniques, have been developed to enhance thermal efficiency and syngas yield while minimizing environmental impacts [40]. Integrating gasification with renewable energy systems, like solar and wind power, further boosts energy efficiency and sustainability, as demonstrated in regional models for areas such as the North Sea.

Gasification technology is pivotal for advancing sustainable energy systems by converting biomass into hydrogen and reducing fossil fuel reliance. This process leverages biomass resources, which are expected to significantly enhance energy output by 2050, offering an efficient alternative to traditional methods that require dry biomass. Integrating gasification with other low-carbon hydrogen production pathways is essential for meeting future energy demands and supporting the transition to renewable energy sources [35, 3, 41, 13, 36]. By addressing feedstock variability challenges and optimizing process parameters through innovative technologies, gasification can significantly contribute to reducing fossil fuel dependence and advancing renewable energy solutions.

5.3 A Survey of Biomass Gasification for Hydrogen Production: Catalysts, Technologies, and Renewable Energy Integration

Biomass gasification for hydrogen production is a viable pathway toward sustainable energy systems, providing an alternative to fossil fuels and aiding in carbon emissions reduction. This survey provides a comprehensive overview of current biomass gasification technologies, catalysts, and their integration with renewable energy systems. It analyzes recent advancements in green technologies, focusing on renewable energy, hydrogen power, and decarbonization, while identifying key challenges and

opportunities in these areas. The survey highlights a gap between scientific output and patenting trends, emphasizing the need for clear green hydrogen production targets in Europe to mitigate investment uncertainties and enhance climate strategies, supporting the global transition to sustainable energy [17, 13].

The survey is organized into sections addressing various aspects of biomass gasification for hydrogen production. The introduction underscores the topic's significance in renewable energy and carbon emission reduction, outlining the survey's objectives. The background section provides an overview of core concepts, including biomass, hydrogen production, and the environmental and economic benefits of biomass as a renewable resource. The gasification process, types of gasifiers, and recent technological advancements are examined, highlighting their effects on efficiency and syngas yield.

The role of catalysts in enhancing hydrogen production during biomass gasification is discussed in detail, focusing on various catalyst types, mechanisms, and recent developments. The survey addresses challenges in catalyst utilization, such as generalizing machine learning models across different elemental compositions and adsorbate-surface interactions. It also explores innovative AI workflows that integrate advanced optimization techniques for catalyst discovery and optimization [45, 44, 14, 46].

The integration of biomass gasification with other renewable energy sources is another critical area explored in this survey. It discusses the potential of hybrid systems and the advantages of integrating various renewable technologies, detailing their economic and operational impacts. Specifically, the survey highlights the necessity of strategic integration measures to optimize the performance of renewable energy sources, particularly in regions like the North Sea, where ambitious development targets exist for offshore wind and hydrogen technologies [17, 47, 36, 48, 37]. The survey also identifies key challenges and opportunities in these areas, including technical, economic, and environmental barriers, while discussing potential future directions and research opportunities aimed at advancing biomass gasification technology and supporting the transition to a sustainable energy future [1, 37, 19, 13].

6 Catalysts in Biomass Gasification

Catalysts are integral to biomass gasification, enhancing chemical reactions and optimizing efficiency and sustainability in producing hydrogen-rich syngas. Their applications include catalytic steam and dry reforming of methane, significantly impacting efficiency, stability, and environmental outcomes. Recent advancements incorporate machine learning to refine catalyst characteristics and reaction conditions, while bi- and tri-metallic catalysts for dry reforming enhance activity and stability, promoting sustainable hydrogen production. These developments underscore the catalysts' role in reducing greenhouse gas emissions and improving production efficiency [35, 42, 49]. This section explores various catalyst categories and their contributions to enhancing reaction pathways, conversion rates, and product yields, setting the stage for a comprehensive exploration of advancements in catalyst technology.

6.1 Types of Catalysts and Their Applications

In biomass gasification, catalysts are crucial for enhancing conversion efficiency and selectivity, particularly for hydrogen-rich syngas production. The choice of catalyst significantly influences reaction pathways, conversion rates, and product yields [49]. Noble metal catalysts, like platinum (Pt), are renowned for high activity and selectivity in hydrogen evolution reactions (HER), but their high cost and limited availability hinder large-scale applications [49]. This has spurred interest in non-noble metal alternatives, including transition metal oxides, carbides, and nitrides, which are abundant, cost-effective, and exhibit high catalytic activity and stability under gasification conditions [49]. Eggshell waste exemplifies unconventional materials with potential as catalysts in transesterification reactions [29].

Complex chalcogenide compositions, such as group-5 MX2 materials like H-TaS2 and H-NbS2, demonstrate promise as electrocatalysts for efficient water splitting, offering high catalytic activity and stability [32]. Catalysts are pivotal in minimizing the environmental impact of energy production processes, significantly contributing to reducing greenhouse gas emissions and fostering sustainable energy systems [3].

12

6.2 Advancements in Catalyst Development

Recent advancements in catalyst development have significantly improved the efficiency and sustainability of biomass gasification for hydrogen production. Integrating density functional theory (DFT) with machine learning models accelerates novel catalyst discovery, predicting optimal configurations that enhance efficiency and cost-effectiveness [50, 31]. Innovative materials, such as two-dimensional topological insulator (TI) LiMgAs, have shown enhanced performance in hydrogen evolution reactions (HER) due to their unique electronic properties [28]. Strained and defective black Bi_2O_3 photocatalysts, developed via high-pressure torsion (HPT) methods, significantly improve hydrogen production through enhanced light absorption and reduced electron-hole recombination [51].

Exploring unconventional materials like eggshell waste provides cost-effective solutions that align with sustainable energy goals by utilizing waste in energy production [29]. Surface overcoating engineering advancements have improved the stability and activity of non-precious metal-based electrocatalysts, essential for the economic viability of hydrogen production [14]. Hybrid catalysts combining various catalytic functions, including piezoelectric and photocatalytic effects, hold promise for enhancing hydrogen production efficiency [33]. Continued exploration of novel materials and methodologies, exemplified by the catlas framework that automates optimal catalyst discovery through machine learning and DFT predictions, is critical for advancing biomass gasification technology [31].

Integrating these advancements into biomass gasification processes can significantly boost hydrogen production efficiency, mitigate environmental impacts, and support the transition to sustainable energy systems [30]. Addressing challenges related to catalyst stability, selectivity, and cost is vital for revolutionizing biomass gasification and its role in the hydrogen economy. The development and deployment of advanced catalyst technologies will be pivotal in realizing biomass gasification's potential as a sustainable energy solution, aiding the global shift towards a low-carbon energy future.

6.3 Challenges in Catalyst Utilization

Utilizing catalysts in biomass gasification for hydrogen production presents several challenges that must be addressed to improve efficiency and economic viability. A primary challenge is the dynamic gasification environment, which can lead to catalyst deactivation due to sintering, poisoning, and coking [52]. Developing robust catalysts that withstand high temperatures and impurities in biomass feedstocks is essential [3].

Cost-effective catalyst development is crucial for biomass gasification's economic viability. Traditional catalysts often rely on precious metals, which are expensive and scarce, limiting their use [28]. Consequently, there is a growing interest in alternative materials, such as non-precious metal-based catalysts and waste-derived materials like eggshell waste, which enhance gasification efficiency [29].

Maintaining catalyst stability and activity over prolonged operational periods is another significant challenge, as catalysts are prone to deactivation from sintering, coking, and poisoning by impurities in biomass feedstocks [50]. Integrating machine learning with catalyst discovery processes, such as the catlas framework, offers a promising approach to identify optimal catalysts by predicting their performance based on DFT calculations [31]. Variability in biomass feedstock characteristics, such as moisture content, ash content, and composition, further complicates catalyst performance in gasification processes [5]. Advanced catalyst design that considers these variabilities is essential for optimizing gasification efficiency and syngas yield [3].

Ongoing research aims to develop novel catalysts that address these challenges. For instance, integrating cyanamide defects into carbon nitride structures has improved photocatalytic activity for hydrogen evolution reactions (HER) [32]. Exploring group-5 MX2 materials, such as H-TaS2 and H-NbS2, has revealed their high catalytic activity beneficial for sustainable energy applications [32]. Combining machine learning with catalyst discovery processes, such as the catlas framework, offers a promising approach to identify optimal catalysts for biomass gasification [31]. Hybrid optimization methods, such as multifidelity Bayesian optimization, can further improve biomass gasification processes by optimizing catalyst properties and process parameters [40]. This approach enables effective exploration of the parameter space, leading to more efficient and sustainable gasification processes.

13

7 Hydrogen Production and Syngas Utilization

7.1 Catalytic Processes in Hydrogen Production

Catalysts are essential for enhancing the efficiency of hydrogen production from syngas, primarily by lowering the activation energy of chemical reactions and accelerating the conversion of biomass into hydrogen-rich syngas. This catalytic enhancement is critical for optimizing process efficiency and increasing the yield of hydrogen [3].

Recent advancements in catalyst technology have emphasized innovative materials and methodologies to boost catalytic performance. For instance, a MEMS-based micro-reformer has achieved a 74% efficiency in hydrogen production, underscoring the potential of micro-scale reformers in this domain [53]. The trend towards miniaturization and precision in catalyst design is pivotal for improving hydrogen production efficiency.

Non-precious metal-based catalysts, including transition metal oxides, carbides, and nitrides, have emerged as cost-effective alternatives to noble metals, maintaining high catalytic activity and stability [54]. Notably, group-5 MX_2 materials such as H-TaS$_2$ and H-NbS$_2$ exhibit high catalytic activity, significantly enhancing hydrogen production efficiency [32].

Innovative approaches integrating piezoelectric and photocatalytic effects have also shown promise in hydrogen production from syngas. For example, defective $BaTiO_{3-x}$ nanoparticles activated by ultrasound and light have facilitated efficient hydrogen production from seawater [33]. This indicates the potential for hybrid catalytic systems that leverage multiple functionalities to improve process efficiency and sustainability.

Furthermore, the development of feature-driven trading models for hybrid power plants is crucial for optimizing energy processes, paralleling how catalysts enhance hydrogen production. These models utilize contextual information, such as historical wind power forecasts, to inform trading decisions, potentially increasing profits by up to 51% while addressing the challenges of renewable energy intermittency [55, 56].

7.2 Innovative Hydrogen Production Techniques

Advancements in hydrogen production techniques are vital for improving the efficiency and sustainability of biomass gasification, particularly in producing hydrogen from syngas. Traditional methods like steam methane reforming (SMR) and conventional water electrolysis face criticism for high energy consumption and carbon emissions. Emerging techniques, such as decoupled water splitting and seawater electrolysis, aim to enhance efficiency and sustainability. Decoupled water splitting separates hydrogen and oxygen production, increasing flexibility, while seawater electrolysis utilizes abundant seawater, reducing reliance on high-purity water and operational costs. Additionally, advancements in electrolysis technologies—alkaline, proton exchange membrane (PEM), and solid oxide electrolysis cells (SOEC)—are being explored to improve the economic viability and carbon intensity of hydrogen production, especially in regions with cleaner energy grids [35, 10, 57, 20, 58].

A promising area of innovation is the development of advanced photocatalytic materials for water splitting, including carbon-based photocathodes, which have shown potential in enhancing photoelectrochemical (PEC) hydrogen production processes [9]. However, challenges remain in improving the stability and efficiency of these materials, particularly regarding charge generation, transport, and recombination [51].

Hybrid systems combining multiple hydrogen production methods are gaining interest. Integrating renewable technologies like solar and wind with biomass gasification can enhance hydrogen production efficiency and sustainability [1]. Energy system models, such as those developed for the North Sea, demonstrate the potential of hybrid systems in optimizing energy production and storage capacities.

Direct seawater electrolysis represents a significant advancement in hydrogen production technology. By integrating seawater reverse osmosis (SWRO) with PEM electrolysis, this approach offers a sustainable pathway to hydrogen production, addressing the challenges of relying on high-purity water in conventional electrolysis processes [10].

7.3 Syngas as a Feedstock for Chemical Processes

Syngas, a versatile mixture of hydrogen (H_2), carbon monoxide (CO), and carbon dioxide (CO_2), is a crucial intermediate in various chemical processes, significantly contributing to hydrogen production and other valuable chemicals. Its composition can be tailored by adjusting gasification parameters, allowing for the production of syngas that serves as a feedstock for applications such as renewable natural gas (RNG) production and the synthesis of hydrogen and electrofuels. This adaptability enhances its potential across sectors, supporting climate change mitigation efforts and integrated renewable energy systems [23, 38, 34].

A primary use of syngas is hydrogen production, a clean energy carrier with significant potential to reduce carbon emissions and facilitate the transition to a low-carbon economy [3]. Hydrogen-rich syngas can be utilized in micro-solid oxide fuel cells (-SOFCs) for portable power generation, offering a sustainable alternative to conventional fuels [7].

Beyond hydrogen, syngas serves as a critical feedstock for synthesizing chemicals like methanol, ammonia, and synthetic natural gas (SNG) [40]. The conversion processes, such as Fischer-Tropsch synthesis, yield liquid hydrocarbons for use as transportation fuels or chemical feedstocks [3]. The versatility of syngas supports its integration into various industrial processes, facilitating the production of a wide range of chemicals and materials.

Moreover, syngas can be utilized in integrated gasification combined cycle (IGCC) plants, which offer high efficiency and low emissions compared to traditional power generation methods [40]. Integrating syngas into power generation can enhance energy efficiency and contribute to reducing greenhouse gas emissions, aligning with global sustainable energy production efforts.

The potential of syngas as a feedstock underscores its significance in transitioning to a low-carbon energy economy. By optimizing gasification processes and integrating syngas with renewable energy systems, such as hydrogen and e-methanol production via Power-to-X (PtX) technologies, the efficiency and sustainability of energy production can be significantly enhanced. This approach not only facilitates renewable energy utilization but also addresses carbon sourcing challenges for electrofuels, contributing to a robust hydrogen infrastructure. Integrating these systems supports the transition to a low-carbon energy future by enabling flexible energy supply chains, reducing surplus renewable generation, and providing substantial economic benefits, ultimately aligning with global net-zero emissions goals [36, 38, 56, 59].

The ongoing exploration of syngas as a feedstock for chemical processes presents significant opportunities for advancing sustainable energy systems. Leveraging syngas versatility and optimizing its production and utilization can unlock new pathways for sustainable energy production and contribute to the global transition towards a low-carbon future. Continued advancements in gasification technologies and strategic syngas integration into existing energy systems will be crucial for maximizing its potential as a sustainable energy carrier, facilitating the shift from fossil fuels to renewable energy sources, and supporting decarbonization across sectors, including transportation and industry. Additionally, employing methods such as power-to-gas (P2G) and coal-to-hydrogen (C2H) can enhance energy system flexibility, reduce greenhouse gas emissions, and optimize renewable resource use, contributing to a resilient and low-carbon energy infrastructure [3, 60, 48, 59, 37].

7.4 Economic and Operational Considerations

The economic and operational dimensions of hydrogen production and syngas utilization are crucial for assessing the feasibility and scalability of biomass gasification technologies within renewable energy systems. Transitioning to green hydrogen incurs significant system costs, primarily due to substantial investments in renewable energy infrastructure and electrolyzers. Research indicates that meeting green hydrogen requirements could increase overall system costs by approximately €82 billion in Europe, highlighting the necessity for strategic policy and investment decisions to balance these costs [61].

A primary economic challenge is the high levelized cost of hydrogen (LCOH), influenced by country-specific investment risks and renewable energy source volatility [11]. Addressing these challenges requires optimizing hydrogen production processes, such as through the Hydrogen Production System Model (HPSM), which enhances production efficiency by considering local conditions and investment risks [11]. Additionally, feature-driven trading models for hybrid power plants can optimize the

coordination of multiple electrolysis modules, reducing operational costs and enhancing economic viability [8].

Operational considerations are also significant in integrating hydrogen production into existing energy systems. Developing energy infrastructure to support the hydrogen economy presents substantial challenges, necessitating strategic planning and investment. The lack of comprehensive data and models for hydrogen production costs, particularly for binary and multicomponent mixtures, adds uncertainty to economic projections [62]. Robust models and data collection efforts are essential for accurately assessing hydrogen production and utilization costs and benefits [11].

Moreover, the economic viability of hydrogen production is influenced by country-specific investment risks and LCOH, which must be carefully considered in strategic planning and decision-making processes to ensure competitiveness in the global energy market [11]. Optimizing transportation delivery schedules and inventory management can enhance hydrogen logistics efficiency, bridging the gap between theoretical research and practical implementation [18].

Integrating syngas into existing chemical processes presents economic opportunities, serving as a feedstock for producing various chemicals and materials, including methanol, ammonia, and synthetic natural gas (SNG) [40]. Developing innovative gasification technologies and optimizing process parameters are crucial for maximizing syngas yield and enhancing biomass gasification's economic viability [40].

The exploration of direct seawater electrolysis as a potential hydrogen production technology underscores the need for sustainable and economically viable methods. This approach addresses challenges related to high-purity water reliance in conventional electrolysis, offering a promising pathway to cost-effective hydrogen production [10]. However, the lack of comprehensive data and models for hydrogen production costs, particularly for non-conventional methods like direct seawater electrolysis, presents challenges in accurately assessing their economic viability. Addressing these uncertainties is crucial for the widespread adoption of sustainable hydrogen production technologies [2].

8 Integration with Renewable Energy

The integration of renewable energy systems with biomass gasification represents a pivotal advancement in the pursuit of sustainable energy solutions. This synergy not only enhances the efficiency of energy production but also fosters a more resilient and diversified energy landscape. As we delve into the specific interactions and benefits of these integrated systems, it is essential to explore the various synergies that arise from their combination. The following subsection will examine the collaborative opportunities and operational efficiencies that can be achieved through the integration of biomass gasification with other renewable technologies, setting the stage for a deeper understanding of their potential impacts on energy sustainability.

8.1 Synergies between Biomass Gasification and Renewable Energy Systems

Biomass gasification, when integrated with renewable energy systems, presents a compelling case for enhancing the sustainability and efficiency of energy production. This integration capitalizes on the synergistic characteristics of various renewable energy sources, such as offshore wind and hydrogen production, to enhance resource efficiency, minimize greenhouse gas emissions, and decrease dependence on fossil fuels. By implementing strategies like grid expansions and electricity storage, as well as utilizing hydrogen for industrial applications, this approach not only optimizes the energy system but also aligns with ambitious targets for carbon neutrality and sustainable development. [17, 48, 38]

A significant synergy between biomass gasification and renewable energy systems lies in the development of hybrid systems that integrate various renewable technologies, such as thermochemical and biological conversion methods, to enhance energy production efficiency and sustainability. These hybrid systems can leverage the diverse characteristics of biomass, which is an abundant and environmentally friendly energy source, to produce a range of bioenergy products, including bio-oil and biodiesel. This approach not only addresses the challenges of fossil fuel depletion and environmental degradation but also positions biomass as a key player in meeting future global energy demands, projected to rise significantly by 2050. [1, 3, 34]. These hybrid systems can enhance energy production efficiency and sustainability by integrating biomass gasification with other renewable energy sources

16

such as solar and wind power . The development of comprehensive energy system models for regions like the North Sea has demonstrated the potential of hybrid systems in optimizing energy production and reducing reliance on non-renewable energy sources .

The integration of biomass gasification with other renewable energy systems offers significant synergies and collaborative opportunities. For instance, the combination of biomass gasification with solar and wind power can enhance the overall efficiency and sustainability of energy production systems [1]. This integration can lead to significant cost savings, as well as reductions in greenhouse gas emissions, supporting the transition towards a low-carbon energy economy .

Moreover, the development of energy system models for regions like the North Sea has demonstrated the potential for integrating biomass gasification with renewable energy systems, highlighting the importance of such integration in advancing renewable energy strategies . These models offer comprehensive insights into optimizing energy production processes by evaluating critical factors such as projected electricity generation, storage capacities, and demand forecasts for 2030 and 2040. They emphasize the integration of variable renewable energy sources (vRES) and highlight the importance of balancing these sources with demand through measures such as grid expansions, hydrogen production, and electricity storage. The findings suggest that strategic combinations of these integration measures can significantly reduce emissions and costs, thereby facilitating a more efficient transition to a low-carbon energy system. [55, 63, 36, 48, 59]

In addition to enhancing energy production efficiency, the integration of biomass gasification with renewable energy systems can also provide economic benefits. By diversifying energy sources and reducing dependency on fossil fuels, hybrid systems can offer cost savings and improve the economic viability of renewable energy projects [1]. The implementation of multifidelity Bayesian optimization techniques, which integrate high and low-fidelity models, can further enhance the performance and efficiency of hybrid energy systems, facilitating their broader adoption [40].

8.2 Hybrid Systems and Their Potential

The integration of biomass gasification with various renewable energy technologies has led to the development of hybrid systems that significantly enhance energy production efficiency and sustainability. This approach leverages the abundant and environmentally friendly characteristics of biomass, which currently contributes approximately 10

Hybrid systems that combine biomass gasification with other renewable technologies, such as solar and wind power, can significantly enhance energy production efficiency by optimizing resource utilization and minimizing environmental impacts. The integration of solar and wind energy with biomass gasification processes can significantly improve the efficiency and sustainability of energy production systems. This is particularly evident in comprehensive energy system models developed for regions like the North Sea, which emphasize the importance of balancing variable renewable energy sources (vRES) with demand through strategies such as grid expansions, electricity storage, and hydrogen production. These models indicate that combining these integration measures can lead to substantial reductions in emissions and energy costs, thereby enhancing the overall performance of energy systems while supporting ambitious decarbonization targets for the region by 2030 and beyond. [64, 48, 34, 47]. These models highlight the potential of hybrid systems in advancing renewable energy strategies and supporting the transition to a low-carbon energy future .

The integration of renewable energy sources, such as solar and wind power, with biomass gasification processes can significantly enhance energy efficiency and sustainability. The integration of solar energy to supply the heat required for gasification processes not only diminishes dependence on fossil fuels but also plays a crucial role in reducing carbon emissions. This shift supports the transition towards a low-carbon energy economy, as evidenced by research indicating that biomass energy consumption can effectively mitigate CO_2 emissions while simultaneously fostering economic growth. By promoting the use of renewable energy sources, such as solar and biomass, we can enhance sustainability and contribute to a more resilient energy infrastructure, aligning with global efforts to combat climate change and promote environmentally responsible development. [12, 13]

Furthermore, the development of hybrid systems that combine biomass gasification with other renewable energy technologies, such as wind and solar power, offers promising potential for enhancing energy production efficiency and sustainability [1]. The integration of these technologies can lead to

17

significant cost savings and operational efficiencies, as well as reduce dependency on fossil fuels and promote energy security .

8.3 Hybrid Systems and Their Potential

Hybrid systems that combine biomass gasification with other renewable energy technologies offer significant potential for enhancing the efficiency and sustainability of energy production. These systems leverage the unique strengths of different renewable energy sources, such as solar and wind power, to optimize energy generation and storage capacities, contributing to a more resilient and sustainable energy system [1].

The integration of biomass gasification with renewable energy sources, such as solar and wind power, not only enhances energy efficiency and sustainability but also plays a crucial role in reducing dependence on fossil fuels, mitigating CO2 emissions, and promoting economic growth. Current estimates indicate that biomass contributes approximately 10

Hybrid systems that combine biomass gasification with other renewable energy technologies, such as solar and wind power, offer significant potential for improving energy production efficiency and sustainability [1]. These systems leverage the complementary strengths of different renewable technologies, optimizing energy generation and storage capacities to meet varying demand patterns and enhance overall energy system resilience .

The integration of biomass gasification with renewable energy systems not only improves energy production efficiency but also offers substantial economic advantages, such as increased GDP per capita, and environmental benefits, including a reduction in CO2 emissions per capita, thereby positioning biomass as a viable policy tool for sustainable development and addressing climate change challenges. [1, 12, 3, 65, 34]. By diversifying energy sources and reducing dependency on fossil fuels, hybrid systems can offer substantial cost savings and contribute to energy security . The development of comprehensive energy system models for regions like the North Sea has demonstrated the potential of hybrid systems in optimizing energy production and storage capacities, highlighting their role in advancing renewable energy strategies .

8.4 Economic and Operational Impacts

9 Challenges and Future Directions

Navigating the complexities of biomass gasification involves addressing technical challenges such as feedstock variability, gasifier design, and process optimization. These challenges are critical to enhancing the efficiency and sustainability of biomass gasification as a viable energy solution.

9.1 Technical Challenges in Biomass Gasification

Biomass gasification is challenged by the heterogeneous nature of biomass feedstocks, which impacts efficiency and consistency due to variations in moisture content, energy density, and composition [5, 3]. Advanced processing techniques and robust system designs are necessary to accommodate these diverse properties. Optimizing process parameters is essential for maximizing syngas yield and efficiency, with multifidelity Bayesian optimization techniques proving effective in exploring parameter spaces [40, 34]. Fluidized-bed gasifiers enhance heat and mass transfer rates, improving syngas yields over fixed-bed systems [40].

Integrating renewable energy sources like solar and wind with gasification processes can enhance energy efficiency and sustainability by providing necessary conversion heat and reducing fossil fuel reliance [3, 12, 59]. Hydrothermal biomass conversion technologies streamline processes by eliminating drying, improving production efficiency. Energy system models, such as those for the North Sea, highlight the potential of integrating gasification with renewable systems to advance strategies [1].

9.2 Economic and Scalability Issues

Economic and scalability challenges impact the feasibility of biomass gasification for hydrogen production. A significant concern is the high levelized cost of hydrogen (LCOH), influenced by

feedstock costs, process efficiency, and investment risks [11]. Addressing these requires investment in advanced technologies and infrastructure to enhance efficiency and reduce costs [1]. Multifidelity Bayesian optimization can improve efficiency, leading to cost reductions and enhanced economic viability [40, 34].

Advanced gasifier designs, such as fluidized-bed systems, are crucial for scalability, offering superior heat and mass transfer rates [40]. Integrating biomass gasification with renewable energy sources can optimize energy generation and storage, reducing fossil fuel reliance and promoting energy security [1]. Energy system models, especially for regions like the North Sea, demonstrate the potential of hybrid systems in optimizing capacities.

Transitioning to a hydrogen economy demands substantial infrastructure investments, including production facilities and distribution networks [66]. Comprehensive data and models are essential for competitive hydrogen production costs, requiring strategic planning and investment.

9.3 Environmental and Sustainability Concerns

Biomass gasification holds potential for sustainable hydrogen production, yet poses environmental challenges like greenhouse gas emissions and air pollution [1]. Advanced gasification technologies and emission controls are necessary to mitigate these impacts. Sustainability in biomass production is crucial, as land for energy crops must balance food production and biodiversity conservation [48, 1]. Unsustainable practices, such as deforestation and monocultures, can lead to environmental degradation. Sustainable land management practices are essential to ensure biomass utilization aligns with environmental and food security goals.

Advanced conversion technologies like hydrothermal liquefaction and co-pyrolysis improve efficiency and reduce environmental impacts, enhancing sustainability [1]. Integrating biomass gasification into energy systems raises challenges in land use and resource management, necessitating comprehensive data and models to assess environmental impacts accurately [62].

9.4 Future Directions and Research Opportunities

Addressing technical, economic, and environmental challenges is crucial for the future of biomass gasification. Variability in feedstock characteristics affects efficiency and consistency, requiring advanced processing and robust system designs [5, 3]. Innovations like multifidelity Bayesian optimization and advanced gasifier designs, such as fluidized-bed gasifiers, show promise in enhancing efficiency and sustainability [40, 34].

Economic barriers, such as high capital costs and investment risks, hinder scalability [11]. Research into cost-effective conversion technologies and optimization models can improve economic viability [18]. Addressing environmental and sustainability concerns is vital for public acceptance, regulatory frameworks, and investment in the hydrogen market [3, 13, 67, 68, 37].

Achieving a sustainable energy future requires integrating high shares of variable renewable energy sources (vRES) into the energy system. This involves strategic investments in infrastructure, supportive policies, and advanced technologies to reduce emissions and costs. By leveraging synergies between offshore energy resources and existing infrastructure, and prioritizing green hydrogen hubs, demand flexibility can be enhanced, aiding in meeting carbon reduction targets for 2030 and beyond [1, 17, 47, 63, 48]. Prioritizing R&D in advanced conversion technologies and integrating biomass gasification with renewable systems can improve efficiency and sustainability, supporting the transition to a low-carbon future.

This survey highlights biomass gasification as a transformative technology in renewable energy systems, emphasizing its potential in the global energy transition. By converting organic materials into hydrogen-rich syngas, biomass gasification offers a sustainable alternative to fossil fuels, aligning with global efforts towards a low-carbon energy future. The integration of biomass gasification into hydrogen production systems underscores its significance in leveraging organic materials as a renewable resource and facilitating clean energy production.

The survey identifies technical, economic, and environmental challenges and opportunities in biomass gasification for hydrogen production, emphasizing the need for advancements in conversion technologies [1, 3, 37]. Developing advanced gasification technologies, such as multifidelity Bayesian

19

optimization techniques and innovative catalyst materials, is crucial for improving process efficiency and sustainability. By addressing challenges related to feedstock variability, gasifier design, and process optimization, biomass gasification's full potential as a sustainable energy solution can be realized.

Integrating biomass gasification with renewable energy systems, such as solar and wind power, can further enhance energy production efficiency and sustainability. Hybrid systems that combine biomass gasification with other renewable technologies can optimize energy generation and storage capacities, reducing dependency on fossil fuels and promoting energy security [1].

Strategic planning and investment in energy infrastructure are essential to support the hydrogen economy. Developing detailed data and sophisticated models for hydrogen production costs, optimizing transportation schedules, and inventory management are crucial for enhancing efficiency and economic feasibility in hydrogen production and integration into various sectors, particularly in decarbonizing transportation [18, 36, 59]. Advanced optimization techniques, such as mixed-integer programming and Markov decision processes, can manage uncertainties in hydrogen production and demand, facilitating a sustainable and economically viable hydrogen supply chain.

10 Integration with Renewable Energy

10.1 Synergies between Biomass Gasification and Renewable Energy Systems

Integrating biomass gasification with renewable energy systems enhances energy efficiency and sustainability by leveraging the strengths of solar, wind, and biomass resources. This integration reduces fossil fuel reliance and addresses climate change by optimizing energy production and promoting economic and environmental sustainability. Particularly in regions like the North Sea, where ambitious renewable energy targets are set for 2030 and 2040, combining biomass with variable renewable energy sources (vRES) and incorporating grid expansions, electricity storage, and hydrogen production is vital for minimizing emissions and reducing energy costs [48, 4].

Hybrid systems exemplify this integration, utilizing solar and wind power to supply heat for gasification, thus enhancing energy production efficiency and facilitating the transition to a low-carbon economy. Energy system models for the North Sea highlight opportunities for integrating biomass gasification with offshore wind and other renewable systems, emphasizing the role of synergies among energy technologies in balancing supply and demand and promoting sustainability [64, 48, 47]. These models underscore the importance of coordinated efforts, such as grid expansions and hydrogen strategies, to enhance energy sustainability.

Furthermore, hybrid systems that integrate biomass gasification with renewable technologies optimize energy generation and storage, enhancing resilience against fluctuating demand [1]. Multifidelity Bayesian optimization techniques can further improve these systems by optimizing process parameters and syngas yield [40].

The economic and operational benefits of integrating biomass gasification with renewable systems include significant cost savings and enhanced energy security through diversified energy sources. Models for the North Sea reveal the potential of hybrid systems to enhance energy production and storage, emphasizing grid expansions, electricity storage, and hydrogen production as key measures for meeting carbon reduction goals [48, 47]. Exploring synergies between offshore oil and gas sectors and renewable energy can further support a sustainable, low-carbon energy future by 2050.

Research into hybrid systems and their integration with biomass gasification technologies is crucial for advancing sustainable energy production. Biomass, as a renewable energy source, holds potential to meet a significant portion of primary energy consumption by 2050. By exploring synergies between hybrid systems and biomass conversion technologies, innovative solutions to energy challenges can be identified, promoting rural development and energy security. However, commercialization faces challenges such as high operational costs, necessitating ongoing exploration and innovation [1, 17]. Leveraging the strengths of diverse renewable technologies and optimizing their integration is essential for supporting the global transition to a low-carbon economy.

10.2 Hybrid Systems and Their Potential

Hybrid systems that integrate biomass gasification with renewable energy technologies such as solar and wind offer a promising approach to enhance energy efficiency and sustainability. These systems can mitigate greenhouse gas emissions and significantly reduce fossil fuel dependence, optimizing resource utilization and supporting a transition to sustainable energy solutions [1, 12, 17, 3, 4].

Energy system models for regions like the North Sea demonstrate the potential of hybrid systems to optimize energy generation and storage capacities. These models are crucial for assessing vRES integration and identifying key measures such as grid expansions, electricity storage, and hydrogen production that balance supply and demand while reducing emissions and costs. The North Sea's offshore wind development targets and the synergy between offshore energy and hydrogen production aim to enhance energy infrastructure and support Europe's broader decarbonization goals [47, 64, 60, 48, 37]. These models highlight the importance of integrating diverse renewable energy systems to enhance overall energy efficiency and sustainability.

The synergy between biomass gasification and renewable energy sources such as solar and wind can lead to significant cost savings and emission reductions, supporting the transition to a low-carbon energy economy. By optimizing resource utilization and enhancing energy system resilience, hybrid systems can provide significant operational cost savings and increased revenues [1, 12, 17, 3, 4].

Innovative gasification technologies, combined with the strategic integration of renewable sources, can greatly improve hydrogen production's economic feasibility and environmental sustainability. Flexible hydrogen production methods, such as those using renewable energy for electrolysis, can manage supply and demand fluctuations, facilitating vRES integration while reducing carbon emissions. Studies highlight the potential for significant cost savings and increased revenues through optimized hydrogen supply chains and energy storage solutions [69, 56, 59, 36, 37].

10.3 Economic and Operational Impacts

The integration of biomass gasification with renewable energy systems presents both economic and operational opportunities and challenges crucial for the feasibility and scalability of hydrogen production. While transitioning to green hydrogen offers substantial environmental benefits, significant capital investments are required for renewable energy infrastructure and advanced gasification technologies. For instance, the European Commission's stringent criteria for electrolysis production could elevate hydrogen costs significantly, necessitating new renewable energy installations. Financial risks associated with green hydrogen projects also pose challenges, requiring flexible asset investments and energy hedging strategies. Despite these hurdles, green hydrogen has the potential to decarbonize various sectors and enhance energy system flexibility [56, 13, 61, 67, 36].

The levelized cost of hydrogen (LCOH) is a primary economic consideration, influenced by factors like feedstock costs and process efficiency [11]. Models such as the Hydrogen Production System Model (HPSM) can optimize production costs by considering local conditions and investment risks [11]. Feature-driven trading models for hybrid power plants further enhance economic viability by optimizing the coordination of multiple electrolysis modules, reducing operational costs [8].

Biomass gasification's economic viability hinges on the availability and sustainability of feedstocks. Advanced biomass conversion technologies, like catalytic upgrading of hydrothermal liquefaction products, can improve economic viability by enhancing efficiency and product quality [24]. Optimizing biomass supply chain logistics through strategies like two-phase stochastic programming can yield cost savings for combined heat and power (CHP) operators [16].

Operational considerations, including strategic energy infrastructure development to support the hydrogen economy, are crucial for effectively integrating biomass gasification with renewable energy. Establishing green hydrogen hubs and optimizing Power-to-X (PtX) systems that utilize local renewable energy sources and carbon recovery from biogas plants are essential for enhancing energy systems' efficiency and cost-effectiveness, supporting the transition to a low-carbon economy [38, 60]. Addressing data and model gaps for hydrogen production processes is critical for assessing economic viability and ensuring competitiveness in the global energy market.

11 Challenges and Future Directions

The exploration of challenges and future directions in biomass gasification for hydrogen production reveals a complex landscape marked by technical, economic, and environmental considerations. As the demand for sustainable energy solutions intensifies, it is imperative to address these multifaceted challenges to unlock the full potential of biomass gasification. This section will delve into the specific technical challenges associated with biomass gasification, including feedstock variability and gasifier design, as well as the optimization of process parameters to enhance efficiency and syngas yield. Understanding these challenges is crucial for advancing biomass gasification technologies and ensuring their viability as a cornerstone of the renewable energy sector.

11.1 Technical Challenges in Biomass Gasification

The technical challenges inherent in biomass gasification are multifaceted, encompassing issues related to the variability of feedstock characteristics, gasifier design, and the optimization of process parameters. A primary challenge is the intrinsic heterogeneity of biomass feedstocks, which varies in moisture content, energy density, and composition. These variations can significantly affect the efficiency and consistency of the gasification process . The complex nature of lignocellulosic biomass, for example, complicates uniform conversion rates, necessitating the development of advanced processing techniques and robust system designs to accommodate a wide range of feedstock properties [3].

In addressing these challenges, the optimization of gasification process parameters is crucial for enhancing efficiency and syngas yield. Recent studies have demonstrated the potential of multifidelity Bayesian optimization techniques, which integrate high and low-fidelity models to improve the exploration of the parameter space and enhance the efficiency of biomass gasification processes . These techniques enable the optimization of critical process parameters, such as temperature, pressure, and gasifying agent composition, leading to increased syngas yield and improved process efficiency [34].

The design and operation of gasifiers also present significant technical challenges. Fixed-bed gasifiers, for instance, are known for their simplicity but may suffer from lower efficiency and higher tar production [1]. In contrast, fluidized-bed gasifiers offer improved heat and mass transfer rates, enhancing the efficiency and syngas yield of the gasification process [40]. The development of advanced gasifier designs, such as fluidized-bed gasifiers, is essential for overcoming these technical challenges and enhancing the efficiency and sustainability of biomass gasification processes [34].

The integration of renewable energy sources, such as solar and wind power, with gasification processes can also address some of the technical challenges associated with biomass gasification. These integrations can enhance energy efficiency and sustainability by providing the necessary heat for gasification processes and reducing reliance on fossil fuels . Comprehensive energy system models developed for regions such as the North Sea have illustrated the significant potential for integrating gasification technology with renewable energy systems, emphasizing the critical role this integration plays in enhancing renewable energy strategies. Specifically, these models highlight that combining grid expansions, electricity storage, and hydrogen production can lead to substantial reductions in emissions and energy costs, thereby supporting ambitious targets for offshore wind development and the transition to a low-carbon energy future. [64, 48, 60, 47]

Catalyst deactivation remains a significant technical challenge in biomass gasification, as the dynamic nature of the gasification environment can lead to issues such as sintering, poisoning, and coking [52]. The loss of catalytic activity, for example, after the reduction of Cu catalysts, can hinder the efficiency of the gasification process, necessitating the development of robust catalysts that can withstand harsh operating conditions, including high temperatures and the presence of impurities in biomass feedstocks [29].

The integration of hydrogen production into existing energy systems poses significant infrastructural and investment challenges, particularly due to the need for retrofitting natural gas networks to accommodate hydrogen transport, as highlighted by studies analyzing the European power system and Great Britain's energy decarbonization pathways. These studies reveal that while electrifying hydrogen production can enhance renewable energy investment and reduce CO emissions, it also introduces uncertainties regarding the optimal allocation of resources and infrastructure development across

various sectors such as heating, industry, and transport. Consequently, prioritizing the establishment of green hydrogen hubs and developing flexible supply and demand models is essential for effectively addressing these challenges and achieving long-term decarbonization goals. [37, 60]. A substantial development of energy infrastructure is required to support the burgeoning hydrogen economy. The lack of comprehensive data and models for hydrogen production costs, as well as the variability of renewable energy sources, necessitates strategic planning and investment. Models like the HPSM can help optimize hydrogen production by accounting for these variables .

11.2 Economic and Scalability Issues

The economic feasibility and scalability of biomass gasification for hydrogen production are pivotal considerations in its deployment as a sustainable energy solution. A significant economic challenge in this domain is the elevated levelized cost of hydrogen (LCOH), which is influenced by various factors including feedstock costs, process efficiency, and country-specific investment risks [11]. High capital costs associated with the development of advanced gasification technologies and the necessary infrastructure for hydrogen production further compound these economic challenges .

One of the key strategies to address these economic challenges involves the optimization of gasification processes to enhance efficiency and reduce costs. Multifidelity Bayesian optimization techniques, which integrate high and low-fidelity models, have been shown to significantly enhance the efficiency of biomass gasification processes by optimizing process parameters and maximizing syngas yield . These advanced optimization techniques facilitate a thorough examination of the parameter space, thereby enhancing process efficiency and cost-effectiveness by enabling the identification of optimal feedstock blends, operational conditions, and pretreatment methods that significantly improve the performance of biorefinery processes and catalyst development. [35, 45, 70, 71]

Scalability is another critical issue that must be addressed for the successful deployment of biomass gasification technologies. The scalability of these technologies is influenced by the availability and sustainability of biomass feedstocks, which are closely linked to agricultural and forestry activities [1]. The variability of biomass feedstock characteristics, such as moisture content, energy density, and composition, poses significant challenges for the consistent and efficient operation of gasification processes . To address these challenges, advanced processing techniques and robust system designs are essential to accommodate a wide range of feedstock properties.

The integration of biomass gasification with other renewable energy sources, such as solar and wind power, offers significant potential for enhancing the scalability and economic viability of hydrogen production. Hybrid systems that combine multiple renewable energy technologies can optimize energy generation and storage capacities, reducing dependency on fossil fuels and promoting energy security [1]. Comprehensive energy system models, such as those developed for regions like the North Sea, have demonstrated the potential of hybrid systems in optimizing energy production and storage capacities, highlighting their role in advancing renewable energy strategies .

The transition to a hydrogen economy necessitates substantial investments in energy infrastructure, including the development of hydrogen production facilities, storage systems, and distribution networks [66]. The lack of comprehensive data and models for hydrogen production costs, particularly for non-conventional methods like direct seawater electrolysis, presents challenges in accurately assessing their economic viability . Addressing these uncertainties through the development of robust models and data collection efforts is essential for optimizing hydrogen production processes and ensuring the competitiveness of hydrogen production in the global energy market .

11.3 Environmental and Sustainability Concerns

The implementation of biomass gasification for hydrogen production, while promising for sustainable energy, must address several environmental and sustainability concerns to ensure its long-term viability. A significant environmental concern associated with the gasification process is the potential release of greenhouse gases (GHGs) and various pollutants, including particulate matter and volatile organic compounds. This is particularly relevant as the production of renewable natural gas (RNG) from biomass can contribute to both emissions and the need for effective carbon capture and sequestration (CCS) strategies. In California, for instance, leveraging existing biomass residues for RNG production could enable the capture and sequestration of approximately 2.9 million metric tons of CO annually, highlighting the dual challenge of mitigating emissions while maximizing resource

23

utilization in the context of stringent climate policies. [17, 23, 65, 4]. These emissions can contribute to air pollution and exacerbate climate change, underscoring the need for advanced gasification technologies and robust emission control strategies .

Biomass feedstock production and utilization also raise sustainability concerns, particularly regarding land use. The cultivation of energy crops must be carefully managed to prevent adverse environmental impacts, such as deforestation, biodiversity loss, and competition with food production . Sustainable land management practices and policies are essential to ensure that biomass utilization aligns with environmental and food security goals [1].

The advancement of sophisticated biomass conversion technologies, particularly hydrothermal lique-faction (HTL) and co-pyrolysis, is essential for effectively addressing pressing environmental and sustainability challenges. HTL, for instance, is gaining recognition for its ability to convert a diverse range of biomass feedstocks—including wet and dry organic materials—into valuable liquid biofuels. This process not only enhances the flexibility of biomass utilization but also facilitates the production of high-quality biocrudes with varying properties, which can lead to significant reductions in harmful heteroatoms when subjected to catalytic upgrading. As the global energy landscape increasingly shifts towards renewable sources, the potential of biomass is projected to expand substantially, making these advanced conversion methods pivotal in promoting sustainable energy solutions and reducing reliance on fossil fuels. [72, 24, 3, 4]. These technologies enhance the efficiency of biomass conversion processes and reduce environmental impacts by enabling the conversion of both dry and wet biomass into valuable energy products, contributing to the circular economy and the reduction of greenhouse gas emissions .

Moreover, the integration of biomass gasification with other renewable energy systems, such as solar and wind power, can further enhance the sustainability of energy production by reducing reliance on fossil fuels and promoting the use of renewable energy sources . Comprehensive energy system models, particularly those tailored for regions like the North Sea, have underscored the significant advantages of integrating biomass gasification with renewable energy systems. These models reveal that such integration is pivotal for enhancing renewable energy strategies, as it facilitates a more balanced energy system by optimizing grid expansions, electricity storage, and low-carbon hydrogen production. The North Sea, with its ambitious targets for offshore wind and innovative synergies between the oil and gas and renewable sectors, serves as a prime example of how these integration measures can lead to substantial reductions in both emissions and energy costs while supporting the transition to a sustainable energy future. [48, 47]

11.4 Future Directions and Research Opportunities

The advancement of biomass gasification for hydrogen production presents a promising avenue for the sustainable energy sector, contingent upon addressing several technical, economic, and environmental challenges. A significant technical challenge in biomass gasification is the inherent variability of biomass feedstock characteristics, including moisture content, energy density, and composition. These factors can lead to inconsistent feedstock flow, affecting both the efficiency and reliability of the gasification process. For instance, variations in moisture levels and particle size can disrupt the continuous feeding of biomass to the reactor, resulting in decreased operational efficiency and increased costs. Advanced process control methods, such as hybrid process control (HPC) and stochastic optimization models, have been developed to mitigate these issues by ensuring a more stable feedstock supply and optimizing reactor operations. Such approaches can enhance throughput and reduce variability, ultimately improving the overall performance of biorefineries. [71, 3, 39, 73, 34]. To address this, future research should focus on developing advanced processing techniques and robust system designs capable of accommodating diverse feedstock properties.

Advancements in gasification technology, particularly through the application of multifidelity Bayesian optimization techniques, offer a promising solution to enhance the efficiency of biomass gasification processes. By employing a combination of high-fidelity computational fluid dynamics (CFD) models and low-fidelity ideal-mixing models, these optimization techniques can effectively fine-tune essential process parameters—including temperature, pressure, and gasifying agent composition—ultimately leading to enhanced syngas yield and improved overall process efficiency. This multi-fidelity Bayesian optimization approach not only addresses the high computational costs associated with CFD models but also leverages real-world fermentation data to maximize gas conversion rates in industrial-scale bioreactors. [45, 70, 42, 40]. Further research should aim to refine these

24

optimization models to incorporate more complex scenarios and additional data, thereby enhancing their robustness and applicability .

Economic and scalability issues remain significant barriers to the broader adoption of biomass gasification for hydrogen production. The high levelized cost of hydrogen (LCOH) is influenced by factors such as feedstock costs, process efficiency, and country-specific investment risks [11]. Addressing these challenges will require strategic investments in advanced gasification technologies and infrastructure to enhance production efficiency and reduce costs . Future research should focus on refining models to account for land and water availability, as well as integrating more localized weather data to improve the accuracy of LCOH estimations [11].

The exploration of hybrid systems that integrate biomass gasification with other renewable energy technologies, such as solar and wind power, offers substantial potential for enhancing energy production efficiency and sustainability. These systems leverage the complementary strengths of different renewable energy sources to optimize energy generation and storage capacities, supporting the global transition to a low-carbon energy future . "To fully harness the potential of hybrid systems in facilitating the transition to a sustainable energy economy, it is crucial to prioritize ongoing research and development, alongside strategic investments in renewable energy infrastructure. This includes enhancing grid capacity, integrating electricity storage solutions, and developing low-carbon hydrogen production capabilities. Such measures will not only reduce emissions and energy system costs but also improve demand flexibility across various sectors, ultimately enabling a more resilient and efficient energy system." [17, 47, 36, 60, 48]

In addition to technical and economic challenges, environmental and sustainability concerns must also be addressed to ensure the long-term viability of biomass gasification for hydrogen production. The use of land for energy crops must be balanced against food production and biodiversity conservation, and sustainable land management practices are essential to mitigate environmental impacts . The advancement of biomass conversion technologies, particularly the catalytic upgrading of hydrothermal liquefaction (HTL) products, significantly enhances the sustainability of biomass energy production by improving conversion efficiency and minimizing environmental impacts. HTL, with its ability to process a diverse range of feedstocks—including wet residual biomass—offers a flexible approach to biomass conversion. This technology, when combined with catalytic hydrotreating, effectively transforms biocrudes into valuable biofuels. For instance, sewage sludge biocrude can yield straight-chain hydrocarbons suitable for diesel, while algal biocrude presents challenges in complete denitrogenation. Additionally, upgraded biocrudes from lignocellulosic sources, such as miscanthus, demonstrate high gasoline-range yields with notable aromatic content. Operating under optimized conditions, such as elevated hydrogen pressure, is crucial for mitigating issues like coking and decarboxylation, thereby enhancing the overall efficiency and sustainability of biomass-derived energy solutions. [3, 24]

Moreover, the development of low-cost, energy-efficient catalysts is crucial for the economic viability of biomass gasification processes. Traditional catalysts often rely on precious metals, which are expensive and limited in availability, posing significant challenges for large-scale applications [28]. The integration of machine learning techniques with catalyst discovery processes, such as the catlas framework, can facilitate the identification of optimal catalysts, improving the efficiency of hydrogen production processes .

11.5   Economic and Scalability Issues

The economic and scalability issues associated with biomass gasification for hydrogen production are significant challenges that must be addressed to ensure the feasibility and widespread adoption of this technology as a sustainable energy solution. One of the primary economic challenges is the high levelized cost of hydrogen (LCOH), which is influenced by various factors, including feedstock costs, process efficiency, and country-specific investment risks [11]. Addressing these challenges requires strategic planning and investment in advanced gasification technologies and infrastructure to enhance production efficiency and reduce costs [1].

The development of advanced gasifier designs, such as fluidized-bed gasifiers, can enhance the efficiency and sustainability of biomass gasification processes by improving heat and mass transfer rates and reducing operational costs . The implementation of multifidelity Bayesian optimization

25

techniques, which integrate high and low-fidelity models, can further enhance the efficiency of biomass gasification processes by optimizing process parameters and maximizing syngas yield [40].

In addition to process optimization, the economic viability of biomass gasification is influenced by the availability and sustainability of biomass feedstocks, which are critical factors in determining the long-term viability of biomass as a renewable energy resource [1]. The development of advanced biomass conversion technologies, such as catalytic upgrading of hydrothermal liquefaction products, can enhance the economic viability of biomass gasification by improving efficiency and product quality [24]. Furthermore, the optimization of biomass supply chain logistics, through approaches such as two-phase stochastic programming, can enhance the efficiency of biomass supply chain management and contribute to cost savings for combined heat and power (CHP) operators [16].

The integration of biomass gasification with other renewable energy sources, such as solar and wind power, offers significant potential for enhancing the scalability and economic viability of hydrogen production. Hybrid systems that combine multiple renewable energy technologies can optimize energy generation and storage capacities, reducing dependency on fossil fuels and promoting energy security [1]. Comprehensive energy system models, such as those developed for regions like the North Sea, have demonstrated the potential of hybrid systems in optimizing energy production and storage capacities, highlighting their role in advancing renewable energy strategies .

The transition to a hydrogen economy necessitates substantial investments in energy infrastructure, including the development of hydrogen production facilities, storage systems, and distribution networks [66]. The lack of comprehensive data and models for hydrogen production costs, particularly for non-conventional methods like direct seawater electrolysis, presents challenges in accurately assessing their economic viability . Addressing these uncertainties through the development of robust models and data collection efforts is essential for optimizing hydrogen production processes and ensuring the competitiveness of hydrogen production in the global energy market .

11.6   Environmental and Sustainability Concerns

"Biomass gasification presents a promising avenue for sustainable hydrogen production, but to establish its viability as a renewable energy solution, it must effectively address various environmental and sustainability challenges, such as the need for efficient biomass conversion methods and the reduction of greenhouse gas emissions associated with traditional fossil fuels. With biomass currently contributing to 10

The sustainability of biomass production is another critical concern, as the use of land for energy crops must be balanced against food production and biodiversity conservation . Unsustainable land use practices, such as deforestation and monoculture plantations, can lead to environmental degradation, loss of biodiversity, and competition with food production [1]. Therefore, sustainable land management practices and policies are essential to ensure that biomass utilization aligns with environmental and food security goals.

The development of advanced biomass conversion technologies, such as hydrothermal liquefaction (HTL) and co-pyrolysis, can enhance the sustainability of biomass energy production by improving efficiency and reducing environmental impacts . These technologies allow for the conversion of both dry and wet biomass into valuable energy products, contributing to the circular economy and the reduction of greenhouse gas emissions [1].

The integration of biomass gasification into existing energy systems also presents sustainability challenges, particularly in terms of land use and resource management. Unsustainable land use practices, such as deforestation and monoculture plantations, can lead to environmental degradation, loss of biodiversity, and competition with food production [1]. Sustainable land management practices and policies are essential to ensure that biomass utilization does not compromise environmental or food security goals [23].

The exploration of direct seawater electrolysis as a potential technology for hydrogen production highlights the need for sustainable and economically viable methods, as conventional approaches often rely on high-purity water [10]. Addressing these challenges through technological innovation and strategic investments is crucial for advancing the sustainability of biomass gasification and its integration into existing energy systems, ultimately contributing to global efforts to mitigate climate change and promote sustainable energy production .

11.7   Future Directions and Research Opportunities

The future of biomass gasification for hydrogen production is promising, yet it hinges on addressing a range of technical, economic, and environmental challenges. One of the primary technical challenges is the inherent variability of biomass feedstock characteristics, such as moisture content, energy density, and composition, which can significantly impact the efficiency and consistency of the gasification process . Addressing this challenge necessitates ongoing research to develop advanced processing techniques and robust system designs that can accommodate a wide range of feedstock properties [3].

Innovative advancements in gasification technology, such as multifidelity Bayesian optimization techniques, have shown promise in enhancing the efficiency of biomass gasification processes by integrating high and low-fidelity models to optimize process parameters and improve syngas yield . The development of advanced gasifier designs, such as fluidized-bed gasifiers, can further enhance the efficiency and sustainability of biomass gasification processes [34].

Economic challenges, such as the high levelized cost of hydrogen (LCOH) and country-specific investment risks, pose significant barriers to the scalability of biomass gasification technologies [11]. To address these challenges, continued research and development of cost-effective biomass conversion technologies, such as catalytic processes that enhance the efficiency of biomass conversion, is essential . The optimization of transportation delivery schedules and inventory management through feature-driven trading models can further enhance the economic viability of biomass gasification processes [18].

In addition to technical and economic challenges, environmental and sustainability concerns must also be addressed to ensure the long-term viability of biomass gasification for hydrogen production. The allocation of land for energy crops must be carefully balanced with the need for food production and the conservation of biodiversity; implementing sustainable land management practices is crucial to mitigate the environmental impacts associated with biomass energy production. This is particularly important given the potential constraints of biomass energy usage, such as land use competition and carbon leakage, which can undermine its benefits for reducing CO_2 emissions and promoting economic growth. Therefore, policymakers must consider these factors to ensure that biomass energy serves as an effective tool for sustainable development while minimizing adverse effects on ecosystems and food security. [17, 12, 65, 4]. The development of advanced biomass conversion technologies, such as hydrothermal liquefaction (HTL) and co-pyrolysis, can enhance the sustainability of biomass energy production by improving efficiency and reducing environmental impacts .

Moreover, the exploration of hybrid systems that integrate biomass gasification with other renewable energy technologies, such as solar and wind power, offers substantial potential for enhancing energy production efficiency and sustainability. By leveraging the complementary strengths of different renewable energy sources and optimizing their integration, hybrid systems can significantly contribute to the global transition towards a low-carbon energy future . Future research should focus on refining the ontology and enhancing the dynamic capabilities of cost modeling components to better inform funding decisions and identify research opportunities [46].

The development of low-cost, energy-efficient catalysts is also crucial for the economic viability of biomass gasification processes. Traditional catalysts often rely on precious metals, which are expensive and limited in availability, posing significant challenges for large-scale applications [28]. Future research should focus on exploring new materials and methods for surface overcoating, with an emphasis on scalability and the integration of advanced characterization techniques [14]. Additionally, the exploration of more complex chalcogenide compositions as viable electrocatalysts for efficient water splitting is an ongoing area of research [15].

The exploration of direct seawater electrolysis as a potential technology for hydrogen production highlights the need for sustainable and economically viable methods, as conventional approaches often rely on high-purity water [10]. Future research should focus on developing low-cost, energy-efficient methods for direct seawater electrolysis, addressing the challenges associated with the reliance on high-purity water in conventional electrolysis processes . By addressing these multifaceted challenges through technological innovation and strategic investments, the full potential of hydrogen as a cornerstone of a sustainable energy future can be realized .

12 Conclusion

Biomass gasification emerges as a transformative process in the renewable energy landscape, offering a viable pathway to reduce carbon emissions and transition away from fossil fuels. By converting organic materials into hydrogen-rich syngas, this technology supports the shift towards sustainable energy solutions and aligns with global decarbonization goals. Its integration into hydrogen production systems is pivotal, utilizing renewable resources to produce hydrogen, a key component of a low-carbon economy.

The survey identifies several challenges and opportunities in the realm of biomass gasification for hydrogen production. These encompass technical, economic, and environmental aspects, with advancements in gasification technologies and catalyst development being crucial for enhancing process efficiency and sustainability. Overcoming issues related to feedstock variability, gasifier design, and process optimization is essential to fully harness biomass gasification's potential as a sustainable energy source.

The synergy between biomass gasification and other renewable energy systems, such as solar and wind, provides significant opportunities for collaboration, enhancing overall energy production efficiency and sustainability. Hybrid systems that combine biomass gasification with other renewable technologies can optimize energy generation and storage, reducing dependency on fossil fuels and strengthening energy security.

Strategic planning and investment in energy infrastructure are imperative to advance the hydrogen economy. Developing comprehensive models for hydrogen production costs and optimizing logistics are vital for enhancing the economic viability of hydrogen production and utilization. Exploring direct seawater electrolysis underscores the importance of sustainable methods to overcome the challenges associated with traditional electrolysis processes.

A holistic approach that combines hydrogen electrification with infrastructure retrofitting is crucial for achieving long-term emissions reduction targets, as emphasized by the European Union's energy transition objectives. The potential for significant cost savings through the integration of biomass gasification with other renewable systems, particularly in regions like the North Sea, underscores the importance of hybrid systems in advancing renewable energy strategies.

References

[1] Azwifunimunwe Tshikovhi and Tshwafo Ellias Motaung. Technologies and innovations for biomass energy production. *Sustainability*, 15(16):12121, 2023.

[2] Sleiman Farah, Neeraj Bokde, and Gorm Bruun Andresen. Cost and co2 emissions co-optimisation of green hydrogen production in a grid-connected renewable energy system, 2024.

[3] Koray Alper, Kubilay Tekin, Selhan Karagöz, and Arthur J Ragauskas. Sustainable energy and fuels from biomass: a review focusing on hydrothermal biomass processing. *Sustainable Energy & Fuels*, 4(9):4390–4414, 2020.

[4] Antonio Tursi. A review on biomass: importance, chemistry, classification, and conversion. *Biofuel Research Journal*, 6(2):962–979, 2019.

[5] Furkan Isikgor and C. Remzi Becer. Lignocellulosic biomass: a sustainable platform for the production of bio-based chemicals and polymers, 2016.

[6] Tehua Wang, Li Tao, Xiaorong Zhu, Chen Chen, Wei Chen, Shiqian Du, Yangyang Zhou, Bo Zhou, Dongdong Wang, Chao Xie, et al. Combined anodic and cathodic hydrogen production from aldehyde oxidation and hydrogen evolution reaction. *Nature catalysis*, 5(1):66–73, 2022.

[7] M Bianchini, N Alayo, L Soler, M Salleras, L Fonseca, J Llorca, and A Tarancon. A pd/al2o3-based micro-reformer unit fully integrated in silicon technology for h-rich gas production, 2021.

[8] Vincent Henkel, Maximilian Kilthau, Felix Gehlhoff, Lukas Wagner, and Alexander Fay. Cost optimized scheduling in modular electrolysis plants, 2024.

[9] Sebastiano Bellani, Maria Rosa Antognazza, and Francesco Bonaccorso. Carbon-based photo-cathode materials for solar hydrogen production, 2019.

[10] MA Khan, Tareq Al-Attas, Soumyabrata Roy, Muhammad M Rahman, Noreddine Ghaffour, Venkataraman Thangadurai, Stephen Larter, Jinguang Hu, Pulickel M Ajayan, and Md Golam Kibria. Seawater electrolysis for hydrogen production: a solution looking for a problem? *Energy & Environmental Science*, 14(9):4831–4839, 2021.

[11] Stephan Kigle, Tapio Schmidt-Achert, and Miguel Ángel Martínez Pérez. Modeling global levelized cost of hydrogen production considering country-specific investment risks, 2023.

[12] Faik Bilgili, Emrah Koçak, Ümit Bulut, and Sevda Kuşkaya. Can biomass energy be an efficient policy tool for sustainable development? *Renewable and Sustainable Energy Reviews*, 71:830–845, 2017.

[13] Koen van Greevenbroek, Johannes Schmidt, Marianne Zeyringer, and Alexander Horsch. Little to lose: the case for a robust european green hydrogen strategy, 2024.

[14] Qiang Liu, Marco Ranocchiari, and Jeroen A van Bokhoven. Catalyst overcoating engineering towards high-performance electrocatalysis. *Chemical Society Reviews*, 51(1):188–236, 2022.

[15] Suresh Chandra Baral, Dilip Sasmal, Mitali Hupele, Sradhanjali Lenka, and Somaditya Sen. Recent advances in hydrogen production using sulfide-based photocatalysts, 2024.

[16] Ignacio Blanco, Daniela Guericke, Juan M. Morales, and Henrik Madsen. A two-phase stochastic programming approach to biomass supply planning for combined heat and power plants, 2018.

[17] Regina Tuganova, Anna Permyakova, Anna Kuznetsova, Karina Rakhmanova, Natalia Monzul, Roman Uvarov, Elizaveta Kovtun, and Semen Budennyy. Relationships between patenting trends and research activity for green energy technologies, 2022.

[18] Umur Hasturk, Albert H. Schrotenboer, Evrim Ursavas, and Kees Jan Roodbergen. Stochastic cyclic inventory routing with supply uncertainty: A case in green-hydrogen logistics, 2023.

[19] Dana Kirchem and Wolf-Peter Schill. Power sector effects of green hydrogen production in germany, 2023.

[20] Mahmoud M. Ramadan, Yuanchen Wang, and Pragya Tooteja. Analysis of hydrogen production costs across the united states and over the next 30 years, 2022.

[21] Nhat Truong Nguyen, Marco Altomare, JeongEun Yoo, Nicola Taccardi, and Patrik Schmuki. Noble metals on anodic tio2 nanotubes mouths: Thermal dewetting of minimal pt co-catalyst loading leads to significantly enhanced photocatalytic h2 generation, 2016.

[22] Maximilian Stargardt, David Kress, Heidi Heinrichs, Jörn-Christian Meyer, Jochen Linßen, Grit Walther, and Detlef Stolten. Global shipyard capacities limiting the ramp-up of global hydrogen transport, 2024.

[23] Jun Wong, Jonathan Santoso, Marjorie Went, and Daniel Sanchez. Market potential for co_2 removal and sequestration from renewable natural gas production in california, 2021.

[24] Daniele Castello, Muhammad Salman Haider, and Lasse Aistrup Rosendahl. Catalytic upgrading of hydrothermal liquefaction biocrudes: Different challenges for different feedstocks, 2019.

[25] Hossein Shahbeik, Alireza Shafizadeh, Mohammad Hossein Nadian, Dorsa Jeddi, Seyedali Mirjalili, Yadong Yang, Su Shiung Lam, Junting Pan, Meisam Tabatabaei, and Mortaza Aghbashlo. Using evolutionary machine learning to characterize and optimize co-pyrolysis of biomass feedstocks and polymeric wastes, 2023.

[26] Zhiwei Jiang, Yongjian Zeng, Ruichao Guo, Lu Lin, Rafael Luque, and Kai Yan. Recent advances on co2-assisted synthesis of metal nanoparticles for the upgrading of biomass-derived compounds, 2024.

[27] Benard Tabu, Visal Veng, Heba Morgan, Shubhra Kanti Das, Eric Brack, Todd Alexander, J. Hunter Mack, Hsi-Wu Wong, and Juan Pablo Trelles. Hydrogen from cellulose and low-density polyethylene via atmospheric pressure nonthermal plasma, 2023.

[28] Raghottam M. Sattigeri, Prafulla K. Jha, Piotr Śpiewak, , and Krzysztof J. Kurzydłowski. Two dimensional limgas; a novel topological quantum catalyst for hydrogen evolution reaction, 2022.

[29] Amanda Laca, Adriana Laca, and Mario Díaz. Eggshell waste as catalyst: A review. *Journal of environmental management*, 197:351–359, 2017.

[30] Massiagbe Diabate, Timothy Vriend, Harish S Krishnamoorthy, and Jian Shi. Hydrogen and battery based energy storage system (ess) for future dc microgrids, 2024.

[31] Brook Wander, Kirby Broderick, and Zachary W. Ulissi. Catlas: an automated framework for catalyst discovery demonstrated for direct syngas conversion, 2022.

[32] Vincent Wing hei Lau, Igor Moudrakovski, Tiago Botari, Simon Weinburger, Maria B. Mesch, Viola Duppel, Jürgen Senker, Volker Blum, and Bettina V. Lotsch. Towards rational design of carbon nitride photocatalysts: Identification of cyanamide "defects" as catalytically relevant sites, 2016.

[33] Yue Jiang, Cui Ying Toe, Sajjad S. Mofarah, Claudio Cazorla, Shery L. Y. Chang, Yanting Yin, Qi Zhang, Sean Lim, Yin Yao, Ruoming Tian, Yuan Wang, Tasmia Zaman, Hamidreza Arandiyan, Gunther G. Andersson, Jason Scott, Pramod Koshy, Danyang Wang, and Charles C. Sorrell. Direct hydrogen production from water/seawater by irradiation/vibration-activated using defective ferroelectric batio3-x nanoparticles, 2022.

[34] Abbas Alpaslan Kocer, Yunus Emre Yuksel, and Murat Ozturk. Investigation of a biomass gasification system based on energy and exergy analysis, 2022.

[35] Paul Seurin, Olusola Olabanjo, Joseph Wiggins, Lorien Pratt, Loveneesh Rana, Rozhin Yasaei, and Gregory Renard. H2-golden-retriever: Methodology and tool for an evidence-based hydrogen research grantsmanship, 2022.

[36] Fabian Stockl, Wolf-Peter Schill, and Alexander Zerrahn. Optimal supply chains and power sector benefits of green hydrogen, 2021.

[37] Germán Morales-España, Ricardo Hernández-Serna, Diego A. Tejada-Arango, and Marcel Weeda. Impact of large-scale hydrogen electrification and retrofitting of natural gas infrastructure on the european power system, 2023.

[38] Alberto Alamia, Behzad Partoon, Eoghan Rattigan, and Gorm Brunn Andresen. Optimizing hydrogen and e-methanol production through power-to-x integration in biogas plants, 2024.

[39] Fikri Kucuksayacigil, Mohammad Roni, Sandra D. Eksioglu, and Qiushi Chen. Optimal control to handle variations in biomass feedstock characteristics and reactor in-feed rate, 2021.

[40] Mahdi Eskandari, Lars Puiman, and Jakob Zeitler. Multi-fidelity bayesian optimisation of syngas fermentation simulators, 2023.

[41] Alissa Ganter, Paolo Gabrielli, Hanne Goericke, and Giovanni Sansavini. Minimum-regret hydrogen supply chain strategies to foster the energy transition of european hard-to-abate industries, 2024.

[42] Alireza Shafizadeh, Hossein Shahbeik, Mohammad Hossein Nadian, Vijai Kumar Gupta, Abdul-Sattar Nizami, Su Shiung Lam, Wanxi Peng, Junting Pan, Meisam Tabatabaei, and Mortaza Aghbashlo. Turning hazardous volatile matter compounds into fuel by catalytic steam reforming: An evolutionary machine learning approach, 2023.

[43] Nongnuch Artrith, Zhexi Lin, and Jingguang G. Chen. Predicting the activity and selectivity of bimetallic metal catalysts for ethanol reforming using machine learning, 2020.

[44] Lowik Chanussot, Abhishek Das, Siddharth Goyal, Thibaut Lavril, Muhammed Shuaibi, Morgane Riviere, Kevin Tran, Javier Heras-Domingo, Caleb Ho, Weihua Hu, Aini Palizhati, Anuroop Sriram, Brandon Wood, Junwoong Yoon, Devi Parikh, C. Lawrence Zitnick, and Zachary Ulissi. The open catalyst 2020 (oc20) dataset and community challenges, 2021.

[45] Nung Siong Lai, Yi Shen Tew, Xialin Zhong, Jun Yin, Jiali Li, Binhang Yan, and Xiaonan Wang. An artificial intelligence (ai) workflow for catalyst design and optimization, 2024.

[46] Lowik Chanussot, Abhishek Das, Siddharth Goyal, Thibaut Lavril, Muhammed Shuaibi, Morgane Riviere, Kevin Tran, Javier Heras-Domingo, Caleb Ho, Weihua Hu, et al. Open catalyst 2020 (oc20) dataset and community challenges. *Acs Catalysis*, 11(10):6059–6072, 2021.

[47] Matteo DAndrea, Mario Garzon Gonzalez, and Russell McKenna. Synergies in offshore energy: a roadmap for the danish sector, 2021.

[48] Jan F. Wiegner, Madeleine Gibescu, and Matteo Gazzani. Unleashing the full potential of the north sea – identifying key energy infrastructure synergies for 2030 and 2040, 2024.

[49] Nicolas Abdel Karim Aramouni, Jad G Touma, Belal Abu Tarboush, Joseph Zeaiter, and Mohammad N Ahmad. Catalyst design for dry reforming of methane: Analysis review. *Renewable and sustainable energy reviews*, 82:2570–2585, 2018.

[50] M. V. Jyothirmai, D. Roshini, B. Moses Abraham, and Jayant K. Singh. Accelerating the discovery of g-c_3n_4-supported single atom catalysts for hydrogen evolution reaction: A combined dft and machine learning strategy, 2022.

[51] Thanh Tam Nguyen and Kaveh Edalati. Efficient photocatalytic hydrogen production on defective and strained black bismuth (iii) oxide, 2024.

[52] Landon Schofield, Benjamin Paren, Ruaridh Macdonald, Yang Shao-Horn, and Dharik Mallapragada. Dynamic optimization of proton exchange membrane water electrolyzers considering usage-based degradation, 2024.

[53] M. Bianchini, N. Alayo, L. Soler, M. Salleras, L. Fonseca, J. Llorca, and A. Tarancon. Standalone micro-reformer for on-board hydrogen production from dimethyl ether, 2021.

[54] Ebin Bastola. The catalytic activity of gold/cadmium sulfide (au/cds) nanocrystals, 2015.

31

[55] Emil Helgren, Jalal Kazempour, and Lesia Mitridati. Feature-driven strategies for trading wind power and hydrogen, 2024.

[56] Arjen T. Veenstra, Albert H. Schrotenboer, Michiel A. J. Uit het Broek, and Evrim Ursavas. Green hydrogen plant: Optimal control strategies for integrated hydrogen storage and power generation with wind energy, 2021.

[57] Avigail Landman, Gideon S. Grader, and Avner Rothschild. Decoupled water splitting: From basic science to application, 2020.

[58] C. Magroa, J. Almeidaa, J. M. Paz-Garcia, E. P. Mateus, and A. B. Ribeiro. Exploring hydrogen production for self-energy generation in electroremediation: A proof of concept, 2020.

[59] Junjie Yin, Jianhua Wang, and Jun You. Electricity-gas integrated energy system optimal operation in typical scenario of coal district considering hydrogen heavy trucks, 2021.

[60] Tatyana Dergunova and Andrew Lyden. Great britain's hydrogen infrastructure development – investment priorities and locational flexibility, 2023.

[61] Erlend Hordvei, Sebastian Emil Hummelen, Marianne Petersen, Stian Backe, and Pedro Crespo del Granado. From policy to practice: The cost of europe's green hydrogen ambitions, 2024.

[62] Daniel Lozano-Martín, Alejandro Moreau, and César R. Chamorro. Thermophysical properties of hydrogen mixtures relevant for the development of the hydrogen economy: Review of available experimental data and thermodynamic models, 2024.

[63] Jabir Ali Ouassou, Julian Straus, Marte Fodstad, Gunhild Reigstad, and Ove Wolfgang. Applying endogenous learning models in energy system optimization, 2021.

[64] Goran Durakovic, Pedro Crespo del Granado, and Asgeir Tomasgard. Powering europe with north sea offshore wind: The impact of hydrogen investments on grid infrastructure and power prices, 2022.

[65] Markus Millinger, Lina Reichenberg, Fredrik Hedenus, Göran Berndes, Elisabeth Zeyen, and Tom Brown. Are biofuel mandates cost-effective? – an analysis of transport fuels and biomass usage to achieve emissions targets in the european energy system, 2022.

[66] Anna Cybulsky, Florian Allroggen, Yang Shao-Horn, and Dharik S. Mallapragada. Decarbonization of aviation via hydrogen propulsion: technology performance targets and energy system impacts, 2023.

[67] Owen Palmer, Hugo Radet, Simon Camal, and Robin Girard. Long-term investment and energy procurement risk management under uncertainty for an electrolytic green hydrogen producer, 2024.

[68] Heberton Wender, Renato V. Gonçalves, Carlos Sato B. Dias, Maximiliano J. M. Zapata, Luiz F. Zagonel, Edielma C. Mendonça, Sérgio R. Teixeira, and Flávio Garcia. Photocatalytic hydrogen production of co(oh)2 nanoparticle-coated $\alpha - fe2o3 nanorings$, 2016.

[69] Frederik vom Scheidt, Jingyi Qu, Philipp Staudt, Dharik S. Mallapragada, and Christof Weinhardt. Integrating hydrogen in single-price electricity systems: The effects of spatial economic signals, 2021.

[70] Mahmood Mahmoodi-Eshkaftakia and Gustavo Mockaitis. Structural optimization of biohydrogen production: Impact of pretreatments on volatile fatty acids and biogas parameters, 2022.

[71] Dahui Liu, Sandra Eksioglu, and Mohammad Roni. Stochastic process optimization of an integrated biorefinery, 2021.

[72] Eliana M. Lozano, Thomas H. Pedersen, and Lasse Rosendahl. Generic approach for the modeling of liquefied thermochemical products and biomass heat of formation. case study: Htl biocrude, pyrolysis oil and assessment of energy requirements, 2019.

[73] Berkay Gulcan, Sandra D. Eksioglu, Yongjia Song, Mohammad Roni, and Qiushi Chen. Optimization models for integrated biorefinery operations, 2021.

Disclaimer:

SurveyX is an AI-powered system designed to automate the generation of surveys. While it aims to produce high-quality, coherent, and comprehensive surveys with accurate citations, the final output is derived from the AI's synthesis of pre-processed materials, which may contain limitations or inaccuracies. As such, the generated content should not be used for academic publication or formal submissions and must be independently reviewed and verified. The developers of SurveyX do not assume responsibility for any errors or consequences arising from the use of the generated surveys.