

No.	Time	Source	Destination	Protocol	Length	Info
32	19:40:32.286363	100.64.166.18	128.119.245.12	HTTP	583	GET /

wireshark-labs/INTRO-wireshark-file1.html HTTP/1.1

Frame 32: 583 bytes on wire (4664 bits), 583 bytes captured (4664 bits) on interface en0, id 0
Ethernet II, Src: 12:1b:8c:50:f4:26 (12:1b:8c:50:f4:26), Dst: HuaweiTechno_8a:5d:45
(c8:33:e5:8a:5d:45)

Destination: HuaweiTechno 8a:5d:45 (c8:33:e5:8a:5d:45)

```
.....0..... = LG bit: Globally unique address (factory default)
```

```

.....0..... = IG bit: Individual address (unicast)

```

Source: 12:1b:8c:50:f4:26 (12:1b:8c:50:f4:26)

```

.....1..... = LG bit: Locally administered address (this is NOT the
factory default)

```

```

.....0..... = IG bit: Individual address (unicast)

```

Type: IPv4 (0x0800)

```
[Stream index: 0]
```

Internet Protocol Version 4, Src: 100.64.166.18, Dst: 128.119.245.12

```
0100 .... = Version: 4
```

```
.... 0101 = Header Length: 20 bytes (5)
```

Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)

Total Length: 569

Identification: 0x0000 (0)

```
010. .... = Flags: 0x2, Don't fragment
```

```
...0 0000 0000 0000 = Fragment Offset: 0
```

Time to Live: 64

Protocol: TCP (6)

```
Header Checksum: 0xb8e8 [validation disabled]
```

```
[Header checksum status: Unverified]
```

Source Address: 100.64.166.18

Destination Address: 128.119.245.12

[Stream index: 3]

Transmission Control Protocol, Src Port: 64666, Dst Port: 80, Seq: 1, Ack: 1, Len: 517

Hypertext Transfer Protocol