```
No.     Time               Source                Destination           Protocol Length Info
     35 19:40:32.571974    128.119.245.12        100.64.166.18         HTTP     305    HTTP/1.1
304 Not Modified
Frame 35: 305 bytes on wire (2440 bits), 305 bytes captured (2440 bits) on interface en0, id 0
Ethernet II, Src: HuaweiTechno_8a:5d:45 (c8:33:e5:8a:5d:45), Dst: 12:1b:8c:50:f4:26 (12:1b:8c:
50:f4:26)
    Destination: 12:1b:8c:50:f4:26 (12:1b:8c:50:f4:26)
        .... ..1. .... .... .... .... = LG bit: Locally administered address (this is NOT the
factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Source: HuaweiTechno_8a:5d:45 (c8:33:e5:8a:5d:45)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
    [Stream index: 0]
Internet Protocol Version 4, Src: 128.119.245.12, Dst: 100.64.166.18
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
    Total Length: 291
    Identification: 0x55af (21935)
    010. .... = Flags: 0x2, Don't fragment
    ...0 0000 0000 0000 = Fragment Offset: 0
    Time to Live: 27
    Protocol: TCP (6)
    Header Checksum: 0x894f [validation disabled]
    [Header checksum status: Unverified]
    Source Address: 128.119.245.12
    Destination Address: 100.64.166.18
    [Stream index: 3]
Transmission Control Protocol, Src Port: 80, Dst Port: 64666, Seq: 1, Ack: 518, Len: 239
Hypertext Transfer Protocol
```