

Introduction to Algorithms

Dynamic Programming

Dynamic Programming

Algorithmic Paradigm

Greedy: Build up a solution incrementally, myopically optimizing some local criterion.

Divide-and-conquer: Break up a problem into multiple sub-problems, solve each sub-problem independently, and combine solution to sub-problems to form solution to original problem.

Dynamic programming. Break up a problem into a series of **overlapping** sub-problems, and build up solutions to larger and larger sub-problems. **Memorize** the answers to obtain polynomial time ALG.

Bellman. Pioneered the systematic study of dynamic programming in the 1950s.

Dynamic Programming Applications

Areas:

- Bioinformatics
- Control Theory
- Information Theory
- Operations Research
- Computer Science: Theory, Graphics, AI, ...

Some famous DP algorithms

- Viterbi for hidden Markov Model
- Unix diff for comparing two files.
- Smith-Waterman for sequence alignment.
- Bellman-Ford for shortest path routing in networks.
- Cocke-Kasami-Younger for parsing context free grammars.

Dynamic Programming

Dynamic programming is nothing but algorithm design by induction!

We just "remember" the subproblems that we have solved so far to avoid re-solving the same sub-problem many times.

Knapsack Problem

Knapsack Problem

Given n objects and a "knapsack."

Item i weighs $w_i > 0$ kilograms and has value $v_i > 0$.

Knapsack has capacity of W kilograms.

Goal: fill knapsack so as to maximize total value.

Ex: OPT is $\{ 3, 4 \}$ with value 40.

$$W = 11$$

Item	Value	Weight
1	1	1
2	6	2
3	18	5
4	22	6
5	28	7

Greedy: repeatedly add item with maximum ratio v_i / w_i .

Ex: $\{ 5, 2, 1 \}$ achieves only value = 35 \Rightarrow greedy not optimal.

Dynamic Programming: First Attempt

Let $OPT(i)$ = Max value of subsets of items $1, \dots, i$ of weight $\leq W$.

Case 1: $OPT(i)$ does not select item i

- In this case $OPT(i) = OPT(i - 1)$

Case 2: $OPT(i)$ selects item i

- In this case, item i does not immediately imply we have to reject other items
- The problem does not reduce to $OPT(i - 1)$ because we now want to pack as much value into box of weight $\leq W - w_i$

Conclusion: We need more subproblems, we need to strengthen IH.

Stronger DP (Strengthening Hypothesis)

Let $OPT(i, w)$ = Max value subset of items $1, \dots, i$ of weight $0 \leq w \leq W$

Case 1: $OPT(i, w)$ selects item i

- In this case, $OPT(i, w) = v_i + OPT(i - 1, w - w_i)$

Case 2: $OPT(i, w)$ does not select item i

- In this case, $OPT(i, w) = OPT(i - 1, w)$.

Take best of the two



Therefore,

$$OPT(i, w) = \begin{cases} 0 & \text{If } i = 0 \\ OPT(i - 1, w) & \text{If } w_i > w \\ \max(OPT(i - 1, w), v_i + OPT(i - 1, w - w_i)) & \text{o.w.,} \end{cases}$$

DP for Knapsack

```
for w = 0 to W
  M[0, w] = 0
for i = 1 to n
  for w = 1 to W
    if (wi > w)
      M[i, w] = M[i-1, w]
    else
      M[i, w] = max {M[i-1, w], vi + M[i-1, w-wi]}
return M[n, W]
```

第 i 个物品的重量大于当前的 w ，说明第 i 个物品放不进来了。于是将 $M(i, w)$ 的价值置为 $M(i-1, w)$ ，实际上就是 $i-1$ 个物品下最大的价值。

Non-recursive

否则，从以下两者中选大的：

1. $i-1$ 个物品下最大的价值
2. $i-1$ 个物品下，重量不超过 $w-w_i$ 时最大的价值（需要确保 i 放进来以后，有足够的容量来存放）+ 当前第 i 个物品的价值

$M(i, w)$ = total value of items from 1 to i (not exceed weight W)

DP for Knapsack

		W + 1 →											
		0	1	2	3	4	5	6	7	8	9	10	11
<div style="display: flex; align-items: center;"> <div style="writing-mode: vertical-rl; transform: rotate(180deg); margin-right: 5px;">n + 1</div> <div style="border-left: 1px solid black; border-right: 1px solid black; height: 100px; margin: 0 5px;"></div> </div>	ϕ	0	0	0	0	0	0	0	0	0	0	0	0
	{ 1 }	0											
	{ 1, 2 }	0											
	{ 1, 2, 3 }	0											
	{ 1, 2, 3, 4 }	0											
	{ 1, 2, 3, 4, 5 }	0											

1. 背容=11, 从1号物品中找出该问题的解
2. 背容=11, 从1号, 2号物品中找出该问题的解
3. 背容=11, 从1号, 2号, 3号物品中找出该问题的解
4. 背容=11, 从1号, 2号, 3号, 4号物品中找出该问题的解
5. 背容=11, 从1号, 2号, 3号, 4号, 5号物品中找出该问题的解

W = 11

```

if (wi > w)
    M[i, w] = M[i-1, w]
else
    M[i, w] = max {M[i-1, w], vi + M[i-1, w-wi]}
    
```

Item	Value	Weight
1	1	1
2	6	2
3	18	5
4	22	6
5	28	7

DP for Knapsack

		W + 1 →											
		0	1	2	3	4	5	6	7	8	9	10	11
<div style="display: flex; align-items: center;"> <div style="border-left: 1px solid black; height: 100px; margin-right: 5px;"></div> <div style="display: flex; flex-direction: column; align-items: center; justify-content: space-between; width: 20px;"> n + 1 ↓ </div> </div>	ϕ	0	0	0	0	0	0	0	0	0	0	0	0
	{ 1 }	0	1	1	1	1	1	1	1	1	1	1	1
	{ 1, 2 }	0											
	{ 1, 2, 3 }	0											
	{ 1, 2, 3, 4 }	0											
	{ 1, 2, 3, 4, 5 }	0											

W = 11

```

if (wi > w)
    M[i, w] = M[i-1, w]
else
    M[i, w] = max {M[i-1, w], vi + M[i-1, w-wi]}
    
```

Item	Value	Weight
1	1	1
2	6	2
3	18	5
4	22	6
5	28	7

DP for Knapsack

		W + 1 →											
		0	1	2	3	4	5	6	7	8	9	10	11
n + 1 ↓	ϕ	0	0	0	0	0	0	0	0	0	0	0	0
	{ 1 }	0	1	1	1	1	1	1	1	1	1	1	1
	{ 1, 2 }	0	1	6	7								
	{ 1, 2, 3 }	0	1										
	{ 1, 2, 3, 4 }	0	1										
	{ 1, 2, 3, 4, 5 }	0	1										

OPT: { 4, 3 }
value = 22 + 18 = 40

W = 11

```

if (wi > w)
    M[i, w] = M[i-1, w]
else
    M[i, w] = max {M[i-1, w], vi + M[i-1, w-wi]}
    
```

Item	Value	Weight
1	1	1
2	6	2
3	18	5
4	22	6
5	28	7

DP for Knapsack

		W + 1 →											
		0	1	2	3	4	5	6	7	8	9	10	11
n + 1 ↓	ϕ	0	0	0	0	0	0	0	0	0	0	0	0
	{1}	0	1	1	1	1	1	1	1	1	1	1	1
	{1, 2}	0	1	6	7	7	7	7	7	7	7	7	7
	{1, 2, 3}	0	1	6	7	7	18	19					
	{1, 2, 3, 4}	0	1										
	{1, 2, 3, 4, 5}	0	1										

OPT: { 4, 3 }
value = 22 + 18 = 40

W = 11

```

if (wi > w)
    M[i, w] = M[i-1, w]
else
    M[i, w] = max {M[i-1, w], vi + M[i-1, w-wi]}
    
```

Item	Value	Weight
1	1	1
2	6	2
3	18	5
4	22	6
5	28	7

DP for Knapsack

		W + 1 →											
		0	1	2	3	4	5	6	7	8	9	10	11
n + 1 ↓	ϕ	0	0	0	0	0	0	0	0	0	0	0	0
	{1}	0	1	1	1	1	1	1	1	1	1	1	1
	{1, 2}	0	1	6	7	7	7	7	7	7	7	7	7
	{1, 2, 3}	0	1	6	7	7	18	19	24	25	25	25	25
	{1, 2, 3, 4}	0	1	6	7	7	18	22	24	28	29		
	{1, 2, 3, 4, 5}	0	1										

OPT: { 4, 3 }
value = 22 + 18 = 40

W = 11

```

if (wi > w)
    M[i, w] = M[i-1, w]
else
    M[i, w] = max {M[i-1, w], vi + M[i-1, w-wi]}
    
```

Item	Value	Weight
1	1	1
2	6	2
3	18	5
4	22	6
5	28	7

DP for Knapsack

		W + 1 →											
		0	1	2	3	4	5	6	7	8	9	10	11
n + 1 ↓	ϕ	0	0	0	0	0	0	0	0	0	0	0	0
	{ 1 }	0	1	1	1	1	1	1	1	1	1	1	1
	{ 1, 2 }	0	1	6	7	7	7	7	7	7	7	7	7
	{ 1, 2, 3 }	0	1	6	7	7	18	19	24	25	25	25	25
	{ 1, 2, 3, 4 }	0	1	6	7	7	18	22	24	28	29	29	40
	{ 1, 2, 3, 4, 5 }	0	1	6	7	7	18	22	28	29	34	34	40

OPT: { 4, 3 }
value = 22 + 18 = 40

W = 11

```

if (wi > w)
    M[i, w] = M[i-1, w]
else
    M[i, w] = max {M[i-1, w], vi + M[i-1, w-wi]}
    
```

Item	Value	Weight
1	1	1
2	6	2
3	18	5
4	22	6
5	28	7

Knapsack Problem: Running Time

Running time: $\Theta(n \cdot W)$

- Not polynomial in input size!
- "Pseudo-polynomial."
- Decision version of Knapsack is NP-complete.

Knapsack approximation algorithm:

There exists a polynomial algorithm that produces a feasible solution that has value within 0.01% of optimum in time $\text{Poly}(n, \log W)$.

DP Ideas so far

- You may have to define an ordering to decrease #subproblems
- You may have to strengthen DP, equivalently the induction, i.e., you may have to carry more information to find the Optimum.
- This means that sometimes we may have to use two dimensional or three dimensional induction