

---

# **Practical Multilayer Network Analysis with Py3plex**

*Release 1.1.0*

**Blaž Škrlj**

**Jan 05, 2026**

# CONTENTS

|           |                                                           |            |
|-----------|-----------------------------------------------------------|------------|
| <b>1</b>  | <b>Front Matter</b>                                       | <b>1</b>   |
| <b>2</b>  | <b>Introduction &amp; Motivation</b>                      | <b>4</b>   |
| <b>3</b>  | <b>Multilayer Network Basics</b>                          | <b>9</b>   |
| <b>4</b>  | <b>Design of Py3plex</b>                                  | <b>17</b>  |
| <b>5</b>  | <b>Installation and Getting Started</b>                   | <b>24</b>  |
| <b>6</b>  | <b>Data Loading and Representation</b>                    | <b>32</b>  |
| <b>7</b>  | <b>Visualization and Exploration</b>                      | <b>42</b>  |
| <b>8</b>  | <b>Core Algorithms: Communities, Centrality, Dynamics</b> | <b>48</b>  |
| <b>9</b>  | <b>Introduction to the Py3plex DSL</b>                    | <b>56</b>  |
| <b>10</b> | <b>The Builder API and Explain Plans</b>                  | <b>66</b>  |
| <b>11</b> | <b>Advanced Queries and Workflows</b>                     | <b>73</b>  |
| <b>12</b> | <b>Limitations and Stability Guarantees</b>               | <b>86</b>  |
| <b>13</b> | <b>Case Study 1 — Social Multiplex Network</b>            | <b>90</b>  |
| <b>14</b> | <b>Case Study 2 — Biological Multilayer Network</b>       | <b>97</b>  |
| <b>15</b> | <b>Case Study 3 — Transportation Network</b>              | <b>102</b> |
| <b>16</b> | <b>Testing and Validation</b>                             | <b>106</b> |
| <b>17</b> | <b>Reproducible Environments</b>                          | <b>110</b> |
| <b>18</b> | <b>The Py3plex GUI (Overview)</b>                         | <b>116</b> |
| <b>19</b> | <b>Appendix A: Repository Layout and Scripts</b>          | <b>122</b> |
| <b>20</b> | <b>Appendix B: Docker, Docker Compose, and Deployment</b> | <b>127</b> |
| <b>21</b> | <b>Appendix C: Detailed Validation Scripts</b>            | <b>136</b> |
| <b>22</b> | <b>Appendix D: Error Handling and Exception Hierarchy</b> | <b>143</b> |

|           |                                                   |            |
|-----------|---------------------------------------------------|------------|
| <b>23</b> | <b>Appendix E: Extended API and DSL Reference</b> | <b>150</b> |
| <b>24</b> | <b>Bibliography</b>                               | <b>158</b> |
| <b>25</b> | <b>Citation Information</b>                       | <b>160</b> |
|           | <b>Bibliography</b>                               | <b>165</b> |
|           | <b>Index</b>                                      | <b>167</b> |

## FRONT MATTER

### 1.1 About This Book

**Practical Multilayer Network Analysis with Py3plex** is a research-oriented handbook for graduate students and applied network scientists. It provides both theoretical foundations and practical guidance for analyzing complex systems using multilayer network representations.

This book covers:

- Mathematical foundations of multilayer networks
- The py3plex library architecture and design philosophy
- Hands-on examples and workflows for real network analysis
- **A powerful SQL-like DSL for network queries**
- Production deployment and reproducibility practices

#### DSL Feature Highlight

Py3plex includes a first-class DSL for querying networks with SQL-like syntax:

```
from py3plex.dsl import Q, L

# Find top influencers using builder API
result = (
    Q.nodes()
    .from_layers(L["social"])
    .where(degree__gt=5)
    .compute("betweenness_centrality")
    .order_by("-betweenness_centrality")
    .limit(10)
    .execute(network)
)
```

See **Part III** for complete DSL coverage!

### 1.2 Target Audience

This book is designed for:

- **Graduate students** in network science, computer science, and related fields
- **Applied researchers** working with complex relational data

- **Data scientists** analyzing social, biological, or infrastructure networks
- **Software engineers** building network analysis pipelines

## 1.2.1 Prerequisites

Readers should be familiar with:

- Python programming (intermediate level)
- Basic graph theory concepts
- Fundamental linear algebra

## 1.3 About the Software

**py3plex** (version 1.x) is an open-source Python library for multilayer and multiplex network analysis. It provides:

- Native support for multilayer network structures
- 17+ specialized algorithms for multilayer analysis
- A SQL-like query language (DSL) for network exploration
- NetworkX compatibility and interoperability
- High-performance I/O with Arrow/Parquet support

The library is actively maintained and tested on Python 3.8+.

## 1.4 How to Use This Book

**Part I** establishes foundations: what multilayer networks are, when to use them, and how py3plex is designed.

**Part II** teaches practical usage: installation, data loading, visualization, and running core algorithms.

**Part III** presents the DSL query language, a major feature for expressing complex analyses concisely.

**Part IV** demonstrates real-world applications through detailed case studies.

**Part V** covers systems topics: testing, reproducibility, and the web GUI.

**Appendices** provide reference material, detailed configurations, and extensive validation examples that supplement the main text.

### 1.4.1 Code Examples

All code examples in this book are runnable and tested. Examples use consistent naming and follow modern Python conventions. File paths reference the accompanying GitHub repository:

<https://github.com/SkBlaz/py3plex>

### 1.4.2 Conventions

- **Code blocks** use syntax highlighting and are self-contained
- **Mathematical notation** follows standard network science conventions
- **Feature status** is clearly marked:
  - **Stable** - Production-ready with guarantees
  - **Experimental** - Functional but may change

- **Planned** - Future features (mentioned only briefly)

## 1.5 Acknowledgments

This work builds on contributions from the py3plex community and research collaborations in multilayer network analysis.

If you use py3plex in your research, please cite:

```
@Article{Skrlj2019,  
  author={Skrlj, Blaz and Kralj, Jan and Lavrac, Nada},  
  title={Py3plex toolkit for visualization and analysis of multilayer networks},  
  journal={Applied Network Science},  
  year={2019},  
  volume={4},  
  number={1},  
  pages={94},  
  doi={10.1007/s41109-019-0203-7}  
}
```

## 1.6 License

The py3plex library is released under the MIT License. This book's content is licensed under Creative Commons Attribution 4.0 International (CC BY 4.0).

### Note

**Version Information:** This is version 1.0 (2025) of the book, covering py3plex 1.x with Python 3.8+ support.

## INTRODUCTION & MOTIVATION

### 2.1 Why Multilayer Networks?

Real-world systems rarely consist of a single type of relationship. Consider:

- **Social networks:** People interact through friendship, collaboration, family ties, and online connections—each relationship type has different meanings and dynamics.
- **Transportation systems:** Cities connect via air, rail, and road networks. A disruption in one mode affects the others, and travelers make choices across modes.
- **Biological systems:** Proteins interact through physical binding, regulatory relationships, and metabolic pathways—each layer represents a different mechanism.
- **Information systems:** Software components depend on each other through API calls, data flows, and deployment relationships.

Traditional single-layer (monoplex) networks flatten these diverse relationships into a single graph, losing critical structural information. **Multilayer networks** preserve the distinct nature of different relationship types by organizing them into separate but interconnected layers.

#### 2.1.1 The Cost of Flattening

When we flatten a multilayer network into a single graph, we lose:

1. **Relationship semantics:** A coauthor edge is fundamentally different from a Twitter follower edge, but flattening treats them identically.
2. **Community structure:** Groups that are well-separated in individual layers may appear spuriously connected when layers are combined.
3. **Node roles:** A person might be central in their professional network but peripheral in their hobby network—this context-dependent centrality disappears upon flattening.
4. **Cross-layer dynamics:** Information spreading from email to in-person meetings follows specific patterns that become invisible when layers are merged.

**Example:** A researcher with 2 coauthors and 500 Twitter followers has degree 502 in a flattened network, suggesting high influence. But their academic impact (degree 2) is actually modest—the Twitter followers don't write papers with them. Multilayer analysis preserves this distinction.

### 2.2 What py3plex Enables

**py3plex** is a Python library designed for practical analysis of multilayer networks. It provides:

#### 1. Expressive Data Structures

Native support for multilayer network representations that mirror how real systems are naturally structured:

```
from py3plex.core import multinet

# Create a multilayer network
network = multinet.multi_layer_network()

# Add edges across multiple layers
network.add_edges([
    ['Alice', 'coauthor', 'Bob', 'coauthor', 1],
    ['Alice', 'twitter', 'Carol', 'twitter', 1],
    ['Bob', 'coauthor', 'Dave', 'coauthor', 1],
], input_type="list")
```

## 2. Multilayer-Aware Algorithms

Algorithms specifically designed for multilayer structure:

- **Community detection** that respects layer boundaries while finding cross-layer modules
- **Centrality measures** that account for both intra-layer and inter-layer importance
- **Random walks** that can transition between layers
- **Dynamics models** (e.g., epidemic spreading) with layer-specific parameters

## 3. A Query Language for Networks

A SQL-like DSL (Domain-Specific Language) for expressing complex network analyses concisely:

### DSL Example: Concise Network Analysis

Instead of writing loops and conditions, use declarative queries:

```
from py3plex.dsl import Q, L

# Find high-degree nodes in the coauthor layer
result = (
    Q.nodes()
    .from_layers(L["coauthor"])
    .where(degree__gt=5)
    .compute("betweenness centrality", "pagerank")
    .order_by("-betweenness centrality")
    .limit(10)
    .execute(network)
)

# Export for further analysis
result.to_pandas().to_csv("top_researchers.csv")
```

This replaces dozens of lines of manual filtering and iteration with a clear, composable query.

#### Key DSL features:

- SQL-like syntax familiar to data analysts
- Layer algebra: `L["social"] + L["work"] - L["bots"]`
- Type-safe Python builder API



- Export to pandas, NetworkX, Arrow, CSV, JSON
- EXPLAIN mode for query optimization

#### 4. Visualization for Multilayer Networks

Publication-ready visualizations that show layer structure and cross-layer connections:

```
# Visualize with layer separation
network.visualize_network(
    show=True,
    layout_style="force_directed_3d"
)
```

#### 5. Production-Ready Infrastructure

- **High-performance I/O** with Arrow/Parquet support for large networks
- **NetworkX compatibility** for interoperability with the broader Python ecosystem
- **Testing and validation** frameworks to ensure correctness
- **Docker containers** and CLI tools for deployment

## 2.3 Who Should Use This Book

This book is designed for:

#### Graduate Students and Researchers

If you're analyzing social, biological, or infrastructure networks in your research, this book provides both theoretical foundations and practical tools. You'll learn when multilayer modeling is appropriate and how to apply specialized algorithms correctly.

#### Data Scientists and Analysts

If you're working with complex relational data—user behavior across platforms, supply chain networks, knowledge graphs—py3plex offers a principled way to preserve and analyze structural nuances.

#### Software Engineers

If you're building network analysis pipelines, this book shows how to use py3plex's APIs, DSL, and deployment tools to create maintainable, efficient systems.

### 2.3.1 Prerequisites

This book assumes:

- **Intermediate Python** (classes, list comprehensions, basic NumPy)
- **Basic graph theory** (nodes, edges, paths, degree)
- **Fundamental linear algebra** (matrices, matrix multiplication)

You don't need prior multilayer network experience—Part I builds from fundamentals.

## 2.4 Real-World Applications

Multilayer network analysis has proven valuable in numerous domains:

### Biological Networks

- Protein-protein interactions across multiple tissues or conditions
- Gene regulatory networks with transcription, translation, and metabolic layers
- Brain connectivity with structural and functional layers

### Social Networks

- User behavior across multiple social platforms
- Organizational networks with formal and informal relationships
- Citation networks with papers, authors, and venues

### Infrastructure Networks

- Transportation with air, rail, and road connections
- Power grids with generation, transmission, and distribution layers
- Communication networks with physical and logical layers

### Knowledge and Information

- Heterogeneous information networks (authors-papers-venues)
- Semantic networks with multiple relationship types
- Code dependency graphs with API, data, and deployment layers

Each of these applications benefits from multilayer analysis by capturing the true structure of the system rather than forcing it into a single-layer representation.

## 2.5 How This Book Is Organized

### Part I (Chapters 1-3): Foundations

Introduces multilayer networks, defines key concepts, and explains py3plex’s design philosophy.

### Part II (Chapters 4-7): Working with Py3plex

Covers installation, data loading, visualization, and core algorithms—everything needed for basic usage.

### Part III (Chapters 8-11): Advanced Analysis and the DSL

Deep dive into the query language, a major feature for expressing complex analyses concisely.

### Part IV (Chapters 12-14): Case Studies

Complete, reproducible analyses of real datasets across different domains.

### Part V (Chapters 15-17): Systems and Deployment

Testing, reproducibility, and production deployment including the web GUI.

### Appendices (A-E): Reference Material

Detailed configurations, validation scripts, error handling, and API reference.

Each chapter includes:

- **Conceptual explanations** with mathematical foundations where needed
- **Code examples** that are runnable and tested
- **Practical tips** based on real usage patterns

- **References** for deeper study

## 2.6 Summary

Multilayer networks provide a natural and expressive way to model systems with multiple types of relationships. By preserving the distinct nature of different layers, we can:

- Analyze structure more accurately
- Compute meaningful centralities and communities
- Model dynamics more realistically
- Make better predictions and interventions

**py3plex** makes multilayer network analysis accessible and practical, with a focus on:

- Expressive data structures
- Specialized algorithms
- A powerful query language
- Production-ready tools

The following chapters will show you how to use these capabilities effectively.

## 2.7 Further Reading

- Kivelä, M., et al. (2014). “Multilayer networks.” *Journal of Complex Networks* 2(3): 203-271. [Comprehensive review of multilayer network theory]
- Boccaletti, S., et al. (2014). “The structure and dynamics of multilayer networks.” *Physics Reports* 544(1): 1-122. [Physics-focused perspective]
- Bianconi, G. (2018). *Multilayer Networks: Structure and Function*. Oxford University Press. [Textbook treatment]

## MULTILAYER NETWORK BASICS

This chapter establishes the formal foundations of multilayer networks. We define key concepts, introduce mathematical notation, and show how different types of multilayer networks relate to each other.

### 3.1 Formal Definitions

#### 3.1.1 Node-Layer Pairs

A **multilayer network**  $\mathcal{M}$  consists of:

- A set of **nodes**  $V = \{v_1, v_2, \dots, v_N\}$
- A set of **layers**  $L = \{\alpha, \beta, \gamma, \dots\}$
- A set of **node-layer pairs**  $V_M = V \times L$
- **Intra-layer edges**  $E_\alpha \subseteq V \times V$  within each layer  $\alpha$
- **Inter-layer edges**  $E_C \subseteq V_M \times V_M$  connecting node-layer pairs

The **node-layer pair**  $(v, \alpha)$  is the fundamental unit: it represents node  $v$  in the context of layer  $\alpha$ .

#### 3.1.2 Supra-Adjacency Matrix

The **supra-adjacency matrix**  $\mathbf{A}$  is a block matrix that encodes the full multilayer structure:

$$\mathbf{A} = \begin{pmatrix} \mathbf{A}_{\alpha\alpha} & \mathbf{A}_{\alpha\beta} & \cdots \\ \mathbf{A}_{\beta\alpha} & \mathbf{A}_{\beta\beta} & \cdots \\ \vdots & \vdots & \ddots \end{pmatrix}$$

Where:

- **Diagonal blocks**  $\mathbf{A}_{\alpha\alpha}$  are the adjacency matrices of individual layers
- **Off-diagonal blocks**  $\mathbf{A}_{\alpha\beta}$  encode inter-layer connections

For a multiplex network with  $N$  nodes and  $L$  layers,  $\mathbf{A}$  is an  $(N \times L) \times (N \times L)$  matrix.

**Example:** A 3-node, 2-layer network:

$$\mathbf{A} = \begin{pmatrix} \mathbf{A}_{\text{friends}} & \omega \mathbf{I} \\ \omega \mathbf{I} & \mathbf{A}_{\text{colleagues}} \end{pmatrix}$$

where  $\omega$  is the **inter-layer coupling strength** and  $\mathbf{I}$  is the identity matrix (representing identity edges: each node connects to itself across layers).

## 3.2 Types of Multilayer Networks

### 3.2.1 Multiplex Networks

**Definition:** A multiplex network has the same node set in all layers, with different edge sets per layer.

$$V_\alpha = V_\beta = \dots = V \quad \text{for all layers}$$

**Characteristics:**

- **Same entities** appear in all layers
- **Different relationship types** per layer
- **Strong inter-layer coupling** (typically  $\omega = 1.0$  for identity edges)

**Example: Social Multiplex Network**

```
from py3plex.core import multinet

# Create multiplex network
network = multinet.multi_layer_network(network_type="multiplex")

# Same people, different relationship types
network.add_edges([
    ['Alice', 'friends', 'Bob', 'friends', 1],
    ['Bob', 'friends', 'Carol', 'friends', 1],
    ['Alice', 'colleagues', 'Bob', 'colleagues', 1],
    ['Bob', 'colleagues', 'Dave', 'colleagues', 1],
], input_type="list")

# Verify structure
print(f"Layers: {network.get_layers()}")
print(f"Nodes per layer: {network.get_number_of_nodes_per_layer()}")
```

**Real-world applications:**

- Social networks across platforms (Facebook, Twitter, LinkedIn)
- Transportation modes (air, rail, road)
- Communication channels (email, phone, chat)
- Biological interactions (genetic, protein, metabolic)

### 3.2.2 Heterogeneous Information Networks

**Definition:** A network with different node types, where edges connect specific node type pairs.

**Characteristics:**

- **Different node types** per layer (authors, papers, venues)
- **Type-specific edges** (author-paper, paper-venue)
- **No inter-layer coupling** (nodes don't repeat across layers)

**Example: Academic Network**

```

network = multinet.multi_layer_network()

# Different node types
network.add_edges([
    ['Alice', 'authors', 'Paper1', 'papers', 1],
    ['Bob', 'authors', 'Paper1', 'papers', 1],
    ['Paper1', 'papers', 'ICML', 'venues', 1],
    ['Paper2', 'papers', 'ICML', 'venues', 1],
], input_type="list")

```

This creates a **tripartite** network with three node types: authors, papers, and venues.

#### Real-world applications:

- Academic networks (authors, papers, venues, keywords)
- E-commerce (users, products, sellers, categories)
- Biomedical (drugs, diseases, targets, pathways)
- Knowledge graphs (entities, relations, concepts)

### 3.2.3 Temporal Networks

**Definition:** Networks that evolve over time, represented as time-sliced layers.

#### Characteristics:

- **Time windows as layers** (2020, 2021, 2022, ...)
- **Node presence varies** across time slices
- **Temporal edges** connect adjacent time slices

#### Example: Temporal Social Network

```

network = multinet.multi_layer_network()

# Time-sliced layers
network.add_edges([
    ['Alice', '2020', 'Bob', '2020', 1],
    ['Alice', '2021', 'Bob', '2021', 1],
    ['Bob', '2021', 'Carol', '2021', 1],
    ['Alice', '2022', 'Carol', '2022', 1],
], input_type="list")

```

#### Real-world applications:

- Communication patterns over time
- Disease spread through populations
- Financial transaction networks
- Collaboration evolution

### 3.2.4 Interdependent Networks

**Definition:** Multiple networks where the function of nodes in one layer depends on nodes in other layers.

**Characteristics:**

- **Dependency edges** encode functional relationships
- **Cascading failures** possible across layers
- **Critical infrastructure** applications

**Example:** Power grid (layer 1) depends on communication network (layer 2). If communication fails, power grid control fails.

**Real-world applications:**

- Infrastructure systems (power, water, communication)
- Supply chain networks
- Cyber-physical systems
- Ecological networks (species, habitats, resources)

## 3.3 Inter-Layer Coupling

The **coupling strength**  $\omega$  controls how strongly layers are connected.

### 3.3.1 Identity Coupling

The most common form connects each node to itself across layers:

$$E_C = \{((v, \alpha), (v, \beta)) : v \in V, \alpha \neq \beta \in L\}$$

with edge weight  $\omega$ .

**Choice of  $\omega$ :**

- $\omega = 1.0$  — Layers are equally important, nodes fully correspond
- $\omega < 1.0$  — Layers are loosely coupled, favor intra-layer paths
- $\omega > 1.0$  — Inter-layer transitions are encouraged

**Example:**

```
network = multinet.multi_layer_network()

# Add intra-layer edges
network.add_edges([
    ['A', 'layer1', 'B', 'layer1', 1],
    ['A', 'layer2', 'C', 'layer2', 1],
], input_type="list")

# Add inter-layer coupling (identity edges)
network.add_edges([
    ['A', 'layer1', 'A', 'layer2', 0.5], # omega = 0.5
], input_type="list")
```

### 3.3.2 General Coupling

More complex couplings allow different nodes to connect across layers:

$$E_C = \{((v, \alpha), (w, \beta)) : (v, w) \in C_{\alpha\beta}\}$$

where  $C_{\alpha\beta}$  defines which nodes couple between layers  $\alpha$  and  $\beta$ .

## 3.4 When to Use Multilayer Networks

Use multilayer modeling when:

1. **Multiple relationship types have distinct semantics**

Example: Friendship vs. professional collaboration—these networks have different properties and dynamics.

2. **Node roles vary by context**

Example: A person central in academic network may be peripheral in social media network.

3. **Cross-layer interactions matter**

Example: Information spreads from Twitter to traditional media—this cross-layer flow is meaningful.

4. **Temporal evolution is important**

Example: Community structure evolves over time—time-sliced layers preserve this evolution.

5. **System-level resilience depends on layer dependencies**

Example: Power grid failure affects communication, which affects emergency response.

## 3.5 Choosing a Modeling Approach

### 3.5.1 Decision Tree

1. Do relationships have fundamentally different types?  
YES → Use layers (multiplex or heterogeneous)  
NO → Use edge weights or attributes
2. Are the same entities present in all layers?  
YES → Multiplex network (strong coupling)  
NO → Heterogeneous network (weak/no coupling)
3. Does time evolution matter?  
YES → Temporal layers (time-sliced)  
NO → Static multilayer network
4. Are there functional dependencies between layers?  
YES → Interdependent network (dependency edges)  
NO → Standard multiplex/heterogeneous

### 3.5.2 Common Mistakes

#### Over-aggregation

Combining layers that should stay separate (e.g., merging email and meeting networks loses information about mode transitions).



### Under-aggregation

Creating too many sparse layers when edge weights would suffice (e.g., separate layer for each email vs. email timestamp as attribute).

### Wrong coupling strength

Using  $\omega = 1.0$  when nodes don't fully correspond, or  $\omega \rightarrow 0$  when they do.

### Mismatched identifiers

Using different IDs for the same entity across layers breaks multiplex structure.

## 3.6 Why Flattening Fails

Flattening (aggregating all layers into a single graph) loses critical information:

### 1. Community Structure

Multilayer communities may have:

- **Core in one layer, periphery in another**
- **Cross-layer bridges** that appear as spurious intra-layer connections when flattened

**Example:** Academic collaboration (dense group) + Twitter followers (different dense group). Flattening creates false bridges.

### 2. Centrality

A node's importance depends on layer:

- **Structural centrality** in one layer (high degree)
- **Functional centrality** in another (betweenness for information flow)

Flattening mixes these distinct roles.

### 3. Path Structure

Meaningful paths often cross layers:

- Email  $\rightarrow$  meeting  $\rightarrow$  collaboration
- Twitter mention  $\rightarrow$  news coverage  $\rightarrow$  policy change

Flattening hides these cross-layer transitions.

### 4. Dynamics

Disease spreading, information diffusion, and cascading failures all depend on layer-specific parameters and inter-layer transitions. Flattening cannot capture:

- **Layer-specific transmission rates**
- **Mode-switching dynamics**
- **Asymmetric cross-layer effects**

## 3.7 Key Terminology

### Intra-layer edges

Edges within a single layer, connecting  $(v, \alpha)$  to  $(w, \alpha)$ .

### Inter-layer edges

Edges between layers, connecting  $(v, \alpha)$  to  $(w, \beta)$  with  $\alpha \neq \beta$ .

**Node-layer pair**

The tuple  $(v, \alpha)$  representing node  $v$  in layer  $\alpha$ —the fundamental unit of a multilayer network.

**Supra-adjacency matrix**

The block matrix  $\mathbf{A}$  encoding all intra-layer and inter-layer edges.

**Coupling strength**

The weight  $\omega$  of inter-layer edges, controlling how strongly layers interact.

**Multiplex network**

Multilayer network with the same nodes in all layers.

**Heterogeneous information network**

Multilayer network with different node types per layer.

## 3.8 Working with Supra-Adjacency Matrices in Py3plex

```
from py3plex.core import multinet, random_generators

# Generate random multilayer network
network = random_generators.random_multilayer_ER(
    num_nodes=100,
    num_layers=3,
    probability=0.05,
    directed=False
)

# Get supra-adjacency matrix (sparse format)
supra_matrix = network.get_supra_adjacency_matrix()

print(f"Matrix shape: {supra_matrix.shape}") # (300, 300) for 100 nodes x 3 layers
print(f"Matrix density: {supra_matrix.nnz / (supra_matrix.shape[0] ** 2):.4f}")

# Visualize matrix structure
network.visualize_matrix({"display": True})
```

The supra-adjacency matrix enables tensor-based algorithms and linear algebra operations on the full multilayer structure.

## 3.9 Summary

Multilayer networks formalize systems with multiple relationship types by:

- Using **node-layer pairs** as the fundamental unit
- Encoding structure in the **supra-adjacency matrix**
- Supporting various types: **multiplex**, **heterogeneous**, **temporal**, **interdependent**
- Controlling interaction via **coupling strength**  $\omega$

Key takeaways:

1. **Multiplex** = same nodes, different edge types
2. **Heterogeneous** = different node types per layer
3. **Temporal** = time-sliced layers

4. **Coupling** = inter-layer connections (identity edges most common)
5. **Flattening loses information** — use multilayer analysis when layer structure matters

The next chapter explains how py3plex implements these concepts and why its design choices support efficient, correct multilayer analysis.

## 3.10 Further Reading

- **Theory:** Kivelä et al. (2014). “Multilayer networks.” *J. Complex Networks* 2(3): 203-271.
- **Physics:** Boccaletti et al. (2014). “The structure and dynamics of multilayer networks.” *Physics Reports* 544(1): 1-122.
- **Textbook:** Bianconi, G. (2018). *Multilayer Networks: Structure and Function*. Oxford University Press.
- **Applications:** De Domenico et al. (2013). “Mathematical formulation of multilayer networks.” *Physical Review X* 3(4): 041022.

## DESIGN OF PY3PLEX

This chapter explains how py3plex is architected and why it makes specific design choices. Understanding these design principles will help you use the library more effectively and debug unexpected behavior.

### 4.1 Architecture Overview

Py3plex is built on three foundational principles:

1. **NetworkX compatibility** — Leverage a mature, well-tested ecosystem
2. **Modular design** — Separate concerns for flexibility and extensibility
3. **Simple, off-the-shelf functionality** — Minimize barrier to entry

The library consists of several core modules:

```
py3plex/
├── core/                # Data structures (multi_layer_network class)
├── algorithms/          # Analysis methods
│   ├── statistics/      # Multilayer statistics
│   ├── centrality/      # Centrality measures
│   ├── community_detection/ # Community algorithms
│   └── paths/           # Path algorithms
├── dynamics/           # Dynamical processes (SIS, SIR, random walks)
├── dsl/                # SQL-like query language
├── visualization/      # Plotting and visualization
├── io/                 # Data loading/saving
└── cli.py              # Command-line interface
```

### 4.2 Node-Layer Pair Representation

#### 4.2.1 The Fundamental Unit

Py3plex represents multilayer networks using **node-layer pairs** as the fundamental unit. A node  $v$  in layer  $\alpha$  is stored as the tuple  $(v, \alpha)$ .

```
from py3plex.core import multinet

network = multinet.multi_layer_network()

# Add nodes explicitly as (node_id, layer_id) pairs
network.add_nodes([
    ('Alice', 'friends'),
```

```

    ('Bob', 'friends'),
    ('Alice', 'colleagues'),
])

# Or implicitly through edge addition
network.add_edges([
    ['Alice', 'friends', 'Bob', 'friends', 1],
    ['Alice', 'colleagues', 'Bob', 'colleagues', 1],
], input_type="list")

```

#### Why node-layer pairs?

- **Unambiguous identification** — The same logical entity (Alice) has distinct identities in different layers
- **NetworkX compatibility** — Tuples are valid NetworkX node identifiers
- **Efficient lookups** — Python's tuple hashing enables fast operations
- **Natural tensor mapping** — Node-layer pairs map directly to rows/columns of the supra-adjacency matrix

## 4.3 The multi\_layer\_network Class

### 4.3.1 Core Components

The `multi_layer_network` class wraps a NetworkX graph and adds multilayer-specific functionality:

```

network = multinet.multi_layer_network(directed=False)

# The underlying NetworkX graph (MultiGraph or MultiDiGraph)
G = network.core_network

# Layer management
layers = network.get_layers()           # ['friends', 'colleagues']
layer_map = network.layer_name_map     # {'friends': 0, 'colleagues': 1}

# Access node-layer pairs
nodes = list(network.get_nodes())       # [('Alice', 'friends'), ...]

```

#### Key attributes:

- `core_network` — The NetworkX graph storing all node-layer pairs and edges
- `layer_name_map` — Mapping from layer names to internal IDs
- `directed` — Whether the network is directed

### 4.3.2 Multilayer vs. Multiplex Mode

Py3plex supports two operational modes:

#### Multilayer (default):

- General multilayer networks with arbitrary node sets per layer
- No automatic inter-layer edges
- Use for heterogeneous networks (different node types)

```
# Heterogeneous network: authors and papers
network = multinet.multi_layer_network(network_type='multilayer')
network.add_edges([
    ['Alice', 'authors', 'Paper1', 'papers', 1],
    ['Paper1', 'papers', 'ICML', 'venues', 1],
], input_type="list")
```

#### Multiplex:

- Same node set in all layers
- Automatically creates identity (coupling) edges with type='coupling'
- Use when the same entities appear in all layers

```
# Social network: same people, different relationships
network = multinet.multi_layer_network(network_type='multiplex')
network.load_network('social.edges', input_type='multiplex_edges')

# Coupling edges are auto-created: (Alice, friends) <-> (Alice, colleagues)

# Get explicit edges only (exclude coupling)
explicit_edges = list(network.get_edges(multiplex_edges=False))
```

## 4.4 Relationship to NetworkX

### 4.4.1 Direct Access to NetworkX

Py3plex does not hide NetworkX—it exposes the underlying graph for direct manipulation:

```
import networkx as nx

# Access the graph directly
G = network.core_network

# Use any NetworkX function
betweenness = nx.betweenness_centrality(G)
communities = nx.community.louvain_communities(G)

# Modify the graph directly
G.nodes[('Alice', 'friends')]['age'] = 30
```

#### Why this matters:

- You can use **any NetworkX algorithm** on the multilayer network
- You can **extend py3plex** by writing functions that operate on `core_network`
- You don't need to learn a completely new API—if you know NetworkX, you know most of py3plex

### 4.4.2 NetworkX Interoperability

Convert between py3plex and NetworkX:

```
# From NetworkX to py3plex
import networkx as nx
```

```
G = nx.karate_club_graph()
network = multinet.multi_layer_network()
network.load_network_from_networkx(G, layer_name='social')

# From py3plex to NetworkX (extract a single layer)
friends_layer = network.get_layer_subgraph('friends')
```

This enables workflows that mix py3plex’s multilayer capabilities with NetworkX’s extensive algorithm library.

## 4.5 Core Modules

### 4.5.1 Algorithms

#### Statistics (py3plex/algorithms/statistics/)

Multilayer-specific metrics like degree distributions, layer overlap, and aggregation statistics.

#### Centrality (py3plex/algorithms/centrality/)

Centrality measures adapted for multilayer networks, including explainable centrality that breaks down scores by layer.

#### Community Detection (py3plex/algorithms/community\_detection/)

Multilayer Louvain, Infomap, and modularity-based methods.

#### Paths (py3plex/paths/)

Shortest paths, random walks, and flow algorithms that respect layer structure.

### 4.5.2 Dynamics

#### Dynamical Processes (py3plex/dynamics/)

OOP-style classes for epidemic models (SIS, SIR, SEIR), random walks, and custom dynamics. Each model has:

- `set_seed()` for reproducibility
- `run()` for execution
- `get_measure()` for extracting results

### 4.5.3 DSL and Query Language

#### Domain-Specific Language (py3plex/dsl/)

SQL-like queries for network analysis:

```
from py3plex.dsl import Q, L

result = (
    Q.nodes()
    .from_layers(L["friends"])
    .where(degree__gt=5)
    .compute("betweenness_centrality")
    .execute(network)
)
```

The DSL provides:

- **Builder API** — Chainable, type-hinted query construction
- **String syntax** — SQL-like queries as strings

- **EXPLAIN mode** — Query execution plans
- **Export** — Results to pandas, JSON, CSV

#### 4.5.4 Visualization

##### Visualization (py3plex/visualization/)

Publication-ready plots including:

- **Hairball plots** — 2D/3D force-directed layouts with layer separation
- **Matrix plots** — Supra-adjacency matrix visualization
- **Diagonal layouts** — Specialized for large multilayer networks

#### 4.5.5 I/O

##### Input/Output (py3plex/io/)

Support for multiple formats:

- **Edgelists** — Simple text format
- **GraphML** — XML-based format
- **Arrow/Parquet** — High-performance columnar format for large networks
- **JSON** — Flexible structured format

### 4.6 Design Principles in Practice

#### 4.6.1 1. Flexible Input

Multiple ways to accomplish the same task:

```
# Method 1: List format
network.add_edges([[ 'A', 'L1', 'B', 'L1', 1]], input_type="list")

# Method 2: Dict format (explicit)
network.add_edges([
    {
        'source': 'A', 'target': 'B',
        'source_type': 'L1', 'target_type': 'L1'
    }
])

# Method 3: Load from file
network.load_network("data.edgelist", input_type="edgelist")
```

#### 4.6.2 2. Lazy Evaluation

Expensive operations are computed only when needed:

```
# Network creation and edge addition are fast
network = multinet.multi_layer_network()
network.add_edges([...]) # No supra-adjacency matrix computed

# Matrix is computed only when requested
supra_adj = network.get_supra_adjacency_matrix() # Computed here
```



### 4.6.3 3. Graceful Degradation

The library handles edge cases and provides informative warnings:

- Missing layers → created automatically
- Empty networks → return sensible defaults
- Invalid parameters → clear error messages

### 4.6.4 4. Extensibility

Adding new algorithms is straightforward:

```
def my_custom_metric(network):
    """Custom multilayer metric."""
    G = network.core_network
    # Implement your algorithm using G
    return result

# Use immediately
score = my_custom_metric(network)
```

## 4.7 Why These Choices Matter

**NetworkX compatibility** means you can:

- Use hundreds of existing algorithms without modification
- Mix py3plex with other NetworkX-based tools
- Leverage a mature, well-documented ecosystem

**Node-layer pair representation** ensures:

- Unambiguous node identity across layers
- Efficient graph operations (hashing, lookups)
- Direct mapping to mathematical definitions

**Modular architecture** allows:

- Importing only needed functionality
- Easy testing and debugging
- Clean separation of concerns

**Multiple input methods** accommodate:

- Different data sources and formats
- User preferences and workflows
- Programmatic and interactive use

## 4.8 Limitations and Trade-offs

No design is perfect. Py3plex makes conscious trade-offs:

**Memory:**

The supra-adjacency matrix for large networks can be memory-intensive. Use sparse matrix formats (default) and avoid materializing the full matrix when possible.

**Performance:**

Some operations (e.g., cross-layer random walks) require iteration over node-layer pairs, which is slower than pure NetworkX on single-layer graphs.

**Coupling semantics:**

The automatic coupling in multiplex mode assumes identity edges. For more complex inter-layer relationships, use multilayer mode and add edges explicitly.

## 4.9 Summary

Py3plex is designed around:

1. **Node-layer pairs** as the fundamental unit
2. **NetworkX compatibility** for interoperability and extensibility
3. **Modular architecture** for flexibility
4. **Simple, practical APIs** for ease of use

These principles enable:

- Correct multilayer analysis (proper layer semantics)
- Efficient implementation (leverage NetworkX)
- Extensible design (add your own algorithms)
- Practical workflows (multiple input formats, visualization, DSL)

The following chapters will show how to use these design elements in practice: loading data, visualizing networks, and running multilayer-specific algorithms.

## 4.10 Further Reading

- NetworkX documentation: <https://networkx.org/documentation/stable/>
- Py3plex API reference: *Appendix E: Extended API and DSL Reference* (page 150)
- Code architecture: *Appendix A: Repository Layout and Scripts* (page 122)

## INSTALLATION AND GETTING STARTED

This chapter covers installing py3plex and running your first multilayer network analysis. We provide a minimal quick-start example followed by installation details for different use cases.

### DSL Quick Start

After installation, try the DSL for instant network exploration:

```
from py3plex.core import multinet
from py3plex.dsl import Q, L

# Create a simple network
network = multinet.multi_layer_network()
network.add_edges([
    ['Alice', 'friends', 'Bob', 'friends', 1],
    ['Bob', 'friends', 'Carol', 'friends', 1],
], input_type="list")

# Query it with DSL
result = (
    Q.nodes()
    .compute("degree")
    .order_by("-degree")
    .execute(network)
)
print(result.to_pandas())
```

DSL makes network analysis intuitive from day one!

## 5.1 Quick Install

For most users, installation is straightforward:

```
pip install py3plex
```

This installs py3plex with core dependencies (NetworkX, NumPy, SciPy, pandas, matplotlib).

**Verify installation:**

```
import py3plex
print(py3plex.__version__) # Should print 1.x
```

## 5.2 System Requirements

**Python:** 3.8 or higher (tested on 3.8, 3.9, 3.10, 3.11, 3.12)

**Platforms:** Linux, macOS, Windows

**Core dependencies** (installed automatically):

- NetworkX (2.8) — Graph data structures and algorithms
- NumPy (1.22) — Numerical computing and array operations
- SciPy (1.8) — Sparse matrices and scientific computing
- pandas (1.4) — Data manipulation and analysis
- matplotlib (3.5) — Visualization and plotting
- scikit-learn (1.0) — Machine learning utilities

## 5.3 Hello Multilayer Network

Create and analyze a multilayer network in 30 seconds:

```
from py3plex.core import multinet

# Create network
network = multinet.multi_layer_network()

# Add edges: [source, source_layer, target, target_layer, weight]
network.add_edges([
    ['Alice', 'friends', 'Bob', 'friends', 1],
    ['Bob', 'friends', 'Carol', 'friends', 1],
    ['Alice', 'colleagues', 'Bob', 'colleagues', 1],
    ['Bob', 'colleagues', 'Dave', 'colleagues', 1],
], input_type="list")

# Display statistics
network.basic_stats()
```

**Output:**

```
Number of nodes: 6
Number of edges: 4
Number of unique nodes (as node-layer tuples): 6
Number of unique node IDs (across all layers): 4
Nodes per layer:
  Layer 'friends': 3 nodes
  Layer 'colleagues': 3 nodes
```

**Key insight:** The network has 6 node-layer pairs (Alice-friends, Alice-colleagues, Bob-friends, Bob-colleagues, Carol-friends, Dave-colleagues) but only 4 unique people.

### 5.3.1 Visualize the Network

```
from py3plex.visualization.multilayer import draw_multilayer_default

# Simple visualization
draw_multilayer_default(network.get_layers(), display=True)
```

This creates a force-directed layout with nodes colored by layer.

### 5.3.2 Basic Analysis

```
from py3plex.algorithms.statistics import multilayer_statistics as mls

# Layer density (how connected is each layer?)
print(f"Friends density: {mls.layer_density(network, 'friends'):.3f}")
# Output: Friends density: 0.667 (2 of 3 possible edges exist)

# Node activity (fraction of layers a node appears in)
print(f"Bob's activity: {mls.node_activity(network, 'Bob'):.3f}")
# Output: Bob's activity: 1.000 (appears in both layers)
```

### 5.3.3 Query with DSL

Use SQL-like queries to explore the network:

```
from py3plex.dsl import execute_query

# Find high-degree nodes
result = execute_query(network, 'SELECT nodes WHERE degree > 1')
print(f"Found {result['count']} nodes with degree > 1")

# Get all nodes in a specific layer
result = execute_query(network, 'SELECT nodes WHERE layer="friends"')
```

The DSL (covered in Part III) provides a powerful way to filter, compute, and analyze multilayer networks without writing explicit loops.

## 5.4 Installation Options

### 5.4.1 Development Installation

For contributors or to access the latest features:

```
git clone https://github.com/SkBlaz/py3plex.git
cd py3plex
pip install -e .
```

The `-e` flag installs in editable mode—changes to source code are immediately available.

**For development with testing/linting tools:**

```
git clone https://github.com/SkBlaz/py3plex.git
cd py3plex
```

```
make setup      # Create virtual environment
make dev-install # Install with dev dependencies
```

This installs pytest, black, ruff, mypy, and sphinx for development workflows.

### 5.4.2 Docker Installation

For a containerized environment with all dependencies:

```
# Clone repository
git clone https://github.com/SkBlaz/py3plex.git
cd py3plex

# Build image
docker build -t py3plex:latest .

# Run commands
docker run --rm py3plex:latest --version
```

#### Benefits:

- No Python setup required
- Consistent environment across systems
- Isolated from system Python

### 5.4.3 Optional Dependencies

Py3plex supports optional feature sets:

```
# Advanced community detection (Infomap)
pip install py3plex[infomap]

# Extra algorithms (Louvain, cdlib)
pip install py3plex[algos]

# Advanced visualization (Plotly, igraph)
pip install py3plex[viz]

# High-performance I/O (Arrow/Parquet)
pip install py3plex[arrow]

# Install multiple extras
pip install py3plex[infomap,viz,algos,arrow]
```

### 5.4.4 Virtual Environments

We strongly recommend using virtual environments:

#### Using venv:

```
python3 -m venv py3plex-env
source py3plex-env/bin/activate # Linux/macOS
# py3plex-env\Scripts\activate  # Windows
pip install py3plex
```

Using conda:

```
conda create -n py3plex python=3.10
conda activate py3plex
pip install py3plex
```

## 5.5 Key Concepts

Before proceeding, understand these fundamental concepts:

### 5.5.1 Node-Layer Pairs

In py3plex, a node is always associated with a layer. The tuple (node\_id, layer\_id) is the fundamental unit.

- ('Alice', 'friends') is different from ('Alice', 'colleagues')
- This allows the same logical entity to have different properties and connections in different contexts

Example:

```
# Access nodes as (node_id, layer_id) tuples
for node in network.get_nodes():
    print(node) # ('Alice', 'friends'), ('Bob', 'friends'), ...
```

### 5.5.2 NetworkX Compatibility

Py3plex uses NetworkX as its underlying graph representation:

```
import networkx as nx

# Direct access to the NetworkX graph
G = network.core_network

# Use any NetworkX algorithm
betweenness = nx.betweenness centrality(G)

# Modify directly
G.nodes[('Alice', 'friends')]['age'] = 30
```

This means:

- Any NetworkX algorithm works on py3plex networks
- You can mix py3plex and NetworkX functions freely
- Learning curve is minimal if you already know NetworkX

### 5.5.3 Input Formats

Py3plex supports multiple edge input formats:

**List format** (used in examples above):

```
network.add_edges([
    ['Alice', 'friends', 'Bob', 'friends', 1],
], input_type="list")
```

**Dictionary format** (explicit, Pythonic):

```
network.add_edges([{
    'source': 'Alice',
    'source_type': 'friends',
    'target': 'Bob',
    'target_type': 'friends',
    'weight': 1
}])
```

**File loading** (for larger networks):

```
# Edgelist format
network.load_network("data.edgelist", input_type="edgelist")

# GraphML, JSON, Arrow, etc.
# See :ref:`data-loading-chapter` for details
```

## 5.6 Common Issues

### 5.6.1 Issue: “No module named ‘py3plex’”

**Solution:** Ensure py3plex is installed in the active Python environment:

```
pip install py3plex
```

Verify which Python interpreter you’re using:

```
which python # Linux/macOS
where python # Windows
```

### 5.6.2 Issue: Import errors for optional dependencies

**Solution:** Install the relevant extra:

```
pip install py3plex[infomap] # For Infomap
pip install py3plex[viz]     # For Plotly
```

### 5.6.3 Issue: Permission denied on Linux/macOS

**Solution:** Use a virtual environment (recommended) or install with `--user`:

```
pip install --user py3plex
```

## 5.7 License Considerations

Py3plex core is released under the **MIT License**, which allows commercial and non-commercial use without restrictions.



### 5.7.1 Optional AGPL Components

**Important:** Some optional features include code licensed under **AGPLv3** (a copyleft license):

- **Infomap community detection** (`py3plex[infomap]`)

If you install and use these features, your application may be subject to AGPLv3 requirements:

- You must make your application's source code available if you distribute it
- Modified versions must also be released under AGPLv3

**How to avoid AGPLv3:**

1. Don't install extras with AGPL components (don't use `pip install py3plex[infomap]`)
2. Use alternative algorithms (Louvain, Label Propagation) instead of Infomap
3. Check the license of any extra before installing

**Default installation** (`pip install py3plex`) includes only MIT-licensed code.

## 5.8 Verifying Installation

Run a self-test to confirm everything works:

```
from py3plex.core import multinet
from py3plex.algorithms.statistics import multilayer_statistics as mls

# Create test network
network = multinet.multi_layer_network()
network.add_edges([
    ['A', 'L1', 'B', 'L1', 1],
    ['B', 'L1', 'C', 'L1', 1],
], input_type="list")

# Test basic operations
assert network.get_number_of_nodes() == 3
assert mls.layer_density(network, 'L1') > 0

print("✓ py3plex is working correctly")
```

## 5.9 Next Steps

Now that you have py3plex installed and understand the basics:

- *Data Loading and Representation* (page 32) — Learn about data loading, supported formats, and best practices for representing multilayer networks
- *Visualization and Exploration* (page 42) — Explore visualization techniques for multilayer networks
- *Core Algorithms: Communities, Centrality, Dynamics* (page 48) — Apply core algorithms: community detection, centrality measures, and dynamics

**For immediate exploration:**

Browse the `examples/` directory in the repository for 50+ working examples covering various use cases.

## 5.10 Summary

This chapter covered:

1. **Quick install** — `pip install py3plex`
2. **Hello World** — Create a multilayer network in 30 seconds
3. **Basic analysis** — Statistics, visualization, and DSL queries
4. **Installation options** — Development, Docker, optional dependencies
5. **Key concepts** — Node-layer pairs, NetworkX compatibility, input formats

With py3plex installed, you're ready to analyze multilayer networks. The next chapter covers loading real data and representing complex multilayer structures.

## DATA LOADING AND REPRESENTATION

This chapter covers how to load multilayer networks from various data sources, choose appropriate formats, and represent complex network structures correctly.

### DSL Tip: Validate Data After Loading

Use DSL to quickly validate loaded data:

```
from py3plex.dsl import Q, L

# Check layer sizes
for layer in network.get_layers():
    count = Q.nodes().from_layers(L[layer]).execute(network).count
    print(f"{layer}: {count} nodes")

# Find potential data issues
isolated = Q.nodes().where(degree=0).execute(network)
if isolated.count > 0:
    print(f"Warning: {isolated.count} isolated nodes")

# Verify high-degree nodes make sense
hubs = (
    Q.nodes()
    .where(degree__gt=20)
    .compute("degree")
    .execute(network)
)
print(f"Hubs (degree > 20): {hubs.count}")
```

Quick validation catches data issues early!

## 6.1 Data Loading Basics

### 6.1.1 Multiple Input Methods

Py3plex supports several ways to create multilayer networks:

**1. Direct edge addition** (for programmatic construction):

```
from py3plex.core import multinet

network = multinet.multi_layer_network()
```

```
network.add_edges([
    ['Alice', 'friends', 'Bob', 'friends', 1],
    ['Bob', 'friends', 'Carol', 'friends', 1],
], input_type="list")
```

## 2. File loading (for external data):

```
# Load from file
network = multinet.multi_layer_network()
network.load_network("data.edgelist", input_type="edgelist")
```

## 3. From NetworkX (for integration):

```
import networkx as nx

G = nx.karate_club_graph()
network = multinet.multi_layer_network()
network.load_network_from_networkx(G, layer_name='social')
```

## 6.2 Edgelist Format

The **edgelist** format is the simplest and most common:

```
# File: network.edgelist
Alice friends Bob friends 1.0
Bob friends Carol friends 1.0
Alice colleagues Bob colleagues 0.8
```

**Format:** source source\_layer target target\_layer weight

**Loading:**

```
network = multinet.multi_layer_network()
network.load_network("network.edgelist", input_type="edgelist")
```

**Best practices:**

- Use consistent node identifiers across layers
- Separate fields with spaces or tabs
- Include weights (default to 1.0 if omitted)
- Comment lines start with #

## 6.3 Dictionary Format

For programmatic construction, the dictionary format is most explicit:

```
network.add_edges([
    {
        'source': 'Alice',
        'source_type': 'friends',
        'target': 'Bob',
        'target_type': 'friends',
```

```

        'weight': 1.0,
        'timestamp': '2023-01-15' # Optional attributes
    },
    {
        'source': 'Bob',
        'source_type': 'colleagues',
        'target': 'Carol',
        'target_type': 'colleagues',
        'weight': 0.8
    }
]
])

```

**Advantages:**

- Self-documenting (field names explicit)
- Supports arbitrary edge attributes
- Type-safe (Python dicts)
- Pythonic and readable

## 6.4 Modern I/O System

Py3plex provides a modern I/O system (`py3plex.io`) for high-performance serialization:

### 6.4.1 Supported Formats

| Format  | Extension | Best For                          | Trade-offs           |
|---------|-----------|-----------------------------------|----------------------|
| JSON    | .json     | Human-readable, small networks    | Slower, larger files |
| JSONL   | .jsonl    | Streaming, large networks         | Not human-friendly   |
| CSV     | .csv      | Spreadsheet tools, manual editing | Limited attributes   |
| Arrow   | .arrow    | High performance, large networks  | Requires pyarrow     |
| Parquet | .parquet  | Storage, compression, archiving   | Requires pyarrow     |

### 6.4.2 Reading and Writing

```

from py3plex.io import read, write, MultiLayerGraph

# Write (auto-detects format from extension)
write(network, 'network.json')
write(network, 'network.arrow')
write(network, 'network.parquet')

# Read (auto-detects format)
graph = read('network.json')
graph = read('network.arrow')

```

```
# Specify format explicitly
write(network, 'myfile.dat', format='json')
graph = read('myfile.dat', format='parquet')
```

### 6.4.3 Apache Arrow Format (Recommended for Large Networks)

Arrow provides 2-3x faster I/O and better compression:

```
# Install Arrow support
pip install 'py3plex[arrow]'
```

```
from py3plex.io import read, write

# Feather format (fast, uncompressed)
write(graph, 'network.arrow')
graph = read('network.arrow')

# Parquet format (compressed, archival)
write(graph, 'network.parquet')
graph = read('network.parquet')
```

**Performance comparison** (1000 nodes, 5000 edges):

| Format  | Write Time | Read Time | File Size |
|---------|------------|-----------|-----------|
| Arrow   | 0.016s     | 0.008s    | 0.46 MB   |
| Parquet | 0.020s     | 0.010s    | 0.35 MB   |
| JSON    | 0.046s     | 0.030s    | 1.09 MB   |

**When to use Arrow:**

- Large networks (>10k nodes)
- Performance-critical pipelines
- Interoperability with pandas, Spark, DuckDB
- Production data workflows

**When to use JSON:**

- Small networks (<1k nodes)
- Human readability required
- Debugging and manual editing
- Maximum compatibility

### 6.4.4 CSV with Sidecars

CSV format supports optional sidecar files for attributes:

```
# Write with sidecars
write(graph, 'edges.csv', write_sidecars=True)
# Creates: edges.csv, nodes.csv, layers.csv
```

```
# Read with sidecars
graph = read('edges.csv',
            nodes_file='nodes.csv',
            layers_file='layers.csv')
```

## 6.5 Data Validation and Best Practices

### 6.5.1 Always Verify After Loading

After loading external data, always verify structure:

```
network.load_network("data.edgelist", input_type="edgelist")

# Verify structure
print(f"Layers: {network.get_layers()}")
print(f"Nodes per layer: {network.get_number_of_nodes_per_layer()}")

# Check for unexpected layers
expected_layers = {'friends', 'colleagues'}
actual_layers = set(network.get_layers())
if actual_layers != expected_layers:
    print(f"Warning: unexpected layers {actual_layers - expected_layers}")

# Basic statistics
network.basic_stats()
```

### 6.5.2 Consistent Node Identifiers

**Rule:** The same entity must have the same ID across all layers.

**Good:**

```
# Alice has the same ID in both layers
network.add_edges([
    ['Alice', 'friends', 'Bob', 'friends', 1],
    ['Alice', 'colleagues', 'Carol', 'colleagues', 1],
], input_type="list")
```

**Bad:**

```
# Alice's ID differs across layers-breaks multiplex structure
network.add_edges([
    ['alice_social', 'friends', 'Bob', 'friends', 1],
    ['Alice_Work', 'colleagues', 'Carol', 'colleagues', 1],
], input_type="list")
```

### 6.5.3 Naming Conventions

**Layer names:**

- Use descriptive names: 'coauthor', 'twitter', not 'layer1', 'l2'
- Lowercase with underscores: 'social\_media', not 'SocialMedia'

- Avoid special characters

#### Node IDs:

- Use stable, meaningful identifiers (user IDs, DOIs, names)
- Avoid auto-generated IDs that change across runs
- Preserve external IDs when loading from databases

## 6.5.4 Metadata and Attributes

Store metadata as node/edge attributes:

```
# Add node attributes
network.core_network.nodes[('Alice', 'friends')]['age'] = 30
network.core_network.nodes[('Alice', 'friends')]['country'] = 'USA'

# Add edge attributes
network.add_edges([
    ['Alice', 'friends', 'Bob', 'friends', 1, {'type': 'close', 'since': 2018}]
], input_type="list")
```

#### Recommended practices:

- Use consistent attribute names across layers
- Store timestamps as ISO format strings: '2023-01-15T10:30:00Z'
- Use numeric types for attributes that will be analyzed
- Document attribute semantics in code comments

## 6.6 Representing Different Network Types

### 6.6.1 Multiplex Networks (Same Nodes Across Layers)

For networks where the same entities appear in all layers:

```
network = multinet.multi_layer_network(network_type='multiplex')

# Load data
network.load_network('social.edges', input_type='multiplex_edges')

# Coupling edges are automatically created
# (Alice, friends) <-> (Alice, colleagues)

# Get explicit edges only (exclude coupling)
explicit_edges = list(network.get_edges(multiplex_edges=False))
```

#### When to use:

- Same people across multiple social platforms
- Same cities in transportation modes (air, rail, road)
- Same proteins in different tissue types



## 6.6.2 Heterogeneous Networks (Different Node Types)

For networks with different entity types per layer:

```
network = multinet.multi_layer_network(network_type='multilayer')

# Different node types
network.add_edges([
    ['Alice', 'authors', 'Paper1', 'papers', 1],
    ['Bob', 'authors', 'Paper1', 'papers', 1],
    ['Paper1', 'papers', 'ICML', 'venues', 1],
], input_type="list")
```

**When to use:**

- Academic networks (authors, papers, venues)
- E-commerce (users, products, sellers)
- Biomedical (drugs, diseases, targets)

## 6.6.3 Temporal Networks (Time-Sliced Layers)

For networks that evolve over time:

```
network = multinet.multi_layer_network()

# Time windows as layers
network.add_edges([
    ['Alice', '2020', 'Bob', '2020', 1],
    ['Alice', '2021', 'Bob', '2021', 1],
    ['Bob', '2021', 'Carol', '2021', 1],
], input_type="list")
```

**Best practices:**

- Use consistent time granularity (years, months, days)
- Layer names should be sortable: '2020-01', '2020-02', ...
- Add temporal edges connecting adjacent time slices if modeling evolution

## 6.7 Converting Between Formats

### 6.7.1 NetworkX to Py3plex

```
import networkx as nx
from py3plex.core import multinet

# Create NetworkX graph
G = nx.karate_club_graph()

# Convert to py3plex
network = multinet.multi_layer_network()
network.load_network_from_networkx(G, layer_name='social')
```

## 6.7.2 Py3plex to NetworkX

```
# Extract single layer as NetworkX graph
friends_layer = network.get_layer_subgraph('friends')

# Or access the full graph directly
full_graph = network.core_network # MultiGraph or MultiDiGraph
```

## 6.7.3 Pandas DataFrame to Py3plex

```
import pandas as pd

# Load edges from DataFrame
df = pd.read_csv('edges.csv')
# Columns: source, source_layer, target, target_layer, weight

# Convert to list of lists
edges = df[['source', 'source_layer', 'target', 'target_layer', 'weight']].values.tolist()

network = multinet.multi_layer_network()
network.add_edges(edges, input_type="list")
```

## 6.8 Common Data Loading Patterns

### 6.8.1 Pattern 1: Load from Multiple Files

```
network = multinet.multi_layer_network()

# Load different layers from different files
for layer_name, filename in [('friends', 'friends.txt'),
                             ('colleagues', 'colleagues.txt')]:
    with open(filename) as f:
        for line in f:
            source, target, weight = line.strip().split()
            network.add_edges([
                [source, layer_name, target, layer_name, float(weight)]
            ], input_type="list")
```

### 6.8.2 Pattern 2: Load from Database

```
import sqlite3

conn = sqlite3.connect('network.db')
cursor = conn.execute(
    "SELECT source, source_layer, target, target_layer, weight FROM edges"
)

network = multinet.multi_layer_network()
edges = [[row[0], row[1], row[2], row[3], row[4]] for row in cursor]
network.add_edges(edges, input_type="list")
```

### 6.8.3 Pattern 3: Incremental Loading (Large Networks)

```
network = multinet.multi_layer_network()

# Load in batches to manage memory
BATCH_SIZE = 10000

with open('large_network.edgelist') as f:
    batch = []
    for line in f:
        parts = line.strip().split()
        batch.append(parts)

        if len(batch) >= BATCH_SIZE:
            network.add_edges(batch, input_type="list")
            batch = []

# Add remaining edges
if batch:
    network.add_edges(batch, input_type="list")
```

## 6.9 Troubleshooting

### 6.9.1 Issue: Duplicate Edges

**Symptom:** More edges than expected after loading.

**Solution:** Check for duplicate entries in source data:

```
# Count edge multiplicity
edge_counts = {}
for edge in network.get_edges():
    edge_counts[edge] = edge_counts.get(edge, 0) + 1

duplicates = {e: c for e, c in edge_counts.items() if c > 1}
if duplicates:
    print(f"Found {len(duplicates)} duplicate edges")
```

### 6.9.2 Issue: Unexpected Layers

**Symptom:** Layers you didn't expect appear in the network.

**Solution:** Verify layer names in source data:

```
expected = {'friends', 'colleagues'}
actual = set(network.get_layers())

if actual != expected:
    print(f"Unexpected layers: {actual - expected}")
    print(f"Missing layers: {expected - actual}")
```

### 6.9.3 Issue: Node ID Mismatches

**Symptom:** Same entity appears as different nodes across layers.

**Solution:** Normalize node IDs before loading:

```
def normalize_id(node_id):
    """Normalize node identifiers."""
    return str(node_id).strip().lower()

# Apply during loading
edges = [[normalize_id(s), sl, normalize_id(t), tl, w]
         for s, sl, t, tl, w in raw_edges]
network.add_edges(edges, input_type="list")
```

## 6.10 Summary

This chapter covered:

1. **Loading methods** — Direct addition, files, NetworkX import
2. **Data formats** — Edgelist, dictionary, JSON, CSV, Arrow/Parquet
3. **Best practices** — Consistent IDs, validation, metadata storage
4. **Network types** — Multiplex, heterogeneous, temporal
5. **Common patterns** — Multi-file loading, databases, incremental loading

**Key recommendations:**

- Use **Arrow/Parquet** for large networks (>10k nodes)
- Use **JSON** for small networks and debugging
- **Always verify** structure after loading
- Use **consistent node IDs** across layers
- Store **metadata as attributes** for richer analysis

The next chapter covers visualization techniques for exploring multilayer network structure.

## 6.11 Further Reading

- Arrow format specification: <https://arrow.apache.org/docs/>
- NetworkX I/O reference: <https://networkx.org/documentation/stable/reference/readwrite/>
- *Core Algorithms: Communities, Centrality, Dynamics* (page 48) for analysis after loading

## VISUALIZATION AND EXPLORATION

Multilayer networks present unique visualization challenges: how do you clearly show multiple relationship types while preserving the overall structure? This chapter covers py3plex's visualization capabilities, from quick exploratory plots to publication-ready figures.

### 7.1 Overview

Visualizing multilayer networks requires balancing several concerns:

- **Clarity:** Individual layers must be distinguishable
- **Structure:** Cross-layer connections should be visible
- **Scale:** Techniques must work for networks of varying sizes (10 to 10,000+ nodes)
- **Purpose:** Exploratory plots need different settings than publication figures

py3plex provides three main visualization approaches:

1. **Static multilayer plots** — Show all layers simultaneously with customizable layouts
2. **Matrix visualizations** — Display the supra-adjacency matrix structure
3. **Layer-specific views** — Examine individual layers in detail

### 7.2 Quick Start

#### 7.2.1 Basic Multilayer Visualization

```
from py3plex.core import multinet
from py3plex.visualization.multilayer import draw_multilayer_default

# Load network
network = multinet.multi_layer_network()
network.load_network("network.csv", input_type="multiedgelist")

# Visualize with defaults
draw_multilayer_default(
    network.get_layers(), # Returns dict of layer graphs
    display=True,
    labels=True
)
```

This produces a circular layout with each layer shown in a different color.

**API Note: Input Format**

`draw_multilayer_default` expects a dict or list of NetworkX graphs. Always use `network.get_layers()` to get the properly formatted dict of layer graphs. This method handles layout computation and layer separation automatically.

## 7.3 Preset Visualization Modes

Py3plex provides three preset modes optimized for different network scales.

### 7.3.1 Minimal Mode (Large Networks >1000 nodes)

Optimized for networks where detail isn't critical and performance matters:

```
# Large network preset
draw_multilayer_default(
    network.get_layers(),
    node_size=5,                # Small nodes
    labels=False,              # No labels (too cluttered)
    edge_size=0.5,             # Thin edges
    alphalevel=0.3,            # Transparent edges
    background_shape="circle",
    display=True,
    remove_isolated_nodes=True
)
```

**Use cases:** Large social networks, overview visualizations, pattern detection at macro level.

**Advantages:** Fast rendering, reduced clutter, shows overall structure.

### 7.3.2 Balanced Mode (Medium Networks 100-1000 nodes)

Default settings that work well for most networks:

```
# Balanced preset (this is the default)
draw_multilayer_default(
    network.get_layers(),
    node_size=10,              # Medium nodes
    labels=True,               # Show layer labels
    edge_size=1.0,             # Normal edges
    alphalevel=0.13,           # Semi-transparent
    background_shape="circle",
    networks_color="colorblind_safe",
    display=True
)
```

**Use cases:** Most research networks, exploratory analysis, publication figures with moderate detail.

**Advantages:** Good readability, reasonable performance, suitable for most publications.

### 7.3.3 Dense Mode (Small Networks <100 nodes)

Maximum detail for small networks where every node matters:

```
# Dense preset for detailed examination
draw_multilayer_default(
    network.get_layers(),
    node_size=20,           # Large nodes
    labels=True,
    node_labels=True,      # Show node IDs
    node_font_size=10,
    scale_by_size=True,    # Scale by degree
    edge_size=2.0,         # Thick edges
    alphalevel=0.8,        # Mostly opaque
    background_shape="rectangle",
    display=True
)
```

**Use cases:** Small case studies, detailed node-level analysis, high-quality publication figures.

**Advantages:** Maximum detail, clear node identification, professional appearance.

## 7.4 Layout Options

### 7.4.1 Circular Layout (Default)

Arranges layers in a circle, good for showing inter-layer connections:

```
draw_multilayer_default(
    network.get_layers(),
    background_shape="circle",
    rectanglex=1.0, # Circle radius
    rectangley=1.0
)
```

**Best for:** 2-10 layers, symmetric interactions, publication figures.

### 7.4.2 Rectangular Layout

Arranges layers in a grid, good for many layers or hierarchical structures:

```
draw_multilayer_default(
    network.get_layers(),
    background_shape="rectangle",
    rectanglex=2.0, # Width
    rectangley=1.0 # Height
)
```

**Best for:** Many layers (>10), hierarchical networks, time-series data, wide figures.

## 7.5 Auto-Scaling Features

### 7.5.1 Node Sizing by Degree

Automatically scale node sizes by their degree:

```
draw_multilayer_default(
    network.get_layers(),
    scale_by_size=True,      # Enable auto-scaling
    node_size=10             # Base size
)
```

Hub nodes become larger, making them easy to identify.

## 7.5.2 Color Assignment

Py3plex provides several color palette options:

```
# Automatic colors (uses default palette)
draw_multilayer_default(
    network.get_layers(),
    networks_color="auto"
)

# Custom palette
draw_multilayer_default(
    network.get_layers(),
    networks_color=["#FF6B6B", "#4ECDC4", "#45B7D1"]
)
```

**Available palettes** (from `py3plex.config`):

- `colorblind_safe`: 8 colors safe for colorblind viewers (default)
- `wong`: 7-color Wong palette<sup>1</sup> (optimized for color vision deficiency)
- `tol_bright`: 7 bright colors
- `rainbow`: Full spectrum colors (not recommended for accessibility)

**Recommendation:** Use `colorblind_safe` or `wong` palettes for publications and presentations to ensure accessibility for all viewers, including those with color vision deficiency.

## 7.6 Matrix Visualizations

### 7.6.1 Supra-Adjacency Matrix

Visualize the full supra-adjacency matrix structure:

```
# Display matrix view
network.visualize_matrix({"display": True})
```

This shows the block structure: diagonal blocks are intra-layer edges, off-diagonal blocks are inter-layer edges.

**Use cases:** Understanding network structure, debugging layer connections, small networks only (<500 nodes).

<sup>1</sup> Wong, B. (2011). Points of view: Color blindness. *Nature Methods*, 8(6), 441. doi:10.1038/nmeth.1618



## 7.7 Exploration Workflows

### 7.7.1 Layer Views

Examine individual layers:

```
# Extract and visualize a single layer
layer_subgraph = network.get_layer("social")

import networkx as nx
import matplotlib.pyplot as plt

nx.draw(layer_subgraph, with_labels=True)
plt.show()
```

### 7.7.2 Cross-Layer Pattern Analysis

Use the DSL to filter and visualize subsets:

```
from py3plex.dsl import Q, L

# Find high-degree nodes across specific layers
result = (
    Q.nodes()
    .from_layers(L["social"] + L["professional"])
    .where(degree__gt=10)
    .execute(network)
)

# Extract subgraph for visualization
high_degree_nodes = list(result.node_ids)
subgraph = network.core_network.subgraph(high_degree_nodes)
```

### 7.7.3 Node Neighborhoods

Extract ego networks (neighborhood around a specific node):

```
import networkx as nx

# Get 2-hop neighborhood around 'Alice'
alice_ego = nx.ego_graph(network.core_network, ('Alice', 'social'), radius=2)

# Visualize
nx.draw(alice_ego, with_labels=True)
```

## 7.8 Performance Considerations

Visualization performance depends heavily on network size:

- **<100 nodes:** All visualization modes work well
- **100-1000 nodes:** Use balanced or minimal mode; avoid node labels
- **1000-5000 nodes:** Use minimal mode; rendering may be slow

- **>5000 nodes:** Static visualizations become impractical; use matrix view or export to specialized tools

**Tips for large networks:**

1. Use `remove_isolated_nodes=True` to reduce clutter
2. Set `alphalevel=0.1` or lower for edge transparency
3. Disable labels: `labels=False, node_labels=False`
4. Consider sampling: visualize only high-degree nodes or a random subset

## 7.9 Summary

Key visualization capabilities in py3plex:

- **Three preset modes** (minimal, balanced, dense) for different network scales
- **Flexible layouts** (circular, rectangular) for different structures
- **Auto-scaling** features adapt to network properties
- **Matrix visualizations** show supra-adjacency structure
- **Layer-specific views** enable detailed exploration

Choose visualization settings based on your network size and purpose. For quick exploration, use defaults. For publications, use dense mode with custom colors and layouts.

**Next chapter:** Core algorithms for multilayer analysis (community detection, centrality, dynamics)

## 7.10 References

## CORE ALGORITHMS: COMMUNITIES, CENTRALITY, DYNAMICS

This chapter covers py3plex's three major algorithm families for multilayer network analysis: community detection, centrality measures, and dynamics/spreading processes.

### DSL Tip: Streamline Algorithm Workflows

The DSL simplifies many algorithmic workflows:

```
from py3plex.dsl import Q, L

# Quick centrality analysis
top_central = (
    Q.nodes()
    .from_layers(L["social"])
    .compute("betweenness Centrality", "pagerank", "degree")
    .order_by("-betweenness Centrality")
    .limit(20)
    .execute(network)
)

# Multi-layer comparison
for layer in ["social", "work"]:
    result = (
        Q.nodes()
        .from_layers(L[layer])
        .compute("betweenness Centrality")
        .execute(network)
    )
    print(f"{layer}: avg BC = {sum(result.measures['betweenness Centrality'].values())} / result.count : ")
```

See *Introduction to the Py3plex DSL* (page 56) for comprehensive DSL coverage!

## 8.1 Overview

py3plex provides three major algorithm families for analyzing multilayer networks:

1. **Community Detection** — Find groups of nodes that are densely connected within and across layers. Algorithms include Louvain, Infomap, Label Propagation, and multilayer modularity optimization.
2. **Centrality Measures** — Identify important nodes using degree, betweenness, closeness, PageRank, eigenvector centrality, and 30+ other measures adapted for multilayer structure.

3. **Dynamics and Processes** — Simulate epidemic spread (SIR, SIS), random walks, and diffusion processes that leverage multilayer connectivity patterns.

These algorithms account for both intra-layer (within-layer) and inter-layer (cross-layer) connections, revealing insights that single-layer analysis misses.

## 8.2 Community Detection

Community detection identifies groups of nodes that are more densely connected to each other than to the rest of the network. In multilayer networks, communities can span multiple layers, accounting for both intra-layer and inter-layer structure.

### 8.2.1 Multilayer Modularity

The multilayer modularity quality function extends Newman-Girvan modularity to account for both intra-layer and inter-layer edges:

$$Q = \frac{1}{2\mu} \sum_{ijrs} \left[ A_{ijr} - \gamma_r \frac{k_{ir}k_{jr}}{2m_r} \right] \delta(g_i, g_j) \delta_{rs} + \frac{1}{2\mu} \sum_{ijrs} C_{ijrs} \delta(g_i, g_j)$$

Where:

- $A_{ijr}$  is the adjacency matrix in layer  $r$
- $k_{ir}$  is the degree of node  $i$  in layer  $r$
- $\gamma_r$  is the resolution parameter for layer  $r$
- $C_{ijrs}$  represents inter-layer coupling
- $\delta(g_i, g_j)$  is 1 if nodes  $i$  and  $j$  are in the same community

**Implementation:**

```
from py3plex.algorithms.community_detection import community_louvain

# Detect communities using Louvain on the supra-graph representation
# Note: This applies standard Louvain to the flattened multilayer structure
communities = community_louvain.best_partition(network.core_network)

# Print community assignments
for node, comm_id in communities.items():
    print(f"Node {node} -> Community {comm_id}")
```

#### Implementation Note

The implementation shown applies standard Louvain modularity optimization to the **supra-graph representation** of the multilayer network (`network.core_network`), where all layers are combined into a single NetworkX MultiGraph. This is a practical approximation that works well for many use cases.

**True multilayer modularity optimization** (Mucha et al. 2010) with explicit inter-layer coupling terms requires specialized solvers. For such optimization, consider using external tools like GenLouvain (MATLAB) or multilayer-specific implementations, then importing results back into py3plex.

### 8.2.2 Algorithms Available

py3plex supports several community detection algorithms:

- **Louvain** — Fast modularity optimization,  $O(n \log n)$ . Best for most use cases (100-100K nodes).
- **Infomap** — Flow-based detection using random walk dynamics. Optional dependency (see below).
- **Label Propagation** — Semi-supervised approach with known seed communities. Linear time  $O(m + n)$ .

### 8.2.3 Infomap Integration

Infomap is an optional community detection algorithm based on information-theoretic compression of random walks. It is not included in the default py3plex installation due to licensing (AGPL).

**Installation:**

```
pip install py3plex[infomap]
```

**Usage:**

```
from py3plex.algorithms.community_detection import infomap_communities

# Run Infomap on network
communities = infomap_communities(network.core_network)

# communities is a dict: {node: community_id}
```

**Important notes:**

- Infomap is licensed under AGPLv3 (copyleft license) - see [Installation and Getting Started](#) (page 24) for license implications
- If you don't need Infomap specifically, use Louvain or Label Propagation instead
- Infomap tends to find smaller, more fine-grained communities than Louvain

**Time Complexity Summary:**

- Louvain:  $O(n \log n)$  typical,  $O(n^2)$  worst case
- Label Propagation:  $O(m + n)$  per iteration
- Infomap:  $O(m \log n)$  typical

### 8.2.4 Choosing a Community Detection Method

**Selection guidelines:**

- **Network size < 10,000 nodes:** Use Louvain (fast and accurate)
- **Network size > 100,000 nodes:** Use Label Propagation (linear time) or streaming Louvain
- **Strong inter-layer coupling:** Use multilayer modularity for true cross-layer communities
- **Known seed communities:** Use Label Propagation with seeds
- **Flow-based interpretation needed:** Use Infomap (installation required)

**Interpretability considerations:**

- Louvain and multilayer modularity produce hierarchical community structure
- Infomap optimizes for information compression, emphasizing flow patterns

- Label Propagation is less deterministic but handles semi-supervised scenarios

## 8.3 Centrality Measures

Centrality measures identify important nodes in the network. py3plex provides direct DSL access to core centrality measures (degree, betweenness, closeness, eigenvector, PageRank, clustering) and seamless integration with NetworkX's 30+ additional centrality algorithms.

**DSL-integrated measures (available via `Q.nodes().compute()`):**

- `degree` — Node degree (number of edges)
- `degree_centrality` — Normalized degree centrality
- `betweenness_centrality` — Betweenness centrality (Brandes algorithm)
- `closeness_centrality` — Closeness centrality
- `eigenvector_centrality` — Eigenvector centrality
- `pagerank` — PageRank centrality
- `clustering` — Local clustering coefficient
- `communities` — Community detection (Louvain)

**Additional measures via NetworkX** (use `network.core_network` with any `nx.*_centrality` function):

- Katz centrality, load centrality, harmonic centrality, current flow betweenness, percolation centrality, subgraph centrality, and many more

See [Appendix E: Extended API and DSL Reference](#) (page 150) for complete API reference.

### 8.3.1 Multilayer PageRank

PageRank extends to multilayer networks by defining random walks that can jump between layers:

$$\pi_i^r = (1 - d) \frac{1}{N \cdot L} + d \sum_{j,s} \frac{A_{ji}^{rs}}{k_j^s} \pi_j^s$$

Where  $\pi_i^r$  is the PageRank of node  $i$  in layer  $r$ ,  $d$  is the damping factor (typically 0.85), and  $A_{ji}^{rs}$  accounts for both intra-layer and inter-layer edges.

**Usage:**

```
from py3plex.algorithms.multilayer_algorithms.centrality import MultilayerCentrality

calc = MultilayerCentrality(network)
pagerank_scores = calc.compute_pagerank(alpha=0.85)
```

### 8.3.2 Degree Centrality

In multilayer networks, degree centrality distinguishes between:

- **Intra-layer degree:** Number of connections within a single layer
- **Inter-layer degree:** Number of connections to other layers
- **Supra-degree:** Total degree across all layers
- **Overlapping degree:** Node-level aggregation ignoring layer distinctions

The **participation coefficient** measures how evenly a node's connections are distributed across layers:

$$P_i = \frac{L}{L-1} \left( 1 - \sum_{r=1}^L \left( \frac{k_i^r}{k_i} \right)^2 \right)$$

Where  $k_i^r$  is degree in layer  $r$  and  $k_i$  is total degree. Values near 1 indicate even distribution (hub-like behavior), values near 0 indicate concentration in one layer.

### 8.3.3 Betweenness Centrality

Multilayer betweenness counts shortest paths through the supra-adjacency graph:

$$BC(i, r) = \sum_{s \neq i, r \neq t, l} \frac{\sigma_{(s,k),(t,l)}(i, r)}{\sigma_{(s,k),(t,l)}}$$

Where  $\sigma_{(s,k),(t,l)}$  is the number of shortest paths from node-layer  $(s,k)$  to  $(t,l)$ , and  $\sigma_{(s,k),(t,l)}(i, r)$  counts paths passing through  $(i, r)$ .

**Time complexity:**  $O(n^3)$  for dense networks,  $O(nm)$  for sparse networks using Brandes' algorithm.

### 8.3.4 Explainable Centrality

Explainable centrality decomposes a node's centrality score by layer contribution, revealing which layers drive importance:

```
from py3plex.algorithms.centralities.explain import explain_node_centrality

# Get layer-wise breakdown of degree centrality
explanation = explain_node_centrality(network, 'Alice', measure='degree')

# Output:
# Layer 'social': degree = 12 (60%)
# Layer 'work':   degree = 8  (40%)
# Total degree:   20
```

This helps answer: “Is Alice influential because of social connections, work connections, or both?”

## 8.4 Dynamics and Processes

py3plex provides comprehensive support for simulating dynamical processes on multilayer networks, including epidemic models and random walks.

**For complete documentation**, see the user guide section on multilayer dynamics and the SIR epidemic simulator documentation.

### 8.4.1 Random Walks

Random walks simulate exploration and diffusion on networks:

```
from py3plex.dynamics import RandomWalkDynamics

# Create random walk
walk = RandomWalkDynamics(network, start_node=0, lazy_probability=0.1)
walk.set_seed(42)
results = walk.run(steps=1000)
```

```
# Analyze trajectory
trajectory = results.get_measure("trajectory")
```

Random walks are fundamental to PageRank, community detection, and network embeddings (Node2Vec, DeepWalk).

### 8.4.2 Epidemic Models

Simulate disease spread and information diffusion with SIR and SIS models:

```
from py3plex.dynamics import SIRDynamics, SISDynamics

# SIR: Susceptible-Infected-Recovered (with immunity)
sir = SIRDynamics(network, beta=0.3, gamma=0.1, initial_infected=0.1)
sir.set_seed(42)
results = sir.run(steps=100)

# Extract measures
prevalence = results.get_measure("prevalence")
state_counts = results.get_measure("state_counts")

print(f"Peak prevalence: {prevalence.max():.2%}")
print(f"Final recovered: {state_counts['R'][-1]}")
```

#### Key parameters:

- $\beta \in (0, 1)$ : Transmission probability per contact (infection probability per contact)
- $\gamma \in (0, 1)$ : Recovery probability per time step
- $R_0 = \frac{\beta}{\gamma} \langle k \rangle$ : Basic reproduction number for homogeneous networks, with epidemic threshold at  $R_0 = 1$

#### Models:

- **SIR** — Epidemic with immunity (measles, chickenpox). Always dies out eventually.
- **SIS** — Endemic disease without immunity (common cold, malware). Reaches stable equilibrium.

### 8.4.3 Multilayer Dynamics

Infection spreads through multiple interaction channels:

```
# Two-layer network: physical + digital contacts
network = multinet.multi_layer_network(directed=False)

# Add physical layer (local connections)
# Add digital layer (global connections)

# Run dynamics
sir = SIRDynamics(network, beta=0.3, gamma=0.1)
results = sir.run(steps=100)
```

The multilayer structure allows simultaneous spread through different contexts, often leading to faster and more extensive diffusion than single-layer networks.



## 8.5 Algorithm Complexity and Scaling

Performance characteristics:

Table 1: Algorithm Complexity Summary

| Algorithm              | Time Complexity      | Memory     | Scales to  |
|------------------------|----------------------|------------|------------|
| Louvain                | $O(n \log n)$        | $O(n + m)$ | 100K nodes |
| Label Propagation      | $O(m + n)$           | $O(n)$     | 1M+ nodes  |
| Degree Centrality      | $O(n + m)$           | $O(n)$     | 10M+ nodes |
| Betweenness Centrality | $O(nm)$              | $O(n^2)$   | 10K nodes  |
| PageRank               | $O(m)$ per iteration | $O(n)$     | 1M+ nodes  |
| SIR Dynamics           | $O(t \cdot m)$       | $O(n)$     | 100K nodes |

When to use each family:

- **Community detection:** When you need to understand group structure and identify functional modules. Use early in exploratory analysis.
- **Centrality measures:** When identifying key nodes for targeting, removal, or intervention strategies. Fast for large networks if using degree-based measures.
- **Dynamics:** When modeling spreading processes, cascades, or temporal evolution. Essential for epidemiology, information diffusion, and failure analysis.

Memory considerations:

- Betweenness centrality requires  $O(n^2)$  memory for path counting; use sampling for networks > 10K nodes
- PageRank and degree-based measures scale well with sparse matrices
- Dynamics simulations require  $O(n)$  memory per time step if storing full state history

## 8.6 Summary

This chapter introduced three core algorithm families for multilayer network analysis:

1. **Community detection** reveals group structure using modularity optimization (Louvain), flow-based methods (Infomap), or label propagation. Choose based on network size and interpretability needs.
2. **Centrality measures** identify important nodes using degree, paths, random walks, or eigenvector-based approaches. Multilayer variants account for cross-layer influence.
3. **Dynamics and processes** simulate epidemic spread, diffusion, and random walks on multilayer networks, capturing how layer structure affects spreading patterns.

All algorithms integrate with the py3plex DSL for concise, expressive workflows. The next chapter introduces the DSL and shows how to chain queries for complex analyses.

### See also

#### Further Reading:

- Community detection details: `docfiles/user_guide/community_detection.rst`
- Centrality implementations: `docfiles/tutorials/multilayer_centrality.rst`
- Dynamics API: `docfiles/sir_epidemic_simulator.rst`

- Algorithm reference: `docfiles/algorithm_guide.rst`

## INTRODUCTION TO THE PY3PLEX DSL

This chapter introduces the py3plex Domain-Specific Language (DSL), a SQL-like query language for expressing multilayer network analyses concisely. The DSL is a **major first-class feature** that sets py3plex apart from other network libraries.

### DSL at a Glance

The DSL provides intuitive SQL-like syntax for network queries:

```
from py3plex.dsl import Q, L

# Simple: Find high-degree nodes
result = Q.nodes().where(degree__gt=5).execute(network)

# Powerful: Multi-layer analysis with export
result = (
    Q.nodes()
    .from_layers(L["social"] + L["work"])
    .where(degree__gt=3)
    .compute("betweenness centrality", "pagerank")
    .order_by("-betweenness centrality")
    .limit(20)
    .export_csv("top_influencers.csv")
    .execute(network)
)
```

Express complex analyses in a few readable lines!

## 9.1 Why a DSL for Networks?

Traditional network analysis requires writing explicit loops and conditionals:

```
# Traditional approach: verbose and error-prone
high_degree_nodes = []
for node in network.get_nodes():
    if node[1] == 'social': # Check layer
        degree = network.core_network.degree(node)
        if degree > 5:
            high_degree_nodes.append(node)

# Compute centrality for filtered nodes
```

```
G = network.core_network # NetworkX graph
centralities = nx.betweenness_centrality(G)
filtered_centralities = {node: centralities[node] for node in high_degree_nodes}
```

The DSL provides a declarative alternative:

```
# DSL approach: clear and concise
from py3plex.dsl import execute_query

result = execute_query(network,
    'SELECT nodes WHERE layer="social" AND degree > 5 '
    'COMPUTE betweenness_centrality'
)
```

#### Benefits:

1. **Declarative** — State *what* you want, not *how* to get it
2. **Readable** — SQL-like syntax is familiar and self-documenting
3. **Composable** — Build complex queries from simple building blocks
4. **Maintainable** — Less code means fewer bugs

## 9.2 DSL Versions

Py3plex provides two DSL interfaces:

#### String DSL (v1)

SQL-like queries as strings. Good for simple queries and REPL exploration.

```
result = execute_query(network, 'SELECT nodes WHERE degree > 5')
```

#### Builder API (v2, recommended)

Python-native chainable API with type hints and autocompletion.

```
from py3plex.dsl import Q, L

result = (
    Q.nodes()
    .from_layers(L["social"])
    .where(degree__gt=5)
    .execute(network)
)
```

This chapter focuses on the **Builder API (v2)** as it provides a better development experience. The string DSL is covered briefly for reference.

## 9.3 Basic Query Structure

A typical DSL query has four parts:

1. **Target** — What to select (nodes or edges)
2. **Layer filtering** — Which layers to include (optional)
3. **Conditions** — Filter criteria (optional)

## 4. Measures — What to compute (optional)

Example:

```
from py3plex.dsl import Q, L

result = (
    Q.nodes()                                # 1. Select nodes
    .from_layers(L["social"])                 # 2. Filter to social layer
    .where(degree__gt=5)                      # 3. Filter by degree > 5
    .compute("betweenness centrality")        # 4. Compute centrality
    .execute(network)                         # Execute query
)
```

## 9.4 Your First Query

Let's build a simple query step-by-step.

Setup:

```
from py3plex.core import multinet
from py3plex.dsl import Q, L

# Create network
network = multinet.multi_layer_network()
network.add_edges([
    ['Alice', 'friends', 'Bob', 'friends', 1],
    ['Bob', 'friends', 'Carol', 'friends', 1],
    ['Carol', 'friends', 'Dave', 'friends', 1],
    ['Alice', 'colleagues', 'Bob', 'colleagues', 1],
    ['Bob', 'colleagues', 'Eve', 'colleagues', 1],
], input_type="list")
```

### Query 1: Select all nodes

```
result = Q.nodes().execute(network)

print(f"Count: {result.count}")
# Output: Count: 7

for node in result:
    print(node)
# Output: ('Alice', 'friends'), ('Bob', 'friends'), ...
```

### Query 2: Filter by layer

```
result = Q.nodes().from_layers(L["friends"]).execute(network)

print(f"Nodes in friends layer: {result.count}")
# Output: Nodes in friends layer: 4
```

### Query 3: Filter by degree

```
result = Q.nodes().where(degree__gt=1).execute(network)
```

```
print(f"High-degree nodes: {result.count}")
# Output: High-degree nodes: 2 (Bob in both layers)
```

#### Query 4: Compute centrality

```
result = (
    Q.nodes()
    .from_layers(L["friends"])
    .compute("betweenness centrality")
    .execute(network)
)

for node, centrality in result.measures['betweenness centrality'].items():
    print(f"{node}: {centrality:.3f}")
# Output: ('Bob', 'friends'): 1.000, others: 0.000
```

## 9.5 Layer Filtering

The DSL provides powerful layer algebra operations.

### DSL Layer Algebra

Layer algebra lets you combine layers with set operations:

```
from py3plex.dsl import Q, L

# Union: nodes in social OR work
Q.nodes().from_layers(L["social"] + L["work"])

# Difference: nodes in social but NOT bots
Q.nodes().from_layers(L["social"] - L["bots"])

# Intersection: nodes in both social AND work
Q.nodes().from_layers(L["social"] & L["work"])

# Complex: (social OR work) - bots
Q.nodes().from_layers(L["social"] + L["work"] - L["bots"])
```

This makes multilayer queries intuitive and expressive!

### 9.5.1 Simple Layer Selection

```
# Single layer
Q.nodes().from_layers(L["social"])

# Multiple layers (union)
Q.nodes().from_layers(L["social"] + L["work"])
```

## 9.5.2 Layer Algebra

**Union (OR):**

```
# Nodes in social OR work layers
Q.nodes().from_layers(L["social"] + L["work"])
```

**Difference (NOT):**

```
# Nodes in social but NOT in bots layer
Q.nodes().from_layers(L["social"] - L["bots"])
```

**Intersection (AND):**

```
# Nodes present in both social AND work
Q.nodes().from_layers(L["social"] & L["work"])
```

**All layers:**

```
# Don't specify from_layers() to query all layers
Q.nodes().where(degree__gt=5)
```

## 9.6 Filtering Conditions

The `where()` method accepts filtering predicates.

### 9.6.1 Degree Filters

```
# Greater than
Q.nodes().where(degree__gt=5)

# Greater than or equal
Q.nodes().where(degree__gte=3)

# Less than
Q.nodes().where(degree__lt=10)

# Less than or equal
Q.nodes().where(degree__lte=5)

# Equal
Q.nodes().where(degree=2)
```

### 9.6.2 Layer Filters

```
# Specific layer
Q.nodes().where(layer="social")

# Exclude layer
Q.nodes().where(layer__ne="bots")
```

### 9.6.3 Multiple Conditions (AND)

```
# Combine conditions
Q.nodes().where(layer="social", degree__gt=3)

# Equivalent to: layer="social" AND degree > 3
```

## 9.7 Computing Measures

The `compute()` method calculates network measures.

### 9.7.1 Single Measure

```
result = (
    Q.nodes()
    .compute("degree")
    .execute(network)
)

# Access results
for node, degree in result.measures['degree'].items():
    print(f"{node}: {degree}")
```

### 9.7.2 Multiple Measures

```
result = (
    Q.nodes()
    .compute("degree", "betweenness centrality", "closeness centrality")
    .execute(network)
)

# Access each measure
degrees = result.measures['degree']
betweenness = result.measures['betweenness centrality']
closeness = result.measures['closeness centrality']
```

### 9.7.3 Available Measures

| Measure                | Description                                       |
|------------------------|---------------------------------------------------|
| degree                 | Node degree (number of neighbors)                 |
| degree centrality      | Normalized degree centrality                      |
| betweenness centrality | Betweenness centrality (path-based importance)    |
| closeness centrality   | Closeness centrality (average distance to others) |
| eigenvector centrality | Eigenvector centrality (importance of neighbors)  |
| pagerank               | PageRank score                                    |
| clustering             | Clustering coefficient                            |



## 9.8 Ordering and Limiting

### 9.8.1 Order By

```
# Order by degree (ascending)
Q.nodes().compute("degree").order_by("degree")

# Order by degree (descending)
Q.nodes().compute("degree").order_by("-degree")

# Order by multiple keys
Q.nodes().compute("degree").order_by("-degree", "node_id")
```

### 9.8.2 Limit

```
# Get top 10 by degree
result = (
    Q.nodes()
    .compute("degree")
    .order_by("-degree")
    .limit(10)
    .execute(network)
)
```

## 9.9 Working with Results

The QueryResult object provides multiple ways to access results.

### 9.9.1 Iteration

```
result = Q.nodes().execute(network)

for node in result:
    print(node)  # ('Alice', 'friends'), ...
```

### 9.9.2 Count

```
result = Q.nodes().where(degree__gt=5).execute(network)
print(f"Found {result.count} nodes")
```

### 9.9.3 Measures

```
result = Q.nodes().compute("degree").execute(network)

# Access as dict
degrees = result.measures['degree']
for node, degree in degrees.items():
    print(f"{node}: {degree}")
```

### 9.9.4 To Pandas

```
# Convert to DataFrame
df = result.to_pandas()
print(df.head())
```

## 9.10 String DSL Syntax (Reference)

For completeness, here's the string DSL syntax:

### Basic queries:

```
# Select nodes
execute_query(network, 'SELECT nodes')

# Filter by layer
execute_query(network, 'SELECT nodes WHERE layer="social"')

# Filter by degree
execute_query(network, 'SELECT nodes WHERE degree > 5')

# Multiple conditions
execute_query(network, 'SELECT nodes WHERE layer="social" AND degree > 3')

# Compute measures
execute_query(network, 'SELECT nodes COMPUTE betweenness centrality')
```

### Operators:

- = — Equal
- != — Not equal
- > — Greater than
- < — Less than
- >= — Greater or equal
- <= — Less or equal
- AND — Logical AND
- OR — Logical OR
- NOT — Logical NOT

## 9.11 Example: Complete Workflow

Here's a complete example demonstrating DSL capabilities:

```
from py3plex.core import multinet
from py3plex.dsl import Q, L

# Create network
network = multinet.multi_layer_network()
network.add_edges([
```

```

['Alice', 'friends', 'Bob', 'friends', 1],
['Bob', 'friends', 'Carol', 'friends', 1],
['Carol', 'friends', 'Dave', 'friends', 1],
['Alice', 'colleagues', 'Bob', 'colleagues', 1],
['Bob', 'colleagues', 'Eve', 'colleagues', 1],
['Eve', 'colleagues', 'Frank', 'colleagues', 1],
], input_type="list")

# Query 1: Find high-degree nodes across all layers
result = (
    Q.nodes()
    .where(degree__gte=2)
    .compute("degree", "betweenness centrality")
    .order_by("-betweenness centrality")
    .execute(network)
)

print("High-degree nodes:")
for node in result:
    degree = result.measures['degree'][node]
    bc = result.measures['betweenness centrality'][node]
    print(f" {node}: degree={degree}, BC={bc:.3f}")

# Query 2: Compare layers
for layer in ['friends', 'colleagues']:
    result = (
        Q.nodes()
        .from_layers(L[layer])
        .compute("degree")
        .execute(network)
    )
    avg_degree = sum(result.measures['degree'].values()) / result.count
    print(f"{layer} layer: {result.count} nodes, avg degree={avg_degree:.2f}")

```

## 9.12 Common Patterns

### 9.12.1 Pattern 1: Filter → Compute → Order → Limit

```

# Find top 10 central nodes in a specific layer
top_10 = (
    Q.nodes()
    .from_layers(L["social"])
    .compute("betweenness centrality")
    .order_by("-betweenness centrality")
    .limit(10)
    .execute(network)
)

```

### 9.12.2 Pattern 2: Layer Comparison

```
# Compare degree distribution across layers
for layer_name in network.get_layers():
    result = (
        Q.nodes()
        .from_layers(L[layer_name])
        .compute("degree")
        .execute(network)
    )
    degrees = list(result.measures['degree'].values())
    print(f"{layer_name}: mean degree = {sum(degrees)/len(degrees):.2f}")
```

### 9.12.3 Pattern 3: Conditional Export

```
# Export high-degree nodes to CSV
(
    Q.nodes()
    .where(degree__gt=5)
    .compute("degree", "betweenness_centrality")
    .order_by("-degree")
    .export_csv("high_degree_nodes.csv")
    .execute(network)
)
```

## 9.13 Summary

This chapter introduced the py3plex DSL:

1. **Motivation** — Declarative queries replace explicit loops
2. **Builder API** — Python-native with type hints (recommended)
3. **Query structure** — Target, layers, conditions, measures
4. **Layer algebra** — Union, difference, intersection operations
5. **Results** — Iteration, measures, pandas export

**Key takeaways:**

- Use **Builder API** for type safety and autocompletion
- **Chain methods** to build complex queries incrementally
- **Layer algebra** enables powerful layer filtering
- **Compute measures** in a single call instead of manual loops

The next chapter covers the EXPLAIN mode for understanding query execution and performance.

## 9.14 Further Reading

- The Builder API and Explain Plans
- Advanced Queries and Workflows
- `examples/network_analysis/example_dsl_builder_api.py` — Complete examples

## THE BUILDER API AND EXPLAIN PLANS

The DSL Builder API provides a Pythonic, type-safe way to construct network queries using method chaining. This chapter covers the builder pattern, query execution plans, and advanced features like parameterization and query reuse.

### 10.1 Builder Pattern and Fluent API

The builder API uses method chaining to construct queries incrementally. Each method returns the query object, allowing you to chain operations naturally:

```
from py3plex.dsl import Q, L

# Basic query with chaining
result = (
    Q.nodes()                # Start with nodes
    .from_layers(L["social"]) # Filter by layer
    .where(degree__gt=5)      # Filter by degree
    .compute("betweenness centrality") # Compute measure
    .order_by("-betweenness centrality") # Sort descending
    .limit(10)               # Take top 10
    .execute(network)        # Execute query
)
```

**Advantages over string DSL:**

- **Type safety:** IDE autocomplete and type checking
- **Composability:** Build queries programmatically
- **Readability:** Self-documenting code
- **Error detection:** Catch mistakes before execution

#### 10.1.1 Method Chaining

Build queries step-by-step:

```
# Start with a base query
q = Q.nodes()

# Add filters
q = q.where(layer="social")
q = q.where(degree__gt=3)

# Add computation
```

```

q = q.compute("degree", "clustering")

# Sort and limit
q = q.order_by("-degree")
q = q.limit(20)

# Execute
result = q.execute(network)

```

**Builder operators:**

| Operator                    | DSL Equivalent            |
|-----------------------------|---------------------------|
| where(degree__gt=5)         | WHERE degree > 5          |
| where(degree__gte=5)        | WHERE degree >= 5         |
| where(degree__lt=5)         | WHERE degree < 5          |
| where(degree__lte=5)        | WHERE degree <= 5         |
| where(layer="social")       | WHERE layer = "social"    |
| where(layer__in=["a", "b"]) | WHERE layer IN ("a", "b") |

## 10.1.2 Type Hints and IDE Support

The builder API is fully type-hinted for modern IDEs:

```

from py3plex.dsl import Q, L

# IDE shows available methods and parameters
result = (
    Q.nodes()           # Autocomplete suggests: where, from_layers, compute, ...
    .where(              # Autocomplete shows: degree__gt, degree__lt, layer, ...
        degree__gt=5    # Type hints ensure correct parameter types
    )
    .compute(            # Autocomplete lists available measures
        "degree",        # String literals with validation
        "betweenness centrality"
    )
    .execute(network)    # Type checker ensures network is correct type
)

```

**Benefits:**

- Catch typos before runtime
- Discover available methods and measures
- Understand query structure through types
- Safer refactoring with IDE support

## 10.2 EXPLAIN Mode

### 10.2.1 Query Execution Plans

Get a query execution plan without actually running the query:

```

from py3plex.dsl import Q

# Build a complex query
q = (
    Q.nodes()
    .from_layers(L["social"])
    .where(degree__gt=5)
    .compute("betweenness centrality", "pagerank")
    .order_by("-betweenness centrality")
    .limit(10)
)

# Get execution plan
plan = q.explain().execute(network)

# Inspect the plan
print(f"Query: {plan.query}")
print(f"Estimated nodes: {plan.estimated_node_count}")

for step in plan.steps:
    print(f"    {step.description}")
    print(f"        Complexity: {step.estimated_complexity}")
    print(f"        Estimated time: {step.estimated_time_ms}ms")

# Check for warnings
for warning in plan.warnings:
    print(f"    {warning}")

```

**Example output:**

```

Query: SELECT nodes FROM layers social WHERE degree > 5
      COMPUTE betweenness centrality pagerank
      ORDER BY -betweenness centrality LIMIT 10

Estimated nodes: ~150

1. Filter by layer
   Complexity: O(n)
   Estimated time: 2ms

2. Filter by degree
   Complexity: O(n)
   Estimated time: 1ms

3. Compute betweenness centrality
   Complexity: O(n³)
   Estimated time: 850ms
   Betweenness centrality is expensive for large graphs

4. Compute pagerank
   Complexity: O(n²)
   Estimated time: 45ms

```

```

5. Sort results
   Complexity:  $O(n \log n)$ 
   Estimated time: 3ms

6. Limit results
   Complexity:  $O(1)$ 
   Estimated time: <1ms

```

## 10.2.2 Complexity Estimates

EXPLAIN mode provides complexity estimates for each operation:

- **$O(1)$**  — Constant time (e.g., limit, basic metadata)
- **$O(n)$**  — Linear in number of nodes (e.g., filtering by attribute)
- **$O(m)$**  — Linear in number of edges (e.g., edge filtering)
- **$O(n \log n)$**  — Log-linear (e.g., sorting)
- **$O(n^2)$**  — Quadratic (e.g., PageRank, all-pairs measures)
- **$O(n^3)$**  — Cubic (e.g., betweenness centrality on large graphs)

Use EXPLAIN to:

1. **Identify bottlenecks** before executing expensive queries
2. **Compare alternative formulations** of the same query
3. **Estimate runtime** for large networks
4. **Optimize query order** (apply cheap filters first)

## 10.2.3 Optimization Tips

### 1. Apply filters before computing measures

```

# Slow: Compute for all, then filter
Q.nodes().compute("betweenness_centrality").where(degree__gt=5)

# Fast: Filter first, then compute
Q.nodes().where(degree__gt=5).compute("betweenness_centrality")

```

### 2. Use layer filtering early

```

# Slow: Compute for all layers
Q.nodes().compute("degree").where(layer="social")

# Fast: Filter to layer first
Q.nodes().from_layers(L["social"]).compute("degree")

```

### 3. Limit results when possible

```

# Top 10 is much faster than computing for all nodes
Q.nodes().compute("degree").order_by("-degree").limit(10)

```

### 4. Choose efficient measures

- **Cheap:** degree, clustering coefficient (local measures)



- **Moderate:** PageRank, eigenvector centrality (iterative)
- **Expensive:** betweenness centrality, closeness centrality (all-pairs)

## 10.3 Advanced Builder Features

### 10.3.1 Parameterized Queries

Use Param to create reusable query templates:

```
from py3plex.dsl import Q, Param

# Create a parameterized query template
influencer_query = (
    Q.nodes()
    .from_layers(L[Param.str("target_layer")])
    .where(degree__gt=Param.int("min_degree"))
    .compute("betweenness centrality")
    .order_by("-betweenness centrality")
    .limit(Param.int("top_n"))
)

# Execute with different parameters
social_influencers = influencer_query.execute(
    network,
    target_layer="social",
    min_degree=10,
    top_n=20
)

work_influencers = influencer_query.execute(
    network,
    target_layer="professional",
    min_degree=5,
    top_n=50
)
```

#### Parameter types:

- `Param.int("name")` — Integer parameter
- `Param.float("name")` — Float parameter
- `Param.str("name")` — String parameter
- `Param.ref("name")` — Untyped reference

#### Benefits:

- **Safety:** Type-checked at execution time
- **Reusability:** One query definition, many executions
- **Maintainability:** Parameters are self-documenting
- **Performance:** Query is parsed once, executed multiple times

### 10.3.2 Query Reuse

Build queries once and execute them multiple times:

```
# Define a query once
high_degree_analysis = (
    Q.nodes()
    .where(degree__gt=10)
    .compute("betweenness centrality", "clustering")
)

# Execute on different networks
result1 = high_degree_analysis.execute(network1)
result2 = high_degree_analysis.execute(network2)
result3 = high_degree_analysis.execute(network3)

# Or execute with different parameters over time
for threshold in [5, 10, 15, 20]:
    q = Q.nodes().where(degree__gt=threshold).compute("degree")
    result = q.execute(network)
    print(f"Threshold {threshold}: {result.count} nodes")
```

### 10.3.3 Converting to DSL String

Convert a builder query back to string format:

```
q = (
    Q.nodes()
    .from_layers(L["social"])
    .where(degree__gt=5)
    .compute("degree")
    .limit(10)
)

# Get DSL string representation
dsl_string = q.to_dsl()
print(dsl_string)
# Output: SELECT nodes FROM layers social WHERE degree > 5
#        COMPUTE degree LIMIT 10
```

Use cases:

- **Logging:** Record queries in application logs
- **Debugging:** Inspect query structure
- **Serialization:** Save queries to files or databases
- **Auditing:** Track what analyses were run

### 10.3.4 Error Handling with Suggestions

The DSL provides helpful error messages with suggestions:

```
from py3plex.dsl import Q, UnknownMeasureError

try:
```

```

# Typo in measure name
result = Q.nodes().compute("betweenes").execute(network)
except UnknownMeasureError as e:
    print(e)
# Output: Unknown measure 'betweenes'. Did you mean 'betweenness centrality'?
#         Known measures: betweenness centrality, closeness centrality, ...

```

## 10.4 Summary

The DSL Builder API provides:

- **Pythonic interface:** Natural method chaining
- **Type safety:** IDE support and autocomplete
- **Query plans:** EXPLAIN mode for optimization
- **Parameterization:** Reusable query templates
- **Error handling:** Helpful “did you mean?” messages

**Best practices:**

1. Use builder API for programmatic queries
2. Run EXPLAIN before executing expensive queries
3. Filter early, compute late
4. Parameterize queries that you’ll reuse
5. Use type hints and IDE support to catch errors

**Next chapter:** Advanced query patterns and workflow integration

## ADVANCED QUERIES AND WORKFLOWS

This chapter covers advanced DSL patterns including dynamics simulation, complex query patterns, and workflow integration.

### 11.1 DSL-Based Dynamics Simulation

The py3plex DSL includes a powerful framework for declarative dynamics simulation on multilayer networks. This section demonstrates how to use the dynamics DSL for epidemic modeling, random walks, and other dynamical processes.

#### 11.1.1 Mathematical Formalism

##### SIS Model (Susceptible-Infected-Susceptible)

The SIS model tracks disease spread with possible reinfection:

- **States:** S (susceptible), I (infected)
- **Update rules** (discrete time, node  $i$ ):
  - $P(S_i \rightarrow I_i) = 1 - (1 - \beta)^{\sum_j A_{ij} I_j(t)}$
  - $P(I_i \rightarrow S_i) = \gamma$
- **Parameters:**
  - $\beta \in (0, 1)$ : transmission probability per contact
  - $\gamma \in (0, 1)$ : recovery probability per time step (also denoted  $\mu$ )
- **Epidemic threshold:**
  - $R_0 = \frac{\beta}{\gamma} \lambda_{\max}(A)$  where  $\lambda_{\max}(A)$  is the largest eigenvalue of the adjacency matrix. Endemic equilibria exist when  $R_0 > 1$ .

##### SIR Model (Susceptible-Infected-Recovered)

The SIR model includes permanent immunity after recovery:

- **States:** S (susceptible), I (infected), R (recovered/removed)
- **Update rules** (discrete time, node  $i$ ):
  - $P(S_i \rightarrow I_i) = 1 - (1 - \beta)^{\sum_j A_{ij} I_j(t)}$
  - $P(I_i \rightarrow R_i) = \gamma$
- **Parameters:**
  - $\beta \in (0, 1)$ : transmission probability per contact

- $\gamma \in (0, 1)$ : recovery probability per time step

The final outbreak size (attack rate) depends on the basic reproduction number  $R_0 = \frac{\beta}{\gamma} \langle k \rangle$ , where  $\langle k \rangle$  is the mean degree. Epidemic threshold at  $R_0 = 1$ .

### Random Walk

Random walk dynamics model diffusion processes:

- **State:** Current node position
- **Update rule:** Move to neighbor  $j$  with probability  $1/\text{degree}(i)$ , or stay at  $i$  with probability  $p_{\text{lazy}}$  (for lazy walks)
- **Parameters:**
  - $p_{\text{teleport}}$ : probability of random teleportation (default: 0.05)
  - $p_{\text{lazy}}$ : probability of staying at current node (default: 0.0)

### 11.1.2 Basic Dynamics DSL Usage

The dynamics DSL uses a builder API similar to the query DSL:

```
from py3plex.core import multinet
from py3plex.dynamics import D, SIS
from py3plex.dsl import L

# Create network
network = multinet.multi_layer_network()
network.add_edges([
    ['Alice', 'social', 'Bob', 'social', 1],
    ['Bob', 'social', 'Carol', 'social', 1],
    ['Carol', 'social', 'Dave', 'social', 1],
], input_type="list")

# Define SIS simulation
sim = (
    D.process(SIS(beta=0.3, mu=0.1)) # Specify process and parameters
    .initial(infected=0.05)          # 5% initially infected
    .steps(100)                      # Run for 100 time steps
    .measure("prevalence", "incidence") # Track measures
    .replicates(10)                  # Run 10 independent simulations
    .seed(42)                        # For reproducibility
)

# Execute simulation
result = sim.run(network)

# Access results
print(f"Mean final prevalence: {result.data['prevalence'][:, -1].mean():.3f}")

# Convert to pandas for analysis
df_dict = result.to_pandas()
prevalence_df = df_dict['prevalence']
```

#### Key components:

1. **D.process()** — Specify the dynamical process (SIS, SIR, RandomWalk)

2. `.initial()` — Set initial conditions
3. `.steps()` — Number of time steps to simulate
4. `.measure()` — Metrics to track during simulation
5. `.replicates()` — Number of independent runs (for averaging)
6. `.seed()` — Random seed for reproducibility
7. `.run()` — Execute the simulation

### 11.1.3 Initial Conditions

The `.initial()` method accepts multiple formats for setting initial infected nodes:

**Float (fraction of nodes):**

```
.initial(infected=0.05) # 5% of nodes randomly infected
```

**Integer (exact count):**

```
.initial(infected=5) # Exactly 5 nodes randomly infected
```

**List of node tuples:**

```
.initial(infected=[('Alice', 'social'), ('Bob', 'work')])
```

**DSL query (dynamic selection):**

```
.initial(infected=Q.nodes().where(degree__gte=5)) # Infect high-degree hubs
```

**Recommended:** Use float fractions (0.05) for reproducibility across different network sizes.

### 11.1.4 Available Measures

Different processes support different measures:

| Process    | Measure             | Description                                  |
|------------|---------------------|----------------------------------------------|
| SIS        | prevalence          | Fraction of infected nodes at each time step |
| SIS        | incidence           | Number of new infections at each time step   |
| SIS        | prevalence_by_layer | Prevalence tracked separately per layer      |
| SIR        | prevalence          | Fraction of infected nodes                   |
| SIR        | state_counts        | Counts of nodes in each state (S, I, R)      |
| RandomWalk | visit_frequency     | Frequency of visits to each node             |
| RandomWalk | state_counts        | Current position over time                   |

### 11.1.5 Multilayer Dynamics

The DSL supports multilayer networks with coupling between layers:

```
from py3plex.dsl import L

# Simulate on specific layers
sim = (
    D.process(SIS(beta=0.25, mu=0.08))
    .on_layers(L["offline"] + L["online"]) # Select layers
```

```

    .coupling(node_replicas="strong")      # Shared node states
    .initial(infected=0.1)
    .steps(120)
    .measure("prevalence", "prevalence_by_layer")
    .replicates(15)
)

result = sim.run(multilayer_network)

```

#### Coupling modes:

- “strong” — Node states shared across all layers (default)
- “independent” — Each layer has independent node states
- “weak” — Partial coupling with cross-layer transmission rate

### 11.1.6 Integration with Query DSL

The dynamics DSL integrates seamlessly with the query DSL for targeted initial conditions:

```

from py3plex.dsl import Q

# Start infection at high-degree nodes (hubs)
sim = (
    D.process(SIS(beta=0.35, mu=0.12))
    .initial(
        infected=Q.nodes().where(degree__gte=5) # Query for hubs
    )
    .steps(100)
    .measure("prevalence")
    .replicates(10)
)

result = sim.run(network)

```

This allows precise control over initial conditions based on network structure, centrality, or other properties.

### 11.1.7 Parameter Comparison Example

Compare dynamics under different parameters:

```

# Compare transmission rates
beta_values = [0.2, 0.3, 0.4, 0.5]
results = {}

for beta in beta_values:
    sim = (
        D.process(SIS(beta=beta, mu=0.1))
        .initial(infected=0.05)
        .steps(80)
        .measure("prevalence")
        .replicates(20)
        .seed(42)
    )

```

```

results[beta] = sim.run(network)

# Analyze final prevalence
for beta, result in results.items():
    mean_final = result.data['prevalence'][:, -1].mean()
    print(f"={beta:.1f}: final prevalence = {mean_final:.3f}")

```

### 11.1.8 Result Analysis

The `SimulationResult` object provides rich analysis capabilities:

```

# Get summary statistics
summary = result.summary()
print(summary)

# Plot time series with confidence intervals
import matplotlib.pyplot as plt
result.plot("prevalence")
plt.show()

# Export to pandas for custom analysis
df_dict = result.to_pandas()
prevalence_df = df_dict['prevalence']

# Compute mean trajectory
mean_trajectory = (
    prevalence_df
    .groupby('t')['value']
    .agg(['mean', 'std'])
)

```

#### Status: Dynamics DSL

The builder API (`D.process()`) is under active development and may change in future releases. The core dynamics classes (`SIRDynamics`, `SISDynamics`, `RandomWalkDynamics`) are stable and production-ready.

## 11.2 Complex Query Patterns

Beyond basic filtering and computation, the DSL supports advanced analysis patterns.

### 11.2.1 Parameterized Comparative Analysis

Systematic comparison across layers using parameterized queries:

```

from py3plex.dsl import Q, L, Param

# Define reusable parameterized query
hub_analysis = (
    Q.nodes()
    .from_layers(L[Param.str("layer")])
    .where(degree__gt=Param.int("threshold"))
)

```



```

        .compute("betweenness centrality", "clustering")
        .order_by("-betweenness centrality")
        .limit(Param.int("top_n"))
    )

    # Execute for multiple layers
    for layer in ["social", "work", "family"]:
        result = hub_analysis.execute(
            network,
            layer=layer,
            threshold=5,
            top_n=20
        )
        df = result.to_pandas()
        df.to_csv(f"{layer}_hubs.csv")
        print(f"{layer}: {result.count} hubs, max BC = {df['betweenness centrality'].max():.3f}")

```

### 11.2.2 Multi-Layer Statistical Summaries

Aggregate statistics across all layers:

```

# Collect statistics for each layer
layer_stats = []
for layer_name in network.get_layers():
    result = (
        Q.nodes()
        .from_layers(L[layer_name])
        .compute("degree", "betweenness centrality", "clustering")
        .execute(network)
    )
    df = result.to_pandas()

    layer_stats.append({
        'layer': layer_name,
        'node_count': result.count,
        'avg_degree': df['degree'].mean(),
        'max_betweenness': df['betweenness centrality'].max(),
        'avg_clustering': df['clustering'].mean(),
    })

# Convert to DataFrame for analysis
import pandas as pd
summary_df = pd.DataFrame(layer_stats)
print(summary_df)

```

### 11.2.3 Layer Algebra for Complex Filters

Combine layers using set operations:

```

from py3plex.dsl import L

# Nodes in social OR work layers
social_or_work = (

```

```

    Q.nodes()
    .from_layers(L["social"] + L["work"])
    .compute("degree")
    .execute(network)
)

# Nodes in social BUT NOT bots
legitimate_social = (
    Q.nodes()
    .from_layers(L["social"] - L["bots"])
    .compute("degree")
    .execute(network)
)

# Intersection of layers
overlap = (
    Q.nodes()
    .from_layers(L["layer1"] & L["layer2"])
    .execute(network)
)

```

### 11.2.4 Aggregations by Node Attributes

Group and aggregate by node properties:

```

# Compute average centrality by community
result = (
    Q.nodes()
    .compute("betweenness centrality", "community")
    .execute(network)
)

df = result.to_pandas()
community_centralty = df.groupby('community')['betweenness centrality'].agg(['mean', 'std', 'max'])
print(community_centralty)

```

## 11.3 Result Conversion

The DSL provides flexible export capabilities for different analysis workflows.

### 11.3.1 To Pandas DataFrames

Convert query results to pandas for statistical analysis:

```

# Execute query
result = (
    Q.nodes()
    .from_layers(L["social"])
    .compute("degree", "betweenness centrality", "clustering")
    .execute(network)
)

```

```
# Convert to DataFrame
df = result.to_pandas()

# Standard pandas operations
print(df.describe())
print(df[df['degree'] > 10])
df.to_csv("results.csv", index=False)
```

**DataFrame structure:**

- Each row is a node
- Columns include: node\_id, layer, computed measures

### 11.3.2 To NetworkX

Export filtered nodes as a NetworkX subgraph:

```
# Query for high-degree nodes
result = (
    Q.nodes()
    .where(degree__gt=10)
    .execute(network)
)

# Extract as NetworkX subgraph
node_ids = list(result.node_ids)
subgraph = network.core_network.subgraph(node_ids)

# Use NetworkX algorithms
import networkx as nx
communities = nx.community.louvain_communities(subgraph)
```

### 11.3.3 To CSV/JSON

Direct export without intermediate DataFrame:

```
# Export to CSV
(
    Q.nodes()
    .from_layers(L["social"])
    .compute("degree", "betweenness_centrality")
    .export_csv("social_centrality.csv")
    .execute(network)
)

# Export to JSON
(
    Q.nodes()
    .compute("degree")
    .export_json("node_degrees.json", orient="records")
    .execute(network)
)
```

**Supported formats:**

- CSV (with custom delimiter)
- JSON (various orientations)
- pandas DataFrame (in-memory)

## 11.4 Workflow Integration

### 11.4.1 Pipeline Composition

Chain multiple queries in analysis pipelines:

```
# Step 1: Find high-degree nodes
hubs = (
    Q.nodes()
    .where(degree__gt=20)
    .execute(network)
)

# Step 2: Compute centrality only for hubs
hub_centrality = (
    Q.nodes()
    .where(node_id__in=list(hubs.node_ids))
    .compute("betweenness_centrality", "closeness_centrality")
    .execute(network)
)

# Step 3: Identify super-hubs
super_hubs = (
    Q.nodes()
    .where(
        node_id__in=list(hubs.node_ids),
        betweenness_centrality__gt=0.1
    )
    .execute(network)
)

print(f"Hubs: {hubs.count}, Super-hubs: {super_hubs.count}")
```

### 11.4.2 Combining with sklearn

Integrate DSL results with machine learning pipelines:

```
from sklearn.cluster import KMeans
from sklearn.preprocessing import StandardScaler

# Extract features using DSL
result = (
    Q.nodes()
    .compute("degree", "betweenness_centrality", "clustering")
    .execute(network)
)

df = result.to_pandas()
```

```

# Prepare features
features = df[['degree', 'betweenness centrality', 'clustering']].values
scaler = StandardScaler()
features_scaled = scaler.fit_transform(features)

# Cluster nodes
kmeans = KMeans(n_clusters=5, random_state=42)
df['cluster'] = kmeans.fit_predict(features_scaled)

# Analyze clusters
print(df.groupby('cluster')[['degree', 'betweenness centrality']].mean())

```

### 11.4.3 Custom Measures

While the DSL provides built-in measures, you can compute custom measures using pandas:

```

# Get base measures
result = (
    Q.nodes()
    .compute("degree", "betweenness centrality")
    .execute(network)
)

df = result.to_pandas()

# Compute custom measure
df['influence_score'] = (
    0.6 * df['degree'] / df['degree'].max() +
    0.4 * df['betweenness centrality'] / df['betweenness centrality'].max()
)

# Find top nodes by custom measure
top_influential = df.nlargest(10, 'influence_score')
print(top_influential[['node_id', 'influence_score']])

```

## 11.5 Performance Tips

### 11.5.1 Query Optimization

For large-scale dynamics simulations:

- Use fewer replicates during development, scale up for production
- Consider using numpy backend for faster computation
- Track only essential measures to reduce memory usage
- Use smaller time steps when necessary but be aware of computational cost

## 11.5.2 Memory Management

For very large networks or long simulations:

- Avoid tracking full trajectories (trajectory measure) if not needed
- Use measure-specific exports rather than full result objects
- Process results in batches for very long time series

## 11.6 Alternative Workflow APIs

Beyond the main DSL, py3plex provides complementary APIs for different programming styles.

### 11.6.1 Dplyr-Style Operations (graph\_ops)

For users familiar with R's dplyr or Python's pandas, graph\_ops provides chainable verb-based operations:

```
from py3plex.graph_ops import nodes

# Dplyr-style pipeline
df = (
    nodes(network)
    .filter(lambda n: n["degree"] > 5)
    .mutate(score=lambda n: n["degree"] * 2)
    .arrange("score", reverse=True)
    .head(10)
    .to_pandas()
)
```

**Key verbs:** filter(), mutate(), arrange(), select(), group\_by(), summarise()

**Use case:** Interactive exploration and data munging with familiar pandas-like syntax.

### 11.6.2 Sklearn-Style Pipelines (pipeline)

For reproducible workflows, pipeline provides scikit-learn style composition:

```
from py3plex.pipeline import Pipeline, LoadStep, AggregateLayers
from py3plex.pipeline import LouvainCommunity, ComputeStats

# Define analysis pipeline
pipe = Pipeline([
    ("load", LoadStep(path="network.graphml")),
    ("aggregate", AggregateLayers()),
    ("community", LouvainCommunity(resolution=1.0)),
    ("stats", ComputeStats()),
])

# Run pipeline
result = pipe.run()

# Reuse pipeline on different network
result2 = pipe.set_params(load__path="network2.graphml").run()
```

**Key steps:** LoadStep, AggregateLayers, LeidenMultilayer, FilterNodes, SaveNetwork

**Use case:** Production workflows, parameter sweeps, and reproducible analysis scripts.

### 11.6.3 Config-Driven Workflows (workflows)

For declarative specification of complex analyses, `workflows` supports YAML/JSON configurations:

```
from py3plex.workflows import run_workflow

config = {
    'input': {'path': 'network.edgelist', 'type': 'edgelist'},
    'steps': [
        {'type': 'community_detection', 'algorithm': 'louvain'},
        {'type': 'centrality', 'measures': ['degree', 'betweenness']},
        {'type': 'export', 'format': 'csv', 'path': 'results.csv'}
    ]
}

results = run_workflow(config)
```

**Use case:** Batch processing, configuration management, and non-programmer friendly analysis.

## 11.7 Summary

This chapter covered:

1. **DSL-based dynamics simulation** — Declarative framework for SIS, SIR, and Random Walk
2. **Mathematical formalism** — Formal definitions of epidemic models
3. **Multilayer coupling** — Simulating dynamics across network layers
4. **Query integration** — Using `Q.nodes()` for targeted initial conditions
5. **Parameter comparison** — Systematic exploration of parameter space
6. **Result analysis** — Rich result objects with pandas export and plotting
7. **Alternative APIs** — Dplyr-style, sklearn-style, and config-driven workflows

**Key takeaways:**

- The dynamics DSL follows the same design philosophy as the query DSL
- Simulations are fully declarative and composable
- Integration with query DSL enables sophisticated initial condition specification
- Results are analysis-ready with pandas, xarray, and plotting support
- Choose API style based on your workflow needs: DSL (query-focused), `graph_ops` (data munging), pipeline (reproducibility), `workflows` (configuration)

## 11.8 Further Reading

- Introduction to the Py3plex DSL
- The Builder API and Explain Plans
- `examples/network_analysis/example_dsl_dynamics.py` — Complete examples
- `examples/advanced/example_dynamics_core.py` — Core dynamics classes

- `docfiles/sir_epidemic_simulator.rst` — SIR multiplex simulator documentation



## LIMITATIONS AND STABILITY GUARANTEES

*This chapter explicitly marks feature status for user confidence*

### 12.1 DSL Feature Status

#### 12.1.1 Stable APIs

Features with strong backward-compatibility guarantees:

- **Node queries** — `Q.nodes()` with filtering and measures
- **Layer algebra** — Union, difference, intersection operations
- **Core measures** — degree, betweenness, closeness, pagerank
- **Result export** — pandas, JSON, CSV formats

**Guarantee:** Stable APIs will not break in minor version updates ( $1.x \rightarrow 1.y$ ).

#### 12.1.2 Experimental Features

Functional but may change in future versions:

- **Edge queries** — `Q.edges()` (limited implementation)
- **Advanced aggregations** — `GROUP BY` equivalents
- **Nested subqueries** — Complex query composition

**Note:** Experimental features are marked in documentation. Use with awareness that API may evolve.

#### 12.1.3 Planned Features

Roadmap items (briefly mentioned, not detailed):

- **Full edge query support** — Complete parity with node queries
- **Graph pattern matching** — Motif detection DSL
- **Temporal queries** — Time-aware filtering

### 12.2 Current Limitations

#### 12.2.1 Query Capabilities

What the DSL **can** do:

- Node filtering by degree, layer, and computed measures

- Compute centrality measures
- Layer algebra operations
- Export results in multiple formats

What the DSL **cannot** (yet) do:

- Complex edge queries (partial support only)
- Nested subqueries
- Aggregate functions (SUM, AVG, etc.)
- Join operations across layers

## 12.2.2 Performance Boundaries

- **Small networks** (<10k nodes) — No issues
- **Medium networks** (10k-100k nodes) — Most queries fast
- **Large networks** (>100k nodes) — Some queries may be slow; use filtering early

## 12.3 Scale and Performance

### 12.3.1 Query Complexity

DSL query operations have different time complexities:

Table 1: Query Operation Complexity

| Operation                            | Time Complexity | Notes                        |
|--------------------------------------|-----------------|------------------------------|
| <code>Q.nodes()</code> (no filter)   | $O(n)$          | Linear scan of nodes         |
| <code>.where(degree__gt=k)</code>    | $O(n + m)$      | Degree computation           |
| <code>.compute("degree")</code>      | $O(n + m)$      | Linear in edges              |
| <code>.compute("betweenness")</code> | $O(nm)$         | Expensive for large networks |
| <code>.compute("pagerank")</code>    | $O(k \cdot m)$  | $k$ iterations, $m$ edges    |
| <code>.order_by()</code>             | $O(n \log n)$   | Sorting results              |
| <code>.limit(k)</code>               | $O(k)$          | Constant after ordering      |
| <code>.to_pandas()</code>            | $O(n)$          | Result materialization       |

**Query optimization tips:**

- Apply `where()` filters early to reduce working set size
- Use `limit()` when you only need top-k results
- Avoid betweenness centrality on networks > 10K nodes (use sampling or degree-based measures)
- Cache results with `.to_pandas()` if reusing the same query output

### 12.3.2 Memory Requirements

**Memory usage guidelines:**

- **Small networks** (<10K nodes): Negligible overhead, all queries run in-memory
- **Medium networks** (10K-100K nodes):
  - Node queries: ~1-10 MB per query result

- Betweenness centrality:  $O(n^2)$  memory, problematic > 20K nodes
- PageRank:  $O(n)$  memory, scales well
- **Large networks** (>100K nodes):
  - Use streaming or chunked queries where possible
  - Disable `autocompute` if metrics are pre-computed: `Q.nodes().compute(..., autocompute=False)`
  - Export results incrementally with `.to_json(stream=True)` if available
  - Consider using external graph databases (Neo4j) for very large networks

**Best practices for large networks:**

1. Filter aggressively with `where()` before computing expensive measures
2. Use degree-based centrality instead of betweenness when possible
3. Sample nodes if exact answers aren't required
4. Leverage layer algebra to query subsets: `Q.nodes().from_layers(L["layer1"])`

### 12.3.3 When Not to Use the DSL

Use direct NetworkX/NumPy for:

- Single-layer graphs (DSL overhead not needed)
- Custom algorithms requiring fine-grained control
- Performance-critical inner loops

## 12.4 API Versioning Policy

### 12.4.1 Semantic Versioning

py3plex follows semantic versioning (MAJOR.MINOR.PATCH):

- **MAJOR** (1.x → 2.x) — Breaking changes possible
- **MINOR** (1.1 → 1.2) — New features, stable API unchanged
- **PATCH** (1.1.0 → 1.1.1) — Bug fixes only

### 12.4.2 Deprecation Policy

Deprecated features are:

1. Marked in documentation and code (warnings)
2. Maintained for at least one minor version
3. Removed in next major version

### 12.4.3 Migration Guides

When breaking changes occur in major versions, py3plex provides:

- **Migration guide documentation** in the CHANGELOG
- **Deprecation warnings** for at least one minor version before removal
- **Code examples** showing old vs. new API usage

- **Automated migration scripts** where feasible (e.g., for simple renames)

Migration guides are published in the `docs/migration/` directory and linked from the main documentation.

## 12.5 Summary

### Stable and production-ready:

- Node queries with filtering
- Core centrality measures
- Layer algebra
- Result export

### Use with awareness:

- Experimental features may change
- Large network performance depends on query structure
- Some features are planned but not yet implemented

The DSL prioritizes transparency about feature status and limitations. Users should feel confident relying on stable APIs while being aware of experimental features and performance boundaries.

#### See also

- **Full DSL reference:** `docfiles/user_guide/dsl.rst`
- **Algorithm roadmap:** `docfiles/algorithm_roadmap.rst`
- **Performance benchmarks:** `benchmarks/` directory

## CASE STUDY 1 — SOCIAL MULTIPLEX NETWORK

### Case Study Template

This case study provides a complete workflow template for social multiplex network analysis. The structure and code patterns are production-ready and can be adapted to your own datasets. Examples use representative synthetic data to demonstrate the analysis pipeline.

### DSL in Case Studies

This case study demonstrates DSL throughout the analysis workflow:

```
from py3plex.dsl import Q, L

# 1. Quick exploratory analysis
for platform in ["facebook", "twitter", "linkedin"]:
    stats = (
        Q.nodes()
        .from_layers(L[platform])
        .compute("degree", "clustering")
        .execute(network)
    )
    df = stats.to_pandas()
    print(f"{platform}: avg degree = {df['degree'].mean():.2f}")

# 2. Find cross-platform influencers
influencers = (
    Q.nodes()
    .from_layers(L["facebook"] + L["twitter"] + L["linkedin"])
    .where(degree__gt=50)
    .compute("betweenness centrality")
    .order_by("-betweenness centrality")
    .limit(20)
    .export_csv("influencers.csv")
    .execute(network)
)

# 3. Platform-specific analysis
twitter_only = (
    Q.nodes()
    .from_layers(L["twitter"] - L["facebook"] - L["linkedin"])
```

```
.compute("degree")
.execute(network)
)
```

DSL enables rapid iteration in exploratory research!

## 13.1 Domain Context

Social media users often maintain multiple online identities across platforms (Facebook, Twitter, LinkedIn, Instagram). This creates a **social multiplex network** where:

- **Nodes** represent users
- **Layers** represent platforms
- **Intra-layer edges** are friendships/follows within a platform
- **Inter-layer edges** link the same user across platforms

**Research questions:**

1. How do user roles vary across platforms?
2. Are influential users consistent across layers, or platform-specific?
3. Do communities align across platforms or fragment differently?
4. What cross-layer patterns emerge (e.g., Twitter influencers who are Facebook novices)?

### 13.1.1 Dataset Structure

**Example dataset:** Multi-platform social network

- **Nodes:** ~5,000 users (some present on multiple platforms)
- **Layers:** 3 platforms (Facebook, Twitter, LinkedIn)
- **Edges:** ~20,000 connections
- **Attributes:** User demographics (age, location), timestamps

**Data format (edgelist):**

```
# Format: source, source_layer, target, target_layer, weight
user_123, facebook, user_456, facebook, 1
user_123, twitter, user_789, twitter, 1
user_123, facebook, user_123, twitter, 1 # Inter-layer link
```

## 13.2 Loading the Data

### 13.2.1 Create and Load Network

```
from py3plex.core import multinet

# Create multilayer network
network = multinet.multi_layer_network(directed=False)

# Load from edgelist
```

```

network.load_network('social_multiplex.edgelist', input_type='edgelist')

# Verify structure
print(f"Nodes: {network.number_of_nodes()}")
print(f"Edges: {len(network.get_edges())}")
print(f"Layers: {network.get_layers()}")

# Basic statistics
network.basic_stats()

```

Expected output:

```

Nodes: 5234
Edges: 18976
Layers: ['facebook', 'twitter', 'linkedin']

```

## 13.3 Full Analysis Pipeline

### 13.3.1 Step 1: Exploratory Analysis

Start with layer-level statistics:

```

from py3plex.dsl import Q, L
import pandas as pd

# Collect statistics for each layer
layer_summary = []

for layer in ["facebook", "twitter", "linkedin"]:
    result = (
        Q.nodes()
        .from_layers(L[layer])
        .compute("degree", "clustering")
        .execute(network)
    )
    df = result.to_pandas()

    layer_summary.append({
        'layer': layer,
        'nodes': result.count,
        'avg_degree': df['degree'].mean(),
        'max_degree': df['degree'].max(),
        'avg_clustering': df['clustering'].mean()
    })

summary_df = pd.DataFrame(layer_summary)
print(summary_df)

```

**Interpretation:** Compare layer densities and clustering to understand platform differences.

### 13.3.2 Step 2: Community Detection

Find communities using multilayer Louvain:

```
from py3plex.algorithms.community_detection import multilayer_louvain

# Detect communities
communities = multilayer_louvain.best_partition(network.core_network)

# Add communities as node attributes
for node, comm_id in communities.items():
    network.core_network.nodes[node]['community'] = comm_id

# Count communities
n_communities = len(set(communities.values()))
print(f"Found {n_communities} communities")

# Largest communities
from collections import Counter
community_sizes = Counter(communities.values())
print("Top 5 communities by size:")
for comm_id, size in community_sizes.most_common(5):
    print(f"Community {comm_id}: {size} nodes")
```

### 13.3.3 Step 3: Centrality Analysis

Identify influential users using multilayer PageRank:

```
from py3plex.algorithms centrality_toolkit import multilayer_pagerank

# Compute multilayer PageRank
pagerank_scores = multilayer_pagerank(network.core_network)

# Use DSL to find top influencers
result = (
    Q.nodes()
    .compute("degree", "betweenness centrality")
    .execute(network)
)

df = result.to_pandas()
df['pagerank'] = df['node_id'].map(pagerank_scores)

# Top influencers
top_influencers = df.nlargest(20, 'pagerank')
print(top_influencers[['node_id', 'degree', 'betweenness centrality', 'pagerank']])
```

### 13.3.4 Step 4: Cross-Layer Patterns

Analyze how user importance varies across platforms:

```
# For each user, compute degree in each layer
user_profiles = {}
```



```

for layer in ["facebook", "twitter", "linkedin"]:
    result = (
        Q.nodes()
        .from_layers(L[layer])
        .compute("degree")
        .execute(network)
    )
    df = result.to_pandas()

    for _, row in df.iterrows():
        user_id = row['node_id'][0] # Extract base user ID
        if user_id not in user_profiles:
            user_profiles[user_id] = {}
        user_profiles[user_id][f"{layer}_degree"] = row['degree']

# Convert to DataFrame
profile_df = pd.DataFrame.from_dict(user_profiles, orient='index').fillna(0)

# Find cross-layer imbalances
profile_df['max_degree'] = profile_df.max(axis=1)
profile_df['min_degree'] = profile_df.min(axis=1)
profile_df['imbalance'] = profile_df['max_degree'] / (profile_df['min_degree'] + 1)

# Users with high imbalance (platform specialists)
specialists = profile_df.nlargest(10, 'imbalance')
print("Platform specialists (high cross-layer imbalance):")
print(specialists)

```

### 13.3.5 Step 5: Visualization

Create publication-ready visualizations:

```

from py3plex.visualization.multilayer import draw_multilayer_default
import matplotlib.pyplot as plt

# Visualize network with communities colored
draw_multilayer_default(
    network.get_layers(),
    node_size=8,
    labels=True,
    background_shape="circle",
    scale_by_size=True, # Scale nodes by degree
    display=True
)

plt.title("Social Multiplex Network - Community Structure")
plt.savefig("social_multiplex_communities.png", dpi=300, bbox_inches='tight')

```

## 13.4 Key Findings (Template)

### 13.4.1 Community Structure

**Observation:** Communities tend to form around shared topics or interests. Nodes with high inter-community connectivity (high betweenness) act as bridges between different social groups. The community structure often correlates with geographic or demographic factors in real social networks.

- **Cross-platform communities:** X% of users in same community across all layers
- **Platform-specific communities:** Y% of communities confined to single layer
- **Community alignment:** Normalized Mutual Information = Z

**Interpretation:** Cross-platform community alignment suggests that social structures persist across different communication channels, likely reflecting offline social relationships or shared interests. Platform-specific communities indicate specialized use cases (e.g., professional networking on LinkedIn vs. casual social interaction on Facebook).

### 13.4.2 Cross-Layer Roles

**Observation:** User roles vary significantly across platforms. A highly central user on one platform may be peripheral on another, reflecting different usage patterns, social contexts, or specialization. Cross-platform influencers (high centrality on multiple layers) are relatively rare but strategically important for information diffusion.

- **Consistent influencers:** N users with high centrality on all platforms
- **Platform specialists:** M users highly central on one platform only
- **Role switching:** Average centrality correlation across layers =

**Interpretation:** [How do user strategies differ by platform?]

## 13.5 Pitfalls Encountered

### 13.5.1 Data Cleaning Issues

**Challenge:** User identity resolution across platforms

- Usernames differ across platforms
- Manual matching required for subset of users
- Missing links lead to underestimated cross-layer effects

**Solution:** Use email-based or profile-based matching when available

### 13.5.2 Performance Considerations

**Challenge:** Betweenness centrality computation slow for large networks

- $O(n^3)$  complexity becomes prohibitive for >10,000 nodes
- Consider sampling or approximation algorithms

**Solution:** Use degree or PageRank for large-scale analysis; reserve betweenness for focused subgraphs

## 13.6 Reproducibility

### 13.6.1 Code Repository

Full analysis code available at: `examples/case_studies/social_multiplex_analysis.py`

To reproduce this analysis:

```
# Clone repository
git clone https://github.com/SkBlaz/py3plex.git
cd py3plex

# Install dependencies
pip install -e .

# Run analysis
python examples/case_studies/social_multiplex_analysis.py
```

### 13.6.2 Data Availability

**Synthetic data** for this case study is available in: `examples/datasets/synthetic_social_multiplex.edgelist`

For real datasets, consider:

- **Twitter + Facebook:** Similar methodology can be applied to real datasets (subject to API access and data use agreements)
- **Academic multiplex:** DBLP + ArXiv coauthorship networks
- **Contact datasets:** See `multilayer_datasets/` directory

## 13.7 Summary

This case study demonstrated:

1. **Data loading** from edgelist format
2. **Exploratory analysis** using DSL for layer statistics
3. **Community detection** with multilayer Louvain
4. **Centrality analysis** with multilayer PageRank
5. **Cross-layer pattern detection** (role switching, specialists)
6. **Visualization** for publication

**Key workflow:**

1. Load → 2. Explore → 3. Detect communities → 4. Compute centrality → 5. Analyze patterns → 6. Visualize

**Adapt this workflow to your own social multiplex datasets by:**

- Adjusting layer names
- Modifying centrality thresholds
- Adding domain-specific measures
- Customizing visualizations

## CASE STUDY 2 — BIOLOGICAL MULTILAYER NETWORK

### Case Study Template

This case study demonstrates a complete workflow for biological multilayer network analysis. The methodology and code patterns are production-ready and applicable to real datasets. Examples use representative synthetic data to illustrate the analysis pipeline while protecting proprietary biological data.

### 14.1 Domain Context

Biological systems exhibit multilayer structure through different interaction types:

- **Protein-protein interactions** — Physical binding
- **Regulatory relationships** — Gene expression control
- **Metabolic pathways** — Enzyme-substrate relationships
- **Co-expression networks** — Correlated expression across conditions

A **biological multiplex network** represents these different interaction mechanisms as separate layers while capturing the same entities (genes/proteins) across layers.

#### Research questions:

1. How do protein functions differ across interaction types?
2. Which genes are central in regulation but peripheral in metabolism?
3. Do communities reflect functional modules consistently across layers?
4. How do dynamics (e.g., epidemic-like spreading) differ by interaction type?

#### 14.1.1 Dataset Structure (Template)

**Example dataset:** Multi-omic interaction network

- **Nodes:** ~2,000 genes/proteins
- **Layers:** Physical interaction, regulatory, metabolic
- **Edges:** ~10,000 interactions across layers
- **Attributes:** GO terms, tissue specificity, expression levels
- **Focus:** Dynamics simulation and layer-specific analysis

**Data format:**

```
# Format: gene_A, interaction_type, gene_B, interaction_type, confidence
BRCA1, protein_interaction, TP53, protein_interaction, 0.95
BRCA1, regulation, ATM, regulation, 0.87
TP53, metabolic, MDM2, metabolic, 0.92
```

## 14.2 Loading and Preprocessing

### 14.2.1 Create and Load Network

```
from py3plex.core import multinet

# Create biological multilayer network
network = multinet.multi_layer_network(directed=True) # Regulation is directed

# Load from biological database format
network.load_network('biological_multiplex.edgelist', input_type='edgelist')

# Add gene annotations (GO terms, etc.)
# annotations = load_annotations('gene_annotations.tsv')
# for node in network.get_nodes():
#     network.core_network.nodes[node]['GO_terms'] = annotations.get(node[0], [])

print(f"Loaded {network.number_of_nodes()} genes")
print(f"Layers: {network.get_layers()}")
```

## 14.3 Analysis Pipeline Sketch

### 14.3.1 Step 1: Network Topology

Analyze structural properties of each interaction layer:

```
from py3plex.dsl import Q, L

# Compare topology across interaction types
for layer in ["protein_interaction", "regulation", "metabolic"]:
    result = (
        Q.nodes()
        .from_layers(L[layer])
        .compute("degree", "clustering")
        .execute(network)
    )
    df = result.to_pandas()
    print(f"{layer}: avg degree = {df['degree'].mean():.2f}, "
          f"avg clustering = {df['clustering'].mean():.3f}")
```

**Expected patterns:**

- Protein interaction: High clustering (modules)
- Regulation: Lower clustering (hierarchical)
- Metabolic: Medium clustering (pathways)

### 14.3.2 Step 2: Dynamics Simulation

Model information spreading or cascade dynamics using SIR model:

```
from py3plex.dynamics import SIRDynamics

# Simulate disease/perturbation spreading
sir = SIRDynamics(
    network,
    beta=0.3,      # Transmission rate
    gamma=0.1,     # Recovery rate
    initial_infected=0.05 # Start with 5% infected
)
sir.set_seed(42)

results = sir.run(steps=100)

# Analyze outbreak size
final_recovered = results.get_measure("state_counts")['R'][-1]
print(f"Final outbreak size: {final_recovered / network.number_of_nodes():.1%}")
```

**Research question:** How does perturbation spread differently through physical vs. regulatory interactions?

### 14.3.3 Step 3: Layer-Specific Analysis

Identify genes that are central in one layer but not others:

```
# Find regulatory hubs
regulatory_hubs = (
    Q.nodes()
    .from_layers(L["regulation"])
    .where(degree__gt=20)
    .compute("betweenness centrality")
    .execute(network)
)

# Find protein interaction hubs
ppi_hubs = (
    Q.nodes()
    .from_layers(L["protein_interaction"])
    .where(degree__gt=20)
    .compute("betweenness centrality")
    .execute(network)
)

# Compare overlap
reg_hub_ids = set(regulatory_hubs.node_ids)
ppi_hub_ids = set(ppi_hubs.node_ids)

overlap = reg_hub_ids & ppi_hub_ids
reg_only = reg_hub_ids - ppi_hub_ids
ppi_only = ppi_hub_ids - reg_hub_ids

print(f"Overlap: {len(overlap)} genes")
print(f"Regulatory only: {len(reg_only)} genes")
```

```
print(f"PPI only: {len(ppi_only)} genes")
```

### 14.3.4 Step 4: Intervention Analysis

Simulate what-if scenarios: node removal, layer removal:

```
import copy

# Baseline dynamics
baseline_sir = SIRDynamics(network, beta=0.3, gamma=0.1)
baseline_sir.set_seed(42)
baseline_results = baseline_sir.run(steps=100)
baseline_outbreak = baseline_results.get_measure("state_counts")['R'][-1]

# Intervention: Remove top hub
network_intervened = copy.deepcopy(network)
top_hub = regulatory_hubs.node_ids[0]
network_intervened.core_network.remove_node(top_hub)

# Dynamics after intervention
intervened_sir = SIRDynamics(network_intervened, beta=0.3, gamma=0.1)
intervened_sir.set_seed(42)
intervened_results = intervened_sir.run(steps=100)
intervened_outbreak = intervened_results.get_measure("state_counts")['R'][-1]

reduction = (baseline_outbreak - intervened_outbreak) / baseline_outbreak
print(f"Outbreak reduced by {reduction:.1%} after removing hub")
```

## 14.4 Key Findings (Template)

### 14.4.1 Spreading Patterns

**Expected observation:** Cascade dynamics depend on layer structure

- **Protein interaction layer:** Slow, localized spreading (high clustering)
- **Regulatory layer:** Fast, global spreading (low clustering, directed)
- **Metabolic layer:** Intermediate spreading

**Interpretation:** Regulatory interactions enable rapid perturbation propagation

### 14.4.2 Layer Interactions

**Expected observation:** Cross-layer hub genes

- Genes highly central in both protein interaction and regulation
- These genes are critical: removing them has amplified impact
- Potential drug targets or disease genes

## 14.5 Summary

This case study template demonstrates:

1. **Biological network loading** with proper directionality
2. **Layer-specific topology** analysis
3. **Dynamics simulation** (SIR model for perturbation spreading)
4. **Intervention analysis** (what-if scenarios)
5. **Cross-layer hub identification**

**To complete this case study:**

1. Obtain biological multiplex dataset (e.g., STRING + RegulonDB + KEGG)
2. Add gene annotations (GO terms, pathways)
3. Run analysis pipeline
4. Validate findings against known biology
5. Visualize with annotations

**Relevant examples:**

- `examples/dynamics/example_sir_model.py` — SIR dynamics
- `examples/network_analysis/example_multilayer_centrality.py` — Centrality analysis
- `docfiles/sir_epidemic_simulator.rst` — SIR documentation



## CASE STUDY 3 — TRANSPORTATION NETWORK

### Case Study Template

This case study outlines a complete workflow for transportation multilayer network analysis. The approach demonstrates advanced techniques including temporal analysis and large-scale DSL queries. Examples use representative synthetic data to illustrate methodology applicable to real transportation datasets.

## 15.1 Domain Context

Urban transportation systems are inherently multilayer:

- **Nodes:** Locations (stations, stops, intersections)
- **Layers:** Transportation modes (subway, bus, bike-share, walking)
- **Edges:** Direct connections between locations within each mode
- **Inter-layer edges:** Transfer points between modes
- **Temporal dimension:** Schedules, rush hours, seasonal patterns

### Research questions:

1. How do disruptions in one mode affect overall connectivity?
2. Which stations are critical hubs across multiple modes?
3. How do communities of well-connected areas differ by mode?
4. What is the optimal multi-modal route between locations?

## 15.2 Potential Analysis Directions

### 15.2.1 Resilience Analysis

Simulate mode disruptions and measure impact:

```
from py3plex.dsl import Q, L

# Baseline connectivity
baseline = (
    Q.nodes()
    .compute("betweenness centrality")
    .execute(network)
)
```

```

# Remove subway layer
reduced_network = network.remove_layer("subway")

# Recompute connectivity
disrupted = (
    Q.nodes()
    .compute("betweenness centrality")
    .execute(reduced_network)
)

# Identify most affected locations
baseline_df = baseline.to_pandas()
disrupted_df = disrupted.to_pandas()

# Compare betweenness changes
for idx in baseline_df.index:
    node = baseline_df.loc[idx, 'node']
    layer = baseline_df.loc[idx, 'layer']
    base_bc = baseline_df.loc[idx, 'betweenness centrality']

    # Find matching node in disrupted network
    disrupted_row = disrupted_df[
        (disrupted_df['node'] == node) & (disrupted_df['layer'] == layer)
    ]
    if not disrupted_row.empty:
        disrupt_bc = disrupted_row.iloc[0]['betweenness centrality']
        impact = (base_bc - disrupt_bc) / base_bc if base_bc > 0 else 0
        if impact > 0.2: # More than 20% reduction
            print(f"High impact: {node} in {layer}, {impact:.1%} reduction")

```

## 15.2.2 Multi-Modal Path Analysis

Find optimal paths using multiple transportation modes:

```

# Shortest path across modes
import networkx as nx

path = nx.shortest_path(
    network.core_network,
    source=('location_A', 'bus'),
    target=('location_B', 'subway')
)

# Identify mode switches in path
mode_switches = 0
for i in range(len(path) - 1):
    current_mode = path[i][1] # Layer is second element of tuple
    next_mode = path[i+1][1]
    if current_mode != next_mode:
        mode_switches += 1
        print(f"Switch from {current_mode} to {next_mode} at {path[i][0]}")

```

```
print(f"Total mode switches: {mode_switches}")
print(f"Path length: {len(path)} stops")
```

### 15.2.3 Temporal Dynamics

Analyze how network properties change throughout the day:

```
from py3plex.dsl import Q
import pandas as pd

# Example: Analyze network at different time windows
time_windows = [(0, 6), (6, 12), (12, 18), (18, 24)] # Hours of day
temporal_stats = []

for start_hour, end_hour in time_windows:
    # Filter edges by time window (assuming temporal metadata)
    result = (
        Q.nodes()
        .compute("degree", "betweenness centrality")
        .execute(network)
    )

    stats = {
        'window': f"{start_hour:02d}:00-{end_hour:02d}:00",
        'avg_degree': result.to_pandas()['degree'].mean(),
        'avg_betweenness': result.to_pandas()['betweenness centrality'].mean()
    }
    temporal_stats.append(stats)

# Display temporal patterns
temporal_df = pd.DataFrame(temporal_stats)
print(temporal_df)
```

### 15.2.4 DSL-Heavy Analysis

Demonstrate advanced DSL patterns:

```
from py3plex.dsl import Q, L, Param

# Parameterized cross-modal analysis
hub_query = (
    Q.nodes()
    .from_layers(
        L[Param.str("mode1")] + L[Param.str("mode2")]
    )
    .where(degree__gt=Param.int("threshold"))
    .compute("betweenness centrality", "closeness centrality")
    .order_by("-betweenness centrality")
    .limit(20)
)

# Execute for different mode combinations
for mode1, mode2 in [("subway", "bus"), ("bus", "bike"), ("subway", "bike")]:
```

```
result = hub_query.execute(  
    network,  
    mode1=mode1,  
    mode2=mode2,  
    threshold=10  
)  
print(f"{mode1} + {mode2}: {result.count} hubs")
```

## 15.3 Summary

This case study (when completed) will demonstrate:

1. **Temporal multilayer networks** — Time-varying structure
2. **Resilience analysis** — Impact of layer removal
3. **Multi-modal routing** — Path finding across layers
4. **Large-scale DSL queries** — Advanced query patterns
5. **Geospatial visualization** — Map-based network rendering

**To complete:**

1. Obtain transportation dataset (GTFS format, OpenStreetMap)
2. Construct multilayer representation
3. Implement temporal slicing
4. Run resilience experiments
5. Visualize with geospatial coordinates

**Relevant resources:**

- GTFS (General Transit Feed Specification) for public transit data
- OpenStreetMap for walking/cycling networks
- `examples/network_analysis/` for DSL patterns

## TESTING AND VALIDATION

py3plex uses a comprehensive testing strategy to ensure correctness across algorithms, data structures, and the DSL. This chapter provides a high-level overview of testing philosophy and organization. **For detailed validation scripts and test code, see Appendix C.**

### 16.1 Testing Philosophy

py3plex testing follows four principles:

1. **Correctness first:** Algorithms must produce mathematically correct results
2. **Conservation laws:** Physical constraints (e.g., probability conservation) must hold
3. **Regression prevention:** Known-good outputs are compared against current runs
4. **Property testing:** Invariants should hold for random inputs

#### 16.1.1 Test Categories

- **Unit tests** — Individual functions and methods in isolation
- **Integration tests** — Module interactions and end-to-end workflows
- **Property-based tests** — Hypothesis-driven testing with random inputs
- **Regression tests** — Compare against reference runs for dynamics models

### 16.2 Test Organization

The test suite is organized by module and functionality:

```
tests/
├── test_core.py           # Core data structures
├── test_dsl*.py          # DSL functionality (10+ files)
├── test_dynamics*.py     # Dynamics models
├── test_algorithms*.py   # Algorithm correctness
├── test_centrality*.py   # Centrality measures
├── test_community*.py    # Community detection
├── test_io*.py           # I/O and serialization
├── test_uncertainty*.py  # Uncertainty quantification
└── property/            # Property-based tests (planned)
```

**Current coverage:** ~85% code coverage across core modules.

## 16.3 Key Validation Strategies

### 16.3.1 Random Walk Conservation

Random walks must conserve probability—transition probabilities from any state must sum to 1:

```
def test_random_walk_conservation():
    """Verify random walk conserves probability."""
    # Implementation in tests/test_random_walk_conservation.py
    # Computes transition matrix and checks row sums 1.0
```

**Tests:** tests/test\_paths.py includes walk conservation checks.

### 16.3.2 Node2Vec Validation

Validate that Node2Vec biases (parameters p and q) have the intended effects:

- Higher p → reduced probability of returning to previous node
- Higher q → preference for local exploration vs. distant jumps

**Tests:** tests/test\_node2vec.py validates bias behavior.

### 16.3.3 Community Detection Validation

Verify that community detection algorithms satisfy basic properties:

- **Modularity bounds:** Q [-0.5, 1.0]
- **Partition completeness:** Every node assigned to exactly one community
- **Singleton handling:** Isolated nodes form their own communities

**Tests:** tests/test\_community\*.py files validate Louvain, Infomap, and other algorithms.

### 16.3.4 Dynamics Validation

Epidemic models must satisfy conservation laws:

- **SIS:**  $S(t) + I(t) = N$  for all t
- **SIR:**  $S(t) + I(t) + R(t) = N$  for all t
- **Steady state:** SIS reaches equilibrium for subcritical parameters

**Tests:** tests/test\_dynamics.py validates SIR, SIS, and other models with reference runs.

## 16.4 Running Tests

### 16.4.1 Basic Test Execution

```
# Run all tests
pytest tests/

# Run specific test file
pytest tests/test_dsl.py

# Run tests matching a pattern
pytest tests/ -k "test_community"
```

```
# Run with coverage
pytest tests/ --cov=py3plex --cov-report=html

# Verbose output
pytest tests/ -v
```

## 16.4.2 Using Makefile

```
make test          # Run all tests
make test-coverage # Generate HTML coverage report
make test-fast     # Run only fast tests (skip slow integration tests)
```

### Test markers:

- `@pytest.mark.slow` — Tests that take >5 seconds
- `@pytest.mark.integration` — End-to-end integration tests
- `@pytest.mark.hypothesis` — Property-based tests

## 16.5 Continuous Integration

py3plex uses GitHub Actions for automated testing on every commit and pull request.

### 16.5.1 GitHub Actions

The CI pipeline tests across:

- **Python versions:** 3.8, 3.9, 3.10, 3.11, 3.12
- **Operating systems:** Ubuntu Linux, macOS, Windows
- **Test suites:** Core, DSL, algorithms, dynamics, I/O

**Build status:** Tests must pass on all platforms before merging.

**Coverage requirements:** New code should maintain or improve coverage (target: 85%+).

#### CI Configuration

The GitHub Actions workflow files are located in `.github/workflows/` in the repository. Key workflows include `test.yml` (main test suite), `lint.yml` (code quality checks), and `docs.yml` (documentation builds).

## 16.6 Summary

py3plex testing ensures correctness through:

1. **Comprehensive test suite** — 200+ tests across core functionality
2. **Multiple validation strategies** — Conservation laws, property tests, reference runs
3. **Continuous integration** — Automated testing on all platforms
4. **High coverage** — 85%+ code coverage

Testing is an ongoing priority. Contributions that add tests for uncovered code or validate edge cases are especially welcome.

**For detailed test scripts and validation examples, see Appendix C.**

**Next chapter:** Reproducible environments and deployment practices



## REPRODUCIBLE ENVIRONMENTS

Reproducibility is fundamental to scientific computing. This chapter covers practices for creating consistent, reproducible analysis environments using py3plex. **For detailed Docker configurations and deployment recipes, see Appendix B.**

### 17.1 Reproducibility Principles

Reproducible research requires:

1. **Isolated environments** — Avoid conflicts between projects and system packages
2. **Dependency pinning** — Lock package versions to prevent drift
3. **Seed management** — Control randomness in stochastic processes
4. **Environment documentation** — Record exact configurations used

Without these practices, analyses may produce different results on different machines or at different times, undermining scientific validity.

### 17.2 Environment Management

#### 17.2.1 Python Virtual Environments

Use `venv` or `conda` to isolate py3plex installations:

**Using `venv` (built-in):**

```
# Create virtual environment
python3 -m venv py3plex-env

# Activate (Linux/macOS)
source py3plex-env/bin/activate

# Activate (Windows)
py3plex-env\Scripts\activate

# Install py3plex
pip install py3plex

# Deactivate when done
deactivate
```

**Using `conda`:**

```
# Create conda environment
conda create -n py3plex python=3.10

# Activate
conda activate py3plex

# Install py3plex
pip install py3plex

# Deactivate
conda deactivate
```

**Recommendation:** Use venv for simple projects, conda when you need non-Python dependencies (e.g., graph-tool, igraph bindings).

### 17.2.2 Dependency Pinning

Lock exact package versions to ensure reproducibility:

**Two-file approach (recommended):**

1. `requirements.in` — High-level dependencies with version ranges

```
# requirements.in
py3plex>=1.0.0
numpy>=1.24.0
networkx>=3.0
```

2. `requirements.txt` — Exact pinned versions (generated)

```
# Generate exact pins from requirements.in
pip-compile requirements.in --output-file requirements.txt

# This creates entries like:
# py3plex==1.1.0
# numpy==1.24.3
# networkx==3.1
# matplotlib==3.7.1
# scipy==1.10.1
# pandas==2.0.2
# (includes all transitive dependencies)
```

**Install from pinned file:**

```
pip install -r requirements.txt
```

**Single-file approach (simpler but less flexible):**

```
# Generate requirements file with exact versions
pip freeze > requirements.txt

# Reproduce environment on another machine
pip install -r requirements.txt
```

**Trade-offs:**

- **Exact pins** (==) ensure reproducibility but may miss security patches
- **Version ranges** (>=) allow updates but may introduce drift
- **Recommended:** Use exact pins in `requirements.txt` for reproducible research, maintain `requirements.in` with ranges for development

**Best practices:**

- Commit `requirements.txt` to version control
- Regenerate when dependencies change
- Use separate files for development (`requirements-dev.txt`) and production

**Example requirements.txt structure (with exact pins):**

```
# Core dependencies (exact versions)
py3plex==1.1.0
numpy==1.24.3
scipy==1.10.1
networkx==3.1

# Optional features
matplotlib==3.7.1
pandas==2.0.2
```

## 17.3 Docker Containers (Overview)

Docker provides the strongest reproducibility guarantees by packaging the entire environment—OS, Python, libraries, and code—into a container.

### 17.3.1 Why Docker?

- **Complete isolation** — No system Python conflicts, no OS differences
- **Perfect reproducibility** — Identical environment across machines and time
- **Portability** — Share complete analysis environment with collaborators
- **Deployment** — Easy transition from development to production

### 17.3.2 Basic Docker Usage

```
# Build py3plex image
docker build -t py3plex:latest .

# Run analysis script
docker run --rm -v $(pwd):/workspace py3plex:latest \
    python /workspace/analysis.py

# Interactive shell
docker run --rm -it py3plex:latest bash
```

**When to use Docker:**

- **Multi-machine reproducibility** — Running on clusters, cloud, or different dev machines
- **Long-term archival** — Preserve exact environment for future replication

- **Production deployment** — Consistent behavior from dev to production

For detailed Dockerfile examples, docker-compose configurations, and deployment recipes, see Appendix B.

## 17.4 Seed Management

### 17.4.1 Controlling Randomness

Set seeds for all stochastic processes to ensure deterministic results:

```
import random
import numpy as np

# Set global seeds
random.seed(42)
np.random.seed(42)

# For dynamics models
from py3plex.dynamics import SIRDynamics

sir = SIRDynamics(network, beta=0.3, gamma=0.1)
sir.set_seed(42) # Reproducible epidemic simulation
results = sir.run(steps=100)

# For random graph generation
import networkx as nx
G = nx.erdos_renyi_graph(100, 0.1, seed=42)
```

**Seed management checklist:**

1. Set seeds at the **start** of scripts before any randomness
2. Document seed values in code comments and papers
3. Use **different seeds** for different experiments (42, 43, 44, ...)
4. Re-run with multiple seeds to assess variability

## 17.5 Recording Environments

### 17.5.1 Document Analysis Environments

Record environment details for publication and replication:

```
import platform
import sys
import py3plex
import numpy as np
import networkx as nx

# Print environment summary
print("Environment Information:")
print(f" Python: {sys.version}")
print(f" Platform: {platform.platform()}")
print(f" py3plex: {py3plex.__version__}")
```

```
print(f" NumPy: {np.__version__}")
print(f" NetworkX: {nx.__version__}")
```

**Include in papers/reports:**

- Python version (e.g., Python 3.10.8)
- py3plex version (e.g., 1.1.0)
- Key dependency versions (NumPy, NetworkX, SciPy)
- Operating system (Linux, macOS, Windows)
- Hardware details for performance-critical analyses

## 17.5.2 Version Control for Code

Use Git to track code changes:

```
# Initialize repository
git init
git add analysis.py requirements.txt
git commit -m "Initial analysis code"

# Tag important versions
git tag -a v1.0 -m "Version used for paper submission"
```

**Best practices:**

- Commit `requirements.txt` and environment configs
- Use meaningful commit messages
- Tag versions used for publications
- Don't commit large datasets (use Git LFS or external storage)

## 17.5.3 Version Control for Data

For input datasets:

- **Small datasets (<100 MB):** Commit directly to Git
- **Medium datasets (100 MB - 1 GB):** Use Git LFS
- **Large datasets (>1 GB):** Store externally (Zenodo, OSF, Dataverse) and include download script

**Example download script:**

```
# download_data.py
import urllib.request

# Dataset DOI and URL
DOI = "10.5281/zenodo.1234567"
URL = "https://zenodo.org/record/1234567/files/network.edgelist"

print(f"Downloading dataset from {DOI}")
urllib.request.urlretrieve(URL, "data/network.edgelist")
print("Download complete")
```

## 17.6 Summary

**Essential practices for reproducible py3plex analyses:**

1. **Use virtual environments** (venv or conda) to isolate dependencies
2. **Pin exact versions** with `pip freeze > requirements.txt`
3. **Set random seeds** for all stochastic processes
4. **Record environment details** in papers and code comments
5. **Use version control** (Git) for code, Git LFS or external storage for data
6. **Consider Docker** for maximum reproducibility and deployment

**For production deployments:**

- Use Docker containers for complete environment isolation
- See Appendix B for Dockerfile templates and docker-compose configurations
- See Appendix A for repository structure best practices

**Next chapter:** Overview of the py3plex GUI for visual exploration

## THE PY3PLEX GUI (OVERVIEW)

The py3plex GUI is a web-based interface for interactive multilayer network exploration. It provides point-and-click access to py3plex features without requiring programming. **For detailed deployment configurations and production setup, see Appendix B.**

### Status: Experimental

The py3plex GUI is **experimental** and designed for **local use only**. It is not hardened for public internet deployment. Use for exploration and learning, not production analysis.

## 18.1 What is the Py3plex GUI?

The GUI is a FastAPI + SvelteKit web application that provides:

- **Network upload** — Load networks from files (edgelist, GraphML, JSON)
- **Interactive visualization** — D3.js-powered network rendering
- **Query interface** — Execute DSL queries via web forms
- **Analysis workflows** — Common operations (centrality, communities) without coding
- **Export results** — Download analysis outputs as CSV/JSON

**Target users:** Researchers learning py3plex, educators demonstrating concepts, non-programmers exploring networks.

## 18.2 Architecture

### 18.2.1 Technology Stack

- **Backend:** FastAPI (Python) — Fast, async HTTP server
- **Frontend:** SvelteKit (JavaScript) — Reactive UI framework
- **Visualization:** D3.js (static), Plotly (interactive)
- **API:** RESTful HTTP endpoints for network operations
- **Storage:** Local filesystem for uploads (no database)

**Component structure:**

```
gui/  
├── api/           # FastAPI backend  
│   └── app.py     # Main server
```

```

├── routes/      # API endpoints
├── models/      # Data models
├── frontend/    # SvelteKit app
│   ├── src/
│   │   ├── routes/ # Pages
│   │   └── lib/     # Components
│   └── static/      # Assets
└── uploads/       # Temporary file storage

```

For detailed architecture documentation, see: `docfiles/gui/gui_architecture.rst`

## 18.3 Running Locally

### 18.3.1 Installation

Install py3plex with GUI dependencies:

```

# Install with GUI extras
pip install 'py3plex[gui]'

# Or from source
cd py3plex
pip install -e '.[gui]'

```

### 18.3.2 Quickstart with Docker Compose

The recommended way to run the GUI locally is using Docker Compose:

```

# Navigate to GUI directory
cd gui

# Start all services (API, frontend, Redis, worker)
docker compose up -d

# Access the GUI at http://localhost:8080
# API available at http://localhost:8000
# Flower (task monitor) at http://localhost:5555

```

**Services started:**

- **API:** FastAPI backend on port 8000 (uvicorn server) - internal
- **Frontend:** SvelteKit dev server on port 5173 - internal
- **Nginx:** Reverse proxy on port 8080 - **access GUI here**
- **Redis:** Task queue backend on port 6379 - internal
- **Worker:** Celery worker for background tasks - internal

**Access the GUI at `http://localhost:8080`** - Nginx routes requests to the appropriate backend services.



### 18.3.3 Manual Development Setup

For development without Docker:

```
# Terminal 1: Start backend
cd gui/api
pip install -r requirements.txt
uvicorn app.main:app --reload --port 8000

# Terminal 2: Start frontend
cd gui/frontend
npm install
npm run dev

# Open browser to http://localhost:5173
```

**Note:** Manual setup requires Redis running separately for background tasks.

### 18.3.4 Configuration

Basic configuration in `gui/api/config.py`:

```
# Development settings
DEBUG = True
HOST = '0.0.0.0'
PORT = 8000

# File handling
UPLOAD_FOLDER = './uploads'
MAX_UPLOAD_SIZE = 100 * 1024 * 1024 # 100 MB

# Analysis limits
MAX_NODES = 10000 # Prevent performance issues
```

## 18.4 Key Workflows

### 18.4.1 Upload and Explore

**Basic workflow:**

1. **Upload network** — Click “Upload Network”, select file (edgelist, GraphML, etc.)
2. **View statistics** — See node count, edge count, layer info
3. **Visualize** — Interactive network rendering with zoom/pan
4. **Layer selection** — Toggle layers on/off for focused viewing
5. **Export** — Download visualization as PNG or SVG

### 18.4.2 Query Interface

Execute DSL queries without writing code:

1. Navigate to “Query” tab
2. Build query using form:

- Select target: nodes or edges
  - Choose layers
  - Add filters (degree, centrality, etc.)
  - Select measures to compute
  - Set ordering and limits
3. Click “Execute”
  4. View results in table
  5. Export as CSV or JSON

**Example:** “Find top 20 nodes by betweenness centrality in the social layer”

### 18.4.3 Analysis Pipelines

Pre-built workflows for common analyses:

- **Community Detection** — Run Louvain or Infomap, visualize communities
- **Centrality Analysis** — Compute degree, betweenness, PageRank
- **Layer Comparison** — Compare statistics across layers
- **Ego Networks** — Extract neighborhoods around selected nodes

Each pipeline provides a guided interface with sensible defaults.

## 18.5 Limitations and Safety

### 18.5.1 Security Considerations

**WARNING:** The GUI is **NOT** secure for public deployment.

- **No authentication** — Anyone with URL access can use it
- **No rate limiting** — Vulnerable to resource exhaustion
- **No input sanitization** — File uploads not sandboxed
- **No HTTPS** — Data transmitted in plaintext

**Safe use cases:**

- Local machine only (localhost)
- Trusted network (lab/office LAN)
- Single-user exploration

**Unsafe use cases:**

- Public internet exposure
- Multi-tenant environments
- Sensitive data processing

**If you must deploy beyond localhost:** The GUI requires significant security hardening. See Appendix B for technical details on authentication, TLS, and reverse proxy configuration. However, note that even with these measures, the GUI is not designed as a production-grade web service and should only be deployed in controlled, trusted environments.

## 18.5.2 Scalability Limits

Performance degrades with network size:

- **<1,000 nodes** — Full interactivity, all features work well
- **1,000-5,000 nodes** — Some slowness, simplify visualizations
- **5,000-10,000 nodes** — Limited features, use minimal layouts
- **>10,000 nodes** — **Use CLI/library instead**, GUI becomes unusable

**Tips for large networks:**

- Use layer filtering to reduce size
- Disable interactive visualization
- Export to CSV and analyze programmatically

## 18.6 When to Use the GUI vs CLI

Use GUI for:

- **Exploratory analysis** — Quick network inspection and hypothesis testing
- **Learning** — Understanding py3plex features interactively
- **Demonstration** — Presenting to non-programmers or stakeholders
- **Rapid prototyping** — Testing analysis ideas before writing code

Use CLI/library for:

- **Large networks** — >5,000 nodes
- **Production workflows** — Automated, reproducible pipelines
- **Complex analyses** — Chaining multiple operations
- **Performance-critical tasks** — Maximum speed and control
- **Reproducibility** — Version-controlled scripts

## 18.7 Summary

The py3plex GUI provides:

- **Interactive exploration** without requiring programming skills
- **Visual network rendering** with D3.js and Plotly
- **Query interface** for executing DSL queries via forms
- **Pre-built workflows** for common analyses
- **Local deployment** for individual researchers and small teams

**Key limitations:**

- **Experimental status** — Not production-ready
- **Security** — Local use only, no public deployment
- **Performance** — Limited to small/medium networks (<5,000 nodes)
- **Features** — Advanced capabilities require CLI/library

For deployment details and security hardening, see Appendix B. For GUI API reference, see: `docfiles/gui/gui_api_reference.rst`

## APPENDIX A: REPOSITORY LAYOUT AND SCRIPTS

This appendix provides a reference for the py3plex repository structure and maps book examples to actual scripts.

### 19.1 Repository Structure

#### 19.1.1 Top-Level Organization

```
py3plex/
├── py3plex/           # Main package
├── tests/             # Test suite
├── examples/          # 50+ example scripts
├── docfiles/          # Documentation source (Sphinx)
├── book/              # This book's source files
├── gui/               # Web GUI application
├── benchmarks/        # Performance benchmarks
├── datasets/          # Sample datasets
├── pyproject.toml      # Package configuration
├── Makefile           # Development automation
└── README.md          # Project overview
```

#### 19.1.2 Main Package Structure

```
py3plex/
├── __init__.py
├── core/              # Data structures
│   ├── multinet.py    # multi_layer_network class
│   └── random_generators.py
├── algorithms/        # Analysis algorithms
│   ├── statistics/
│   ├── centrality/
│   ├── community_detection/
│   └── paths/
├── dynamics/          # Dynamical processes
│   ├── models.py      # SIS, SIR, SEIR
│   ├── core.py
│   └── compartmental.py
├── dsl/               # Query language
│   ├── __init__.py
│   ├── builder.py      # Builder API
│   └── executor.py
```

```

├── export.py
├── visualization/      # Plotting
├── io/                 # I/O handlers
│   ├── readers.py
│   └── writers.py
├── cli.py              # Command-line interface
├── graph_ops.py        # Dplyr-style API
├── pipeline.py         # sklearn-style pipelines
└── workflows.py       # Config-driven workflows

```

## 19.2 Examples Directory

The `examples/` directory contains 50+ working scripts organized by topic:

```

examples/
├── getting_started/    # Introductory examples
├── network_analysis/  # Core analysis examples
│   ├── example_dsl_builder_api.py    # DSL chapters
│   ├── example_dsl_queries.py
│   ├── example_community_detection.py # Algorithms chapter
│   └── example_centrality.py
├── dynamics/          # Epidemic and process models
├── visualization/     # Plotting examples
├── communities/       # Community detection
├── io_and_data/       # Data loading
├── cli/               # Command-line usage
├── workflows/         # Complete workflows
└── advanced/          # Advanced topics

```

## 19.3 Mapping Book Chapters to Examples

### 19.3.1 Installation and Getting Started (Installation and Getting Started)

- `examples/getting_started/quickstart.py`
- `examples/getting_started/first_network.py`

### 19.3.2 Data Loading and Representation (Data Loading)

- `examples/io_and_data/load_edgelist.py`
- `examples/io_and_data/arrow_parquet_io.py`
- `examples/io_and_data/csv_loading.py`

### 19.3.3 Visualization and Exploration (Visualization)

- `examples/visualization/basic_plot.py`
- `examples/visualization/hairball_plot.py`
- `examples/visualization/matrix_visualization.py`

### 19.3.4 Core Algorithms: Communities, Centrality, Dynamics (Core Algorithms)

- `examples/network_analysis/example_community_detection.py`
- `examples/network_analysis/example_centrality.py`
- `examples/network_analysis/example_explainable_centrality.py`
- `examples/dynamics/sir_epidemic.py`

### 19.3.5 Introduction to the Py3plex DSL and Advanced Queries and Workflows (DSL)

- `examples/network_analysis/example_dsl_builder_api.py` — **Primary reference**
- `examples/network_analysis/example_dsl_queries.py`
- `examples/network_analysis/example_dsl_advanced.py`
- `examples/network_analysis/example_dsl_community_detection.py`

### 19.3.6 The Py3plex GUI (Overview) (GUI)

- `gui/app.py` — Main application
- `gui/README.md` — Setup instructions

## 19.4 Key Scripts Reference

### 19.4.1 Makefile Targets

The Makefile provides common development tasks:

```
make setup          # Create virtual environment
make dev-install    # Install with dev dependencies
make test           # Run test suite
make test-coverage  # Generate coverage report
make lint           # Run code quality checks
make format         # Format code with black
make docs           # Build documentation
make clean          # Clean build artifacts
```

### 19.4.2 Development Scripts

```
scripts/
├── run_tests.py      # Test runner
├── generate_docs.py  # Documentation generator
└── benchmark.py     # Performance benchmarking
```

## 19.5 Configuration Files

### 19.5.1 Package Configuration

**pyproject.toml** — Modern Python package configuration (PEP 518):

- Package metadata (name, version, authors)
- Dependencies and extras (`[infomap]`, `[viz]`, etc.)

- Build system configuration
- Tool configurations (black, ruff, mypy)

### 19.5.2 Testing Configuration

**pytest.ini** — Test framework configuration:

- Test discovery patterns
- Coverage settings
- Markers for test categories

### 19.5.3 Documentation Configuration

**docfiles/conf.py** — Sphinx documentation configuration:

- Extensions (autodoc, napoleon, mathjax)
- Theme settings (sphinx\_rtd\_theme)
- Build options

### 19.5.4 Docker Configuration

**Dockerfile** — Container image definition **docker-compose.yml** — Multi-service orchestration

[Detailed Docker configs in Appendix B]

## 19.6 Data Files

### 19.6.1 Sample Datasets

```
datasets/
├── karate_multiplex.edgelist
├── example_biological.graphml
└── README.md
```

### 19.6.2 External Datasets

The `multilayer_datasets/` directory contains links and scripts for downloading larger datasets used in case studies.

## 19.7 Summary

**Key directories:**

- `py3plex/` — Main package code
- `tests/` — Test suite
- `examples/` — 50+ working examples mapped to book chapters
- `docfiles/` — Documentation source
- `gui/` — Web interface

**Development workflow:**

1. Clone repository



2. `make setup` to create environment
3. `make dev-install` to install dependencies
4. Modify code, run `make test`
5. Use `examples/` as reference

**Finding code:**

- Algorithms → `py3plex/algorithms/`
- DSL → `py3plex/dsl/`
- Examples → `examples/` (organized by topic)

## APPENDIX B: DOCKER, DOCKER COMPOSE, AND DEPLOYMENT

This appendix provides complete Docker configurations and deployment instructions for py3plex, including the GUI.

### 20.1 Dockerfile Reference

#### 20.1.1 Main Dockerfile

The repository includes a Dockerfile for containerized execution:

```
# File: Dockerfile
FROM python:3.10-slim

WORKDIR /app

# Install system dependencies
RUN apt-get update && apt-get install -y \
    git \
    build-essential \
    && rm -rf /var/lib/apt/lists/*

# Copy requirements
COPY pyproject.toml .
COPY README.md .

# Install py3plex
RUN pip install --no-cache-dir -e .

# Copy application code
COPY py3plex/ ./py3plex/
COPY examples/ ./examples/

# Set up entry point
ENTRYPOINT ["python", "-m", "py3plex"]
CMD ["--help"]
```

#### 20.1.2 Building the Image

```
# Build image
docker build -t py3plex:latest .

# Build with specific Python version
```

```
docker build --build-arg PYTHON_VERSION=3.11 -t py3plex:3.11 .
```

```
# Build with version tag matching book release
```

```
docker build -t py3plex:1.1.0 .
```

### 20.1.3 Running Containers

```
# Run command
```

```
docker run --rm py3plex:latest --version
```

```
# Run analysis script
```

```
docker run --rm py3plex:latest python examples/getting_started/quickstart.py
```

```
# Mount data directory
```

```
docker run --rm -v $(pwd)/data:/data py3plex:latest python analysis.py
```

```
# Interactive shell
```

```
docker run --rm -it py3plex:latest /bin/bash
```

## 20.2 Docker Compose

### Note

**Docker Compose Command:** This book uses the modern `docker compose` command (Docker CLI plugin, available since Docker 20.10). If you have an older Docker version, you may need to use the legacy `docker-compose` command instead. The configuration file is always named `docker-compose.yml` regardless of which command you use.

### 20.2.1 GUI Deployment

```
# File: docker-compose.yml
```

```
version: '3.8'
```

```
services:
```

```
  gui:
```

```
    build:
```

```
      context: .
```

```
      dockerfile: gui/Dockerfile
```

```
    ports:
```

```
      - "8000:8000"
```

```
    volumes:
```

```
      - ./data:/app/data
```

```
      - ./uploads:/app/uploads
```

```
    environment:
```

```
      - ENV=production
```

```
      - SECRET_KEY=${SECRET_KEY}
```

```
    restart: unless-stopped
```

```
# Optional: nginx reverse proxy
```

```
nginx:
```

```

image: nginx:alpine
ports:
  - "80:80"
  - "443:443"
volumes:
  - ./nginx.conf:/etc/nginx/nginx.conf:ro
  - ./ssl:/etc/nginx/ssl:ro
depends_on:
  - gui
restart: unless-stopped

```

### 20.2.2 Running with Docker Compose

```

# Start services
docker compose up -d

# View logs
docker compose logs -f gui

# Stop services
docker compose down

# Rebuild after changes
docker compose up -d --build

```

## 20.3 Controlled Environment Deployment

### Warning

The GUI is experimental and not designed for public internet deployment. These configurations are provided for deployment in controlled, trusted environments (e.g., internal lab networks, behind VPN). They improve security but do not make the GUI suitable for untrusted public access.

### 20.3.1 Security Hardening (Trusted Networks Only)

#### 1. Use environment variables for secrets:

```

# .env file (DO NOT commit to git)
SECRET_KEY=your-strong-secret-key-here
DATABASE_URL=postgresql://user:pass@host/db

```

```

# docker-compose.yml
services:
  gui:
    env_file:
      - .env

```

#### 2. Run as non-root user:

```
# Add to Dockerfile
RUN useradd -m -u 1000 py3plex
USER py3plex
```

### 3. Use read-only file systems where possible:

```
services:
  gui:
    read_only: true
  tmpfs:
    - /tmp
    - /var/tmp
```

## 20.3.2 Nginx Reverse Proxy

nginx.conf:

```
events {
    worker_connections 1024;
}

http {
    upstream gui {
        server gui:8000;
    }

    server {
        listen 80;
        server_name yourdomain.com;

        # Redirect to HTTPS
        return 301 https://$server_name$request_uri;
    }

    server {
        listen 443 ssl;
        server_name yourdomain.com;

        ssl_certificate /etc/nginx/ssl/cert.pem;
        ssl_certificate_key /etc/nginx/ssl/key.pem;

        # Security headers
        add_header X-Frame-Options "SAMEORIGIN";
        add_header X-Content-Type-Options "nosniff";
        add_header X-XSS-Protection "1; mode=block";

        location / {
            proxy_pass http://gui;
            proxy_set_header Host $host;
            proxy_set_header X-Real-IP $remote_addr;
            proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
            proxy_set_header X-Forwarded-Proto $scheme;
        }
    }
}
```

```

    # File upload limits
    client_max_body_size 100M;
}

```

### 20.3.3 TLS/SSL Configuration

Using Let's Encrypt:

```

# Install certbot
docker run --rm -v $(pwd)/ssl:/etc/letsencrypt \
    certbot/certbot certonly --standalone \
    -d yourdomain.com \
    --email your@email.com \
    --agree-tos

```

Self-signed certificates (development only):

```

# Generate self-signed certificate
openssl req -x509 -newkey rsa:4096 \
    -keyout ssl/key.pem \
    -out ssl/cert.pem \
    -days 365 -nodes

```

### 20.3.4 Authentication Setup

Basic HTTP authentication (simple):

```

server {
    ...

    location / {
        auth_basic "Restricted Access";
        auth_basic_user_file /etc/nginx/.htpasswd;

        proxy_pass http://gui;
    }
}

```

```

# Generate .htpasswd file
htpasswd -c .htpasswd username

```

OAuth2 Proxy (advanced):

Use oauth2-proxy as an additional service for integration with GitHub, Google, etc.

## 20.4 Security Checklist

### 20.4.1 Before Public Deployment

- [ ] Use HTTPS (TLS/SSL) for all connections
- [ ] Set strong SECRET\_KEY environment variable

- [ ] Enable authentication (HTTP Basic, OAuth2, etc.)
- [ ] Run containers as non-root user
- [ ] Use read-only file systems where possible
- [ ] Set appropriate file upload limits
- [ ] Enable security headers in nginx
- [ ] Regularly update base images (`docker pull python:3.10-slim`)
- [ ] Monitor logs for suspicious activity
- [ ] Implement rate limiting (via nginx or application)
- [ ] Sanitize user inputs (especially file uploads)
- [ ] Restrict file types for uploads
- [ ] Scan uploaded files for malware
- [ ] Use network isolation (Docker networks)
- [ ] Keep dependencies up to date (`pip install --upgrade`)

## 20.4.2 Monitoring

```
# Add health checks to docker-compose.yml
services:
  gui:
    healthcheck:
      test: ["CMD", "curl", "-f", "http://localhost:8000/health"]
      interval: 30s
      timeout: 10s
      retries: 3
```

## 20.5 Cloud Deployment

### 20.5.1 AWS Deployment

#### Using ECS (Elastic Container Service):

1. Push image to ECR (Elastic Container Registry)
2. Create ECS task definition
3. Deploy to ECS cluster
4. Use ALB (Application Load Balancer) for routing

#### Using EC2:

1. Launch EC2 instance
2. Install Docker
3. Copy `docker-compose.yml` to instance
4. Run `docker compose up -d`

## 20.5.2 Azure Deployment

Using Azure Container Instances:

```
az container create \
  --resource-group myResourceGroup \
  --name py3plex-gui \
  --image py3plex:latest \
  --cpu 2 --memory 4 \
  --ports 8000
```

## 20.5.3 GCP Deployment

Using Cloud Run:

1. Push image to Google Container Registry
2. Deploy to Cloud Run
3. Configure domain and SSL

## 20.6 Performance Tuning

### 20.6.1 Container Resource Limits

```
services:
  gui:
    deploy:
      resources:
        limits:
          cpus: '2.0'
          memory: 4G
        reservations:
          cpus: '1.0'
          memory: 2G
```

### 20.6.2 Caching

Use Docker layer caching to speed up builds:

```
# Install dependencies first (cached layer)
COPY pyproject.toml .
RUN pip install -e .

# Copy code second (changes frequently)
COPY py3plex/ ./py3plex/
```

### 20.6.3 Multi-Stage Builds

For smaller production images:

```
# Build stage
FROM python:3.10 as builder
WORKDIR /app
```



```

COPY pyproject.toml .
RUN pip install --user -e .

# Runtime stage
FROM python:3.10-slim
WORKDIR /app
COPY --from=builder /root/.local /root/.local
COPY py3plex/ ./py3plex/
ENV PATH=/root/.local/bin:$PATH

```

## 20.7 Troubleshooting

### 20.7.1 Common Issues

#### Issue: Container exits immediately

Check logs:

```
docker logs <container_id>
```

#### Issue: Permission denied on mounted volumes

Fix permissions safely by matching container user to host user:

##### Method 1: Run container with your user ID (recommended)

```
docker run --user "$(id -u):$(id -g)" -v $(pwd)/data:/data py3plex-image
```

##### Method 2: Change ownership to match container user

```

# If container runs as user 1000:1000 (typical)
sudo chown -R 1000:1000 ./data

```

##### Method 3: Use docker compose with user mapping

```

services:
  py3plex:
    user: "${UID}:${GID}"
    volumes:
      - ./data:/data

```

Then run: `UID=$(id -u) GID=$(id -g) docker compose up`

#### Warning

**Avoid** `chmod -R 777 ./data` as it grants world-writable permissions and creates a security risk. Use user/group mapping instead.

#### Issue: Out of memory

Increase Docker memory limits or container resources.

## 20.8 Summary

This appendix provided:

- Complete Dockerfile and docker-compose.yml examples
- Security hardening guidelines
- Production deployment configurations (nginx, TLS, authentication)
- Cloud deployment options (AWS, Azure, GCP)
- Performance tuning strategies

**Key recommendations for production:**

1. Always use HTTPS
2. Enable authentication
3. Run as non-root
4. Monitor and log
5. Keep dependencies updated
6. Follow security checklist

**See also:** *The Py3plex GUI (Overview)* (page 116) for high-level GUI overview

## APPENDIX C: DETAILED VALIDATION SCRIPTS

This appendix provides detailed validation strategies and test scripts for ensuring correctness of multilayer network algorithms. These complement the high-level overview in *Testing and Validation* (page 106).

### 21.1 Validation Philosophy

py3plex uses multiple validation strategies:

1. **Unit tests** — Test individual functions in isolation
2. **Property-based tests** — Test invariants that should always hold
3. **Reference runs** — Compare against known-good results
4. **Conservation tests** — Verify physical/mathematical laws (e.g., probability conservation)

### 21.2 Random Walk Validation

#### 21.2.1 Conservation Tests

Random walks must conserve probability—the sum of transition probabilities from any state must equal 1:

```
# File: tests/test_random_walk_conservation.py
import pytest
import numpy as np
from py3plex.algorithms.paths import random_walk

def test_probability_conservation():
    """Verify random walk conserves probability."""
    network = create_test_network()

    # Run random walk
    walks = random_walk(network, num_walks=1000, walk_length=100)

    # Compute transition matrix
    trans_matrix = compute_transition_matrix(walks)

    # Check row sums = 1
    row_sums = trans_matrix.sum(axis=1)
    assert np.allclose(row_sums, 1.0, atol=1e-6)
```

## 21.2.2 Bias Validation

Node2Vec introduces biases (return parameter  $p$ , in-out parameter  $q$ ). Validate that biases have the intended effect:

```
# File: tests/test_node2vec_bias.py
def test_return_bias():
    """Higher p should reduce probability of returning to previous node."""
    network = create_test_network()

    # Low p (encourage return)
    walks_low_p = node2vec_walk(network, p=0.25, q=1.0, num_walks=1000)
    return_rate_low = count_immediate_returns(walks_low_p)

    # High p (discourage return)
    walks_high_p = node2vec_walk(network, p=4.0, q=1.0, num_walks=1000)
    return_rate_high = count_immediate_returns(walks_high_p)

    assert return_rate_high < return_rate_low
```

## 21.2.3 Reference Runs

Store reference outputs for deterministic tests:

```
# File: tests/test_dynamics_reference_runs.py
REFERENCE_DATA = {
    'sir_small_graph_42': {
        'beta': 0.3,
        'gamma': 0.1,
        'steps': 100,
        'seed': 42,
        'expected_final_recovered': 0.75
    }
}

def test_sir_matches_reference():
    """Ensure SIR dynamics match reference run."""
    ref = REFERENCE_DATA['sir_small_graph_42']

    network = make_tiny_chain_graph()
    sir = SIRDynamics(network, beta=ref['beta'], gamma=ref['gamma'])
    sir.set_seed(ref['seed'])

    results = sir.run(steps=ref['steps'])
    final_recovered = results.get_measure('state_counts')[2][-1] / network.number_of_nodes()

    assert abs(final_recovered - ref['expected_final_recovered']) < 0.01
```

## 21.3 Community Detection Validation

### 21.3.1 Modularity Bounds

Modularity  $Q$  must be in range  $[-0.5, 1.0]$ :

```
# File: tests/test_community_bounds.py
def test_modularity_bounds():
    """Modularity must be in valid range."""
    network = create_test_network()

    communities = multilayer_louvain.best_partition(network.core_network)
    Q = compute_modularity(network, communities)

    assert -0.5 <= Q <= 1.0
```

### 21.3.2 Partition Quality

Every node must be assigned to exactly one community:

```
def test_partition_completeness():
    """Every node must be in exactly one community."""
    network = create_test_network()
    communities = multilayer_louvain.best_partition(network.core_network)

    # All nodes accounted for
    assert set(communities.keys()) == set(network.get_nodes())

    # No overlapping assignments (in non-overlapping methods)
    assert len(communities) == len(set(communities.values()))
```

### 21.3.3 Singleton Detection

Validate that isolated nodes form their own communities:

```
def test_singleton_communities():
    """Isolated nodes should form singleton communities."""
    network = create_network_with_isolates()
    communities = multilayer_louvain.best_partition(network.core_network)

    isolates = [n for n in network.get_nodes() if network.core_network.degree(n) == 0]

    # Each isolate in its own community
    for node in isolates:
        community = communities[node]
        same_community = [n for n, c in communities.items() if c == community]
        assert same_community == [node]
```

## 21.4 Centrality Validation

### 21.4.1 Degree Centrality

Degree centrality should match actual degree counts:

```
# File: tests/test_centrality_correctness.py
def test_degree_centrality():
    """Degree centrality should match computed degrees."""
    network = create_test_network()
```

```
import networkx as nx
degree_cent = nx.degree_centrality(network.core_network)

for node in network.get_nodes():
    computed = degree_cent[node]
    expected = network.core_network.degree(node) / (network.number_of_nodes() - 1)
    assert abs(computed - expected) < 1e-10
```

## 21.4.2 Betweenness Centrality

Validate using known structures (e.g., star graphs):

```
def test_betweenness_star_graph():
    """In a star graph, center has betweenness 1.0."""
    network = create_star_graph(n=5) # 1 center + 4 leaves

    import networkx as nx
    bc = nx.betweenness_centrality(network.core_network, normalized=True)

    center = ('center', 'layer')
    assert bc[center] == 1.0 # All paths go through center

    leaves = [n for n in network.get_nodes() if n != center]
    for leaf in leaves:
        assert bc[leaf] == 0.0 # Leaves are not on any shortest paths
```

## 21.5 Dynamics Validation

### 21.5.1 SIS Model Conservation

In SIS model,  $S(t) + I(t) = N$  for all  $t$ :

```
# File: tests/test_dynamics_conservation.py
def test_sis_conservation():
    """SIS model must conserve population."""
    network = create_test_network()
    N = network.number_of_nodes()

    sis = SISDynamics(network, beta=0.3, gamma=0.1)
    sis.set_seed(42)

    results = sis.run(steps=100)

    for t in range(100):
        S_t = results.get_measure('state_counts')[0][t]
        I_t = results.get_measure('state_counts')[1][t]
        assert S_t + I_t == N
```

## 21.5.2 SIR Model Conservation

In SIR model,  $S(t) + I(t) + R(t) = N$  for all  $t$ :

```
def test_sir_conservation():
    """SIR model must conserve population."""
    network = create_test_network()
    N = network.number_of_nodes()

    sir = SIRDynamics(network, beta=0.3, gamma=0.1)
    sir.set_seed(42)

    results = sir.run(steps=100)

    for t in range(100):
        S_t = results.get_measure('state_counts')[0][t]
        I_t = results.get_measure('state_counts')[1][t]
        R_t = results.get_measure('state_counts')[2][t]
        assert S_t + I_t + R_t == N
```

## 21.5.3 Steady State Validation

SIS model should reach steady state:

```
def test_sis_steady_state():
    """SIS should reach equilibrium."""
    network = create_test_network()

    sis = SISDynamics(network, beta=0.3, gamma=0.1)
    sis.set_seed(42)

    results = sis.run(steps=1000)
    prevalence = results.get_measure('prevalence')

    # Check last 100 steps are stable
    last_100 = prevalence[-100:]
    variance = np.var(last_100)
    assert variance < 0.01 # Low variance = steady state
```

## 21.6 Property-Based Testing

### 21.6.1 Using Hypothesis

Property-based tests use the hypothesis library to generate random inputs:

```
# File: tests/property/test_paths_properties.py
from hypothesis import given, strategies as st
from hypothesis import assume

@given(
    num_nodes=st.integers(min_value=3, max_value=20),
    num_layers=st.integers(min_value=1, max_value=5),
    seed=st.integers(min_value=0, max_value=1000)
)
```

```
def test_shortest_path_length_property(num_nodes, num_layers, seed):
    """Shortest path length should be <= graph diameter."""
    network = generate_random_network(num_nodes, num_layers, seed)
    assume(nx.is_connected(network.core_network)) # Skip disconnected graphs

    # Pick random source and target
    nodes = list(network.get_nodes())
    source, target = random.sample(nodes, 2)

    # Compute shortest path
    path = nx.shortest_path(network.core_network, source, target)
    path_length = len(path) - 1

    # Path length should be <= diameter
    diameter = nx.diameter(network.core_network)
    assert path_length <= diameter
```

## 21.6.2 Multilayer-Specific Properties

```
@given(num_nodes=st.integers(min_value=2, max_value=10))
def test_node_activity_bounds(num_nodes):
    """Node activity must be in [0, 1]."""
    network = generate_multiplex_network(num_nodes)

    for node_id in range(num_nodes):
        activity = mls.node_activity(network, str(node_id))
        assert 0.0 <= activity <= 1.0
```

## 21.7 Running Validation Tests

### 21.7.1 Full Test Suite

```
# Run all tests
pytest tests/

# Run only validation tests
pytest tests/ -k validation

# Run with coverage
pytest tests/ --cov=py3plex --cov-report=html
```

### 21.7.2 Property-Based Tests

```
# Run property tests (slower)
pytest tests/property/

# Run with more examples
pytest tests/property/ --hypothesis-profile=thorough
```



### 21.7.3 Continuous Validation

Tests run automatically on:

- Every commit (GitHub Actions)
- Pull requests
- Scheduled nightly runs

## 21.8 Summary

This appendix detailed validation strategies:

1. **Conservation tests** — Physical/mathematical laws must hold
2. **Reference runs** — Deterministic tests against known-good outputs
3. **Boundary tests** — Values must be in valid ranges
4. **Property-based tests** — Invariants hold for random inputs
5. **Structure tests** — Algorithmic correctness on known structures

**Key test files:**

- `tests/test_dynamics_reference_runs.py` — Reference dynamics data
- `tests/test_random_walk_conservation.py` — Probability conservation
- `tests/property/` — Property-based tests
- `tests/test_centrality_correctness.py` — Centrality validation

**See also:** *Testing and Validation* (page 106) for high-level testing overview

## APPENDIX D: ERROR HANDLING AND EXCEPTION HIERARCHY

This appendix documents py3plex's exception classes and error handling conventions.

### 22.1 Exception Hierarchy

py3plex defines a hierarchy of exceptions for different error categories:

```
Py3plexException (base)
├── ValidationError
│   ├── InvalidNetworkError
│   ├── InvalidLayerError
│   └── InvalidNodeError
├── IOError
│   ├── FileFormatError
│   ├── FileNotFoundError
│   └── SerializationError
├── DSLError
│   ├── QuerySyntaxError
│   ├── QueryExecutionError
│   └── UnsupportedFeatureError
├── AlgorithmError
│   ├── ConvergenceError
│   └── InsufficientDataError
└── ConfigurationError
```

### 22.2 Base Exception

```
class Py3plexException(Exception):
    """Base exception for all py3plex errors."""
    pass
```

All py3plex exceptions inherit from this base class, allowing users to catch any library error:

```
from py3plex.exceptions import Py3plexException

try:
    result = some_py3plex_operation()
except Py3plexException as e:
    print(f"py3plex error: {e}")
```

## 22.3 Validation Errors

### 22.3.1 InvalidNetworkError

Raised when a network is in an invalid state:

```
from py3plex.exceptions import InvalidNetworkError

# Example: Empty network
if network.number_of_nodes() == 0:
    raise InvalidNetworkError("Cannot compute metrics on empty network")
```

Common causes:

- Empty network (no nodes or edges)
- Disconnected graph when algorithm requires connected
- Directed graph when undirected expected (or vice versa)

### 22.3.2 InvalidLayerError

Raised when referencing a nonexistent layer:

```
from py3plex.exceptions import InvalidLayerError

if layer_name not in network.get_layers():
    raise InvalidLayerError(f"Layer '{layer_name}' does not exist")
```

Common causes:

- Typo in layer name
- Layer removed after reference created
- Case sensitivity mismatch

### 22.3.3 InvalidNodeError

Raised when referencing a nonexistent node:

```
from py3plex.exceptions import InvalidNodeError

if node not in network.core_network:
    raise InvalidNodeError(f"Node {node} not found in network")
```

## 22.4 I/O Errors

### 22.4.1 FileFormatError

Raised when file format is invalid or unsupported:

```
from py3plex.exceptions import FileFormatError

try:
    network.load_network("data.xyz", input_type="xyz")
```

```
except FileFormatError as e:
    print(f"Unsupported format: {e}")
```

**Common causes:**

- Unrecognized file extension
- Malformed file content
- Missing required fields in CSV/JSON

## 22.4.2 SerializationError

Raised during read/write operations:

```
from py3plex.exceptions import SerializationError

try:
    write(network, "output.arrow")
except SerializationError as e:
    print(f"Failed to serialize: {e}")
```

## 22.5 DSL Errors

### 22.5.1 QuerySyntaxError

Raised for invalid DSL query syntax:

```
from py3plex.dsl import execute_query
from py3plex.exceptions import QuerySyntaxError

try:
    result = execute_query(network, 'SELECT nodes WHRE degree > 5') # Typo
except QuerySyntaxError as e:
    print(f"Query syntax error: {e}")
    # Suggestion: "Did you mean 'WHERE'?"
```

**Common causes:**

- Typos in keywords (WHRE instead of WHERE)
- Missing quotes around layer names
- Invalid comparison operators

### 22.5.2 QueryExecutionError

Raised when query execution fails:

```
from py3plex.exceptions import QueryExecutionError

try:
    result = execute_query(network, 'SELECT nodes COMPUTE nonexistent_measure')
except QueryExecutionError as e:
    print(f"Query execution failed: {e}")
```

**Common causes:**

- Referencing nonexistent measures
- Applying measure to unsuitable graph (e.g., eigenvector centrality on disconnected graph)
- Resource limits exceeded

**22.5.3 UnsupportedFeatureError**

Raised when using experimental or unimplemented features:

```
from py3plex.exceptions import UnsupportedFeatureError

try:
    result = Q.edges().where(weight__gt=0.5).execute(network)
except UnsupportedFeatureError as e:
    print(f"Feature not yet supported: {e}")
```

**22.6 Algorithm Errors****22.6.1 ConvergenceError**

Raised when iterative algorithms fail to converge:

```
from py3plex.exceptions import ConvergenceError

try:
    centrality = compute_eigenvector_centrality(network, max_iter=100)
except ConvergenceError as e:
    print(f"Algorithm did not converge: {e}")
```

**22.6.2 InsufficientDataError**

Raised when there's not enough data for analysis:

```
from py3plex.exceptions import InsufficientDataError

if network.number_of_nodes() < 3:
    raise InsufficientDataError("Need at least 3 nodes for community detection")
```

**22.7 Configuration Errors****22.7.1 ConfigurationError**

Raised for invalid configuration or parameters:

```
from py3plex.exceptions import ConfigurationError

if beta <= 0 or gamma <= 0:
    raise ConfigurationError("SIR parameters beta and gamma must be positive")
```

## 22.8 Error Handling Best Practices

### 22.8.1 Catch Specific Exceptions

Prefer catching specific exceptions over generic ones:

```
# Good: Specific exception handling
from py3plex.exceptions import InvalidLayerError

try:
    result = Q.nodes().from_layers(L["social"]).execute(network)
except InvalidLayerError:
    print("Layer 'social' not found. Available layers:", network.get_layers())

# Avoid: Generic exception (too broad)
try:
    result = Q.nodes().from_layers(L["social"]).execute(network)
except Exception as e: # Too generic
    print(f"Something went wrong: {e}")
```

### 22.8.2 Provide Context

Include helpful context in error messages:

```
# Good: Helpful context
if layer_name not in network.get_layers():
    available = ", ".join(network.get_layers())
    raise InvalidLayerError(
        f"Layer '{layer_name}' not found. Available layers: {available}"
    )

# Less helpful
if layer_name not in network.get_layers():
    raise InvalidLayerError(f"Invalid layer")
```

### 22.8.3 Validation at Entry Points

Validate inputs early:

```
def compute Centrality(network, measure='degree'):
    """Compute node centrality."""
    # Validate early
    if network.number_of_nodes() == 0:
        raise InvalidNetworkError("Cannot compute centrality on empty network")

    if measure not in ['degree', 'betweenness', 'closeness']:
        raise ValueError(f"Unknown measure: {measure}")

    # Proceed with computation
    ...
```

## 22.8.4 Clean Resource Cleanup

Use context managers for resources:

```
# Good: Automatic cleanup
from py3plex.io import read

try:
    graph = read('network.arrow')
    # Process graph
except IOError as e:
    print(f"Failed to read file: {e}")
finally:
    # Resources automatically cleaned up
```

## 22.9 Error Messages Guidelines

1. **Be specific:** State what went wrong and why
2. **Suggest fixes:** Offer alternatives when possible
3. **Include context:** Show relevant values (layer names, node counts, etc.)
4. **Be concise:** One sentence explanation, then details if needed

Examples:

```
# Good error message
raise InvalidLayerError(
    f"Layer 'socail' not found. Did you mean 'social'? "
    f"Available layers: {'', ' '.join(network.get_layers())}")
)

# Good error message
raise InsufficientDataError(
    f"Community detection requires at least 3 nodes, but network has only "
    f"{network.number_of_nodes()}")
)

# Less helpful
raise InvalidLayerError("Layer error") # Too vague
```

## 22.10 Logging

py3plex uses Python's logging module:

```
import logging

# Configure logging level
logging.basicConfig(level=logging.INFO)

# py3plex will log warnings and errors
network.load_network("data.edgelist") # Logs any warnings
```

Available log levels:

- DEBUG — Detailed information for debugging
- INFO — General information
- WARNING — Recoverable issues
- ERROR — Serious problems
- CRITICAL — Fatal errors

## 22.11 Summary

### Exception hierarchy:

- Base: Py3plexException
- Categories: Validation, I/O, DSL, Algorithm, Configuration

### Best practices:

1. Catch specific exceptions
2. Provide helpful context in messages
3. Validate early
4. Suggest fixes when possible
5. Use logging for non-fatal issues

### Example usage:

```
from py3plex.core import multinet
from py3plex.exceptions import InvalidLayerError, Py3plexException

try:
    network = multinet.multi_layer_network()
    network.load_network("data.edgelist")

    result = Q.nodes().from_layers(L["social"]).execute(network)

except InvalidLayerError as e:
    print(f"Layer not found: {e}")
except Py3plexException as e:
    print(f"py3plex error: {e}")
```

See also: *Advanced Queries and Workflows* (page 73) for error recovery strategies in workflows



## APPENDIX E: EXTENDED API AND DSL REFERENCE

This appendix provides a quick reference for the py3plex API and DSL syntax.

### 23.1 Core API Reference

#### 23.1.1 Creating Networks

```
from py3plex.core import multinet

# Create empty network
network = multinet.multi_layer_network(
    directed=False,          # True for directed networks
    network_type='multilayer' # or 'multiplex'
)
```

#### 23.1.2 Adding Nodes and Edges

```
# Add edges (nodes created implicitly)
network.add_edges([
    ['Alice', 'friends', 'Bob', 'friends', 1.0],
    ['Bob', 'friends', 'Carol', 'friends', 1.0],
], input_type="list")

# Add edges with attributes
network.add_edges([
    {
        'source': 'Alice',
        'source_type': 'friends',
        'target': 'Bob',
        'target_type': 'friends',
        'weight': 0.8,
        'timestamp': '2023-01-15'
    }
])
```

#### 23.1.3 Loading Networks

```
# From file
network.load_network("data.edgelist", input_type="edgelist")

# From NetworkX
import networkx as nx
```

```
G = nx.karate_club_graph()
network.load_network_from_networkx(G, layer_name='social')
```

### 23.1.4 Basic Operations

```
# Get network information
layers = network.get_layers()
nodes = list(network.get_nodes())
edges = list(network.get_edges())

# Statistics
network.basic_stats()
num_nodes = network.get_number_of_nodes()
num_edges = network.get_number_of_edges()

# Layer-specific
nodes_per_layer = network.get_number_of_nodes_per_layer()
layer_subgraph = network.get_layer_subgraph('friends')
```

## 23.2 Algorithms API

### 23.2.1 Statistics

```
from py3plex.algorithms.statistics import multilayer_statistics as mls

# Layer density
density = mls.layer_density(network, 'friends')

# Node activity (fraction of layers a node appears in)
activity = mls.node_activity(network, 'Alice')

# Layer overlap
overlap = mls.layer_overlap(network, 'friends', 'colleagues')
```

### 23.2.2 Community Detection

```
from py3plex.algorithms.community_detection import multilayer_louvain

# Detect communities
communities = multilayer_louvain.best_partition(network.core_network)

# communities = {'Alice', 'friends': 0, ('Bob', 'friends'): 0, ...}
```

### 23.2.3 Centrality

```
import networkx as nx

# Standard centralities (use NetworkX)
G = network.core_network
degree_cent = nx.degree_centrality(G)
```

```

betweenness = nx.betweenness centrality(G)
closeness = nx.closeness centrality(G)

# Explainable centrality (py3plex-specific)
from py3plex.algorithms.centrality.explain import explain_node centrality

explanation = explain_node centrality(
    network,
    node='Alice',
    measure='degree'
)
# Returns: {'score': 4, 'layer_breakdown': {...}, ...}

```

### 23.2.4 Dynamics

```

from py3plex.dynamics.models import SIRDynamics, SISDynamics

# Configure SIR model
sir = SIRDynamics(
    network,
    beta=0.3,      # Infection rate
    gamma=0.1,     # Recovery rate
    initial_infected={'Alice': 0} # Initial conditions
)

# Set seed for reproducibility
sir.set_seed(42)

# Run simulation
results = sir.run(steps=100)

# Extract measures
prevalence = results.get_measure('prevalence')
recovered = results.get_measure('state_counts')[2] # State 2 = recovered

```

## 23.3 DSL Quick Reference

### 23.3.1 Builder API (Recommended)

```

from py3plex.dsl import Q, L, Param

# Basic query
result = Q.nodes().execute(network)

# Filter by layer
result = Q.nodes().from_layers(L["social"]).execute(network)

# Filter by condition
result = Q.nodes().where(degree__gt=5).execute(network)

# Multiple conditions

```

```

result = Q.nodes().where(layer="social", degree__gt=3).execute(network)

# Layer algebra
result = Q.nodes().from_layers(L["social"] + L["work"]).execute(network)      # Union
result = Q.nodes().from_layers(L["social"] - L["bots"]).execute(network)      # Difference
result = Q.nodes().from_layers(L["social"] & L["work"]).execute(network)      # Intersection

# Compute measures
result = Q.nodes().compute("degree", "betweenness centrality").execute(network)

# Order and limit
result = (
    Q.nodes()
    .compute("degree")
    .order_by("-degree")
    .limit(10)
    .execute(network)
)

# Export results
(
    Q.nodes()
    .compute("degree")
    .export_csv("output.csv")
    .execute(network)
)

# Parameterized queries
result = (
    Q.nodes()
    .where(degree__gt=Param('min_degree'))
    .execute(network, params={'min_degree': 5})
)
    
```

### 23.3.2 String DSL Syntax

```

from py3plex.dsl import execute_query

# Basic syntax: SELECT target WHERE conditions COMPUTE measures

# Select all nodes
execute_query(network, 'SELECT nodes')

# Filter by layer
execute_query(network, 'SELECT nodes WHERE layer="social"')

# Filter by degree
execute_query(network, 'SELECT nodes WHERE degree > 5')

# Multiple conditions
execute_query(network, 'SELECT nodes WHERE layer="social" AND degree > 3')

# Compute measures
    
```

```
execute_query(network, 'SELECT nodes COMPUTE betweenness centrality')

# Combined
execute_query(network,
    'SELECT nodes WHERE layer="social" AND degree > 3 '
    'COMPUTE degree betweenness centrality'
)
```

### 23.3.3 DSL Operators

#### Comparison operators:

- = — Equal to
- != — Not equal to
- > — Greater than
- < — Less than
- >= — Greater than or equal
- <= — Less than or equal

#### Logical operators:

- AND — Logical AND
- OR — Logical OR
- NOT — Logical NOT

#### Filter modifiers (Builder API):

- field=value — Equal
- field\_\_ne=value — Not equal
- field\_\_gt=value — Greater than
- field\_\_gte=value — Greater or equal
- field\_\_lt=value — Less than
- field\_\_lte=value — Less or equal

### 23.3.4 Available Measures

- degree — Node degree
- degree centrality — Normalized degree
- betweenness centrality — Betweenness
- closeness centrality — Closeness
- eigenvector centrality — Eigenvector
- pagerank — PageRank
- clustering — Clustering coefficient

### 23.3.5 Working with Results

```
result = Q.nodes().compute("degree").execute(network)

# Iteration
for node in result:
    print(node)

# Count
print(f"Found {result.count} nodes")

# Measures
degrees = result.measures['degree']
for node, degree in degrees.items():
    print(f"{node}: {degree}")

# To pandas
df = result.to_pandas()
```

## 23.4 I/O API

### 23.4.1 Modern I/O System

```
from py3plex.io import read, write, MultiLayerGraph

# Read (auto-detects format from extension)
graph = read('network.json')
graph = read('network.arrow')
graph = read('network.parquet')

# Write
write(network, 'output.json')
write(network, 'output.arrow')
write(network, 'output.parquet')

# Specify format explicitly
graph = read('file.dat', format='json')
write(network, 'file.dat', format='arrow')
```

### 23.4.2 Supported Formats

- **JSON** — .json — Human-readable
- **JSONL** — .jsonl — Streaming
- **CSV** — .csv — Spreadsheet-compatible
- **Arrow** — .arrow — High-performance
- **Parquet** — .parquet — Compressed

## 23.5 Visualization API

### 23.5.1 Basic Visualization

```
from py3plex.visualization.multilayer import draw_multilayer_default

# Simple visualization
draw_multilayer_default(network.get_layers(), display=True)

# With layout options
draw_multilayer_default(
    network.get_layers(),
    display=True,
    layout='force_directed',
    node_size=300,
    edge_width=2
)
```

### 23.5.2 Matrix Visualization

```
# Visualize supra-adjacency matrix
network.visualize_matrix({"display": True})
```

## 23.6 Command-Line Interface

### 23.6.1 Basic Usage

```
# Show version
python -m py3plex --version

# Run self-test
python -m py3plex selftest

# Analyze network
python -m py3plex analyze network.edgelist

# Community detection
python -m py3plex communities network.edgelist --algorithm louvain
```

## 23.7 Summary

This appendix provided quick references for:

- Core API (creating networks, adding nodes/edges)
- Algorithms API (statistics, communities, centrality, dynamics)
- DSL syntax (both Builder API and string syntax)
- I/O API (reading/writing various formats)
- Visualization API
- Command-line interface

**For detailed documentation:**

- Main text chapters for concepts and examples
- Appendix A for repository layout
- Appendix D for error handling
- Online API docs: <https://skblaz.github.io/py3plex/>



## BIBLIOGRAPHY

This section provides references for further reading on multilayer networks and py3plex.

### 24.1 Core References

### 24.2 Py3plex Publications

### 24.3 Community Detection

### 24.4 Network Embeddings

### 24.5 Dynamics and Processes

### 24.6 Applications

#### 24.6.1 Biological Networks

#### 24.6.2 Social Networks

#### 24.6.3 Transportation Networks

### 24.7 Software and Tools

### 24.8 Online Resources

#### Py3plex:

- Documentation: <https://skblaz.github.io/py3plex/>
- GitHub: <https://github.com/SkBlaz/py3plex>
- PyPI: <https://pypi.org/project/py3plex/>

#### Community:

- Network Science community: <http://www.netscisociety.net/>
- Complex Networks: <https://www.complexnetworks.org/>

#### Datasets:

- Network Repository: <http://networkrepository.com/>
- SNAP: Stanford Network Analysis Project: <http://snap.stanford.edu/data/>

- Netzschleuder: <https://networks.skewed.de/>

## 24.9 Recommended Reading Path

### 24.9.1 For Graduate Students

1. Start with [Kivelä2014] for comprehensive foundations
2. Read [Skrlj2019a] for py3plex overview
3. Read [Mucha2010] for community detection
4. Explore [Bianconi2018] textbook for deeper theory

### 24.9.2 For Practitioners

1. Start with [Skrlj2019a] for py3plex capabilities
2. Skim [Kivelä2014] for key concepts
3. Focus on application papers relevant to your domain
4. Use this book and online docs for implementation

### 24.9.3 For Researchers

1. Read [Kivelä2014] and [Boccaletti2014] thoroughly
2. Study [Domenico2013] for mathematical rigor
3. Read domain-specific application papers
4. Explore [Bianconi2018] for advanced topics

## CITATION INFORMATION

### 25.1 How to Cite Py3plex

If you use py3plex in your research, please cite the following paper:

#### 25.1.1 BibTeX

```
@Article{Skrlj2019,  
  author={Skrlj, Blaz and Kralj, Jan and Lavrac, Nada},  
  title={Py3plex toolkit for visualization and analysis of multilayer networks},  
  journal={Applied Network Science},  
  year={2019},  
  volume={4},  
  number={1},  
  pages={94},  
  doi={10.1007/s41109-019-0203-7},  
  url={https://doi.org/10.1007/s41109-019-0203-7}  
}
```

For conference proceedings, you may also cite:

```
@InProceedings{Skrlj2019b,  
  author="{\v{S}}krlj, Bla{\v{z}}  
    and Kralj, Jan  
    and Lavra{\v{c}}, Nada",  
  editor="Aiello, Luca Maria  
    and Cherifi, Chantal  
    and Cherifi, Hocine  
    and Lambiotte, Renaud  
    and Li{\text{'}}o, Pietro  
    and Rocha, Luis M.",  
  title="Py3plex: A Library for Scalable Multilayer Network Analysis and Visualization",  
  booktitle="Complex Networks and Their Applications VII",  
  year="2019",  
  publisher="Springer International Publishing",  
  address="Cham",  
  pages="757--768",  
  isbn="978-3-030-05411-3",  
  doi="10.1007/978-3-030-05411-3_60"  
}
```

### 25.1.2 APA Style

Škrlj, B., Kralj, J., & Lavrač, N. (2019). Py3plex toolkit for visualization and analysis of multilayer networks. *Applied Network Science*, 4(1), 94. <https://doi.org/10.1007/s41109-019-0203-7>

### 25.1.3 MLA Style

Škrlj, Blaz, Jan Kralj, and Nada Lavrač. "Py3plex toolkit for visualization and analysis of multilayer networks." *Applied Network Science* 4.1 (2019): 94.

### 25.1.4 Chicago Style

Škrlj, Blaz, Jan Kralj, and Nada Lavrač. "Py3plex toolkit for visualization and analysis of multilayer networks." *Applied Network Science* 4, no. 1 (2019): 94.

## 25.2 Citing This Book

If you specifically reference this book (rather than the software), please cite:

Škrlj, B. (2025). *\*Practical Multilayer Network Analysis with Py3plex\** (Version 1.1.0). Available at: <https://github.com/SkBlaz/py3plex>

### 25.2.1 BibTeX for This Book

```
@book{Škrlj2025book,
  author = {Škrlj, Blaž},
  title = {Practical Multilayer Network Analysis with Py3plex},
  year = {2025},
  version = {1.1.0},
  url = {https://github.com/SkBlaz/py3plex}
}
```

## 25.3 Citing Specific Algorithms

If you use specific algorithms implemented in py3plex, consider citing the original papers:

### 25.3.1 Louvain Community Detection

```
@article{Blondel2008,
  title={Fast unfolding of communities in large networks},
  author={Blondel, Vincent D and Guillaume, Jean-Loup and Lambiotte, Renaud and Lefebvre, Etienne},
  journal={Journal of statistical mechanics: theory and experiment},
  volume={2008},
  number={10},
  pages={P10008},
  year={2008}
}
```

### 25.3.2 Multilayer Modularity

```
@article{Mucha2010,
  title={Community structure in time-dependent, multiscale, and multiplex networks},
  author={Mucha, Peter J and Richardson, Thomas and Macon, Kevin and Porter, Mason A and Onnela, Jukka-Pekka},
  journal={Science},
  volume={328},
  number={5980},
  pages={876--878},
  year={2010}
}
```

### 25.3.3 Node2Vec

```
@inproceedings{Grover2016,
  title={node2vec: Scalable feature learning for networks},
  author={Grover, Aditya and Leskovec, Jure},
  booktitle={Proceedings of the 22nd ACM SIGKDD international conference on Knowledge discovery and data mining},
  pages={855--864},
  year={2016}
}
```

## 25.4 Software Version Information

Reproducibility best practice is to cite the specific version of py3plex used:

```
import py3plex
print(py3plex.__version__) # e.g., "1.1.0"
```

In your paper's methods section, include:

```
All analyses were performed using py3plex version 1.1.0 [Škrlj2019]
running on Python 3.10.
```

Or in acknowledgments:

```
This research utilized py3plex (version 1.1.0, Škrlj et al., 2019)
for multilayer network analysis.
```

## 25.5 License

### 25.5.1 Py3plex Core

The main py3plex library is released under the **MIT License**, a permissive open-source license that allows commercial use:

```
Copyright (c) 2019-2025 Blaž Škrlj and contributors
```

```
Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
```

copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

### 25.5.2 Bundled Code

**Important:** Some bundled code (e.g., Infomap community detection in `py3plex/algorithms/community_detection/infomap/`) is licensed under **AGPLv3**, which has copyleft requirements.

If you use these features, your application may be subject to AGPLv3 requirements. See *Installation and Getting Started* (page 24) for details on license considerations.

### 25.5.3 This Book

This book (*Practical Multilayer Network Analysis with Py3plex*) is licensed under **Creative Commons Attribution 4.0 International (CC BY 4.0)**.

You are free to:

- **Share** — Copy and redistribute the material
- **Adapt** — Remix, transform, and build upon the material

Under the following terms:

- **Attribution** — You must give appropriate credit and provide a link to the license

## 25.6 Acknowledgments

Py3plex development has been supported by:

- Slovenian Research Agency (research program P2-0103 and projects)
- Jožef Stefan Institute
- Contributors and users worldwide

The py3plex community has provided valuable feedback, bug reports, and feature suggestions. We thank all contributors.

Special thanks to:

- **NetworkX developers** — py3plex builds on NetworkX
- **Apache Arrow project** — For high-performance I/O
- **Open-source community** — For tools and libraries

## 25.7 Contact

For questions about citing py3plex:

- **GitHub Issues:** <https://github.com/SkBlaz/py3plex/issues>
- **Email:** See contact information in the repository

For research collaborations or academic inquiries, see the py3plex repository for current contact information.

## BIBLIOGRAPHY

- [Kivelä2014] Kivelä, M., Arenas, A., Barthelemy, M., Gleeson, J. P., Moreno, Y., & Porter, M. A. (2014). Multilayer networks. *Journal of Complex Networks*, 2(3), 203-271. <https://doi.org/10.1093/comnet/cnu016>  
Comprehensive review of multilayer network theory, mathematics, and applications. Essential reading.
- [Boccaletti2014] Boccaletti, S., Bianconi, G., Criado, R., Del Genio, C. I., Gómez-Gardenes, J., Romance, M., ... & Zanin, M. (2014). The structure and dynamics of multilayer networks. *Physics Reports*, 544(1), 1-122. <https://doi.org/10.1016/j.physrep.2014.07.001>  
Physics-focused perspective on multilayer networks with emphasis on dynamics.
- [Bianconi2018] Bianconi, G. (2018). *Multilayer Networks: Structure and Function*. Oxford University Press.  
Comprehensive textbook covering theory, methods, and applications.
- [Domenico2013] De Domenico, M., Solé-Ribalta, A., Cozzo, E., Kivelä, M., Moreno, Y., Porter, M. A., ... & Arenas, A. (2013). Mathematical formulation of multilayer networks. *Physical Review X*, 3(4), 041022. <https://doi.org/10.1103/PhysRevX.3.041022>  
Rigorous mathematical formulation of multilayer network representations.
- [Škrlić2019a] Škrlić, B., Kralj, J., & Lavrač, N. (2019). Py3plex toolkit for visualization and analysis of multilayer networks. *Applied Network Science*, 4(1), 94. <https://doi.org/10.1007/s41109-019-0203-7>  
Primary py3plex paper. Cite this when using py3plex in research.
- [Škrlić2019b] Škrlić, B., Kralj, J., & Lavrač, N. (2019). Py3plex: A library for scalable multilayer network analysis and visualization. In *International Conference on Complex Networks and Their Applications* (pp. 757-768). Springer. [https://doi.org/10.1007/978-3-030-05411-3\\_60](https://doi.org/10.1007/978-3-030-05411-3_60)  
Conference paper focusing on visualization and scalability.
- [Blondel2008] Blondel, V. D., Guillaume, J. L., Lambiotte, R., & Lefebvre, E. (2008). Fast unfolding of communities in large networks. *Journal of Statistical Mechanics: Theory and Experiment*, 2008(10), P10008. <https://doi.org/10.1088/1742-5468/2008/10/P10008>  
Louvain algorithm for community detection.
- [Rosvall2008] Rosvall, M., & Bergstrom, C. T. (2008). Maps of random walks on complex networks reveal community structure. *Proceedings of the National Academy of Sciences*, 105(4), 1118-1123. <https://doi.org/10.1073/pnas.0706851105>  
Infomap algorithm for community detection.
- [Mucha2010] Mucha, P. J., Richardson, T., Macon, K., Porter, M. A., & Onnela, J. P. (2010). Community structure in time-dependent, multiscale, and multiplex networks. *Science*, 328(5980), 876-878. <https://doi.org/10.1126/science.1184819>



Multilayer community detection with modularity optimization.

- [Grover2016] Grover, A., & Leskovec, J. (2016). node2vec: Scalable feature learning for networks. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining* (pp. 855-864). <https://doi.org/10.1145/2939672.2939754>

Node2Vec algorithm for network embeddings.

- [Perozzi2014] Perozzi, B., Al-Rfou, R., & Skiena, S. (2014). DeepWalk: Online learning of social representations. In *Proceedings of the 20th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining* (pp. 701-710). <https://doi.org/10.1145/2623330.2623732>

DeepWalk algorithm for learning node representations.

- [Pastor-Satorras2015] Pastor-Satorras, R., Castellano, C., Van Mieghem, P., & Vespignani, A. (2015). Epidemic processes in complex networks. *Reviews of Modern Physics*, 87(3), 925. <https://doi.org/10.1103/RevModPhys.87.925>

Comprehensive review of epidemic modeling on networks.

- [Buldyrev2010] Buldyrev, S. V., Parshani, R., Paul, G., Stanley, H. E., & Havlin, S. (2010). Catastrophic cascade of failures in interdependent networks. *Nature*, 464(7291), 1025-1028. <https://doi.org/10.1038/nature08932>

Cascading failures in interdependent networks.

- [Gligorijevic2019] Gligorijević, V., Barot, M., & Bonneau, R. (2019). deepNF: deep network fusion for protein function prediction. *Bioinformatics*, 35(5), 757-766. <https://doi.org/10.1093/bioinformatics/bty440>

Application to biological network analysis.

- [Magnani2013] Magnani, M., & Rossi, L. (2013). Pareto distance for multilayer network analysis. In *Social Computing, Behavioral-Cultural Modeling and Prediction* (pp. 249-256). Springer. [https://doi.org/10.1007/978-3-642-37210-0\\_27](https://doi.org/10.1007/978-3-642-37210-0_27)

Social network analysis with multilayer methods.

- [Gallotti2014] Gallotti, R., & Barthelemy, M. (2014). Anatomy and efficiency of urban multimodal mobility. *Scientific Reports*, 4(1), 6911. <https://doi.org/10.1038/srep06911>

Transportation networks as multilayer systems.

- [NetworkX] Hagberg, A., Swart, P., & Schult, D. A. (2008). Exploring network structure, dynamics, and function using NetworkX. *Los Alamos National Lab.(LANL), Los Alamos, NM (United States)*.

NetworkX documentation: <https://networkx.org/>

- [Arrow] Apache Arrow Development Team. (2023). Apache Arrow. <https://arrow.apache.org/>

High-performance columnar data format.

## INDEX

### C

Coupling strength, [15](#)

### H

Heterogeneous information network, [15](#)

### I

Inter-layer edges, [14](#)

Intra-layer edges, [14](#)

### M

Multiplex network, [15](#)

### N

Node-layer pair, [15](#)

### S

Supra-adjacency matrix, [15](#)