

## Program 7

1. Write a program to demonstrate generics with multiple object parameters.

```
import java.io.*;
import java.lang.*;
import java.util.*;

class gen<T>
{
    T ob;
    gen(T o)
    {
        ob=o;
    }
    T getob()
    {
        return ob;
    }
    void showtype()
    {
        System.out.println("Type of T is " +
ob.getClass().getName());
    }
}

class generic
{
    public static void main(String[] args)
    {
        String n;
        Scanner sc=new Scanner(System.in);
        System.out.println("Enter the Integer Number to Be
Displayed Using the generic style");
        n=sc.next();
        gen<Integer> ob1=new gen<Integer>(Integer.parseInt(n));
        ob1.showtype();
        int val=ob1.getob();
        System.out.println("Value is: " + val);

        System.out.println();

        System.out.println("Enter the String to Be Displayed
Using the generic style");
        n=sc.next();
        gen<String> ob2=new gen<String>(n);
        ob2.showtype();
        String x=ob2.getob();
        System.out.println("Value : " + x);
    }
}
```

```


        System.out.println();

        System.out.println("Enter the Double Number to Be
Displayed Using the generic style");
        n=sc.next();
        gen<Double> ob3=new gen<Double>(Double.parseDouble(n));
        ob3.showtype();
        double ans=ob3.getob();
        System.out.println("Value : " + ans);

    }
}

```

Output



```

Windows PowerShell
PS D:\sem3\ooj_lab\27-11-20> javac .\generic.java
PS D:\sem3\ooj_lab\27-11-20> java generic
Enter the Integer Number to Be Displayed Using the generic style
12
Type of T is java.lang.Integer
Value is: 12

Enter the String to Be Displayed Using the generic style
qwerty
Type of T is java.lang.String
Value : qwerty

Enter the Double Number to Be Displayed Using the generic style
3.1416
Type of T is java.lang.Double
Value : 3.1416
PS D:\sem3\ooj_lab\27-11-20>

```

\*\*\*\*\*

## Program 8

2. Write a program that demonstrates handling of exceptions in inheritance tree. Create a

base class called “Father” and derived class called “Son” which extends the base

class. In Father class, implement a constructor which takes the age and throws the

exception WrongAge( ) when the input age<0. In Son class, implement a constructor

that cases both father and son's age and throws an exception if son's age is >=father's age.

```
import java.util.*;

class WrongAge extends Exception {
    int detail;
    WrongAge(int a) {
        detail = a;
    }
    public String toString() {
        return "enter correct age "+detail+" is invalid";
    }
}

class father{
    public int age;
    Scanner in =new Scanner(System.in);
    father() throws WrongAge{
        System.out.print("Enter the father's age :");
        age= in.nextInt();
        if(age<0)
            throw new WrongAge(age);
    }
}

class son extends father{
    Scanner in =new Scanner(System.in);
    int fage;
    son(father f) throws WrongAge{
        this.fage=f.age;
        System.out.print("Enter the son's age :");
        this.age= in.nextInt();
    }
}
```

```


        if(this.age<0)
            throw new WrongAge(age);
        if(this.age>f.age)
            throw new WrongAge(age);
    }

}

class ages{
    public static void main(String[] args){
        try{
            father f= new father();
            son s= new son(f);
        }
        catch(Exception e){
            System.out.println(e);
        }
    }
}

```

Output:



```

Windows PowerShell
Copyright (C) Microsoft Corporation. All rights reserved.

Try the new cross-platform PowerShell https://aka.ms/pscore6

PS C:\Users\HP> cd D:\sem3\ooj_lab\27-11-20
PS D:\sem3\ooj_lab\27-11-20> javac .\ages.java
PS D:\sem3\ooj_lab\27-11-20> java ages
Enter the father's age :35
Enter the father's age :35
Enter the son's age :22
PS D:\sem3\ooj_lab\27-11-20> java ages
Enter the father's age :54
Enter the father's age :54
Enter the son's age :56
enter correct age 56 is invalid
PS D:\sem3\ooj_lab\27-11-20>

```

\*\*\*\*\*