Dataset: journal.pone.0175818_S1Dataset_Spain_cardiac_arrest_EDITED..csv

K–Means elbow plot

Dataset: journal.pone.0175818_S1Dataset_Spain_cardiac_arrest_EDITED..csv

Clustering: KMEANS

Parameters used: k = 2

Dataset: journal.pone.0175818_S1Dataset_Spain_cardiac_arrest_EDITED..csv

K–Medians elbow plot

Dataset: journal.pone.0175818_S1Dataset_Spain_cardiac_arrest_EDITED..csv

Clustering: KMEDIANS

Parameters used: k = 2

Dataset: journal.pone.0175818_S1Dataset_Spain_cardiac_arrest_EDITED..csv

DBSCAN elbow plot

Dataset: journal.pone.0175818_S1Dataset_Spain_cardiac_arrest_EDITED..csv

Clustering: DBSCAN
Parameters used: minPoints = 11, epsilon = 14.70267

Dataset: journal.pone.0175818_S1Dataset_Spain_cardiac_arrest_EDITED..csv

DBSCAN clustering with visual inspection
Parameters used: minPoints = 19, epsilon = 15

Dataset: journal.pone.0175818_S1Dataset_Spain_cardiac_arrest_EDITED..csv

HDBSCAN elbow plot

Dataset: journal.pone.0175818_S1Dataset_Spain_cardiac_arrest_EDITED..csv

Clustering: HDBSCAN
Parameters used: minPoints = 5

Dataset: journal.pone.0175818_S1Dataset_Spain_cardiac_arrest_EDI

Hyperparameter combinations ranked by its average Silhouette score

Dataset: journal.pone.0175818_S1Dataset_Spain_cardiac_arrest_EDITED..csv

Algorithms ranked by their average Silhouette score