

RSpec Workshop

Workshop Repo

```
git clone https://github.com/Skipants/rspec-workshop/
```

Run `bin/bootstrap` to download Ruby 2.7.2 and set up the project databases.

It should complete with RSpec running and having a warning.

Unit Testing

- ▶ Follows “Arrange-Act-Assert”. This just means, do the following steps
 1. Setup the state and variables needed for your test
 2. Run the code under test
 3. Check that the code under test matches your expectations

Example Unit Test File in RSpec

Docs @ <https://relishapp.com/rspec/rspec-core/docs>

```
require "spec_helper"
```

```
RSpec.describe Game do
  describe "#score" do
    let(:game) { Game.new }

    it "returns 0 for an all gutter game" do
      20.times { game.roll(0) }
      expect(game.score).to eq(0)
    end
  end
end
```

Breaking Down Each Part of a Unit Test

```
require "spec_helper"
```

This loads the “spec_helper” file, which is the conventional file for loading the Ruby and RSpec environment. For loading the whole Rails environment, “rails_helper” is used. In the financeit app, there is only a “rails_helper”. This is generally bad practice as having separate files allows you to run spec files that don’t need Rails more quickly. eg. Unit tests on plain Ruby objects.

Breaking Down Each Part of a Unit Test

```
RSpec.describe Game do
```

RSpec's code block for putting tests in. The convention is to pass the class under test to “describe”. This can be a string as well. For tests like integration or feature tests that don't map 1-to-1 to the tests, you would probably use a string that describes the feature under test instead.

Breaking Down Each Part of a Unit Test

```
describe "#score" do
```

A nested describe block. You can nest as many as you'd like, but it generally gets messy if you are more than 3 describe's deep. Also aliased as context. The convention is that describe is used for classes and method names, context for descriptive text. eg.:

```
describe "#score" do  
  context "after 20 rolls" do
```

Breaking Down Each Part of a Unit Test

```
let(:game) { Game.new }
```

Sets the game variable for each test in this describe block. `let` is lazy loaded on each test. Part of the “Arrange” step. It also has a variant `let!` that is called *once* at the beginning of that whole block for every test within. That’s useful for expensive operations. When in doubt just use `let`.

Breaking Down Each Part of a Unit Test

```
it "returns 0 for an all gutter game" do
```

The block for the test itself.

Breaking Down Each Part of a Unit Test

```
20.times { game.roll(0) }
```

The code under test. Part of the “Act” step.

Breaking Down Each Part of a Unit Test

```
expect(game.score).to eq(0)
```

`expect...to` is RSpec's way of making an assertion. Part of the “Assert” step.

Running Your Tests

- ▶ You run your whole suite with `bundle exec rspec`.
- ▶ You can run one file with `bundle exec rspec filename`
- ▶ Check `rspec --help` to see all the commands available

Unit Test Exercise

Fill out the spec in `spec/lib/string_spec.rb`

Goal: Just getting comfortable writing a test for something already written

Time: 10 minutes

Tips:

- ▶ Run the spec with `bundle exec rspec` or `bundle exec rspec spec/lib/string_spec.rb`
- ▶ Don't overthink it
- ▶ You probably don't need to do any setup

File Conventions

Test files under `spec/` are usually 1-to-1 matches with files and their objects under the root folder or under `app/` with `_spec.rb` appended.

Examples:

1. `app/models/loan.rb => spec/models/loan_spec.rb`
2. `app/controllers/loan.rb =>`
`spec/controllers/loans_controller_spec.rb`
3. `lib/helper.rb => spec/lib/helper_spec.rb`

File Convention Exceptions

`spec/factories/`

- ▶ Contains `factory_bot` factories (more on that later)

`spec/fixtures/`

- ▶ Contain non-ruby files useful for testing, eg. images.
- ▶ Not to be confused with test-unit's fixtures, which are yaml files. We replace that with `factory_bot`.

`spec/integration/`

- ▶ Not actually the conventional place for integration tests for RSpec. These should be in `spec/requests/`

File Convention Exceptions

spec/requests/

- ▶ <https://relishapp.com/rspec/rspec-rails/v/4-0/docs/request-specs/request-spec>
- ▶ RSpec Rails' wrapper for integration tests
- ▶ They tend to follow how multiple method calls work together. More on these later.

spec/routing/

- ▶ RSpec tests for your routes
- ▶ I've actually never written one of these in my life.
- ▶ Probably useful if your routes are crazy and you are trying to refactor them.

spec/support/

- ▶ Files that are included by tests that contain abstractions and reusable pieces of code
- ▶ The place every included file for specs gets dumped.

Test Driven Development (TDD)

This just means writing tests before rather than after writing your application code. Some opinions on it are that it produces better code.

Andrew's Opinions™ on TDD

Pros:

- ▶ It helps frame the problem and give you a clear picture on how you can solve it
- ▶ You usually end up with cleaner code because you've analyzed how it should look from the start rather than incrementally making changes
- ▶ Gives you confidence your code works
- ▶ Much quicker than testing in the browser

Andrew's Opinions™ on TDD

Cons:

- ▶ Extra work is required when testing untested legacy code. Untested code most likely makes it hard to write tests covering it because it wasn't written with tests in mind; boundaries aren't clear and do not provide a good entry point for your tests.
- ▶ Writing tests requires you do know what your inputs and outputs will look like, but you might not understand what the code should look like until you've tried different things first
- ▶ It's a different way of thinking that needs to be practiced.

Andrew's Opinions™ on TDD

Overall I think it works great when fixing bugs or making new additions. It's much harder when starting a new application where the architecture isn't flushed out yet.

Unit Test TDD Exercise

Given a class Months, implement a method that calculates the average amount of days of 3 months by name

Class is located in `lib/months.rb`

Constraints: - Write a test before even typing anything into `lib/months.rb`

Goal: To get comfortable with TDD

Time: 20 minutes

Unit Test TDD Exercise

Tips:

- ▶ You will need to create a test file for class `lib/months.rb` given the convention we talked about
- ▶ Don't worry about good code; our goal here is testing first.
- ▶ When requiring `spec_helper`, application files aren't loaded by default. Use `require_relative '/path/to/file/'` to load `lib/months.rb`.
- ▶ Use `Months.days_to_months` when implementing the feature to make this less about figuring out Date/Time methods and more just worrying about the problem
- ▶ Hardcode the values in your test rather than directly using `Months.days_to_months` inside your test.
- ▶ Run the spec file as often as possible with `bundle exec rspec filename`
- ▶ Use RSpec's `be_within` matcher to test decimal values.

Stubs and Mocks

<https://relishapp.com/rspec/rspec-mocks/docs>

Stubs

<https://relishapp.com/rspec/rspec-mocks/v/3-10/docs/basics/allowing-messages>

You can stub methods on any object by using `allow(object).to receive(:method)`. This is useful for returning a certain response from a method that isn't under test but is required to get your test to work as expected.

For example, setting the internal state of an object and then calling another method that depends on it:

```
context "#barks?" do
  it "barks if it had no treats today" do
    dog = Dog.new
    allow(dog).to receive(:treats_eaten) { 0 }

    expect(dog.barks?).to eq(true)
  end
end
```


Mocks

<https://relishapp.com/rspec/rspec-mocks/v/3-10/docs/verifying-doubles/using-an-instance-double>

You can make a mock of an object using `instance_double`. RSpec will use this to verify that any calls made on the object are only ones that an instance of that object would accept. The string passed to `instance_double` needs to be the class name.

```
it 'notifies the console' do
  notifier = instance_double("ConsoleNotifier")
  allow(notifier).to receive(:notify).with("suspended as")

  user = User.new(notifier)
  user.suspend!
end
```

You can not call methods from a class on a double unless you've already stubbed them via `allow` or are checking them via `expect...receive`.

Creating stubs directly on mocks

```
notifier = instance_double("ConsoleNotifier")  
allow(notifier).to receive(:notify).with("suspended as")
```

can simply become:

```
notifier = instance_double("ConsoleNotifier", notify: "susp")
```

Stubbing and Mocking Exercise

Implement the following:

- ▶ A unit test for your average method that gives the correct average during a leap year using a stub
- ▶ A unit test for `.valid?` *without* adding code to `#name` and instead uses a mock

Goal: To get comfortable with mocking and stubbing

Time: 30 minutes

Stubbing and Mocking Exercise

Tips:

- ▶ Your leap year test should probably have 'February' as one of the months you test against
- ▶ Determine what method you're stubbing to make it a leap year
- ▶ `.valid?` takes in an instance of `Months`
- ▶ Remember, `#name` should stay empty. Don't add any code there.

Request (Integration) Tests

RSpec Rail's implementation of integration

<https://relishapp.com/rspec/rspec-rails/v/4-0/docs/request-specs/request-spec>

```
it "creates a Widget and redirects to the Widget's page"
  get "/widgets/new"
  expect(response).to render_template(:new)

  post "/widgets", :params => { :widget => { :name => "My

  expect(response).to redirect_to(assigns(:widget))
  follow_redirect!

  expect(response).to render_template(:show)
  expect(response.body).to include("Widget was successful")
end
```

Request (Integration) Tests

- ▶ Integration tests are used to test how different parts of an application work together. In the context of a Rails app, it's how calling multiple endpoints in a row interact.
- ▶ An example is testing the flow of a user signup. It has multiple pages and at the end you may want to check something like whether the user was created or not.
- ▶ In the `financeit` app, we have integration tests under both `integration` and `requests`. The convention for RSpec is that they should be under `requests/`.
- ▶ Integration tests in RSpec test the content of the frontend, but we also generally use Cucumber for that.

Request (Integration) Tests

With integration tests, you're expectations probably want to check the side effects eg.

```
expect(User.count).to eq(1)
```

or

```
expect do  
  post '/users'  
end.to change{ User.count }.from(0).to(1)
```

We may also want to check what the endpoints under test return in their response:

```
expect(JSON.parse(response.body)).to eq({ full_name: "John
```

Breaking Down Each Part of an Integration Test

```
get "/widgets/new"  
expect(response).to render_template(:new)
```

Integration tests hit endpoints just like a user or front-end would as they use the app. This says “when the user GETs /widgets/new, Rails renders the template ‘new’ ”

I actually don't use `render_remlate` very much as it's often kind of redundant. It's more useful in cases where you're rendering a template that you wouldn't expect. Like rendering an error page.

Breaking Down Each Part of an Integration Test

```
post "/widgets", :params => { :widget => { :name => "My Wid
```

You can also send parameters to an endpoint.

Breaking Down Each Part of an Integration Test

```
expect(response).to redirect_to(assigns(:widget))
```

`assigns` checks what the controller assigned `@widget` to. This can be a useful way to check what sort of data we're passing to our views.

Breaking Down Each Part of an Integration Test

`follow_redirect!`

A helper method that we need to call to update the response after a redirect.

Breaking Down Each Part of an Integration Test

```
expect(response).to render_template(:show)
expect(response.body).to include("Widget was successfully c
```

Our expectations of what we get as a response after being redirected.

A Note on Setting Up Reusable State

With `let` it's very tempting to highlight every different change in state as a different variable. eg.:

```
let(:first_name) { "John" }  
let(:last_name) { "Doe" }
```

```
context ".full_name" do  
  it "puts the first and last name together" do  
    expect(full_name(first_name, last_name)).to eq("Doe, Jo  
  end
```

```
context "with a different name" do  
  let(:first_name) { "Jane" }  
  
  it "works" do  
    expect(full_name(first_name, last_name)).to eq("Doe,  
  end  
end  
end
```

A Note on Setting Up Reusable State

Using `let` this way becomes very complicated as the amount of `let` or `context` blocks increase. Duplication is totally OK in tests and is encouraged. Tests are made to be disposable. It's a lot easier to understand which state can be deleted with each test when they are part of the test itself. Instead consider:

```
context ".full_name" do
  it "puts the first and last name together" do
    expect(full_name("John", "Doe")).to eq("Doe, John")
  end

  it "works with a different first name" do
    expect(full_name("Jane", "Doe")).to eq("Doe, Jane")
  end
end
```

Now it's a lot easier to tell how the state differs between each test.

A Note on Setting Up Reusable State

With more complicated state, you can avoid reusing the same data over and over again by providing a base set of parameters that works for the base case and mutate it in each test. eg.:

Check out `reusable_state_example.rb`

Now you can reuse the other parameters that we need for this method without having to repeat yourself in each test.

Request Spec TDD Exercise

Implement the following:

- ▶ A user can ping people by name via `POST /pings` with a name, greeting, and company
- ▶ The greeting must always be “hello” and the company must always be “financeit”
- ▶ A user can only get help from `GET /help` if they have sent a `POST /pings` with `name=@skipants`. Otherwise the user gets a 404 response.

Constraints:

- ▶ Write an integration test before doing any code.
- ▶ Write an invariant of the test – if you have called `POST /pings` with a name other than `@skipants`, then you should get a 404 from `GET /help`.

Goal: To get more comfortable with TDD and integration tests

Time: 45 minutes

Request Spec TDD Exercise

Tips:

- ▶ Each integration test should be calling both the `POST /pings` and `GET /help` in the same test.
- ▶ Start with a file in `spec/requests/`. Don't sweat the filename – integration test names are more subjective than unit test files.
- ▶ Use a base set of parameters named `valid_params` and use `Hash#merge` to highlight the difference in state between your base case and the invariant
- ▶ You don't need to save `greeting` or `company` to the database. That constraint is just there to enforce and get you used to the usage of `valid_params`.
- ▶ `GET /help` should not be taking in any parameters.

Factory Bot

A gem used for organizing fixture data. Instead of passing the same parameters over and over to `.create` a database record, you can use factory definitions and traits to abstract that stuff away. It also provides a way to organize fixtures in such a way that they are reusable among different tests.

https://github.com/thoughtbot/factory_bot/blob/master/GETTING_STARTED

Factory Bot

```
FactoryBot.define do
  factory :employee do
    # attributes
    login { 'employee' }
    email { 'employee@example.com' }

    # association
    supervisor

    # trait
    trait :suspended do
      suspended_at { DateTime.current }
    end
  end
end
```

You can now save an employee with this base set of data to the database in your test with `create(:employee)`

Factory Bot

- ▶ You can also use a `Employee` object without creating a database record with `build`: `employee = build(:employee)`
- ▶ If you want different data on your fixture, you can also pass it to `create` or `build`: `build(:employee, login: "johndoe")`
- ▶ Traits are a nice way to describe a type of a fixture so it can be reused. It also inherits the base set of parameters (login, email in this case) `employee = build(:employee, :suspended)`
- ▶ Read the docs for more!

Controller Specs

Unit tests for controllers. RSpec Rails provides some helper methods to make these simpler.

<https://relishapp.com/rspec/rspec-rails/v/4-0/docs/controller-specs>

```
RSpec.describe TeamsController do
  describe "GET index" do
    it "assigns @teams" do
      team = Team.create
      get :index
      expect(assigns(:teams)).to eq([team])
    end

    it "renders the index template" do
      get :index
      expect(response).to render_template("index")
    end
  end
end
```

Controller Spec Helpers

- ▶ Controller specs have access to a response object and matchers like `render_template` in the same way integration specs do.
- ▶ Instead of a relative URL, controller specs request methods like `get` and `post` call the method directly on the controller. in the previous example, instead of `get /teams`, we call `get :index`.
- ▶ `assigns` is used in the same fashion as integration tests. It maps to the instance variable assigned in the controller. You probably want to test what a controller `assigns` because it is like the output of a controller similar to how a return value is the output of a method.

Controller Spec + Factory Bot Exercise

Reimplement the previous integration test for pinging @skipants as a controller test on HelpController with one new requirement: The user gets a 200 from GET /help only if they pinged @skipants once per day. If they pinged more than once they get a 404 from /help.

Constraints:

- ▶ Set up the state of the test using Factory Bot.

Goal: To get comfortable with controller specs and Factory Bot

Time: 30 minutes

Controller Spec + Factory Bot Exercise

Tips:

- ▶ In the previous exercise you probably called the `/pings` endpoint. In this exercise you should instead save the pings straight to the database as part of your setup.
- ▶ You have to create both the factory and the test file for this exercise
- ▶ Try using a trait to automatically make a ping with a name of “@skipants”. You probably wouldn’t do this normally as it’s simpler to just build

Tips For Testing

- ▶ Avoid using several `let` statements. It ends up making code harder to follow. Like we talked about earlier, use a base set of reusable state and modify it within the tests.
- ▶ Avoid writing to the database if you don't have to. Favour `factory_bot`'s `build` over `create`. Writing to the database is very slow and is the main culprit of slowdown in large test suites.
- ▶ `factory_bot` will cascade creates when you use `create` and it has associations making it write even more to the database than you'd expect.