

0.1 | Record of understanding:

The writing style here is more similar to my notes, which I personally use as a record of my understanding. If you would like this to be written up more formally, please let me know!

0.1.1 | 1. Paper Title:

A COVID-19 pandemic Al-based system with deep learning forecasting and automatic statistical data acquisition: Development and Implementation Study

0.1.2 | 2. What question or phenomenon was being investigated in this study and why?

- COVID is a large problem, almost all of the AI studies around it are region specific or centered around a single country
- CPAIS (COVID-19 Pandemic AI System) aims to solve this by automatically compiling databases to form a worldwide dateset
 - Including governmental responses
 - · allows heatmap viz of different policies in different countries,
 - · and predictive modeling, ofc.

0.1.3 | 3. What background information did you need to understand in order to understand the question, main experiment, main finding, and significance? (i.e. what did you find yourself digging into in the introduction or through outside sources; what was the most relevant background info?)

ARIMA: Auto Regressive Integrated Moving Average

- Type of Auto Regressive (AR, not Augmented Reality) model
 - used for processes which change over time (economics, web traffic, ect.)
- · Very similar to ARMA, but with a more complex stochastic term
- · Uses time series data
 - ie. use differences between values rather than the actual value
 - p, d, q
 - p: order of AR term, or time lag
 - · d: "degree of differencing"
 - · q: order of MA term, or size of moving average window

Predicted Y_t = Constant + Linear combination Lags of Y (upto p lags) + Linear Combination of Lagged forecast errors (upto q lags) - Good article

Huxley · 2020-2021 Page 1 of 3

MLP: Multilayer Perceptron Neural Networks

- Just a feed forward network, but with hidden layers. Pretty ambiguous term, left relatively ambiguous in the paper.
- · Fancy name for a vanilla neural net
- They highlight: designed to solve non-linearly separable problems
 - · with sigmoid
- They used nnfor, which means they used R.

MAE (vs RMSE):

• Mean Absolute Error, which I haven't used before, is like RMSE (root mean square error) but less punishing for bigger errors.

MAPE: Mean Absolute Percentage Error

- · aka Mean Absolute Percentage Deviation
- · loss function, used for measuring forecast accuracy.
- · average of percentage errors
- · generally not good..

0.1.4 | 4. What was the main thing the researchers found out and how did they do so?...

- 1. what were the main (1-2) experiments?
 - 1. Dateset gen and renewal:
 - 1. using crawler on source
 - 2. integrating the data into existing database
 - 3. statistical analysis with predefined procedure
 - 1. The experimentation comes in at this step with different deep learning models and techniques

2. Main Models:

- 1. LSTM: long term short term memory
 - 1. A type of recurrent neural network which uses a 'cell state' and forget gates to have both long and short term memory
 - 2. better forecast accuracy than other models
- 2. ARIMA: Auto Regressive Integrated Moving Average
 - 1. statistical learning model with time series regression
- 2. Created a 14-day forecasting model for COVID-19
- 3. what data did they generate?
 - 1. Generated a worldwide automatically updating dateset for COVID-19 with their automation technology
 - 2. And also, generated consistent forecasting data of the next 14 days
 - 3. Finally, generated data on the correlation of government policies and COVID-19
- 4. what does that data mean?
 - 1. The dateset, innit of itself, means nothing.
 - 2. the forecasting data means what we can expect for the next two weeks
 - 3. the correlation data *can* mean what governmental policies work best for dealing with COVID-19

Huxley · 2020-2021 Page 2 of 3

0.1.5 | 5. What was the significance or larger impact of the main finding?

Huxley · 2020-2021 Page 3 of 3