

With Custom auto-fill you can customize how the auto-fill function works.

You can use this feature to for example:

- create your how Severity formula
- create your own Look up functions

SETTINGS

URL Calc - The endpoint the platform calls when the users triggers the auto-fill.

Tooltip Text - The text the user sees in the UI when hovering the button

REQUEST FORMAT EXAMPLE:

```
{
  "Code": "F-2024-6313",
  "Name": "Test code block",
  "Type": "Vulnerability",
  "Status": "PendingFix",
  "Impact": 0,
  "Likelihood": 0,
  "Criticality": "Medium",
  "CVSS40Vector": null,
  "CVSS40Score": null,
  "CVSS31Vector": "",
  "CVSS31Score": null,
  "CVSS30Vector": null,
  "CVSS30Score": null,
  "CVSS20Vector": null,
  "CVSS20Score": null,
  "VulnerabilityTypes": [],
  "CWEs": [
    "CWE-20",
    "CWE-404",
    "CWE-552",
    "CWE-1187"
  ],
  "CVEs": [
    "CVE-2020-3555",
    "CVE-2020-5555",
    "CVE-2022-2222",
    "CVE-2019-2323"
  ]
}
```

```
},
"Assets": [],
"CustomFields": [
{
"Name": "Dropdown1",
"FieldType": 3,
"Value": "2"
},
{
"Name": "Dropdown2",
"FieldType": 3,
"Value": "1"
},
{
"Name": "Dropdown3",
"FieldType": 3,
"Value": ""
}
]
}
```

RESPONSE FORMAT EXAMPLE:

```
{ "result": "2" }
```

Where "2" is the value to apply in the Field