

This guide explains how to customize the display of finding details in reports using a query string-like syntax.

BASIC STRUCTURE

The token uses URL-style parameters separated by `&` characters. For example:

```
{Finding_Details?header_table.title=Summary&group.1.fields=description,impact}
```

CONFIGURATION SECTIONS

1. HEADER TABLE (OPTIONAL)

Display key information at the top of each finding:

```
header_table.title=Summary Table&
header_table.fields=severity,status,cvss&
header_table.cols=2&
header_table.show_finding_title=true&
```

2. TABLES

Add tables anywhere in your finding layout:

```
table.1.title=Summary&
table.1.fields=severity,status&
table.1.cols=2&
```

3. GROUPS

Organize fields into logical groups:

```
group.1.title=Overview&
group.1.fields=description,impact&

group.2.title=Technical Details&
group.2.fields=cvss,assets&
group.2.hide_field_titles=true&
```

You can hide the titles for each field using the `hide_field_titles` property.

4. DISPLAY SETTINGS

GENERAL SETTINGS

```
setting.hide_empty_fields=true (default)
setting.key_suffix=: (default)
setting.empty_message=No findings found
```

TITLE SETTINGS

```
setting.title.html_tag=h1&
setting.title.display_severity=true&
setting.title.show=true&
```

LAYOUT SETTINGS

Choose between table or headings layout:

```
setting.layout=table&
setting.evidences.layout=table&
```

```
setting.layout=headings&
setting.evidences.layout=headings&
```

EVIDENCE DISPLAY

```
setting.evidence_table.format=VisibleInstances& (default)
setting.evidence_table.title=Evidence Details&
```

Customizing Evidence Columns: You can control exactly which fields appear in your evidence table and in what order using the `setting.evidence_table.fields` parameter

For a full list of available fields and configuration examples, please read our detailed guide: [Dynamic Evidence Tables in {Finding_Details} Token](#)

ASSET DISPLAY

```
setting.assets.format=list1& (default)
setting.assets.display_count=30& (default)
```

5. FILTERING AND SORTING (OPTIONAL)

Filter findings by various criteria:

```
setting.filter.type=Vulnerability&
setting.filter.code=F-2025-0001,F-2025-0002&
setting.filter.status=ReadyRetest,PendingFix&
setting.filter.severity=Critical,High&
setting.filter.labels=Security,PCI-DSS&

setting.sort.field=severity&
setting.sort.direction=Descending&
```

Filter and sort is optional.

In case of the need to display only **specific** findings, `setting.filter.code=<code1,code2>` is the solution.

As default, the sort will be **Criticality**, then **CVSS**. then **Code**.

At the moment, the sort option only supports one field.

HTML STRUCTURE AND CSS CLASSES

The Finding Details token generates a hierarchical HTML structure that organises vulnerability information into logical groups and fields.

```
<div class="finding-details-container">
```

Purpose: Top-level container for all finding details content.

MAIN WRAPPER

```
<div class="finding-details-wrapper layout-headings">
```

Purpose: Primary wrapper that contains all finding content and defines the layout strategy.

CSS Classes:

- `finding-details-wrapper`: Base wrapper class
- `layout-headings`: Layout modifier (can be `layout-headings`, `layout-table`)

TITLE SECTION

```
<h1 class="finding-details-title">Unencrypted Telnet Server - Critical</h1>
```

Purpose: Displays the finding title with optional severity indicator.

CSS Class: `finding-details-title`

HTML Tag: Configurable (h1, h2, h3, etc.) via token settings

GROUP STRUCTURE

Groups organize related fields together under optional headings:

```
<div class="finding-details-group [group-title]">
  <h4 class="finding-details-group-title">Classification</h4>
  <!-- Fields go here -->
</div>
```

CSS Classes:

- `finding-details-group` : Base group container
- `[group-title]` : CSS class matching the group title (e.g., `classification` , `recommendations`) when a title is present
- `finding-details-group-title` : Group heading (only present when group has a title)

FIELD STRUCTURE

Each field follows a consistent pattern:

```
<div class="finding-details-field [field-name]">
  <div class="finding-details-field-header">
    <strong>Field Name</strong>
  </div>
  <div class="finding-details-field-body">
    <!-- Field content -->
  </div>
</div>
```

CSS Classes:

- `finding-details-field` : Base field container
- `[field-name]` : Specific field identifier (e.g., `severity` , `assets` , `description`)
- `finding-details-field-header` : Field label container (hidden when `hide_field_titles=true`)
- `finding-details-field-body` : Field content container

CSS CLASS REFERENCE

CONTAINER CLASSES

Class	Purpose	Usage
<code>findings_vuln_detailslist</code>	Root container	Top-level styling and spacing
<code>finding-details-wrapper</code>	Main content wrapper	Overall layout and structure
<code>layout-headings</code>	Layout modifier	Indicates heading-based layout

STRUCTURE CLASSES

Class	Purpose	Usage
<code>finding-details-title</code>	Finding title	Title typography and spacing
<code>finding-details-group</code>	Group container	Group spacing and organization

finding-details-group-title	Group heading	Group title styling
finding-details-field	Individual field	Field spacing and layout
finding-details-field-header	Field label	Label typography and emphasis
finding-details-field-body	Field content	Content styling and spacing

FIELD CLASSES

Each field automatically receives a CSS class matching its field name from the token configuration:

```
.finding-details-field.[field-name] { /* Custom styles */ }
```

GROUP CLASSES

When a group has a title, the group container receives a CSS class matching the title (lowercased):

```
.finding-details-group.[group-title] { /* Custom styles */ }
```

IMPORTANT NOTE ABOUT NUMBERING

When using tables and groups, the numbers after `table.` and `group.` determine the overall order of appearance. These numbers should be distinct across both tables and groups. For example:

```
header_table... (always appears first)
group.1... (appears second)
table.2... (appears third)
group.3... (appears fourth)
```

AVAILABLE FIELDS

EXAMPLES

Here's an example combining multiple settings:

```
{Finding_Details?
group.1.fields=description,assets,occurrence,status,evidence_table&
group.2.title=Classification&
group.2.fields=severity,impact,likelihood,cvss,vulnerability_types,cwes,cves,exploits,labels&
group.3.title=Recommendations&
group.3.fields=background_information,remediation,external_url&
group.4.title=Compliance&
group.4.fields=compliance,compliance_status,compliance_comment&
setting.title.html_tag=h1&
setting.title.display_severity=true&
setting.title.show=true&
setting.layout=headings&
setting.evidence_table.title=Evidence Title&
setting.evidence_table.format=all&
setting.assets.format=list2&
setting.filter.type=Vulnerability&
setting.filter.status=PendingFix,Fixed,test&
setting.sort=status&
}
```

V1 EQUIVALENT

```

{Finding_Details?

group.1.fields=description&
group.1.hide_field_titles=true&

group.2.title=&
group.2.fields=assets,occurrence&

group.3.title=Classification&
group.3.fields=severity,impact,likelihood,vulnerability_types,cwes,cves,exploits&

group.4.title=Recommendations&
group.4.fields=background_information,remediation,external_url&

group.5.title=Compliance&
group.5.fields=compliance,compliance_status&

group.6.title=Evidences&
group.6.fields=evidence_table,evidences&

setting.title.html_tag=h1&
setting.title.display_severity=true&
setting.title.show=true&
setting.layout=headings&
setting.evidences.layout=headings&
setting.evidence_table.title=Evidence Title&
setting.evidence_table.format=all&
setting.assets.format=list1
}

```

V2 EQUIVALENT

```

{Finding_Details?

group.1.fields=description,assets,occurrence&

group.2.title=Classification&
group.2.fields=severity,impact,likelihood,vulnerability_types,cwes,cves,exploits&

group.3.title=Recommendations&
group.3.fields=background_information,remediation,external_url&

group.4.title=Compliance&
group.4.fields=compliance,compliance_status&

group.5.title=Evidences&
group.5.fields=evidence_table,evidences&

setting.title.html_tag=div&
setting.title.display_severity=true&
setting.title.show=true&
setting.layout=table&
setting.evidences.layout=table&
setting.evidence_table.title=Evidence Title&
setting.evidence_table.format=all&
setting.assets.format=list1&
setting.key_suffix=:
}

```

V3 EQUIVALENT

```

{Finding_Details?

header_table.title=&
header_table.fields=severity,cvss,impact,likelihood&
header_table.cols=2&
header_table.show_finding_title=true&

```

```

group.1.fields=assets,description,occurrence&

group.2.title=Classification&
group.2.fields=impact,likelihood,vulnerability_types,cwes,cves,exploits&

group.3.title=Recommendations&
group.3.fields=background_information,remediation,external_url&

group.4.title=Compliance&
group.4.fields=compliance,compliance_status&

group.5.title=Evidences&
group.5.fields=evidence_table,evidences&

setting.title.html_tag=h1&
setting.title.display_severity=false&
setting.title.show=false&

setting.layout=header&
setting.evidences.layout=headings&
setting.evidence_table.title=&
setting.evidence_table.format=all&

setting.assets.format=list1
}

```

PCICOMPLIANCE EQUIVALENT

```

{Finding_Details?

header_table.title=&
header_table.fields=severity,cvss,impact,likelihood&
header_table.cols=2&
header_table.show_finding_title=true&

group.1.fields=assets,description,occurrence&

group.2.title=Classification&
group.2.fields=impact,likelihood,vulnerability_types,cwes,cves,exploits&

group.3.title=Recommendations&
group.3.fields=background_information,remediation,external_url&

group.4.title=Compliance&
group.4.fields=compliance,compliance_status,pci_evidence_table&

group.5.title=Evidences&
group.5.fields=evidence_table,evidences&

setting.title.html_tag=h1&
setting.title.display_severity=false&
setting.title.show=false&

setting.layout=headings&
setting.evidences.layout=headings&
setting.evidence_table.title=&
setting.evidence_table.format=all&

setting.assets.format=list1

}

```